

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418712
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Rupp; Timothy J. et al.

Camera assembly for vehicle and vehicle including same

Abstract

A camera assembly for a vehicle can include a first glass pane, a second glass pane, a garnish panel and a camera. The vehicle can have a side panel and a window opening in the side panel. The first glass pane can be configured to cover the widow opening and have a first light transmissivity. The second glass pane can be configured to cover a portion of the side panel that is adjacent to the opening and have a second light transmissivity that is greater than the first light transmissivity. The garnish panel can extend across the second glass pane. The camera can oppose the second glass pane.

Inventors:	Rupp; Timothy J. (Dublin, OH), Isings; Connor (Columbus, OH)
Applicant:	Honda Motor Co., Ltd. (Tokyo, JP)
Family ID:	1000008819092
Assignee:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Appl. No.:	18/508700
Filed:	November 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250159327 A1	May. 15, 2025

Publication Classification

Int. Cl.: B60J10/00 (20160101); B32B17/10 (20060101); B60J10/70 (20160101); H04N23/57 (20230101); B60R11/00 (20060101)

U.S. Cl.:

CPC **H04N23/57** (20230101); **B32B17/10036** (20130101); **B60J10/70** (20160201);
B60R2011/0026 (20130101)

Field of Classification Search

CPC: H04N (23/57); B32B (17/10036); B60J (10/70); B60R (2011/0026); B60R (11/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7322755	12/2007	Neumann et al.	N/A	N/A
8067077	12/2010	Bauer	428/40.9	H01Q 1/22
8934052	12/2014	Luan	348/374	H10F 39/804
9097375	12/2014	Hanson	N/A	F16J 15/008
9857797	12/2017	Hara et al.	N/A	N/A
9976973	12/2017	Watkins	N/A	G01N 15/134
10054721	12/2017	Hsu	N/A	G02B 7/021
10155824	12/2017	Fujikawa	N/A	A61Q 19/007
10347179	12/2018	Kim	N/A	G09G 3/3266
11279108	12/2021	Bard et al.	N/A	N/A
2009/0078873	12/2008	Sakemoto	250/339.11	G01J 5/58
2010/0046059	12/2009	McCabe	359/263	G02B 5/0858
2011/0144284	12/2010	Heuer	525/394	C08L 69/00
2013/0106787	12/2012	Lee	345/175	H04N 23/50
2015/0181099	12/2014	Van Der Tempel	348/135	G01S 7/4911
2017/0220844	12/2016	Jones	N/A	G06V 40/1318
2018/0048909	12/2017	Liu	N/A	H04N 19/105
2018/0081093	12/2017	Wang	N/A	H04N 23/20
2018/0124394	12/2017	Xu	N/A	H04N 19/573
2018/0152727	12/2017	Chuang	N/A	H04N 19/70
2020/0398646	12/2019	Mujcinovic et al.	N/A	N/A
2021/0372645	12/2020	Harder	N/A	F24F 11/52
2022/0132047	12/2021	Nagashima et al.	N/A	N/A
2022/0250555	12/2021	Blanche et al.	N/A	N/A
2022/0347974	12/2021	Sadakane et al.	N/A	N/A
2023/0038114	12/2022	Davis et al.	N/A	N/A
2023/0096675	12/2022	Chiba	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202009018488	12/2011	DE	N/A
2022117943	12/2021	WO	N/A
2023140220	12/2022	WO	N/A

Primary Examiner: Huang; Frank F

Attorney, Agent or Firm: KENEALY VAIDYA LLP

Background/Summary

BACKGROUND

(1) The disclosed subject matter relates to a camera assembly for a vehicle. More particularly, the disclosed subject matter relates to methods and apparatus that can provide the appearance of a continuous privacy glass pane for a vehicle while transmitting ambient light to a camera located behind the pane that is sufficient for the desired operation of the camera.

(2) A vehicle can include one or more cameras that are arranged to provide a respective view of the space outside of the vehicle and provide real-time images to the driver and/or a controller of a driver assistance system or an autonomous vehicle. For example, the vehicle can include a camera mounted at the rear end of the vehicle that provides a video image for the driver when the vehicle travels in reverse. The vehicle can also include cameras that capture images of the space along the two sides of the vehicle and at the front of the vehicle. The cameras can be concealed behind a transparent panel or pane and can be sealed in a compartment that protects the camera from dust, debris and fluids in the space outside of the vehicle.

SUMMARY

(3) Some embodiments are directed to a camera assembly for a vehicle that can include a first glass pane, a second glass pane, a garnish panel and a camera. The vehicle can have a side panel and a window opening in the side panel. The first glass pane can be configured to cover the window opening and have a first light transmissivity. The second glass pane can be configured to cover a portion of the side panel that is adjacent to the window opening and have a second light transmissivity that is greater than the first light transmissivity. The garnish panel can extend across the second glass pane. The camera can oppose the second glass pane.

(4) Some embodiments are directed to a camera assembly for a vehicle that can include a camera, a first glass pane, a second glass pane, a garnish panel and an adhesive sealant. The first glass pane can have a first light transmissivity and be spaced away from the camera. The second glass pane can be adjacent to the first glass pane and overlap the camera. The second glass pane can have a second light transmissivity that is greater than the first light transmissivity. The garnish panel can cover the second glass pane and include a through hole configured to be aligned with the camera. The adhesive sealant can connect the garnish panel to the second glass pane.

(5) Some embodiments are directed to a vehicle that can include a side panel, a first glass pane, a second glass pane, a garnish panel and a camera. The side panel can extend along a longitudinal direction of the vehicle, and can include a window opening. The first glass pane can be mounted on the side panel, cover the window opening and have a first light transmissivity. The second glass pane can be mounted on a portion of the side panel that is adjacent to the window opening in the longitudinal direction. The second glass pane can have a second light transmissivity that is greater than the first light transmissivity, and can include an outer surface and an inner surface. The garnish panel can be adhered to the outer surface of the second glass pane. The camera can be mounted on the side panel and oppose the inner surface of the second glass pane. The camera can have an optical axis that intersects the longitudinal direction at an oblique angle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosed subject matter of the present application will now be described in more detail with reference to exemplary embodiments of the apparatus and method, given by way of example, and with reference to the accompanying drawings, in which:

(2) FIG. 1 is a schematic illustration of a perspective view of a vehicle including a camera system

made in accordance with principles of the disclosed subject matter.

(3) FIG. 2 is an enlarged view of the rear half of the vehicle of FIG. 1.

(4) FIGS. 3 and 4 are cross-sectional views taken along line 3-3 of FIG. 2.

(5) FIG. 5 is a plan view of a garnish panel of the camera system of FIG. 1.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

(6) A few inventive aspects of the disclosed embodiments are explained in detail below with reference to the various figures. Exemplary embodiments are described to illustrate the disclosed subject matter, not to limit its scope, which is defined by the claims. Those of ordinary skill in the art will recognize a number of equivalent variations of the various features provided in the description that follows.

(7) In a vehicle, a camera can be mounted behind a transparent cover or panel made of plastic or glass to observe or monitor a space adjacent the vehicle. The camera can be any known type of digital camera including what is known in the vehicle art as a safety camera. In some cases, an opening or space for the camera and a transparent panel sealing the space occupied by the camera can be seen by an observer outside of vehicle. The observer might perceive this arrangement as detracting from the aesthetic appearance of the vehicle. Thus, it can be advantageous to mount the camera behind one of the glass panes forming a window of the vehicle. In such a location, the camera can receive light from outside the vehicle via the window glass without detracting from the aesthetic appearance of the vehicle.

(8) A vehicle can include a plurality of window openings that are covered by glass panes. Some glass panes can be referred to as privacy glass. The privacy glass can be tinted with a dark color such as, but not, limited to, a brown or a black color. Privacy glass can limit the extent to which an observer can clearly see the inside of the vehicle. Thus, privacy glass can be advantageous for the security and privacy of the contents and passengers, and reduce the solar heat input to the passenger space in the vehicle. Privacy glass can also enhance the aesthetic appearance of the vehicle.

(9) Due to the low light transmissivity, it can be disadvantageous to mount a camera behind a pane of privacy glass. Green glass can also be used on a vehicle to cover a window opening in the body panel. Green glass can have a light green tint and a light transmissivity that is greater than that of privacy glass. The light transmissivity of green glass can be sufficient for the performance desired for a camera, such as a safety camera. However, using green glass and privacy glass on the same portion of the vehicle can detract from the aesthetic appearance of the vehicle.

(10) Thus, there is a need for a camera assembly that can be compatible with the aesthetic appeal of privacy glass.

(11) FIGS. 1 and 2 illustrate an embodiment of a safety camera system **10** for a vehicle **12** made in accordance with principles of the disclosed subject matter. FIGS. 1 and 2 show the left side of the vehicle **12** and a front end **14** of the vehicle **12**. The right side of the vehicle **12** can be a mirror image of the left side. The vehicle **12** can extend in a longitudinal direction L, a transverse direction T and vertical direction V.

(12) The vehicle **12** can include a front windshield **16**, a glass roof panel **18**, a rear windshield **20**, a front door **22**, a rear door **24** and a side panel **26**. The front door **22** can include a front glass pane **28** and the rear door **24** can include a rear glass pane **30**. The rear windshield **20** can also be referred to a rear window, a backlight, a tailgate glass or a liftgate glass. The glass roof panel **18** can be referred to as a glass pane and be a fixed panel or a movable panel. The glass roof panel **18** can be referred to as a sunroof or a moon roof if the glass roof panel **18** is movable.

(13) The front windshield **16** and the front glass pane **28** can be green glass panes and the glass roof panel **18**, the rear windshield **20** and the rear glass pane **30** can be privacy glass. The safety camera assembly **10** can be located between the glass roof panel **18**, the rear glass pane **30** and the rear windshield **20** in the longitudinal direction L of the vehicle **12**. Thus, it can be advantageous for the safety camera assembly **10** to have an external appearance that is the same as or

complimentary to privacy glass.

(14) The safety camera assembly **10** can include a first glass pane **32**, a garnish panel **34** and a camera **36**. The first glass pane **32** can be privacy glass and the garnish panel **34** can have an exterior surface that is visually compatible with the aesthetic appearance of privacy glass. Thus, an observer can perceive the outside of the vehicle **12** as having a continuous expanse of privacy glass that extends from the rear glass pane **30** to the rear windshield **20**, inclusively.

(15) Referring to FIG. **3**, the safety camera assembly **10** can include a second glass pane **40**. The second glass pane **40** can be made from green glass or any other appropriate type of glass that can transmit an amount of light that is sufficient for the desired performance of the camera **36**. That is, the second glass pane **40** can have a light transmissivity that is greater than the light transmissivity of the first glass pane **32**, the glass roof panel **18**, the rear glass pane **30** and the rear windshield **20**, and a color that is different from the color of the first glass pane **32**, glass roof panel **18**, the rear glass pane **30** and the rear windshield **20**.

(16) The garnish panel **34** can be made from plastic and include an exterior surface **42** that has a color and gloss finish that matches, or is aesthetically compatible with, the color and gloss finish of the of the first glass pane **32**, glass roof panel **18**, the rear glass pane **30**, and the rear windshield **20**. The garnish panel **34** can extend across the second glass pane **40** along the longitudinal direction L and the vertical direction V of the vehicle **12**. The garnish panel **34** can be opaque so that the garnish panel **34** can conceal the camera **36** from the view of an observer located outside of the vehicle **12**. Referring to FIGS. **3** and **5**, the garnish **34** can include a through hole **44**. Referring to FIG. **4**, the camera **36** can have an optical axis A1 that extends through the through hole **44**.

(17) Thus, light from the space outside of the vehicle **36** can pass through the through hole **44** and the second glass pane **40** and enter the camera **36**. The camera **36** can be configured to form image data from the light that enters camera **36**. The image data can represent the object(s) in the space outside of the vehicle **12** and can be processed by a display device for presentation to the operator of the vehicle **12**.

(18) Referring to FIGS. **1-3**, the side panel **26** can be made from any appropriate material such as, but not limited to, steel, aluminum alloy, carbon fiber, fiber-reinforced plastic, sheet molded plastic, or fiberglass, or a composite that includes any one or more of the these materials, or a composite that includes any one of these materials and another material. The side panel **26** can include a window opening **46** and the first glass pane **32** can cover the window opening **46**. Referring to FIG. **3**, the first glass pane **32** can include an exterior surface **48** that faces the outside of the vehicle **12**. The side panel **26** can include an exterior surface **50** that faces the outside of the vehicle **12**. The exterior surface **42** of the garnish panel **34** can be co-planar with the exterior surfaces **48**, **50**. The surfaces **42**, **48**, **50** can be described as being flush with each other, or at least can appear to an observer to be flush with each other.

(19) The second glass pane **40** can be configured to cover a portion **52** of the side panel **26** that is adjacent to the window opening **46**. The second glass pane **40** can have an inner surface **54**, an outer surface **56**, and a peripheral edge **58**. The garnish panel **34** can be mounted onto the outer surface **56**. The peripheral edge **58** can extend around a perimeter of the second glass pane **40** and can extend from and be connected to each of the inner surface **54** and outer surface **56** in a perpendicular relationship with each surface **54**, **56**.

(20) The outer surface **56** can be offset from the outer surface **48** of the first glass pane **32** and the outer surface **50** of the side panel **26** in the transverse direction T of the vehicle **12**. The outer surface **56** can be offset from the exterior surfaces **48**, **50** by an amount that is sufficient for the exterior surfaces **42**, **48**, **50** to be, or appear to be, flush with each other.

(21) The through hole **44** in the garnish panel **34** can be larger than the light aperture of the camera **36** so that the camera **36** can have an appropriate field of view of the space outside of the vehicle **12**. Referring to FIG. **4**, boundary lines V1 and V2 can delineate the field of view of the camera **36**. In order to provide an appropriate size for the field of view, the through hole **44** may permit an

observer of the outside of the vehicle **12** to see all or most of the camera **36**.

(22) The camera assembly **10** can include an encapsulation **60** that is connected to the second glass panel **40** and the camera **36** so the encapsulation **60** obstructs all but the light aperture of the camera **36**. The encapsulation **60** can have a dark color with a matte finish. Thus, the encapsulation **60** can obscure the observers view of the camera **36** and provide the observer with a pleasant perception of the aesthetic appearance of the vehicle **12** and the camera assembly **10**.

(23) The encapsulation **60** can be formed from a rubber or other elastomeric material. The encapsulation **60** can be connected to the second glass pane **40** in any appropriate manner such as, but not limited to, elastic expansion of the encapsulation **60** by the second glass panel **40**, over-molding onto the second glass panel **40**, or adhesive. The encapsulation **60** can abut the camera **36** and the inner surface **54** and the peripheral edge **58** of the second glass panel **40**.

(24) The encapsulation **60** can include a first wall **62**, a protrusion **64**, a through hole **66** and a perimeter wall **68**. The first wall **62** can abut the inner surface **54** of the second glass pane **40**. The first wall **62** can be elongated in the longitudinal direction L of the vehicle **12** and extend across the inner surface **54** along the longitudinal direction L and the vertical direction V of the vehicle **12**. The first wall **62** can be a flat wall or appear to one of ordinary skill as a flat wall.

(25) The protrusion **64** can extend away from the inner surface **54** of the second glass pane **40** in a direction that intersects the longitudinal direction L and the transverse direction T of the vehicle **12**. An acute angle can be formed between the inner surface **54** and the protrusion **64**. The protrusion **64** can extend from a first portion **70** of the first wall **62** and generally toward a second portion **72** of the first wall **62** along the longitudinal direction L. The protrusion **64** can be spaced away from the field of view of the camera **36**. The protrusion **64** can have any appropriate shape so that the protrusion **64** is spaced away from the field of view and also abuts the camera **36**.

(26) The through hole **66** can extend through the protrusion **64** and be adjacent to the second portion **72** of the first wall **62**. The through hole **66** can be located on the optical axis A of the camera **36**. The camera **36** can extend into the through hole **66**. The through holes **44**, **66** can have any appropriate shape such as, but not limited to, a polygon, a circle or an oval. The through hole **66** can have a first dimension D1 measured perpendicular to the optical axis A1 that is smaller than a second dimension D2 of the through hole **44** of the garnish panel **34** that is measured in the longitudinal direction L of the vehicle **12**.

(27) The perimeter wall **68** can encircle the first wall **62** and protrude from the first wall **62** in the transverse direction T of the vehicle **12** toward an exterior of the vehicle **12**. The perimeter wall **68** can surround the second glass pane **40** and abut the peripheral edge **58** of the second glass pane **40**.

(28) Referring to FIG. 4, the garnish panel **34** can have a third dimension D3 (e.g., length, circumference, perimeter) and the second glass pane **40** can have a fourth dimension D4 (e.g., length, circumference, perimeter), each measured in the longitudinal direction L of the vehicle **12**. The third dimension D3 of the garnish **34** can be greater than the fourth dimension D4 of the second glass pane **40** and the garnish panel **34** can overhang beyond the peripheral edge **58** of the second glass pane **40** in the longitudinal direction L. The perimeter wall **68** of the encapsulation **60** can abut the inner surface **74** of the garnish panel **34** where the garnish panel **34** overhangs from the peripheral edge **58**.

(29) Returning to FIG. 3, the encapsulation **60** can include a lip seal **76** that abuts the side panel **26**. The lip seal **76** can protrude from the perimeter wall **68** generally in the longitudinal direction L of the vehicle **12**. That is, the encapsulation **60** can extend from the peripheral edge **58** of the second glass pane **40** to the side panel **26** in the longitudinal direction L of the vehicle **12**. Thus, the encapsulation **60** can form a seal between the second glass pane **40** and the side panel **26**.

(30) The camera assembly **10** can include an adhesive sealant that connects the garnish panel **34** onto the second glass pane **40**. The adhesive sealant is schematically illustrated in FIG. 3 as a dotted line triangle and can include a first bead **78** and a second bead **80**. The first bead **78** can be adjacent to and extend along the peripheral edge **58** of the second glass pane **40**. The first bead **78**

can follow and be spaced inwardly from the entire peripheral edge **58**. The second bead **80** can be adjacent to surround the through hole **44** of the garnish panel **34**. The second bead **80** can be spaced outwardly from the through hole **44**. The beads **78, 80** can adhere the inner surface **74** of the garnish panel **34** to the outer surface **56** of the second glass pane **40** and seal the connection against fluid, dust and debris.

(31) The camera assembly **10** can include an adhesive sealant **82** that adheres the encapsulation **60** to the side panel **26**. The adhesive sealant **82** is schematically illustrated in FIG. **3** as a dotted line triangle and can be a bead that is adjacent to and spaced inwardly from the outer perimeter of the encapsulation **60**. The adhesive sealant bead **82** can follow the entire perimeter of the encapsulation **60**.

(32) The adhesive sealant beads **78, 80, 82** can include any appropriate material that can bond the material of the garnish panel **34** to the second glass pane **40** and bond the encapsulation **60** to the side panel **26**. In exemplary embodiments, the beads **78, 80, 82** can be formed from a urethane material, a silicon material, an acrylic material or silane-modified polymer.

(33) The camera assembly **10** can include a mount **84** that can secure the camera **36** to the side panel **26**. The mount **84** can be mounted onto the side panel **26** by a pair of threaded fasteners **86**. Each of the threaded fasteners can include a nut that is welded onto the side panel **26** and a bolt that extends through a through hole **88** in the mount **84** and a through hole **90** in the side panel **26**. The nut can be centered on the through hole **90** in the side panel **26**.

(34) The side panel **26** can include a camera opening **92** that is spaced away from the window opening **46** in the longitudinal direction **L** of the vehicle **12**. The camera opening **92** can have a fifth dimension **D5** that is measured in the longitudinal direction **L**. The fifth dimension **D5** can be greater than the second dimension **D2** and less than the fourth dimension **D4** and the third dimension **D3**. The second glass pane **40** can span the camera opening **92** in the longitudinal direction **L** and can be spaced away from the camera opening **92** in the transverse direction **T** of the vehicle **12**. The mount **84** can span the camera opening **92** in the longitudinal direction **L**.

(35) Referring to FIGS. **1-3**, the camera assembly **10** can include a molding **94** that is connected to and extends around the perimeter of the first glass pane **32**. Referring to FIG. **3**, the molding **94** can be formed from a rubber or other elastic material and can include a lip seal **96** that abuts at least one of the garnish panel **34** and the encapsulation **60**. That is, the molding **94** can extend from the first glass pane **32** to the garnish panel **34** (and/or the encapsulation **60**) in the longitudinal direction **L** of the vehicle **12** and seal a space between the first glass pane **32** and the garnish panel **34** and the encapsulation **60** from fluids dust and debris.

(36) Referring to FIG. **4**, the camera **36** can oppose the inner surface **54** of the second glass pane **40** generally in the transverse direction **T** of the vehicle **12**. The optical axis **A1** of the camera **36** can intersect the longitudinal direction **L** of the vehicle **12** at an oblique angle.

(37) The through hole **44** of the garnish panel **34** can have a hole axis **A2** and the optical axis **A1** of the camera can intersect the hole axis **A2**. The camera **36** can be offset with respect to the hole axis **A2** in a direction that is away from the first glass pane **32**. That is, the camera **36** can be spaced away from the hole axis **A2** in the longitudinal direction **L** of the vehicle **12**.

(38) The vehicle **12** can include one or more spaces along the side of the vehicle **12** that cannot be observed by the operator of the vehicle **12** with a rearview mirror or side view mirror. These unobservable spaces can be referred to as blind spots. The blind spots can be located at the sides of the vehicle **12** and behind the vehicle **12**. In exemplary embodiments, the camera **36** can be a component of a system that monitors the blind spot(s) of the vehicle **12** and warns the operator of the vehicle **12** when an object is present in the blind spot(s). Of course, the camera **36** and safety camera assembly **10** can be used for other purposes such as in autonomous driving systems or any other communications system that desires information related to the environment surrounding a vehicle **12**.

(39) The camera **36** can be any appropriate optical device, such as, but not limited to, a charge-

coupled device (“CCD”), that can capture images of the space outside of the vehicle **12** and transmits the image data to an image processing unit. The image processing unit can be configured to control a video display and/or provide an audio and/or a video message to the operator of vehicle **12** that is indicative of the real-time status of the space outside the vehicle **12**. The camera **36** can be referred to as a rear safety camera.

(40) In summary, the garnish panel **34** can have an exterior surface that is visually compatible with the aesthetic appearance of privacy glass while the light transmissivity of the green glass of the second glass pane **40** can be sufficient for the desired operation of the camera **36**. Moreover, the second glass pane **40** can be encapsulated by the encapsulation **60** and the encapsulation **60** can include the projection **64** that goes around the lens of the camera **36** to provide a good appearance when a user, owner, potential user or potential owner looks into the through hole **44** in the garnish panel **34** from an exterior view of the vehicle **12**. Thus, the camera assembly **10** can allow a user or owner of the vehicle **12** to obtain the benefits of privacy glass with the additional benefit of a camera aesthetically concealed behind the privacy glass.

(41) The second glass pane **40** and the garnish panel **34** can be adhered to the side panel **26** with an adhesive sealant to create a water tight seal. This can allow the camera **36** to be mounted in a dry area inside the body of the vehicle **12** and create a flush appearance when a user, owner, potential user or potential owner observes the vehicle **12** from the outside.

(42) Thus, the camera assembly **10** can provide an aesthetic benefit that is compatible with privacy glass while maintaining the desired imaging performance for camera **36**.

(43) While certain embodiments of the invention are described above, it should be understood that the invention can be embodied and configured in many different ways without departing from the spirit and scope of the invention.

(44) FIGS. **1** and **2** depict a four-door vehicle such as a sports-utility vehicle or crossover vehicle. However, the camera system **10** can be used with any vehicle that is configured for travel along any one or combination of improved, unimproved, and unmarked paths. For example, embodiments are intended to include or otherwise cover any type of vehicle, including a two-door vehicle, station wagon, minivan, truck, other types of all-terrain vehicle (ATV), semi-tractor, off-highway vehicle, motorcycles, boats, planes, etc.

(45) Instead of located at the side of the vehicle **12**, the camera assembly can be mounted at the rear end of the vehicle **12** adjacent to the rear windshield **20** or even in a front window depending on the application of the vehicle and imaging requirements.

(46) Instead of being located towards the rear of the first glass pane **32** in the longitudinal direction L of the vehicle **12**, alternate embodiments can include the second glass pane **40** and the garnish panel **34** located in front of the first glass pane **32** in the longitudinal direction L, or below or above the first glass pane **32** in the vertical direction V of the vehicle **12**.

(47) In alternate embodiments, one or both of the glass panes **32**, **40** and the garnish panel **34** can have inner and outer surfaces that are curved with respect to any of the longitudinal direction L, the transverse direction T and the vertical direction V of the vehicle.

(48) The glass panes **32**, **40** and the garnish panel **34** can have any regular shape or any irregular shape. Any of the panels **26**, **34** can be multi-part structures or a single integrally formed by stamping or molding a continuous material. Similarly, the molding **94**, the mount **84**, and the encapsulation **60** can each or all be integral with each other in various combinations, and/or can be integral with the side panel **26**, or they can all be separate structures. The panels **26**, **34**, encapsulation **60**, mount **84**, and molding **94** can be plastic, metal, rubber, ceramic or other known material or combination of materials.

(49) Alternate embodiments can include any appropriate manner of connecting the mount **84** onto the side panel **26** such as, but not limited to, clip(s), clamp(s), adhesive, or any combination of these items.

Claims

1. A camera assembly for a vehicle having a side panel and a window opening in the side panel, the camera assembly comprising: a first glass pane configured to cover the window opening and having a first light transmissivity; a second glass pane located adjacent the first glass pane and configured to cover a portion of the side panel that is adjacent to the opening, the second glass pane having a second light transmissivity that is greater than the first light transmissivity; a garnish panel extending across the second glass pane; and a camera opposing the second glass pane.
2. The camera assembly according to claim 1, wherein the first glass pane has a first color and the second pane has a second color that is different from the first color, and the garnish panel is plastic and includes an exterior surface that has a gloss color that matches the first color.
3. The camera assembly according to claim 1, wherein the first glass pane is privacy glass and the second glass pane is green glass.
4. The camera assembly according to claim 1, wherein the second glass pane has an outer surface and the garnish panel is mounted onto the outer surface, the first glass pane has a first exterior surface, and the garnish panel has a second exterior surface that is co-planar with the first exterior surface.
5. The camera assembly according to claim 1, further comprising: an encapsulation, wherein the second glass pane has an inner surface, an outer surface, and a peripheral edge, the peripheral edge extends around a perimeter of the second glass pane and extends from and is connected to each of the inner surface and the outer surface, the encapsulation abuts the inner surface and the peripheral edge.
6. The camera assembly according to claim 5, wherein the encapsulation includes a first wall that abuts the second glass pane, a protrusion that extends away from inner surface, and a through hole that extends through the protrusion and is adjacent to the first wall, and the camera extends into the through hole.
7. The camera assembly according to claim 1, further comprising: a urethane adhesive connecting the garnish panel onto the second glass pane.
8. The camera assembly according to claim 1, further comprising: a mount configured to be mounted onto the side panel, wherein the camera is mounted onto the mount.
9. The camera assembly according to claim 1, wherein the garnish panel includes a through hole having a hole axis, and the camera has an optical axis that intersects the hole axis.
10. The camera assembly according to claim 9, wherein the camera is offset with respect to the hole axis in a direction that is away from the first glass pane.
11. A camera assembly for a vehicle, comprising: a camera; a first glass pane having a first light transmissivity and being spaced away from the camera; a second glass pane adjacent to the first glass pane and overlapping the camera, the second glass pane has a second light transmissivity that is greater than the first light transmissivity; a garnish panel covering at least a portion of the second glass pane and including a through hole aligned with the camera; and an adhesive sealant connecting the garnish panel to the second glass pane.
12. The camera assembly according to claim 11, wherein the camera has an optical axis that extends through the through hole, and the second glass pane is at a location along the optical axis that is between the camera and the garnish panel.
13. The camera assembly according to claim 12, further comprising: an encapsulation connected to the second glass pane, the encapsulation abuts the camera and includes a through hole that is located on the optical axis.
14. A vehicle comprising: a side panel extending along a longitudinal direction of the vehicle, the side panel including a window opening, a first glass pane mounted on the side panel, covering at least a portion of the window opening and having a first light transmissivity; a second glass pane

mounted on a portion of the side panel that is adjacent to the window opening in the longitudinal direction, the second glass pane has a second light transmissivity that is greater than the first light transmissivity, the second glass pane includes an outer surface and an inner surface; a garnish panel adjacent to the outer surface of the second glass pane; and a camera located adjacent and opposing the inner surface of the second glass pane.

15. The vehicle according to claim 14, further comprising: an encapsulation having a first wall abutting the inner surface of the second glass pane and a projection that extends away from the inner surface of the second glass pane, wherein the camera abuts each of the first wall and the projection, a first adhesive sealant adheres the garnish panel to the outer surface of the second glass pane, and a second adhesive sealant adheres the encapsulation to the side panel.

16. The vehicle according to claim 15, wherein the second glass pane has a green color, the first glass pane has a color that is different from the green color and includes a first exterior surface, the side panel includes a second exterior surface, the garnish panel includes a third exterior surface that is co-planar with each of the first exterior surface and the second exterior surface, and the second exterior surface has a gloss color that matches the color of the first glass pane.

17. The vehicle according to claim 16, wherein at least one of the first adhesive sealant and the second adhesive sealant is a urethane adhesive sealant.

18. The vehicle according to claim 15, wherein the encapsulation includes a lip seal that abuts the side panel.

19. The vehicle according to claim 18, further comprising: a molding connected to the first glass pane, and the molding includes a seal lip that abuts at least one of the encapsulation and the garnish panel.

20. The vehicle according to claim 14, further comprising: a mount, wherein the side panel includes a camera opening that is spaced away from the window opening in the longitudinal direction, the second glass pane spans the camera opening in the longitudinal direction and is spaced away from the camera opening in a transverse direction of the vehicle, the second glass pane has an exterior surface facing away from the vehicle and the first glass pane has an exterior surface facing away from the vehicle, the exterior surface of the first glass pane and the exterior surface of the second glass pane are offset from each other in the transverse direction of the vehicle, the mount is adjacent to the side panel and spans the camera opening in the longitudinal direction, and the camera is mounted onto the mount and has an optical axis that extends through the camera opening.
