

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12419003
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Wang; Pao-Ching et al.

Cabinet and server system

Abstract

A cabinet for mounting server to rack includes a chassis, a handle, a lever, and a linkage. The rack includes a support. The support comprises a first limiting surface and a second limiting surface. An axis of the lever is perpendicular to an axis of the handle, the lever comprises a first limiting part and a second limiting part. When the handle rotates, the linkage drives the lever rotate, the first limiting part pushes the first limiting surface to push the chassis out of the rack, or the second limiting part pushes the second limiting surface to push the chassis into the rack. A server system using the cabinet is also disclosed.

Inventors:	Wang; Pao-Ching (New Taipei, TW), Lin; Chieh-Hsiang (New Taipei, TW)
Applicant:	Fulian Precision Electronics (Tianjin) Co., LTD. (Tianjin, CN)
Family ID:	1000008819010
Assignee:	Fulian Precision Electronics (Tianjin) Co., LTD. (Tianjin, CN)
Appl. No.:	18/222506
Filed:	July 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240334635 A1	Oct. 03, 2024

Foreign Application Priority Data

CN	202310348465.5	Mar. 31, 2023
----	----------------	---------------

Publication Classification

Int. Cl.:	H05K7/14 (20060101)
------------------	---------------------

U.S. Cl.:

CPC H05K7/1488 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6147872	12/1999	Roy	361/801	H05K 7/1409
11388829	12/2021	Shih	N/A	H05K 7/1488
2003/0080568	12/2002	Busby	361/801	A47B 81/06
2004/0242039	12/2003	Griffin	439/157	H05K 7/1409
2005/0111178	12/2004	Bradley	360/99.06	H05K 7/1411
2006/0215373	12/2005	Joist	361/726	H05K 7/1409
2024/0093706	12/2023	Lin	N/A	F16B 2/06

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112462867	12/2021	CN	N/A

Primary Examiner: Parker; Allen L

Assistant Examiner: Augustin; Christopher L

Attorney, Agent or Firm: ScienBiziP, P.C.

Background/Summary

FIELD

(1) The disclosure herein generally relates to information handling systems, and more particularly relates to a cabinet and a server system.

BACKGROUND

(2) In server system, for mounting the cabinet to the rack more conveniently, the cabinet usually has a handle. The handle is used to save effort. However, due to the limited space in the front of the cabinet, the handle has insufficient space for structure designing, resulting in the problem of poor labor-saving effect for the handle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Many aspects of the disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily drawn to scale, the emphasis instead being placed upon clearly illustrating the principles of the disclosure. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

(2) FIG. 1 is an isometric view of a server system according to an embodiment of the present disclosure, showing the rack comprising two supports, and showing the cabinet in a locked position.

(3) FIG. 2 is a top and cutaway view of the cabinet of FIG. 1.

(4) FIG. 3 is an isometric and cutaway view of the cabinet of FIG. 1, showing the cabinet in an unlocked position.

(5) FIG. 4 is a top and cutaway view of the cabinet of FIG. 3.

(6) FIG. 5 is an isometric view of a chassis of the cabinet of FIG. 1.

DETAILED DESCRIPTION

(7) It will be appreciated that for simplicity and clarity of illustration, where appropriate, reference numerals have been repeated among the different figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of the embodiments described herein. However, it will be understood by those of ordinary skill in the art that the embodiments described herein can be practiced without these specific details. In other instances, methods, procedures, and components have not been described in detail so as not to obscure the related relevant feature being described. Also, the description is not to be considered as limiting the scope of the embodiments described herein. The drawings are not necessarily to scale and the proportions of certain parts have been exaggerated to better illustrate details and features of the present disclosure.

(8) The present disclosure, including the accompanying drawings, is illustrated by way of examples and not by way of limitation. Several definitions that apply throughout this disclosure will now be presented. It should be noted that references to “an” or “one” embodiment in this disclosure are not necessarily to the same embodiment, and such references mean “at least one”.

(9) The term “comprising” means “including, but not necessarily limited to”; it specifically indicates open-ended inclusion or membership in a so-described combination, group, series, and the like.

(10) Without a given definition otherwise, all terms used have the same meaning as commonly understood by those skilled in the art. The terms used herein in the description of the present disclosure are for the purpose of describing specific embodiments only, and are not intended to limit the present disclosure.

(11) As shown in FIG. 1 to FIG. 5, a server system **100** in one embodiment includes a rack **300** and a plurality of servers **400**. The plurality of servers **400** can be slidably installed onto the rack **300**, such as by rails.

(12) The rack **300** includes at least four supports. Only two supports (supports **10**) in the front of the rack **300** are shown in FIG. 1.

(13) Each of the plurality of servers **400** includes a cabinet **200**. The cabinet **200** includes a chassis **20**, and the chassis **20** is configured for receiving electronic elements, such as, hard disk drives, mainboards, expansion cards, riser cards, and so on.

(14) The rack **300** has an installation position for each server **400**. The chassis **20** is detachably located on the installation position, so to install the server **400** into the rack **300**. After installing the server **400** into the rack **300**, the supports **10** stands beside the chassis **20**. Furthermore, the chassis **20** enters the installation position along a X direction, and the supports **10** stands on the side of the chassis **20** along the Y direction.

(15) At least one of the two supports **10** includes a first limiting surface **11** and a second limiting surface **12**, and the first limiting surface **11** and the second limiting surface **12** are located on opposite sides of the support **10**, and the first limiting surface **11** and the second limiting surface **12** are located on the same side of the installation position.

(16) The cabinet **200** further includes a handle **30**, a lever **40**, and a linkage **50**. The handle **30** is rotatably connected to the chassis **20**. The lever **40** is rotatably connected to the chassis **20**. The linkage **50** is connected to the handle **30** and the lever **40**. The axis of the lever **40** and the handle

30 are perpendicular to each other.

(17) The lever **40** includes a first limiting part **41** and a second limiting part **42**. When the chassis **20** is located on the installation position, the first limiting part **41** is located on the side of the first limiting surface **11** opposite to the second limiting surface **12**, and the second limiting part **42** is located on the side of the second limiting surface **12** opposite to the first limiting surface **11**. The first limiting part **41** and a second limiting part **42** lock the chassis **20** to the support **10**, so to lock the server **400** on the rack **300**.

(18) When the server **400** is located on the rack **300** and the lever **40** is rotated clockwise, the first limiting part **41** pushes the first limiting surface **11**. During the rotation of the lever **40**, the chassis **20** will be gradually pushed out of the installation position, so that the server **400** can be taken out from the rack **300**.

(19) When to load the server **400** to the rack **300**, put the server **400** in the installation position until the first limiting part **41** contact the first limiting surface **11**, and then rotate the lever **40** counterclockwise, the second limiting part **42** pushes the second limiting surface **12**. During the rotation of the lever **40**, the chassis **20** will be gradually pushed into the installation position, so that the server **400** can be positioned on the rack **300**.

(20) In some embodiments, the linkage **50** includes a first bevel gear **51** and a second bevel gear **52**. The first bevel gear **51** is located on the handle **30** and rotates with the handle **30**. The second bevel gear **51** is located on the lever **40** and rotates with the lever **40**. The second bevel gear **51** is engaged with the first bevel gear **51**. The rotating axis of the first bevel gear **51** and the second bevel gear **52** are perpendicular to each other. When turning the handle **30**, the handle **30** rotates the first bevel gear **51**, and the first bevel gear **51** rotates the second bevel gear **51**, and the second bevel gear **51** rotates the lever **40**.

(21) The linkage **50** allows the axis of the lever **40** and the handle **30** are perpendicular to each other, so the force direction of the handle **30** can be vertically transformed. Thereby the linkage **50** saves the space of the chassis **20**.

(22) In some embodiments, the chassis **20** includes a bottom wall **21** and a side wall **22**, and the side wall **22** is vertical to the bottom wall **21**. A cavity **20a** is formed between the bottom wall **21** and the side wall **22**. The handle **30**, the first bevel gear **51** and the second bevel gear **52** are in the cavity **20a**. The cavity **20a** is used for containing the server **400**. The bottom wall **21** is used for supporting the server **400**. The side wall **22** is used for positioning the server **400**. The support **10** is located on the side of the side wall **22** opposite to the bottom wall **21**. The handle **30** is rotatably connected to the inner side of the side wall **22**. The lever **40** is rotatably connected to the inner side of the bottom wall **21**. The axis of the first bevel gear **51** is vertical to the side wall **22**. The axis of the second bevel gear **52** is perpendicular to the bottom wall **21**. The handle **30**, the lever **40** and the linkage **50** are located on the outer end of the bottom wall **21** and the side wall **22**.

(23) In some embodiments, the handle **30** and the lever **40** is sheet metal, the handle **30** is connected to the side wall **22**, and the lever **40** is connected to the bottom wall **21**.

(24) When the server **400** is located on the rack **300**, the handle **30** is in the cavity **20a**. And when to take out the server **400** from the rack **300**, the handle **30** is rotated out of the cavity **20a**.

(25) In some embodiments, a groove **23** is defined in the bottom wall **21** or the side wall **22**. The groove **23** communicates with the cavity **20a**, the lever **40** can extend out of the cavity **20a** via the groove **23**. The first limiting part **41** and the second limiting part **42** are able to extend out of the chassis **20**, so to abut against the support **10**. When the server **400** is located on the rack **300**, the first limiting part **41** and the second limiting part **42** are extended out of the cavity **20a** via the groove **23**. When to take the server **400** out of the rack **300** or to put the server **400** into rack **300**, the second limiting part **42** is in the cavity **20a**, and only the first limiting part **41** is extended out of the cavity **20a** via the groove **23**, avoiding the second limiting part **42** interfering with the support **10**.

(26) In some embodiments, the extendable part of the lever **40** out of the chassis **20** has an opening

43. The opening 43 is located between the first limiting part 41 and the second limiting part 42. The opening 43 is configured for avoiding the support 10.

(27) In some embodiments, the first limiting surface 11 and the second limiting surface 12 are parallel to each other. The distance between the first limiting part 41 and the second limiting part 42 is greater than the distance between the first limiting surface 11 and the second limiting surface 12, to avoid the lever 40 being stuck when the lever 40 turns. In some embodiments, the support 10 is a pipe with a rectangular cross-section, and the first limiting surface 11 and the second limiting surface 12 are the two opposite sides of the pipe.

(28) In some embodiments, the handle 30 includes a fold part 31, the fold part 31 is located on the side of the handle 30 opposite to the linkage 50. The fold part 31 is vertical to the side wall 22. A mounting hole 311 is defined in the fold part 31. The mounting hole 311 can be aligned with a hole of the chassis 20. The mounting hole 311 is configured for mounting screws to fix the handle 30 to the chassis 20, avoiding the chassis 20 from being separated from the rack 300. When the server 400 is located on the rack 300, the mounting hole 311 is aligned with the hole of the chassis 20.

(29) In some embodiments, there are two supports 10 and two levers 40. When the server 400 is located on the rack 300, two supports 10 are located on opposite sides of the chassis 20 in the direction Y. Two levers 40 are connected on either side of the chassis 20 in the direction Y. Each of the two levers 40 is configured for pushing the support 10 on the same side.

(30) Furthermore, there are two handles 30 and two linkages 50. Each of the two levers 40 is connected to one handle 30 by one linkage 50. When to load the server 400 in the rack 300, rotate the two handles 30 respectively to latch both sides of the chassis 20 to the supports 10. When to unload the server 400 from the rack 300, rotate the two handles 30 respectively to unlatch the both sides of the chassis 20 from the supports 10. The two handles 30 provides double insurances, preventing the chassis 20 from being separated from the rack 300.

(31) In some other embodiments, there are two supports 10, two levers 40, one handle 30, and one linkage 50. The two levers 40 are rotated by the one handle 30 and the one linkage 50 synchronously. When the handle 30 is turned, the two first bevel gears 51 and the two second bevel gears 52 rotates synchronously, so that the two levers 40 push the two supports 10 at the same time.

(32) The embodiments shown and described above are only examples. Even though numerous characteristics and advantages of the present technology have been set forth in the foregoing description, together with details of the structure and function of the present disclosure, the disclosure is illustrative only, and changes may be made in the detail, including in matters of shape, size, and arrangement of the parts within the principles of the present disclosure, up to and including the full extent established by the broad general meaning of the terms used in the claims.

Claims

1. A cabinet configured for mounting a server to a rack, the cabinet comprising: a chassis; a handle rotatably connected to the chassis; a lever rotatably connected to the chassis; and a linkage connected to the handle and the lever, wherein an axis of the lever is perpendicular to an axis of the handle, the lever comprises a first limiting part and a second limiting part, and when the handle is rotated, the handle rotates the lever by the linkage, the first limiting part pushes a first limiting surface of the rack to push the chassis out of the rack, or the second limiting part pushes a second limiting surface of the rack to push the chassis into the rack; the linkage comprises a first bevel gear and a second bevel gear, the first bevel gear is located on the handle and rotates with the handle, the second bevel gear is located on the lever and engages with the first bevel gear, an axis of the first bevel gear is perpendicular to an axis of the second bevel gear.

2. The cabinet of claim 1, wherein the chassis comprises a bottom wall and a side wall, the side wall is perpendicular to the bottom wall, the handle is rotatably connected to the side wall, the lever is rotatably connected the bottom wall, an axis of the first bevel gear is perpendicular to the side

wall, an axis of the second bevel gear is perpendicular to the bottom wall.

3. The cabinet of claim 2, wherein a cavity is defined between the bottom wall and the side wall, the handle, the first bevel gear, and the second bevel gear are located in the cavity.

4. The cabinet of claim 3, wherein a groove is defined between the bottom wall and the side wall, the groove is communicated with the cavity, the lever is partially located in the cavity, and the first limiting part and the second limiting part extend out of the cavity through the groove.

5. The cabinet of claim 4, wherein an opening is defined on the lever, the opening is located between the first limiting part and the second limiting part, the opening is configured for avoiding a support.

6. The cabinet of claim 1, wherein the handle comprises a fold part, the fold part is located on a side of the handle away from the linkage, the fold part defines a mounting hole.

7. The cabinet of claim 1, wherein the first limiting surface and the second limiting surface are parallel, a distance between the first limiting part and the second limiting part is greater than a distance between the first limiting surface and the second limiting surface.

8. A server system comprising: a plurality of servers; and a rack, wherein the rack comprises a support, each of the plurality of servers comprises a cabinet, the cabinet comprises: a chassis; a handle rotatably connected to the chassis; a lever rotatably connected to the chassis; and a linkage connected to the handle and the lever; the chassis is located on a side of the support, the support comprises a first limiting surface and a second limiting surface, the first limiting surface and the second limiting surface are located on opposite sides of the support and are located on a same side of the chassis, an axis of the lever is perpendicular to an axis of the handle, the lever comprises a first limiting part and a second limiting part, and when the handle is rotated, the handle rotates the lever by the linkage, the first limiting part pushes the first limiting surface to push the chassis out of the rack, or the second limiting part pushes the second limiting surface to push the chassis into the rack; the linkage comprises a first bevel gear and a second bevel gear, the first bevel gear is located on the handle and rotates with the handle, the second bevel gear is located on the lever and engages with the first bevel gear, an axis of the first bevel gear is perpendicular to an axis of the second bevel gear.

9. The server system of claim 7, wherein the chassis comprises a bottom wall and a side wall, the side wall is perpendicular to the bottom wall, the support is located on a side of the side wall opposite to the bottom wall, the handle is rotatably connected to the side wall, the lever is rotatably connected the bottom wall, an axis of the first bevel gear is perpendicular to the side wall, an axis of the second bevel gear is perpendicular to the bottom wall.

10. The server system of claim 9, wherein a cavity is defined between the bottom wall and the side wall, the handle, the first bevel gear, and the second bevel gear are located in the cavity.

11. The server system of claim 10, wherein a groove is defined between the bottom wall and the side wall, the groove is communicated with the cavity, the lever is partially located in the cavity, and the first limiting part and the second limiting part extend out of the cavity through the groove.

12. The server system of claim 11, wherein an opening is defined on the lever, the opening is located between the first limiting part and the second limiting part, the opening is configured for avoiding the support.

13. The server system of claim 8, wherein the handle comprises a fold part, the fold part is located on a side of the handle away from the linkage, the fold part defines a mounting hole.

14. The server system of claim 8, wherein the first limiting surface and the second limiting surface are parallel, a distance between the first limiting part and the second limiting part is greater than a distance between the first limiting surface and the second limiting surface.

15. A server system comprising: a plurality of servers; and a rack, wherein the rack comprises two supports, each of the plurality of servers comprises a cabinet, the cabinet comprises: a chassis; two handles rotatably connected to the chassis; two levers rotatably connected to the chassis; and two linkages connected to the two handles and the two levers; the chassis is located between the two

supports, each of the two supports comprises a first limiting surface and a second limiting surface, the first limiting surface and the second limiting surface are located on opposite sides of each of the two supports and are located on a same side of the chassis, each of the two levers is respectively connected to each of the two handles by each of the two linkages, an axis of each of the two levers is perpendicular to an axis of each of the two handles, each of the two levers comprises a first limiting part and a second limiting part, and when each of the two handles is rotated, each of the two handles rotates each of the two levers by each of the two linkages, each of the two first limiting parts pushes each of the two first limiting surfaces to push the chassis out of the rack, or each of the two second limiting parts pushes each of the two second limiting surfaces to push the chassis into the rack.

16. The server system of claim 15, wherein each of the two linkages comprises a first bevel gear and a second bevel gear, each of the two first bevel gears is located on each of the two handles and rotates with each of the two handles, each of the two second bevel gears is located on each of the two levers and engages with each of the two first bevel gears, an axis of each of the two first bevel gears is perpendicular to an axis of each of the two second bevel gears.

17. The server system of claim 16, wherein the chassis comprises a bottom wall and two side walls, the two side walls are perpendicular to the bottom wall, the two side walls are located on opposite sides of the bottom wall, each of the two handles is rotatably respectively connected to each of the two side walls, the two levers is rotatably connected the bottom wall, an axis of each of the two first bevel gears is perpendicular to each of the two side walls, an axis of each of the two second bevel gears is perpendicular to the bottom wall.

18. The server system of claim 17, wherein a cavity is defined between the bottom wall and the two side walls, the two handles, the two first bevel gears, and the two second bevel gears are located in the cavity, two grooves is defined and each of the two grooves is located between the bottom wall and each of the two side walls, the two grooves are communicated with the cavity, each of the two levers is partially located in the cavity, and each of the two first limiting parts and each of the two second limiting parts extend out of the cavity through each of the two grooves.
