

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383719
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Rothenberg; Ashley Rachel et al.

Disinfecting cap with re-use prevention

Abstract

A medical connector for connection to a corresponding medical connector is described. The medical connector includes a housing having a radial protrusion and a cavity, the cavity defined by a closed end, an open end, a partially cylindrical sidewall and a radial sidewall. The medical connector further includes an insert disposed within the housing, the insert including a locking tab having at least one thread on the inner wall of the locking tab and a recessed notch on the outer wall of the locking tab. The at least one thread of the locking tab engages at least one thread of a corresponding medical connector. Disposed within the cavity, the recessed notch rotates from a first position to a second position, wherein the second position contains a locking structure for non-removably securing the insert to the housing, while allowing for removal of the corresponding medical connector.

Inventors: Rothenberg; Ashley Rachel (Morris Plains, NJ), Oshinski; Matthew (Oak Ridge, NJ)

Applicant: Becton, Dickinson and Company (Franklin Lakes, NJ)

Family ID: 78081243

Assignee: Becton, Dickinson and Company (Franklin Lakes, NJ)

Appl. No.: 17/229173

Filed: April 13, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210322749 A1	Oct. 21, 2021

Related U.S. Application Data

us-provisional-application US 63131007 20201228

Publication Classification

Int. Cl.: **A61M39/10** (20060101); **A61M39/02** (20060101)

U.S. Cl.:

CPC **A61M39/1011** (20130101); **A61M39/0247** (20130101); A61M2039/0258 (20130101); A61M2205/273 (20130101)

Field of Classification Search

CPC: A61M (39/1011); A61M (39/0247); A61M (2039/0258); A61M (2205/273); A61M (2205/581); A61M (39/20); A61M (2039/1033); A61M (2039/1044); A61M (39/10); A61M (2005/3104); A61M (2005/312); A61M (2039/0288); A61M (5/3202); A61M (39/162); A61M (39/16); A61M (2205/0205); A61M (39/165); A61M (39/18); A61M (2039/0036); A61M (2039/0285); B65D (41/04); F16L (2201/20); F16L (2201/44); B08B (9/023); A61B (90/70); A61J (1/2096); A61J (1/1443); Y10S (604/905)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3403679	12/1967	Sinclair et al.	N/A	N/A
4597758	12/1985	Aalto et al.	N/A	N/A
4642102	12/1986	Ohmori	N/A	N/A
4711363	12/1986	Marino	N/A	N/A
4738376	12/1987	Markus	N/A	N/A
4906231	12/1989	Young	N/A	N/A
5084017	12/1991	Maffetone	N/A	N/A
5496288	12/1995	Sweeney	N/A	N/A
5676406	12/1996	Simmons et al.	N/A	N/A
5755696	12/1997	Caizza	N/A	N/A
5984123	12/1998	Mogami et al.	N/A	N/A
6565529	12/2002	Kimber et al.	N/A	N/A
6632199	12/2002	Tucker et al.	N/A	N/A
7083605	12/2005	Miyahara	N/A	N/A
8012131	12/2010	Moser et al.	N/A	N/A
8388894	12/2012	Colantonio	N/A	N/A
8647308	12/2013	Solomon et al.	N/A	N/A
8715231	12/2013	Woehr	N/A	N/A
8721627	12/2013	Alpert et al.	N/A	N/A
8777504	12/2013	Shaw et al.	N/A	N/A
8961475	12/2014	Solomon et al.	N/A	N/A
9039989	12/2014	Lui et al.	N/A	N/A
9132223	12/2014	Wakeel	N/A	N/A
9192449	12/2014	Kerr et al.	N/A	N/A
10099048	12/2017	Chiu et al.	N/A	N/A

10166381	12/2018	Gardner et al.	N/A	N/A
10376686	12/2018	Burkholz et al.	N/A	N/A
10589080	12/2019	Hitchcock et al.	N/A	N/A
10603481	12/2019	Avula et al.	N/A	N/A
10871246	12/2019	Marici et al.	N/A	N/A
11353147	12/2021	Marici	N/A	N/A
11511100	12/2021	Ryan	N/A	N/A
11628288	12/2022	Soloman et al.	N/A	A61M 39/18
2003/0093009	12/2002	Newby et al.	N/A	N/A
2003/0209681	12/2002	Leinsing et al.	N/A	N/A
2004/0039341	12/2003	Ranalletta	N/A	N/A
2004/0044318	12/2003	Fiser et al.	N/A	N/A
2005/0147525	12/2004	Bousquet	N/A	N/A
2005/0197646	12/2004	Connell et al.	N/A	A61M 39/20
2007/0060904	12/2006	Vedrine et al.	N/A	N/A
2007/0129705	12/2006	Trombley, III et al.	N/A	N/A
2008/0010766	12/2007	Kaufman et al.	N/A	N/A
2008/0171995	12/2007	Mtullo et al.	N/A	N/A
2008/0177250	12/2007	Howlett et al.	N/A	N/A
2010/0000040	12/2009	Shaw et al.	N/A	N/A
2010/0049170	12/2009	Solomon et al.	N/A	N/A
2010/0050351	12/2009	Colantonio et al.	N/A	N/A
2010/0100056	12/2009	Cawthon et al.	N/A	N/A
2011/0046603	12/2010	Felsovalyi et al.	N/A	N/A
2011/0054440	12/2010	Lewis	N/A	N/A
2011/0213341	12/2010	Solomon et al.	N/A	N/A
2011/0264037	12/2010	Foshee et al.	N/A	N/A
2012/0039764	12/2011	Solomon et al.	N/A	N/A
2012/0111368	12/2011	Rahimy et al.	N/A	N/A
2012/0123386	12/2011	Tsals	N/A	N/A
2012/0302997	12/2011	Gardner et al.	N/A	N/A
2013/0085474	12/2012	Charles et al.	N/A	N/A
2013/0171030	12/2012	Ferlic et al.	N/A	N/A
2013/0197485	12/2012	Gardner et al.	N/A	N/A
2013/0338644	12/2012	Solomon et al.	N/A	N/A
2014/0052074	12/2013	Tekeste	N/A	N/A
2014/0150832	12/2013	Rogers et al.	N/A	N/A
2014/0191501	12/2013	Brugger et al.	N/A	A61M 39/1011
2014/0366914	12/2013	Kerr et al.	N/A	N/A
2015/0094666	12/2014	Bates et al.	N/A	N/A
2016/0045629	12/2015	Gardner et al.	N/A	N/A
2016/0067422	12/2015	Davis et al.	N/A	N/A
2016/0158520	12/2015	Ma et al.	N/A	N/A
2017/0203087	12/2016	Ryan et al.	N/A	N/A
2018/0085568	12/2017	Drmanovic	N/A	N/A
2018/0200145	12/2017	Sanders et al.	N/A	N/A
2018/0200500	12/2017	Ziebol et al.	N/A	N/A
2018/0237190	12/2017	Iwasaki	N/A	N/A
2018/0243547	12/2017	Fox et al.	N/A	N/A

2018/0256879	12/2017	Chiu et al.	N/A	N/A
2018/0256883	12/2017	Follman	N/A	A61M 39/162
2019/0001115	12/2018	Ma	N/A	A61M 39/162
2019/0151643	12/2018	Alpert	N/A	N/A
2019/0234540	12/2018	Marici	N/A	A61M 39/20
2019/0308006	12/2018	Erekovcanski et al.	N/A	N/A
2019/0351212	12/2018	Dudar et al.	N/A	N/A
2020/0147360	12/2019	Arnett	N/A	A61M 39/1011
2020/0238070	12/2019	Ryan	N/A	N/A
2021/0100996	12/2020	Wijesuriya et al.	N/A	A61M 39/0247
2021/0187267	12/2020	Jiang	N/A	N/A
2022/0273931	12/2021	Jiang et al.	N/A	N/A
2023/0080687	12/2022	Ryan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2523133	12/2012	CA	N/A
1322119	12/2000	CN	N/A
101541361	12/2008	CN	N/A
101631585	12/2009	CN	N/A
101980746	12/2010	CN	N/A
201807018	12/2010	CN	N/A
102188766	12/2010	CN	N/A
102448502	12/2011	CN	N/A
103025374	12/2012	CN	N/A
103083767	12/2012	CN	N/A
204161736	12/2014	CN	N/A
206198472	12/2016	CN	N/A
216022674	12/2021	CN	N/A
10247963	12/2003	DE	N/A
202005004079	12/2005	DE	N/A
0589379	12/1993	EP	N/A
2606930	12/2012	EP	N/A
2832391	12/2014	EP	N/A
3275490	12/2017	EP	N/A
2408259	12/2004	GB	N/A
2518646	12/2014	GB	N/A
S5841561	12/1982	JP	N/A
H03139363	12/1990	JP	N/A
H04501672	12/1991	JP	N/A
2001502191	12/2000	JP	N/A
2001521792	12/2000	JP	N/A
2004208740	12/2003	JP	N/A
2008532701	12/2007	JP	N/A
2008239164	12/2007	JP	N/A
2008253775	12/2007	JP	N/A
2009526241	12/2008	JP	N/A
2010527276	12/2009	JP	N/A

2012522593	12/2011	JP	N/A
2013509274	12/2012	JP	N/A
2015517377	12/2014	JP	N/A
2016511119	12/2015	JP	N/A
2016104214	12/2015	JP	N/A
0019878	12/1999	WO	N/A
200024442	12/1999	WO	N/A
200224551	12/2001	WO	N/A
2011066586	12/2010	WO	N/A
2012144026	12/2011	WO	N/A
2013046857	12/2012	WO	N/A
2014159346	12/2013	WO	N/A
2015004728	12/2014	WO	N/A
2015127285	12/2014	WO	N/A
2015174953	12/2014	WO	N/A
2016158144	12/2015	WO	N/A
2017087400	12/2016	WO	N/A
2017095373	12/2016	WO	N/A
2018106508	12/2017	WO	N/A
2018237090	12/2017	WO	N/A
2019147906	12/2018	WO	N/A
2019212637	12/2018	WO	N/A
2020056120	12/2019	WO	N/A
2020112767	12/2019	WO	N/A

OTHER PUBLICATIONS

“PCT International Search Report and Written Opinion in PCT/US2021/027219 dated Oct. 22, 2021, 22 pages”. cited by applicant

Non-Final Office Action in U.S. Appl. No. 16/774,853 dated Feb. 1, 2022, 12 pages. cited by applicant

“Non-Final Office Action in U.S. Appl. No. 17/076,102 dated Aug. 24, 2021, 10 pages”. cited by applicant

PCT Invitation to Pay Additional Fees in PCT/US2021/019546, mailed on Jun. 15, 2021, 17 pages. cited by applicant

PCT International Search Report and Written Opinion in PCT/US2021/027214 dated Jul. 19, 2021, 14 pages. cited by applicant

PCT International Search Report and Written Opinion in PCT/US2021/027218 dated Jul. 22, 2021, 14 pages. cited by applicant

PCT International Search Report and Written Opinion in PCT/US2021/027220 dated Jul. 21, 2021, 15 pages. cited by applicant

PCT Invitation to Pay Additional Fees in PCT/US2021/027219, mailed on Jul. 22, 2021, 15 pages. cited by applicant

“Ruhof Dry Sponges”, Ruhof, Sep. 30, 2016, <https://www.ruhof.com/products/ruhof-dry-sponges> (Year: 2016). cited by applicant

Primary Examiner: Tsai; Michael J

Assistant Examiner: Farrell; Kathleen Paige

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Application No. 63/011,359, filed Apr. 17, 2020, and U.S. Provisional Application No. 63/131,007, filed Dec. 28, 2020, the entire disclosures of which are hereby incorporated by reference herein.

TECHNICAL FIELD

(1) The present disclosure generally relates to medical connectors. In particular, the present disclosure relates to mating elements of medical connectors having re-use prevention features and disinfection features.

BACKGROUND

(2) Vascular access devices (VAD's) are commonly used therapeutic devices and include intravenous (IV) catheters. There are two general classifications of VAD's: peripheral catheters and central venous catheters. Bacteria and other microorganisms may gain entry into a patient's vascular system from access hubs and ports/valves upon connection to the VAD when delivering fluids or pharmaceuticals to a patient. Each access hub, connection, port or valve is associated with some risk of transmitting a catheter related bloodstream infection (CRBSI), which can be costly and potentially lethal.

(3) In order to decrease CRBSI cases and to ensure VAD's are used and maintained correctly, standards of practice have been developed, which include disinfecting and cleaning procedures.

(4) Disinfection caps have been added to the Society for Healthcare Epidemiology of America (SHEA) guidelines and have also been incorporated into the Infusion Nurses Standards (INS) guidelines.

(5) In developed markets, when utilizing an IV catheter, a needleless connector will typically be used to close off the system and then subsequently accessed to administer medication or other necessary fluids via the catheter to the patient. INS Standards of Practice recommend the use of a needleless connector and state that it should be "consistently and thoroughly disinfected using alcohol, tincture of iodine or chlorhexidine gluconate/alcohol combination prior to each access." The disinfection of the needleless connector is ultimately intended to aid in the reduction of bacteria that could be living on the surface and possibly lead to a variety of catheter related complications including CRBSI. Nurses will typically utilize a 70% isopropyl alcohol (IPA) pad to complete this disinfection task by doing what is known as "scrubbing the hub." However, compliance and the level of disinfection attributed to this practice typically relies on the ability and competency of the user. In addition to a lack of compliance to "scrubbing the hub", it has also been noted through clinician interviews that there is often a variation in scrub time, dry time and the number of times the needleless connector is scrubbed.

(6) Threaded needleless connectors are used to decrease CRBSI cases and to ensure VAD's are used and maintained properly as threaded connectors are more secure than slip connectors. However, while threaded needleless connectors, such a threaded luer connectors, are more secure, they require more manipulation by the clinician and the connection is not as quick as luer slip connectors

(7) Thus, there is a need for medical connectors capable of disinfecting luer connectors and reuse prevention thereby reducing risk of the disinfectant entering the blood stream. Further, there is a need for devices which mate with medical connectors which provide for the security of threaded connectors but the ease of use of slip-connectors.

SUMMARY

(8) One aspect of the present disclosure pertains to medical connectors and mating elements of a medical connector (i.e., a needleless connector) having a housing, a locking structure and an insert disposed within the medical connector. The housing has a substantially cylindrical housing body having a radial protrusion extending from the cylindrical housing body and a cavity defined by a closed end, an open end, a partially cylindrical inner sidewall of the housing body and a radial sidewall of the radial protrusion. In some embodiments, the closed end further includes a lumen for the transfer of fluid beyond the closed end. The locking structure is disposed on a lateral portion of the radial sidewall of the cavity, the locking structure including a sloped tab. The insert is advanced into the cavity of the housing, the insert comprising a discoid body having a distal surface, a proximal surface, a sidewall and a locking tab extending proximally from the sidewall, the insert includes at least one thread on an inner wall of the locking tab and a recessed notch disposed on a distal portion of an outer wall of the locking tab.

(9) In one or more embodiments, the insert rotates from a first position to a locking position, the first position being defined by a medial portion of the radial sidewall and the locking position being defined by the lateral portion, the lateral portion including the locking structure. In one or more embodiments, the recessed notch engages a ledge of the sloped tab when the recessed notch is advanced past the sloped tab. In one or more embodiments, the locking tab elastically deforms.

(10) In one or more embodiments, the locking structure further includes an outwardly sloped surface which slopes outwardly from a medial or leftward position to a lateral or rightward position.

(11) In one or more embodiments, the outwardly sloped surface extends at least partially a length of the arc of the radial sidewall. In one or more embodiments, the outwardly sloped surface extends an entire length of the arc of the radial sidewall.

(12) In one or more embodiments, the sloped tab extends from a lateral portion of the outwardly sloped surface. In one or more embodiments, the outwardly sloped surface causes deformation of the locking tab.

(13) In one or more embodiments, the locking structure further includes a proximally sloped surface, the proximally sloped surface located adjacent to a ledge of the sloped surface.

(14) In one or more embodiments, the proximally sloped surface slopes inwardly with respect to the radial sidewall from a distal position to a proximal position.

(15) In one or more embodiments, the distal surface of the insert abuts an inner top surface of the cavity of the housing when the insert is fully advanced into the cavity.

(16) In one or more embodiments, the medical connector further comprises an absorbent material disposed between the distal surface of the insert and an inner top surface of the cavity of the housing when the insert is fully advanced into the cavity. In one or more embodiments, the absorbent material contains a disinfectant.

(17) In one or more embodiments, fully advancing the insert into the cavity in a distal direction causes the distal surface of the insert and the inner top surface of the cavity of the housing to compress the absorbent material, the absorbent material releasing the disinfectant. Disinfectant evacuates into the cavity by a gap defined by the partially cylindrical inner sidewall of the housing and the sidewall of the insert.

(18) In one or more embodiments, the diameter of the partially cylindrical inner sidewall of the housing has a larger diameter than the sidewall of the insert.

(19) In one or more embodiments, a retention tab is disposed on an inner top surface of the housing, the inner top surface non-removably securing an aperture disposed on the distal surface of the insert, the aperture extending therethrough.

(20) A second aspect of the present disclosure pertains to a medical connector having a housing, a locking structure and an insert disposed within medical connector. The housing has a substantially cylindrical housing body having a radial protrusion extending from the cylindrical housing body and a cavity defined by a closed end, an open end, a partially cylindrical inner sidewall of the

housing body and a radial sidewall of the radial protrusion. The locking structure is disposed on a lateral portion of the radial sidewall of the cavity, the locking structure including a sloped tab. The insert is advanceable into the cavity of the housing, the insert comprising a discoid body having a distal surface, a proximal surface, a sidewall and a locking tab extending proximally from the sidewall, the insert including at least one thread on an inner wall of the locking tab and a recessed notch disposed on a distal portion of an outer wall of the locking tab. Threading a corresponding medical connector into the cavity causes the insert to be advanced into the cavity, the corresponding medical connector having at least one thread to engage the at least one thread of the insert.

(21) In one or more embodiments, the corresponding medical connector is removably threaded into the cavity.

(22) A third aspect of the present disclosure pertains to a medical connector of a syringe having a housing protruding in a distal direction from a distal wall of a syringe barrel of the syringe, the housing including a cavity defined by the distal wall of the syringe barrel, an open end opposite the distal wall and a partially cylindrical sidewall extending from the distal wall to the open end, the housing further including a radial sidewall defined by a radial protrusion extending laterally from the housing, the radial protrusion and the radial sidewall being in the shape of a laterally protruding arc.

(23) The syringe further comprises a tapered hub disposed within the cavity of the housing, the tapered hub extending in a distal direction from the distal wall of the syringe barrel, the tapered hub configured to interdigitate with a corresponding cavity of a housing of a vascular access device.

(24) The syringe further comprises a locking structure disposed on the radial sidewall including an outwardly sloped surface, and a sloped tab, the sloped surface slopes outwardly from a medial or leftward position to a lateral or rightward position, the outwardly sloped surface extending at least partially the length of the arc of the radial sidewall, the sloped tab slopes outwardly from a lateral or rightward position to a medial or leftward position, the sloped tab including a ledge formed by a wall at a substantially right angle with respect to the radial sidewall.

(25) The syringe further comprises an insert having a generally discoid body, the discoid body having a proximal surface, a distal surface a sidewall, a locking tab and an aperture, the locking tab extending from the distal surface, the aperture is disposed on the proximal surface of the discoid body and extends therethrough, the insert further includes at least one thread is disposed on the inner wall of the locking tab.

(26) A first position is defined by the medial or leftward portion of the radial sidewall and a locking position is defined by the sloped tab and the ledge. The housing is configured as a medical connector able to receive a male luer fitting of a vascular access device. When the insert is advanced proximally into the cavity of the housing, the locking tab is disposed in the first position causing the locking tab insert to elastically deform outwardly with respect to the radial sidewall. When the insert rotationally approaches the locking position, the outwardly sloped surface further elastically deforms the locking tab inward until the recessed notch passes the ledge of the radial sidewall, when the notch has passed the ledge and the notch non-releasably engages the ledge, thereby preventing medial or leftward movement of the locking tab.

(27) A third embodiment of the present disclosure pertains to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, an inner sidewall extending between the distal wall to the open end and a cavity. At least one helical thread disposed on an inner sidewall of the cavity. A channel is disposed on the inner sidewall having a substantially rectangular profile extending from the distal wall to the open end. An absorbent material abutting an inner distal surface of the housing

(28) The medical connector further comprises a leaf spring disposed within the channel, the leaf spring having a rectangular cross-section and an arc, the arc is between a distal portion and a proximal portion, the distal portion is non-removably attached to the channel, the proximal portion

abutting the channel in an initial state.

(29) Upon advancement of a corresponding medical connector into the cavity, at least one thread of the corresponding medical connector depresses the arc of the spring into the channel causing the proximal portion of the spring to defect away from the channel defining a final state; A proximal end of the proximal portion of the spring engages a lower segment of the least one thread of the corresponding medical connector, thereby locking the corresponding medical connector within the cavity in a threaded fit and an interference fit

(30) A fourth embodiment of the present disclosure relates to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, an inner distal surface and a cavity defined by the proximal open end and the closed distal end. The medical connector further comprises a cupped spring comprising a frusto-conical shaped disk body having at least two prongs extending from a proximal edge of the disk body, the at least two prongs extending from a proximal edge of the disc body in a proximal direction, each of the at least two prongs comprise a proximal portion and a distal portion adjacent to the proximal portion, the distal portion forming a medial hook extending toward a center of the disk body, the medial hook comprising a medial edge configured to engage with a corresponding thread of a corresponding medical connector. The medical connector further comprises an absorbent material abutting an inner distal surface of the housing.

(31) Advancement of the corresponding medical connector into the cavity causes the disk body to deform inward, pushing the proximal edge of the disk body against a lower segment of the least one thread of the corresponding medical connector, thereby locking the corresponding medical connector within the cavity.

(32) A fifth embodiment of the present disclosure relates to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, an inner sidewall extending between the distal wall to the open end and a cavity. At least one helical thread disposed on an inner sidewall of the cavity, the helical thread having a distal portion unitarily formed onto the inner sidewall and a frangible portion proximal to the distal portion configured to detach and cross-thread upon threading and advancing a corresponding thread of a corresponding medical connector into the cavity. An absorbent material abutting an inner distal surface of the housing

(33) A sixth embodiment of the present disclosure relates to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, a sidewall extending between the distal wall to the open end, a cavity extending from the open end to the distal wall, an inner distal surface, and at least one tooth extending medially into the cavity from an inner sidewall of the housing, the at least one tooth positioned a distance from the inner distal surface of the housing.

(34) The medical connector further comprises an insert in the shape of a discoid body, the discoid body having a proximal surface and a distal surface, at least two locking tabs extending from the distal surface in a distal direction away from the distal surface, each of the at least two locking tabs having a hooked proximal end configured to interlock with corresponding thread of a corresponding medical connector, and a plurality of ridges disposed on a sidewall of the discoid body, the plurality of ridges configured to interdigitate with the least one tooth of the housing. An absorbent material abuts the inner distal surface of the distal wall of the housing.

(35) A seventh aspect of the present disclosure relates to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, a sidewall extending between the distal wall to the open end and a cavity. The medical connector further comprises an insert in the shape of a C-shaped body having a distal end in the form of an arc and an open proximal end, and two living hinges extending from the distal end. An absorbent material abuts the inner distal surface of the distal wall of the housing.

(36) Advancement of a corresponding medical connector into the cavity causes deflection of the c-shaped body, thereby locking the open proximal end against threads of a corresponding medical

connector.

(37) An eighth aspect of the present disclosure relates to a medical connector comprising a substantially cylindrical housing having a distal wall, a proximal open end, a sidewall extending between the distal wall to the open end and a cavity, an inner distal surface, a medial wall positioned a distance from the inner distal surface of the housing.

(38) The medical connector further comprises an insert in the shape of a C-shaped body having a distal portion in the form of an arc, an open proximal portion and at least two living hinges extending tangential to the distal portion. An absorbent material abuts the inner distal surface of the distal wall of the housing. Advancement of a corresponding medical connector into the cavity causes deflection of the insert, thereby locking the open proximal end against threads of the medical connector. The medial wall further includes an aperture configured to receive the distal portion of the insert.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A illustrates a perspective view of a housing of a medical connector assembly according to a first exemplary embodiment of the disclosure;
- (2) FIG. 1B illustrates a perspective side view of a housing body of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (3) FIG. 2A illustrates a perspective view of an insert bottom view of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (4) FIG. 2B illustrates a perspective view of an insert bottom view of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (5) FIG. 3 illustrates a perspective bottom view of the housing body of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (6) FIG. 4 illustrates a perspective side view of the housing body and the insert of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (7) FIG. 5 illustrates a perspective bottom view of the housing body of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (8) FIG. 6 illustrates a perspective bottom view of the housing body and the insert of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (9) FIG. 7 illustrates a bottom view of the housing body and the insert of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (10) FIG. 8 illustrates a bottom view of the housing body and the insert of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (11) FIG. 9 illustrates a cross-sectional side view of the housing body and the insert of the medical connector in accordance with the embodiment as shown in FIG. 1;
- (12) FIG. 10 illustrates the elastic deformation of the locking tab in the first position and the locking position;
- (13) FIG. 11 illustrates a cross-sectional view of a medical connector inserted in the housing body and the insert of the medical connector;
- (14) FIG. 12 illustrates a side perspective view of the medical connector inserted in the housing body and the insert of the medical connector;
- (15) FIG. 13A illustrates a perspective view of a housing of a syringe in accordance with a second embodiment of the present disclosure.
- (16) FIG. 13B illustrates a top view of the housing of the syringe in accordance with the second embodiment as shown in FIG. 13A;
- (17) FIG. 13C illustrates a perspective side view of the housing of the syringe in accordance with

the second embodiment as shown in FIG. 13A;

(18) FIG. 13D illustrates a perspective side view of the housing of the syringe in accordance with the second embodiment as shown in FIG. 13A;

(19) FIG. 14A illustrates a perspective side view of an insert in accordance with the second embodiment as shown in FIG. 13A;

(20) FIG. 14B illustrates a perspective side view of the insert in accordance with the second embodiment as shown in FIG. 13A;

(21) FIG. 15 illustrates a perspective side view of the insert inserted into the housing of the syringe in accordance with the second embodiment as shown in FIG. 13A;

(22) FIG. 16 illustrates a cross-sectional view of the insert inserted into the housing of the syringe in accordance with the second embodiment as shown in FIG. 13A;

(23) FIG. 17 illustrates a perspective view of a housing of a medical connector in accordance with a third embodiment of the present disclosure.

(24) FIG. 18A illustrates a cross-sectional view of the housing in an initial state in accordance with the third embodiment as shown in FIG. 17;

(25) FIG. 18B illustrates a cross-sectional view of the housing in the initial state in accordance with the third embodiment as shown in FIG. 17;

(26) FIG. 19 illustrates a perspective view of the housing in a final state in accordance with the third embodiment as shown in FIG. 17;

(27) FIG. 20 illustrates a cross-sectional view of the housing in the final state in accordance with the third embodiment as shown in FIG. 17;

(28) FIG. 21A illustrates a cross-sectional view of a housing in an initial state in accordance with a fourth embodiment of the present disclosure;

(29) FIG. 21B illustrates a cross-sectional view of the housing in the initial state in accordance with a fourth embodiment as shown in FIG. 21A;

(30) FIG. 22A illustrates a cross-sectional view of the housing in a final state in accordance with a fourth embodiment as shown in FIG. 21A;

(31) FIG. 22B illustrates a cross-sectional view of the housing in a final state in accordance with a fourth embodiment as shown in FIG. 21A;

(32) FIG. 22C illustrates a cross-sectional view of the housing in a final state in accordance with a fourth embodiment as shown in FIG. 21A;

(33) FIG. 23A illustrates a perspective side view of a housing in an initial state in accordance with a fifth embodiment of the present disclosure;

(34) FIG. 23B illustrates a cross-sectional view of the housing in the initial state in accordance with a fifth embodiment as shown in FIG. 23A;

(35) FIG. 24A illustrates a perspective view of the housing in a final state in accordance with a fifth embodiment as shown in FIG. 23A;

(36) FIG. 24B illustrates a cross-sectional view of the housing in the final state in accordance with a fifth embodiment as shown in FIG. 23A;

(37) FIGS. 25A and 25B illustrate perspective views of an insert in accordance with a sixth embodiment of the present disclosure;

(38) FIG. 26 illustrates a cross-sectional view of the insert of FIGS. 25A and 25B disposed within a housing of an exemplary medical connector in accordance with the sixth embodiment of the present disclosure;

(39) FIG. 27 illustrates a cross-sectional view of an insert disposed within a housing of an exemplary medical connector in accordance with a seventh embodiment of the present disclosure; and

(40) FIGS. 28A and 28B illustrate a cross-sectional view of an insert disposed within a housing of an exemplary medical connector in accordance with an eighth embodiment of the present disclosure.

DETAILED DESCRIPTION

(41) Embodiments of the disclosure pertain to a sterile, medical connector for connection to and disinfection of a corresponding medical connector having an open lumen, including male, female needleless connectors, luer connectors, and stopcocks. In some embodiments, the medical connectors can male or female luer connectors. In some embodiments, the medical connector can be a cap or a connector of a syringe. In some embodiments, the medical connectors of the present disclosure are incorporated in medical devices. In some embodiments, the medical connectors of the present disclosure are mating elements incorporated in medical devices. Embodiments of the medical connector comprise a housing, an insert and an absorbent material, the insert and absorbent material disposed within the housing. Upon inserting a corresponding medical connector into the housing, the corresponding medical connector is advanced against the housing and insert which compresses the absorbent material thereby releasing antimicrobial disinfectant fluid or gel (hereinafter “disinfectant”), and in some embodiments, prevents reuse of the medical connector and the corresponding medical connector. The disinfectant disinfects the corresponding medical connector. In one or more embodiments, the medical connector and corresponding medical connector as described in detail below has the means to be of a single use, wherein the insert of the medical connector non-releasably locks onto the housing of the medical connector.

(42) The housing comprises a substantially cylindrical body having a radial protrusion and a cavity defined by a closed end, an open end, a partially cylindrical inner sidewall of the housing and a radial sidewall of the radial protrusion. The inner sidewall of the housing having a length $L_{sub.C}$ extending from the closed end to a distal wall. In one or more embodiments, the open end includes an engagement surface wherein a peelable seal is attached to.

(43) In one or more embodiments, the insert includes an inner wall. In one or more embodiments, the inner wall of the insert has at least one thread adapted to engage a female luer connector. The medical connector provides a mechanical barrier for connectors and contains an antimicrobial agent for disinfection. The medical connector of the present disclosure also allows the practitioner to streamline the disinfecting process while blocking the lumen of open luers to facilitate the mitigation of the ingress of contaminants and disinfectant into the open lumens of the connectors, thereby reducing risk of the contaminants and disinfectant entering the blood stream.

(44) With respect to terms used in this disclosure, the following definitions are provided.

(45) As used herein, the use of “a,” “an,” and “the” includes the singular and plural.

(46) As used herein, the term “catheter related bloodstream infection” or “CRBSI” refers to any infection resulting from the presence of a catheter or IV line.

(47) As used herein, the terms “medical connector” and “corresponding medical connector” refer to needleless and needle-free medical connectors such as BD MAXPLUS, BD MAXZERO™, STARTSITE™, NEUTRACLEAR™, BD Q-SYTE™ by BECTON DICKENSON AND COMPANY®. Furthermore, the terms “medical connector” and “corresponding medical connector” refer to sterile connectors having a male or female open lumen, luer connectors, and stopcocks. The terms “medical connector” and “corresponding medical connector” also refer to mating elements of needleless and needle-free connectors and can be incorporated into medical devices which connect to medical connectors, such as a cap or a connector of a syringe. The medical connector can include elements which connect or mate to the corresponding medical connector, such as a male medical connector having elements which mate to a corresponding female medical connector.

(48) As used herein, the term “needleless connector” and “corresponding needleless connector” refer to a male and female connector combination. Where the needleless connector is a male needleless connector, the corresponding needleless connector is a female needleless connector. Likewise, where the needleless connector is a female needleless connector, the corresponding needleless connector is a male needleless connector. The needleless connector can be a cap, a connector of a syringe, a connector of a vascular access device, a connector of a stopcock, a luer

connector with a corresponding open luer connector, a connector having a valve, a connector lacking a valve, a manifold port, stopcock, any conventional medical device having needleless connectors, or a regular open luer connector.

(49) As used herein, the term “Luer connector” refers to a connection collar that is the standard way of attaching syringes, catheters, hubbed needles, IV tubes, etc. to each other. The Luer connector consists of male and female interlocking tubes, slightly tapered to hold together better with even just a simple pressure/twist fit. Luer connectors can optionally include an additional outer rim of threading, allowing them to be more secure. The Luer connector male end is generally associated with a flush syringe and can interlock and connect to the female end located on the vascular access device (VAD). Luer connector also has a distal end that releasably attaches the Luer connector to the hub of a VAD, and a proximal end that releasably attaches the Luer connector to the barrel of a syringe.

(50) As used herein, ISO 80369-7:2016 defines a specification for standard Luer connectors including a 6% taper between the distal end and the proximal end. A male standard luer connector increases from the open distal end to the proximal end. A female standard luer connector decreases from the open proximal end to the distal end. According to ISO 80369-7:2016, a male standard luer connector has an outer cross-sectional diameter measured 0.75 mm from the distal end of the tip of between 3.970 mm and 4.072 mm. The length of the male standard luer taper is between 7.500 mm to 10.500 mm. The outer cross-sectional diameter measured 7.500 mm from the distal end of the tip is between 4.376 mm and 4.476 mm. As used herein, the phrases “male standard luer connector” and “female standard luer connector” shall refer to connectors having the dimensions described in ISO 80369-7, which is hereby incorporated by reference in its entirety.

(51) As would be readily appreciated by skilled artisans in the relevant art, while descriptive terms such as “lock”, “tip”, “hub”, “thread”, “sponge”, “prong”, “protrusion/insert”, “tab”, “slope”, “wall”, “top”, “side”, “bottom” and others are used throughout this specification to facilitate understanding, it is not intended to limit any components that can be used in combinations or individually to implement various aspects of the embodiments of the present disclosure.

(52) The matters exemplified in this description are provided to assist in a comprehensive understanding of exemplary embodiments of the disclosure. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the embodiments described herein can be made without departing from the scope and spirit of the disclosure. Also, descriptions of well-known functions and constructions are omitted for clarity and conciseness.

(53) In one or more exemplary implementation of the embodiments of present disclosure, the medical connector is in the form of a cap having mating elements which connect to a corresponding medical connector, such as threads, a tab or a flange. The cap comprising a housing and an insert. The insert of the cap, connector cap or disinfecting cap includes at least one thread and other features in any and all combinations allowing it to interface with a corresponding thread or plurality of threads of female threaded fittings.

(54) According to further exemplary implementations of the embodiments of the present disclosure, configuration of structural elements making up the insert include a tab protruding from the insert, the tab comprising at least one thread to connect to the corresponding thread or plurality of threads of corresponding medical connectors.

(55) According to still further exemplary implementations of the embodiments of the present disclosure, female threads are sized and have a thread pattern that will engage with a standard ISO594-2 type of male fitting and/or a male threads that are sized and have a thread pattern that will engage with a standard ISO594-2 type of female fitting. An example of an ISO594-2 type of fitting is a Q-style fitting.

(56) According to still further exemplary implementations of the embodiments of the present disclosure, the tab of the insert may bend or elastically deform in order to allow better interference fit compliance with the fittings.

(57) In one or more embodiments, the female medical connector may be selected from the group consisting essentially of needle-free connectors, catheter luer connectors, stopcocks, and hemodialysis connectors. In one or more embodiments, the medical connector is selected from a Q-Syte connector, MaxPlus, MaxPlus Clear, MaxZero, UltraSite, Caresite, InVision-Plus, Safeline, OneLink, V-Link, ClearLink, NeutraClear, Clave, MicroClave, MicroClave Clear, Neutron, NanoClave, Kendall, Nexus, InVision, Vadsite, Bionector, etc.

(58) In one or more embodiments, the male medical connector may be an intravenous tubing end or a stopcock. In some embodiments, the medical connectors described are configured to receive slip connectors such as luer slip connectors. In some embodiments, the medical connectors described include one or more engagement elements such as teeth or c-clips which are configured to engage onto threaded connectors and slip connectors by advancing the threaded connector or slip connector into the medical connector. In some embodiments, the medical connectors described can engage with threaded connectors, such as threaded luer connectors, only by advancement of the threaded connector into the medical connector without requiring the clinician to thread, rotate, or torque the threaded connector or its mating element.

(59) In some embodiments, the teeth or c-clips further comprise a set of tabs protruding from a distal end of the teeth or c-clips. In a fully advanced position, the set of tabs interlock with a thread of a corresponding medical connector. The set of tabs engage the thread of the needleless connector to non-removably lock the corresponding medical connector. In some embodiments, the set of tabs is wider than the spring. In some embodiments, the set of tabs is configured to de-thread from the corresponding thread and jump off the thread path to prevent re-use.

(60) In some embodiments, upon full advancement of a corresponding threaded medical connector the medical connector of embodiments described herein are configured to create an audible click or sound detectable by either the clinician or ancillary detection systems.

(61) Before describing several exemplary embodiments of the disclosure, it is to be understood that the disclosure is not limited to the details of construction or process steps set forth in the following description. The disclosure is capable of other embodiments and of being practiced or being carried out in various ways.

(62) Referring now to the drawings, wherein like reference numerals designate identical or corresponding parts throughout the several views, embodiments of the present disclosure are described as follows.

(63) A first aspect of the present disclosure relates to a housing **110** of a medical connector **100**. As shown in FIGS. **1A** and **1B**, the medical connector is in the form of a cap. In some embodiments, the housing **110** pertains to elements which connect or mate to a corresponding medical connector. The housing **110** of the medical connector **100** is of a partially cylindrical shape which is integral with a radial protrusion **180**, the radial protrusion **180** being in the form of a protruding arc. The angle of the protruding arc ranges from 10 degrees to 350 degrees. The housing **110** includes a cavity defined by a closed end **112**, an open end **114** and a partially cylindrical inner sidewall **120**. The partially cylindrical inner sidewall **120** is integral with a radial sidewall **182**. The radial protrusion **180** includes a first sidewall **181A** and a second sidewall **181B**. The radial sidewall **182** of the housing **110** includes a locking structure described in further detail below.

(64) The closed end **112** is in a distal location and the open end **114** is in a proximal location relative to the closed end **112**. In one or more embodiments, the partially cylindrical inner sidewall **120** has a substantially constant diameter DB. In one or more embodiments, the partially cylindrical inner sidewall **120** can further be outwardly tapered, wherein the taper increases proximally towards the open end **114**. A corresponding medical connector is received through the open end **114** into the cavity **130**.

(65) The housing **110** further includes an outer sidewall **116**. The outer sidewall **116** in the depicted embodiment has partially cylindrical shape with a smooth surface and a chamfer **118**. In one or more embodiments, the chamfer **118** may be rounded. In one or more embodiments the chamfer

118 may extend partially around the outer sidewall **116**. In one or more embodiments, the outer sidewall **116** may have a plurality of axial ribs. In one or more embodiments, the outer sidewall **116** may have a plurality of radial ribs. In one or more embodiments, the outer sidewall **116** may have a grip surface for ease of manipulation by a practitioner. The grip surface may be textured or have a coating.

(66) A second aspect of the present disclosure relates to an insert **150** disposed within the housing **110**. As shown in FIGS. 2A and 2B, insert **150** has a generally discoid body **152** having a distal surface **154**, a proximal surface **156** and a sidewall **158**. From the sidewall **158** extends a locking tab **160**, the locking tab **160** extending from the proximal surface **156** in a proximal direction away from the proximal surface **156** of the discoid body **152**. In one or more embodiments, the discoid body **152** includes an aperture **153** disposed on the distal surface **154** of the discoid body **152**, the aperture **153** extending therethrough. The center of the aperture **153** is concentric with the center of the discoid body **152**. The discoid body **152** has a diameter $D_{sub.DB}$, the diameter $D_{sub.DB}$ being smaller than the diameter D_{is} of the partially cylindrical inner sidewall **120**, defining a gap between the gap between the sidewall **158** and the partially cylindrical inner sidewall **120** of the housing **110**.

(67) In one or more embodiments, the locking tab **160** is a cantilevered prong having a distal portion **162** and a proximal portion **164**. In one or more embodiments, the distal portion **162** is integral with the sidewall **158** of the discoid body **152**. In one or more, the distal portion **162** and the sidewall **158** of the discoid body **152** can be bonded together through ultrasonic welding or solvent resistant biocompatible adhesive. In the preferred embodiment, the distal portion **162** is at an obtuse angle with respect to the proximal surface **156** of the discoid body **152**. In one or more embodiments, the distal portion is at a right angle or at an acute angle with respect to the proximal surface **156** of the discoid body **152**. In one or more embodiments, the locking tab **160**, the distal portion **162** and the proximal portion bend deflect or elastically deform, either in combination or individually. In an exemplary implementation, at least a portion of the locking tab **160** elastically deforms inwardly to cause an interference fit between the locking tab **160** and the corresponding medical connector.

(68) The proximal portion **164** of the locking tab **160** further comprises an outer wall **166** and an inner wall **168**. The outer wall **166** of the locking tab **160** includes a recessed notch **170**. The recessed notch **170** is adjacent to the proximal edge of proximal portion **164** and extends in a distal direction at least partially the length of the proximal portion **164**. In one or more embodiments, the recessed notch **170** is adjacent to the lateral or right edge of the outer wall **166** with respect to the outer wall **166**. In one or more embodiments, the recessed notch **170** is adjacent to the medial edge or left edge of the outer wall **166** with respect to the outer wall **166**.

(69) In one or more embodiments, where the corresponding medical connector is advanced distally into the housing **110** by threading the corresponding medical connector in a rightward or lateral angular direction as per ISO 80369-7:2016 standards, the recessed notch **170** is disposed on the lateral or right edge of the outer wall **166** with respect to the outer wall **166**. In one or more embodiments, where the corresponding medical connector is advanced distally into the housing **110** by threading the corresponding medical connector in a leftward angular direction, the recessed notch **170** is disposed on the medial or left edge of the outer wall **166** with respect to the outer wall **166**. The depicted embodiment of FIGS. 2A and 2B show the recessed notch **170** disposed on the lateral or right edge of the outer wall **166** with respect to the outer wall **166**. In one or more embodiment of the current disclosure, the recessed notch **170** is rectangular. In one or more alternate embodiments of the current disclosure, the recessed notch may also be semi-circular, semi-ovular, triangular, or any other geometric shape.

(70) At least one thread **172** is disposed on the inner wall **168** of the locking tab **160**. In the preferred embodiment, the at least one thread **172** has a helical shape. The helical shape is essentially tapered from one direction to another. In one or more embodiments, the taper decreases

from a rightward or lateral direction to a medial or left direction with respect to the outer wall **166**.

(71) In one or more embodiments, where the corresponding medical connector is advanced distally into the housing **110** by threading the corresponding medical connector in a clockwise, rightward or lateral angular direction as per ISO 80369-7:2016 standards, the taper decreases from a clockwise direction with respect to the outer wall **166**. In one or more embodiments, where the corresponding medical connector is advanced distally into the housing **110** by threading the corresponding medical connector in a counter-clockwise or leftward angular direction, the taper decreases from a counter-clockwise direction with respect to the outer wall **166**. The depicted embodiment of FIGS. **2A** and **2B** show the taper decreasing from a clockwise direction with respect to the outer wall **166**.

(72) In one or more embodiments, the corresponding medical connector is first partially advanced distally into the housing **110** until a luer tip of the corresponding medical connector abuts the proximal surface **154** of the discoid body **152**. In one or more embodiments, the corresponding medical connector is first partially advanced distally into the housing **110** until threads of the corresponding medical connector abut the at least one thread **172**. In one or more embodiments, advancement of the corresponding medical connector into the housing **110** causes advancement of the discoid body **152** into the housing body **110**. The corresponding medical connector can then be rotated which causes locking and final advancement of the discoid body **152** into the housing **110**.

(73) A third aspect of the present disclosure, as shown in FIG. **3**, relates to the locking structure disposed within the cavity **130** of housing **110**, the locking structure having features which are disposed or integral with the radial sidewall **182** of the housing **110**. The locking structure includes an outwardly sloped surface **184** which slopes outwardly counter-clockwise from a first sidewall **181A** to a second sidewall **181B**. In the depicted embodiment, the outwardly sloped surface **184** extends at least partially the length of the arc of the radial sidewall **182**. In one or more embodiments, the outwardly sloped surface **184** extends the entire length of the arc of the radial sidewall **182**. From a lateral portion of the outwardly sloped surface **184** extends a sloped tab **186**. The sloped tab **186** slopes outwardly clockwise. The sloped tab **186** includes a ledge **188** formed by a wall at a substantially right angle with respect to the radial sidewall **182**. In one or more embodiments, adjacent to the ledge **188** is a proximally sloped surface **190**, the proximally sloped surface **190** slopes inwardly with respect to the radial sidewall **182** from a distal position to a proximal position.

(74) As shown in FIG. **3**, a portion of the radial sidewall **182** adjacent to the first sidewall **181A** is substantially smooth with no protrusions or indentations, and portion of the radial sidewall **182** adjacent to the second sidewall **181B** includes the outwardly sloped surface **184**, sloped tab **186**, the ledge **188** and the proximally sloped surface **190**. As used herein, a first position **192** is defined by the portion of the radial sidewall **182** adjacent to the first sidewall **181A** and a locking position **194** is defined by the sloped tab **186** and the ledge **188**. As shown in FIG. **4**, when insert **150** is advanced distally into the cavity **130** of the housing **110**, the locking tab **160** is disposed in the first position **192**. In one or more embodiments, advancement of the insert **150** into the cavity **130** causes the locking tab to elastically deform outwardly with respect to the radial sidewall **182**. With the insert **150** fully advanced into the cavity **130**, the insert **150** can rotate freely along the arc of the radial sidewall **182**. As the insert **150** approaches the locking position **194**, the outwardly sloped surface **184** further elastically deforms the locking tab **160** until the recessed notch **170** passes the ledge **188** of the radial sidewall **182**. When the notch **170** has passed the ledge **188**, the notch nonreleasably engages the ledge **188**, thereby preventing clockwise movement of the locking tab **160**.

(75) In some embodiments, when the notch **170** has passed the ledge **188**, an audible click or sound is created and is detectable by the clinician or ancillary detection systems to indicate that the insert **150** and thus the needleless connector has reached a fully locked position.

(76) FIGS. **5** and **6** illustrate perspective views of the insert **150** in the first position **192** and the locking position **194**, respectively. Likewise, FIGS. **7** and **8** illustrate a top view of the insert **150** in

the first position **192** and the locking position **194**, respectively. As depicted in FIGS. 7 and 8, the thickness of the radial sidewall **182** gradually increases from a value of T.sub.1 to T.sub.2 due to the outwardly sloped surface **184**.

(77) FIG. 9 depicts a partially cross-sectional view of the cavity **130** wherein the insert **150** is fully advanced into the cavity **130** and is in the first position **192**. For illustration purposes, the distal surface **154** of the discoid body **152** directly abuts the inner top surface **122** of the housing **110**, however, in one or more embodiments, an absorbent material **199** containing disinfectant is disposed between the distal surface **154** of the discoid body **152** and the inner top surface **122** of the housing **110**. Advancement of a corresponding medical connector into cavity **130** compresses the absorbent material **199** thereby releasing disinfectant. In one or more embodiments, the closed end **112** includes a concentric retention tab **124** which mechanically locks onto the aperture **153** of the discoid body **152**, thereby preventing removal of the insert **150**. In one or more embodiments, the concentric retention tab comprises a distal cylindrical shape and a proximal cylindrical shape, the proximal cylindrical shape having a greater diameter than the distal cylindrical shape. In one or more embodiments, the diameter of the proximal cylindrical shape is greater than the diameter of the aperture **153** of the discoid body **152**, creating a snap-fit connection between the retention tab **124** and the aperture **153** of the discoid body **152**.

(78) In one or more embodiments, the retention tab **124** is long enough to allow for placement of a cylindrical absorbent material disk between the discoid body **152** and the inner top surface **122** of the housing **110**, the cylindrical absorbent material disk having an aperture extending therethrough. The total length of the retention tab **124** is equal or slightly greater than the thickness of the discoid body **152** and the thickness of the cylindrical absorbent material disk, whereby the cylindrical absorbent material disk is in an uncompressed state. Insertion of a connector compresses the cylindrical absorbent material disk, thereby releasing disinfectant into the cavity **130**.

(79) As shown in FIGS. 11 and 12, the corresponding medical connector is a female needleless connector **80**.

(80) As shown in FIG. 11, in one or more embodiments, the absorbent material **199** is placed in the cavity **130**, the absorbent material **199** abutting the proximal surface **156** of the discoid body **152**. Insertion of a female needleless connector **80** compresses the absorbent material **199**, thereby releasing disinfectant into the cavity **130**. At least one thread **82** of the connector **80** engages at the at least one thread **172** of the insert **150**. The at least one thread **82** is disposed on a hub **84** of the female needleless connector **80**.

(81) As shown in FIG. 12, in operation, a female connector **80** having at least one thread **82** engages the at least one thread **172** of the insert **150**, thereby causing advancement of the female connector **80** and the insert **150** into the housing **110**. As the locking tab **160** nonreleasably locks into the second position and the absorbent material **199** (not shown for purposes of clarity) is compressed, disinfectant is released into the cavity **130**. In embodiments where the absorbent material **199** is disposed against the closed distal end **112** of the housing **110**, the released disinfectant evacuates through the gap **123** created between the discoid body **152** and the partially cylindrical inner sidewall **120**. After disinfection is complete, the female connector **80** is unthreaded in the opposite direction, allowing for release of the female connector **80** while the ledge **188**, engaged to the recessed notch **170**, prevents the removal of the insert **150**. FIG. 10 depicts the elastic deformation of the locking tab **160** in the first position **192** and the locking position **194**, respectively. The deformation causes the at least one thread **172** to further securely engage the at least one thread of the female connector **80**. For purposes of illustration, the locking tab **160** in the first position **192** is depicted directly above the locking tab **160** in the locking position. Deformation of the locking tab **160** is illustrated relative to the line AA, with the locking tab **160** deforming inward.

(82) A second embodiment of the present disclosure relates to a housing **210** of syringe **200**. As shown in FIGS. 13A through 13D, the housing **210** protrudes in a distal direction from a distal wall

212 of a syringe barrel **213** of the syringe **200**. As shown in **13A**, the housing **210** of the second embodiment is configured as a needleless connector able to receive a male luer fitting commonly associated with VADs. The housing **210** includes a cavity **230** defined by the distal wall **212** of the syringe barrel **213**, an open end **214** opposite the distal wall **212** and a partially cylindrical sidewall **216** extending from the distal wall **212** to the open end **214**. A tapered hub **232** is disposed within the cavity **230**, the tapered hub **232** extending in a distal direction from the distal wall **212** of the syringe barrel **213**. The tapered hub **232** is configured to interdigitate with a corresponding cavity of a housing of the VAD (not shown). In some embodiments, the tapered hub **232** is configured to create a fluid-tight seal with the housing of the VAD. In some embodiments, the tapered hub **232** is configured to create an interference fit with the housing of the VAD.

(83) The housing **210** and the partially cylindrical sidewall **216** are of a partially cylindrical shape, the partially cylindrical sidewall **216** having an integral radial protrusion **280** extending laterally from the housing **210**. The radial protrusion **280** defines a radial sidewall **282**, the radial sidewall **282** including a locking structure described in further detail below. The radial protrusion **280** and the radial sidewall **282** are in the shape of a laterally protruding arc. The angle of the protruding arc ranges from 10 degrees to 350 degrees.

(84) In one or more embodiments, the partially cylindrical inner sidewall **216** has a substantially constant diameter. In one or more embodiments, the partially cylindrical inner sidewall **216** can include an outward taper, wherein the taper increases distally towards the open end **214**.

(85) The housing **210** further includes an outer sidewall **216**. The outer sidewall **216** in the depicted embodiment has partially cylindrical shape which includes a smooth surface and a chamfer **218**. In one or more embodiments, the chamfer **218** may be rounded. In one or more embodiments the chamfer **218** may extend partially around the distal end of the outer sidewall **216**.

(86) The locking structure, as best shown in FIGS. **13B** through **13D**, is disposed within the cavity **230** of housing **210**, the locking structure having features which are integral with the radial sidewall **282** of the housing **210**. The locking structure includes an outwardly sloped surface **284** which slopes outwardly from a medial or leftward position to a lateral or rightward position. In the depicted embodiment, the outwardly sloped surface **284** extends at least partially the length of the arc of the radial sidewall **282**. In one or more embodiments, the outwardly sloped surface **284** extends the entire length of the arc of the radial sidewall **282**. From a lateral portion of the outwardly sloped surface **284** extends a sloped tab **286**. The sloped tab **286** slopes outwardly from a lateral or rightward position to a medial or leftward position. The sloped tab **286** includes a ledge **288** formed by a wall at a substantially right angle with respect to the radial sidewall **282**. In one or more embodiments, adjacent to the ledge **288** is a proximally sloped surface **290**, the proximally sloped surface **290** slopes inwardly with respect to the radial sidewall **282** from a distal position to a proximal position.

(87) As best shown in FIGS. **13C** and **13D**, a medial or leftward portion of the radial sidewall **282** is substantially smooth with no protrusions or indentations, and a lateral or rightward portion of the radial sidewall **282** includes the outwardly sloped surface **284**, sloped tab **286**, the ledge **288** and the proximally sloped surface **290**. As used herein, a first position **292** is defined by the medial or leftward portion of the radial sidewall **282** and a locking position **294** is defined by the sloped tab **286** and the ledge **288**.

(88) As shown in FIGS. **14A** and **14B**, insert **250** has a generally discoid body **252** having a proximal surface **254**, a distal surface **256** and a sidewall **258**. From the sidewall **258** extends a locking tab **260**, the locking tab **260** extending from the distal surface **256** in a distal direction away from the distal surface **256** of the discoid body **252**. In one or more embodiments, the discoid body **252** includes an aperture **253** disposed on the proximal surface **254** of the discoid body **252**, the aperture **253** extending therethrough. The center of the aperture **253** is concentric with the center of the discoid body **252**. The discoid body **252** has a diameter $D_{sub.DB}$, the diameter $D_{sub.DB}$ being smaller than the diameter D_{is} of the partially cylindrical inner sidewall **220**, defining a gap

between the gap between the sidewall **258** and the partially cylindrical inner sidewall **220** of the housing **210**.

(89) In one or more embodiments, the locking tab **260** is configured as a cantilevered prong having a proximal portion **262** and a distal portion **264**. In one or more embodiments, the proximal portion **262** is integral with the sidewall **258** of the discoid body **252**. In one or more, the proximal portion **262** and the sidewall **258** of the discoid body **252** can be bonded together through ultrasonic welding or solvent resistant biocompatible adhesive. In the preferred embodiment, the proximal portion **262** is at an obtuse angle with respect to the distal surface **256** of the discoid body **252**. In one or more embodiments, the proximal portion **262** is at a right angle or at an acute angle with respect to the distal surface **256** of the discoid body **252**. In one or more embodiments, the locking tab **260**, the proximal portion **262** and the distal portion bend deflect or elastically deform, either in combination or individually. In an exemplary implementation, at least a portion of the locking tab **260** elastically deforms inwardly to cause an interference fit between the locking tab **260** and the corresponding medical connector.

(90) The proximal portion **264** of the locking tab **260** further comprises an outer wall **266** and an inner wall **268**. The outer wall **266** of the locking tab **260** includes a recessed notch **270**. The recessed notch **270** is adjacent to the distal edge of the distal portion **264** and extends in a proximal direction at least partially the length of the distal portion **264**. In one or more embodiments, the recessed notch **270** is adjacent to the lateral or right edge of the outer wall **266** with respect to the outer wall **266**. In one or more embodiments, the recessed notch **270** is adjacent to the medial edge or left edge of the outer wall **266** with respect to the outer wall **266**.

(91) As shown in FIGS. **15** and **16**, in one or more embodiments, where the VAD is advanced proximally into the housing **210** by threading the VAD in a leftward angular direction as per ISO 80369-7:2016 standards, the recessed notch **270** is disposed on the medial or left edge of the outer wall **266** with respect to the outer wall **266**. In one or more embodiments, where the VAD is advanced distally into the housing **210** by threading the VAD in a rightward angular direction, the recessed notch **270** is disposed on the medial or left edge of the outer wall **266** with respect to the outer wall **266**. Referring back to the depicted embodiment of FIGS. **14A** and **14B** show the recessed notch **270** disposed on the lateral or right edge of the outer wall **266** with respect to the outer wall **266**. In one or more embodiment of the current disclosure, the recessed notch **270** is rectangular. In one or more alternate embodiments of the current disclosure, the recessed notch **270** may also be semi-circular, semi-ovular, triangular, or any other geometric shape.

(92) At least one thread **272** is disposed on the inner wall **268** of the locking tab **260**. In the preferred embodiment, the at least one thread **272** has a helical shape. The helical shape is essentially tapered from one direction to another. In one or more embodiments, the taper decreases from a rightward or lateral direction to a medial or left direction with respect to the outer wall **266**.

(93) In one or more embodiments, where the VAD is advanced distally into the housing **210** by threading the VAD clockwise, rightward or lateral angular direction as per ISO 80369-7:2016 standards, the taper decreases from a leftward or medial direction with respect to the outer wall **266**. In one or more embodiments, where the VAD is advanced proximally into the housing **210** by threading the VAD connector in a counter-clockwise or leftward angular direction, the taper decreases from a rightward or lateral direction with respect to the outer wall **266**. The depicted embodiment of FIGS. **14A** and **14B** show the taper decreasing from a leftward or medial direction with respect to the outer wall **266**.

(94) As previously described with respect to the first embodiment, and as shown in FIGS. **15** and **16**, when insert **250** is advanced proximally into the cavity **230** of the housing **210**, the locking tab **260** is disposed in the first position **292**. In one or more embodiments, advancement of the insert **250** into the cavity **230** causes the locking tab to elastically deform outwardly with respect to the radial sidewall **282**. With the insert **250** fully advanced into the cavity **230**, the insert **250** can rotate freely along the arc of the radial sidewall **282**. As the insert **250** rotationally approaches the locking

position **294**, the outwardly sloped surface **284** further elastically deforms the locking tab **260** inward until the recessed notch **270** passes the ledge **288** of the radial sidewall **282**. When the notch **270** has passed the ledge **288**, the notch non-releasably engages the ledge **288**, thereby preventing medial or leftward movement of the locking tab **260**.

(95) In some embodiments, when the notch **270** has passed the ledge **288**, an audible click or sound is created and is detectable by the clinician or ancillary detection systems to indicate that the insert **250** and thus the medical connector has reached a fully locked position.

(96) As best shown in FIG. **16**, the proximal surface **254** of the insert **250** abuts the distal wall **212** of a syringe barrel **213** of the syringe **200** in the fully advanced position. In one or more embodiments, a circular protrusion **234** is disposed on the tapered hub **232**. The circular protrusion **234** is configured to non-removably lock the insert **250** in the fully advanced position. The circular protrusion **234** is located a distance from the distal wall **212** of a syringe barrel **213** and the distance is configured to be equal to or slightly larger than the thickness of the discoid body of the insert **250**. In one or more embodiments, the circular protrusion **234** has a substantially triangular cross section, the triangular cross section having a proximal right angled surface with respect to the tapered hub **232** and a distal acute angled surface with the tapered hub **232**. The distal acute angled surface of the circular protrusion **234** is configured to create slight deformation of the insert **250** as the insert **250** comes into contact with the distal acute angled surface of the circular protrusion **234** as the insert **250** is advanced proximally. The proximal right surface of the circular protrusion **234** is configured to non-removably secure the insert **250** when the insert **250** completely transverses over the triangular cross section of the circular protrusion **234**.

(97) A third embodiment of the present disclosure relates to a housing **310** of a medical connector **300**. FIGS. **17**, **18A** and **18B** illustrate the medical connector **300** in an initial, un-activated state and FIGS. **19** and **20** illustrate the medical connector **300** in a final, activated state where a corresponding medical connector (not shown) has been fully advanced into a cavity **330** the housing **310**.

(98) As shown in FIG. **17** through **18B**, the medical connector **300** comprises a substantially cylindrical housing **310** having a distal wall **312**, a proximal open end **314**, a sidewall **316** extending between the distal wall **312** to the open end **314** and a cavity **330**. The cavity **330** extends from the open end **314** to the distal wall **312**. In one or more embodiments, an absorbent material **399** in the form of a disk is disposed within the cavity **330**, abutting an inner distal surface **322** of the distal wall **312**. An inner sidewall surface **318** of the sidewall **316** includes a channel **324** extending from the distal wall **312** to the open end **314**. On the inner sidewall surface **318**, the channel **324** has a substantially rectangular profile, while the channel **324** extends a depth into the sidewall **316**. The depth of the channel **324** is configured to at least partially interdigitate with a spring **350** as discussed in further detail below.

(99) The housing further includes a plurality of threads **320** disposed on the inner sidewall surface **318**, however the plurality of threads **320** are not disposed on the channel **324**. The plurality of threads **320** are configured to thread with a corresponding thread **82** of a female needleless connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**).

(100) As shown in FIGS. **17** though **18B**, and as best shown in FIG. **18B**, the spring **350** is configured as a leaf spring having a rectangular cross-section and an arc **352**. In one or more embodiments, the arc **352** is pointed, forming a ramp. The arc **352** is between a distal portion **354** and a proximal portion **356**. The distal portion **354** is non-removably attached to the channel **324**, while the proximal portion **356** is not attached to the channel **324** and may freely deflect. In operation, the proximal portion **356** abuts the channel **324** in the initial state, as shown in FIGS. **17-18B**. As the needleless connector **80** is advanced into the cavity **330**, the least one thread **82** depresses the arc **352** of the spring **350** into the channel **324**. Depression of the arc **352** cause the proximal portion **354** of the spring **350** to deflect outward, away from the channel **324**. In the fully advanced position as shown in FIGS. **19** and **20**, a proximal end **355** of the proximal portion **354** of

the spring **350** engages a lower segment of the least one thread **82** of the needleless connector **80**, thereby locking the needleless connector **80** within the cavity **330** in a threaded fit and an interference fit. In one or more embodiments, the needleless connector **80** is removably locked within the cavity **330**. In one or more embodiments, the needleless connector **80** is non-removably locked within the cavity **330** by means of configurations of the spring **350** including, but not limited to, utilizing a stiffer spring.

(101) In embodiments where the needleless connector **80** is removable from the cavity **330**, the spring **350** does not return to the initial state, thereby preventing re-use of the housing **310**.

(102) In some embodiments, when the needleless connector **80** is fully advanced into the cavity **330** and the spring **350** engages corresponding thread **82**, an audible click or sound is created and is detectable by the clinician or ancillary detection systems to indicate that the needleless connector **80** is fully advanced into the cavity **330**.

(103) In some embodiments, the proximal end **355** of the spring **350** further comprises a set of tabs **353** protruding from the proximal end **355**. In some embodiments, the set of tabs **353** are in the form of a C-clip. In the fully advanced position, the set of tabs **353** interlock with a thread of the corresponding needleless connector **80**. The set of tabs **353** engage the thread of the needleless connector **80** to non-removably lock the corresponding needleless connector **80**. In some embodiments, the set of tabs **353** is wider than the spring **350**. In some embodiments, the set of tabs **353** is configured to de-thread from the corresponding thread **82** and jump off the thread path to prevent re-use.

(104) A fourth embodiment of the present disclosure relates to a housing **410** of a medical connector **400**. FIGS. **21A** and **21B** illustrate the medical connector **400** in an initial, un-activated state and FIG. **22** illustrates the medical connector **400** in a final, activated state where a needleless connector (not shown) has been fully advanced into a cavity **430** the housing **410**.

(105) As shown in FIGS. **21A** and **21B**, the medical connector **400** comprises a substantially cylindrical housing **410** having a distal wall **412**, a proximal open end **414**, a sidewall **416** extending between the distal wall **412** to the open end **414** and a cavity **430**. The cavity **430** extends from the open end **414** to the distal wall **412**. A cupped spring **350** (also known in the art as a Belleville spring) is disposed within the cavity **330**, wherein an open distal end **352** of the cupped spring **350** abuts an inner distal surface **422** of the distal wall **412** of the housing **410**.

(106) The cupped spring **450** comprises a frusto-conical shaped disk body **452** having at least two prongs **456** extending from a proximal edge **454** of the disk body **452**. While the dimensions of the frusto-conical shape of the disk body **452** determine the spring constant and spring characteristics generally, the at least two prongs **456** may have different spring constant and spring characteristics in relation to the disk body **452**. In one or more embodiments, the at least two prongs **456** have a stiffer spring constant and spring characteristics in relation to the disk body **452**. In one or more embodiments, the at least two prongs **456** are rigid.

(107) The at least two prongs **456** extend from a proximal edge **454** of the disc body **452** in a proximal direction. Each of the at least two prongs **456** comprise a proximal portion **458** and a distal portion **460** adjacent to the proximal portion **458**. The distal portion **460** forms a medial hook **462** extending toward a center of the disk body **452**. The medial hook **562** comprises a medial edge **464** configured to engage with a corresponding thread **82** of a corresponding needleless luer connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**). In one or more embodiments, an absorbent material **498** in the form of a disk is disposed within the cavity **430**. The absorbent material **498** abuts a proximal surface of the disk body **452**.

(108) FIGS. **21A** and **21B** illustrate the medical connector **400** in an initial, un-activated state and FIGS. **22A** through **22C** illustrate the medical connector **400** in a final, activated state where a needleless connector (not shown) has been fully advanced into a cavity **430** the housing **410**. In operation, the hub **84** of the corresponding needleless connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**) is advanced into the cavity **430** of the housing **410**. As

the hub **84** comes into contact and advances against the disk body **452**, the disk body **452** deforms from the initial state of FIGS. **21A** and **21B** to the final state of FIG. **22A** through **22C**. The disk body **452** deforms inward, pushing the proximal edge **454** of the disk body **452** in a proximal direction, thereby causing the least two prongs **456** to advance in a proximal direction, whereby the medial hook **462** is further advanced in a lateral direction. In the final state, the medial hook **462** latches onto the at least one thread **82**, thereby locking the needle connector **80** into the housing **410** due to the spring force. In the fully advanced position as shown in FIGS. **19** and **20**, a proximal end **355** of the proximal portion **354** of the spring **350** engages a lower segment of the least one thread **82** of the needleless connector **80**, thereby locking the needleless connector **80** within the cavity **330** in a threaded fit and an interference fit. In one or more embodiments, the needleless connector **80** is removably locked within the cavity **330**. In one or more embodiments, the needleless connector **80** is non-removably locked within the cavity **330** by means of configurations of the spring **350** including, but not limited to, utilizing a stiffer spring. The medial hook **456** in the fully advanced position creates a threaded fit and an interference fit with the at least one thread **82** of the needleless connector **80**. In one or more embodiments, the needleless connector **80** is removably locked within the cavity **430**. In one or more embodiments, the needleless connector **430** is non-removably locked within the cavity **430** by means of configurations of the spring **450** including, but not limited to, utilizing a stiffer spring.

(109) In embodiments where the needleless connector **80** is removed from the cavity **330**, the spring **450** does not return to the initial state, thereby preventing re-use of the housing **310**.

(110) As shown in FIG. **22A** through **22C**, in some embodiments, when the needleless connector **80** is fully advanced into the cavity **430** and the spring **450** engages corresponding thread **82**, an audible click or sound is created and is detectable by the clinician or ancillary detection systems to indicate that the needleless connector **80** is fully advanced into the cavity **430**.

(111) As shown in **22A**, in some embodiments, the medial hook **462** further comprises a set of tabs **453** protruding from the medial hook **462**. In some embodiments, the set of tabs **453** are in the form of a C-clip. In the fully advanced position, the set of tabs **453** interlock with a thread of the corresponding needleless connector **80**. The set of tabs **653** engage the thread of the needleless connector **80** to non-removably lock the corresponding needleless connector **80**. In some embodiments, the set of tabs **353** is wider than the spring **350**. In some embodiments, the set of tabs **353** is configured to de-thread from the corresponding thread **82** and jump off the thread path to prevent re-use.

(112) As shown in **22B** and **22C**, in some embodiments, the medial edge **464** is elongated in a lateral and medial direction. In some embodiments, the medial edge **464** is configured as a c-clip. In the fully advanced position, the medial edge **464** interlocks with a thread of the corresponding needleless connector **80**. The elongated medial edge **464** engages the thread of the needleless connector **80** to non-removably lock the corresponding needleless connector **80**. In some embodiments, the medial edge **464** is wider than the spring **350**. In some embodiments, the medial edge **464** is configured to de-thread from the corresponding thread **82** and jump off the thread path to prevent re-use.

(113) A fifth embodiment of the present disclosure relates to a housing **510** of a medical connector **500**. FIGS. **23A** and **23B** illustrate the medical connector **500** in an initial, un-activated state and FIGS. **24A** and **24B** illustrate the medical connector **500** in a final, activated state where a needleless connector (not shown) has been fully advanced into a cavity **530** the housing **510**. In the final state, the needleless connector is removable however the medical connector **500** has integrated features preventing re-use of the medical connector **500**, as explained in further detail below.

(114) The medical connector **500** comprises a substantially cylindrical housing **510** having a distal wall **512**, a proximal open end **514**, a sidewall **516** extending between the distal wall **512** to the open end **514** and a cavity **530**. The cavity **530** extends from the open end **514** to the distal wall **512**. On an inner sidewall **518** of the cavity **530** at least one helical thread **550** is disposed, the

helical thread **550** extending at least partially the length of the inner sidewall **518**.

(115) The at least one helical thread **550** comprises a distal portion **552** which is unitarily formed onto the inner sidewall **518** and a frangible portion **554** proximal to the distal portion configured to detach and cross-thread upon threading and advancing a corresponding thread **82** of a corresponding needleless luer connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**) into the cavity. Upon removal of the luer connector **80**, the frangible portion **554** does not return to the initial state, thereby preventing re-use of the housing **510**.

(116) In one or more embodiments, the frangible portion **554** in the initial state as shown in FIG. **23B** does not follow the thread pattern of the at least one helical thread **550**. In one or more embodiments, as shown in FIG. **23B**, the frangible portion **554** has a greater approach angle $\emptyset$ than the approach angle ∂ of the distal portion **552** of the at least one helical thread **550**. The greater approach angle $\emptyset$ is configured to cause deformation of the frangible portion **554**. Deformation of the frangible portion **554** prevents re-use of the needleless connector **500** due to thread misalignment. Removal of the corresponding needleless luer connector **80** does not return the frangible portion **554** to the original angle $\emptyset$ of the frangible portion **554**, and thus the medical connector **500** cannot be reused. Specifically, as shown in FIG. **24B**, insertion and subsequent removal of the corresponding needleless luer connector **80** causes frangible portion **554** to have a near-zero approach angle, whereby the frangible portion **554** is substantially parallel to the inner distal surface **522** of the housing **510**.

(117) In one or more embodiments, and as specifically shown in FIG. **23B**, the frangible portion **554** extends a quarter turn. In one or more embodiments the frangible portion **554** extends a half turn. In one or more embodiments the frangible portion **554** extends a three quarter turn.

(118) In one or more embodiments, absorbent material **599** is placed in the cavity **530**, the absorbent material **599** abutting an inner distal surface **522** of the housing **510**. Insertion of a corresponding needleless connector **80** compresses the absorbent material **599**, thereby releasing disinfectant into the cavity **530**.

(119) A sixth embodiment of the present disclosure relates to an insert **650** disposed within a housing **610** of a medical connector **600**. FIGS. **25A** and **25B** illustrate embodiments of the insert **650** and FIG. **26** illustrates the medical connector **600** in an initial, un-activated state. In a final, activated state, as described in further detail below, a needleless connector (not shown) is fully advanced into a cavity **630** the housing **610**.

(120) As shown in FIGS. **25A** and **25B**, insert **650** has a generally discoid body **652** having a proximal surface **654** and a distal surface **656**. From the proximal surface **654** extend at least two locking tabs **660**, the at least two locking tabs **660** extending from the distal surface **656** in a distal direction away from the distal surface **656** of the discoid body **652**. Each of the at least two locking tabs **660** comprise a hooked proximal end **662**. The hooked proximal end **662** is configured to interlock with corresponding thread **82** of a corresponding needleless luer connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**) upon threading and advancing the corresponding thread of a corresponding needleless luer connector into the cavity.

(121) In one or more embodiments, the discoid body **652** further includes an aperture **653** disposed on the proximal surface **654** of the discoid body **652**, the aperture **653** extending therethrough. The center of the aperture **653** is concentric with the center of the discoid body **652**. As shown in FIG. **26** and as explained in further detail below, the aperture **653** is configured to non-removably interlock with a hooked protrusion **640** of the housing **610**.

(122) In one or more embodiments, the discoid body **652** further includes a plurality of ridges **672** disposed on a sidewall **670** of the discoid body **652**. The plurality of ridges **672** extend into the discoid body **652** in a medial direction from the sidewall **670** of the discoid body **652**. As shown in FIG. **26** and as explained in further detail below, the plurality of ridges **672** are configured to interdigitate with at least one tooth **634** of the housing **610**.

(123) In one or more embodiments, as shown in FIG. **25B**, the discoid body **652** further includes a

living hinge **676** disposed across the discoid body **652**. As shown in FIG. **26** the living hinge **676** is configured to bend the discoid body **652**. Bending of the discoid body **652** causes the least two locking tabs **660** to threads of a medical connector.

(124) As shown in FIG. **26**, the medical connector **600** comprises a substantially cylindrical housing **610** having a distal wall **612**, a proximal open end **614**, a sidewall **616** extending between the distal wall **612** to the open end **614** and a cavity **630**. The cavity **630** extends from the open end **614** to the distal wall **612**. In one or more embodiments, an absorbent material (not shown) in the form of a disk is disposed within the cavity **630**, abutting an inner distal surface **622** of the distal wall **612**.

(125) In one or more embodiments, a hooked protrusion **640** extends concentrically from the inner distal surface **622** of the housing **610**. The hooked protrusion **640** is configured to non-removably interlock with the aperture **653** of the discoid body **652** upon full advancement of the discoid body **652** into the cavity **630** of the housing **610**, thereby preventing re-use of the medical connector **600**.

(126) In one or more embodiments, at least one tooth **634** extends medially into the cavity **630** from an inner sidewall **618**. The at least one tooth **634** is positioned a distance from the inner distal surface **622** of the housing **610**. In one or more embodiments, the at least one tooth **634** is positioned substantially parallel to a proximal end **641** of the hooked protrusion **640**. The at least one tooth **634** and the plurality of ridges **672** of the discoid body **652** are configured to interdigitate with one another, wherein the at least one tooth **634** and the plurality of ridges **672** have substantially corresponding shapes. In one or more embodiments, the at least one tooth **634** has a substantially triangular shape and the plurality of ridges **672** have a corresponding triangular profile. In one or more embodiments, at least one ledge **637** is disposed on the inner distal surface **622** of the housing **610**.

(127) As shown in FIG. **26**, the medical connector **600** is in an initial position. Upon full advancement of the corresponding needleless luer connector **80**, the hooked protrusion **640** is received within the aperture **653** of the discoid body **652**. However, full advancement is inhibited by misalignment of the plurality of ridges **672** and the at least one tooth **634**. Thus, full advancement can occur when the plurality of ridges **672** align with the at least one tooth **634**. In the final state, the insert **650** is non-removably locked due to the hooked protrusion **640** being received within the aperture **653** of the discoid body **652**.

(128) In one or more embodiments, absorbent material (not shown) is placed in the cavity **630**, the absorbent material abutting the inner distal surface **622** of the housing **610**. Insertion of a corresponding needleless connector **80** compresses the absorbent material, thereby releasing disinfectant into the cavity **630**.

(129) As shown in FIG. **27**, a seventh embodiment of the present disclosure relates to a medical connector **700** comprising of a housing **710** and an insert **750** disposed within the housing **710**. As explained in further detail below, the insert **750** is of a resilient and flexible material and comprises at least two living hinges **760** to grip onto a thread **82** of a corresponding needleless luer connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**).

(130) The housing **710** has a substantially cylindrical shape and comprises a distal wall **712**, a proximal open end **714**, a sidewall **716** extending between the distal wall **712** to the open end **714** and a cavity **730**. The cavity **730** extends from the open end **714** to the distal end **712**. In one or more embodiments, an absorbent material (not shown) in the form of a disk is disposed within the cavity **730**, abutting an inner distal surface **722** of the housing **710**. In one or more embodiments, the distal end **712** of the housing **710** is in the shape of a medially facing hook.

(131) The insert **750** comprises a C-shaped body **752** having a distal end **754** in the form of an arc and an open proximal end **756**. From the distal end **754** extend the two living hinges **760**. The two living hinges **760** are in the form of cantilevered prongs. As the corresponding needleless luer connector **80** is advanced into the cavity **730**, the C-shaped body **752**, including the distal end **754** and the living hinges **760**, deflect. The resilient material of the insert **750** causes the corresponding

needleless luer connector **80** to be retained by the open proximal end **756** of the insert **750**. The two living hinges **760** provide a countering force against the C-shaped body **752** of the insert.

(132) In one or more embodiments, absorbent material (not shown) is placed in the cavity **730**, the absorbent material abutting an inner distal surface **722** of the housing **510**. Insertion of a corresponding needleless connector **80** compresses the absorbent material, thereby releasing disinfectant into the cavity **730**.

(133) As shown in FIGS. **28A** and **28B**, an eighth embodiment of the present disclosure relates to a medical connector **800** comprising of a housing **810** and an insert **850** disposed within the housing **810**. As explained in further detail below, the insert **850** is of a resilient and flexible material and at least two living hinges **860** to grip onto a thread **82** of a corresponding needleless luer connector **80** of one of the previous embodiments (as seen in FIGS. **11** and **12**).

(134) The housing **810** has a substantially cylindrical shape and comprises a distal wall **812**, a proximal open end **814**, a sidewall **816** extending between the distal wall **812** to the open end **814** and a cavity **830**. The cavity **830** extends from the open end **814** to the distal wall **812**. In one or more embodiments, an absorbent material (not shown) in the form of a disk is disposed within the cavity **830**, abutting an inner distal surface **822** of the distal wall **812**. In one or more embodiments, the distal wall **812** further protrudes in a medial direction.

(135) In one or more embodiments, a protrusion **840** extends concentrically from the inner distal surface **822** of the housing **810**. The protrusion **840** is configured to non-removably interlock with an aperture **853** of the C-shaped body **852** upon full advancement of the C-shaped body **852** into the cavity **830** of the housing **810**, thereby preventing re-use of the needleless connector **800**. The protrusion **840** is configured to aid in alignment and advancement of the insert **850** into the cavity **830** of the housing **810**.

(136) In one or more embodiments, a medial wall **823** is positioned a distance from the inner distal surface **822** of the housing **810**. The medial wall **823** further includes an aperture **824** configured to receive a distal portion **854** of the insert **850** explained in further detail below.

(137) The insert **850** comprises a C-shaped body **852** having a distal portion **854** in the form of an arc and an open proximal end **856**. Tangential to the distal portion **854** extend at least two living hinges **860**. The two living hinges **860** are in the form of cantilevered prongs. As the corresponding needleless luer connector **80** is advanced into the cavity **830**, the C-shaped body **852**, including the distal portion **854** and the at least two living hinges **860**, deflect. The resilient material of the insert **850** causes the corresponding needleless luer connector **80** to be retained by the open proximal end **856** of the insert **850**. The two living hinges **860** provide a countering force against the C-shaped body **852** of the insert.

(138) In one or more embodiments, the C-shaped body **852** further includes a stem **857** having a cylindrical profile extending in a distal direction from the distal portion **854**. From the stem extends a bulbous protrusion **859**. The C-shaped body **852**, stem **857** and the bulbous protrusion **859** form a unitary body through which an aperture **861** extends. The aperture **861** is configured to receive the protrusion **840** of the housing **810** while the stem **857** and the bulbous protrusion **859** are configured to interlock with the aperture **824** of the housing **810**.

(139) As the corresponding needleless luer connector **80** is advanced into the cavity **830**, the C-shaped body **852**, including the distal portion **854** and the living hinges **860**, deflect. The resilient material of the insert **850** causes the corresponding needleless luer connector **80** to be retained by the open proximal end **856** of the insert **850**. The two living hinges **860** provide a countering force against the C-shaped body **852** of the insert.

(140) In one or more embodiments, absorbent material (not shown) is placed in the cavity **830**, the absorbent material abutting the medial wall **823** of the housing **510**. Insertion of a corresponding needleless connector **80** compresses the absorbent material, thereby releasing disinfectant into the cavity **830**.

(141) In one or more embodiments, the corresponding medical connector may be selected from the

group consisting essentially of needle-free connectors, catheter luer connectors, stopcocks, and hemodialysis connectors. In one or more embodiments, the needleless connector is selected from a Q-Syte connector, MaxPlus, MaxPlus Clear, MaxZero, UltraSite, Caresite, InVision-Plus, Safeline, OneLink, V-Link, ClearLink, NeutraClear, Clave, MicroClave, MicroClave Clear, Neutron, NanoClave, Kendall, Nexus, InVision, Vadsite, Bionector, etc.

(142) In one or more embodiments, the male connector may be an intravenous tubing end, a stopcock or male lock luer.

(143) In some embodiments, the connector comprises a needleless injection site, which may sometimes be referred to as a needleless injection port, hub, valve, or device, or as a needleless access site, port, hub, valve, or device, and which can include such brands as, for example, Clave® (available from ICU Medical, Inc.), SmartSite® (available from Cardinal Health, Inc.), and Q-Syte™ (available from Becton, Dickinson and Company). In some embodiments, the needleless connector can be connected with any of a variety of different needleless injection sites, such as those previously listed. In one or more embodiments, after the needleless connector has been coupled with connector, it is unnecessary to disinfect (e.g., treat with an alcohol swab) the connector prior to each reconnection of the connector with another connector, as the connector will be kept in an uncontaminated state while coupled with the needleless connector. Use of the needleless connector replaces the standard swabbing protocol for cleaning connectors.

(144) Such connectors are generally and commonly used as catheter and other fluid-tight protective connectors in medical applications. In one or more embodiments, medical connector (**100, 200, 300, 400, 500, 600, 700, 800**) provides a protective cover for a corresponding needleless luer connector when engaged with the connector when threads from the corresponding needleless luer connector engage and form a releasable connection with the medical connector (**100, 200, 300, 400, 500, 600, 700, 800**)

(145) The medical connector (**100, 200, 300, 400, 500, 600, 700, 800**) is made from any of a number of types of plastic materials such as polycarbonate, polypropylene, polyethylene, polyethylene terephthalate, polylactide, acrylonitrile butadiene styrene or any other moldable plastic material used in medical devices. In one or more embodiments, the medical connector (**100, 200, 300, 400, 500, 600, 700, 800**) comprises a polypropylene or polyethylene material.

(146) The medical connector (**100, 200, 300, 400, 500, 600, 700, 800**) can achieve disinfection when used on luer connectors by integrating disinfectant in the cavity (**130, 230, 330, 430, 530, 630, 730, 830**). The disinfectant or antimicrobial agent can be directly included in the absorbent material or disinfectant or antimicrobial agent can be absorbed into sponges or foam material that fills the cavity (**130, 230, 330, 430, 530, 630, 730, 830**). Medical connector (**100, 200, 300, 400, 500, 600, 700, 800**) is designed to be compatible in interacting with various disinfectants. In one or more embodiments, the disinfectant or antimicrobial agent may include variations of alcohol or chlorhexidine. In one or more embodiments, the disinfectant or antimicrobial agent is selected from the group consisting essentially of isopropyl alcohol, ethanol, 2-propanol, butanol, methylparaben, ethylparaben, propylparaben, propyl gallate, butylated hydroxyanisole (BHA), butylated hydroxytoluene, t-butyl-hydroquinone, chloroxylenol, chlorhexidine, chlorhexidine diacetate, chlorhexidine gluconate, povidone iodine, alcohol, dichlorobenzyl alcohol, dehydroacetic acid, hexetidine, triclosan, hydrogen peroxide, colloidal silver, benzethonium chloride, benzalkonium chloride, octenidine, antibiotic, and mixtures thereof. In a specific embodiment, the disinfectant or antimicrobial agent comprises at least one of chlorhexidine gluconate and chlorhexidine diacetate. In one or more embodiments, the disinfectant or antimicrobial agent is a fluid or a gel.

(147) In one or more embodiments the absorbent material is a nonwoven material, foam, or a sponge. In a specific embodiment, the absorbent material is polyethylene foam. The foam may be open celled, semi-opened or closed celled and may be molded or extruded or die cut from sheeting. In one or more embodiments, the absorbent reservoir material is molded or extruded or die cut from sheeting to form a cylindrical block shape

(148) A peelable seal minimizes entry of potential particulate hazard and also provides a substantially impermeable enclosure for the medical connector (**100, 200, 300, 400, 500, 600, 700, 800**), provides a leak prevention and protection enclosure, protects the contents of absorbent material contained within the cavity (**130, 230, 330, 430, 530, 630, 730, 830**), and/or maintains a sealed, sterilized environment. The peelable seal provides a sufficient seal at a range of temperatures, pressures, and humidity levels. In one or more embodiments, the peelable seal comprises an aluminum or multi-layer polymer film peel back top. In a specific embodiment, the peelable seal is heat-sealed or induction sealed to the end face of the locking lid or to the needleless connector open end. In one or more embodiments, the peelable seal comprises a moisture barrier.

(149) In some embodiments, the medical connector is configured as a cap containing disinfectant within a cavity of the housing and capable of blocking the lumens of corresponding medical connectors to minimize ingress of disinfectant and microbial agents into connectors, thereby reducing risk of the disinfectant and microbial agents entering the blood stream of a patient.

(150) While the present disclosure has been shown and described with reference to certain exemplary embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the embodiments of the present disclosure. For example, a disinfection sponge can comprise any suitable disinfecting or other application-specific substance, and can be made of any suitable material. Also, the inner and/or the outer housing of the medical connector can be single shot molded, or made by other suitable process. Furthermore, any of the features or elements of any exemplary implementations of the embodiments of the present disclosure as described above and illustrated in the drawing figures can be implemented individually or in any combination(s) as would be readily appreciated by skilled artisans without departing from the spirit and scope of the embodiments of the present disclosure.

(151) In addition, the included drawing figures further describe non-limiting examples of implementations of certain exemplary embodiments of the present disclosure and aid in the description of technology associated therewith. Any specific or relative dimensions or measurements provided in the drawings other as noted above are exemplary and not intended to be limiting.

(152) Reference throughout this specification to “one embodiment,” “certain embodiments,” “one or more embodiments” or “an embodiment” means that a particular feature, structure, material, or characteristic described in connection with the embodiment is included in at least one embodiment of the disclosure. Thus, the appearances of the phrases such as “in one or more embodiments,” “in certain embodiments,” “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily referring to the same embodiment of the disclosure. Furthermore, the particular features, structures, materials, or characteristics may be combined in any suitable manner in one or more embodiments.

(153) Although the disclosure herein has provided a description with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present disclosure. It will be apparent to those skilled in the art that various modifications and variations can be made to the method and apparatus of the present disclosure without departing from the spirit and scope of the disclosure. Thus, it is intended that the present disclosure include modifications and variations that are within the scope of the appended claims and their equivalents.

Claims

1. A medical connector comprising: a housing having a single, substantially cylindrical housing body having a radial protrusion extending from the substantially cylindrical housing body and a cavity within the substantially cylindrical housing body that is defined by a distal closed end, a

proximal open end, a partially cylindrical inner sidewall of the substantially cylindrical housing body and a radial inner sidewall of the radial protrusion, the radial inner sidewall of the radial protrusion has a larger diameter than the partially cylindrical inner sidewall of the substantially cylindrical housing body; a locking structure disposed on the radial inner sidewall of the radial protrusion, the locking structure including a sloped tab, wherein a locking position is being defined by the sloped tab and a first position disposed circumferentially adjacent to the sloped tab; an insert advanceable into, and rotatable from the first position to the locking position within the cavity of the substantially cylindrical housing body, the insert comprising a discoid body having a distal surface, a proximal surface, a peripheral sidewall and a cantilever locking tab extending proximally from the peripheral sidewall, the cantilever locking tab defining an inner wall facing the cavity and an outer wall facing the radial inner sidewall of the radial protrusion, the insert including at least one thread disposed on the inner wall of the cantilever locking tab for direct mating, threaded engagement with a corresponding thread formed on a corresponding medical connector inserted within the cavity, and a recessed notch disposed on a proximal portion of the outer wall of the locking tab, the notch opposing the sloped tab when the locking tab is rotated to the locking position; and an absorbent material disposed between the distal surface of the insert and an inner top surface of the cavity of the housing, such that the absorbent material does not make direct contact with a corresponding medical connector, the absorbent material containing a disinfectant, wherein insertion of the corresponding medical connector into the cavity compresses the absorbent material, thereby releasing disinfectant into the cavity.

2. The medical connector of claim 1, wherein the recessed notch of the insert engages a ledge of the sloped tab of the locking structure when the recessed notch is advanced past the sloped tab during insert rotation.

3. The medical connector of claim 2, wherein an audible click or sound is created when the recessed notch is advanced past the ledge of the sloped tab.

4. The medical connector of claim 1, wherein the locking structure further includes an outwardly sloped surface that adjoins the sloped tab, which slopes radially outwardly from the radial inner sidewall toward the cavity and extends circumferentially from the first position to the locking position.

5. The medical connector of claim 4, wherein the outwardly sloped surface contacts the outer wall of the locking tab and causes deformation of the locking tab toward the cavity.

6. The medical connector of claim 1, wherein the locking structure further includes a proximally sloped surface that incorporates the sloped tab, the proximally sloped surface located adjacent to a ledge of the sloped tab, the proximally sloped surface slopes inwardly with respect to the radial inner sidewall of the radial protrusion from a distal position to a proximal position thereupon, wherein the recessed notch of the insert engages the ledge when the recessed notch is advanced past the sloped tab during insert rotation.

7. The medical connector of claim 1, wherein the distal surface of the insert abuts an inner top surface of the cavity of the housing when the insert is fully advanced into the cavity.

8. The medical connector of claim 1, wherein fully advancing the insert into the cavity in a distal direction causes the distal surface of the insert and the inner top surface of the cavity of the housing to compress the absorbent material, the absorbent material releasing the disinfectant.

9. The medical connector of claim 8, wherein the disinfectant evacuates into the cavity by a gap defined by the partially cylindrical inner sidewall of the housing and the peripheral sidewall of the insert.

10. The medical connector of claim 1, wherein a diameter of the partially cylindrical inner sidewall of the housing is larger than a corresponding diameter of the peripheral sidewall of the insert.

11. The medical connector of claim 1, wherein a retention tab is disposed on an inner top surface of the housing, the retention tab non-removably securing thereabout a through aperture disposed on the distal surface of the insert.

12. A medical connector comprising: a housing having a single, substantially cylindrical housing body having a radial protrusion extending from the substantially cylindrical housing body and a cavity within the substantially cylindrical housing body that is defined by a distal closed end, a proximal open end, a partially cylindrical inner sidewall of the substantially cylindrical housing body and a radial inner sidewall of the radial protrusion, the radial inner sidewall of the radial protrusion has a larger diameter than the partially cylindrical inner sidewall of the substantially cylindrical housing body; a locking structure disposed on the radial inner sidewall of the radial protrusion, the locking structure including a sloped tab; and an insert advanceable into the cavity of the housing body, the insert comprising a discoid body having a distal surface, a proximal surface, a peripheral sidewall and a cantilever locking tab extending proximally from the peripheral sidewall, the locking tab defining an inner wall facing the cavity and an outer wall facing the radial inner sidewall, the insert including at least one thread disposed on the inner wall of the cantilever locking tab for direct mating, threaded engagement with a corresponding thread formed on a corresponding female needleless connector inserted within the cavity, and a recessed notch disposed on a proximal portion of the outer wall of the cantilever locking tab, wherein threading the female needleless connector into the cavity causes the insert to be advanced into the cavity, and causes the recessed notch to oppose and engage the sloped tab; an absorbent material disposed between the distal surface of the insert and an inner top surface of the cavity of the housing, such that the absorbent material does not make direct contact with the corresponding female needleless connector, the absorbent material containing a disinfectant, wherein insertion of the corresponding female needleless connector into the cavity compresses the absorbent material, thereby releasing disinfectant into the cavity.

13. The medical connector of claim 12, wherein the female needleless connector is removably threaded into the cavity.
