

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388879
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Sodagar; Iraj

Methods for discovery of media capabilities of 5G edge

Abstract

A method of managing capabilities of a media streaming network using at least one processor, including receiving a capability request for media streaming capabilities of an edge data network (EDN); determining the media streaming capabilities of the EDN; transmitting a capability response based on the determined media streaming capabilities; receiving a media processing workflow request based on the capability response; establishing a media streaming session according to the media processing workflow request; and streaming media content based on the media streaming session.

Inventors:	Sodagar; Iraj (Palo Alto, CA)
Applicant:	TENCENT AMERICA LLC (Palo Alto, CA)
Family ID:	78413520
Assignee:	TENCENT AMERICA LLC (Palo Alto, CA)
Appl. No.:	18/541048
Filed:	December 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240137393 A1	Apr. 25, 2024

Related U.S. Application Data

continuation parent-doc US 17213679 20210326 US 11902337 child-doc US 18541048
us-provisional-application US 63075461 20200908
us-provisional-application US 63066692 20200817
us-provisional-application US 63052104 20200715

Publication Classification

Int. Cl.: **H04L65/1059** (20220101); **H04L65/1063** (20220101); **H04L65/60** (20220101);
H04L67/51 (20220101); **H04N21/647** (20110101); **H04W4/20** (20180101)

U.S. Cl.:

CPC **H04L65/1059** (20130101); **H04L65/1063** (20130101); **H04L65/60** (20130101);
H04L67/51 (20220501); **H04N21/647** (20130101); **H04W4/20** (20130101);

Field of Classification Search

CPC: H04L (65/1059); H04L (65/1063); H04L (65/60); H04L (67/16); H04L (41/5009); H04L
(67/1008); H04L (67/1012); H04L (65/65); H04L (67/1004); H04L (67/101); H04N
(21/647); H04W (4/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8806031	12/2013	Kondur	709/228	H04L 41/0895
2008/0112405	12/2007	Cholas	370/389	H04L 63/062
2008/0270610	12/2007	John et al.	N/A	N/A
2010/0198977	12/2009	Shetty et al.	N/A	N/A
2011/0090898	12/2010	Patel	370/352	H04L 12/66
2017/0317894	12/2016	Dao	N/A	H04L 41/5009
2018/0316746	12/2017	Shattil	N/A	N/A
2019/0098091	12/2018	Shinde	N/A	H04L 67/125
2019/0349628	12/2018	Cholas	N/A	H04N 21/4433
2019/0373443	12/2018	Palaniappan	N/A	H04W 60/00
2020/0137642	12/2019	Hong	N/A	H04L 65/40
2020/0404069	12/2019	Li	N/A	H04W 8/24
2021/0136177	12/2020	Hall	N/A	H04L 67/63
2021/0136178	12/2020	Casey	N/A	H04L 47/823
2021/0219268	12/2020	Li	N/A	H04L 1/08
2021/0243264	12/2020	Yoon	N/A	H04L 41/5058
2021/0274418	12/2020	Zhou	N/A	H04W 80/02
2021/0314391	12/2020	Lee	N/A	H04W 48/18
2022/0369218	12/2021	Gupta	N/A	H04W 48/18

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2003-209566	12/2002	JP	N/A
2020/033088	12/2019	WO	N/A

OTHER PUBLICATIONS

“3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 5G Media Streaming (5GMS); General description and architecture (Release 16)”, 3GPP TS 26.501 V16.3.1, Mar. 2020, 63 pages (Year: 2020). cited by examiner

“3rd Generation Partnership project; Technical Specification Group Services and System Aspects; Architecture for enabling Edge Applications; (Release 17)”, 3GPP TS 23.558 V0.2.0, Apr. 2020, 55 pages (Year: 2020). cited by examiner

“3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 5G Media Streaming (5GMS); General description and architecture (Release 16) Draft”, 3GPP TS 26.501 V16.3.1, Mar. 2020, 68 pages; retrieved from https://www.3gpp.org/ftp/tsg_sa/WG4_CODEC/TSGS4_109-e/Inbox/ (Year: 2020). cited by examiner

3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 5G Media Streaming (5GMS); General description and architecture (release 16). cited by applicant

3rd Generation Partnership project; Technical Specification Group Services and System Aspects; Architecture for enabling Edge Applications; (Release 17). cited by applicant

International Search Report dated Jul. 7, 2021 in International Application No. PCT/US21/27431. cited by applicant

Written Opinion of the International Searching Authority dated Jul. 7, 2021 in International Application No. PCT/US21/27431. cited by applicant

Communication dated Jul. 1, 2025 issued by Japanese Patent Office in Japanese Application No. 2024-037846. cited by applicant

Primary Examiner: Tran; Alex H.

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This is a Continuation of U.S. patent application Ser. No. 17/213,679, filed on Mar. 26, 2021, which is priority from U.S. Provisional Application No. 63/021,411, filed on May 7, 2020, U.S. Provisional Application No. 63/066,692, filed on Aug. 17, 2020, U.S. Provisional Application No. 63/075,461, filed on Sep. 8, 2020, U.S. Provisional Application No. 63/026,432, filed on May 18, 2020, and U.S. Provisional Application No. 63/052,104, filed on Jul. 15, 2020, in the United States Patent and Trademark Office, the disclosure of which is incorporated herein by reference in its entirety.

FIELD

(1) Embodiments of this disclosure are directed to media processing and streaming methods and systems, more particularly to discovery of network processing capabilities of 5G edge networks by external application servers, which allows the external application servers to learn about the current capabilities of the 5G network before requesting to set up any network-based processing.

BACKGROUND

(2) Network and cloud platforms are used to run various applications. However, there is no standard based solution to describe the characteristics of a network or cloud platform or its elements.

(3) 3rd Generation Partnership Project (3GPP) TS26.501 defines the workflow for external application servers to establish network processing in 5G networks for uplink and downlink streaming applications.

(4) European Telecommunications Standards Institute (ETSI) Multi-access Edge Computing (MEC) standard defines an architecture for instantiation, running, and managing applications on cloud platforms.

(5) The current 5G Edge architecture defined in 3GPP TS23.558 only defines the general architecture and discovery of edge server hardware capabilities. It does not address the discovery of edge server capabilities for media processing, which is more than raw hardware capabilities. It also does not address the environmental characteristics of the edge server.

(6) In NBMP standard, the NBMP Source is the entity providing the workflow description to Workflow Manager to create, run, manage and monitor a media workflow. The interaction between NBMP Source and Workflow Manager is through a set of NBMP Operation APIs.

(7) In the case of the 5G Streaming Media Architecture (5GMSA), the source device of media streams establishes an uplink session with an application function/application server (AF/AS) pairs in the network. A receiving device also establishes a downlink session with AF/AS to stream/download content from the network.

(8) However, there is not edge computing architecture in 5GMSA that allows the deployment of network and edge processing or the split rendering of media streaming using the edge and network resources.

SUMMARY

(9) According to one or more embodiments, a method of managing capabilities of a media streaming network using at least one processor includes receiving a capability request for media streaming capabilities of an edge data network (EDN); determining the media streaming capabilities of the EDN; transmitting a capability response based on the determined media streaming capabilities; receiving a media processing workflow request based on the capability response; establishing a media streaming session according to the media processing workflow request; and streaming media content based on the media streaming session.

(10) According to one or more embodiments, a device for managing capabilities of a media streaming network includes at least one memory configured to store program code; and at least one processor configured to read the program code and operate as instructed by the program code, the program code including: first receiving code configured to cause the at least one processor to receive a capability request for media streaming capabilities of an edge data network (EDN); determining code configured to cause the at least one processor to determine the media streaming capabilities of the EDN; first transmitting code configured to cause the at least one processor to transmit a capability response based on the determined media streaming capabilities; second receiving code configured to cause the at least one processor to receive a media processing workflow request based on the capability response; establishing code configured to cause the at least one processor to establish a media streaming session according to the media processing workflow request; and streaming code configured to cause the at least one processor to stream media content based on the media streaming session.

(11) According to one or more embodiments, a non-transitory computer-readable medium storing instructions, the instructions including: one or more instructions that, when executed by one or more processors of a device for managing capabilities of a media streaming network, cause the one or more processors to: receive a capability request for media streaming capabilities of an edge data network (EDN); determine the media streaming capabilities of the EDN; transmit a capability response based on the determined media streaming capabilities; receive a media processing workflow request based on the capability response; establish a media streaming session according to the media processing workflow request; and stream media content based on the media streaming session.

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further features, the nature, and various advantages of the disclosed subject matter will be more apparent from the following detailed description and the accompanying drawings in which:

(2) FIG. 1 is a diagram of an environment in which methods, apparatuses, and systems described herein may be implemented, according to embodiments.

(3) FIG. 2 is a block diagram of example components of one or more devices of FIG. 1.

(4) FIG. 3 is a block diagram of a network architecture for media streaming, according to embodiments.

(5) FIG. 4 is a block diagram of a network architecture for media streaming, according to embodiments.

(6) FIG. 5 is a block diagram of a network architecture for media streaming, according to embodiments.

(7) FIG. 6 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(8) FIG. 7 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(9) FIG. 8 is a block diagram of a network architecture for media streaming, according to embodiments.

(10) FIG. 9 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(11) FIG. 10 is a block diagram of a network architecture for media streaming, according to embodiments.

(12) FIG. 11 is a block diagram of a network architecture for media streaming, according to embodiments.

(13) FIG. 12 is a block diagram of a network architecture for media streaming, according to embodiments.

(14) FIG. 13 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(15) FIG. 14 is a block diagram of a network architecture for media streaming, according to embodiments.

(16) FIG. 15 is a block diagram of a network architecture for media streaming, according to embodiments.

(17) FIG. 16 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(18) FIG. 17 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(19) FIG. 18 is a block diagram illustrating an example process for network capability discovery, according to embodiments.

(20) FIG. 19 is a block diagram of a network architecture for media streaming, according to embodiments.

(21) FIG. 20 is a block diagram of a network architecture for media streaming, according to embodiments.

(22) FIG. 21 is a block diagram of a network architecture for media streaming, according to embodiments.

(23) FIG. 22 is a block diagram of a network architecture for media streaming, according to embodiments.

(24) FIG. 23 is a block diagram of a network architecture for media streaming, according to embodiments.

(25) FIG. 24 is a flowchart of an example process for managing capabilities of a media streaming

network, according to embodiments.

DETAILED DESCRIPTION

(26) FIG. 1 is a diagram of an environment **100** in which methods, apparatuses, and systems described herein may be implemented, according to embodiments. As shown in FIG. 1, the environment **100** may include a user device **110**, a platform **120**, and a network **130**. Devices of the environment **100** may interconnect via wired connections, wireless connections, or a combination of wired and wireless connections.

(27) The user device **110** includes one or more devices capable of receiving, generating, storing, processing, and/or providing information associated with platform **120**. For example, the user device **110** may include a computing device (e.g., a desktop computer, a laptop computer, a tablet computer, a handheld computer, a smart speaker, a server, etc.), a mobile phone (e.g., a smart phone, a radiotelephone, etc.), a wearable device (e.g., a pair of smart glasses or a smart watch), or a similar device. In some implementations, the user device **110** may receive information from and/or transmit information to the platform **120**.

(28) The platform **120** includes one or more devices as described elsewhere herein. In some implementations, the platform **120** may include a cloud server or a group of cloud servers. In some implementations, the platform **120** may be designed to be modular such that software components may be swapped in or out depending on a particular need. As such, the platform **120** may be easily and/or quickly reconfigured for different uses.

(29) In some implementations, as shown, the platform **120** may be hosted in a cloud computing environment **122**. Notably, while implementations described herein describe the platform **120** as being hosted in the cloud computing environment **122**, in some implementations, the platform **120** may not be cloud-based (i.e., may be implemented outside of a cloud computing environment) or may be partially cloud-based.

(30) The cloud computing environment **122** includes an environment that hosts the platform **120**. The cloud computing environment **122** may provide computation, software, data access, storage, etc. services that do not require end-user (e.g. the user device **110**) knowledge of a physical location and configuration of system(s) and/or device(s) that hosts the platform **120**. As shown, the cloud computing environment **122** may include a group of computing resources **124** (referred to collectively as “computing resources **124**” and individually as “computing resource **124**”).

(31) The computing resource **124** includes one or more personal computers, workstation computers, server devices, or other types of computation and/or communication devices. In some implementations, the computing resource **124** may host the platform **120**. The cloud resources may include compute instances executing in the computing resource **124**, storage devices provided in the computing resource **124**, data transfer devices provided by the computing resource **124**, etc. In some implementations, the computing resource **124** may communicate with other computing resources **124** via wired connections, wireless connections, or a combination of wired and wireless connections.

(32) As further shown in FIG. 1, the computing resource **124** includes a group of cloud resources, such as one or more applications (“APPs”) **124-1**, one or more virtual machines (“VMs”) **124-2**, virtualized storage (“VSs”) **124-3**, one or more hypervisors (“HYPs”) **124-4**, or the like.

(33) The application **124-1** includes one or more software applications that may be provided to or accessed by the user device **110** and/or the platform **120**. The application **124-1** may eliminate a need to install and execute the software applications on the user device **110**. For example, the application **124-1** may include software associated with the platform **120** and/or any other software capable of being provided via the cloud computing environment **122**. In some implementations, one application **124-1** may send/receive information to/from one or more other applications **124-1**, via the virtual machine **124-2**.

(34) The virtual machine **124-2** includes a software implementation of a machine (e.g. a computer) that executes programs like a physical machine. The virtual machine **124-2** may be either a system

virtual machine or a process virtual machine, depending upon use and degree of correspondence to any real machine by the virtual machine **124-2**. A system virtual machine may provide a complete system platform that supports execution of a complete operating system (“OS”). A process virtual machine may execute a single program, and may support a single process. In some implementations, the virtual machine **124-2** may execute on behalf of a user (e.g. the user device **110**), and may manage infrastructure of the cloud computing environment **122**, such as data management, synchronization, or long-duration data transfers.

(35) The virtualized storage **124-3** includes one or more storage systems and/or one or more devices that use virtualization techniques within the storage systems or devices of the computing resource **124**. In some implementations, within the context of a storage system, types of virtualizations may include block virtualization and file virtualization. Block virtualization may refer to abstraction (or separation) of logical storage from physical storage so that the storage system may be accessed without regard to physical storage or heterogeneous structure. The separation may permit administrators of the storage system flexibility in how the administrators manage storage for end users. File virtualization may eliminate dependencies between data accessed at a file level and a location where files are physically stored. This may enable optimization of storage use, server consolidation, and/or performance of non-disruptive file migrations.

(36) The hypervisor **124-4** may provide hardware virtualization techniques that allow multiple operating systems (e.g. “guest operating systems”) to execute concurrently on a host computer, such as the computing resource **124**. The hypervisor **124-4** may present a virtual operating platform to the guest operating systems, and may manage the execution of the guest operating systems. Multiple instances of a variety of operating systems may share virtualized hardware resources.

(37) The network **130** includes one or more wired and/or wireless networks. For example, the network **130** may include a cellular network (e.g. a fifth generation (5G) network, a long-term evolution (LTE) network, a third generation (3G) network, a code division multiple access (CDMA) network, etc.), a public land mobile network (PLMN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), a telephone network (e.g. the Public Switched Telephone Network (PSTN)), a private network, an ad hoc network, an intranet, the Internet, a fiber optic-based network, or the like, and/or a combination of these or other types of networks.

(38) The number and arrangement of devices and networks shown in FIG. **1** are provided as an example. In practice, there may be additional devices and/or networks, fewer devices and/or networks, different devices and/or networks, or differently arranged devices and/or networks than those shown in FIG. **1**. Furthermore, two or more devices shown in FIG. **1** may be implemented within a single device, or a single device shown in FIG. **1** may be implemented as multiple, distributed devices. Additionally, or alternatively, a set of devices (e.g. one or more devices) of the environment **100** may perform one or more functions described as being performed by another set of devices of the environment **100**.

(39) FIG. **2** is a block diagram of example components of one or more devices of FIG. **1**. The device **200** may correspond to the user device **110** and/or the platform **120**. As shown in FIG. **2**, the device **200** may include a bus **210**, a processor **220**, a memory **230**, a storage component **240**, an input component **250**, an output component **260**, and a communication interface **270**.

(40) The bus **210** includes a component that permits communication among the components of the device **200**. The processor **220** is implemented in hardware, firmware, or a combination of hardware and software. The processor **220** is a central processing unit (CPU), a graphics processing unit (GPU), an accelerated processing unit (APU), a microprocessor, a microcontroller, a digital signal processor (DSP), a field-programmable gate array (FPGA), an application-specific integrated circuit (ASIC), or another type of processing component. In some implementations, the processor **220** includes one or more processors capable of being programmed to perform a function. The

memory **230** includes a random access memory (RAM), a read only memory (ROM), and/or another type of dynamic or static storage device (e.g. a flash memory, a magnetic memory, and/or an optical memory) that stores information and/or instructions for use by the processor **220**.

(41) The storage component **240** stores information and/or software related to the operation and use of the device **200**. For example, the storage component **240** may include a hard disk (e.g. a magnetic disk, an optical disk, a magneto-optic disk, and/or a solid state disk), a compact disc (CD), a digital versatile disc (DVD), a floppy disk, a cartridge, a magnetic tape, and/or another type of non-transitory computer-readable medium, along with a corresponding drive.

(42) The input component **250** includes a component that permits the device **200** to receive information, such as via user input (e.g. a touch screen display, a keyboard, a keypad, a mouse, a button, a switch, and/or a microphone). Additionally, or alternatively, the input component **250** may include a sensor for sensing information (e.g. a global positioning system (GPS) component, an accelerometer, a gyroscope, and/or an actuator). The output component **260** includes a component that provides output information from the device **200** (e.g. a display, a speaker, and/or one or more light-emitting diodes (LEDs)).

(43) The communication interface **270** includes a transceiver-like component (e.g., a transceiver and/or a separate receiver and transmitter) that enables the device **200** to communicate with other devices, such as via a wired connection, a wireless connection, or a combination of wired and wireless connections. The communication interface **270** may permit the device **200** to receive information from another device and/or provide information to another device. For example, the communication interface **270** may include an Ethernet interface, an optical interface, a coaxial interface, an infrared interface, a radio frequency (RF) interface, a universal serial bus (USB) interface, a Wi-Fi interface, a cellular network interface, or the like.

(44) The device **200** may perform one or more processes described herein. The device **200** may perform these processes in response to the processor **220** executing software instructions stored by a non-transitory computer-readable medium, such as the memory **230** and/or the storage component **240**. A computer-readable medium is defined herein as a non-transitory memory device. A memory device includes memory space within a single physical storage device or memory space spread across multiple physical storage devices.

(45) Software instructions may be read into the memory **230** and/or the storage component **240** from another computer-readable medium or from another device via the communication interface **270**. When executed, software instructions stored in the memory **230** and/or the storage component **240** may cause the processor **220** to perform one or more processes described herein. Additionally, or alternatively, hardwired circuitry may be used in place of or in combination with software instructions to perform one or more processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

(46) The number and arrangement of components shown in FIG. 2 are provided as an example. In practice, the device **200** may include additional components, fewer components, different components, or differently arranged components than those shown in FIG. 2. Additionally, or alternatively, a set of components (e.g. one or more components) of the device **200** may perform one or more functions described as being performed by another set of components of the device **200**.

(47) FIG. 3 is a diagram of a media architecture **300** for media streaming. In embodiments, media architecture **300** may be used for uplink streaming or downlink streaming. A 5G media streaming uplink (5GMS) Application Provider **301** may use 5GMS for streaming services. 5GMS Application provider **301** may provide a 5GMS Aware Application **302** on the UE **303** to make use of 5GMS Client **304** and network functions using interfaces and APIs defined in 5GMS. 5GMS Application Server (AS) may be an AS dedicated to 5G Media Streaming. 5GMS Client **304** may be a UE **303** internal function dedicated to 5G Media Streaming.

(48) 5GMS Application Function (AF) **306** and 5GMS AS **305** may be Data Network (DN) **307**

functions. Functions in trusted DNs may be trusted by the operator's network. Therefore, AFs in trusted DNs may directly communicate with all 5G Core functions. Functions in external DNs may only communicate with 5G Core functions via the Network Exposure Function (NEF) **308** using link **320**.

(49) The media architecture **300** may connect UE **303** internal functions and related network functions for 5G Media Uplink Streaming. Accordingly, media architecture **300** may include a number of functions. For example, 5GMS Client **304** on UE **303** may be an originator of 5GMS service that may be accessed through interfaces/APIs. 5GMS Client **304** may include two sub-functions, media session handler (MSH) **309** and media streamer **310**. MSH **309** may communicate with the 5GMS AF **306** in order to establish, control and support the delivery of a media session. The MSH **309** may expose APIs that can be used by the 5GMS Aware Application **302**. Media Streamer **310** may communicate with 5GMS AS **305** in order to stream the media content and provide a service to the 5GMS Aware Application **302** for media capturing and streaming, and the MSH **309** for media session control. 5GMS Aware Application **302** may control 5GMS Client **303** by implementing external application or content service provider specific logic and enabling the establishment of a media session. 5GMS AS **305** may host 5G media functions. 5GMS Application Provider **301** may be an external application or content specific media functionality, e.g., media storage, consumption, transcoding and redistribution that uses 5GMS to stream media from 5GMS Aware Application **302**. 5GMS AF **306** may provide various control functions to the MSH **309** on the UE **303** and/or to 5GMS Application Provider **301**. 5GMS AF **306** may relay or initiate a request for different Policy or Charging Function (PCF) **311** treatment or interact with other network functions.

(50) Media architecture **300** may include a number of different interfaces. For example, link M1 may be a 5GMS Provisioning API exposed by 5GMS AF **306** to provision usage of media architecture **300** and to obtain feedback. Link M2 may be a 5GMS Publish API exposed by 5GMS AS **305** and used when 5GMS AS **305** in trusted DN, such as DN **307**, is selected to receive content for streaming service. Link M3 may be an internal API used to exchange information for content hosting on 5GMS AS **305** within a trusted DN such as DN **307**. Link M4 may be a Media Uplink Streaming API exposed by 5GMS AS **323** to Media Streamer **310** to stream media content. Link M5 may be a Media Session Handling API exposed by 5GMS AF **305** to Media Session Handler for media session handling, control and assistance that also include appropriate security mechanisms e.g. authorization and authentication. Link M6 may be a UE **303** Media Session Handling API exposed by MSH **309** to 5GMS Aware Application **302** to make use of 5GMS functions. Link M7 may be a UE Media Streamer API exposed by Media Streamer **310** to 5GMS Aware Application **302** and MSH **309** to make use of Media Streamer **310**. Link M8 may be an Application API which is used for information exchange between 5GMS Aware Application **302** and 5GMS Application Provider **301**, for example to provide service access information to the 5GMS Aware Application **302**.

(51) FIG. 4 is a diagram of a 5G edge network architecture **400**, according to embodiments. Edge Data Network (EDN) **401** is a local Data Network. Edge Application Server (EAS) **402** and Edge Enabler Server (EES) **403** are contained within the EDN **401**. Edge Configuration Server (ECS) **404** provides configurations related to EES **403**, including details of EDN **401** hosting EES **403**. User Equipment (UE) **405** contains Application Client (AC) **406** and Edge Enabler Client (EEC) **407**. EAS **402**, EES **403** and ECS **404** may interact with the 3GPP Core Network **408**.

(52) EES **403** provides supporting functions needed for EAS **402** and EEC **407**. Functionalities of EES **403** may include: provisioning of configuration information to EEC **407**, enabling exchange of application data traffic with EAS; supporting the functionalities of API invoker and API exposing function, for example as specified in 3GPP TS 23.222; interacting with 3GPP Core Network **408** for accessing the capabilities of network functions either directly (e.g. via PCF) or indirectly (e.g. via Service Capability Exposure Function (SCEF)/NEF/SCEF+NEF); supporting

the functionalities of application context transfer; supporting external exposure of 3GPP network and service capabilities to EASs **402** over link EDGE-3; supporting the functionalities of registration (i.e., registration, update, and de-registration) for EEC **407** and EAS **402**; and supporting the functionalities of triggering EAS **402** instantiation on demand.

(53) EEC **407** provides supporting functions needed for AC **406**. Functionalities of EEC **407** may include: retrieval and provisioning of configuration information to enable the exchange of Application Data Traffic with EAS **402**; and discovery of EASs **402** available in the EDN **401**.

(54) ECS **404** provides supporting functions needed for the EEC **407** to connect with an EES **403**. Functionalities of ECS **404** are: provisioning of Edge configuration information to the EEC **407**, for example the information for the EEC **407** to connect to the EES **403** (e.g. service area information applicable to LADN); and the information for establishing a connection with EESs **403** (such as URI); supporting the functionalities of registration (i.e., registration, update, and de-registration) for the EES **403**; supporting the functionalities of API invoker and API exposing function as specified in 3GPP TS 23.222; and interacting with 3GPP Core Network **408** for accessing the capabilities of network functions either directly (e.g. PCF) or indirectly (e.g. via SCEF/NEF/SCEF+NEF).

(55) AC **406** is the application resident in the UE **405** performing the client function.

(56) EAS **402** is the application server resident in the EDN **401**, performing the server functions. The AC **406** connects to EAS **402** in order to avail the services of the application with the benefits of Edge Computing. It is possible that the server functions of an application are available only as an EAS **402**. However, it is also possible that certain server functions are available both at the edge and in the cloud, as an EAS **402** and an Application Server resident in the cloud respectively. The server functions offered by an EAS **402** and its cloud Application Server counterpart may be the same or may differ; if they differ, the Application Data Traffic exchanged with the AC may also be different. EAS **402** may consume the 3GPP Core Network **408** capabilities in different ways, such as: it may invoke 3GPP Core Network **408** function APIs directly, if it is an entity trusted by the 3GPP Core Network **408**; it may invoke 3GPP Core Network **408** capabilities through EES **403**; and it may invoke the 3GPP Core Network **408** capability through the capability exposure functions i.e. SCEF or NEF.

(57) Architecture **400** may include a number of different interfaces for enabling edge applications, which may be referred to as reference points. For example, link EDGE-1 may be a reference point which enables interactions between the EES **403** and the EEC **407**. It supports: registration and de-registration of EEC **407** to EES **403**; retrieval and provisioning of EAS **402** configuration information; and discovery of EASs **402** available in the EDN **401**.

(58) Link EDGE-2 may be a reference point which enables interactions between EES **403** and the 3GPP Core Network **408**. It supports: access to 3GPP Core Network **408** functions and APIs for retrieval of network capability information, e.g. via SCEF and NEF APIs as defined in 3GPP TS 23.501, 3GPP TS 23.502, 3GPP TS 29.522, 3GPP TS 23.682, 3GPP TS 29.122; or with EES **403** deployed within the MNO trust domain (see 3GPP TS 23.501 clause 5.13, 3GPP TS 23.503, 3GPP TS 23.682) Link EDGE-2 may reuse 3GPP reference points or interfaces of EPS or 5GS considering different deployment models.

(59) Link EDGE-3 may be a reference point which enables interactions between EES **403** and EASs **402**. It supports: registration of EASs **402** with availability information (e.g. time constraints, location constraints); de-registration of EASs **402** from EES **403**; discovery of target EAS **402** information to support application context transfer; providing access to network capability information (e.g. location information, Quality of Service (QoS) related information); and requesting the setup of a data session between AC **406** and EAS **402** with a specific QoS.

(60) Link EDGE-4 may be a reference point which enables interactions between ECS **404** and EEC **407**. It supports: provisioning of Edge configuration information to the EEC **407**.

(61) Link EDGE-5 may be a reference point which enables interactions between AC and EEC **407**.

(62) Link EDGE-6 may be a reference point which enables interactions between ECS **404** and EES **403**. It supports: registration of EES **403** information to ECS **404**.

(63) Link EDGE-7 may be a reference point which enables interactions between EAS **402** and the 3GPP Core Network **408**. It supports: access to 3GPP Core Network **408** functions and APIs for retrieval of network capability information, e.g. via SCEF and NEF APIs as defined in 3GPP TS 23.501, 3GPP TS 23.502, 3GPP TS 29.522, 3GPP TS 23.682, 3GPP TS 29.122; or with EAS **402** deployed within the MNO trust domain (see 3GPP TS 23.501 clause 5.13, 3GPP TS 23.682) Link EDGE-7 may reuse 3GPP reference points or interfaces of EPS or 5GS considering different deployment models.

(64) Link EDGE-8 may be a reference point which enables interactions between the ECS **404** and the 3GPP Core Network **408**. It supports: a) access to 3GPP Core Network **408** functions and APIs for retrieval of network capability information, e.g. via SCEF and NEF APIs as defined in 3GPP TS 23.501, 3GPP TS 23.502, 3GPP TS 29.522, 3GPP TS 23.682, 3GPP TS 29.122; and with the ECS **404** deployed within the MNO trust domain (see 3GPP TS 23.501 clause 5.13, 3GPP TS 23.682) Link EDGE-8 may reuse 3GPP reference points or interfaces of EPS or 5GS considering different deployment models.

(65) Embodiments corresponding to FIGS. 5-7 relate to workflows and procedures to discover the capabilities of the 5G network by the external entities in two stages, for example, 1. Discovery of hardware capabilities of Edge Application Server 2. Discovery of media-specific capabilities of Edge Application Server

(66) Before establishing the media processing workflow on an edge server, the processing capabilities of the edge server must be discovered. These capabilities may include: 1. Available hardware resources including processing units, storage, and network elements 2. The environmental characteristics including the operating system (OS), version of OS and other parameters 3. The throughput and delay range that the edge server can provide 4. The media processing function libraries, the functional description and input/output formats of the various functions such as a. Encoding, transcoding and multi-rate encoding into different formats b. Manifest generation c. Encryptions and content protection d. Content replacement such as ad insertion e. Added media such as closed caption, object detection, content filtering

(67) The current TS23.558 only addresses the first item. Embodiments provide an architecture and methods for discovery of the second to fourth items.

(68) FIG. 5 illustrates an architecture **500** in which elements from architecture **400** of FIG. 4 are combined with elements from architecture **300** of FIG. 3. In order to avoid unnecessary duplication, redundant description has been omitted.

(69) As shown in FIG. 5, media streamer **310** and MSH **309** are included in AC **406**, and 5GMS AS **305** and 5GMS **306** are included in EAS **402**. MSH **309** may communicate with AC **406** through link U1, 5GMS AS **305** may communicate with 5GMS AF **306** through link N2, and 5GMS AF **306** may communicate with EAS **402** through link N1.

(70) FIG. 6 illustrates a process **600** which may relate to a call flow for discovering edge data network capabilities. Process **600** may be performed using architecture **500**, or any other architecture as desired.

(71) Process **600** may extend the TS23.558 APIs to enable the discovery of media capabilities of the edge data networks (EDNs).

(72) As shown in FIG. 6, the capabilities discovery is performed by requesting and responding through link U1, link EDGE-7, link N1, and link N2 APIs, and in reverse.

(73) According to process **600**, at operation **6010**, MSH **309** may send a request for processing capabilities to AC **406** using link U1. At operation **6020**, AC **406** may send a request for processing capabilities to EAS **402** using link EDGE-7. At operation **6030**, EAS **402** may send a request for processing capabilities to 5GMS AF **306** using link N1. At operation **6040**, 5GMS AF **306** may send a request for processing capabilities to 5GMS AS **305** using link N2.

(74) According to process **600**, at operation **6050**, 5GMS AS **305** may send a response including the processing capabilities to 5GMS AF **306** using link N2. At operation **6060**, 5GMS AF **306** may send a response including the processing capabilities to EAS **402** using link N1. At operation **6070**, EAS **402** may send a response including the processing capabilities to AC **406** using link EDGE-7. At operation **6080**, AC **406** may send a response including the processing capabilities to MSH **309** using link U1.

(75) Link EDGE-7 API is defined by TS23.558. To support the capability discovery shown herein, the link EDGE-7 API may be extended. Link U1, link N1, and link N2 may be internal APIs.

(76) FIG. 7 illustrates a process **700** which may relate to a call flow for discovering edge data network capabilities. Process **700** may be performed using architecture **500**, or any other architecture as desired.

(77) Process **700** may use the TS23.558 APIs to discover the hardware capabilities of the edge data network, but use the direct API to discover media-specific capabilities.

(78) As shown in FIG. 7, the capabilities discovery is performed by requesting and responding through U1, EDGE-7 at one stage (operations **7010-7040**), and through M5, and N2 APIs in the second stage (operations **7050-7080**).

(79) According to process **700**, at operation **7010**, MSH **309** may send a request for processing capabilities to AC **406** using link U1. At operation **7020**, AC **406** may send a request for processing capabilities to EAS **402** using link EDGE-7. At operation **7030**, EAS **402** may send a response including the processing capabilities to AC **406** using link EDGE-7. At operation **7040**, AC **406** may send a response including the processing capabilities to MSH **309** using link U1.

(80) According to process **700**, at operation **7050**, MSH **309** may send a request for processing capabilities to 5GMS AF **306** using link M5. At operation **7060**, 5GMS AF **306** may send a request for processing capabilities to 5GMS AS **305** using link N2. At operation **7070**, 5GMS AS **305** may send a response including the processing capabilities to 5GMS AF **306** using link N2. At operation **7080**, 5GMS AF **306** may send a response including the processing capabilities to MSH **309** using link M5.

(81) Link EDGE-7 API is defined by TS23.558, and link M5 is defined in TS26.501. To support the capability discovery shown herein, the link EDGE-7 and link M5 APIs may be extended.

(82) In process **700**, MSH **309** may discover the hardware capabilities through link U1 and link EDGE-7 APIs, and the media-specific capabilities through link M5 API.

(83) In tables throughout the disclosure, additional information is italicized. Further, a notation “M” indicates mandatory information, and a notation “O” indicates optional information.

Throughout the disclosure, the terms “mandatory” and “optional” used in this way indicate that particular elements are considered to be mandatory or optional within a particular embodiment, and not within every embodiment.

(84) Table 1 shows extensions for link EDGE-7 API to support media discovery functions according to FIGS. 5-7.

(85) TABLE-US-00001

TABLE 1	Edge-7 extensions	Information	element	Status	Description	Used
in	Maximum	O	Maximum request rate from the Process 600	Request	Application Client	supported
by	and	rate	the server.	Process 700	Maximum	O
			The maximum response time	Process 600		
			Response advertised for the Application and time	Client's service requests.	Process 700	Availability
			O	Advertised percentage of time the Process 600 server is available for the and	Application Client's	use.
			Process 700	Available	O	The maximum compute resource
			Process 600	Compute	available for	the Application and Client.
			Process 700	Available	O	The maximum graphical compute
			Process 600	Graphical	resource available for the and	Compute Application Client.
			Process 700	Available	O	The maximum memory resource
			Process 600	Memory	available for the Application and Client.	Process 700
			Available	O	The maximum storage resource	Process 600
			Storage	available for the Application and Client.	Process 700	Supported
			O	The OS and architecture	Callflow 1 environment and 2	Flow
			Control	O	Flow control capabilities	Process 600
			Repository	O	List and location of repositories	

Process 600 Functions O List of built-in functions and Process 600 workflows, and their performance

(86) Table 2 shows embodiments of example data extension for link M5 API to support media discovery functions according to FIGS. 5-7.

(87) TABLE-US-00002 TABLE 2 M5 extensions Information element Status Description Used in Flow Control O Flow control capabilities Process 600 Repository O List and location of repositories Process 600 Functions O List of built-in functions and Process 600 workflows, and their performance

(88) Tables 3-6 describe parameters added to link EDGE-7 and link M5 APIs in accordance with FIGS. 5-7.

(89) TABLE-US-00003 TABLE 3 Static image information object Name Definition os operation system version version number of operation system architecture hardware architecture environment environment

(90) TABLE-US-00004 TABLE 4 Flow control parameters Name Definition typical-delay typical expected delay for the resource. min-delay minimum delay (i.e. amount time from input to output sample) adequate for this resource max-delay maximum delay required for this resource typical-throughput typical expected throughput for this resource min-throughput minimum bandwidth required for this resource max-throughput maximum bandwidth adequate for this resource averaging-window averaging window used to calculate the throughput. The default is one second.

(91) TABLE-US-00005 TABLE 5 Repository parameters Name Definition mode Provides the mode for the repository preference. The following values are allowed: 'strict': only the listed repositories in this descriptor shall be used for deployment of the workflow. 'preferred': the listed repositories in this descriptor shall be used first for the deployment of the workflow. If a Function is not found in these repositories, a different repository may be used. 'available': the listed repositories in this descriptor may be used first for the deployment of the workflow. Other repositories may also be used. If more than one repository is listed, then the order of listing indicates the preference order of use from high to low, i.e. the first repository is the most preferred one. The default value is 'available'. Repository Information about supported repositories Location Location of the Repository. It shall be a valid URL according to IETF RFC 3986. name Name of the Repository description Provides a human-readable description for the Repository

(92) As shown in Table 5, the supported repositories are described. Each repository includes a list of supported functions.

(93) TABLE-US-00006 TABLE 6 Function Descriptions Name Description Scheme Unique identifier General Description of the function including: Name Description Brand Compatibility with standards keywords Input Description of inputs Output Description of outputs Processing Processing model and if it is consist of multiple functions Requirements The computational, memory, storage and bandwidth requirements Configuration The configuration parameter names and descriptions Client-Assistance Additional inputs during the operation Assertion Supported Assertion tests Variables Exposed variables Events Exposed events Security Security support static image The URL for the static image Dynamic image Information for building the dynamic image including request the scheme and patching URL.

(94) As shown in Table 6, the function descriptions describe the list of supported functions and their characteristics can be retrieved. These characteristics may include: 1. Supported input formats, codecs, and codec profiles/levels, resolutions, frame rates 2. Transcoding with formats, output codecs, codec profiles/levels, bitrates, and others 3. Reformatting with output format, 4. Combination of input media streams, e.g. network-based stitching, mixing, 5. Recognition or synthesis of media

(95) Accordingly, embodiments may provide a method for discovering the 5G network capabilities by the application through 3GPP Edge APIs and a call flow wherein the 5G device gathers the currently available resources from application server including media capabilities, wherein the

3GPP Edge APIs are extended to provide media capabilities of the edge network to the application.
(96) Embodiments may provide a method for discovering the 5G network capabilities by the application in two stages through 3GPP Edge APIs and then through 3GPP 5GMSA APIs, and a call flow wherein the 5G device gathers the currently available resources from application server including media capabilities, wherein the 3GPP Edge and 5GMSA APIs are extended to provide media capabilities of the edge network to the application.

(97) Embodiments may provide a method of discovering 5G application server environment parameters, wherein the application can discover information about the 5G Application Server operation system, environment parameters, and related information to run 1st and 3rd party applications, libraries, and functions on the 5G Application Server.

(98) Embodiments corresponding to FIGS. **8-10** may extend the 5G edge architectures discussed above to allow the following: 1. Discovery of available EASs **402** by a 5GMS AP **301** 2. Discovery of any available EAS **402** capabilities by 5GMS AP **301**

(99) FIG. **8** illustrates an architecture **800** in which elements from architecture **400** of FIG. **4** are combined with elements from architecture **300** of FIG. **3**. In order to avoid unnecessary duplication, redundant description has been omitted.

(100) As shown in FIG. **8**, link EDGE-9 allows communication between EAS **402** and 5GMS AP **301**, link EDGE-10 allows communication between EES **403** and 5GMS AP **301**, and link EDGE-11 allows communication between ECS **404** and 5GMS AP **301**.

(101) FIG. **9** illustrates a process **900** which may relate to a call flow for discovering Edge Data Network **401** capabilities. Process **900** may be performed using architecture **800**, architecture **1000** discussed below, or any other architecture as desired.

(102) Process **900** may extend the TS23.558 APIs to enable the discovery of media capabilities of the edge data networks by the 5GMS AP **301**.

(103) According to process **900**, at operation **9010**, 5GMS AP **301** may send a request for provisioning to ECS **404** using link EDGE-11. At operation **9020**, ECS **404** provisions and provides a list of EESs **403** to 5GMS AP **301** using link EDGE-11. At operation **9030**, 5GMS AP **301** requests registration from an EES **403** included in the list of EESs **403** using link EDGE-10. At operation **9040**, EES **403** registers and provides a list and locations of EASs **402** to 5GMS AP **301** using link EDGE-10. At operation **9050**, 5GMS AP **301** may request a service from an EAS **402** included in the list of EASs **402** using link EDGE-9. At operation **9050**, EAS **402** starts running the service and confirms the service to 5GMS AP **301** using link EDGE-9, and 5GMS AP **301** connects to EAS **402** and uses the service

(104) FIG. **10** illustrates an architecture **1000** in which elements from architecture **400** of FIG. **4** are combined with elements from architecture **300** of FIG. **3**. In order to avoid unnecessary duplication, redundant description has been omitted.

(105) In FIG. **10**, 5GMS AS **305** and 5GMS AF **306** as well as ECS **404** and EES **403** may be logical entities. All or some of them may be combined when implemented. EASs **402** may be multiple entities. From the point of view of 5GMS AS **305**, all EAS **402** entities are part of the 5GMS AP **301**. Link M2 provides the media flow between 5GMS AS **305** and 5GMS AP **301**. Because some or all of the application may be run on an EAS **402**, 5GMS AS **305** may be connected to the EAS **402** through 5GMS AP **301**.

(106) Accordingly, in embodiments 5GMS AP **301** may discover the list and location of the EASs **402** directly.

(107) In embodiments, 5GMS AP **301** may discover the capabilities of EASs **402**.

(108) In embodiments, 5GMS AP **301** may request service(s) from EAS **402** directly and instantiate and use those services.

(109) In embodiments, 5GMS AP **301** may perform any above functions without going through UE **303**.

(110) In embodiments, the same resources that UE **303** uses to communicate with the EDN **401** can

be used by the 5GMS AP **301** and no new resources are needed.

(111) In embodiments, architecture **300** may be combined with architecture **400**, providing a mechanism to set up media services on edge servers and providing a media flow between 5GMS AS **305** and EAS **402**.

(112) Accordingly, embodiments may provide a method for discovering the EDN **401** capabilities by the 5GMS AP **301** through new APIs and a call flow wherein the 5GMS AS **305** can discover the list of available edge servers, provision for a subset of them, discover the location and capabilities of the provisioned one, discover more details about a specific EAS **402**, and then request a service from that server, wherein the currently standardized resources can be used to perform the above operations.

(113) Embodiments may provide a method of combining 5G edge data network and 5G media data network where the two architectures are combined and control and data flow are arranged such that part of the media application may be run on an EAS **402** and the session can be established using the standard processes of 5G edge networks and 5G media streaming architecture.

(114) Embodiments corresponding to FIGS. **11-13** may extend the 5G edge architectures discussed above to allow the following: 1. An edge platform architecture extended using a “pseudo” Edge Enable Client **1201** in 5GMS AP **301**. 2. Instantiation of 5GMS AF **305** and 5GMS AS **305** in an EAS **402** 3. Support of MEC host **1202** or a similar function in EAS **402**

(115) FIGS. **11-12** illustrate architecture **1100** and architecture **1200** in which elements from architecture **400** of FIG. **4** are combined with elements from architecture **300** of FIG. **3**, and additional elements are added. In order to avoid unnecessary duplication, redundant description has been omitted.

(116) In FIG. **11**, Edge Discovery Function (EDF) **1101** enables 5GMS AP **301** to discover EASs **402** and their capabilities. One way to realize this is to use a pseudo EEC **1201** as the EDF **1101**. Then EDGE-10, EDGE-11 and EDGE-12 are EDGE-1, EDGE-4 and EDGE-5 respectively, as shown for example in FIG. **12** In embodiments, EDF **1101** can be potentially realized with a solution provided by SA2 or SA5. Edge Orchestrator (EO) **1102** may be an orchestration service for requesting running specific apps on the EAS **402**. EO **1101** may be provided by 5G Network Operator. In embodiments, 5GMS AP **301** Provider may include an EO service function. Edge Host (EH) **1103** may be a service that manages running specific apps on the EAS **402**.

(117) FIG. **12** shows architecture **1200**, which may be an example of architecture **1100** implemented using MEC. In FIG. **12**, EDF **1101** is implemented using EEC functionality and link EDGE-1 is used for discovery. A MEC System Manager **1203** is used as EO **1101**. MEC System manager **1203** can be implemented by 5G network operator, or by the 5GMS AP **301**. The link M1 interface is used as link EDGE-9. A MEC Host **1202** is used as EH **1103**.

(118) FIG. **13** illustrates a process **1300** which may relate to a call flow for discovering Edge Data Network capabilities. Process **1300** may be performed using architecture **1200**, architecture **1300**, or any other architecture as desired.

(119) According to process **1300**, at operation **1310**, 5GMS AP **301** may send a request for provisioning to ECS **404** using EDF **1101** and link EDGE-1. At operation **1320**, ECS **404** provisions and provides a list of EESs **403** to 5GMS AP **301** using link EDGE-1. At operation **1330**, 5GMS AP **301** requests registration from an EES **403** included in the list of EESs **403** using link EDGE-4. At operation **1340**, EES **403** registers and provides a list and locations of EASs **402** to 5GMS AP **301** through EDF **1101** using link EDGE-4. At operation **1350**, 5GMS AP **301** may request a service from an EAS **402** included in the list of EASs **402** using EO **1101** and link EDGE-9. At operation **1350**, EAS **402** starts running the service and confirms the service to 5GMS AP **301** using link EDGE-9, and 5GMS AP **301** connects to EAS **402** and uses the service. For example, EAS **402** starts an instance of 5GMS AF **306** and 5GMS AS **305**, MSH **309** and 5GMS AF **306** and 5GMS AS **305** may set up the media session, and the media streaming may start.

(120) In embodiments, 5GMS AP **301** may discover the list, location, and capabilities of the EASs

402 directly using the existing edge standard.

(121) In embodiments, 5GMS AP **301** may discover the EAS **402** capabilities directly using the existing edge standard.

(122) In embodiments, 5GMS AP **301** may request service(s) from EAS **402** directly and instantiate and use those services using standards such as MEC.

(123) In embodiments, 5GMS AP **301** may perform any above functions without going through UE **303**.

(124) In embodiments, the appropriate EAS **402** instantiates a single 5GMS AF **306** and 5GMS AS **305** and therefore the media will flow through this EAS **402**.

(125) In embodiments, the same resources that UE **303** uses to communicate with the EDN **401** can be used by the 5GMS AP **301** and no new resources are needed.

(126) In embodiments, architecture **300** may be combined with architecture **400**, providing a mechanism to set up media services on edge servers and providing a media flow between 5GMS AS **305** and EAS **402**.

(127) Accordingly, embodiments may provide a method for discovering the 5G edge data network capabilities by the 5GMS AP **301** through existing APIs using a pseudo client in the application and a call flow wherein the 5GMS AP **301** can discover the list of available edge servers, provision for a subset of them, discover the location and capabilities of the provisioned one, discover more details about a specific edge application server, and then request a service from that server using a standard orchestration solution, wherein the currently standardized resources can be used to perform the above operations.

(128) Embodiments may provide a method of combining 5G edge data network, 5G media data network, and MEC architecture, where the three architectures are combined and control and data flow are arranged such that part of the media application may be run on an EAS **402** and the session can be established using the standard processes of 5G edge networks and 5G media streaming architecture.

(129) Embodiments corresponding to FIGS. **14-18** may extend the 5G edge architectures discussed above to include 5G discovery server (DS) **1401** which may include the list of 5GMS AS **305** and, in embodiments, their capabilities. Embodiments relating to FIGS. **14-18** may relate to workflows and procedures to discover the associated 5GMS AF **306** locations and the capabilities of their corresponding 5GMS AS **305** by the 5GMS AP **301** in two stages: 1. Discovery of the list (and in some embodiments the 5GMS AS **305** capabilities) of available 5GMS AFs **306** in the DS **1401** 2. Discovery of media-specific capabilities of a particular 5GMS AS **305**

(130) FIG. **14** illustrates an architecture **1400** which includes some elements from architecture **300** of FIG. **3**, along with an additional element, DS **1401**. In order to avoid unnecessary duplication, redundant description has been omitted.

(131) In FIG. **14**, DS **1401** may be used for the discovery of available 5GMS ASs **305**. as can be seen in FIG. **14**, MSH **309** may communicate with discovery server **1401** using link M10, and 5GMS AP **301** may communicate with DS **1401** using link M9. The 5GMS AP **301** or an external application server may use the DS **1401** to obtain a list of 5GMS AS **305**. Each entry in the DS **1401** may include some or all of the following information: 1. Name and description of 5GMS AS **305** 2. URL of the corresponding 5GMS AF **306** 3. The capabilities of the corresponding 5GMS AS **305**

(132) FIG. **15** illustrates an architecture **1500** which includes some elements from architecture **300** of FIG. **3**, along with DS **1401**. In order to avoid unnecessary duplication, redundant description has been omitted

(133) FIGS. **16-18** illustrates processes **1600**, **1700**, and **1800** which may relate to call flows for discovering network capabilities. Process **1600**, **1700**, and **1800** may be performed using architecture **1400**, architecture **1500**, or any other architecture as desired.

(134) Processes **1600**, **1700**, and **1800** may extend the TS26.501 APIs to enable the discovery of

5G application servers.

(135) Process **1600** relates to a call flow in which 5GMS AP **301** may discover network capabilities. According to process **1600**, at operation **1610**, 5GMS AP **301** may send a request for a list of AFs to DS **1401** using link M9. At operation **1620**, DS **1401** may provide the list of available AFs to 5GMS AP **301** using link M9. At operation **1630**, 5GMS AP **301** may send a request for capabilities to 5GMS AF **306** using link M1. At operation **1640**, 5GMS AF **306** may send a request for capabilities to 5GMS AS **305** using link M3. At operation **1650**, 5GMS AS **305** may send a response including the capabilities to 5GMS AF **306** using link M3. At operation **1660**, 5GMS AF **306** may send a response including the capabilities to 5GMS AP **301** using link M1.

(136) In embodiments, 5GMS Aware Application (AA) **302** included on the UE **303** may discover the network capabilities through 5GMS AP **301**, as shown for example in process **1700** of FIG. 17, and through MSH **309**, as shown for example in process **1800** of FIG. 18.

(137) According to process **1700**, at operation **1701**, 5GMS AA **302** may send a request for a list of AFs to 5GMS AP **301** using link M8. At operation **1702**, 5GMS AP **301** may send a request for a list of AFs to DS **1401** using link M9. At operation **1703**, DS **1401** may provide the list of available AFs to 5GMS AP **301** using link M9. At operation **1704**, 5GMS AP **301** may provide the list of available AFs to 5GMS AA **302** using link M8.

(138) At operation **1705**, 5GMS AA **302** may send a request for capabilities to 5GMS AP **301** using link M8. At operation **1706**, 5GMS AP **301** may send a request for capabilities to 5GMS AF **306** using link M8. At operation **1707**, 5GMS AF **306** may send a request for capabilities to 5GMS AS **305** using link M3. At operation **1708**, 5GMS AS **305** may send a response including the capabilities to 5GMS AF **306** using link M3. At operation **1709**, 5GMS AF **306** may send a response including the capabilities to 5GMS AP **301** using link M1. At operation **1710**, 5GMS AP **301** may send a response including the capabilities to 5GMS AA **302** using link M8.

(139) According to process **1800**, at operation **1801**, 5GMS AA **302** may send a request for a list of AFs to MSH **309** using link M6. At operation **1802**, MSH **309** may send a request for a list of AFs to DS **1401** using link M10. At operation **1803**, DS **1401** may provide the list of available AFs to MSH **309** using link M10. At operation **1804**, MSH **309** may provide the list of available AFs to 5GMS AA **302** using link M6.

(140) At operation **1805**, 5GMS AA **302** may send a request for capabilities to MSH **309** using link M8. At operation **1806**, MSH **309** may send a request for capabilities to 5GMS AF **306** using link M5. At operation **1806**, 5GMS AF **306** may send a request for capabilities to 5GMS AS **305** using link M3. At operation **1808**, 5GMS AS **305** may send a response including the capabilities to 5GMS AF **306** using link M3. At operation **1809**, 5GMS AF **306** may send a response including the capabilities to MSH **309** using link M5. At operation **1810**, MSH **309** may send a response including the capabilities to 5GMS AA **302** using link M6.

(141) Table 7 shows information for entries in the DS **1401**, according to embodiments:

(142) TABLE-US-00007 TABLE 7 Discovery server information Information element Status
Description URL M AF's URL name O The name of Application Server description O A description of the server location O Location of the server capabilities O Maximum capabilities of the Application Server M: Mandatory, O: Optional

(143) Table 8 shows information for application server capabilities, according to embodiments:

(144) TABLE-US-00008 TABLE 8 Application Server capabilities Information element Status
Description Maximum O Maximum request rate from the Request Application Client supported by rate the server. Maximum O The maximum response time Response advertised for the Application time Client's service requests. Availability O Advertised percentage of time the server is available for the Application Client's use. Available O The maximum compute resource Compute available for the Application Client. Available O The maximum graphical compute Graphical resource available for the Compute Application Client. Available O The maximum memory resource Memory available for the Application Client. Available O The maximum storage resource Storage

available for the Application Client. Supported O The OS and architecture environment Flow Control O Flow control capabilities Repository O List and location of repositories Functions O List of built-in functions and workflows, and their performance M: Mandatory, O: Optional

(145) Accordingly, embodiments may provide a method for discovering 5GMS AS **305** by the 5GMS AP **301** through a DS **1401** by which the URL of the 5GMS AF **306** and additional information, including capabilities of the corresponding application servers, may be listed.

(146) Embodiments may provide a method for discovering the 5GMS AS **305** by 5GMS AA **302** through the 5GMS AS **305** by which the 5GMS AA **302** can discover the available the 5GMS ASs **305** and their capabilities.

(147) Embodiments may provide a method for discovering the 5GMS AS **305** by 5GMS AA **302** through the MSH **309** by which the 5GMS AA **302** can discover the available 5GMS ASs **305** and their capabilities.

(148) Embodiments may provide a method of conveying the application server and application function information in the DS **1401**, wherein the URL and other information of 5GMS ASs **305** are listed in the DS **1401**.

(149) Embodiments may provide a method of discovering 5GMS AS **305** environment parameters, as well as built-in functions and supported repositories. wherein information about the 5GMS AS **305** operation system, environment parameters, and related information to run 1st and 3rd party applications, libraries, and functions on the 5GMS AS **305** can be discovered.

(150) Embodiments corresponding to FIGS. **19-23** relate to various possible deployment scenarios to use the network and edge processing in 5GMS architecture. The use of NBMP standard as a specific case of network and edge processing is also addressed.

(151) With reference to FIG. **19**, an NBMP system **1900** includes an NBMP source **1910**, an NBMP workflow manager **1920**, a function repository **1930**, one or more media processing entities **1950**, a media source **1960**, and a media sink **1970**.

(152) The NBMP source **1910** may receive instructions from a third party entity, may communicate with the NBMP workflow manager **1920** via an NBMP workflow API **1992**, and may communicate with the function repository **1930** via a function discovery API **1991**. For example, the NBMP source **1910** may send a workflow description document(s) (WDD) to the NBMP workflow manager **1920**, and may read the function description of functions stored in the function repository **1930**, the functions being media processing functions stored in memory of the function repository **1930** such as, for example, functions of media decoding, feature point extraction, camera parameter extraction, projection method, seam information extraction, blending, post-processing, and encoding. The NBMP source **1910** may include or be implemented by at least one processor and memory that stores code configured to cause the at least processor to perform the functions of the NBMP source **1910**.

(153) The NBMP source **1910** may request the NBMP workflow manager **1920** to create workflow including tasks **1952** to be performed by the one or more media processing entities **1950** by sending the workflow description document, which may include several descriptors, each of which may have several parameters.

(154) For example, the NBMP source **1910** may select functions stored in the function repository **1930** and send the workflow description document to the NBMP workflow manager **1920** that includes a variety of descriptors for description details such as input and output data, required functions, and requirements for the workflow. The workflow description document may include a set of task descriptions and a connection map of inputs and outputs of tasks **1952** to be performed by one or more of the media processing entities **1950**. When the NBMP workflow manager **1920** receives such information from the NBMP source **1910**, the NBMP workflow manager **1920** may create the workflow by instantiating the tasks based on function names and connecting the tasks in accordance with the connection map.

(155) Alternatively or additionally, the NBMP source **1910** may request the NBMP workflow

manager **1920** to create workflow by using a set of keywords. For example, NBMP source **1910** may send the NBMP workflow manager **1920** the workflow description document that may include a set of keywords that the NBMP workflow manager **1920** may use to find appropriate functions stored in the function repository **1930**. When the NBMP workflow manager **1920** receives such information from the NBMP source **1910**, the NBMP workflow manager **1920** may create the workflow by searching for appropriate functions using the keywords that may be specified in a Processing Descriptor of the workflow description document, and use the other descriptors in the workflow description document to provision tasks and connect them to create the workflow.

(156) The NBMP workflow manager **1920** may communicate with the function repository **1930** via a function discovery API **1993**, which may be a same or different API from the function discovery API **1991**, and may communicate with one or more of the media processing entities **1950** via an API **1994** (e.g. an NBMP task API). The NBMP workflow manager **1920** may include or be implemented by at least one processor and memory that stores code configured to cause the at least processor to perform the functions of the NBMP workflow manager **1920**.

(157) The NBMP workflow manager **1920** may use the API **1994** to setup, configure, manage, and monitor one or more tasks **1952** of a workflow that is performable by the one or more media processing entities **1950**. In an embodiment, the NBMP workflow manager **1920** may use the API **1994** to update and destroy the tasks **1952**. In order to configure, manage, and monitor tasks **1952** of the workflow, the NBMP workflow manager **1920** may send messages, such as requests, to one or more of the media processing entities **1950**, wherein each message may have several descriptors, each of which have several parameters. The tasks **1952** may each include media processing functions **1954** and configurations **1953** for the media processing functions **1954**.

(158) In an embodiment, after receiving a workflow description document from the NBMP source **1910** that does not include a list of the tasks (e.g. includes a list of keywords instead of a list of tasks), the NBMP workflow manager **1920** may select the tasks based on the descriptions of the tasks in the workflow description document to search the function repository **1930**, via the function discovery API **1993**, to find the appropriate functions to run as tasks **1952** for a current workflow. For example, the NBMP workflow manager **1920** may select the tasks based on keywords provided in the workflow description document. After the appropriate functions are identified by using the keywords or the set of task descriptions that is provided by the NBMP source **1910**, the NBMP workflow manager **1920** may configure the selected tasks in the workflow by using the API **1994**. For example, the NBMP workflow manager **1920** may extract configuration data from information received from the NBMP source, and configure the tasks **1952** based on the configuration data.

(159) The one or more media processing entities **1950** may be configured to receive media content from the media source **1960**, process the media content in accordance with the workflow, that includes tasks **1952**, created by the NBMP workflow manager **1920**, and output the processed media content to the media sink **1970**. The one or more media processing entities **1950** may each include or be implemented by at least one processor and memory that stores code configured to cause the at least processor to perform the functions of the media processing entities **1950**.

(160) The media source **1960** may include memory that stores media and may be integrated with or separate from the NBMP source **1910**. In an embodiment, the NBMP workflow manager **1920** may notify the NBMP source **1910** when a workflow is prepared and the media source **1960** may transmit media content to the one or more of the media processing entities **1950** based on the notification that the workflow is prepared.

(161) The media sink **1970** may include or be implemented by at least one processor and at least one display that is configured to display the media that is processed by the one or more media processing entities **1950**.

(162) As discussed above, messages from the NBMP Source **1910** (e.g. a workflow description document for requesting creation of a workflow) to the NBMP workflow manager **1920**, and messages (e.g. for causing the workflow to be performed) from the NBMP workflow manager **1920**

to the one or more media processing entities **1950** may include several descriptors, each of which may have several parameters. In cases, communication between any of the components of the NBMP system **1900** using an API may include several descriptors, each of which may have several parameters.

(163) FIGS. **20-23** illustrate architectures **2000**, **2100**, **2200**, and **2300** elements from architecture **300** of FIG. **3** are combined with elements from system **1900**, and additional elements are added. In order to avoid unnecessary duplication, redundant description has been omitted.

(164) FIG. **20** illustrates architecture **2000**, in which network processing is included in the application server. As can be seen in FIG. **20**, NBMP source **1910**, NBMP workflow manager **1920**, and one or more media processing entities (MPE) **1950** are located in the 5GMS AP **301**.

(165) A process for establishing, operation, and tearing down a session may include: 1. 5GMS AA **302** makes a request through M8 to NBMP source **1910**. 2. NBMP source **1910** builds the Workflow Description (WD) and requests the NBMP source **1910** to instantiate the Workflow. 3. NBMP workflow manager **1920** discovers various MPEs **1950** and finds enough number of MPEs **1950** to run the workflow 4. NBMP workflow manager **1920** instantiates the workflow. 5. NBMP workflow manager **1920** responds to NBMP source **1910** with updated WD. 6. NBMP source **1910** responds to 5GMS AA **302** with 5GMS AF **306** and 5GMS AS **305** information. 7. 5GMS AA **302** requests MSH **309** to establish the session. 8. MSH **309** establishes the session and acknowledges 5GMS AA **302**. 9. 5GMS AA **302** start ingesting the content. 10. The session runs. 11. 5GMS AA **302** requests NBMP source **1910** to end the session. 12. NBMP source **1910** request NBMP workflow manager **1920** to end the Workflow. 13. NBMP workflow manager **1920** acknowledges the stopping of the Workflow. 14. NBMP source **1910** acknowledges 5GMS AA **302** the stopping of the workflow. 15. 5GMS AA **302** requests MSH **309** to stop the session.

(166) Table 9 shows the required standard interfaces in this scenario:

(167) TABLE-US-00009 TABLE 9 Required Standard APIs for entire Workflow Processing in Application Server Standard 5GMS M1, M2, M4, M5 Workflow N3 Processing

(168) FIG. **21** illustrates architecture **2100**, in which NBMP source **1910** and NBMP workflow manager **1920** are included in 5GMS AP **301**. As can be seen in FIG. **21**, NBMP source **1910** and NBMP workflow manager **1920** are located in the 5GMS AP **301**, and MPEs **1950** are located in 5GMS AS **305**.

(169) A process for establishing, operation, and tearing down a session may include: 1. 5GMS AA **302** makes a request through M8 to Workflow Source (NBMP source **1910**). 2. NBMP source **1910** builds the Workflow Description (WD) and requests the NBMP workflow manager **1920** to instantiate the Workflow. 3. NBMP workflow manager **1920** discovers 5GMS AS **305** with enough number of MPEs **1950** to run the workflow 4. NBMP workflow manager **1920** instantiates the workflow through 5GMS AS **305**. 5. NBMP workflow manager **1920** responds to NBMP source **1910** with updated WD. 6. NBMP source **1910** responds to 5GMS AA **302** with 5GMS AF **306** and 5GMS AS **305** information. 7. 5GMS AA **302** requests MSH **309** to establish the session. 8. MSH **309** establishes the session and acknowledges 5GMS AA **302**. 9. 5GMS AA **302** start ingesting the content. 10. The session runs. 11. 5GMS AA **302** requests NBMP source **1910** to end the session. 12. NBMP source **1910** request NBMP workflow manager **1920** to end the Workflow. 13. NBMP workflow manager **1920** request 5GMS AS **305** to stop MPEs **1950**. 14. NBMP workflow manager **1920** acknowledges the stopping of the Workflow. 15. NBMP source **1910** acknowledges 5GMS AA **302** the stopping of the workflow. 16. 5GMS AA **302** requests MSH **309** to stop the session.

(170) Table 10 shows the required standard interfaces in this scenario:

(171) TABLE-US-00010 TABLE 10 Required Standard APIs when MPE 1950 in 5GMS AS 305 Standard FLUS M1, M4, M5 Workflow N2, N3 Processing

Note that N2 may be a closed API implemented by the AP-operator agreement.

(172) FIG. **22** illustrates architecture **2200**, in which NBMP workflow manager **1920** and MPE **1950** are included in 5GMS AS **305** 1. 5GMS AA **302** makes a request through M8 to Workflow

Source (NMBP source **1910**). 2. NMBP source **1910** builds the Workflow Description (WD) and discovers 5GMS AS **305** which can perform the media. 3. NMBP source **1910** requests the appropriate 5GMS ASs **305** NMBP workflow manager **1920** to instantiate the Workflow. 4. NMBP workflow manager **1920** instantiates the workflow inside 5GMS AS **305**. 5. NMBP workflow manager **1920** responds to NMBP source **1910** with updated WD. 6. NMBP source **1910** responds to 5GMS AA **302** with 5GMS AF **306** and 5GMS AS **305** information. 7. 5GMS AA **302** requests MSH **309** to establish the session. 8. MSH **309** establishes the session and acknowledges 5GMS AA **302**. 9. 5GMS AA **302** start ingesting the content. 10. The session runs. 11. 5GMS AA **302** requests NMBP source **1910** to end the session. 12. NMBP source **1910** request NMBP workflow manager **1920** of 5GMS AS **305** to end the Workflow. 13. NMBP workflow manager **1920** acknowledges the stopping of the Workflow. 14. NMBP source **1910** acknowledges 5GMS AA **302** the stopping of the workflow. 15. 5GMS AA **302** requests MSH **309** to stop the session.

(173) Table 11 shows the required standard interfaces in this scenario:

(174) TABLE-US-00011 TABLE 11 NMBP workflow manager 1920 and MPE 1950 in 5GMS AS 305 Standard FLUS M1, M4, M5 Workflow N1, N3

(175) FIG. 23 illustrates architecture 2300, in which NMBP source **1910** is included in MSH **309**, and NMBP workflow manager **1920** and MPE **1950** are included in 5GMS AS **305**.

(176) A process for establishing, operation, and tearing down a session may include: 1. 5GMS AA **302** requests MSH **309** through M6 to start a session 2. NMBP source **1910** builds the Workflow Description (WD) and discovers 5GMS AS **305** which can perform the media through M5 or other means. 3. MSH **309**'s NMBP source **1910** requests the NMBP workflow manager **1920** of the appropriate 5GMS AS **305** to instantiate the Workflow. 4. NMBP workflow manager **1920** instantiates the workflow inside 5GMS AS **305**. 5. NMBP workflow manager **1920** responds to MSH **309** with updated WD. 6. MSH **309** responds to 5GMS AA **302**. 7. 5GMS AA **302** requests MSH **309** to establish the session. 8. MSH **309** establishes the session and acknowledges 5GMS AA **302**. 9. 5GMS AA **302** start ingesting the content. 10. The session runs. 11. 5GMS AA **302** requests MSH **309** to end the session. 12. MSH **309**'s NMBP source **1910** request NMBP workflow manager **1920** of 5GMS AS **305** to end the Workflow. 13. NMBP workflow manager **1920** acknowledges the stopping of the Workflow. 14. MSH **309** acknowledges 5GMS AA **302** the stopping of the workflow.

(177) Table 12 shows the required standard interfaces in this scenario:

(178) TABLE-US-00012 TABLE 12 Workflow Source in MSH 309, NMBP workflow manager 1920, and MPE 1950 in 5GMS AS 305 Standard FLUS M1, M4, M5 Workflow N4

Note that M5 is with the support of Workflow Manager APIs.

(179) Table 13 shows a summary of deployment scenarios.

(180) TABLE-US-00013 TABLE 13 Summary of the deployment scenarios Scenario Standard API All Workflow module in 5GMS M1, M2, M4, M5 Application Server Workflow N3 Processing MPE 1950 in 5GMS AS 305 FLUS M1, M4, M5 Workflow N2, N3 Processing NMBP workflow manager 1920 FLUS M1, M4, M5 and MPE 1950 in 5GMS AS 305 Workflow N1, N3 Processing NMBP source 1910 in MSH FLUS M1, M4, M5 309, and both NMBP workflow Workflow N3 manager 1920 and MPE 1950 in 5GMS AS 305

Note that N2 may be a closed API implemented by the AP-operator agreement. Also, note that M5 is with the support of NBMP Workflow Manager APIs.

(181) It is possible to deploy other variations of the above scenarios. For instance, the NMBP workflow manager **1920** and MPE **1950** can be supported in 5GMS AS **305** with the NMBP source **1910** is supported in 5GMS AA **302**, or all NMBP source **1910**, NMBP workflow manager **1920** and MPE **1950** are supported in 5GMS AS **305**.

(182) In the 5GMS general architecture (5GMSA), more than one 5GMS AF **306** and 5GMS AS **305** pair may exist. In those cases, NMBP source **1910** and/or NMBP workflow manager **1920** must discover the capabilities of multiple 5GMS AF **306** and 5GMS AS **305** pairs for running the

network media workflow on the most suitable 5GMS AS **305**.

(183) Accordingly, embodiments may provide a method for deployment of any network or edge-based media processing such as NBMP workflow management in 5GSA environment wherein 4 different scenarios is considered, including implementing a) Entire network processing modules in Application Server, b) media processing services in 5GMS AS **305** c) workflow manager and media processing services in 5GMS AS **305**, and d) NBMP source **1910** in MSH **309**, and both NBMP workflow manager **1920** and MPE **1950** are in 5GMS AS **305**. In each scenario the workflow processing modules may be implemented in a different module of the 5GSM architecture, wherein for each scenario the APIs between network processing and 5GSA are defined, where APIs are divided to the APIs according to the 3GPP 5GSA standards, the internal APIs for each module and the private APIs between the service provider and the operator.

(184) Embodiments may provide methods including separate call flow for the establishment, management, and tears down of Workflow processing and 5GSA joint session for each of the four scenarios of method **1**, wherein each case's call flow, a workflow session, and a FLUS session are set up, where appropriate information is exchanged through the APIs defined in method **1** to establish and manage a joint session where the content is up-streamed from the device to the network using 5GSA and then it is processed in a cloud or edge service using the network workflow processing.

(185) Embodiments may provide methods for implementing the NBMP standard as the network workflow processing, for deployment with 5GSA.

(186) FIG. **24** is a flowchart is an example process **2400** for managing capabilities of a media streaming network. In some implementations, one or more process blocks of FIG. **2400** may be performed by one or more elements of any of the systems or architectures discussed above.

(187) As shown in FIG. **24**, process **2400** may include receiving a capability request for media streaming capabilities of an edge data network (EDN) (block **2402**). In embodiments, the EDN may correspond to EDN **401** discussed above.

(188) As further shown in FIG. **24**, process **2400** may include determining the media streaming capabilities of the EDN (block **2404**).

(189) As further shown in FIG. **24**, process **2400** may include transmitting a capability response based on the determined media streaming capabilities (block **2406**).

(190) As further shown in FIG. **24**, process **2400** may include receiving a media processing workflow request based on the capability response (block **2408**).

(191) As further shown in FIG. **24**, process **2400** may include establishing a media streaming session according to the media processing workflow request (block **2410**).

(192) As further shown in FIG. **24**, process **2400** may include streaming media content based on the media streaming session (block **2412**).

(193) In embodiments, the media streaming capabilities relate to at least one of available hardware resources, environmental characteristics of the EDN, a current throughput of an edge server associated with the EDN, an current delay range of the edge server, available media processing function libraries, functional descriptions of one or more functions, and characteristics of the one or more functions.

(194) In embodiments, the receiving of the capability request may include receiving, by an edge application server (EAS), a first capability request from a media streaming handler of a client device, and the determining of the media streaming capabilities may include transmitting, by the EAS, a second capability request to at least one of a media streaming application function or a media streaming application server included in the EAS. In embodiments, the EAS may correspond to EAS **402** discussed above.

(195) In embodiments, the first capability request may be transmitted using an edge application programming interface (API), and the second capability request is transmitted using a media streaming API.

(196) In embodiments, the capability request may be received by an edge configuration server (ECS) from a media streaming application provider (AP). In embodiments, the AP may correspond to 5GMS AP **301** discussed above, and the ECS may correspond to ECS **404** discussed above.

(197) In embodiments, the determining of the media streaming capabilities may include transmitting, from the ECS to the AP, a list of a plurality of edge enabler servers (EES); receiving, by the ECS from the AP, a registration request for an EES from among the plurality of EESs; and transmitting, from the EES to the AP, a list of a plurality of EASs including the media streaming capabilities. In embodiments, the EES may correspond to EES **403** discussed above.

(198) In embodiments, the media processing workflow request may be transmitted from the AP to an EAS from among the plurality of EASs based on the list of the plurality of EASs.

(199) In embodiments, the list of the plurality of EASs may be transmitted to the AP through an edge discovery function (EDF). In embodiments, the EDG may correspond to EDF **1101** discussed above.

(200) In embodiments, the EDF may be included in the AP.

(201) Although FIG. **24** shows example blocks of process **2400**, in some implementations, process **2400** may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. **24**. Additionally, or alternatively, two or more of the blocks of process **2400** may be performed in parallel.

(202) Further, the example methods according to embodiments of the instant application may be implemented by processing circuitry (e.g., one or more processors or one or more integrated circuits). In one example, the one or more processors execute a program that is stored in a non-transitory computer-readable medium to perform one or more of the example methods.

(203) The techniques described above can be implemented as computer software using computer-readable instructions and physically stored in one or more computer-readable media.

(204) Embodiments of the present disclosure may be used separately or combined in any order. Further, each of the embodiments (and methods thereof) may be implemented by processing circuitry (e.g., one or more processors or one or more integrated circuits). In one example, the one or more processors execute a program that is stored in a non-transitory computer-readable medium.

(205) The foregoing disclosure provides illustration and description, but is not intended to be exhaustive or to limit the implementations to the precise form disclosed. Modifications and variations are possible in light of the above disclosure or may be acquired from practice of the implementations.

(206) As used herein, the term component is intended to be broadly construed as hardware, firmware, or a combination of hardware and software.

(207) Even though combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of possible implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one claim, the disclosure of possible implementations includes each dependent claim in combination with every other claim in the claim set.

(208) No element, act, or instruction used herein should be construed as critical or essential unless explicitly described as such. Also, as used herein, the articles “a” and “an” are intended to include one or more items, and may be used interchangeably with “one or more.” Furthermore, as used herein, the term “set” is intended to include one or more items (e.g., related items, unrelated items, a combination of related and unrelated items, etc.), and may be used interchangeably with “one or more.” Where only one item is intended, the term “one” or similar language is used. Also, as used herein, the terms “has,” “have,” “having,” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

Claims

1. A method of managing capabilities of a media streaming network using at least one processor, the method comprising: receiving a capability request for media streaming capabilities of an edge data network (EDN); determining the media streaming capabilities of the EDN; transmitting a capability response based on the determined media streaming capabilities; receiving a media processing workflow request based on the capability response; establishing a media streaming session according to the media processing workflow request; and streaming media content based on the media streaming session, wherein the capability request is received by a 5G media streaming (MS) application function (AF) and from a media streaming application provider (AP), wherein a confirmation, based on a list of a plurality of edge application servers (EASs) and any of environmental characteristics, a throughput and delay range, media processing function libraries, and input/output formats of functions, is transmitted from the 5GMS AF and to the AP through an edge discovery function (EDF) included in the AP, wherein a first capability request and a second capability request are transmitted by different application programming interfaces (APIs), and wherein the capability request is one of the first capability request and the second capability request.
2. The method of claim 1, wherein the media streaming capabilities relate to at least one of media content transcoding, content protection, advertisement insertion, closed captioning, available hardware resources, environmental characteristics of the EDN, a current throughput of an edge server associated with the EDN, and a current delay range of the edge server.
3. The method of claim 1, wherein the receiving of the capability request comprises receiving, by an edge application server (EAS), the first capability request from a media streaming handler of a client device.
4. The method of claim 3, wherein the determining of the media streaming capabilities comprises transmitting, by the EAS, the second capability request to at least one of a media streaming application function or a media streaming application server included in the EAS.
5. The method of claim 1, wherein the capability request is received by an edge configuration server (ECS).
6. The method of claim 5, wherein the determining of the media streaming capabilities comprises: transmitting, from the ECS to the AP, a list of a plurality of edge enabler servers (EES); receiving, by the ECS from the AP, a registration request for an EES from among the plurality of EESs; and transmitting, from the EES to the AP, a list of a plurality of edge application servers (EAS) including the media streaming capabilities.
7. The method of claim 6, wherein the media processing workflow request is transmitted from the AP to an EAS from among the plurality of EASs based on the list of the plurality of EASs.
8. The method of claim 1, wherein the first capability request is transmitted using an edge API.
9. The method of claim 8, wherein the second capability request is transmitted using a media streaming API.
10. A device for managing capabilities of a media streaming network, the device comprising: at least one memory configured to store program code; and at least one processor configured to read the program code and operate as instructed by the program code, the program code including: first receiving code configured to cause the at least one processor to receive a capability request for media streaming capabilities of an edge data network (EDN); determining code configured to cause the at least one processor to determine the media streaming capabilities of the EDN; first transmitting code configured to cause the at least one processor to transmit a capability response based on the determined media streaming capabilities; second receiving code configured to cause the at least one processor to receive a media processing workflow request based on the capability response; establishing code configured to cause the at least one processor to establish a media

streaming session according to the media processing workflow request; streaming code configured to cause the at least one processor to stream media content based on the media streaming session, wherein the capability request is received by a 5G media streaming (MS) application function (AF) and from a media streaming application provider (AP), wherein a confirmation, based on a list of a plurality of edge application servers (EASs) and any of environmental characteristics, a throughput and delay range, media processing function libraries, and input/output formats of functions, is transmitted from the 5GMS AF and to the AP through an edge discovery function (EDF) included in the AP, wherein a first capability request and a second capability request are transmitted by different application programming interfaces (APIs), and wherein the capability request is one of the first capability request and the second capability request.

11. The device of claim 10, wherein the media streaming capabilities relate to at least one of media content transcoding, content protection, advertisement insertion, closed captioning, available hardware resources, environmental characteristics of the EDN, a current throughput of an edge server associated with the EDN, and a current delay range of the edge server.

12. The device of claim 10, wherein the first receiving code further comprises third receiving code configured to cause the at least one processor to receive, by an edge application server (EAS), the first capability request from a media streaming handler of a client device.

13. The device of claim 12, wherein the determining code further comprises second transmitting code configured to cause the at least one processor to transmit, by the EAS, the second capability request to at least one of a media streaming application function or a media streaming application server included in the EAS.

14. The device of claim 10, wherein the capability request is received by an edge configuration server (ECS).

15. The device of claim 14, wherein the determining of the media streaming capabilities comprises: second transmitting code configured to cause the at least one processor to transmit, from the ECS to the AP, a list of a plurality of edge enabler servers (EES); fourth receiving code configured to cause the at least one processor to receive, by the ECS from the AP, a registration request for an EES from among the plurality of EESs; and third transmitting code configured to cause the at least one processor to transmit, from the EES to the AP, a list of a plurality of edge application servers (EAS) including the media streaming capabilities.

16. The device of claim 15, wherein the media processing workflow request is transmitted from the AP to an EAS from among the plurality of EASs based on the list of the plurality of EASs.

17. The device of claim 15, wherein the first capability request is transmitted using an edge application programming interface (API).

18. The device of claim 17, wherein the second capability request is transmitted using a media streaming API.

19. A non-transitory computer-readable medium storing instructions, the instructions comprising: one or more instructions that, when executed by one or more processors of a device for managing capabilities of a media streaming network, cause the one or more processors to: receive a capability request for media streaming capabilities of an edge data network (EDN); determine the media streaming capabilities of the EDN; transmit a capability response based on the determined media streaming capabilities; receive a media processing workflow request based on the capability response; establish a media streaming session according to the media processing workflow request; and stream media content based on the media streaming session, wherein the capability request is received by a 5G media streaming (MS) application function (AF) from a media streaming application provider (AP), wherein a confirmation, based on a list of a plurality of edge application servers (EASs) and any of environmental characteristics, a throughput and delay range, media processing function libraries, and input/output formats of functions, is transmitted from the 5GMS AF and to the AP through an edge discovery function (EDF) included in the AP, wherein a first capability request and a second capability request are transmitted by different application

programming interfaces (APIs), and wherein the capability request is one of the first capability request and the second capability request.

20. The non-transitory computer-readable medium of claim 19, wherein the media streaming capabilities relate to at least one media content transcoding, content protection, advertisement insertion, closed captioning, of available hardware resources, environmental characteristics of the EDN, a current throughput of an edge server associated with the EDN, and a current delay range of the edge server.
