

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282502

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ARASE; Kunio

TRANSMISSION DEVICE FOR UNMANNED AERIAL VEHICLE

Abstract

A transmission device for an unmanned aerial vehicle (UAV), wherein arms driving propellers are positionable to not interfere with an air cleaner and a radiator. A transmission device for a UAV in which arms are positioned on a machine body upper section and propellers are driven using a straight-four engine, the transmission device including a drive gear that is attached to a crankshaft; a clutch shaft drive gear that meshes with the drive gear; a bevel gear that drives a drive shaft; a drive shaft base gear that is driven by the bevel gear; a top section gear train that includes a drive shaft main gear, a left sub-gear meshing with the main gear, a reverse gear meshing with the main gear, and a right sub-gear meshing with the reverse gear; first and second bevel gears that mesh with the left sub-gear and drive the first and second arms.

Inventors: ARASE; Kunio (Hamamatsu-shi, Shizuoka, JP)

Applicant: ARASE AIZAWA AEROSPATIALE LLC (Hamamatsu-shi, Shizuoka, JP)

Family ID: 84546029

Appl. No.: 18/861775

Filed (or PCT Filed): October 02, 2023

PCT No.: PCT/JP2023/035886

Foreign Application Priority Data

JP 2022-163594

Oct. 11, 2022

Publication Classification

Int. Cl.: B64U50/27 (20230101); B64U10/14 (20230101); B64U50/11 (20230101)

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a transmission system for an unmanned aerial vehicle, and more specifically, to a transmission system for an unmanned aerial vehicle that allows propeller-driving arms extending from the airframe to be arranged in a way that prevents interference with radiators or air cleaners installed on the upper part of the unmanned aerial vehicle, without raising the positions of the arms.

BACKGROUND OF THE INVENTION

[0002] As an example, Patent Document 1 (Japanese Patent No. 6932411) discusses an unmanned aerial vehicle with a two-cylinder engine. When constructing a new unmanned aerial vehicle (quadcopter) with a four-cylinder engine, replacing the two-cylinder engine of the aircraft, the increased sizes of the air cleaner and radiator would cause interference with the four arms that drive the propellers. If the height of the drive shaft is increased to raise the mounting positions of the arms, interference between the arms and the air cleaner or radiator can be avoided, but the overall height of the airframe will increase. If the height of the airframe is increased, both the transportability of the airframe to the airfield and the ability to load cargo and equipment onto the lower part of the airframe would be compromised.

PRIOR-ART DOCUMENT

Patent Document

[0003] Patent document 1: Japanese Patent No. 6932411

SUMMARY OF THE INVENTION

Technical Problem

[0004] To overcome the issues of the prior art, the present invention aims to provide a transmission system for an unmanned aerial vehicle that allows the propeller-driving arms to be arranged in a way that prevents them from interfering with the air cleaner or radiator.

Solution to Problem

[0005] A transmission system for an unmanned aerial vehicle according to the present invention is provided for the unmanned aerial vehicle, which includes an airframe, four arms, namely a first arm, a second arm, a third arm, and a fourth arm, arranged on the airframe in a clockwise direction, propellers provided on each end of the respective arms, and an inline four-cylinder engine that drives the propellers. The transmission system includes the following components: [0006] a drive gear mounted on a crankshaft of the inline four-cylinder engine: [0007] a driven gear mounted on a clutch shaft, which meshes with the drive gear: [0008] a bevel gear mounted on the clutch shaft via a centrifugal clutch, which drives a drive shaft perpendicular to the clutch shaft; [0009] a base gear mounted on the drive shaft, driven by the bevel gear: [0010] a top gear assembly, which includes: [0011] a main gear mounted on the drive shaft: [0012] a left sub-gear that meshes with the main gear: [0013] a reverse gear that meshes with the main gear: [0014] a right sub-gear that meshes with the reverse gear: [0015] a first bevel gear and a second bevel gear, each meshing with the left sub-gear, wherein the first bevel gear drives the first arm, and the second bevel gear drives the second arm: and [0016] a third bevel gear and a fourth bevel gear, each meshing with the right sub-gear, wherein the third bevel gear drives the third arm, and the fourth bevel gear drives the fourth arm.

[0017] The inline four-cylinder engine is arranged with the crankshaft positioned laterally, oriented

right and left relative to the airframe.

[0018] The inline four-cylinder engine is arranged with the pistons positioned horizontally.

[0019] An air cleaner is positioned on an upper front portion of the airframe, and a radiator is positioned on an upper rear portion of the airframe.

Advantageous Effects of the Invention

[0020] The transmission system of the unmanned aerial vehicle according to the present invention includes a top gear assembly including the main gear mounted on the drive shaft, the left sub-gear meshing with the main gear, the inverting gear meshing with the main gear, and the right sub-gear meshing with the inverting gear. This arrangement of the top gear assembly allows the first arm and the second arm, extending to the left rear and left front of the airframe respectively, and the third arm and the fourth arm, extending to the right front and right rear of the airframe respectively, to be spaced apart in the lateral direction. The spacing between the first arm and the fourth arm, as well as between the second arm and the third arm, can be widened, allowing the air cleaner and the radiator to be placed in these spaces without interfering with the arms.

[0021] The inline four-cylinder engine is arranged with the crankshaft positioned laterally, oriented right and left relative to the airframe, making it easier to achieve lateral balance of the airframe compared to an arrangement where the crankshaft is oriented longitudinally.

[0022] The inline four-cylinder engine is arranged with the pistons and cylinders positioned horizontally, so that the pistons and cylinders are horizontal, and the crankshaft is positioned laterally. This arrangement reduces the height of the airframe compared to an arrangement where the pistons and cylinders are positioned vertically, and the crankshaft is positioned laterally.

[0023] Even when the air cleaner is positioned at the upper front of the airframe and the radiator is positioned at the upper rear of the airframe, the arms can be arranged to avoid interference with the air cleaner and radiator without raising the height of the drive shaft, allowing the height of the airframe to be reduced. The positions of the second arm and the third arm can be set lower than the top of the air cleaner in a side view.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is an external view of an unmanned aerial vehicle equipped with a transmission system according to the present invention.

[0025] FIG. 2 is a perspective view of an airframe with the propellers, arms, cover, and feet removed.

[0026] FIG. 3 is a perspective view of the airframe with a gear assembly on the upper part of the airframe in FIG. 2 exposed by removing the covering components.

[0027] FIG. 4 is an enlarged perspective view of the transmission system according to the present invention.

[0028] FIG. 5 is a perspective view of the airframe shown in FIG. 3 with the propellers, arms, and feet mounted.

[0029] FIG. 6 is a plan view of the airframe shown in FIG. 5.

[0030] FIG. 7 is a left side view of the airframe shown in FIG. 5.

DESCRIPTION OF THE EMBODIMENTS

[0031] Hereinafter, a transmission system **100** of an unmanned aerial vehicle **200** according to the present invention will be described in detail with reference to the accompanying drawings.

Embodiments

[0032] FIG. 1 is an external view of an unmanned aerial vehicle **200** equipped with the transmission system **100** according to the present invention. The unmanned aerial vehicle **200** has four propellers **6** on the upper part of the airframe **5**. The airframe **5** is equipped with a pair of feet

38 on its lower part and is covered by a cover **39**. In a plan view of the airframe **5**, the propellers **6** include a first propeller **1**, a second propeller **2**, a third propeller **3**, and a fourth propeller **4** in a clockwise direction. The airframe **5** also features a first arm **7**, a second arm **8**, a third arm **9**, and a fourth arm **10**, which are arranged in a roughly diagonal pattern on its upper part, with the propellers **6** mounted at the ends of the respective arms and configured to rotate horizontally. Thus, the unmanned aerial vehicle **200** is also called a quadcopter. Each propeller **6** has two blades **6a** and is designed to overlap with the adjacent propellers and to be foldable. All four propellers are positioned at the same height.

[0033] FIG. **2** is a perspective view of the airframe **5** with the propellers, arms, cover, and feet removed. The airframe **5** includes an air cleaner **11** arranged at the upper front, a radiator **12** positioned at the upper rear, and a muffler **13** extending towards the rear. An inline four-cylinder engine **15** is arranged with a crankshaft **14** positioned laterally, oriented right and left relative to the airframe **5**. The first arm **7**, second arm **8**, third arm **9**, and fourth arm **10** are removed in the figure. Therefore, relative to the forward direction of the airframe **5**, the connection part **7a** of the first arm **7** protrudes to the left rear, the connection part **8a** of the second arm **8** protrudes to the left front, the connection part **9a** of the third arm **9** protrudes to the right front, and the connection part **10a** of the fourth arm **10** protrudes to the right rear.

[0034] FIG. **3** is a perspective view of the airframe **5** with the gear assembly on the upper part of the airframe **5** in FIG. **2** exposed by removing the covering components. The base parts of the connection part **7a** of the first arm **7**, which protrudes to the left rear, and the connection part **8a** of the second arm **8**, which protrudes to the left front, are arranged to be laterally separated from the base parts of the connection part **9a** of the third arm **9**, which protrudes to the right front, and the connection part **10a** of the fourth arm **10**, which protrudes to the right rear, relative to the forward direction of the airframe **5**. This arrangement allows the first arm **7**, protruding to the left rear, and the fourth arm **10**, protruding to the right rear, to be positioned in a way that prevents them from colliding with the radiator **12**. Similarly, the second arm **8**, protruding to the left front, and the third arm **9**, protruding to the right front, can be positioned to prevent them from colliding with the air cleaner **11**.

[0035] FIG. **4** is an enlarged perspective view of the transmission system **100** according to the present invention. The first propeller **1**, second propeller **2**, third propeller **3**, and fourth propeller **4** are driven by an inline four-cylinder engine **15**. The inline four-cylinder engine **15** includes a first piston **16**, second piston **17**, third piston **18**, and fourth piston **19**. Each piston is positioned horizontally, which helps to reduce the height of the airframe **5**. The crankshaft **14** is positioned laterally, oriented right and left relative to the airframe **5**. The crankshaft **14** rotates due to the intake, compression, combustion, and exhaust motions of each piston. The crankshaft **14** is provided with a drive gear **20**, which rotates along with the crankshaft **14**.

[0036] The crankshaft **14** is accompanied by a horizontally aligned clutch shaft **23** that is equipped with a driven gear **21** that meshes with the drive gear **20**. When the rotation of the driven gear **21**, which meshes with the drive gear **20**, becomes constant, an internal centrifugal clutch **22** within the driven gear **21** is activated, causing a follower gear **37** to rotate, which in turn rotates a bevel gear **24** mounted on the clutch shaft **23**. The rotation of the bevel gear **24** rotates causes a base gear **26**, mounted on a vertical drive shaft **25** perpendicular to the clutch shaft **23**, to rotate. The rotation of the base gear **26** then causes a main gear **27**, mounted on the drive shaft **25**, to rotate.

[0037] The rotation of the main gear **27** causes a left sub-gear **28**, which is mounted on the left sub-drive shaft **29** and meshes with the main gear **27**, to rotate. Simultaneously, a reverse gear **30**, which also meshes with the main gear **27**, rotates as well. The rotation of the reverse gear **30** causes a right sub-gear **31**, which is mounted on a right sub-drive shaft **32** and meshes with the reverse gear **30**, to rotate. The main gear **27**, left sub-gear **28**, reverse gear **30**, and right sub-gear **31** are collectively referred to as a top gear assembly **40**. Instead of driving the first to fourth arms directly from the main gear **27**, the driving force can be distributed between the left sub-gear **28** and the

right sub-gear **31** to drive the arms.

[0038] The rotation of the left sub-gear **28** subsequently causes a first bevel gear **33**, which meshes with the left sub-gear **28**, to rotate, thereby driving a first arm **7**. Similarly, the rotation of the left sub-gear **28** causes a second bevel gear **34**, which meshes with the left sub-gear **28**, to rotate, thereby driving a second arm **8**. The rotation of the right sub-gear **31** causes a third bevel gear **35**, which meshes with the right sub-gear **31**, to rotate, thereby driving a third arm **9**. Likewise, the rotation of the right sub-gear **31** causes a fourth bevel gear **36**, which meshes with the right sub-gear **31**, to rotate, thereby driving a fourth arm **10**.

[0039] FIG. **5** is a perspective view of the airframe **5** shown in FIG. **3** with the propellers, arms, and feet mounted. As shown in the figure, the first arm **7**, which protrudes to the left rear, and the fourth arm **10**, which protrudes to the right rear, can be positioned so as not to interfere with the radiator **12**. Likewise, the second arm **8**, which protrudes to the left front, and the third arm **9**, which protrudes to the right front, can be positioned so as not to interfere with the air cleaner **11**.

[0040] FIG. **6** is a plan view of the airframe **5** shown in FIG. **5**. As shown in the figure, a top gear assembly **40**, which includes the main gear **27**, the left sub-gear **28** that meshes with the main gear **27**, the reverse gear **30** that meshes with the main gear **27**, and the right sub-gear **31** that meshes with the reverse gear **30**, is provided. This arrangement allows the first arm and second arm, which extend to the left rear and left front respectively, and the third arm and fourth arm, which extend to the right front and right rear respectively, to be positioned apart in the lateral direction. Therefore, the first arm **7**, which protrudes to the left rear, and the fourth arm **10**, which protrudes to the right rear, can be positioned so as not to interfere with the radiator **12**. Likewise, the second arm **8**, which protrudes to the left front, and the third arm **9**, which protrudes to the right front, can be positioned so as not to interfere with the air cleaner **11**.

[0041] FIG. **7** is a left side view of the airframe **5** shown in FIG. **5**. The inline four-cylinder engine **15** is arranged with the crankshaft **14** oriented laterally relative to the airframe **5**, making it easier to achieve left-right balance of the airframe. The inline four-cylinder engine **15** is arranged with the pistons positioned horizontally, which reduces the height of the aircraft compared to positioning the pistons vertically. The air cleaner **11** is positioned at the upper front of the airframe **5**, and the radiator **12** is positioned at the upper rear. The top gear assembly **40** allows the arms to avoid interference with the air cleaner **11** and radiator **12** as positioned without increasing the height of the drive shaft **25**. In a side view, it can be seen that the second arm **8** is positioned lower than the top of the air cleaner **11**.

INDUSTRIAL APPLICABILITY

[0042] The present invention is suitable as a transmission system for unmanned aerial vehicles, allowing the propeller drive arms to avoid interference with the radiator or air cleaner without raising their position.

DESCRIPTION OF REFERENCE SIGNS

[0043] **1**. First propeller [0044] **2**. Second propeller [0045] **3**. Third propeller [0046] **4**. Fourth propeller [0047] **5**. Airframe [0048] **6**. Propeller [0049] **6a**. Blade [0050] **7**. First arm [0051] **7a**. Connection part [0052] **8**. Second arm [0053] **8a**. Connection part [0054] **9**. Third arm [0055] **9a**. Connection part [0056] **10**. Fourth arm [0057] **10a**. Connection part [0058] **11**. Air cleaner [0059] **12**. Radiator [0060] **13**. Muffler [0061] **14**. Crankshaft [0062] **15**. Inline four-cylinder engine [0063] **16**. First piston [0064] **17**. Second piston [0065] **18**. Third piston [0066] **19**. Fourth piston [0067] **20**. Drive gear [0068] **21**. Driven gear [0069] **22**. Centrifugal clutch [0070] **23**. Clutch shaft [0071] **24**. Bevel gear [0072] **25**. Drive shaft [0073] **26**. Base gear [0074] **27**. Main gear [0075] **28**. Left sub-gear [0076] **29**. Left sub-drive shaft [0077] **30**. Reverse gear [0078] **31**. Right sub-gear [0079] **32**. Right sub-drive shaft [0080] **33**. First bevel gear [0081] **34**. Second bevel gear [0082] **35**. Third bevel gear [0083] **36**. Fourth bevel gear [0084] **37**. Follower gear [0085] **38**. Foot [0086] **39**. Cover [0087] **40**. Top gear assembly [0088] **100**. Transmission system [0089] **200**. Unmanned aerial vehicle

Claims

1. A transmission system for an unmanned aerial vehicle, the unmanned aerial vehicle including an airframe; four arms, namely a first arm, a second arm, a third arm, and a fourth arm arranged on the airframe in a clockwise direction; propellers provided on each end of the respective arms; and an inline four-cylinder engine that drives the propellers; the transmission system comprising: a drive gear mounted on a crankshaft of the inline four-cylinder engine; a driven gear mounted on a clutch shaft, meshing with the drive gear; a bevel gear mounted on the clutch shaft via a centrifugal clutch, driving a drive shaft perpendicular to the clutch shaft; a base gear mounted on the drive shaft and driven by the bevel gear; a top gear assembly comprising: a main gear mounted on the drive shaft; a left sub-gear meshing with the main gear; a reverse gear meshing with the main gear; and a right sub-gear meshing with the reverse gear; a first bevel gear and a second bevel gear, each meshing with the left sub-gear, the first bevel gear driving the first arm and the second bevel gear driving the second arm; and a third bevel gear and a fourth bevel gear, each meshing with the right sub-gear, the third bevel gear driving the third arm and the fourth bevel gear driving the fourth arm.
 2. The transmission system for the unmanned aerial vehicle according to claim 1, wherein the inline four-cylinder engine is arranged with the crankshaft positioned laterally, oriented right and left relative to the airframe.
 3. The transmission system for the unmanned aerial vehicle according to claim 1, wherein the inline four-cylinder engine is arranged with pistons positioned horizontally.
 4. The transmission system for the unmanned aerial vehicle according to claim 1, wherein an air cleaner is positioned on an upper front portion of the airframe, and a radiator is positioned on an upper rear portion of the airframe.
-