

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282506

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Sinclair; Ashley et al.

BOXING MACHINE

Abstract

A boxing machine (1) comprises a first boxing station (100A) and a second boxing station (100B). The boxing machine (1) further comprises a product conveyor (200) extending from a product inlet (202) to the first boxing station (100A) and from the first boxing station (100A) to the second boxing station (100B). The boxing machine (1) further comprises a box conveyor (300) extending from a box inlet (302) to the first boxing station (100A) and from the first boxing station (100A) to the second boxing station (100B). The first boxing station (100A) is configured to insert a first set of products (2) from the product conveyor (200) to a sideways-oriented box (3) on the box conveyor (300). The second boxing station (100B) is configured to insert a second set of products (2) to the sideways-oriented box (3) on the box conveyor (300).

Inventors: Sinclair; Ashley (Sheffield, South Yorkshire, GB), Beardsmore; Darren (Sheffield, South Yorkshire, GB)

Applicant: GRIPPLE AUTOMATION LIMITED (Sheffield, South Yorkshire, GB)

Family ID: 1000008641569

Appl. No.: 18/702580

Filed (or PCT Filed): October 17, 2022

PCT No.: PCT/IB2022/059931

Foreign Application Priority Data

GB	2114889.5	Oct. 19, 2021
GB	2215070.0	Oct. 13, 2022

Publication Classification

Int. Cl.: B65B5/02 (20060101); B65B5/10 (20060101); B65B35/36 (20060101); B65B35/50 (20060101)

U.S. Cl.:

CPC B65B5/024 (20130101); B65B5/106 (20130101); B65B35/36 (20130101); B65B35/50 (20130101);

Background/Summary

FIELD OF THE INVENTION

[0001] Embodiments of the present invention relate to a boxing machine. In particular, but not exclusively, they relate to a boxing machine for inserting multiple products into boxes.

BACKGROUND TO THE INVENTION

[0002] Boxing machines for inserting multiple products into boxes are known. Such machines are also referred to as end of line packaging machines.

[0003] It is challenging to design a boxing machine that can operate at a high speed without frequent jams.

BRIEF DESCRIPTION OF VARIOUS EMBODIMENTS OF THE INVENTION

[0004] According to an aspect of the invention there is provided a boxing machine comprising:

[0005] a first boxing station; [0006] a second boxing station; [0007] from the first boxing station to the second boxing station; and [0008] a box conveyor extending from a box inlet to the first boxing station and from the first boxing station to the second boxing station, [0009] wherein the first boxing station is configured to insert a first set of products from [0010] the product conveyor to a sideways-oriented box on the box conveyor, and [0011] wherein the second boxing station is configured to insert a second set of products to the sideways-oriented box on the box conveyor.

[0012] An advantage of side-filling of each box, split between two boxing stations, is that the boxing machine is able to operate at a much higher speed.

[0013] The additional optional features mentioned below further enable the boxing machine to operate at a high speed without frequent jams.

[0014] The first boxing station may be configured to insert a plurality of accumulated products, collectively defining the first set of products, into the box. The second boxing station may be configured to insert a plurality of accumulated products, collectively defining the second set of products, into the box.

[0015] The second boxing station may be configured to stack the second set of products onto the first set of products within the sideways-oriented box. A product insertion height of the second boxing station may be higher than a product insertion height of the first boxing station, so that when the box is sideways-oriented the second set of products is stacked on the first set of products and when the box is upright-oriented the second set of products is alongside the first set of products.

[0016] Each boxing station may comprise a robotic picker. The robotic picker may comprise an end effector arrangement configured to pick products from the product conveyor.

[0017] The end effector arrangement may be sized to pick a plurality of products at once. The end effector arrangement may be configured as an array. The end effector arrangement may comprise vacuum means or other effector means, such as an array of vacuum end effectors for picking a plurality of products at once.

[0018] The robotic picker may comprise a parallel manipulator. An advantage is fast and stable operation

[0019] Each boxing station may comprise a product accumulator. The product accumulator may comprise a platform between the product conveyor and the box conveyor. The robotic picker may be configured to pick at least one product from the product conveyor and place the product on the product accumulator. The picking may comprise lifting and the placing may comprise lowering. The robotic picker may be configured to assemble the respective first or second set of products on the product accumulator.

[0020] The robotic picker may be configured to pick one or more further products from the product conveyor and place the one or more further products adjacent the placed product(s) to form an array or a row or a column.

[0021] The robotic picker may be configured to stack additional products on the array or row or column, such that the first set of products is a stack and the second set of products is a stack. The stack can then be inserted into the box.

[0022] Each boxing station may comprise an inserter configured to laterally move the respective first or second set of products into the sideways-oriented box.

[0023] The inserter may be configured as a stack inserter configured to insert an entire stack of products into the box at once (e.g., in one movement). The inserter may be configured as a multiple-stack inserter configured to insert multiple adjacent stacks of products into the box at once.

[0024] The inserter may be configured to slide the respective first or second set of products into the box. The inserter may comprise a lateral pusher for pushing the respective first or second set of products laterally into the box.

[0025] The inserter may be configured to move from a starting position towards the box in a first path and then to return to the starting position in a second path bypassing a placing location of the robotic picker. This provides a speed advantage because the next sets of products can be assembled while the inserter is returning to its starting position.

[0026] The inserter may be configured to move within a channel defined by the product accumulator. The product accumulator may comprise guide portions, such as walls, defining the channel, the channel extending towards the box conveyor.

[0027] The boxing machine may comprise a control system. The control system may control various functions.

[0028] The control system may be configurable to control filling of boxes with an odd number of products. In said configuration, the control system may be configured to select alternating ones of the first boxing station and the second boxing station, for each boxing cycle, to provide an additional product (the odd-numbered product) to each successive box. An advantage of the alternating selection is increased speed (when measured over multiple boxing cycles) due to the avoidance of cumulative dwell time of one of the boxing stations.

[0029] The boxing machine may comprise a box folding system configured to fold a base of the box upstream of the first boxing station and configured to fold a top of the box downstream of the second boxing station.

[0030] The product conveyor and the box conveyor may be substantially parallel to each other. The box may be oriented so that an opening of the box faces the product conveyor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] For a better understanding of various examples of embodiments of the present invention reference will now be made by way of example only to the accompanying drawings in which:

[0032] FIG. 1 illustrates an example plan view of a boxing machine;

[0033] FIG. 2 illustrates a perspective view of an example boxing station;

[0034] FIG. **3** illustrates an example top perspective view of a product accumulator and an inserter of a boxing station;
[0035] FIG. **4** schematically illustrates example paths of an inserter of a boxing station;
[0036] FIG. **5** schematically illustrates first and second boxing stations being configured for different product insertion heights; and
[0037] FIG. **6** schematically illustrates an example a control system for a boxing station.

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS OF THE INVENTION

[0038] FIG. **1** illustrates an example plan view of a boxing machine **1**.

[0039] The boxing machine **1** comprises a product conveyor **200**, boxing stations **100** including a first boxing station **100A**, a second boxing station **100B**, and a box conveyor **300**. The boxing stations **100** provide products **2** from the product conveyor **200** to boxes **3** on the box conveyor **300**.

[0040] The product conveyor **200** may comprise a powered conveyor belt or any other appropriate conveyor.

[0041] The product conveyor **200** comprises a product inlet **202** configured to receive products **2** from an upstream process.

[0042] The product conveyor **200** extends to the first boxing station **100A** which is configured to extract a first set (e.g., approximately half) of products **2** from the product conveyor **200**.

[0043] The product conveyor **200** extends further to the second boxing station **100B** which is configured to extract a second set (e.g., approximately half) of the products **2** from the product conveyor **200**.

[0044] The second boxing station **100B**, if it is the last boxing station, may be configured to extract the remainder of the products **2** from the product conveyor **200**.

[0045] If any products **2** are missed by both the first and second boxing stations **100A**, **100B**, the products **2** may fall off an end of the product conveyor **200** into a collection container, or alternatively the product conveyor **200** could recirculate.

[0046] As shown, the box conveyor **300** may comprise a powered conveyor. The box conveyor **300** may extend in a direction substantially parallel to the product conveyor **200**. The box conveyor **300** may be alongside the product conveyor **200**, with the first and second boxing stations **100A**, **100B** therebetween. The box conveyor **300** may move boxes **3** in the same direction as products **2** moved by the product conveyor **200**.

[0047] The box conveyor **300** comprises a box inlet **302** configured to receive boxes **3**. The boxes **3** entering the product conveyor **200** may be fully or partially unfolded. The boxes **3** are sideways-oriented.

[0048] The box conveyor **300** may firstly extend past a base folder **306** of a box **3** folding system **304**. The illustrated base folder **306** is configured to fold base flaps of each box **3** into a closed configuration. The base folder **306** may be located upstream of the first boxing station **100A**. The base folder **306** may comprise a plurality of actuators, each actuator for folding a different base flap of the box **3**.

[0049] The box conveyor **300** then extends to the first boxing station **100A** which is configured to laterally insert the first set of products **2** into a sideways-oriented box **3**. The base of the box **3** may be closed but its top flaps may still be open, leaving a sideways-oriented top opening of the box **3** through which the products **2** can be inserted.

[0050] The product conveyor **200** extends further to the second boxing station **100B** which is configured to laterally insert the second set of products **2** into the sideways-oriented box **3**, to complete a filling of the box **3**.

[0051] The box **3** then passes along the box conveyor **300** from the second boxing station **100B** to a top folder **308** of the box folding system **304**. The top folder **308** is configured to fold the top flaps of the box **3** into a closed configuration, to enclose the inserted products **2** within the box **3**. The top folder **308** may comprise a plurality of actuators, each actuator for folding a different top flap

of the box **3**.

[0052] The boxing stations **100** are now described in more detail, with reference to FIGS. **2-4**. These Figures illustrate the first boxing station **100A**. The second boxing station **100B** may have any one or more of the same features as the first boxing station **100A**.

[0053] The first boxing station **100A** may be configured to insert a plurality of accumulated products **2**, collectively defining the first set of products **2**, into the box **3**. To achieve this, the first boxing station **100A** comprises a robotic picker **102**, a product accumulator **110**, and an inserter **120**. The robotic picker **102** is configured to deposit products **2** onto the product accumulator **110**, and the inserter **120** is configured to insert the accumulated products **2** into the box **3**.

[0054] The robotic picker **102**, shown in FIG. **2**, may be configured as a pick and place robot. The robotic picker **102** is configured to automatically detect the positions of products **2** on the product conveyor **200**, lift the products **2** from the product conveyor **200**, and lower them onto the product accumulator **110**. Detection of the products **2** can be achieved by known sensing means, such as a camera.

[0055] The illustrated robotic picker **102** comprises a parallel manipulator **104** connected to an end effector arrangement **106** configured to pick products **2** from the product conveyor **200**. The robotic picker **102** may be located above the product conveyor **200**, between the product conveyor **200** and the product accumulator **110**, with the parallel manipulator **104** facing downwards.

[0056] The parallel manipulator **104** may comprise three degrees of translational freedom. The end effector arrangement **106** may comprise a degree of rotational freedom, for rotating products **2** about a vertical axis. The parallel manipulator **104** comprises actuating arms arranged in at least a tripod. Each actuating arm may comprise hinge joints such as a shoulder joint and an elbow joint.

[0057] The end effector arrangement **106** may be sized to pick a plurality of products **2** at once. The end effector arrangement **106** may comprise a regular or irregular array of end effectors **108**. The size of the array depends on how many products **2** are to be picked at once, and the product size. The array can comprise three or more rows and three or more columns of end effectors **108**.

[0058] The end effector arrangement **106** may be configured to secure a top surface of the product. The end effector arrangement **106** may comprise vacuum means for attaching to the top surface. The vacuum means may comprise an array of vacuum end effectors **108**. Alternatively, the end effector arrangement **106** can comprise another effector means.

[0059] The illustrated product accumulator **110** comprises a platform between the product conveyor **200** and the box conveyor **300**. The robotic picker **102** is configured to assemble the set of products **2** on the product accumulator **110**.

[0060] The robotic picker **102** may be configured to assemble the set of products **2** by placing a first subset of one or more products **2** on the product accumulator **110**. The first subset may comprise a row or a column of products **2**.

[0061] In some examples, the robotic picker **102** is then configured to pick one or more further products **2** from the product conveyor **200** and place the one or more further products **2** adjacent the already-placed product(s) to extend the row or column or to form an array of at least two rows and at least two columns.

[0062] Additionally, or alternatively, the robotic picker **102** is configured to pick one or more additional products **2** from the product conveyor **200** and stack the one or more additional products **2** onto the already-placed product(s). In this example, the assembled set of products **2** is a stack. The assembled set of products **2** may comprise a row of stacked products **2**, a column of stacked products **2**, or an array of stacked products **2**.

[0063] The assembled set of products **2** can then be inserted into the box **3** by the inserter **120**.

[0064] The illustrated inserter **120** is configured to laterally move the respective first or second set of products **2** into the sideways-oriented box **3** (not shown in FIGS. **2-3**). The inserter **120** comprises a lateral pusher **122** for pushing the set of products **2** along the product accumulator **110**, laterally into the opening of the sideways-oriented box **3**. The lateral pusher **122** may be configured

to slide the products **2** along the platform surface of the product accumulator **110** and into the box **3**. The lateral pusher **122** may comprise a movable upright plate or the like.

[0065] If the set of products **2** comprises a stack of products **2**, the lateral pusher **122** may be sized so that the inserter **120** functions as a stack inserter configured to insert the entire stack of products **2** into the box **3** at once (e.g., in one movement).

[0066] If the set of products **2** comprises a row, column or array of stacked products **2**, the lateral pusher **122** may be sized so that the inserter **120** functions as a multiple-stack inserter configured to insert multiple adjacent stacks of products **2** into the box **3** at once.

[0067] The inserter **120** further comprises an actuator arrangement **124** configured to move the lateral pusher **122**. An example cyclic motion path of the lateral pusher **122** is shown in FIG. **4**.

[0068] As shown in FIG. **4**, the actuator arrangement **124** of the inserter **120** is configured to move the lateral pusher **122** from a starting position towards the box **3** in a first path **400**. The starting position of the first path **400** is proximal to the product conveyor **200**. The first path **400** extends through a placing location of the robotic picker **102**. The first path **400** may terminate proximal to the box conveyor **300**. The first path **400** may comprise a linear and/or approximately horizontal path.

[0069] The first path **400** may terminate inside an envelope of the box **3**. The lateral pusher **122** may move through the opening of the open top flaps of the box **3**. This ensures that the set of products **2** is pushed to the base of the sideways-oriented box **3**.

[0070] The actuator arrangement **124** of the inserter **120** is then configured to return the lateral pusher **122** to the starting position in preparation for a next boxing cycle.

[0071] The actuator arrangement **124** may comprise an additional degree of freedom, so that the return path (second path **402**) of the lateral pusher **122** is different from the first path **400**. This enables the lateral pusher **122** to bypass the placing location of the robotic picker **102**, so that the robotic picker **102** can assemble the set of products **2** for the next boxing cycle before the lateral pusher **122** has completed returning to the starting position.

[0072] The second path **402** may first comprise reversing the lateral pusher **122** out of the box **3**, in examples in which the first path **400** terminated inside the box **3**.

[0073] The second path **402** then comprises a bypass portion extending around the placing location of the robotic picker **102**. The bypass portion of the second path **402** may be vertically and/or laterally offset relative to the first path **400**.

[0074] In the example of FIG. **4**, the bypass portion of the second path **402** is vertically offset from the first path **400**. In the illustrated implementation, the bypass portion of the second path **402** is below the first path **400**.

[0075] The illustrated bypass portion of the second path **402** is below the product accumulator **110** whereas the first path **400** is on (above) the product accumulator **110**. Once the placing location has been passed, the lateral pusher **122** can be lifted to the starting position.

[0076] In order to facilitate the first path **400** and the second path **402** of FIG. **4**, the actuator arrangement **124** of the inserter **120** can comprise two degrees of translational freedom. These comprise a horizontal degree of freedom and a vertical degree of freedom. As shown in FIGS. **2-3**, the actuator arrangement **124** may comprise a horizontally slidable carriage **125** to enable the horizontal degree of freedom. The carriage **125** may comprise a vertically-movable output configured to change a vertical separation of the lateral pusher **122** from the carriage **125**, to enable the vertical degree of freedom.

[0077] The actuator arrangement **124** and the lateral pusher **122** may be located to opposite sides of the product accumulator **110**. Therefore, in order to prevent interference between the actuator arrangement **124** and the product accumulator **110**, the product accumulator **110** may comprise a slot **116** as shown in FIG. **3**. The path of the slot **116** depends on the direction of the first path **400** of the lateral pusher **122**. The slot **116** may be linear and extends towards the box conveyor **300**. The width of the slot **116** may be narrow enough that products **2** on the product accumulator **110** do

not fall through the slot **116**.

[0078] FIGS. **2** and **3** also illustrate the product accumulator **110** comprising guide portions **112** for constraining the set of products **2** to a channel **114** while the set of products **2** is being inserted into the box **3**. The illustrated guide portions **112** comprise side guide portions such as side walls. The guide portions **112** may comprise a guide portion **112** to each side of the slot **116**. The width separation of the guide portions **112** depends on the width of the set of products **2** and/or the dimensions of the box **3**. The width separation may be adjustable.

[0079] FIG. **2** also illustrates deployable top flap holders **118A**, **118B** configured to hold open the top flaps of the box **3** while the products **2** are inserted into the box **3**. The top flap holders **118A**, **118B** can comprise a first top flap holder **118A** for holding open a first top flap of the box **3** and a second top flap holder **118B** for holding open a second top flap of the box **3**.

[0080] The top flap holders **118A**, **118B** may each comprise a hinged member. The hinged members may be mounted to the guide portions **112** of the product accumulator **110**. The hinged members may be swung open in opposite directions by their respective actuators, to engage with top flaps of the box **3** to hold the top flaps open.

[0081] In some examples, each top flap holder **118A**, **118B** also comprises a floor portion **119**, so that when the top flap holders **118A**, **118B** are swung open the floor portions **119** create a bridge between the product accumulator **110** and the box **3**.

[0082] Once the operation of the first boxing station **100A** is complete, the box **3** moves downstream along the box conveyor **300** from the first boxing station **100A** to the second boxing station **100B**, until the box **3** is aligned with the second boxing station **100B**, and then the second boxing station **100B** inserts the second set of products **2** into the box **3** that already contains the first set of products **2**. As mentioned previously, the second boxing station **100B** may comprise the same features as the first boxing station **100A**. Some differences of the second boxing station **100B** are described below.

[0083] Referring to FIG. **5**, the second boxing station **100B** can be configured to stack the second set of products **2** onto the first set of products **2** within the sideways-oriented box **3**. The second set of products **2** then rests on the first set of products **2** within the sideways-oriented box **3** (i.e., the sets of products **2** are side-by-side when the box **3** is upright). In order to facilitate stacking of the second set of products **2** on the first set of products **2**, a product insertion height **504** of the second boxing station **100B** may be higher than a product insertion height **502** of the first boxing station **100A**.

[0084] The product insertion height **502**, **504** may be defined, at least in part, by the height of the product accumulator **110**. The difference in product insertion heights **502**, **504** may be configurable by an operator, to suit the product and box dimensions. The inserter **120** and the robotic picker **102** may be height-adjustable.

[0085] FIG. **6** schematically illustrates an example of a control system **600**. The control system **600** may control various functions of the boxing stations **100**. Some control aspects are known or outside the scope of this disclosure.

[0086] The control system **600** may comprise one or more controllers. The controllers may belong to the separate actuators/robots and there may or may not be a central controller for centrally controlling functions of the boxing machine **1**. Each controller may comprise a processor, memory and computer program code.

[0087] The control system **600** may be configured to enable the split filling of the box **3**. This includes, for example, controlling the robotic picker **102** of the first boxing station **100A** to pick a subset of the products **2** on the product conveyor **200**, so that some products **2** pass through to the second boxing station **100B**.

[0088] In some use cases, the proportions of products **2** picked by the first boxing station **100A** and the second boxing station **100B** may be split approximately 50/50.

[0089] In some examples, an operator may wish to fill a box **3** with an odd number of products **2**.

This means that one boxing station (e.g., first boxing station **100A**) will pick, place and insert an additional product compared to the other boxing station (e.g., second boxing station **100B**). As a result, the second boxing station **100B** would dwell as it waits for the first boxing station **100A** to complete. In order to avoid dwell, the control system **600** may be configured in an 'odd filling' configuration.

[0090] In the odd filling configuration, the control system **600** may be configured to alternate which one of the boxing stations **100** picks an additional product. In other words, the control system **600** selects alternating ones of the first boxing station **100A** and the second boxing station **100B**, for each boxing cycle, to provide the additional product (the odd-numbered product) to each successive box **3**.

[0091] Although embodiments of the present invention have been described in the preceding paragraphs with reference to various examples, it should be appreciated that modifications to the examples given can be made without departing from the scope of the invention as claimed. Although the illustrated embodiment enables filling of up to 20 boxes per minute/insertion of up to 120 products per minute, speed and/or precision may not be as important in some implementations. For example: [0092] the robotic picker **102** could be replaced with a different means for transferring a product to the product accumulator **110**, such as a pusher or any other appropriate means; [0093] the inserter **120** could be replaced with a different means for transferring a product to a box **3**, such as a product accumulator tilting device or any other appropriate means. [0094] the robotic picker **102** and the inserter **120** could be merged into a single device for transferring products **2** from the product conveyor **200** to the box **3**, optionally without a product accumulator **110**.

[0095] Features described in the preceding description may be used in combinations other than the combinations explicitly described.

[0096] Although functions have been described with reference to certain features, those functions may be performable by other features whether described or not.

[0097] Although features have been described with reference to certain embodiments, those features may also be present in other embodiments whether described or not.

[0098] Whilst endeavoring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance it should be understood that the Applicant claims protection in respect of any patentable feature or combination of features hereinbefore referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.

Claims

1. A boxing machine comprising: a first boxing station; a second boxing station; a product conveyor extending from a product inlet to the first boxing station and from the first boxing station to the second boxing station; and a box conveyor extending from a box inlet to the first boxing station and from the first boxing station to the second boxing station, wherein the first boxing station is configured to insert a first set of products from the product conveyor to a sideways-oriented box on the box conveyor, and wherein the second boxing station is configured to insert a second set of products to the sideways-oriented box on the box conveyor.
2. The boxing machine of claim 1, wherein the first boxing station is configured to insert a plurality of accumulated products, collectively defining the first set of products, into the sideways-oriented box, and wherein the second boxing station is configured to insert a plurality of accumulated products, collectively defining the second set of products, into the sideways-oriented box.
3. The boxing machine of claim 1, wherein the second boxing station is configured to stack the second set of products onto the first set of products within the sideways-oriented box.
4. The boxing machine of claim 3, wherein a product insertion height of the second boxing station is higher than a product insertion height of the first boxing station, so that when the box is

sideways-oriented the second set of products is stacked on the first set of products and when the box is upright-oriented the second set of products is alongside the first set of products.

5. The boxing machine of claim 1, wherein each boxing station comprises a robotic picker, wherein the robotic picker comprises an end effector arrangement configured to pick products from the product conveyor, and wherein the end effector arrangement is sized to pick a plurality of products at once.

6. The boxing machine of claim 5, wherein the robotic picker comprises a parallel manipulator.

7. The boxing machine of claim 5, wherein each boxing station comprises a product accumulator, wherein the product accumulator comprises a platform between the product conveyor and the box conveyor

8. The boxing machine of claim 7, wherein the robotic picker is configured to pick at least one product from the product conveyor and place the at least one product on the product accumulator, and wherein the robotic picker is configured to assemble the respective first or second set of products on the product accumulator.

9. The boxing machine of claim 8, wherein the robotic picker is configured to pick one or more further products from the product conveyor and place the one or more further products adjacent the placed at least one product to form an array or a row or a column.

10. The boxing machine of claim 9, wherein the robotic picker is configured to stack additional products on the array or row or column, such that the first set of products is a stack and the second set of products is a stack.

11. The boxing machine of claim 1, wherein each boxing station comprises an inserter configured to laterally move the respective first or second set of products into the sideways-oriented box.

12. The boxing machine of claim 11, wherein the inserter is configured as a stack inserter configured to insert an entire stack of products into the sideways-oriented box in one movement.

13. The boxing machine of claim 12, wherein the inserter is configured as a multiple-stack inserter configured to insert multiple adjacent stacks of products into the sideways-oriented box at once.

14. The boxing machine of claim 11, wherein the inserter is configured to slide the respective first or second set of products into the sideways-oriented box.

15. The boxing machine of claim 11, wherein the inserter is configured to move from a starting position towards the sideways-oriented box in a first path and then to return to the starting position in a second path bypassing a placing location of the robotic picker.

16. The boxing machine of claim 11, wherein each boxing station comprises a robotic picker, wherein the robotic picker comprises an end effector arrangement configured to pick products from the product conveyor, wherein the end effector arrangement is sized to pick a plurality of products at once, wherein each boxing station comprises a platform between the product conveyor and the box conveyor, and wherein the inserter is configured to move within a channel defined by the product accumulator.

17. The boxing machine of a claim 1, comprising a control system, wherein the control system is configured to control filling of boxes with an odd number of products, wherein in said configuration, the control system is configured to select alternating ones of the first boxing station and the second boxing station, for each boxing cycle, to provide an additional product to each successive sideways-oriented box.

18. The boxing machine of claim 1, wherein the boxing machine comprises a box folding system configured to fold a base of the box upstream of the first boxing station and configured to fold a top of the box downstream of the second boxing station.

19. The boxing machine of claim 1, wherein the product conveyor and the box conveyor are substantially parallel to each other, arranged such that an opening of the sideways-oriented box faces the product conveyor in use.
