

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250282515
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	Wang; Tianlong

Sticker Dispenser

Abstract

A sticker dispenser with sticker roll carrier for dispensing stickers, wherein the stickers are peelably adhered to liner paper and wound into a sticker roll. The sticker dispenser with a sticker roll carrier includes a housing having a first chamber with an opening, a sticker roll carrier assembled in the first chamber and configured to carry the sticker rolls, and a cover detachably connected to the housing to cover the opening of the first chamber, thereby retaining the sticker roll carrier within the first chamber. The present disclosure enables direct cartridge replacement upon depletion of the sticker rolls, thereby significantly facilitating the sticker roll replacement operation for users.

Inventors:	Wang; Tianlong (Shenzhen, CN)
Applicant:	Wang; Tianlong (Shenzhen, CN)
Family ID:	96948544
Appl. No.:	19/220292
Filed:	May 28, 2025

Foreign Application Priority Data

CN	2024200709553	Jan. 11, 2024
CN	2025201610111	Jan. 23, 2025

Related U.S. Application Data

parent US continuation-in-part 18641685 20240422 parent-grant-document US 12358678 child US 19220292

Publication Classification

Int. Cl.: B65C9/00 (20060101); B65H16/00 (20060101); B65H35/00 (20060101)

U.S. Cl.:

CPC **B65C9/0006** (20130101); **B65H16/005** (20130101); **B65H35/002** (20130101);
B65C2201/00 (20130101); B65C2210/00 (20130101); B65H2601/325 (20130101);
B65H2701/194 (20130101)

Background/Summary

BACKGROUND

Technical Field

[0001] The present disclosure relates to a technical field of sticker dispensing, and more specifically to a sticker dispenser.

Related Art

[0002] Stickers are sheets that can be attached to other items. The stickers can be printed with barcodes, QR codes, or various symbols or patterns, to be used for information recording, stickering, or entertainment. Commonly, a commercially available sticker is peelably attached onto a liner paper, and a user can manually bend the liner paper such that an edge of the sticker opens up a small opening from the liner paper, whereby the sticker can be removed. This conventional method of peeling off the sticker is inconvenient, in which the liner paper may be wrinkle, and the sticker or liner paper may be torn.

[0003] Based on this, the Applicant has developed a sticker dispenser, such as published Chinese patents No. CN219970240U and CN219750321U, which realizes automatic peeling off of stickers by driving a sticker roll to rotate by means of a motor and changing conveying directions of the liner paper and the sticker at a position close to an output port. These technical solutions proposed by the Applicant overcome the above problems existing in the related art. However, the above technical solutions are adopted with a motor to drive the sticker roll to rotate, requiring the use of electrical components such as motor, circuit board, battery, etc., which is costly and requires charging or replacing the battery after a long-term use.

SUMMARY

[0004] However, the vocabulary expression of the present disclosure is only used to describe some embodiments (whether or not already in the claims) disclosed in this specification, rather than a complete description of all possible embodiments.

[0005] In order to solve the problems existing in the prior art, the present disclosure provides a sticker dispenser with a sticker roll carrier, wherein a detachable sticker cartridge is pre-loaded with sticker rolls by the manufacturer. This configuration enables direct sticker cartridge replacement upon depletion of the sticker rolls, thereby significantly facilitating the sticker roll replacement operation for users.

[0006] In order to achieve the above objectives, the technical solutions adopted in the present disclosure are as follows.

[0007] A sticker dispenser with a sticker roll carrier for dispensing stickers, wherein the stickers are peelably affixed to liner paper and wound into sticker rolls each having a central positioning hole. The sticker dispenser with a sticker roll carrier comprises a housing including a first chamber with an opening, a sticker roll carrier configured to carry the sticker rolls and assembled in the first chamber; and a cover detachably connected to the housing to cover the opening of the first chamber, thereby retaining the sticker roll carrier within the first chamber.

[0008] In some embodiments, the sticker roll carrier comprises an upper plate and a lower plate arranged opposite to each other, with a sleeve column and a winding shaft disposed between the upper and lower plates. The sleeve column is configured for mounting the sticker rolls thereon,

while the winding shaft is adapted to wind the liner paper after sticker separation.

[0009] In some embodiments, the sticker roll carrier further comprises a sticker conveying section and a turn-peeling portion disposed between the upper plate and lower plate. The sticker conveying section is arranged between the sleeve column and the turn-peeling portion to transport stickers toward the turn-peeling portion. The turn-peeling portion is positioned between the sticker conveying section and the winding shaft, configured to divert the liner paper in a direction different from the sticker's travel path, thereby enabling separation of the stickers from the liner paper.

[0010] In some embodiments, the upper plate and lower plate are discrete components, with at least one of the sleeve column, sticker conveying section, and turn-peeling portion being integrally formed with the lower plate.

[0011] Preferably, at least one of the sleeve column, sticker conveying section, and turn-peeling portion is provided with snap hooks, snap grooves, positioning protrusions, or positioning recesses, while the upper plate is provided with mating parts configured to engage or interlock with the snap hooks, snap grooves, positioning protrusions, or positioning recesses.

[0012] In some embodiments, the edges between the upper plate and lower plate are arranged in an open configuration, wherein the sticker rolls sleeved on the sleeve column are constrained by the inner sidewall of the first chamber within the housing to prevent unwinding.

[0013] In some embodiments, the winding shaft and the housing are equipped with a coupling mechanism that cooperates with each other. The coupling mechanism includes a protruding shaft disposed on one of the winding shaft or the housing, and a corresponding shaft sleeve disposed on the other. Wherein the protruding shaft or the shaft sleeve disposed on one of the winding shaft is connected to the winding shaft through a snap-fit fastener.

[0014] In some embodiments, the sleeve column is a hollow column, and the housing includes a positioning post inserted into the sleeve column. The positioning post has an operation button disposed thereon and a snap-fit component operated by the operation button. The cover is provided with a through hole for exposing the operation button and a snap-fit mating component engaged with the snap-fit component.

[0015] In some embodiments, the housing includes an insertion positioning portion and a snap-fixing portion respectively disposed at opposite edges of the opening. The cover is correspondingly provided with an insertion mating portion and an elastic snap-fit portion, wherein the cover is connected to the housing by means of the insertion mating portion engaging with the insertion positioning portion, and the elastic snap-fit portion elastically snapping onto the snap-fixing portion.

[0016] In some embodiments, the housing includes an outer shell and a base shell. The outer shell includes a peripheral side wall and a partition wall disposed between upper and lower edges of the peripheral side wall, thereby defining the first chamber above the partition wall and a second chamber below the partition wall. The second chamber accommodates a driving mechanism for rotating the winding shaft, while the base shell covers the lower edge of the peripheral side wall.

[0017] In some embodiments, the driving mechanism is a manual driving mechanism comprising an operating member configured to operatively reciprocate within a set range, and a transmitting mechanism transmission-connected to both the operating member and the winding shaft, capable of transmitting power output from the operating member to the winding shaft to drive rotation thereof. The transmitting mechanism includes a one-way clutching device, which couples to transmit power when the operating member moves in a first direction, and separates to disconnect the power transmission when the operating member moves in a second direction opposite to the first direction.

[0018] In some embodiments, the transmitting mechanism is a gear train transmitting mechanism comprising a plurality of intermeshing gears. The one-way clutching device includes a movable gear configured to be movable between a coupled position and a detached position, and a force-applying member configured to apply a resilient force to the movable gear in a direction

maintaining the movable gear in the coupled position. During movement of the operating member in the second direction, the movable gear is capable of overcoming the resilient force to move from the coupled position to the detached position.

[0019] In some embodiments, the transmitting mechanism is a gear train transmitting mechanism comprising a plurality of intermeshing gears. The one-way clutching device includes a movable gear configured to be movable between a coupled position and a detached position; and a force-applying member configured to apply a resilient force to the movable gear in a direction maintaining the movable gear in the coupled position. During movement of the operating member in the first direction, the movable gear is capable of overcoming the resilient force to move from the detached position to the coupled position.

[0020] Preferably, at least one wall of the second chamber includes a guide slot configured to guide the movement path of the movable gear as it transitions between the coupled position and the detached position.

[0021] Preferably, guide slots are disposed on both opposing walls of the second chamber, and adapted to the ends of the gear shaft of the movable gear.

[0022] Preferably, the force-applying member is a torsion spring or resilient sheet having a resilient arm that abuts against the movable gear to exert the resilient force.

[0023] In some embodiments, the transmitting mechanism includes an actuating gear disposed upstream of and remaining coupled to the movable gear in a transmission direction of the power, and a driven gear disposed downstream of and detachably coupled to the movable gear in the transmission direction of the power. In condition of the operating member moving in the second direction, the actuating gear acts on the movable gear in a direction such that the movable gear is separated from the driven gear.

[0024] Preferably, the operating member comprises a rack portion, and the transmitting mechanism includes a first gear coupled to the rack portion. The first gear and the actuating gear are coaxially disposed, with the actuating gear having a diameter D that is more than double a diameter d of the first gear.

[0025] Preferably, the driven gear is fixedly connected to the winding shaft.

[0026] Preferably, the operating member is attached with a reset spring configured to apply a force to the operating member in a direction causing movement in the second direction.

[0027] Preferably, the operating member is configured to pivot around a set axis.

[0028] Preferably, the one-way clutching device is a one-way bearing that is coupled to a transmitting gear within the transmitting mechanism.

[0029] In some embodiments, the driving mechanism is an electric driving mechanism including an electric motor configured to output rotational power and being transmission-connected to the winding shaft. The electric motor is at least partially disposed within the first chamber and adapted to extend through the central positioning hole of the sticker roll.

[0030] Preferably: the housing comprises an extension shell protruding into the first chamber, wherein at least a portion of the electric motor is disposed within said extension shell.

[0031] Preferably, the extension shell is configured to extend through the central positioning hole, thereby positioning the sticker roll.

[0032] Preferably, the extension shell is provided with an accommodation configured to form a pickup space between itself and the wall surface of the central positioning hole, wherein the sticker roll is adapted to be grasped and removed from the pickup space.

[0033] Preferably, the electric motor is provided with a positioning portion corresponding to the accommodation, wherein the positioning portion engages with the accommodation to circumferentially fix the electric motor relative to the extension shell.

[0034] Preferably, when viewed along the sticker conveying direction from upstream to downstream, the external contour of the sticker dispenser is configured with gradually decreasing dimensions.

[0035] In some embodiments, the sticker dispenser with sticker roll carrier comprises a photoelectric device disposed adjacent to the output port and configured to acquire output information of the stickers based on photoelectric signals, and a light-shielding portion configured to prevent interference of external light with the photoelectric signals which blocks external light from entering the photoelectric device through the output port.

[0036] Preferably: the light-shielding portion is formed at the edge of the output port and extends from the output port toward the photoelectric device.

[0037] Preferably, the light-shielding portion is provided with an anti-adhesion portion on its surface opposite to the adhesive side of the sticker, wherein the anti-adhesion portion comprises ribs or protrusions whose tops are formed with cutting edges.

[0038] Compared to the prior art, the present disclosure provides a sticker dispenser with a sticker roll carrier, comprising a housing having a first chamber with an opening, a sticker roll carrier assembled within the first chamber and configured to carry sticker rolls, and a cover detachably connected to the housing to enclose the opening of the first chamber, thereby constraining the sticker roll carrier within the first chamber. The sticker rolls are pre-loaded by the manufacturer, enabling direct replacement of the sticker cartridge when depleted, which significantly facilitates the sticker roll replacement operation for users.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0039] To more clearly illustrate the technical solutions of the embodiments of the present disclosure, the accompanying drawings of the embodiments will be briefly described below, and it will be apparent that the accompanying drawings in the following description relate only to some embodiments of the present disclosure and are not a limitation of the present disclosure.

[0040] FIG. 1 is a perspective view of a manual sticker dispenser according to an embodiment of the present disclosure.

[0041] FIG. 2 is a perspective view of a manual sticker dispenser according to the embodiment of the present disclosure at another viewing angle.

[0042] FIG. 3 is a perspective view of a manual sticker dispenser according to the embodiment of the present disclosure.

[0043] FIG. 4 is a perspective view of a manual sticker dispenser according to the embodiment of the present disclosure at another viewing angle.

[0044] FIG. 5 is a perspective view of a manual sticker dispenser showing an operating member and a transmitting mechanism according to the embodiment of the present disclosure.

[0045] FIG. 6 is a partially view of a manual sticker dispenser showing an operating member and a transmitting mechanism according to the embodiment of the present disclosure from another viewing angle.

[0046] FIG. 7 is a schematic diagram of an action of a transmitting mechanism when an operation member is pressed in a manual sticker dispenser according to the embodiment of the present disclosure from another viewing angle.

[0047] FIG. 8 is a schematic diagram of an action of a transmitting mechanism when an operating member is reset in a manual sticker dispenser according to the embodiment of the present disclosure at another viewing angle.

[0048] FIG. 9 is a perspective view of an electric sticker dispenser according to the present disclosure.

[0049] FIG. 10 is a partial enlarged view of the output port of the electric sticker dispenser according to the present disclosure.

[0050] FIG. 11 is an exploded perspective view of the electric sticker dispenser shown in FIG. 9.

[0051] FIG. **12** is an exploded perspective view of the electric sticker dispenser shown in FIG. **9** at another viewing angle.

[0052] FIG. **13** is a perspective view of the electric sticker dispenser shown in FIG. **9** with the lower plate removed.

[0053] FIG. **14** is a perspective view showing the electric motor, transmitting mechanism and winding shaft of the electric sticker dispenser shown in FIG. **9**.

[0054] FIG. **15** is an exploded perspective view showing the electric motor, transmitting mechanism and winding shaft of the electric sticker dispenser shown in FIG. **9**.

[0055] FIG. **16** is an exploded perspective view of another embodiment of the electric sticker dispenser according to the present disclosure.

[0056] FIG. **17** is a partial enlarged view of the output port of the electric sticker dispenser shown in FIG. **12**.

[0057] FIG. **18** is a perspective view of the electric sticker dispenser shown in FIG. **12**.

[0058] FIG. **19** is a perspective view of a sticker dispenser with a sticker roll carrier according to the embodiment of the present disclosure.

[0059] FIG. **20** is a perspective disassembled view of the embodiment in FIG. **19**, showing the sticker roll carrier loaded with sticker rolls.

[0060] FIG. **21** is a schematic view of the components shown in FIG. **20** with the sticker rolls omitted.

[0061] FIG. **22** is a schematic view of the components shown in FIG. **21** at another viewing angle.

[0062] FIG. **23** is a further perspective disassembled view of the embodiment shown in FIG. **19**.

[0063] FIG. **24** is a schematic view of the components shown in FIG. **23** at another viewing angle.

[0064] FIG. **25** is a perspective view of another embodiment of the sticker dispenser with sticker roll carrier according to the present disclosure.

[0065] FIG. **26** is a schematic view of the components shown in FIG. **25** at another viewing angle.

[0066] FIG. **27** is a perspective disassembled view of the embodiment shown in FIG. **25** with sticker rolls loaded on the sticker roll carrier.

[0067] FIG. **28** is a further perspective disassembled view of the embodiment shown in FIG. **25**.

[0068] FIG. **29** is a schematic view of the components shown in FIG. **28** at another viewing angle.

[0069] FIG. **30** is a schematic view showing the usage deployment of the sticker roll according to the present disclosure.

[0070] FIG. **31** is a sectional view of the sticker and liner paper in the sticker roll according to the present disclosure.

[0071] FIG. **32** is a schematic view showing the operational state of the sticker roll embodiment illustrated in FIG. **30**.

[0072] FIG. **33** is a schematic view of another embodiment of the sticker roll carrier according to the present disclosure.

[0073] FIG. **34** is a partial enlarged view of the turn-peeling portion of the sticker roll carrier.

[0074] FIG. **35** is a schematic view of another embodiment of the turn-peeling portion of the sticker roll carrier according to the present disclosure.

[0075] FIG. **36** is a schematic view of another embodiment of the turn-peeling portion of the sticker roll carrier according to the present disclosure.

[0076] FIG. **37** is a schematic view of another embodiment of the turn-peeling portion of the sticker roll carrier according to the present disclosure.

DETAILED DESCRIPTION

[0077] To make the purpose, technical solutions, and advantages of the embodiments of the present disclosure clearer, the present disclosure will be described in further detail below in conjunction with the accompanying drawings. The components in the embodiments of the present disclosure generally described and illustrated in the accompanying drawings herein may be arranged and designed in a variety of different configurations. Based on the embodiments in the present

disclosure, all other embodiments obtained by those skilled in the art without creative labor are within the scope of the present disclosure.

[0078] It should be noted that similar symbols and letters denote similar items in the following accompanying drawings, and therefore, once an item is defined in an accompanying drawing, it is not required to be further defined and explained in subsequent accompanying drawings.

[0079] Unless otherwise defined, technical terms or scientific terms used in the present disclosure shall have the ordinary meaning understood by those skilled in the art. The terms “first”, “second”, etc. used in the specification and in the claims of the present disclosure do not indicate any order, number, or importance, but are only intended to distinguish between different components.

Similarly, the terms “a”, “one”, or “the”, etc. do not indicate a limitation of number, but rather the presence of at least one. The terms such as “include” or “contain” mean that the element or object appearing before the “include” or “contain” covers the element or object listed after the “include” or “include”, and do not exclude other elements or objects. The terms of “center”, “up”, “down”, “left”, “right”, “vertical”, “horizontal”, “inside”, “outside”, etc. are only intended to indicate a relative positional relationship, and when the absolute position of the described object is changed, the relative positional relationship may also be changed accordingly, which is only for the purpose of facilitating the description of the present disclosure and simplifying the description, and is not intended to indicate or imply that the device or element referred to must have a particular orientation, be constructed and operated in a particular orientation, and therefore cannot be construed as a limitation of the present disclosure.

[0080] In the description of the present disclosure, it is to be noted that, unless otherwise expressly provided and limited, the terms “mounted”, “connected”, and “coupled” are to be understood in a broad sense. For example, it may be a fixed connection, a removable connection, or a connection in one piece; it may be a mechanical connection or an electrical connection; it may be a direct connection or an indirect connection through an intermediate medium; and it may be a connection within the two elements. For those skilled in the art, the specific meaning of the above terms in the present disclosure can be understood in specific cases.

[0081] Some embodiments of the present disclosure are described in detail below in conjunction with the accompanying drawings. The features in the following embodiments may be combined with each other without conflict.

[0082] Referring to FIGS. **1** to **8**, the present disclosure disclosed a manual sticker dispenser A for peeling a sticker on a sticker roll **71**. The sticker is peelably affixed to a liner paper **72** and wound into the sticker roll **71**. The manual sticker dispenser A is constructed to be capable of peeling the sticker from the liner paper **72** during a sticker conveying process and outputting the sticker from an output port **110**.

[0083] Referring to FIG. **3**, the manual sticker dispenser A includes a housing **1**, the housing **1** defining a first chamber **14** for accommodating the sticker roll **71**; a conveying path **141** is defined in the first chamber **14**, and the housing **1** defines the output port **110** in communication with the first chamber **14**. A peeling structure **142** is arranged on the conveying path **141**, the peeling structure **142** being disposed at the output port **110**. The peeling structure **142** is configured to peel the sticker from the liner paper **72** by conveying the liner paper **72** in a direction different from a travel direction of the sticker. Specifically, the peeling structure **142** includes a turn-peeling portion. The liner paper **72** extends in a relatively flat attitude towards the output port **110** when the liner paper **72** is disposed upstream of the turn-peeling portion, and the liner paper **72** is bent backwards at the turn-peeling portion to travel in a direction different from the travel direction of the sticker, causing the sticker to be peeled off of the liner paper **72**. The liner paper **72** after reverse bending at the turn-peeling portion is wound on a winding shaft **140**. When the winding shaft **140** is driven to rotate, the winding shaft **140** pulls the liner paper **72** and the sticker affixed to the liner paper **72** to travel on the conveying path **141**, and the sticker is peeled off through the peeling structure **142**.

[0084] Referring to FIGS. **3** and **4**, the manual sticker dispenser A includes the winding shaft **140**, a

transmitting mechanism, and an operating member **41**. The operating member **41** is connected to the transmitting mechanism, and the transmitting mechanism is power-transferably connected to the winding shaft **140**. The operating member **41** is configured to operatively reciprocate within a set range. Specifically: the operating member **41** is configured to be driven by an operating force to move in a first direction to move from a first position to a second position, as well as to move in a second direction opposite to the first direction to reset from the second position to the first position when the operating force is released. During the movement of the operating member **41** from the first position to the second position, a continuous power transmission chain is formed between the operating member **41**, the transmitting mechanism, and the winding shaft **140** to drive the winding shaft **140** in a positive rotation to wind the liner paper **72**. During the resetting of the operating member from the second position to the first position, the power transmission chain is disconnected at least in one place between the operating member **41**, the transmitting mechanism, and the winding shaft **140**, in order to avoid driving the winding shaft **140** in reverse.

[0085] Referring to FIGS. **3** and **4**, in some embodiments, the housing **1** includes a main body shell **11**, an upper cover **12** disposed at a top of the main body shell **11**, and a lower cover **13** disposed at a bottom of the main body shell **11**. The main body shell **11** includes a bottom wall and a peripheral wall disposed at an edge of the bottom wall, where upper and lower edges of the peripheral wall extend beyond the bottom wall to define a first chamber **14** above the bottom wall for accommodating the sticker roll **71**, the winding shaft **140** and to define a second chamber **15** below the bottom wall for arranging the operating member **41** and the transmitting mechanism. An end of the upper cover **12** is arranged with an elastic buckle **121** to detachably connect the upper cover **12** to the main body shell **11** for an easy replacement of the sticker roll **71**. The lower cover **13** is fixed to the main body shell **11** by screw locking to prevent the transmitting mechanism arranged in the second chamber **15** from falling out caused by the user easily opening the lower cover **13**.

[0086] Referring to FIGS. **4** to **6**, in some embodiments, the operating member **41** is a pressable component, specifically a lever mechanism, configured to pivot around a set axis. The operating member **41** is pivotally connected to the housing **1**, which includes a pressing portion **411** and a rack portion **412**. The pressing portion **411** is exposed to the housing **1** and can be pressed by the user. The operating member **41** is in the first position before being pressed and is movable to the second position after being pressed. When the pressing portion **411** is pressed, the operating member **41** rotates about its pivot shaft, moving the rack portion **412**. The operating member **41** is a one-piece part, e.g. plastic injection molded, and the rack portion **412** has multiple teeth integrally molded for use in conjunction with the transmitting mechanism for transmitting power. In the embodiments, the rack portion **412** is curved and an axis of the curved shape is an axis of the pivot shaft of the operating member **41**. The operating member **41** is resiliently pressed against the rack portion **412** by a reset spring **413**, and the reset spring **413** provides a resilient force in the opposite direction to that of the pressing force. When the pressing force applied to the pressing portion is withdrawn, the reset spring **413** pushes the operating member **41** to rotate and reset to the first position prior to the application of the pressing force.

[0087] Further, the transmitting mechanism is a gear train transmitting mechanism including multiple gears coupled to each other, which is configured to connect the operating member **41** and the winding shaft **140** in a transmission, and to transmit the power output from the operating member **41** to the winding shaft **140** in order to drive the winding shaft **140** to rotate. The transmitting mechanism includes a one-way clutching device, which is configured to be coupled when the operating member **41** is moved in the first direction to implement the power transmission, and to be uncoupled when the operating member **41** is moved in the second direction opposite to the first direction to disconnect the power transmission. In some embodiments, the transmitting mechanism includes a driven gear **44** fixed relative to the winding shaft **140**, an actuating gear **42** driven in engagement with the rack portion **412** of the operating member **41**, and a movable gear **43** disposed between the driven gear **44** and the actuating gear **42**. Specifically, the transmitting

mechanism includes the actuating gear **42** located upstream of and remaining coupled to the movable gear **43** in the power transmission direction, and the driven gear **44** located downstream of and detachably coupled to the movable gear **43** in the power transmission direction.

[0088] A gear shaft of the actuating gear **42** is non-translatably connected to the housing **1**, and the actuating gear **42** is only capable of rotating about the axis of its gear shaft and is not movable in its axial and radial directions. In the embodiments, the actuating gear **42** is a double-layered tower gear having a small-diameter toothed disk **421** and a large-diameter toothed disk **422** that are arranged coaxial, the small-diameter toothed disk **421** of the actuating gear **42** being engaged with the rack portion **412** of the operating member **41**, and the large-diameter toothed disk **422** of the actuating gear **42** being engaged with the movable gear **43**. In other embodiments, the large-diameter toothed disk **422** may be understood as an actuating gear, and the small-diameter toothed disk **421** as a first gear further included in the transmitting mechanism and coupled to the rack portion **412**, the first gear and the actuating gear are coaxially disposed. The diameter D of the actuating gear is greater than double the diameter d of the first gear.

[0089] The movable gear **43** is configured to be movable between a coupled position and a detached position. i.e. a gear shaft of the movable gear **43** is translationally connected to the housing **1**, while the movable gear **43** is also rotatable about an axis of its gear shaft. An end of the gear shaft of the movable gear **43** is connected to a bottom wall of the main body shell **11** and the other end of the gear shaft of the movable gear **43** is connected to the lower cover **13**. Specifically, the bottom wall of the main body shell **11** defines an upper elongate slot (Not shown in the figures) configured for an upper end of the gear shaft of the movable gear **43** to be inserted and slide therein: the lower cover **13** defines a lower elongate slot **131** configured for a lower end of the gear shaft of the movable gear **43** to be inserted and slide therein. The upper elongate slot and the lower elongate slot **131** are opposite each other in the top-bottom direction, forming guide slots for the rotation shaft of the movable gear **43** to be inserted into and to slide within. When the rack portion **412** of the operating member **41** is engaged with the movable gear **43**, the movable gear **43** can be pushed to slide along the guiding slot. When the movable gear **43** slides to the coupled position, it can engage with the driven gear **44**. When the movable gear **43** slides to the detached position, it can disengage with the driven gear **44**.

[0090] In some embodiments, the one-way clutching device includes the movable gear **43** and a force-applying member **45**. The movable gear **43** is resiliently pushed against by the force-applying member **45**, and the force-applying member **45** is configured to apply a resilient force to hold the movable gear **43** in the coupled position. When the operating member **41** moves in the second direction from the second position to the first position, the operating member **41** drives the movable gear **43** to overcome the resilient force and to slip to the detached position. The force-applying member **45** may be a torsion spring or a resilient sheet, with a resilient arm that abuts against the movable gear **43** to exert the resilient force. In the embodiments, the force-applying member **45** is a torsion spring having two resilient arms, one of which abuts against the movable gear **43** and the other abuts against the housing **1**. In the embodiments, the spring force of the force-applying member **45** is overcome to separate the movable gear **43** from the driven gear **44**. In other embodiments, the force-applying member **45** is configured to apply a resilient force for the movable gear **43** to remain in the detached position, and the operating member **41** drives the movable gear **43** to overcome the resilient force to slide to the coupled position when the operating member **41** moves in the first direction from the first position to the second position: herein when the operating force is released, the movable gear **43** is separated under the action of the spring force of the force-applying member **45**. For the above mentioned embodiments, the force-applying member **45** instantly drives the movable gear **43** to the detached position from the driven gear **44** when the external force on the operating member **41** is removed, such that the separation is timelier and the driven gear **44** can be better avoided from being driven to rotate in reverse. Further, there exists a small slip distance for the movable gear **43** to move from the detached position to the

coupled position during the movement of the operating member **41** in the first direction, and the driven gear **44** is not driven in the slip distance. i.e. there exists a small empty travel distance of the operating member **41**. In some embodiments, the reset spring **413** provides a resilient resetting force greater than the resilient force applied to the movable gear **43** by the force-applying member **45**.

[0091] In some embodiments, the movable gear **43** is a double-layered tower gear having a small-diameter toothed disk **431** and a large-diameter toothed disk **432** that are arranged coaxial, the small-diameter toothed disk **431** of the movable gear **43** being engaged with the driven gear **44**, and the large-diameter toothed disk **432** of the movable gear **43** being engaged with the large-diameter toothed disk **422** of the actuating gear **42**. The provision of the actuating gear **42** and movable gear **43** may serve to amplify the fact that the rotation angle of the actuating gear **42** is less than the rotation angle of the driven gear **44** during the movement of the operating member **41** from the first position to the second position.

[0092] The driven gear **44** is coaxially and relatively fixedly connected to the winding shaft **140**. In the embodiment, the driven gear **44** is connected to the winding shaft **140** by a coupling mechanism. Specifically, a gear shaft of the driven gear **44** is arranged with a polygonal post, and a lower end of the winding shaft **140** is arranged with a polygonal sleeve, the polygonal post being inserted into the polygonal sleeve to realize a relative fixation of the polygonal post and the polygonal sleeve in a rotation direction.

[0093] Referring to FIG. 7, which is a schematic diagram of an action of the transmitting mechanism during the movement of the operating member **41** in the first direction driven by an operating force. A force is applied to the pressing portion **411** of the operating member **41** as shown by the arrow above thereof, the rack portion **412** of the operating member **41** rotates inwardly as shown by the arrow above thereof, and the actuating gear **42** rotates clockwise as shown by the arrow, in which case the movable gear **43** is pushed to translate in a direction close to the driven gear **44** and engage with the driven gear **44**, and the driven gear **44** clockwise rotates as shown by the arrow: driving the winding shaft **140** to rotate in order to pull the liner paper **72** to move, thereby realizing the peeling off of the sticker and the output of the sticker.

[0094] Referring to FIG. 8, which is a schematic diagram of an action of the transmitting mechanism during a process in which the operating force applied to the operating member **41** is released and the operating member **41** is driven by the reset spring **413** to move in the second direction to reset to the first position. A force is applied to the rack portion **412** of the operating member **41** as shown by the arrow above thereof, the pressing portion of the operating member **41** moves outward as shown by the arrow above thereof, and the actuating gear **42** rotates counterclockwise as shown by the arrow, in which case the movable gear **43** is pushed to translate in a direction away from the driven gear **44** and disengage with the driven gear **44**, and the rotation of the movable gear **43** driven by the actuating gear **42** is unable to be transmitted to the driven gear **44**, i.e., the driven gear **44** does not rotate counterclockwise, and the winding shaft **140** does not move, thereby avoiding that the wound liner paper is loosened and the sticker cannot be output when the operating member is pressed next time, caused by the winding shaft **140** rotating counterclockwise in the course of resetting the operating member **41**.

[0095] It should be noted that the present embodiment is illustrated with the movable gear **43** and the driven gear **44** is able to be disengaged as an example, and it can be understood that in other embodiments, it is sufficient to arrange such that a disengagement is feasible at any position in the transmission chain between the operating member **41** and the winding shaft **140**. It should also be noted that, in the present embodiment, the switching between engagement and disengagement is achieved by translation of the movable gear **43**, which in other embodiments can be achieved by means of a ratchet structure. For example, in some embodiments, the one-way clutching device is a one-way bearing, i.e. an overrunning clutch, which is coupled to a transmitting gear within the transmitting mechanism. The one-way bearing is free to rotate in one direction independently of the

winding shaft **140**. While in the other direction opposite, the one-way bearing is locked to the winding shaft **140** and both rotate in synchronization.

[0096] As can be seen from the above preferred embodiments, the present disclosure provides a manual sticker dispenser A including a winding shaft **140**, a transmitting mechanism, and an operating member **41**. The operating member **41** is configured to be driven by an operating force to move in a first direction, and is configured to move in a second direction opposite to the first direction when the operating force is released. During a movement of the operating member **41**, a continuous power transmission chain is formed between the operating member **41**, the transmitting mechanism, and the winding shaft **140**, to drive the winding shaft **140** to rotate and wind the liner paper. During a movement of the operating member **41** in the second direction, the one-way clutching device disconnects the power transmission, which avoids driving the winding shaft **140** in reverse. Therefore, the output of stickers may be realized by manually applying force on the operating member **41**, without using electrical components, thereby reducing costs and enhancing operability and entertainment.

[0097] Referring to FIGS. **9** to **15**, an electric sticker dispenser B according to another embodiment of the present disclosure is used for peeling stickers **811** from a sticker roll **81**. The stickers **811** are peelably affixed to liner paper **812** and wound into the sticker roll **81**. The electric sticker dispenser B is configured to separate the stickers **811** from the liner paper **812** during a sticker conveying process and output the stickers through a sticker output port **210**.

[0098] The electric sticker dispenser B comprises a housing **2**, an electric motor **5**, a winding shaft **240**, a transmitting mechanism **53**, a power switch **51**, and an activation assembly **52**. A turn-peeling portion **243**, a sticker guide portion **242**, and a liner paper guide portion **244** are all disposed on the housing **2**. The following describes each component of the electric sticker dispenser B in detail.

[0099] Referring to FIGS. **9** to **11**, the housing **2** is a plastic component, with the turn-peeling portion **243**, sticker guide portion **242**, and liner paper guide portion **244** integrally injection-molded on the housing **2**. The housing **2** defines a first chamber **24** accommodating the liner paper **812** with adhered stickers **811** wound in a roll or folded in layers. The output port **210** communicates between the first chamber **24** and the exterior of the housing **2**, enabling the stickers **811** to be conveyed from the first chamber **24** to the output port **210** and partially exposed outside the housing **2** for user removal. In some embodiments, the housing **2** comprises an upper cover **22**, a main body shell **21**, and a lower cover **23**, where both the upper cover **22** and lower cover **23** are plate-shaped, and the main body shell **21** is box-shaped with a compartment. The housing **2** includes at least one peripheral wall that defines the first chamber **24** internally. In some embodiments, the main body shell **21** includes a peripheral wall forming the circumferential enclosure and a base wall connected to the lower end of the peripheral wall, with an open upper portion of the main body shell **21**. The peripheral wall and base wall collectively define the first chamber **24**, while the upper cover **22** is mounted over the open upper portion of the main body shell **21** to cover the first chamber **24**. The lower cover **23** is installed beneath the base wall of the main body shell **21**, forming an installation space for the transmitting mechanism **53** between the lower cover **23** and the base wall.

[0100] The housing **2** has an extension shell **241** protruding into the first chamber **24**. The extension shell **241** is configured as a downward-opening cylindrical structure. Specifically, the extension shell **241** extends upward from the base wall of the main body shell **21**, forming an opening at its connection with the base wall to allow at least a portion of the electric motor **5** to be inserted through the opening into the extension shell **241**, thereby extending into the first chamber **24**. The shape and dimensions of the extension shell **241** are configured to accommodate the sticker roll **81** being sleeved over it while allowing rotational movement around the extension shell **241**. Specifically, the sticker roll **81** is provided with a central positioning hole **82**, and the extension shell **241** is configured to extend through the central positioning hole **82** for positioning the sticker

roll **81**. The radial dimension of the extension shell **241** is smaller than that of the central positioning hole **82** to ensure the sticker roll **81** can be properly sleeved over the central positioning hole **82**. In some embodiments, the radial dimension of the central positioning hole **82** is configured to be significantly larger than that of the extension shell **241**, enabling the sticker roll **81** to become eccentrically offset relative to the extension shell **241** when the wound liner paper **812** and stickers **811** are reduced, thereby facilitating sticker **811** conveyance. The extension shell **241** is formed as a substantially cylindrical sleeve to allow rotational movement of the sticker roll **81** about the extension shell **241**, an accommodation is provided on the extension shell **241**, configured to form a pickup space (not shown in the figures) between itself and the wall surface of the central positioning hole **82**, allowing the sticker roll **81** to be grasped and removed from the pickup space. In some embodiments, at least a portion of the electric motor **5** is disposed within the extension shell **241**, which is configured as a cylindrical sleeve with a vertical planar surface on its peripheral wall to facilitate alignment and installation with the electric motor **5**. The vertical planar surface forms the accommodation. The electric motor **5** is provided with a positioning portion (e.g., a planar surface on the motor's peripheral wall) corresponding to the accommodation, wherein the positioning portion engages with the accommodation to circumferentially fix the electric motor **5** relative to the extension shell, thereby securing the electric motor **5** in position within the extension shell **241**. In some embodiments, the electric sticker dispenser **B** adopts a whistle-like configuration. When viewed along the sticker conveying direction from upstream to downstream, the external contour of electric sticker dispenser **B** is configured with gradually decreasing dimensions.

[0101] Referring to FIGS. **12** to **15**, the winding shaft **240** is capable of winding the liner paper **812** to convey the stickers **811** to the output port **210**. The electric motor **5** outputs rotational power and is transmission-connected to the winding shaft **240** through the transmitting mechanism **53**, thereby driving the winding shaft **240** to rotate and pull the liner paper **812** for conveying and peeling the stickers **811**. The liner paper **812** after sticker peeling is wound on the winding shaft **240** to form a liner paper roll **83**. The main body of the electric motor **5** is positioned within the extension shell **241** located in the first chamber **24**, with its output shaft oriented downward and situated between the lower cover **23** and the base wall of the main body shell **21** of the housing **2**. Similarly, the lower end of the winding shaft **240** is positioned between the lower cover **23** and the base wall of the main body shell **21**, while the transmitting mechanism **53**, located in the same space, is transmission-connected between the output shaft of the electric motor **5** and the winding shaft **240**. The transmitting mechanism **53** includes a gear train coupled between the electric motor **5** and the winding shaft **240**, comprising a driven gear coupled to the winding shaft **240**, where the lower end of the winding shaft **240** is provided with a sleeve portion **2401** that meshes with and connects to the driven gear. Specifically, in some embodiments, the gear train comprises a first gear **531**, a second gear **532**, a third gear **533**, and a fourth gear **534**, wherein the second gear **532** to the fourth gear **534** are all dual-layer gears. The first gear **531** is sleeved on the output shaft of the electric motor **5**, the second gear **532** meshes with and is transmission-connected to the first gear **531**, the third gear **533** meshes with and is transmission-connected to the second gear **532**, and the fourth gear **534** meshes with and is transmission-connected to the third gear **533**. The fourth gear **534** serves as the aforementioned driven gear, and the inner wall surface of the sleeve portion **2401** of the winding shaft **240** is provided with teeth structures to mesh with and connect to the fourth gear **534**. The second gear **532** is fixedly provided with a second gear shaft **5321**, the third gear **533** is fixedly provided with a third gear shaft **5331**, and the fourth gear **534** is fixedly provided with a fourth gear shaft **5341**. These gear shafts are configured to support and mount their respective gears between the lower cover **23** and the base wall of the main body shell **21**, wherein the end of the fourth gear shaft **5341** facing the winding shaft **240** is tightly pressed into the winding shaft **240** via interference fit to ensure reliable connection between the fourth gear **534** and the winding shaft **240**.

[0102] Referring to FIGS. **16** to **18**, the present disclosure is an electric sticker dispenser C of another embodiment. Components identical to those in the aforementioned embodiments will not be redundantly described. In some embodiments, the electric sticker dispenser C may further include a photoelectric device **6** and a light-shielding portion **63**. The photoelectric device **6** acquires output information of the stickers based on photoelectric signals and is disposed adjacent to the output port **210**. The light-shielding portion **63** configured to prevent interference of external light with the photoelectric signals serves to block external light from entering the photoelectric device **6** through the output port **210**.

[0103] Furthermore, the light-shielding portion **63** is formed at the edge of the output port **210** and extends from the output port **210** toward the photoelectric device **6**. The surface of the light-shielding portion **63** opposite to the adhesive side of the stickers **811** is provided with an anti-adhesion portion **631**, which consists of ribs or protrusions whose tops are formed with cutting edges.

[0104] The main body shell **21** houses an operation circuit board internally, with the photoelectric device **6** mounted on the operation circuit board. A cover plate **61** is installed on the main body shell **21** to shield the operation circuit board, featuring an avoidance hole **62** that exposes the photoelectric device **6** by providing accommodation. The avoidance hole **62** prevents the photoelectric device **6** from being obstructed by the cover plate **61**. The cover plate **61** covers most areas of the operation circuit board, thereby providing protective functionality for the circuit board.

[0105] The electric sticker dispenser C provided in this embodiment incorporates a photoelectric device **6** positioned adjacent to the output port **210** for detecting sticker output information, thereby enhancing intelligent control and notification capabilities of the electric sticker dispenser B. The electric sticker dispenser C includes a light-shielding portion **63** configured to block external light from entering the photoelectric device **6** through the output port **210**, preventing interference with detection accuracy. This configuration ensures more precise detection, avoids erroneous judgments, and improves the accuracy of intelligent control and notifications in the electric sticker dispenser B.

[0106] Referring to FIGS. **30** to **32**, in some embodiments, the sticker roll **81** comprises windable liner paper **812** and stickers **811** peelably adhered to the liner paper **812**. The sticker roll **81** conveys the stickers along a conveyance path direction *z* to an output port. Each sticker **811** includes a face stock layer **8111** and an adhesive layer **8112**, with the back side of the face stock layer **8111** bonded to one side of the adhesive layer **8112** with a first adhesive force therebetween. The liner paper **812** comprises a base material **8122** and a release layer **8121** thereon, the release layer **8121** having a smooth surface treated with release properties, wherein the other side of the adhesive layer **8112** is bonded to the surface of the release layer **8121** with a second adhesive force therebetween, and wherein the first adhesive force is greater than the second adhesive force. It should be understood that the stickers **811** are temporarily adhered to the liner paper **812** via the adhesive layer **8112**, such that during peeling, the face stock layer **8111** remains bonded to the adhesive layer **8112** while the adhesive layer **8112** separates from the release layer **8121**, thereby preventing damage to either the stickers **811** or the liner paper **812**. Both the first and second adhesive forces refer to the bonding force per unit area perpendicular to the adhesive layer **8112**.

[0107] The liner paper **812** comprises a base material **8122** and a release layer **8121** thereon. The base material **8122** may include, but is not limited to, conventional kraft paper, offset paper, glassine paper, translucent or transparent paper, fabric, or plastic film. The release layer **8121** may include, but is not limited to, various organic or inorganic release treatment agents with release properties such as silicone resins or non-silicone compounds, applied as single-sided or double-sided coatings. The liner paper **812** is integrally formed as an elongated strip without tear lines or perforations, and can be wound from one end along the longitudinal axis of the strip to form the sticker roll **81** with a central positioning hole **82**. A plurality of stickers **811** are peelably adhered to the liner paper **812**, spaced apart along the winding direction, wherein the winding direction refers to outward winding forming the sticker roll **81** with the stickers **811** positioned on the outer side of

the roll, such that the bottom layer of the sticker roll **81** exposes the face stock layer **811**. [0108] Referring to FIGS. **23** to **24** and **30** to **34**, in some embodiments, a sticker dispenser further includes a sticker roll carrier **9**. The sticker roll carrier **9** comprises an upper plate **91** and a lower plate **92** arranged opposite to each other, with a sleeve column **93** and a winding shaft **94** disposed between the upper and lower plates. The sleeve column **93** is configured for mounting the sticker roll **81** through its central positioning hole **82**, while the winding shaft **94** is detachably arranged between the upper and lower plates and can be fixed to the other end of the liner paper **812** for winding the liner paper **812** after sticker **811** separation to form a liner paper roll **83**. The sticker roll carrier **9** additionally includes a sticker conveying section **95** and a turn-peeling portion **96** positioned between the upper and lower plates. Along the conveying path formed from the sleeve column **93** to the winding shaft **94** for the liner paper **812**, the sticker conveying section **95** is located between the sleeve column **93** and the turn-peeling portion **96** to transport stickers toward the turn-peeling portion **96**, whereas the turn-peeling portion **96** is positioned between the sticker conveying section **95** and the winding shaft **94** to divert the liner paper **812** in a direction different from the travel path of the stickers **811**, thereby effecting separation of the stickers **811** from the liner paper **812**.

[0109] Furthermore, the upper plate **91** and lower plate **92** may be discrete components, with the sleeve column **93**, sticker conveying section **95**, and turn-peeling portion **96** arranged therebetween. At least one of the sleeve column **93**, sticker conveying section **95**, or turn-peeling portion **96** is provided with snap hooks, snap grooves **930**, positioning protrusions, or positioning recesses **9501**, while the upper plate **91** or lower plate **92** is provided with mating parts configured to engage or interlock with said snap hooks, snap grooves **930**, positioning protrusions, or positioning recesses **9501**.

[0110] In some embodiments, taking as an example the configuration where the sleeve column **93**, sticker conveying section **95**, and turn-peeling portion **96** are all integrally formed with the lower plate **92**, the lower plate **92** is implemented as a horizontally extended thin plate with the sleeve column **93**, sticker conveying section **95**, and turn-peeling portion **96** all vertically extending upward from the thin plate. The lower plate **92** along with the sleeve column **93**, sticker conveying section **95**, and turn-peeling portion **96** are all plastic components that can be manufactured through integrated injection molding.

[0111] In some embodiments, the sleeve column **93** is configured as a hollow cylinder with snap grooves **930** provided on its peripheral wall. The sticker roll carrier **9** further includes an inner limiting portion **950** positioned between the upper plate **91** and lower plate **92** on the inner side of the sticker output path. The inner limiting portion **950** is formed as a hollow triangular prism vertically extending upward from the lower plate **92**, with its upper triangular opening constituting the positioning recess **9501**. The hollow triangular prism configuration is merely exemplary, where both the base edge of the triangular prism and the sticker conveying section **95** are disposed on opposite sides of the conveying path, forming an upstream limiting structure for the liner paper **812** and sticker **811** conveyance path between the sticker conveying section **95** and the prism's base edge.

[0112] In some embodiments, the turn-peeling portion **96** comprises an outer limiting portion **960** and a guide structure **961**, both formed as plate-like structures vertically extending upward from the lower plate **92**. A peeling point is created at the junction between the outer limiting portion **960** and the guide structure **961**, where the conveying direction of both the sticker **811** and liner paper **812** changes to establish a structure enabling their separation. Specifically, after the winding shaft **94** is fixed to the other end of the liner paper **812**, it provides tension to advance the liner paper **812** along the conveying path. Under this tension, the liner paper **812** first travels from the inner limiting portion **950** toward the sticker conveying section **95**, proceeds past the sticker conveying section **95** to reach the junction point, where its direction changes toward the winding shaft **94**, ultimately being wound onto the winding shaft **94** to form the liner paper roll **83**. The tension

provides a peeling force at the peeling point, where this peeling force exceeds the second adhesive strength. Since the remaining portion of the sticker **811** has not yet reached the peeling point, it continues to receive tension from the liner paper **812** along the conveying path, maintaining the sticker's forward movement through either pulling or pushing forces. At the peeling point, the liner paper **812** and sticker **811** begin separating due to their divergent travel directions. The peeling force refers specifically to the force perpendicular to the adhesive layer **8112**.

[0113] In some embodiments, the outer limiting portion **960** and the guide structure **961** form an acute-angle configuration designed to generate effective peeling force. It should be understood that the vertically extending plate-like structures are merely exemplary, as any configuration of the outer limiting portion **960** and guide structure **961** that alters the travel direction of the liner paper **812** to create a peeling point at their junction, thereby producing peeling force to initiate separation between the liner paper **812** and sticker **811** at this point, falls within the scope of the present disclosure. As illustrated in FIGS. **35** to **37**, the configuration between the outer limiting portion **960** and guide structure **961** is not limited to forming an acute angle, provided that their arrangement can redirect the liner paper **812** to establish the peeling point with sufficient peeling force for separation initiation, all such implementations are protected under the turn-peeling portion **96** of the present disclosure.

[0114] In some embodiments, as shown in FIG. **33**, the lower plate **92** is further provided with a mounting post **97** at an end distant from the sleeve column **93**, where both the mounting post **97** and sleeve column **93** serve to connect with the upper plate **91**. The mounting post **97** further includes a pressing-limiting portion **970** positioned relative to the turn-peeling portion **96**, with a gap formed between the pressing-limiting portion **970** and the guide structure **961** to allow passage of the liner paper **812**. The pressing-limiting portion **970** is disposed between the turn-peeling portion **96** and the winding shaft **94** to maintain a fixed travel direction for the liner paper **812** when passing through the gap, preventing directional deviation that might otherwise occur as the liner paper **812** accumulates and thickens during winding on the winding shaft **94**.

[0115] Referring to FIG. **24**, in some embodiments, the upper plate **91** comprises an engagement hook **911** configured to mate with the snap groove **930**, a positioning protrusion **913** designed for insertion into the positioning recess **9501**, and a locking post **912** adapted to engage with the mounting post **97**. Through the coordinated interaction of these structures, the upper plate **91** becomes securely fastened to the lower plate **92**, with the engagement hook **911**, positioning protrusion **913**, and locking post **912** collectively constituting the mating assembly. In other embodiments, the snap hooks, snap grooves **930**, positioning protrusions, or positioning recesses **9501** and their corresponding mating parts may adopt alternative configurations. In some embodiments, these snap hooks, snap grooves **930**, positioning protrusions, or positioning recesses **9501** may alternatively be disposed on the turn-peeling portion **96**. It is understandable that as long as the sleeve column **93**, the winding shaft **94**, the sticker conveying section **95**, the inner limiting portion **950**, the turn-peeling portion **96**, the outer limiting portion **960**, the guiding structure **961**, the mounting column **97**, and the pressing-limiting portion **970** are arranged between the upper plate **91** and the lower plate **92**, and allow the sticker roll **81** to form a conveying path from the sleeve column **93** to the winding shaft **94** between them, it does not affect the essence of the present disclosure sought to be protected whether the upper plate **91** and the lower plate **92** are separate components, or the upper plate **91** and the lower plate **92** are integrally formed, or all the aforementioned components are separate parts, or any two of the aforementioned components are integrally formed. Similarly, it is understandable that the aforementioned components represent the preferred configuration for this embodiment. Even if some of these components are omitted, as long as the arrangement still enables the sticker roll **81** to form a conveying path from the sleeve column **93** to the winding shaft **94** and allows the release paper **812** and the sticker **811** to begin separating at the peeling point, such variations shall fall within the scope of protection claimed by the present disclosure.

[0116] Referring to FIGS. 20 to 22, the edges between the upper plate 91 and the lower plate 92 are arranged in an open configuration. The sticker roll 81 sleeved on the sleeve column 93 is restrained by the inner wall of the first chamber 34 within the housing 3 to prevent unwinding. In other words, in this embodiment, only the discretely distributed sleeve column 93, winding shaft 94, sticker conveying section 95, turn-peeling portion 96, and mounting column 97 are provided between the upper plate 91 and the lower plate 92, without any continuous walls. This results in a structurally simple sticker roll carrier 9 with minimal material usage and low cost. Since the sticker roll carrier 9 itself lacks continuous walls and an enclosed chamber, the sticker roll 81 sleeved on the sleeve column 93 relies on the inner wall of the first chamber 34 within the housing 3 to prevent loosening.

[0117] Referring further to FIGS. 23 and 24, the winding shaft 94 needs to be rotationally driven by the driving mechanism 10. Therefore, the winding shaft 94 is an independent component rotatably mounted between the upper plate 91 and the lower plate 92. The winding shaft 94 and the housing 3 are equipped with a coupling mechanism that cooperates with each other. The coupling mechanism includes a protruding shaft disposed on one of the winding shaft 94 or the housing 3, and a corresponding shaft sleeve 98 disposed on the other. The driving mechanism 10 transmits power to the winding shaft 94 through the engagement of the protruding shaft and the shaft sleeve 98, thereby driving the winding shaft 94 to rotate and wind the liner paper. In this embodiment, the protruding shaft or shaft sleeve 98 mounted on the winding shaft 94 is connected to the winding shaft 94 via a snap-fit fastener 980. Specifically, the protruding shaft in this embodiment is arranged on the housing 3, while the shaft sleeve 98 is mounted on the winding shaft 94. The shaft sleeve 98 features a polygonal shaft hole exposed below the lower plate 92 and is equipped with a snap-fit fastener 980 that extends upward beyond the lower plate 92. The winding shaft 94 is provided with a corresponding snap-fit hole 940 that engages with the snap-fit fastener 980. The shaft sleeve 98 includes a flange, and its snap-fit fastener 980 passes through from below the lower plate 92 to lock with the winding shaft 94. The flange of the shaft sleeve 98 is constrained against the lower plate 92, collectively ensuring the secure connection of the winding shaft 94. This prevents the winding shaft 94 from tilting away from its own axis, guaranteeing connection reliability.

[0118] Referring to FIGS. 20 and 24, the housing 3 includes an insertion positioning portion 311 and a snap-fixing portion 312 respectively disposed on opposite edges of the opening of the first chamber 34. The upper cover 32 is correspondingly provided with an insertion mating portion 321 and an elastic snap-fit portion 322. The upper cover 32 is connected to the housing 3 by means of the insertion mating portion 321 engaging with the insertion positioning portion 311, and the elastic snap-fit portion 322 elastically snapping with the snap-fixing portion 312. In this embodiment, the insertion positioning portion 311 is a slot, the snap-fixing portion 312 is a block, and the insertion mating portion 321 is an insertion sheet.

[0119] After the sticker roll carrier 9 is assembled into the first chamber 34 of the housing 3, the insertion mating portion 321 on the upper cover 32 is tilted and inserted into the insertion positioning portion 311 of the housing 3. Then, pressing the end of the upper cover 32 where the elastic snap-fit portion 322 is located causes the elastic snap-fit portion 322 to engage with the snap-fixing portion 312, completing the assembly. For disassembly, pressing the elastic snap-fit portion 322 allows the upper cover 32 to be lifted, enabling the sticker roll carrier 9 inside the first chamber 34 to be removed and replaced. Furthermore, an elastic ejection component may be provided inside the housing 3 to partially eject the sticker roll carrier 9 when the snap engagement between the upper cover 32 and the housing 3 is released, facilitating its removal.

[0120] In some embodiments, the housing 3 comprises an outer shell and a lower cover 33. The outer shell includes a peripheral side wall 313 and a partition wall 341, with the peripheral side wall 313 being provided with an output port 310. The partition wall 341 is disposed between the upper and lower edges of the peripheral side wall 313 to enclose a first chamber 34 above the

partition wall **341** and a second chamber **35** below the partition wall **341**. The second chamber **35** accommodates a driving mechanism **10** for rotating the winding shaft **94**, while the lower cover **33** is mounted to cover the lower edge of the peripheral side wall **313**.

[0121] In some embodiments, the driving mechanism **10** is a manually operated mechanism comprising a toggle lever, a gear set driven by the toggle lever, a clutch, a reset component, and other associated parts. Pressing the toggle lever drives the winding shaft **94** to rotate, thereby winding the liner paper and enabling the peeling of stickers.

[0122] Referring to FIGS. **19** and **24**, the present disclosure shows an alternative embodiment of a sticker dispenser **D** incorporating a sticker roll carrier for dispensing stickers **811**. The stickers **811** are detachably adhered to liner paper **812** and wound to form a sticker roll **81**. The sticker dispenser comprises a housing **3**, a top cover **32**, and a sticker roll carrier **9**. The housing **3** features the first chamber **34** with an opening. The sticker roll carrier **9** serves to support the sticker roll **81** and is installed within the first chamber **34**. The top cover **32** encloses the opening of the first chamber **34** and is detachably attached to the housing **3** to securely maintain the sticker roll carrier **9** within the first chamber **34**.

[0123] In the sticker dispenser of the present disclosure, the sticker roll carrier **9** does not serve as an exterior surface component but functions solely to support the sticker roll **81** and facilitate sticker **811** dispensing. This design allows for greater material selection flexibility in manufacturing the sticker roll carrier **9** and permits reduced production precision, thereby lowering costs. When the sticker roll **81** is exhausted, users simply need to open the top cover **32**, replace the used sticker roll carrier **9** with a new one, and then reclose the top cover **32**. As part of the exterior assembly, the top cover **32** remains in permanent use without replacement, minimizing the number of components requiring replacement during sticker roll changes and further reducing operational costs.

[0124] Referring to FIGS. **25** to **29**, schematic diagrams illustrate another embodiment of a sticker dispenser **E** with a sticker roll carrier according to the present disclosure. Descriptions of components identical to those in the previous embodiment are omitted. The primary distinction between this embodiment and the aforementioned one lies in the connection structure between the top cover **32** and the housing **3**. Specifically, the sticker roll carrier **9** in this embodiment maintains substantially the same overall configuration as its counterpart in the previous embodiment, except for structural modifications to the upper plate **91**, which in this version features a through hole **910**. In some embodiments, the housing **3** incorporates a positioning post **342** inserted into the sleeve column **93**, with the top of the positioning post **342** equipped with an operation button **343** and a snap-fit component **344** controlled by said button. The top cover **32** includes a through hole **323** exposing the operation button **343** and a snap-fit mating component **324** that couples with the snap-fit component **344**. For this particular embodiment, the snap-fit mating component **324** comprises a vertically extending retention plate containing a retention groove, where the snap-fit component **344** remains secured within the groove under spring force to maintain engagement, while actuation of the operation button **343** disengages the snap-fit component **344** from the groove to release the connection.

[0125] During assembly of the sticker dispenser in this embodiment, first install the sticker roll carrier **9** into the first chamber **34** of the housing **3**. Then press the top cover **32** downward onto the opening of the first chamber **34**. During this pressing operation, the snap-fit mating component **324** pushes against the sloped surface of the snap-fit component **344**, causing it to move laterally and compress the spring. When the retention groove on the snap-fit mating component **324** aligns with the snap-fit component **344**, the snap-fit component **344** resets under spring force and engages with the retention groove, thereby securing the top cover **32** in place. For disassembly, actuate the operation button **343** to disengage the snap-fit component **344** from the snap-fit mating component **324**, allowing removal of both the top cover **32** and the sticker roll carrier **9** from the first chamber **34**. Optionally: an elastic ejection component may be installed within the housing **3** to partially

eject the sticker roll carrier **9** when the engagement between the top cover **32** and housing **3** is released, facilitating its removal.

[0126] Referring to FIG. **29**, in some embodiments, the driving mechanism **10** is electrically powered and includes a motor, a battery for powering the motor, a gear set driven by the motor, etc. The main body portion of the motor is housed within the positioning post **342** of the housing **3** to optimize space utilization. In this embodiment, the peripheral side wall **313** of the housing **3** is provided with a control button **314** for activating the motor, while the lower cover **33** features a charging port **331** for recharging the battery. The unmentioned portions of this embodiment are similar to those in the aforementioned embodiments and may be configured by referring to the sticker dispenser D with sticker roll carrier.

[0127] Through the description of the preferred embodiments above, it can be understood that the sticker dispenser with a sticker roll carrier provided in the present disclosure comprises a housing **3**, a top cover **32**, and a sticker roll carrier **9**. The sticker roll carrier **9**, carrying the sticker roll **81**, is assembled within the first chamber **34** of the housing **3**. The top cover **32** covers the opening of the first chamber **34** and is detachably connected to the housing **3** to retain the sticker roll carrier **9** within the first chamber **34**. This configuration ensures the sticker roll carrier **9** does not serve as an exterior component but functions solely to support the sticker roll **81** and facilitate sticker dispensing. Consequently, the material selection for the sticker roll carrier **9** offers greater flexibility, and its manufacturing precision requirements can be reduced, thereby lowering production costs. When the sticker roll **81** is depleted, users simply need to open the top cover **32**, replace the used sticker roll carrier **9** with a new one, and then reclose the top cover **32**. As a permanent exterior component, the top cover **32** remains in long-term use without replacement, minimizing the number of components requiring substitution during sticker roll changes and further reducing operational costs.

[0128] As mentioned above, the driving mechanism **10** can be either manually-operated or electrically-powered. For the manually-operated mechanism, the unmentioned portions in this embodiment are similar to those in the aforementioned embodiments and may be configured by referring to the manual sticker dispenser A. Regarding the electrically-powered mechanism, the unmentioned portions in this embodiment are similar to those in the previous embodiments and may be set up by referring to the electric sticker dispensers B and C. The identical aspects of the sticker roll carrier **9** across aforementioned embodiments will not be repeatedly described.

[0129] It should be noted that the present disclosure is not limited to the above embodiments. According to the creative spirit of the present disclosure, those skilled in the art can also make other modifications, which should not be interpreted as limiting the scope of the present disclosure. It should be noted that all modifications and substitutions equivalent to the embodiment should be included in the scope of the present disclosure. Therefore, the scope of protection of the present disclosure shall be subject to the scope defined in the claims.

Claims

1. A sticker roll carrier for supporting a sticker roll to dispense stickers, comprising: a lower plate: a sleeve column disposed on the lower plate; and a turn-peeling portion disposed on the lower plate: wherein the sticker roll comprises a windable liner paper and stickers peelably adhered to the liner paper; wherein one end of the liner paper is wound outward in a winding direction to form the sticker roll with a central positioning hole, and another end of the liner paper is capable of providing tension to guide the liner paper from the central positioning hole along the turn-peeling portion: wherein the stickers are disposed on an outer side of the sticker roll: wherein the sleeve column is configured for the central positioning hole to be sleeved and mounted thereon; wherein the turn-peeling portion is capable of directing the passing liner paper and the stickers along different conveyance paths to separate the stickers from the liner paper.

2. The sticker roll carrier of claim 1, wherein the sticker comprises a face stock layer and an adhesive layer, with the back side of the face stock layer bonded to one side of the adhesive layer with a first adhesive force therebetween: wherein the liner paper comprises a base material and a release layer with a smooth surface treated with release properties; and wherein the other side of the adhesive layer is bonded to the surface of the release layer with a second adhesive force therebetween, and the first adhesive force is greater than the second adhesive force.
3. The sticker roll carrier of claim 2, wherein the turn-peeling portion comprises a peeling point where the liner paper and the sticker are directed along different traveling paths.
4. The sticker roll carrier of claim 3, wherein a peeling force generated at the peeling point that exceeds the second adhesive force, causing separation between an opposite side of the adhesive layer and the release layer surface.
5. The sticker roll carrier of claim 4, further comprising a sticker conveying section disposed on the lower plate, and the sticker conveying section is positioned along the conveyance path between the sleeve column and the turn-peeling portion.
6. The sticker roll carrier of claim 5, further comprising an inner limiting portion disposed on the lower plate, wherein the inner limiting portion is positioned along the conveyance path between the sleeve column and the sticker conveying section.
7. The sticker roll carrier of claim 6, further comprising a pressing-limiting portion disposed on the lower plate, wherein the pressing-limiting portion is disposed opposite to the turn-peeling portion, with a gap formed between the pressing-limiting portion and a guiding structure to allow passage of the liner paper.
8. The sticker roll carrier of claim 1, further comprising an upper plate disposed opposite to the lower plate, wherein the sleeve column, the turn-peeling portion, the sticker conveying section, and the pressing-limiting portion are all disposed between the upper plate and the lower plate.
9. The sticker roll carrier of claim 8, wherein a winding shaft is further disposed between the upper plate and the lower plate, and the winding shaft is configured to secure the other end of the liner paper, so that it provides tension force for winding the liner paper to form a liner paper roll after sticker separation.
10. The sticker roll carrier of claim 8, wherein the upper plate and the lower plate are separate components, and at least one of the sleeve column, the sticker conveying section, and the turn-peeling portion is integrally formed with the lower plate.
11. The sticker roll carrier of claim 8, wherein at least one of the sleeve column, the sticker conveying section, and the turn-peeling portion is provided with snap hooks, snap grooves, positioning protrusions or positioning recesses, and the upper plate comprises mating portions that engage or insert with snap hooks, snap grooves, positioning protrusions or positioning recesses.
12. A sticker dispenser with sticker roll carrier for dispensing stickers, wherein the stickers are peelably adhered to liner paper and wound into a sticker roll with a central positioning hole, the sticker dispenser comprises: a housing including a first chamber with an opening; a sticker roll carrier disposed within the first chamber and configured to carry the sticker roll; and a cover disposed over the opening of the first chamber, and the cover is detachably connected to the housing to retain the sticker roll carrier within the first chamber.
13. The sticker dispenser with sticker roll carrier of claim 12, wherein the sticker roll carrier comprises: an upper plate: a lower plate oppositely disposed to the upper plate: a sleeve column configured for mounting the sticker roll, and disposed between the upper plate and the lower plate; and a winding shaft disposed between the upper plate and the lower plate, and adapted to wind the liner paper after sticker separation.
14. The sticker dispenser with sticker roll carrier of claim 13, wherein the sticker roll carrier comprises: a sticker conveying section disposed between the upper plate and lower plate; and a turn-peeling portion disposed between the upper plate and lower plate: wherein the sticker conveying section is positioned between the sleeve column and the turn-peeling portion to convey

stickers toward the turn-peeling portion, and the turn-peeling portion is arranged between the sticker conveying section and the winding shaft to direct the liner paper along a different path from the stickers, thereby effecting separation of the stickers from the liner paper.

15. The sticker dispenser with sticker roll carrier of claim 13, wherein the winding shaft and the housing are provided with mutually engaged coupling mechanism, the coupling mechanism comprises a protruding shaft disposed on one of the winding shaft or the housing and a shaft sleeve disposed on the other: wherein the protruding shaft or shaft sleeve mounted on the winding shaft is connected thereto via a snap-fit fastener.

16. The sticker dispenser with sticker roll carrier of claim 13, wherein the sleeve column is a hollow cylinder, and the housing includes a positioning post inserted into the sleeve column; wherein the top end of the positioning post comprises an operation button and a snap-fit component actuated by the operation button, and the cover comprises a through hole for exposing the operation button and a snap-fit mating component that couples with the snap-fit component.

17. The sticker dispenser with sticker roll carrier of claim 12, wherein the housing comprises an insertion positioning portion and a snap-fixing portion respectively disposed on opposite edges of the opening, and the cover correspondingly comprises an insertion mating portion and an elastic snap-fit portion: wherein the cover is attached to the housing through both insertion engagement between the insertion mating portion and insertion positioning portion, and elastic snap-fit coupling between the elastic snap-fit portion and snap-fixing portion.

18. The sticker dispenser with sticker roll carrier of claim 15, wherein the housing comprises an outer shell and a base cover, and the outer shell comprises a peripheral side wall and a partition wall disposed between upper and lower edges of the peripheral side wall to form the first chamber above the partition wall and a second chamber below the partition wall; wherein the second chamber accommodates a driving mechanism for rotating the winding shaft, and the base cover is mounted to cover the lower edge of the peripheral side wall.

19. The sticker dispenser with sticker roll carrier of claim 18, wherein the driving mechanism is a manually-operated mechanism, comprising: an operating member, configured to operatively reciprocate between a first position and a second position; and a transmitting mechanism, transmission-connected to the operating member and the winding shaft, being capable of transmitting power output from the operating member to the winding shaft to drive the winding shaft to rotate: wherein the transmitting mechanism comprises a one-way clutching device, coupled in condition of the operating member moving in a first direction to implement a transmission of the power, and uncoupled in condition of the operating member moving in a second direction opposite to the first direction to disconnect the transmission of the power.

20. The sticker dispenser with sticker roll carrier of claim 19, wherein the transmitting mechanism is a gear train transmitting mechanism comprising a plurality of gears coupled to each other, the one-way clutch device comprises: a movable gear, configured to be movable between a coupled position and a detached position; and a force-applying member, applying a resilient force to the movable gear towards the coupled position: wherein in condition of the operating member moving in the second direction to reset from the second position to the first position, the movable gear moves from the coupled position to the detached position due to the movement of the operating member in the second direction overcoming the resilient force.

21. The sticker dispenser with sticker roll carrier of claim 19, wherein the transmitting mechanism is a gear train transmitting mechanism formed by multiple intermeshing gears, the one-way clutch device comprises: a movable gear, configured to be movable between a coupled position and a detached position; and a force-applying member, configured to apply elastic force to the movable gear in a direction maintaining the coupled position: wherein in condition of the operating member moving in the first direction to move from the first position to the second position, the movable gear moves from the detached position to the coupled position, driven by the resilient force of the force-applying member.

- 22.** The sticker dispenser with sticker roll carrier of claim 20, wherein at least one wall of the second chamber is provided with guide slots for guiding the movement path of the movable gear when it moves between the coupled position and the detached position.
- 23.** The sticker dispenser with sticker roll carrier of claim 20, wherein the transmitting mechanism comprises: an actuating gear, positioned upstream of and permanently coupled with the movable gear in the power transmission direction; and a driven gear, positioned downstream of and separably coupled with the movable gear in the power transmission direction: wherein when the operating member moves along the second direction, the actuating gear acts upon the movable gear to separate it from the driven gear.
- 24.** The sticker dispenser with sticker roll carrier of claim 19, wherein a reset spring is attached to the operating member and configured to apply force to the operating member in the second direction of movement.
- 25.** The sticker dispenser with sticker roll carrier of claim 18, wherein the driving mechanism, being an electric driving mechanism, comprises: an electric motor that outputs rotational power and is transmission-connected to the winding shaft; wherein at least a portion of the electric motor is disposed within the first chamber and adapted to extend through the central positioning hole of the sticker roll.
- 26.** The sticker dispenser with sticker roll carrier of claim 25, wherein the housing comprises an extension cover protruding into the first chamber, with at least a portion of the electric motor being disposed within the extension cover.
- 27.** The sticker dispenser with sticker roll carrier of claim 26, wherein the extension cover is configured to extend through the central positioning hole so as to position the sticker roll.
- 28.** The sticker dispenser with sticker roll carrier according to claim 27, wherein the extension cover has an accommodation configured to form a pickup space between itself and the wall surface of the central positioning hole, allowing the sticker roll to be gripped and removed from the pickup space.
- 29.** The sticker dispenser with sticker roll carrier of claim 28, wherein the electric motor has a positioning portion corresponding to the accommodation for cooperating with the accommodation to circumferentially fix the electric motor relative to the extension cover.
- 30.** The sticker dispenser with sticker roll carrier of claim 19, further comprising: an optical-electronic device, disposed adjacent to the output port and configured to acquire sticker output information based on photoelectric signals; and a light-shielding portion, arranged to prevent external light interference with photoelectric signals by blocking external light from entering the optical-electronic device through the output port.
-