

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283516

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Orel; Erik et al.

FREEWHEEL DEVICE AND FREEWHEEL CLUTCH

Abstract

A freewheel device having a first freewheel component and a second freewheel component which is axially coupled to the first freewheel component via an axially effective coupling device. When there is relative rotation between the first and second freewheel component in a first rotational direction, it connects the two components together for conjoint rotation and, when there is relative rotation in an opposite second rotational direction, releases the two components so that they can rotate relative to each other and which has at least one coupling element which is subjected to a spring force by means of a spring element. The spring element fixes the coupling element on the first freewheel component and specifies a tilting axis about which the coupling element can be tilted against the spring force.

Inventors: Orel; Erik (Skalica, SK), Slezák; Luboslav (Podbranc, SK)

Applicant: Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)

Family ID: 85979496

Assignee: Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)

Appl. No.: 18/859543

Filed (or PCT Filed): March 30, 2023

PCT No.: PCT/DE2023/100244

Foreign Application Priority Data

DE 10 2022 110 177.0

Apr. 27, 2022

Publication Classification

Int. Cl.: F16D41/12 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is the U.S. National Phase of PCT Appln. No. PCT/DE2023/100244 filed Mar. 30, 2023, which claims priority to DE 10 2022 110 177.0 filed Apr. 27, 2022, the entire disclosures of which are incorporated by reference herein.

TECHNICAL FIELD

[0002] The disclosure relates to a freewheel device. The disclosure further relates to a freewheel clutch.

BACKGROUND

[0003] EP 3 404 279 A1 describes a switchable freewheel clutch comprising a first freewheel component and a second freewheel component, which is coupled to the first freewheel component via a coupling device. The coupling device comprises a plurality of coupling elements which are acted upon by helical spring elements for rotationally engaging in the second freewheel component.

SUMMARY

[0004] The object of the present disclosure is to fix the coupling element to the first freewheel component more cost-effectively and simply. Furthermore, the spring element should be designed to be more cost-effective and space-saving and should be secured more reliably to the first freewheel component.

[0005] At least one of these objects is achieved by a freewheel device having the features described herein. This allows the coupling element to be fixed to the first rotating component in a cost-effective and simple manner and the spring element to be designed more cost-effectively.

[0006] The freewheel device can be arranged in a vehicle. The vehicle can be a motor vehicle. The freewheel device can be arranged in a drive train of the vehicle.

[0007] The freewheel device can be designed to be switchable. The coupling device can be activated or deactivated according to an axial relative position between the first freewheel component and the second freewheel component. When the coupling device is deactivated, the first freewheel component and the second freewheel component are released to rotate relative to each other regardless of the rotational direction of relative rotation.

[0008] The first freewheel component can be rotatable about an axis of rotation or can be fixed in a rotationally fixed manner. The second freewheel component can be rotatable about an axis of rotation or can be fixed in a rotationally fixed manner.

[0009] The first and/or second freewheel component can have a toothing for connection to a connecting component. The first and/or second freewheel component can transmit or support a torque. During relative rotation, the torque can be transmitted in the first rotational direction via the coupling device.

[0010] The coupling element can be made of a metal. The coupling element can be designed as a punched component. The coupling element can be punched from a sheet metal component.

[0011] In a preferred embodiment of the disclosure, it is advantageous if the coupling element for the conjoint rotation connection between the first and second freewheel components engages form-fittingly in a coupling structure in the second freewheel component. The coupling structure can have a toothing into which the coupling element releasably engages in a form-fitting manner. The toothing can be designed as an axial toothing on the second freewheel component. The axial toothing can be located directly axially opposite the coupling element.

[0012] The spring element can be designed to be mirror-symmetrical with respect to a plane of symmetry which includes an axis of symmetry running parallel to the first longitudinal axis and comprises the tilting axis as a normal. This allows the spring element to be reliably secured to the first freewheel component and to be designed cost-effectively.

[0013] A preferred embodiment of the disclosure is advantageous in which the spring element has a rectilinear first spring portion bearing against the first freewheel component and running parallel to a first longitudinal axis, and has a second spring portion protruding away from it at an angle. Preferably, the first spring portion secures the coupling element to the first freewheel component. The second spring portion can exert the spring force on the coupling element, in particular directed towards the second freewheel component.

[0014] In a particular embodiment of the disclosure, it is advantageous if the spring element is constructed in the form of a wire and the first spring portion is a rectilinear first wire portion and the second spring portion is a rectilinear second wire portion. This allows the spring element to be constructed cost-effectively and with minimal weight. The first and/or second wire portion may have a circular or other cross-section.

[0015] In a preferred embodiment of the disclosure, it is advantageous if the spring element has a fastening portion via which the spring element is fastened to the coupling element. The fastening portion can be received in a clamp-like manner on the coupling element.

[0016] In a particular embodiment of the disclosure, it is advantageous if the fastening portion adjoins the first spring portion. This allows the spring element to be made as compact as possible.

[0017] In a preferred embodiment of the disclosure, the fastening portion defines the tilting axis about which the coupling element can be deflected against the spring action of the second spring portion in a direction facing the first freewheel component. This allows both a securing of the coupling element and a tilting movement of the coupling element to be realized.

[0018] In a preferred embodiment of the disclosure, the spring element has a contact portion which bears against the coupling element for transmitting the spring force to the coupling element and is spaced apart from the fastening portion. The contact portion and the fastening portion may be spaced apart from each other with respect to the first longitudinal axis. The contact portion can be directly adjacent to the second spring portion.

[0019] In a particular embodiment of the disclosure, it is advantageous if the fastening portion is suspended as a first U-shaped portion in the coupling element and the first and second spring portions form the legs of a second U-shaped portion. This allows the installation space of the spring element to be further reduced.

[0020] Furthermore, at least one of the above-mentioned objects is achieved by a freewheel clutch for switchable torque transmission, comprising the freewheel device with at least one of the preceding features, in which the first freewheel component and the second freewheel component are connected to one another in a torque-transmitting manner during relative rotation in the first rotational direction and with which torque transmission between the first freewheel component and the second freewheel component is interrupted during relative rotation in the second rotational direction.

[0021] Further advantages and advantageous embodiments of the disclosure arise from the description of the figures and the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] The disclosure is described in detail below with reference to the drawings. In the drawings:

[0023] FIG. 1: shows an exploded view of a freewheel clutch in a particular embodiment of the disclosure.

[0024] FIG. 2: shows a three-dimensional view of the spring element from FIG. 1.

[0025] FIG. 3: shows a three-dimensional view of the spring element and the coupling element from FIG. 1.

[0026] FIG. 4: shows a detail of a three-dimensional view of the first freewheel component from FIG. 1.

[0027] FIG. 5: shows a detail of a three-dimensional view of the first freewheel component and the spring element from FIG. 1.

[0028] FIG. 6: shows a detail of a three-dimensional view of the freewheel clutch from FIG. 1.

DETAILED DESCRIPTION

[0029] FIG. 1 shows an exploded view of a freewheel clutch in a particular embodiment of the disclosure. The freewheel clutch **10** comprises a freewheel device **12** having a first freewheel component **14** and a second freewheel component **16**. The first freewheel component **14** comprises an external tothing **18** for connection to a connecting element and an internal tothing **20** for connection to a shaft.

[0030] The second freewheel component **16** is coupled to the first freewheel component **14** via a coupling device **22** which, during a relative rotation between the first and second freewheel components **14**, **16** in a first rotational direction **24**, connects the two components together for conjoint rotation, and, during a relative rotation in an opposite second rotational direction **26**, releases the two components to rotate relative to each other. The freewheel device **12** can be designed to be switchable in that the first and second freewheel components **14**, **16** are axially movable relative to each other. The coupling device **22** is activated or deactivated according to the relative axial position between the first and second freewheel components **14**, **16**. When the coupling device **22** is deactivated, the first and second freewheel components **14**, **16** are released to rotate relative to each other regardless of the rotational direction **24**, **26**.

[0031] The coupling device **22** comprises a plurality of coupling elements **30** which are arranged circumferentially distributed on an axial side **28** of the first freewheel component **14** and on each of which a spring force acts via a spring element **32**. The coupling device **22** further comprises a coupling structure **34** on an axial side **36** of the second freewheel component **16** axially opposite the axial side **28** of the first freewheel component **14**. The coupling structure **34** is designed as an axial tothing **38**, into which the coupling elements **30** engage form-fittingly during relative rotation in the first rotational direction **24**.

[0032] The coupling elements **30** are preferably designed as snap-in bodies **40** which, supported by the spring force of the spring elements **32**, engage form-fittingly in the coupling structure **34** of the second freewheel component **16** for the conjoint rotation connection between the first and second freewheel components **14**, **16** and are fastened in openings **42** in the first freewheel component **14**.

[0033] FIG. 2 shows a three-dimensional view of the spring element from FIG. 1. The spring element **32** is designed in the form of a wire, comprising a first spring portion **44**, which bears against the first freewheel component and which runs parallel to a first longitudinal axis **46** in a straight line, and has a rectilinear second spring portion **48** protruding at an angle therefrom. The first spring portion **44** is designed as a rectilinear first wire portion **50** and the second spring portion **48** is designed as a rectilinear second wire portion **52**.

[0034] The first spring portion **44** is followed by a fastening portion **54** which fastens the spring element **32** to the coupling element. The fastening portion **54** extends directly from the first spring portion **44**, while the second spring portion **48** merges into a contact portion **56** which bears against the coupling element and is spaced apart from the fastening portion **54** with respect to the first longitudinal axis **46**.

[0035] FIG. 3 shows a three-dimensional view of the spring element and the coupling element from FIG. 1. The spring element **32** is pre-installed on the coupling element **30**, preferably clipped in. The spring element **32** and the coupling element **30** form a pre-installation assembly. The fastening portion **54** is suspended as a first U-shaped portion **58** in a groove **59** in the coupling element **30**.

The first and second spring portions **44**, **48** form the legs of a second U-shaped portion **60**. The second spring portion **48** extends at an angle relative to the first spring portion **44**.

[0036] The fastening portion **54** defines a tilting axis **62** about which the coupling element **30** can be deflected counter to the spring action of the second spring portion **48** in a direction **63** facing the first freewheel component. The second spring portion **48** bends downwards in the direction of the first freewheel component.

[0037] The angle of inclination of the second spring portion **44** defines the inclination of the coupling element **30** about the tilting axis **62**.

[0038] The spring element **32** is designed to be mirror-symmetrical with respect to a plane of symmetry **66** which includes an axis of symmetry **64** running parallel to the first longitudinal axis **46** and comprises the tilting axis **62** as a normal.

[0039] FIG. **4** shows a detail of a three-dimensional view of the first freewheel component from FIG. **1**. The first freewheel component **14** has the opening **42** for receiving the coupling element. The contour of the opening **42** is matched to the contour of the coupling element. As a result, the stability of the first freewheel component **14** can be increased and the first freewheel component **14** can be designed to be lighter and more space-saving.

[0040] FIG. **5** shows a detail of a three-dimensional view of the first freewheel component and the spring element from FIG. **1**. The first freewheel component **14** accommodates the spring element **32**. For this purpose, the first spring portion **44** is suspended in a shoulder **68** of the first freewheel component **14** and thus the spring element **32** is fastened to the first freewheel component **14**. The spring element **32** can be released from the first freewheel component **14** by pressing the two opposite first spring portions **44** towards each other and thus the first spring portion **44** can be removed from the shoulder **68**.

[0041] The first freewheel component **14** has a ramp **69** by which the first spring portion **44** is compressed and the spring element **32** can be easily inserted.

[0042] FIG. **6** shows a detail of a three-dimensional view of the freewheel clutch from FIG. **1**. The freewheel clutch **10** comprises the first freewheel component **14**, the coupling element **30** and the spring element **32** which fastens said coupling element to the first freewheel component **14**. The coupling element **30** is fixed to the first freewheel component **14** via the spring element **32**. The fastening portion **54** secures the spring element **32** to the coupling element **30** and the first spring portion **44** is suspended in the shoulder **68** of the first freewheel component **14**. The coupling element **30** is arranged inclined relative to the first freewheel component **14** and can be tilted against the spring force of the spring element **32** toward the first freewheel component **14** about the tilting axis **62** defined by the fastening portion **54**.

[0043] The coupling element **30** protrudes axially from the axial side **28** of the first freewheel component **14** due to the inclined arrangement and can thus engage form-fittingly in the coupling structure of the second freewheel component.

LIST OF REFERENCE SIGNS

[0044] **10** Freewheel clutch [0045] **12** Freewheel device [0046] **14** First freewheel component [0047] **16** Second freewheel component [0048] **18** External toothing [0049] **20** Internal toothing [0050] **22** Coupling device [0051] **24** First rotational direction [0052] **26** Second rotational direction [0053] **28** Axial side [0054] **30** Coupling element [0055] **32** Spring element [0056] **34** Coupling structure [0057] **36** Axial side [0058] **38** Axial toothing [0059] **40** Snap-in body [0060] **42** Opening [0061] **44** First spring portion [0062] **46** First longitudinal axis [0063] **48** Second spring portion [0064] **50** First wire portion [0065] **52** Second wire portion [0066] **54** Fastening portion [0067] **56** Contact portion [0068] **58** Portion [0069] **59** Groove [0070] **60** Portion [0071] **62** Tilting axis [0072] **63** Direction [0073] **64** Axis of symmetry [0074] **66** Plane of symmetry [0075] **68** Shoulder [0076] **69** Ramp

Claims

- 1.** A freewheel device having a first freewheel component, a second freewheel component, which is axially coupled to the first freewheel component via an axially effective coupling device, which, when there is relative rotation between the first and second freewheel components in a first rotational direction, connects the first and second freewheel components together for conjoint rotation and, when there is relative rotation in an opposite second rotational direction, releases the first and second freewheel components so that they can rotate relative to each other and which has at least one coupling element which is subjected to a spring force by a spring element, wherein the spring element fixes the coupling element on the one hand to the first freewheel component and on the other hand defines a tilting axis about which the coupling element can be tilted against the spring force.
 - 2.** The freewheel device according to claim 1, wherein the coupling element for the conjoint rotation connection between the first and second freewheel components engages form-fittingly in a coupling structure in the second freewheel component.
 - 3.** The freewheel device according to claim 1, wherein the spring element has a rectilinear first spring portion bearing against the first freewheel component and running parallel to a first longitudinal axis and has a second spring portion protruding at an angle therefrom.
 - 4.** The freewheel device according to claim 3, wherein the spring element is constructed in the form of a wire and the first spring portion is a rectilinear first wire portion and the second spring portion is a rectilinear second wire portion.
 - 5.** The freewheel device according to claim 1, wherein the spring element has a fastening portion, via which the spring element is fastened to the coupling element.
 - 6.** The freewheel device according to claim 5, wherein the fastening portion adjoins the first spring portion.
 - 7.** The freewheel device according to claim 5, wherein the fastening portion defines the tilting axis about which the coupling element can be deflected against a spring action of the second spring portion in a direction facing the first freewheel component.
 - 8.** The freewheel device according to claim 5, wherein the spring element has a contact portion which bears against the coupling element for transmitting the spring force to the coupling element and is spaced apart from the fastening portion.
 - 9.** The freewheel device according to claim 5, wherein the fastening portion is suspended as a first U-shaped portion in the coupling element and the first and second spring portions form the legs of a second U-shaped portion.
 - 10.** A freewheel clutch for switchable torque transmission, comprising the freewheel device according to claim 1, in which the first freewheel component and the second freewheel component are connected to one another in a torque-transmitting manner during relative rotation in the first rotational direction, and with which a torque transmission between the first and second freewheel components is interrupted during relative rotation in the second rotational direction.
-