

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283551

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

MÜLLER; Sebastian et al.

VALVE FOR CONTROLLING THE FLOW OF A FLUID

Abstract

A valve which includes a valve housing in which a valve member is positioned which can be positioned in a closed position and in a maximum open position as part of a lifting movement which can be caused by a drive apparatus. A spring apparatus causes the valve member to reach an intermediate open position when the drive apparatus is deactivated. The spring apparatus contains a closing spring acting in the closing direction and an opening spring acting in the opening direction, the spring forces of which are matched to one another in such a way that the intermediate open position forms a basic position of the valve.

Inventors: MÜLLER; Sebastian (Walddorfhäslach, DE), PATZ; Heiko (Weilheim, DE), SZILI; Tamás (Esslingen, DE)

Applicant: FESTO SE & CO. KG (Esslingen, DE)

Family ID: 1000008641797

Appl. No.: 18/862366

Filed (or PCT Filed): April 28, 2023

PCT No.: PCT/EP2023/061274

Foreign Application Priority Data

DE 10 2022 110 949.6

May. 04, 2022

Publication Classification

Int. Cl.: F16K31/06 (20060101); F16K1/42 (20060101)

U.S. Cl.:

Background/Summary

[0001] This application claims priority to DE 10 2022 110 949.6, filed 4 May 2022, which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] The invention relates to a valve for controlling the flow of a fluid, comprising a valve housing which delimits a valve chamber into which a feed channel for feeding in fluid and a working channel enabling a fluid outlet open, wherein a feed channel opening of the feed channel is framed by a valve seat facing the valve chamber, opposite which valve seat in the valve chamber there is a closing surface positioned on an axial front side of a valve member of the valve, wherein the valve member is movable in the axial direction of a main axis of the valve by a lifting movement, which is caused by a driving force of a drive apparatus of the valve, and which lifting movement is oriented in the axial direction of a main axis, in a closed position, in which the valve bears with its closing surface against the valve seat and thereby separates the feed channel from the valve chamber in a fluid-tight manner, or in at least one open position raised from the valve seat and thereby releasing a fluid connection between the feed channel and the valve chamber in permanent fluid connection with the working channel, and wherein the valve member is constantly biased in the direction of the closed position by a closing spring of a spring apparatus of the valve.

[0003] A valve of this type known from DE 10 2013 011 759 A1 comprises a valve member which is pretensioned by a closing spring into a closed position in which it rests within a valve chamber against a valve seat surrounding a feed channel opening, thereby preventing fluid from entering the valve chamber from a feed channel. By actuating an electric drive apparatus based on an electrodynamic operating principle, the valve member can be moved into at least one open position raised from the valve seat and held in this open position so that a pressurized fluid fed into the feed channel can overflow into the valve chamber and flow out of the valve chamber through a working channel leading to a consumer. As the valve member takes up the closed position when the drive apparatus is deactivated, it is a valve of the “Normally Closed” type. Due to the required power consumption, such a valve has energy disadvantages in applications that regularly require a much longer maintenance of an open position compared to maintaining a closed position, as the drive apparatus must be activated for a correspondingly long time. A valve described in WO 2017/080602 A1 is subject to the same issue.

[0004] Electrically actuated valves of the “Normally Closed” type are also described in DE 2 208 183 A1, DE 297 23 707 U1, DE 10 2014 220 222 A1, EP 0 611 349 B1 and EP 0 698 738 B1.

[0005] EP 1 959 177 B1 and U.S. Pat. No. 6,367,766 B1 describe valves of the “Normally Open” type, which take up an open position that allows fluid flow when the drive apparatus is deactivated. Here, however, particularly high drive forces must be applied to maintain the closed position, since not only the spring force of an opening spring constantly acting in the opening direction must be overcome, but also the fluid pressure acting on the valve member in the opening direction. Using a weaker spring to remedy the problem could possibly no longer guarantee safe opening when the drive apparatus is deactivated. A reduction in the opening force due to the fluid pressure could only be achieved with a significantly reduced nominal diameter and correspondingly lower flow values.

SUMMARY OF THE INVENTION

[0006] It is the object of the invention to take measures that enable energy-saving and reliable operation of a valve while allowing high flow rates.

[0007] This object is solved by a valve in conjunction with the features mentioned at the beginning

in that, in addition to the closing spring, the spring apparatus has an opening spring which constantly biases the valve member in the direction of the at least one open position, wherein the closing spring and the opening spring, which acts in the opposite direction in this respect, are mutually coordinated with respect to their spring forces in such a way that the valve member takes up a basic position without driving forces of the drive apparatus, which basic position is an intermediate open position lying between the closed position and a maximum open position.

[0008] In this way, a valve is present whose type can be described as “Normally Partially Open”. The spring apparatus, which comprises both a closing spring and an opening spring, holds the valve member in an open position known as the intermediate open position when the drive apparatus is deactivated, i.e. when no drive forces are exerted on the valve member by the drive apparatus, in which fluid flow from the feed channel into the valve chamber is possible, albeit at a lower flow rate than in the maximum open position. The intermediate open position of the valve member is a stroke position in which the closing forces generated by the closing spring and the opening forces generated by the opening spring equalize, resulting in a quasi-zero force point. In order to close or further open the valve from the intermediate open position, opposing drive forces are required from the drive apparatus, although these are lower than the drive forces required for a pure “Normally Closed” valve or a pure “Normally Open” valve of comparable nominal size.

[0009] In principle, the valve can be configured as a valve actuated by fluid power, in particular pneumatically, with a correspondingly configured drive apparatus. However, preferred is a valve configuration whose drive apparatus is of an electrically actuatable type and which can be referred to as an electric drive apparatus. In particular, an electrodynamic drive apparatus based on Lorentz forces, or an electromagnetic drive apparatus based on reluctance forces is used.

[0010] In order to close the valve in an electrically actuated drive apparatus starting from the intermediate open position of the valve member, it is preferable to generate a current in a coil apparatus of the drive apparatus, which generates a force acting in the closing direction and presses the valve member against the spring force of the opening spring acting in the opening direction against the valve seat. To reopen the valve from the closed position, the drive force acting to close the valve can be reduced or removed. When the intermediate open position is reached, the direction of current flow in the coil apparatus can be reversed so that a drive force acting in the opening direction is generated, which now acts against the closing spring and opens the valve further beyond the intermediate open position.

[0011] As the valve member has to be moved from the intermediate open position by less than the maximum possible lift for the closing process, the drive forces to be applied are correspondingly low, so that there is no risk of overheating due to the electrical energy input, even with a large nominal width. The same applies to holding the valve member in any open position beyond the intermediate open position, wherein there is also a cooling effect caused by the fluid flowing through.

[0012] In an embodiment considered to be particularly favorable, the drive apparatus comprises a first drive component formed by an electrical coil apparatus and a second drive component interacting with the electrically powered coil apparatus to generate a driving force acting on the valve member in the axial direction of the main axis. One of these two drive components is positioned on the valve member, the other on the valve housing. In this way, for example, a solenoid valve can be realized or preferably an electrodynamic operating principle realized as a solenoid plunger principle or as a moving coil principle.

[0013] Preferably, the valve comprises a control electronics configured to control the drive apparatus. In conjunction with an electric drive apparatus, the control electronics is configured in particular in such a way that it can generate an electrical power to the drive apparatus which has either an opening current direction acting on the valve member or a closing current direction acting on the valve member, so that the valve member can be closed or opened further starting from the intermediate open position by selecting a corresponding current direction. If a lifting movement

over the full lift between the closed position and the maximum open position is desired, the control electronics can reverse the current direction when passing through the intermediate open position. [0014] Preferably, the control electronics of the valve can be used to electrically power the drive apparatus in both current directions with variable current intensity. In this way, any partial open position between the closed position and the maximum open position can be continuously adjusted. Such a valve can preferably be operated as a proportional valve.

[0015] In particular, the control electronics is integrated into the valve housing or attached to the outside of it. However, it can also be realized as a separate component. For example, it contains a circuit board fitted with a microprocessor.

[0016] In order to enable precise adjustment of a desired lifting position and, accordingly, a desired flow rate, it is preferable for the valve to comprise a position detection apparatus by means of which lifting positions of the valve member that can be reached during the lifting movement of the valve member can be detected. In particular, the position detection apparatus is connected to the optional control electronics, which can process the valve member position data supplied by the position detection apparatus as feedback information.

[0017] Preferably, the control electronics has a closed-loop control functionality. In this way, closed-loop position control of the drive apparatus is possible on the basis of the position data obtained by means of the position detection apparatus. The position detection apparatus expediently has at least one Hall sensor or another measuring apparatus for determining the stroke position, wherein the other measuring apparatus can also be configured for laser-based or ultrasound-based position detection, for example. The position detection apparatus is expediently equipped with the functionality of a displacement measuring system configured for continuous position detection.

[0018] Preferably, the two springs of the spring apparatus acting in opposite directions on the valve member are configured with respect to force in such a way that the valve member in the intermediate open position takes up at least essentially a half-open position, in which the flow cross-section available for the fluid passing through the feed channel opening is approximately or exactly half as large as a maximum flow cross-section released in the maximum open position of the valve member.

[0019] In particular, in the intermediate open position, the valve member reaches a lifting position in which it is only just above the closing point at which the closing surface of the valve member touches the valve seat fixed to the housing.

[0020] Both the closing spring and the opening spring are expediently each a compression spring. Such a configuration is preferred to that of a return spring. In particular, both the closing spring and the opening spring are coil springs.

[0021] In order to preset the desired intermediate open position, the closing spring and the opening spring are expediently configured such that they have force-displacement characteristics and/or winding pitches that are matched to one another and in particular differ from one another.

[0022] A configuration in which the closing spring and the opening spring are configured as separate individual springs of the spring apparatus is considered to be particularly advantageous. This favors the coordinated configuration of the spring forces on both sides and enables a particularly space-saving accommodation in the valve housing, in particular in that the opening spring coaxially encloses the closing spring, or vice versa.

[0023] Alternatively, the spring apparatus could have only a single spring element which is gripped by the valve member at a point located between its two end regions, wherein the gripping point is selected according to the desired spring force ratio. The intermediate tapping can be realized, for example, by attaching the valve member to the single spring element at the relevant point, wherein the length sections of the one-piece spring element axially adjoining the tapping point on both sides act as an opening spring in one case and as a closing spring in the other case.

[0024] In a configuration regarded as favorable, the valve member comprises a hat-shaped anterior

end section which comprises a front ground wall carrying the closing surface, a sleeve-shaped sidewall extending axially away from the inner feed channel opening starting from the ground wall, and an annular disc-shaped support wall projecting radially outwards from the sidewall at an axial distance from the front ground wall. In this case, the closing spring is positioned so that it is enclosed by the sleeve-shaped sidewall and is supported on the one hand on the ground wall of the valve member and on the other hand on a housing-fixed support body positioned axially opposite the ground wall. The opening spring is positioned so that it surrounds the sleeve-shaped sidewall and is supported axially on the valve housing inside the valve chamber on the one hand and on the support section of the valve member on the other. The sleeve-shaped sidewall is located radially between the closing spring and the opening spring, wherein the closing spring is enclosed by the opening spring over at least part of its overall length in a coaxial arrangement.

[0025] Preferably, the valve member is made of several parts and comprises a one-piece valve member base body, on which a preferably disk-shaped sealing element is positioned on the front side facing the inner feed channel opening as a further component of the valve member, which defines the closing surface cooperating with the valve seat.

[0026] The closing surface of the valve member is preferably formed on a sealing element consisting of a rubber-elastic material.

[0027] In principle, the invention can be realized with valves of any functionality. The embodiment according to the invention proves to be particularly advantageous in conjunction with a 2/2-way valve. The invention can be implemented both in pure switching valves and in proportional valves.

[0028] The valve seat can be formed directly on the valve housing. Preferably, it has a collar-like, axially raised structure, wherein it defines an annular sealing edge against which the closing surface rests in the closed position of the valve member.

[0029] According to an advantageous embodiment of the invention, the valve seat is located on a sleeve-shaped valve seat element which is separate from the valve housing, is aligned coaxially to the main axis and is inserted into an inner end section of the feed channel with a variable axial position relative to the main axis and is fixed to the housing. During assembly of the valve, the axial position of the valve seat element with respect to the valve housing can be variably adjusted and fixed axially immovable to the valve housing in the set target position. For example, the valve seat element can be pressed into the end section of the feed channel with variable press-fit depth. Additionally or alternatively, adhesive fixing or screw fixing could also be considered. The variability of the axial position during valve assembly offers the advantage of being able to perform a calibration in order to compensate for both the geometric component tolerances and the spring tolerances. If the valve has an electric drive apparatus, the valve seat element and consequently the valve seat can be moved within the valve housing during calibration, for example, until a desired flow rate is achieved for a given electric current.

[0030] It is particularly advantageous to provide special pressure compensation measures with regard to the valve member in order to realize relatively large nominal diameters and still keep the drive forces to be applied low. In this respect, it is preferable if the valve member has a compensation surface which is oriented axially in the opposite direction to the closing surface and which compensation surface delimits a compensation chamber formed in the valve housing, which compensation chamber constantly communicates with the region axially upstream of the closing surface via at least one compensation channel passing through the valve member. This means that the fluid pressure in the area upstream of the closing surface and in the compensation chamber is always at least essentially the same, resulting in compensation of the pressure force acting axially on the valve member.

[0031] At least essentially complete pressure compensation is possible if, in an advantageous manner, the compensation surface of the valve member is at least essentially and preferably exactly the same size as the area of the inner feed channel opening that can be covered by the valve member, i.e., the area framed by the valve seat. The pressure force compensation is effective both

in the closed position and in any open position of the valve member. As a result, the valve member can be forced to its lifting movement with a very low driving force and held in the respective lifting position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0032] The invention is explained in more detail below with reference to the enclosed drawing. It shows:

[0033] FIG. 1 a preferred embodiment of the valve according to the invention in a longitudinal section, wherein the valve member is shown taking up the intermediate open position and wherein the lifting positions taken up by the valve member in the closed position and in the maximum open position are additionally indicated by dotted lines, and

[0034] FIG. 2 an isometric exploded view of the valve illustrated in FIG. 1.

DETAILED DESCRIPTION

[0035] The valve designated in its entirety by reference number 1 has a valve housing 2, which is preferably made up of several parts and comprises a valve chamber 3 in its interior.

[0036] Several valve channels 4, 5 which pass through the valve housing 2 and through which a fluid can flow open into the valve chamber 3; these are, by way of example, a feed channel 4 and a working channel 5. At its opposite end region, the feed channel 4 opens out via an outer connection opening 4a and the working channel 5 opens out via an outer connection opening 5a to an outer surface 6 of the valve housing 2, so that in particular it is possible to connect a further fluid line to each.

[0037] During operation of the valve 1, the feed channel 4 is connected via its outer connection opening 4a to an external pressure source P, which provides a pressurized fluid, wherein this is in particular compressed air.

[0038] During operation of the valve 1, the working channel 5 is in fluid connection via its outer connection opening 5a with a consumer A, which is, for example, a fluid-actuated actuator.

[0039] The valve 1 makes it possible to control a fluid flow between the feed channel 4 and the working channel 5, namely through the valve chamber 3. The valve 1 allows either shutting off, i.e., closing the fluid connection between the feed channel 4 and the valve chamber 3, or opening this fluid connection with the result that the pressurized fluid can flow from the feed channel 4 through the valve chamber 3 into the working channel 5.

[0040] The feed channel 4 opens into the valve chamber 3 with an inner channel opening, referred to below as feed channel opening 7 for better differentiation. The feed channel opening 7 is located in the area of a ground surface 3a of the valve chamber 3 and is framed by an annular valve seat 8 facing the valve chamber 3. The valve seat 3 is expediently configured in a collar-shaped raised form with respect to a surface section of the ground surface 3a surrounding it.

[0041] The valve 1 has an imaginary main axis 10. The feed channel opening 7 and the valve seat 8 are aligned in the axial direction of this main axis 10, wherein they are positioned in particular coaxially thereto. The ground surface 3a extends in particular in a plane orthogonal to the main axis 10.

[0042] The working channel 5 opens into the valve chamber 3 distanced from the feed channel opening 7 and, in particular, laterally, wherein its corresponding channel opening is referred to as working channel opening 12. While the fluid connection between the valve chamber 3 and the working channel 5 is permanently open, the fluid connection between the feed channel 4 and the valve chamber 3 can be controlled by means of a valve member 13 of the valve 1.

[0043] While the valve 1 of the embodiment example is designed as a 2/2-way valve, a design with a different valve functionality is also possible, for example with a 3/2 valve function. In such cases

in particular, the valve **1** can easily have one or more additional valve channels which open into the valve chamber **3**.

[0044] Preferably, the valve member **13** has an elongated shape and, by way of example, has an imaginary longitudinal axis **14** that coincides with the main axis **10**.

[0045] In the embodiment example, the valve chamber **3** is formed by the axial end region of a blind-hole-like reception recess **16** of the valve housing **2**, into which the valve member **13** is inserted. The valve member **13** has an axial front side **15** with which it faces the valve chamber **3**. The valve member **13** also has an axial rear side **19** opposite the axial front side **15** in the axial direction of the main axis **10**.

[0046] The reception recess **16** is bounded axially on the inside by a ground surface **16a** formed on the valve housing **2**, which forms the ground surface **3a** of the valve chamber **3**. On the outside axially opposite the ground surface **16a**, the reception recess **16** is closed by a closing element **11**, for example a lid-shaped closing element, of the valve housing **2**. The valve member **13** is located axially between the ground surface **3a**, **16a** and the closing element **11**, wherein it delimits the valve chamber **3** on a side axially opposite the ground surface **16a**.

[0047] The valve member **13** comprises an axially oriented end surface on its axial front side **15**, which forms a closing surface **26** facing the feed channel opening **7** and the valve seat **8**. Upon actuation of a drive apparatus **27** of the valve **1**, the valve member **13** can be caused to perform a linear lifting movement **28**, which is oriented in the axial direction of the main axis **10** and is illustrated in the drawing by a double arrow. The valve member **13** can be moved either in a first direction of movement **28a** pointing forwards in the direction of the valve seat **8** or in a second direction of movement **28b** pointing backwards in the opposite direction in the sense of moving away from the valve seat **8**. For this purpose, the drive apparatus **27** can exert a correspondingly oriented drive force on the valve member **13**.

[0048] Within the lifting movement **28**, the valve member **13** can be positioned in different lifting positions. One of these lifting positions is an open position shown in FIG. **1** and additionally indicated by a dotted line, referred to as intermediate open position **41**, in which the valve member **13** is lifted with its closing surface **26** from the valve seat **8**, albeit by an amount that is less than a possible maximum amount.

[0049] Other possible lifting positions of the valve member **13** are a closed position **42** and an open position designated as maximum open position **43**, each of which is also indicated by a dotted line in FIG. **1**.

[0050] In the closed position **42**, the valve member **13** rests with its closing surface **26** against the valve seat **8** with sealing and at the same time covers the feed channel opening **7**. In this way, the feed channel **4** in the closed position **42** of the valve member **13** is separated in a fluid-tight manner from the valve chamber **3** and the working channel **5** permanently connected to it.

[0051] The distance measured in the axial direction of the main axis **10** between the valve seat **8** and the closing surface **26**, which is also referred to as the axial distance, determines a free flow cross-section that is available to the fluid or the fluidic pressure medium for the transition between the feed channel **4** and the valve chamber **3**. The free flow cross-section determines the flow rate of the overflowing fluid, which can also be referred to as the flow rate.

[0052] In the maximum open position **43** of the valve member **13**, the closing surface **26** is positioned at the greatest possible axial distance from the valve seat **8**. This maximum axial distance is greater than the axial distance between the closing surface **26** and the valve seat **8** in the intermediate open position **41**.

[0053] In the maximum open position **43** of the valve member **13**, the fluidic pressure medium fed into the feed channel **4** has a released maximum flow cross-section for passing into the valve chamber **3**. In the intermediate open position **41** of the valve member **13**, the released flow cross-section is smaller than the maximum flow cross-section.

[0054] By actuating the drive apparatus **27** accordingly, the valve member **13** can optionally be

positioned at least in the closed position **42**, in the maximum open position **43** or in the intermediate open position **41**.

[0055] If the valve **1** is configured as a switching valve, the movability of the valve member **13** is preferably limited to these three lifting positions. Preferably, however, the valve **13** is configured as a continuously adjustable proportional valve in accordance with the illustrated embodiment example, wherein the valve member **13** can be positioned not only in the intermediate open position **41**—in particular steplessly—but also in any other open positions between the closed position **42** and the maximum open position **43**, which can be designated as partial open positions. In any of these other partial open positions, the distance between the closing surface **26** and the valve seat **8** is greater or smaller than in the intermediate open position **41**.

[0056] The exemplary valve member **13** has a pot-like shape with a ground wall **17** associated with the axial front side **15** and a hollow cylindrical sidewall **18** projecting from the ground wall **17** in the direction of the axial rear side **19**. The pot shape defines a valve member interior **22** facing away from the valve chamber **3** and also separated in this respect.

[0057] The valve **1** is equipped with a spring apparatus **32**, which is integrated between the valve member **13** and the valve housing **2** as far as the flow of force is concerned. The spring apparatus **32** holds the valve member **13** in the intermediate open position **41** when the drive apparatus **27** mentioned above does not exert any driving forces on the valve member **13**. In other words, the intermediate open position **41** represents a basic position of the valve member **13**, which the valve member **13** takes up when the drive apparatus is deactivated. The valve **1** is therefore (only) partially open when the drive apparatus **27** is deactivated, so that it can be described as a valve of a new type “Normally Partially Open”.

[0058] This functionality results from a special configuration of the spring apparatus **32**. The spring apparatus **32** has a closing spring **32a** on the one hand and an opening spring **32b** on the other. The closing spring **32a** is a spring that constantly acts on the valve member **13** in the direction of the closed position, for example in the first direction of movement **28a**, with a spring force that can be designated as closing force FS. The opening spring **32b** is a spring that constantly acts on the valve member **13** in the opening direction, for example in the second direction of movement **28b**, with a spring force that can be designated as opening force FO. The valve member **13** is therefore constantly acted upon in opposite directions of the main axis **10** by spring forces FS, FO, which are provided on the one hand by the closing spring **32a** and on the other hand by the oppositely acting opening spring **32b**.

[0059] The closing spring **32a** and the opening spring **32b**, which are also referred to simply as springs **32a**, **32b** when named together, are matched to each other with regard to their spring forces FS, FO in such a way that the valve member **13** takes up the described basic position, i.e. the intermediate open position **41**, without any effective drive forces from the drive apparatus **27**. In the basic position or intermediate open position **41**, there is a balance of forces between the two springs **32a**, **32b** on the valve member **13**, so that one can speak of a force zero point, since no resulting spring forces act on the valve member **13** in the axial direction of the main axis **10**.

[0060] Each of the two springs **32a**, **32b** is supported on the valve member **13** on the one hand and directly or indirectly on the valve housing **2** on the other.

[0061] Although it would in principle be possible to realize one or both of the springs **32a**, **32b** as compression springs, they are expediently mechanical springs **32a**, **32b** according to the illustrated embodiment example.

[0062] According to the illustrated embodiment example, the drive apparatus **27** is preferably of electrically actuated configuration. By applying an electrical actuating voltage, the drive apparatus **27** can cause a driving force acting on the valve member **13** in the axial direction of the main axis **10**, which, by overcoming the spring forces FS, FO of the two springs **32a**, **32b**, causes a lifting movement **28** of the valve member **13** in the first direction of movement **28a** or the second direction of movement **28b** and by means of which the valve member **13** can be held in a set lifting

position for as long as desired. The drive force of the drive apparatus 27 is added to the closing force FS or the opening force FO, depending on the direction of action.

[0063] Preferably, the electrically actuable drive apparatus 27 comprises a first drive component 34 and a second drive component 35 interacting with the first drive component 34 to generate the driving force. One of the two drive components 34, 35 is positioned on the valve member 13, the other of the two drive components 34, 35 is positioned on the valve housing 2. As an example, the first drive component 34 is positioned on the valve member 13 and the second drive component 35 on the valve housing.

[0064] One of the two drive components 34, 35 is expediently configured as an electrical coil apparatus 34a that can be electrically powered by applying the aforementioned actuating voltage. The lifting position currently taken by the valve member 13 relative to the valve seat 8 depends on the level and polarity of the actuating voltage applied to the electrical coil apparatus 34a. The selected polarity determines a current direction of the electric current flowing through the coil apparatus 34a and, accordingly, the effective direction of the drive force that can be generated.

[0065] By way of example, the first drive component 34 is the coil apparatus 34a. As an example, it is positioned at the valve member 13 and is supported in particular by its sidewall 18. It therefore always participates in the lifting movement 28. When electrically powered, the coil apparatus 34a cooperates with the second drive component 35, which is stationary with respect to the valve housing 2.

[0066] Preferably and according to the illustrated embodiment example, the drive apparatus 27 is an electrodynamic drive apparatus 27. In this case, the second drive component 35 comprises a permanent magnet apparatus 35a, which cooperates with the coil apparatus 34a according to the electrodynamic operating principle.

[0067] As an example, the permanent magnet apparatus 35a enters the valve member interior 22 from the axial rear side 19. It sits, for example, on a support projection 20 of the closing element 11, which projects centrally into the reception recess 16 and is, for example, rod-shaped. In particular, the permanent magnet apparatus 35a consists of at least one ring magnet 44, which is coaxial with the main axis 10 and is flanked axially on both sides by an annular ferromagnetic forward conductance disk 45.

[0068] Preferably, the second drive component 35 also contains a ferromagnetic guiding sleeve 46 which is stationary relative to the valve housing 2, is inserted coaxially into the reception recess 16 and encloses the valve member 13 radially on the outside. The guiding sleeve 46 expediently functions simultaneously as a guide element for radial support and linear guidance of the valve member 13 during the lifting movement 28. Preferably, the valve member 13 has a plurality of axially spaced-apart annular collar-like guiding fins 47 on the radial outside, which bear against the inner circumferential surface of the guiding sleeve 46 in a slidingly displaceable manner. The coil apparatus 34a, which has at least one coil section 48 consisting of wound wire, is conveniently positioned axially between the guiding fins 47.

[0069] When the coil apparatus 34a is electrically powered, the charge carriers flowing in it cooperate with the permanent magnetic field of the permanent magnet apparatus 35a, resulting in the so-called Lorentz force, which acts as a driving force for the valve member 13. The current direction determines the effective direction of the Lorentz force and consequently the driving force, while the current strength determines the level of the driving force.

[0070] As an example, the electrodynamic drive apparatus 27 is configured as a plunger coil drive. However, a configuration as a plunger magnet drive with an interchanged arrangement of the two drive components 34, 35 and a permanent magnet apparatus 35a that participates in the lifting movement 28 is also possible.

[0071] According to an embodiment example, the second drive component 35 is designed as a ferromagnetic apparatus instead of a permanent magnet apparatus 35a, which interacts with the coil apparatus 34a according to the reluctance principle.

[0072] It is understood that other configurations of drive apparatuses **27** can also be provided for actuating the valve member **13**.

[0073] Preferably, the valve member **13** is made up of several parts, wherein it has a particularly one-piece valve member base body **48**, which is equipped on the axial front side **15** with a sealing element **49** consisting of an elastomer material or another rubber-elastic material. As an example, the aforementioned pot shape of the valve member **13** is determined by the shape of the valve member base body **48**. The ground wall **17** of the valve member **13** is composed of a base section **48a** of the valve member base body **48** and the sealing element **49** attached to the front outside of this base section **48a**.

[0074] The sealing element **43** is preferably disk-shaped. According to the embodiment example, it is buttoned into the base section **42a**, but can additionally or alternatively also be glued or welded in place, for example. In any case, the elastically flexible sealing element **43** is supported in the axial direction of the main axis **10** by the base section **42a** of the valve member base body **42**.

[0075] The closing surface **26** is formed on the sealing element **43**. Expediently, the closing surface **26** is limited to a central area of the forward-facing front end face of the sealing element **49**. The outer diameter of the sealing element **49** is larger overall than the outer diameter of the closing surface **26**. In this respect, the closing surface **26** is framed by an annular surface section of the front end face of the sealing element **49**, which extends radially outwards to a radial outer circumferential surface of the sealing element **49**.

[0076] Expediently, the valve **1** contains a control electronics **52** designed to electrically control the drive apparatus **27**. The control electronics **52**, which is only indicated schematically, is expediently integrated into the valve housing **2**, wherein it can either be mounted on the valve housing **2** or positioned separately in this respect.

[0077] The control electronics **52** is configured to electrically power the drive apparatus **27** and is connected to the coil apparatus **34a** via at least one electrical control cable **53**. The control cable **53** is in particular flexible so that the permanent magnet apparatus **35a** can follow the lifting movement **28** unhindered. The control electronics **52** can generate the variable electrical powering already explained with varying current strength and varying current direction. Operating information for the control electronics **52** can be entered at an electrical input **54** of the control electronics **52**, in particular target position information for a desired lifting position of the valve member **13**.

[0078] Expediently, the valve **1** is equipped with a position detection apparatus **55**, which is also only schematically indicated and which contains, by way of example, a permanent magnet **55a** positioned on the movable valve member **13** and a Hall sensor **55b** positioned in a fixed position on the valve housing **2** and there, for example, on the closing element **11**. By interacting with the permanent magnet **55a**, the Hall sensor **55b** is able to detect lifting positions of the valve member **13** that can be adopted during the lifting movement **28**, wherein in particular a stepless detection of each lifting position including the closed position is possible. The position detection apparatus **55** is electrically connected to the control electronics **52** via at least one feedback cable **56** in order to supply it with the determined position data.

[0079] The control electronics **52** expediently comprises a closed-loop control functionality that enables position-closed-loop-controlled actuation of the drive apparatus **27** and accordingly allows very precise positioning of the valve member **13** in the desired target lifting positions.

[0080] The spring apparatus **32** acting on the valve member **13** is preferably configured such that, in the intermediate open position, the valve member **13** releases a flow cross-section for the fluid passing through the feed channel opening **7** that is at least essentially and preferably exactly half as large as a maximum flow cross-section released in the maximum open position of the valve member. In the non-actuated operating state, the valve **1** is half open in this case. However, it is understood that the spring apparatus **32** can be configured differently in accordance with the respective application in order to keep a specifically desired flow cross-section open in the

intermediate open position.

[0081] The desired configuration of the spring apparatus **32** can be achieved simply by selecting matching force-displacement characteristics and/or winding pitches for the closing spring **32a** and the opening spring **32b**. For example, the two springs **32a**, **32b** are configured differently from one another, in particular such that the closing spring **32a** has a steeper spring characteristic curve than the opening spring **32b**.

[0082] The force-related configuration of the spring apparatus **32** is exemplarily favored by the fact that the closing spring **32a** and the opening spring **32b** are separate, individual springs **32a**, **32b** of the spring apparatus **32**. In this way, each spring **32a**, **32b** can be manufactured and provided as a separate component independently of the other spring **32b**, **32a**. In principle, however, it is possible to provide a single one-piece spring element as spring apparatus **32**, which is connected to the valve member **13** at a point that is spaced apart from the two axial spring ends and can be designated as a tapping point, so that one of the length sections of the spring element axially adjoining the tapping point on both sides forms the closing spring **32a** and the other forms the opening spring **32b**.

[0083] Preferably, both springs **32a**, **32b** are configured as compression springs. This applies to the illustrated embodiment example just as much as an advantageous configuration of both springs **32a**, **32b** as helical springs. Accordingly, as an example, both the closing spring **32a** and the opening spring **32b** are configured as helical compression springs. This is associated with the advantageous possibility of making a coaxial arrangement of the two springs **32a**, **32b**, which is also realized in the embodiment example, wherein one of the two springs **32a**, **32b** coaxially encloses the other of the two springs **32b**, **32a** at least over a partial length. In other words, the two springs **32a**, **32b** overlap in the axial direction of the main axis **10**.

[0084] As an example, the Closing spring **32a** has a smaller diameter than the Opening spring **32b**, wherein the Opening spring **32b** encloses the Closing spring **32a** with radial clearance.

[0085] An anterior end section **58** of the valve member **13**, which comprises the closing surface **26**, preferably has a hat-shaped configuration. The anterior end section **58** includes the preferably circularly contoured ground wall **17**, a sleeve-shaped sidewall **59** extending from the edge of the ground wall **17** in the direction of the axial rear side **19** and thus axially away from the feed channel opening **7**, and an annular disk-shaped support wall **60** positioned at an axial distance from the ground wall **17** in a coaxial arrangement on the sidewall **59** and projecting radially outwards from the sidewall **59**.

[0086] The sleeve-shaped sidewall **59** and the support wall **60** are components of the sidewall **18** of the overall pot-shaped valve member **13**. The support wall **60** is adjoined towards the axial rear side **19** by a sleeve-shaped holding wall **62**, which also forms a section of the sidewall **18** and which bears the first drive component **34**.

[0087] Together with the sleeve-shaped sidewall **59**, the ground wall **17** delimits a longitudinal section of the valve member interior **22**. The closing spring **32a** is positioned in this valve member interior **22** and is therefore enclosed radially on the outside by the sleeve-shaped sidewall **59**. It bears on the one hand on the inner surface of the ground wall **17** of the valve member **13** axially opposite the closing surface **26** and on the other hand on a support body **23** fixed to the housing axially opposite the ground wall **17**. As an example, the support body **63** is advantageously formed by the permanent magnet apparatus **35a**.

[0088] The opening spring **32b** is located inside the valve chamber **3** outside the valve member interior **22**, wherein it encloses the sleeve-shaped sidewall **59**. It bears on the valve member **13** on the one hand and on the valve housing **2** on the other in the axial direction of the main axis **10**. Preferably, the bearing is provided on the surface of the support wall **60** facing the ground surface **16a** with respect to the valve member **13** and on the ground surface **16a** of the reception recess **16** with respect to the valve housing **2**.

[0089] During operation of the valve **1**, the valve member **13** takes the basic position shown in the

drawing and defining an intermediate open position **41** when the drive apparatus **27** is deactivated due to a lack of drive forces. Starting from this basic position, the valve member **13** can be moved in the direction of the closed position **42** by overcoming the opening spring force FO of the opening spring **32b** or in the direction of the maximum open position **43** by overcoming the closing spring force FS of the closing spring **32a**, depending on the direction of electrical powering of the coil apparatus **34a** controlled by the control electronics **52**.

[0090] If, starting from the closed position **42** or starting from the maximum open position **43**, a full lift is required to switch to the other extreme position, the control electronics **52** causes a reversal of the current direction in the coil apparatus **34a** when passing through the intermediate open position **41**.

[0091] Starting from the closed position **42**, the control electronics **52** initially cause a reduction in the drive force acting in the first direction of movement **28a**, wherein after overcoming the force zero point located in the intermediate open position **41**, the direction of current in the coil apparatus **34a** is reversed, so that a drive force acting in the second direction of movement **28b** is created. Starting from the maximum open position **43**, this operating sequence takes place in reverse.

[0092] The maximum open position of the valve member **13** is preferably defined by the fact that the valve member **13** comes to rest against a stop **70** fixed to the housing during its lifting movement **28** in the second direction of movement **28b**. The valve member **13** is pressed against the stop **70** by a correspondingly high drive force of the drive apparatus **27**. Expediently, the stop **70** is formed by the support body **23**. The closed position results from the contact of the closing surface **26** with the valve seat **8** during the lifting movement **28** taking place in the first direction of movement **28a**.

[0093] Preferably, the valve **1** is equipped with members which compensate the feed fluid pressure present via the feed channel **4** on the valve member **13** in order to keep the actuating forces for switching and holding the valve member **13** as low as possible. These compensation members include a compensation surface **37** formed on the valve member **13** and oriented axially opposite to the closing surface **26**, which in the embodiment example is formed on the rear side of the ground wall **17** and delimits a compensation chamber **24** formed by a partial space of the valve member interior **22**. The compensation chamber **24** communicates with the area in the valve housing **2** axially upstream of the closing surface **26** via a fluid channel referred to as compensation channel **36** due to its mode of operation.

[0094] As an example, the compensation chamber **24** is radially bounded by a sleeve-shaped chamber wall **65**, which is a component of the valve member **13** and projects away from the ground wall **17** in the direction of the axial rear side **19**. It is coaxially surrounded by the sleeve-shaped sidewall **59**. Between the sleeve-shaped chamber wall **65** and the sleeve-shaped sidewall **59** there is an annular space in which the closing spring **32a** extends. On the rear side facing axially away from the ground wall **17**, the compensation chamber **24** is closed by a closing body **66**, which is fixed to the housing and in particular is piston-shaped, and which rests against the inner circumferential surface of the sleeve-shaped chamber wall **65**, which is axially movable with respect to the closing body **66**, with dynamic sealing. As an example, the closing body **66** is positioned on the end face of the support projection **20**.

[0095] In particular, the compensation channel **36** passes through the ground wall **17** of the valve member **13**, wherein it communicates with the compensation chamber **24** at the rear and opens out to the closing surface **26** at its front via a compensation opening **38**. In this way, the fluid pressure prevailing in the area upstream of the closing surface **26** is picked up by the compensation channel **36**, which therefore also prevails at the same level in the compensation chamber **24**. Consequently, the same pressure is applied to the closing surface **26** and the compensation surface **37**, so that the pressure forces are compensated. It is particularly advantageous if the compensation surface **37** is at least essentially and in particular exactly the same size as the cross-sectional area of the feed channel opening **7** framed by the valve seat **8**.

[0096] It is expedient if measures are taken with valve **1** that enable simple compensation of any geometric component tolerances and/or spring tolerances during manufacture. These measures are a corresponding calibration option. Calibration can be carried out by moving the valve seat **8** relative to the valve housing **2** in the axial direction of the main axis **10** in order to change the axial distance to the ground surface **16a**.

[0097] In a calibration procedure that can be carried out during the manufacture of the valve **1**, the valve seat **8** is axially displaced until a desired flow rate is reached at a given current intensity of the electric current flowing through the coil apparatus **34a**, which is measured during the calibration procedure.

[0098] The movability of the valve seat **8**, which enables calibration, is exemplarily realized by the fact that the valve seat **8** is formed on the end face of a sleeve-shaped valve seat element **67** which is separate from the valve housing **2** and aligned coaxially to the main axis **10**. The valve seat element **67** is inserted into an inner end section **68** of the feed channel **6** opposite the outer connection opening **4a** with a variable axial position in relation to the axial direction of the main axis **10** and is fixed to the housing. During calibration, the valve seat element **67** can be moved relative to the valve housing **2** in the axial direction of the main axis **10** as part of a calibration movement **69** indicated by a double arrow and, in particular, can be moved linearly. In the operational, completed state of the valve **1**, the position of use of the valve seat element **67** set in relation to the valve housing **2** is blocked so that no undesired changes in position can occur.

[0099] As an example, the valve seat element **67** is pressed into the inner end section **68** of the feed channel **4** with a variable press-fit depth and fixed in a force-fit manner. Alternatively or additionally, an adhesive connection can be provided for fixing. It is also possible, for example, to configure the valve seat element **67** as a screw element with an external thread that is screwed into an internal thread formed in the inner end section **68**. In this case, the threaded connection is permanently blocked in a suitable manner when the desired position of use is reached during calibration.

[0100] In an advantageous calibration process, the coil apparatus **34a** is electrically powered by means of the control electronics **52** or an external power source with a predetermined current intensity and a predetermined current direction, so that the valve member **13** takes a certain lifting position based on the sum of the actuating forces acting on it, i.e. the driving force generated by the applied current as well as the closing force FS and the opening force FO of the two springs **32a**, **32b**, whereupon the valve seat element **67** is moved in the axial direction of the main axis **10** relative to the valve housing **2** by the calibration movement **69** until a desired flow rate is achieved. Any flow sensor is used to measure the flow rate during calibration.

[0101] To summarize again briefly, in the illustrated embodiment example, the valve member **13** is constantly acted upon by the closing spring **32a** with a spring force acting in the first direction of movement **28a**, referred to as closing force FS, and by the opening spring **32b** with a spring force acting in the second direction of movement **28b**, referred to as opening force FO. The intermediate open position **41** of the valve member **13** is located where the closing force FS and the opening force FO are equal, taking into account the spring characteristics of the two springs **32a**, **32b**. This means that the intermediate open position **41**, which acts as the basic position, can be preset as desired by a correspondingly coordinated configuration of the two springs **32a**, **32b**. This can be done in particular as part of a calibration during the manufacture of the valve **1**.

[0102] The valve **1** can optionally be equipped with adjustment members that allow the spring preload of the closing spring **32a** and/or the opening spring **32b** to be subsequently changed in order to be able to vary and adjust the basic position as required even after the valve **1** has been completed.

Claims

- 1.** A valve for controlling the flow of a fluid, comprising a valve housing which delimits a valve chamber into which a feed channel for feeding in fluid and a working channel enabling a fluid outlet open, wherein a feed channel opening of the feed channel is framed by a valve seat facing the valve chamber, opposite which valve seat in the valve chamber there is a closing surface positioned on an axial front side of a valve member of the valve, wherein the valve member is movable in the axial direction of a main axis of the valve by a lifting movement, which is caused by a driving force of a drive apparatus of the valve, and which lifting movement is oriented in the axial direction of a main axis, in a closed position, in which the valve bears with its closing surface against the valve seat and thereby separates the feed channel from the valve chamber in a fluid-tight manner, or in at least one open position raised from the valve seat and thereby releasing a fluid connection between the feed channel and the valve chamber in permanent fluid connection with the working channel and wherein the valve member is constantly biased in the direction of the closed position by a closing spring of a spring apparatus of the valve, wherein in addition to the closing spring, the spring apparatus has an opening spring which constantly biases the valve member in the direction of the at least one open position, wherein the closing spring and the opening spring, which acts in the opposite direction in this respect, are mutually coordinated with respect to their spring forces in such a way that the valve member takes up a basic position without driving forces of the drive apparatus, which basic position is an intermediate open position lying between the closed position and a maximum open position.
- 2.** The valve according to claim 1, wherein the drive apparatus is of an electrically actuatable type.
- 3.** The valve according to claim 1, wherein the drive apparatus is configured as an electrodynamic drive apparatus.
- 4.** The valve according to claim 1, wherein the drive apparatus comprises a first drive component formed by an electrical coil apparatus and a second drive component interacting with the electrically powered electrical coil apparatus to generate a driving force acting on the valve member in the axial direction of the main axis, wherein one of the two drive components is positioned on the valve member and the other of the two drive components is positioned on the valve housing.
- 5.** The valve according to claim 2, wherein the valve comprises a control electronics configured to control the drive apparatus.
- 6.** The valve according to claim 5, wherein the control electronics is configured to electrically power the drive apparatus, wherein both an opening current direction acting on the valve member and a closing current direction acting on the valve member can be generated by the control electronics in the drive apparatus.
- 7.** The valve according to claim 1, wherein the valve comprises a position detection apparatus for detecting lifting positions of the valve member that can be reached during the lifting movement.
- 8.** The valve according to claim 1, wherein, in the intermediate open position, the valve member releases a flow cross-section for the fluid passing through the feed channel opening which is at least essentially half as large as a maximum flow cross-section released in the maximum open position of the valve member.
- 9.** The valve according to claim 1, wherein the closing spring and the opening spring are each a compression spring.
- 10.** The valve according to claim 1, wherein the closing spring and the opening spring are each a coil spring.
- 11.** The valve according to claim 1, wherein the closing spring and the opening spring have force-displacement characteristics and/or winding pitches that are matched to one another.
- 12.** The valve according to claim 1, wherein the closing spring and the opening spring are configured as separate, individual springs of the spring apparatus.
- 13.** The valve according to claim 12, wherein of the closing spring and the opening spring, one of

the two springs coaxially encloses the other of the two springs. **14.** The valve according to claim 12, wherein the valve member comprises a hat-shaped anterior end section with a front ground wall comprising the closing surface, a sleeve-shaped sidewall extending axially away from the feed channel opening starting from the front of the ground wall and an annular disc-shaped support wall projecting radially outwards from the sleeve-shaped sidewall at an axial distance from the front ground wall, wherein the closing spring is enclosed by the sleeve-shaped sidewall and is supported on the one hand on the ground wall of the valve member and on the other hand on an axially opposite housing-fixed support body and wherein the opening spring surrounds the sleeve-shaped sidewall and is supported within the valve chamber on the one hand on the valve housing and on the other hand on the support wall of the valve member.

15. The valve according to claim 1, wherein the valve member comprises a valve member base body, on the front side of which facing the feed channel opening a separate sealing element of the valve member comprising the closing surface is positioned.

16. The valve according to claim 1, wherein the closing surface is formed on a sealing element of the valve member consisting of a rubber-elastic material.

17. The valve according to claim 1, wherein the valve is configured as a 2/2-way valve.

18. The valve according to claim 1, wherein the valve seat framing the feed channel opening is formed on a sleeve-shaped valve seat element which is separate with respect to the valve housing, is aligned coaxially with the main axis, is inserted into an inner end section of the feed channel with a variable axial position with respect to the main axis and is fixed to the valve housing in a manner fixed to the housing.

19. The valve according to claim 1, wherein the valve member comprises a compensation surface which is oriented axially opposite to the closing surface and which compensation surface delimits a compensation chamber formed in the valve housing, which compensation chamber constantly communicates with the region axially upstream of the closing surface via at least one compensation channel passing through the valve member and opening out with at least one compensation opening at the closing surface.

20. The valve according to claim 7, wherein a position-controlled actuation of the drive apparatus can preferably be carried out on the basis of position data obtained by means of the position detection apparatus.
