

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385586
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Jianhua; Ye et al.

Compression teeth ring connection pipe fitting

Abstract

The present disclosure provides a compression teeth ring connection pipe fitting, which includes a pipe fitting body and a sealing component; the pipe fitting body includes a middle pipe section, a first flared section, and a second flared section; a diameter of the first flared section is greater than a diameter of the middle pipe section, and a first limit platform is formed at a connection position between the two; a diameter of the second flared section is greater than that of the first flared section, and a second limit platform is formed at a connection position between the two; the sealing component includes a sealing ring, a high temperature sealing ring, and a teeth ring that are coaxial and sequentially arranged; inner rings of the sealing ring, the high temperature sealing ring, and the teeth ring form a space for nesting a steel pipe body.

Inventors: Jianhua; Ye (Tianjin, CN), Qingnian; Zhou (Beijing, CN)

Applicant: Guolin (Tianjin) Technology Co., Ltd. (Tianjin, CN); Shanghai Zep Tech Co., Ltd (Shanghai, CN)

Family ID: 89998365

Assignee: Guolin (Tianjin) Technology Co., Ltd. (Tianjin, CN); Shanghai Zep Tech Co., Ltd (Shanghai, CN)

Appl. No.: 18/500230

Filed: November 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240068611 A1	Feb. 29, 2024

Foreign Application Priority Data

CN	202011124020.1	Oct. 20, 2020
----	----------------	---------------

Related U.S. Application Data

continuation-in-part parent-doc US 17470715 20210909 US 11873924 child-doc US 18500230

Publication Classification

Int. Cl.: F16L37/092 (20060101)

U.S. Cl.:

CPC F16L37/0925 (20130101);

Field of Classification Search

CPC: F16L (37/091); F16L (37/095); F16L (37/098); F16L (37/0925); F16L (25/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010/0314863	12/2009	Ohara	285/31	F16L 37/091

Primary Examiner: Dunwoody; Aaron M

Attorney, Agent or Firm: JEEN IP LAW, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation-in-part of U.S. patent application Ser. No. 17/470,715, filed on Sep. 9, 2021, which claims priority to Chinese Patent Application No. 202011124020.1 filed on Oct. 20, 2020. The afore-mentioned patent applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates to the technologies field clamp pipe fittings, and in particular, to a compression teeth ring connection pipe fitting.

BACKGROUND

(2) A pipeline is a device that is connected by pipes, pipe connectors, and valves to transport fluids. Generally, after being pressurized by a blower, compressor, pump, and boiler, the fluid flows from the high-pressure part of the pipeline to the low-pressure part thereof, and can also be transported using its own pressure or gravity.

(3) In the existing technology, traditional fluid transmission pipelines are generally used for thick-walled or thin-walled pipe fittings, which are connected by pipe fittings. Thread connections are usually used between pipe fittings, which results in poor sealing performance, low installation efficiency, and inability to meet leakage prevention standards in high temperature environments.

SUMMARY

(4) The purpose of the present disclosure is to provide a compression teeth ring connection pipe fitting to alleviate a problem of poor sealing between the pipe fitting and the pipeline in the prior

art, and an inability to meet leakage prevention standards in high temperature environments.

(5) The present disclosure provides a compression teeth ring connection pipe fitting connecting between two steel pipe bodies. The compression teeth ring connection pipe fitting includes a pipe fitting body and a sealing component; the pipe fitting body includes a middle pipe section, a first flared section, and a second flared section, where the first flared section and the second flared section are extended along an axis of the pipe fitting body at both ends thereof; a diameter of the first flared section is greater than a diameter of the middle pipe section, and a first limit platform is formed at a connection position between the two; the first limit platform limits an installed steel pipe body in an axis direction; a diameter of the second flared section is greater than the diameter of the first flared section, and a second limit platform is formed at a connection position between the two; the sealing component includes a sealing ring, a high temperature sealing ring, and a teeth ring that are coaxial and sequentially arranged; inner rings of the sealing ring, the high temperature sealing ring, and the teeth ring form a space for nesting the steel pipe body; the second limit platform limits the sealing ring in an axis direction.

(6) In an embodiment of the present disclosure, the second flared section is inwardly formed with a first annular boss in a radial direction; the second flared section has a maximum wall thickness at the first annular boss, and a sealing ring limit groove is formed between the first annular boss and the first limit platform to accommodate the sealing ring; an inner diameter of the first annular boss is larger than an outer diameter of the high temperature sealing ring.

(7) In an embodiment of the present disclosure, a second annular boss is formed inwardly at an edge of a socket of the second flared section in the radial direction; a teeth ring limit groove is formed between the first annular boss and the second annular boss to accommodate the teeth ring.

(8) In an embodiment of the present disclosure, the second flared section has a same wall-thickness at each position of the second flared section.

(9) In an embodiment of the present disclosure, at least one side of the high temperature sealing ring is recessed inwardly to form one groove.

(10) In an embodiment of the present disclosure, at least one side of the high temperature sealing ring is recessed inwardly to form multiple grooves, the multiple grooves are spaced radially along the high temperature sealing ring in a radial direction.

(11) In an embodiment of the present disclosure, an opening of the groove gradually increases from an inside to an outside.

(12) In an embodiment of the present disclosure, a cross-sectional shape of the groove is trapezoidal or triangular.

(13) In an embodiment of the present disclosure, both end surfaces of the high temperature sealing ring are planar surface and the high temperature sealing ring has a same wall-thickness at each point.

(14) In an embodiment of the present disclosure, the high temperature sealing ring is made of stainless steel, copper, or graphite.

(15) In an embodiment of the present disclosure, the teeth ring includes a teeth ring body and an inner ring protruding from the teeth ring body, and the inner ring is a toothed shaped structure; the teeth ring body is in an open ring structure; the toothed structure is configured to insert into the steel pipe body when being subjected to a mutual compression with the steel pipe body.

(16) In an embodiment of the present disclosure, the teeth ring body is in a “C” shaped structure and is made of a radially shrinkable metal material.

(17) In an embodiment of the present disclosure, the toothed shape structure includes multiple teeth spaced along an extension direction of the teeth ring body, and the teeth are extended from the inner ring of the teeth ring body towards its axis direction.

(18) In an embodiment of the present disclosure, the toothed shaped structure is arranged in two rows, and some teeth of the two rows of toothed shaped structure are faced with each other.

(19) In an embodiment of the present disclosure the toothed shaped structure is arranged in two

rows, and some teeth of the two rows of toothed shaped structure are misaligned with each other.

(20) In an embodiment of the present disclosure, the toothed shaped structure is arranged in a row, and multiple teeth of the row of toothed shaped structure are arranged at equal intervals.

(21) In an embodiment of the present disclosure, multiple teeth of the toothed shaped structure are arranged on an edge of at least one side of the teeth ring body.

(22) The compression teeth ring connection pipe fitting provided by the present disclosure has at least the following beneficial effects: during a specific connection process, the steel pipe body is inserted into the pipe fitting body, and an insertion end of the steel pipe body abuts against the first limit platform. The first limit platform limits the steel pipe body in an axis direction to prevent the steel pipe body from shifting along the axial direction; at the same time, the steel pipe body can be sleeved in a space formed by the sealing ring, the high temperature sealing ring, and the teeth ring. The second limit platform can limit the sealing ring in an axis direction, which can prevent the sealing ring from shifting along the axial direction; after the aforementioned installation is completed, a position of the second flared section can be tightened with a help of a crimping tool, the second flared section is forced to contract inwardly, so that inner rings of the sealing ring, the high temperature sealing ring, and the teeth ring are tightly attached to an outer circumference of the steel pipe body. By setting the sealing ring, a connection sealing between the steel pipe body and the pipe fitting body can be improved. Due to a melting of the sealing ring in a high temperature environment and losing the sealing effect, the high temperature sealing ring is provided at an outer side of the sealing ring. The high temperature sealing ring can replace the sealing ring and play a sealing role after the sealing ring loses its sealing effect. In a general design, the high temperature sealing ring meets a certain leakage standard, which can slowly release high temperature and high pressure inside the pipeline, thus it has a high-pressure resistance, thereby avoiding explosion accidents in the pipeline. And, the setting of the teeth ring can ensure a reliable and stable connection between the steel pipe body and the pipe fitting body, which plays a certain tensile and torsional role. It can be seen that the compression teeth ring connection pipe fitting not only has good connection sealing performance, but also can be suitable for high temperature environments. In high temperature environments, it also has good connection sealing performance, playing a role in preventing leakage. In addition, during a specific installation process, the steel pipe body is inserted into the pipe fitting body, and the insertion end of the steel pipe body abuts against the first limit platform. The first limit platform can limit the steel pipe body in the axial direction. At the same time, the steel pipe body is sleeved in the space formed by the sealing ring, the high temperature sealing ring, and the teeth ring, which renders an entire installation process relatively simple and easy to operate.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) In order to provide a clearer explanation of the specific embodiments of the present disclosure or the technical solutions in the prior art, a brief introduction will be given to the drawings required for the specific embodiments or the description of the prior art. It is obvious that the drawings in the following description are some embodiments of the present disclosure. For ordinary technical personnel in the art, other drawings can be obtained based on these drawings without any creative work.

(2) FIG. 1 is a schematic diagram of a split structure of a compression teeth ring connection pipe fitting and two steel pipe bodies provided in an embodiment of the present disclosure.

(3) FIG. 2 is a cross-sectional view of a pipe fitting body in Embodiment 1 of the present disclosure.

(4) FIG. 3 is a schematic diagram of a connection structure of the compression teeth ring

connection pipe fitting in Embodiment 1 of the present disclosure.

(5) FIG. 4 is a schematic diagram of a disassembly structure of the compression teeth ring connection pipe fitting in Embodiment 1 of the present disclosure.

(6) FIG. 5 shows a cross-sectional view of the pipe fitting body shown in FIG. 2 with a sealing ring, a high temperature sealing ring, and a teeth ring installed at both ends of the pipe fitting body.

(7) FIG. 6 is a cross-sectional view of a steel pipe body inserted at one end of the pipe fitting body on the basis of FIG. 5 before crimping.

(8) FIG. 7 is a cross-sectional view of the steel pipe body inserted at one end of the pipe fitting body on the basis of FIG. 5 after crimping.

(9) FIG. 8 is a partially enlarged schematic diagram of A in FIG. 7.

(10) FIG. 9 is a schematic diagram of a processing process of the pipe fitting body in Embodiment 1 of the present disclosure.

(11) FIG. 10 is a first structural schematic diagram of the high temperature sealing ring.

(12) FIG. 11 is a second structural schematic diagram of the high temperature sealing ring.

(13) FIG. 12 is a third structural schematic diagram of the high temperature sealing ring.

(14) FIG. 13 is a fourth structural schematic diagram of the high temperature sealing ring.

(15) FIG. 14 is a fifth structural schematic diagram of the high temperature sealing ring.

(16) FIG. 15 is a first structural schematic diagram of the teeth ring.

(17) FIG. 16 is a second structural schematic diagram of the teeth ring.

(18) FIG. 17 is a third structural schematic diagram of the teeth ring.

(19) FIG. 18 is a fourth structural schematic diagram of the teeth ring.

(20) FIG. 19 is a fifth structural schematic diagram of the teeth ring.

(21) FIG. 20 is a sixth structural schematic diagram of the teeth ring.

(22) FIG. 21 is a seventh structural schematic diagram of the teeth ring.

(23) FIG. 22 is an eighth structural schematic diagram of the teeth ring.

(24) FIG. 23 is a ninth structural schematic diagram of the teeth ring.

(25) FIG. 24 is a structural schematic diagram of the pipe fitting body in Embodiment 2 of the present disclosure.

(26) FIG. 25 is a cross-sectional view of the pipe fitting body in Embodiment 2 of the present disclosure.

(27) FIG. 26 shows a cross-sectional view of the pipe fitting body shown in FIG. 25 with the sealing ring, the high temperature sealing ring, and the teeth ring installed at both ends thereof.

(28) FIG. 27 is a schematic diagram of a processing and an installation of the compression teeth ring connection pipe fitting in Embodiment 2 of the present disclosure.

(29) Numeral reference: **10**—Steel pipe body; **100**—Pipe fitting body; **110**—Middle pipe section; **120**—First flared section; **130**—Second flared section; **140**—First limit platform; **150**—Second limit platform; **160**—Sealing ring limit groove; **170**—Teeth ring limit groove; **180**—Shrinkage section; **131**—First annular boss; **132**—Second annular boss; **200**—Sealing ring; **300**—High temperature sealing ring; **400**—Teeth ring; **410**—Teeth ring body; **420**—Teeth.

DESCRIPTION OF EMBODIMENTS

(30) In order to render the purpose, technical solution, and advantages of the embodiments of the present disclosure clearer, the following will provide a clear and complete description of the technical solution in the embodiments of the present disclosure in combination with the drawings. Obviously, the described embodiments are a part of the embodiments of the present disclosure, not all of them. The devices of the embodiments of the present disclosure typically described and shown in the drawings can be arranged and designed in various different configurations.

(31) Therefore, the detailed description of the embodiments of the present disclosure provided in the drawings is not intended to limit the scope of the present disclosure, but only to represent some embodiments of the present disclosure. Based on the embodiments in the present disclosure, all other embodiments obtained by ordinary technicians in the art without creative work fall within the

protection scope of the present disclosure.

(32) It should be noted that similar reference and letters represent similar terms in the following drawings, so once a term is defined in one drawing, further definition and explanation are not required in subsequent drawings.

(33) In the description of the present disclosure, it should be noted that the terms “center”, “up”, “bottom”, “left”, “right”, “vertical”, “horizontal”, “inside”, “outside”, etc. indicate an orientation or position relationship based on the orientation or position relationship shown in the drawings, or the orientation or position relationship that is commonly placed when the product of the disclosure is used, solely for a convenience of describing the present disclosure and simplifying the description, rather than indicating or implying that the device or component referred to must have a specific orientation, be constructed and operated in a specific orientation, therefore it cannot be understood as a limitation of the present disclosure. In addition, terms “first”, “second”, “third”, etc. are only used to distinguish descriptions and cannot be understood as indicating or implying relative importance.

(34) In addition, terms such as “horizontal” and “vertical” do not mean that the component is required to be absolutely horizontal or suspended, but can be slightly tilted. If “horizontal” only refers to its direction being more horizontal compared to “vertical”, it does not mean that the structure must be completely horizontal, but can be slightly tilted.

(35) In the description of the present disclosure, it should also be noted that unless otherwise specified defined and limited, terms “setting”, “installation”, “connection to”, and “connection with” should be broadly understood, for example, they can be a fixed connection, a detachable connection, or an integrated connection; it can be a mechanical connection or an electrical connection; it can be a directly connection, or an indirect connection through an intermediate medium, or it can be an internal connection between two components. For ordinary technical personnel in this field, specific meanings of the above terms in the present disclosure can be understood in specific circumstances.

(36) The following will provide a detailed explanation of some embodiments of the present disclosure in combination with the drawings. Without conflict, the following embodiments and the features in the embodiments can be combined with each other.

Embodiment 1

(37) Referring to FIGS. 1 to 6, this embodiment provides a compression teeth ring connection pipe fitting connecting between two steel pipe bodies **10**. The compression teeth ring connection pipe fitting includes a pipe body **100** and a sealing component. The pipe fitting body **100** includes a middle pipe section **110**, a first flared section **120** and a second flared section **130**, the first flared section **120** and the second flared section **130** are extended along an axis of the pipe fitting body **100** at both ends thereof. A diameter of the first flared section **120** is greater than a diameter of the middle pipe section **110**, and a first limit platform **140** is formed at a connection position between the two. The first limit platform **140** is configured to limit an installed steel pipe body **10** in an axial direction. A diameter of the second flared section **130** is greater than the diameter of the first flared section **120**, and a second limit platform **150** is formed at a connection position between the two. The sealing component includes a sealing ring **200**, a high temperature sealing ring **300**, and a teeth ring **400** that are coaxial and sequentially arranged; inner rings of the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400** form a space for nesting the steel pipe body **10**. The second limit platform **150** is configured to limit the sealing ring **200** in an axial direction.

(38) During a specific connection, the steel pipe body **10** is inserted into the pipe fitting body **100**, and an insertion end of the steel pipe body **10** abuts against the first limit platform **140**. The first limit platform **140** limits the steel pipe body **10** in an axial direction to prevent the steel pipe body **10** from shifting along the axial direction. At the same time, the steel pipe body **10** can be nested in the space formed by the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400**. The second limit platform **150** can limit the sealing ring **200** in an axial direction, which can

prevent the sealing ring **200** from shifting along the axial direction. After the aforementioned installation is completed, the second flared section **130** can be tightened with a help of a crimping tool, the second flared section **130** is forced to contract inwardly, so that inner rings of the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400** are tightly adhered to an outer circumference of the steel pipe body **10**. By setting the sealing ring **200**, a connection sealing between the steel pipe body **10** and the pipe fitting body **100** can be improved; due to a melting of the sealing ring **200** in a high temperature environment and losing the sealing effect, the high temperature sealing ring **300** is provided on an outer side of the sealing ring **200**. The high temperature sealing ring **300** can replace the sealing ring **200** in its sealing function after it loses its sealing effect. In a general design, the high temperature sealing ring **300** meets a certain leakage standard, and a small amount of gas can leak out from this, allowing the high temperature and high pressure inside the pipeline to be released, thereby playing a role in pressure resistance, and avoiding pipeline explosion accidents; at the same time, the setting of the teeth ring **400** can ensure a reliable and stable connection between the steel pipe body **10** and the pipe fitting body **100**, and thereby playing a certain tensile and torsional role.

(39) It can be seen that the compression teeth ring connection pipe fitting not only has good connection sealing performance, but also can be suitable for high temperature environments. In high temperature environments, it also has good connection sealing performance and plays a role in preventing leakage. In addition, during a specific installation process, the steel pipe body **10** is inserted into the pipe fitting body **100**, and the insertion end of the steel pipe body **10** abuts against to the first limit platform **140**. The first limit platform **140** can limit the steel pipe body **10** in the axial direction. At the same time, the steel pipe body **10** is sleeved in the space formed by the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400**, which renders an entire installation process relatively simple and easy to operate.

(40) In one embodiment of the present application, in combination with FIGS. 2 and 5, the second flared section **130** is inwardly formed with a first annular boss **131** in a radial direction; the second flared section **130** has a maximum wall thickness at the first annular boss **131**, and a sealing ring limit groove **160** is formed between the first annular boss **131** and the first limit platform **140** to accommodate the sealing ring **200**; an inner diameter of the first annular boss **131** is slightly larger than an outer diameter of the high temperature sealing ring **300**.

(41) During an installation process, it is necessary to first install the sealing ring **200** at the sealing ring limit groove **160** of the sealing ring, then install the high temperature sealing ring **300** at the first ring boss **131**, and finally install the teeth ring **400**. By setting the sealing ring limit groove **160**, it is convenient for the sealing ring **200** to be installed in place in a timely manner, and at the same time, it can prevent its position deviation after the installation is in place; by setting the first annular boss **131**, it is convenient for the high temperature sealing ring **300** to be installed in place in a timely manner; the aforementioned structure is suitable for a thick-walled pipe fitting, and it also has good pressure and impact resistance performances when adopting a design of thick-walled pipe fitting.

(42) Furthermore, further combining FIGS. 2 and 5, a second annular boss **132** is formed inwardly at an edge of a socket of the second flared section **130** in the radial direction; a teeth ring limit groove **170** is formed between the first annular boss **131** and the second annular boss **132** to accommodate the teeth ring **400**. This arrangement facilitates a timely installation of the teeth ring **400** and prevents its position deviation after installation.

(43) During the specific installation process, the sealing ring **200**, high temperature sealing ring **300**, and teeth ring **400** are installed in sequence as shown in FIG. 5, and then the steel pipe body **10** is inserted into the pipe fitting body **100** as shown in FIG. 6, and the insertion end of the pipe fitting body **100** abuts against the first limit platform **140**.

(44) Based on FIGS. 7 and 8, after all of the above are installed in place, the second flared section **130** is pressed inwardly using a crimping tool, which causes the second flared section **130** to

collapse, thereby squeezing the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400**, which renders them tightly adhere between the steel pipe body **10** and the second flared section **130** to ensure sealing and stability. The compression teeth ring connection pipe fitting in this embodiment uses a crimping tool to crimp and deform the pipe fitting body **100**, thereby instantly completing the connection between the pipe fitting body **100** and the steel pipe body **10**. The crimping tool crimps the second flared section **130** of the pipe fitting, and the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400** are installed on an inner side of the second flared section **130**. All three are compressed at the same time, the sealing ring **200** and high temperature sealing ring **300** inside the second flared section **130** are forced to tightly adhere to the steel pipe body **10**; and thus, it has a sealing and sealing effect, and the teeth ring **400** shrinks and firmly fastens the steel pipe body **10**, and thereby providing good connection, tensile and torsional resistance.

(45) The thick-walled pipe fittings are made of carbon steel as the base material, which has a lower cost compared to stainless steel or copper pipe fitting. A surface of the pipe fitting can be processed with zinc plating and EP (Epoxy cover) anti-corrosion, and its service life is longer compared to ordinary galvanized materials.

(46) Referring to FIG. **9**, a processing method of the pipe fitting body **100** includes the following steps: S1, flaring one end of the pipe fitting body **100** using a flaring device to form a first flared section **120**, and then flaring again using the flaring device on the first flared section **120** to form a second flared section **130**; S2, processing a first annular boss and a second annular boss **132** in the second flared section **130**.

(47) In this embodiment, the high temperature sealing ring **300** can adopt the following structural forms. In a practical application, different structural forms or sizes of high temperature sealing ring **300** can be selected according to needs.

(48) Referring to FIGS. **10** and **11**, one side of the high temperature sealing ring **300** is recessed inwardly to form a groove.

(49) Furthermore, an opening of the groove gradually increases from an inside to an outside.

(50) For example, a cross-sectional shape of the groove is trapezoidal or triangular, and of course, it can also be other shapes, which will not be listed here.

(51) In other embodiments, referring to FIG. **12**, both ends of the high temperature sealing ring **300** are recessed inwardly to form a groove, and a cross-sectional shape of the grooves is trapezoidal.

(52) Referring to FIG. **13**, both sides of the high temperature sealing ring **300** are recessed inwardly to form two grooves, which are spaced radially along the high temperature sealing ring **300**; for example, the cross-sectional shape of the groove is triangular.

(53) Referring to FIG. **14**, both end surfaces of the high temperature sealing ring **300** are planer surface and the high temperature sealing ring **300** has a same wall-thickness at each point.

(54) In this embodiment, a material of the high temperature sealing ring **300** is not limited to stainless steel, copper, or graphite, but it can also be other high temperature resistant materials, which will not be listed here.

(55) On the basis of the above embodiments, referring to FIGS. **15** to **23**, the teeth ring **400** includes a teeth ring body **410** and an inner ring protruding from the teeth ring body **410**; and the inner ring is a toothed shaped structure. The teeth ring body **410** is in an open ring structure; the toothed structure is configured to insert into the steel pipe body **10** when it is compressed with the steel pipe body **10** so as to form a tight and reliable connection structure between the two, thereby effectively preventing the steel pipe body **10** from detaching from the pipe fitting body **100**.

(56) It should be noted that as long as the toothed shaped structure can be inserted into the steel pipe body **10** during a mutual compression with the steel pipe body **10**, all structural forms are within the protection scope of the present disclosure.

(57) In a specific implementation, the teeth ring body **410** is in a “C” shaped structure and is made of a radially shrinkable metal material, so that when the teeth ring body **410** is compressed by a

crimping tool on the second flared section **130** of the pipe fitting body **100**, it can shrink inwardly and hold the steel pipe body **10**.

(58) In this embodiment, the teeth ring **400** can adopt the following structural form.

(59) The toothed structure includes multiple teeth **420** spaced along an extension direction of the teeth ring body **410**. The teeth **420** are extended from the inner ring of the teeth ring body **410** towards its own axis direction. Of course, the form of teeth **420** extending slightly from the inner ring of the teeth ring body **410** to its own axis direction is also within the protection scope of the present disclosure.

(60) Referring to FIG. **15**, the toothed structure is two rows, some teeth **420** are faced with each other and some teeth **420** are misaligned with each other.

(61) Referring to FIGS. **16** and **17**, the toothed structure is arranged in two rows, some teeth **420** of one row of the toothed structure are misaligned relative to the teeth **420** of the other row of the toothed structure. Where, the structure and setting position of the teeth **420** in FIG. **16** and FIG. **17** are slightly different.

(62) Referring to FIGS. **18** and **19**, the toothed structure is set in two rows, where the teeth **420** of one row of the toothed structure are offset by a certain distance from the teeth **420** of the other row of the toothed structure.

(63) Referring to FIG. **20**, the toothed structure is arranged in a row along the extension direction of the teeth ring body **410**.

(64) Referring to FIGS. **21** and **22**, the toothed structure is arranged at an edge of both sides of the teeth ring body **410**.

(65) Referring to FIG. **23**, the toothed structure is located at the edge of one side of the teeth ring body **410**.

(66) When the second flared section **130** is recessed inwardly through a crimping tool, it can cause the second flared section **130** to collapse, thereby squeezing the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400**. While squeezing the teeth ring **400**, the teeth ring **420** can be inserted into the steel pipe body **10**, which forms a tighter and more reliable connection between the two, and plays a good tensile and torsional role.

Embodiment 2

(67) Referring to FIGS. **24** and **25**, this embodiment also provides a compression teeth ring connection pipe fitting. The difference from Embodiment 1 is that the first annular boss **131** is not provided, and an edge of the socket of the second flared section **130** gradually retracts inwardly to form a smooth transition of a shrinkage section **180**. A diameter of the shrinkage section **180** is smaller than an outer diameter of the teeth ring **400**. This structure is suitable for a thin-walled pipe fitting having a wall thickness between 1.5 mm and 3 mm compared to a thick-walled pipe fitting. Its connection performance is consistent with that of the thick-walled pipe fitting (connection performance is not limited to tensile, torsional, seismic, bending, etc.), and which reduced material costs. Due to the wall thickness ranging from 1.5 mm to 3 mm, it can be hydraulically formed in one go without the need for mechanical processing, and reduces process costs.

(68) Referring to FIG. **26**, the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400** are sequentially connected between the second limit platform **150** and the shrinkage section **180**.

(69) Referring to FIG. **27**, a processing and assembly method for the compression teeth ring connection pipe fitting includes the following steps: flaring the two ends of the pipe fitting body **100** using a flared device to form the first flared section **120**, and then flaring again using the flared device on the first flared section **120** to form the second flared section **130**; connecting the sealing ring **200**, the high temperature sealing ring **300**, and the teeth ring **400** in sequence between the second limit platform **150** corresponding to the second flared section **130** and the shrinking section **180**.

(70) Finally, it should be noted that the above embodiments are only used to illustrate the technical

solution of the present disclosure and not to limit it; although the present disclosure has been described in detail with reference to the aforementioned embodiments, ordinary technical personnel in this field should understand that they can still modify the technical solutions recorded in the aforementioned embodiments, or equivalently replace some or all of the technical features; and these modifications or substitutions do not make the essence of the corresponding technical solutions deviate from the scope of the various embodiments of the present disclosure.

Claims

1. A compression teeth ring connection pipe fitting connecting between two steel pipe bodies, wherein the compression teeth ring connection pipe fitting comprises a pipe fitting body and a sealing component; the pipe fitting body comprises a middle pipe section, a first flared section, and a second flared section; the first flared section and the second flared section are extended along an axis of the pipe fitting body at two ends thereof; a diameter of the first flared section is greater than a diameter of the middle pipe section, and a first limit platform is formed at a connection position between the middle pipe section and the flared section; the first limit platform limits an installed steel pipe body in an axis direction; a diameter of the second flared section is greater than the diameter of the first flared section, and a second limit platform is formed at a connection position between the first flared section and the second flared section; the sealing component comprises a sealing ring, a high temperature sealing ring, and a teeth ring; an inner ring of the sealing ring, an inner ring of the high temperature sealing ring, and an inner ring of the teeth ring form a space for nesting the steel pipe body; the second limit platform limits the sealing ring in an axis direction; wherein at least one side of the high temperature sealing ring is recessed inwardly to form one groove.
2. The compression teeth ring connection pipe fitting according to claim 1, wherein the second flared section is inwardly formed and provided with a first annular boss in a radial direction; the second flared section has a maximum wall thickness at the first annular boss, and a sealing ring limit groove is formed between the first annular boss and the second limit platform to accommodate the sealing ring; an inner diameter of the first annular boss is larger than an outer diameter of the high temperature sealing ring.
3. The compression teeth ring connection pipe fitting according to claim 2, wherein a second annular boss is formed inwardly at an edge of a socket of the second flared section in the radial direction; a teeth ring limit groove is formed between the first annular boss and the second annular boss to accommodate the teeth ring.
4. The compression teeth ring connection pipe fitting according to claim 1, wherein the second flared section has a same wall-thickness at each position of the second flared section.
5. The compression teeth ring connection pipe fitting according to claim 1, wherein at least one side of the high temperature sealing ring is recessed inwardly to form multiple grooves, the multiple grooves are spaced along the high temperature sealing ring in a radial direction.
6. The compression teeth ring connection pipe fitting according to claim 1, wherein an opening of the groove gradually increases from an inside to an outside.
7. The compression teeth ring connection pipe fitting according to claim 5, wherein an opening of each groove gradually increases from an inside to an outside.
8. The compression teeth ring connection pipe fitting according to claim 6, wherein a cross-sectional shape of the groove is trapezoidal or triangular.
9. The compression teeth ring connection pipe fitting according to claim 1, wherein two end surfaces of the high temperature sealing ring are planar surface and the high temperature sealing ring has a same wall-thickness at each point.
10. The compression teeth ring connection pipe fitting according to claim 1, wherein the high temperature sealing ring is made of stainless steel, copper, or graphite.

11. The compression teeth ring connection pipe fitting according to claim 1, wherein the teeth ring comprises a teeth ring body and an inner ring protruding from the teeth ring body, and the inner ring is a toothed shaped structure; the teeth ring body is in an open loop structure; the toothed structure is configured to insert into the steel pipe body when being subjected to a mutual compression with the steel pipe body.
 12. The compression teeth ring connection pipe fitting according to claim 11, wherein the teeth ring body is in a “C” shaped structure and is made of a radially shrinkable metal material.
 13. The compression teeth ring connection pipe fitting according to claim 11, wherein the toothed structure comprises multiple teeth spaced along an extension direction of the teeth ring body, and the teeth are extended from the inner ring of the teeth ring body towards an axis direction of the teeth.
 14. The compression teeth ring connection pipe fitting according to claim 13, wherein the toothed shaped structure is arranged in two rows, and some teeth of the two rows of the toothed shaped structure are faced with each other.
 15. The compression teeth ring connection pipe fitting according to claim 14, wherein some teeth are misaligned with each other.
 16. The compression teeth ring connection pipe fitting according to claim 13, wherein the toothed structure is arranged in a row, and multiple teeth of the row of toothed shaped structure are arranged at equal intervals.
 17. The compression teeth ring connection pipe fitting according to claim 13, wherein multiple teeth of the toothed shaped structure are provided at one edge of at least one side of the teeth ring body.
-