

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383035
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Sanchez; Kalley

Self-supporting shade and kit for electronic devices

Abstract

A free-standing shade comprising a self-supporting base, an at least partially opaque shield, and means for removably securing the shield to the base, and an assembly including the same, are provided. The base comprises a first plate and a second plate extending at an angle from a rear edge of the first plate, where the first plate is sized to support an object, such as an electronic device or even DJ equipment, to be shaded thereon. The securement means may be disposed on an inside of the second plate along a forward edge of such plate and is operative to suspend the shield at an angle over any of the base to provide shade over the supported object. The securement means may be configured as two horizontal bars spaced apart from each other to engage an edge of the shield and permit rapid assembly and dismantling of the shade.

Inventors:	Sanchez; Kalley (Monterey Park, CA)
Applicant:	Sanchez; Kalley (Monterey Park, CA)
Family ID:	93845193
Appl. No.:	18/335616
Filed:	June 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240415247 A1	Dec. 19, 2024

Publication Classification

Int. Cl.: G06F1/16 (20060101); A45B23/00 (20060101)

U.S. Cl.:

CPC A45B23/00 (20130101); A45B2023/0006 (20130101); A45B2023/0093 (20130101)

Field of Classification Search

CPC: A45B (23/00); A45B (2023/0006); A45B (2023/0093)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2109881	12/1937	Goldberg	135/117	A47G 9/062
4082102	12/1977	Heuer	135/120.2	E04H 15/003
4295481	12/1980	Gee	135/96	E04H 15/58
4491435	12/1984	Meier	403/56	F16M 11/2078
5033528	12/1990	Volcani	403/56	F16M 11/40
5137072	12/1991	Traspadini	160/370.22	B60J 1/2063
5641191	12/1996	Jia	403/90	F16M 11/2078
5752537	12/1997	Kranzler	135/900	E04H 15/003
9175496	12/2014	Darquea	N/A	E04H 15/003
9351415	12/2015	Zaccaria	N/A	H04B 1/3888
10963010	12/2020	Griffin	N/A	G02B 27/0018
12135582	12/2023	Manthei	N/A	G06F 1/1603
2013/0148204	12/2012	Allen	359/601	G02F 1/133502
2015/0288319	12/2014	Hartman	136/246	H02S 20/30
2017/0279478	12/2016	Fathollahi	N/A	H04B 1/3877
2017/0279944	12/2016	Gander	N/A	H04M 1/04
2017/0322590	12/2016	Jacobs	N/A	H04M 1/026
2019/0297178	12/2018	Gander	N/A	H04M 1/215
2023/0363560	12/2022	Scott	N/A	E04B 1/3445

Primary Examiner: Leiby; Christopher E

Attorney, Agent or Firm: Omni Legal Group

Background/Summary

GOVERNMENT CONTRACT

(1) Not applicable.

CROSS-REFERENCE TO RELATED APPLICATIONS

(2) Not applicable.

STATEMENT RE. FEDERALLY SPONSORED RESEARCH/DEVELOPMENT

(3) Not applicable.

COPYRIGHT & TRADEMARK NOTICES

(4) A portion of the disclosure of this patent document may contain material which is subject to copyright protection. This patent document may show and/or describe matter which is or may become trade dress of the owner. The copyright and trade dress owner has no objection to the facsimile reproduction by any one of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyrights and trade dress rights whatsoever.

TECHNICAL FIELD

(5) The disclosed subject matter relates generally to shades, and, more particularly, to protective sun covers for electronic devices that may be readily engaged or disengaged as needed or desired.

BACKGROUND

(6) Coachella, Stagecoach, Ultra, and Lollapalooza, are just a few well-known music festivals drawing crowds of thousands annually. These festivals are often all-day, outdoor events, starting during the day and lasting until well into the night, creating a dynamic and immersive experience for attendees. While the extended festival day is exciting and enjoyable to most attendees, it can present challenges to the staff and crew who have to ensure equipment is protected from changing conditions.

(7) Currently, many DJs and other sound professionals protect their equipment through the use of temporary shade structures, such as umbrellas and pop-up tents. However, umbrellas, pop-up tents, and other similar temporary structures are bulky, time-consuming to set up and take down, inefficient, and can even obscure the DJ from view. These temporary structures often provide the shading surface from several feet over the desired area. This means that not only is sensitive equipment inadequately protected from elements such as dust, rain, or accidental spills, but it also requires constant adjustment to maintain the shade over a targeted area, such as over the DJ's turn table, mixers, soundboard, laptop computer, smart phone and the like as the sun changes position throughout the event. This distracts from the event itself, as attendees, and even the DJs, get distracted by the constant adjustment necessary to protect the equipment from the sun.

Consequently, there is a need for an improved shading mechanism that can be rapidly assembled to provide consistent shade to a desired area and rapidly dismantled without disturbing any items placed within the desired area.

(8) One proposal for a sun shade is U.S. Pat. No. 10,963,010 to Griffin, which teaches a foldable, three panel light shade mounted along the edges of a laptop computer screen using clips. Another proposal is found in U.S. Pat. No. 9,310,615 to Allen, which teaches a foldable sun blocking and privacy hood. Both of these depend on a vertical component to provide structural support to the shade. The need for vertical support offered by the electronic device to be used severely limits its applicability. Indeed, many soundboards and other sound equipment-especially those used at music events-require vertical clearance to permit the user to access any touchscreens and/or controls in the form of knobs, dials, and slides. As the current proposals require the electronic device itself to provide vertical support for the shade, they are unsuitable for many types of sound equipment. Further, these proposals comprise lateral supports, which create a barrier between adjacent devices. This severely limits the ability to rapidly access various devices and limits their usability to only devices that fall within a predetermined size. As a result, these proposals cannot accommodate a wide range of uses and devices.

(9) There remains a need for self-supporting shades configured to accommodate a wide range of devices and equipment that can be rapidly assembled and dismantled.

SUMMARY

(10) The present disclosure is directed to a low-profile shade comprising a base, shield, and a securement means, wherein the securement means is operative to suspend the shield from the base to provide shade over at least a portion of such base. More particularly, the present disclosure is directed to a low-profile sun cover that may be rapidly assembled to selectively provide shade and further dismantled without the need for specialized tools or otherwise disturbing any object, such as an electronic device, positioned on the base. The electronic device may be any electronic device, such as a turn table, mixer, soundboard, laptop or tablet computer, smart phone, and the like. While the disclosure will be described in connection with the electronic device, a person of ordinary skill will recognize that any object may be shaded and the reference to the electronic device is in the interest of brevity.

(11) For purposes of summarizing, certain aspects, advantages, and novel features have been

described. It is to be understood that not all such advantages may be achieved in accordance with any one particular embodiment. Thus, the disclosed subject matter may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages without achieving all advantages as may be taught or suggested.

(12) In one embodiment, the base comprises a first plate and a second plate extending upward at an angle from a rear edge of the first plate. In some embodiments, the second plate may extend off the rear edge of the first plate at an outward angle greater than 90° . Of course, in other embodiments the second plate may extend off the rear edge at about a 90° angle or inwards towards the first plate.

(13) In one embodiment, the securement means may be integrated on or applied to the base. More particularly, the securement means may be disposed on the second plate in a manner operative to suspend any of the shield over any of the first plate. Of course, in another embodiment, the securement means may be integrated on or applied to the shield. Indeed it is even contemplated that the securement means may be an independent structure operative to securely engage the base and the shield with one another.

(14) In some embodiments, the shield may engage with the second plate at about a ninety-degree angle relative to the second plate. As the second plate, in some embodiments, extends outward from the first plate at an angle greater than 90° , the shield may be suspended at an upward angle relative to the first plate. This arrangement may enable viewing of the electronic device from an elevated position. It is further contemplated that the arrangement may permit viewing of a top surface of the electronic when the shield is secured. In another embodiment, the shield may engage with the second plate at an angle greater than 90° , which one of ordinary skill in the art will recognize may even further increase the visibility of any top surface of the electronic from an elevated position when the shield is secured.

(15) The securement means may be any means operative to securely engage the shield with the base at a fixed angle. In one embodiment, the securement means may be operative to removably secure the shield to the base using a friction fit. The friction fit may be configured in any manner a person of ordinary skill in the art may desire. In one embodiment, the securement means may comprise two horizontal bars spaced apart from each other operative to engage with an edge of the shield. In some embodiments, such horizontal bars may comprise a rubberized, felt, or other lining operative to effectuate the exemplary friction fit. In an embodiment, the securement means may be disposed on an inside of the second plate along a forward edge of the second plate and positioned to suspend the shield at an angle configured to permit at least some vertical visualization of an object, such as the electronic device, situated on the first plate. In another embodiment, the securement means may be configured as a slot extending across any of the inner surface of the second plate. Of course, other securement means may be utilized, such as magnets, clips, clasps, hooks, fasteners, brackets, adhesives, hook and loop fasteners, and the like, and the aforementioned are provided as non-limiting examples only. In some embodiments, a combination of securement means may be utilized.

(16) Any of the sun cover may be formed of an at least partially opaque material, operative to reduce direct light to the electronic device. For example, at least any of the shield may be configured at least partially opaque to provide a removable shade over the electronic device.

(17) Several advantages of the shade and assembly are that they: (a) create a self-supporting shade for use with electronic devices; (b) permit a plurality of sun covers to be utilized in combination with one another to create a laterally continuous shading structure; (c) protects electronic components, such as devices and wires, from access and debris via members in an audience situated opposite any user of the assembly and electronic device; and (d) expands the user's field of view of and access to shaded devices over certain alternative sun protection devices.

(18) Thus, it is an object of this invention to provide a low-profile shade for electronic devices.

(19) It is another object of the invention to provide a shade that may be rapidly assembled.

- (20) It is a further object of this invention to provide a removable shield that may be rapidly dismantled without disturbing any electronic devices shaded by the shield.
- (21) It is still a further object of the invention to suspend the shield in a manner operative to permit vertical viewing of and access to the object to be shaded.
- (22) It is yet another object of the invention to provide a shade that can be abutted with others to provide continuous shade over a greater lateral area.
- (23) One or more of the above-disclosed embodiments, in addition to certain alternatives, are provided in further detail below with reference to the attached figures. The disclosed subject matter is not, however, limited to any particular embodiment disclosed.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows a front perspective view of an embodiment of the shade.
- (2) FIG. 2 shows a rear perspective view of an embodiment of the shade.
- (3) FIG. 3 shows a front exploded perspective view of an embodiment of the shade.
- (4) FIG. 4 shows a side perspective view of an embodiment of the shade in use.
- (5) The disclosed embodiments may be better understood by referring to the figures in the attached drawings, as provided below. The attached figures are provided as non-limiting examples for providing an enabling description of the method and system claimed. Attention is called to the fact, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore not to be considered as limiting of its scope. One skilled in the art will understand that the invention may be practiced without some of the details included in order to provide a thorough enabling description of such embodiments. Well-known structures and functions have not been shown or described in detail to avoid unnecessarily obscuring the description of the embodiments.
- (6) For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the invention. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present invention. The same reference numerals in different figures denote the same elements.
- (7) The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.
- (8) The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements or signals, electrically, mechanically or otherwise. Two or more electrical elements may be electrically coupled, but not mechanically or otherwise coupled; two or more mechanical elements may be mechanically coupled, but not electrically or otherwise coupled; two or more electrical elements may be mechanically coupled, but not electrically or otherwise coupled. Coupling (whether mechanical, electrical, or otherwise) may be for any length of time, e.g., permanent or semi-permanent or only for an instant.

DETAILED DESCRIPTION

(9) Having summarized various aspects of the present disclosure, reference will now be made in detail to that which is illustrated in the drawings. While the disclosure will be described in connection with these drawings, there is no intent to limit it to the embodiment or embodiments disclosed herein. Rather, the intent is to cover all alternatives, modifications and equivalents included within the spirit and scope of the disclosure as defined by the appended claims.

(10) With reference to FIGS. **1-4**, one embodiment of a sun cover **100** may comprise a self-supporting base **110**, and a securement means **130** configured to removably secure with a sun shield **120**. FIG. **4** provides one example of the sun cover **100** in use with an exemplary object to be shaded is provided as an electronic device **400**. The electronic device **400** shown is configured as a media player, however, any electronic device may be utilized. For example, computers, tablets, electronic interfaces, switchboards, soundboards or mixers, or any other device that a person of ordinary skill may desire.

(11) With reference to FIGS. **1-2** in particular, the base **110** may comprise a first plate **112** and a second plate **114** extending off an edge of the first plate **112**. The first plate **112**, may be sized to receive any portion of an electronic device, such as exemplary electronic device **400** in FIG. **4**, and may be configured to anchor the sun cover **100** in place.

(12) Returning to FIGS. **1** and **2**, the second plate **114** may extend off a rear edge **115** of the first plate **112** at an outward angle relative to an inner surface **116** of the first plate **112**. In some embodiments, the angle between the first plate **112** and the second plate **114** may be from about 45° to about 165°. For example, the second plate **114** may extend off the first plate **112** at an angle from about 90° to about 135°. Of course, the second plate **114** may extend off the rear edge **115** of the first plate **112** at any angle a person of ordinary skill in the art may desire. The sun cover **100** may be sized to accommodate any electronic device **400**. In one embodiment, the sun cover **100** may be sized to accommodate electronic devices **400** having a height of less than about thirty-six inches.

(13) In some embodiments, the base **110** may have a width from about six inches to about forty-eight inches. In some embodiments, the base **110** may have a width from about sixteen inches to about thirty inches. A person of ordinary skill will recognize that the particular width of the base **110** will not limit the size of the electronic device **400** to be shaded. It is contemplated that a plurality of sun covers may be sequentially abutted along a lateral edge to accommodate electronic devices of greater width. In some embodiments, the shield **120** may have a width of about equal to the width of the base **110**. In other embodiments, the shield may have a width of less than or greater than the width of the base. It is contemplated that the shield having a width different than the width of the base may permit the sun cover to accommodate varying types and styles of electronic devices. Further, the shield, having any width, may be operative to secure a plurality of abutting bases to each other to form. A person of ordinary skill in the art will recognize that a plurality of sun covers may be aligned with one another along a lateral edge of the bases to create a continuous sun cover. It is contemplated that aligning the plurality of sun covers along the lateral edges may permit the plurality of sun covers to accommodate electronic devices of various sizes or even a plurality of electronic devices.

(14) With reference now to FIG. **3**, the securement means **130** may be located on the second plate **114** of the base **110**. More specifically, the securement means **130** may be aligned with a forward edge **117** of the second plate **114**. As shown in FIGS. **1**, **2**, and **4**, the securement means **130** may be operative to suspend the shield **120** at about a 90° angle relative to the second plate **114**. In FIG. **4** in particular, the second plate **114** extending off the first plate **112** at an outward angle relative to an inner surface **116** of the first plate **112** is operative to suspend the shield **120** upwards relative to the first plate **112**. This may permit the electronic device **400** to be viewed from above, permitting use of the sun cover **100** with a large range of digital interfaces. Of course, in other embodiments, the securement means **130** may suspend the shield at any angle relative to the first and second plates.

(15) Returning to FIG. **3**, the securement means **130** may be configured as a first horizontal bar **132** and a second horizontal bar **134** spaced apart from each other to securely engage an edge of the

shield **120**. The first horizontal bar **132** may be parallel to the forward edge **117** of the second plate **114**, and the second horizontal bar **134** may be parallel to the first horizontal bar **132**. The distance between the first horizontal bar **132** and the second horizontal bar **134** may be defined by an edge of the shield **120**. It is contemplated that the first horizontal bar **132** and the second horizontal bar **134** being spaced apart from each at a distance about equal to the edge of the shield **120** may permit the shield **120** to removably secure to the base **110**.

(16) Of course, in other embodiments, not shown, any suitable securement means may be utilized. For example, and without limitation, the securement means may comprise a slot, magnets, clips, clasps, hooks, fasteners, brackets, latches, adhesives, Velcro, or any other suitable attachment means. The securement means may further comprise additional elements, such as a rubberized lining, felt lining, and the like, operative to improve securement of the shield **120** therein.

(17) In addition, the shield **120** may be substantially rectangular in shape wherein at least one edge is configured to removably secure with the securement means **130**. Of course, other shapes may be utilized, and the aforementioned is provided as a non-limiting example only. In some embodiments, not shown, each corner on the shield may be rounded and any edge may be configured to removably secure to the securement means. In other embodiments, such as the embodiment shown in FIG. **3**, the corners corresponding with the edge of the shield **120** engage to the securement means **130** may be sharp.

(18) The shield **120** being operative to removably secure with the forward edge of the second plate **114** may permit the shield **120** to be removed during use. Permitting the shield **120** to be rapidly secured or removed from the base **110** may render the device beneficially adaptable to changing conditions, such as the setting sun. Further, the shield **120** may secure to the base **110** in a manner to permit removal when shade is no longer desired while avoiding any need to remove of the electronic device **400** from the base **110**.

(19) The shield **120** may be at least partially opaque. In one exemplary embodiment, the shield **120** may be fully opaque. It is contemplated that the shield **120**, being opaque, may reduce the light permitted to pass through, thereby providing shade. In some embodiments, the base **110** may be at least partially opaque, or in other embodiments, may be fully opaque. It is contemplated that the sun cover **100** being at least partially opaque may reduce direct light, and even heat, on the object to be shaded. In other embodiments, the sun cover **100** may have varying levels of opacity, allowing for at least partial viewing of the electronic device through the shield **120** and/or base **110**. It is contemplated that varying levels of opacity (or translucency, as the case may be) may permit the viewing of any of the electronic device **400** or light emitting from the electronic device **400**, or even presenting a design on any of the sun cover **100**, enhancing the user experience, while reducing radiation to the electronic device **400**.

(20) In an embodiment, the sun cover **100** comprises a low thermal conductivity material, such as hard plastic. The hard plastic may be rigid, durable, stable, and have low thermal conductivity. It is contemplated that this may be considered a suitable option to provide shade to electronic devices, such as the electronic device **400** shown in FIG. **4**, and may reduce direct heat to the electronic device. Of course, other materials may be utilized, including, without limitation, foam, ceramic, wood, cork, glass, acrylic, or any other material that may be desired.

(21) Indeed, a person of ordinary skill in the art will recognize that media players are often utilized with a plurality of electronic device in order to facilitate the integration of audio and visual content. As a result, the lack of additional supports, such as support from the electronic device itself or lateral supports, may accommodate various configurations and sizes of electronic devices and permit continuous lateral access to the electronic devices.

(22) It should be emphasized that the above-described embodiments are merely examples of possible implementations. Many variations and modifications may be made to the above-described embodiments without departing from the principles of the present disclosure. All such modifications and variations are intended to be included herein within the scope of this disclosure

and protected by the following claims.

CONCLUSIONS, RAMIFICATIONS, AND SCOPE

(23) While certain embodiments of the invention have been illustrated and described, various modifications are contemplated and can be made without departing from the spirit and scope of the invention. For example, the type of objects to be shaded may vary depending on the particular needs and interests of the end user and the sun cover may be adapted to accommodate various types of goods. Accordingly, it is intended that the invention not be limited, except as by the appended claim(s).

(24) The teachings disclosed herein may be applied to other systems, and may not necessarily be limited to any described herein. The elements and acts of the various embodiments described above can be combined to provide further embodiments. All of the above patents and applications and other references, including any that may be listed in accompanying filing papers, are incorporated herein by reference. Aspects of the invention can be modified, if necessary, to employ the systems, functions and concepts of the various references described above to provide yet further embodiments of the invention.

(25) Particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being refined herein to be restricted to any specific characteristics, features, or aspects of the self-supporting shade and kit for electronic devices with which that terminology is associated. In general, the terms used in the following claims should not be constructed to limit the self-supporting shade and kit for electronic devices to the specific embodiments disclosed in the specification unless the above description section explicitly define such terms. Accordingly, the actual scope encompasses not only the disclosed embodiments, but also all equivalent ways of practicing or implementing the disclosed system, method and apparatus. The above description of embodiments of the self-supporting shade and kit for electronic device is not intended to be exhaustive or limited to the precise form disclosed above or to a particular field of usage.

(26) While specific embodiments of, and examples for, the method, system, and apparatus are described above for illustrative purposes, various equivalent modifications are possible for which those skilled in the relevant art will recognize.

(27) While certain aspects of the method and system disclosed are presented below in particular claim forms, various aspects of the method, system, and apparatus are contemplated in any number of claim forms. Thus, the inventor reserves the right to add additional claims after filing the application to pursue such additional claim forms for other aspects of the self-supporting shade and kit for electronic devices.

Claims

1. A table-top shade configured to protect one or more electronic devices from the sun and other elements comprising: a self-supporting base having a first plate and a second plate extending at an angle from a rear edge of the first plate; an at least partially opaque shield; and a securement means configured to removably engage the shield with the forward edge of the second plate at a fixed angle over at least a portion of the first plate.
2. The shade of claim 1, wherein the base is at least partially opaque.
3. The shade of claim 1, wherein the securements means is configured as a slot on an inside of the second plate and operative to engage with an edge of the removable shield.
4. The shade of claim 1, wherein the securement means is configured as two horizontal bars spaced apart from each other and operative to engage with an edge of the removable shield.
5. The shade of claim 1, wherein the first and second plate are bodily integrated with one another along an angled junction corresponding to the rear edge of the first plate.
6. The shade of claim 5, wherein the securement means is disposed on an inside of the second plate

along the forward edge of the second plate and positioned to suspend the shield at an angle configured to permit at least some vertical visualization of an object situated on the first plate.

7. The shade of claim 1, wherein the base and shield are plastic.

8. A shade assembly for protecting one or more electronic devices from the sun and other elements comprising: a self-supporting base having a first plate and a second plate extending at an angle from a rear edge of the first plate, the first plate sized to support an object to be shaded thereon; an at least partially opaque shield; and a securement means configured to removably engage the shield with the forward edge of the second plate at a fixed angle over at least a portion of the first plate.

9. The shade of claim 8, wherein the base is at least partially opaque.

10. The shade of claim 9, wherein the securement means is disposed on an inside of the second plate along the forward edge of the second plate and positioned to suspend the shield at an angle configured to permit at least some vertical visualization of an object situated on the first plate.

11. The shade of claim 10, wherein the securement means is disposed on an inside of the second plate along the forward edge of the second plate and positioned to suspend the shield at an angle configured to permit at least some vertical visualization of an object situated on the first plate.

12. The shade of claim 8, wherein the securement means is configured as two horizontal bars spaced apart from each other, and operative to engage with an edge of the removable shield.

13. The shade of claim 8, wherein the base and shield are plastic.
