

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385476
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lu; Weidong et al.

Air compressor

Abstract

The patent application discloses an air compressor. The air compressor comprises a pair of pistons, a motor, a flywheel, a pulley, a crankshaft. Each piston is reciprocable in a corresponding one of the cylinders so as to reciprocate along the axis of the corresponding cylinder to vary a working volume of the cylinder. The motor comprise an output shaft. The pulley transmits torque from said output shaft to said flywheel so as to rotate said flywheel about said axis upon rotation of said output shaft. The crankshaft interconnects said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel. The diameter of the pulley is smaller than that of said flywheel.

Inventors:	Lu; Weidong (Los Altos, CA), Kwok; Daisy (Los Altos, CA)
Applicant:	Lu; Weidong (Los Altos, CA); Kwok; Daisy (Los Altos, CA)
Family ID:	94260756
Appl. No.:	18/356685
Filed:	July 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250027488 A1	Jan. 23, 2025

Publication Classification

Int. Cl.: **F04B27/02** (20060101); **F04B27/00** (20060101); **F04B35/04** (20060101); **F04B53/00** (20060101); **F04B25/00** (20060101)

U.S. Cl.:

CPC **F04B27/005** (20130101); **F04B35/04** (20130101); **F04B53/006** (20130101); F04B25/005 (20130101); F04B27/02 (20130101)

Field of Classification Search

CPC: F04B (27/02); F04B (27/005); F04B (35/04); F04B (25/005); F04B (53/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1846656	12/1931	Rayfield	417/458	F04B 27/005
2008/0168898	12/2007	Hardin	92/153	F04B 39/123
2011/0256001	12/2010	Kobayashi	417/339	F04B 25/005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104074706	12/2013	CN	F04B 23/06

OTHER PUBLICATIONS

engineeringtoolbox.com, published Mar. 2023, URL:
https://web.archive.org/web/20230324170016/https://www.engineeringtoolbox.com/pulley-diameters-speeds-d_1620.html (Year: 2023). cited by examiner

Primary Examiner: Fink; Thomas

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to an air compressor, and particularly relates to an air compressor that is mounted on a tank.

BACKGROUND

(2) In the traditional two-stage compressor, the motor is directly connected to the crank and connecting rod mechanism of the compressor. Under high load conditions, the motor torque needs to be increased to meet the high load conditions, so that the cost of the motor and the whole machine will be greatly increased.

(3) Therefore, there is a need to have a better and efficient compressed air control device with a high pressure air output and high torque.

SUMMARY

(4) In one aspect, one embodiment discloses an air compressor. The air compressor comprises a pair of pistons, a motor, a flywheel, a pulley, and a crankshaft. Each piston is reciprocable in a corresponding one of the cylinders so as to reciprocate along the axis of the corresponding cylinder to vary a working volume of the cylinder. The motor comprises an output shaft. The pulley transmits torque from said output shaft to said flywheel so as to rotate said flywheel about said axis upon rotation of said output shaft. The crankshaft interconnects said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel. The diameter of the pulley is smaller than that of said flywheel.

- (5) Optionally in any aspect, the ratio between the diameter of the pulley and that of flywheel is about 27:104.
- (6) Optionally in any aspect, the air compressor further comprises a drive belt transmitting torque from said output shaft to said flywheel.
- (7) Optionally in any aspect, the air compressor further comprises a bearing supporting said flywheel for rotation about an axis.
- (8) Optionally in any aspect, the air compressor further comprises a shaft extending along said axis between said flywheel and said bearing, wherein said shaft has a first end portion and a second end portion.
- (9) Optionally in any aspect, said first end portion is journaled in said bearing for rotation about said axis.
- (10) Optionally in any aspect, the second end portion is received within a bore in said flywheel.
- (11) Optionally in any aspect, the air compressor further comprises a connecting rod, wherein the piston is configured to connect to one end of the connecting rod.
- (12) Optionally in any aspect, the cylinders have at least one low pressure cylinder and a high pressure cylinder.
- (13) Optionally in any aspect, the air compressor may further comprise a conduit connecting the low pressure cylinder and the high pressure cylinder.
- (14) In further another aspect, one embodiment discloses an air compressor. The air compressor comprises at least two separate cylinder housings, a pair of pistons, a motor, a flywheel, a pulley, and a drive belt. The at least two separate cylinder housings have each cylinder housing defining a cylinder with an axis. The axes are parallel and spaced apart. The pair of pistons with each piston is reciprocable in a corresponding one of the cylinders so as to reciprocate along the axis of the corresponding cylinder to vary a working volume of the cylinder. The motor has an output shaft. The pulley is on the output shaft of the motor. The drive belt connecting the pulley and flywheel. The drive belt transmits torque from said output shaft to said flywheel so as to rotate said flywheel about said axis upon rotation of said output shaft.
- (15) Optionally in any aspect, the air compressor further comprises a crank shaft interconnecting said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel.
- (16) Optionally in any aspect, the diameter of the pulley is smaller than that of said flywheel.
- (17) Optionally in any aspect, the ratio between the diameter of the pulley and that of flywheel is about 27:104.
- (18) Optionally in any aspect, the air compressor further comprises a shaft extending along said axis between said flywheel and said bearing.
- (19) Optionally in any aspect, the air compressor may further comprise a connecting rod, wherein the piston is configured to connect to one end of the connecting rod.
- (20) Optionally in any aspect, the shaft has a first end portion and a second end portion, said first end portion is journaled in said bearing for rotation about said axis, wherein the second end portion is received within a bore in said flywheel.
- (21) In still further another aspect, one embodiment discloses an air compressor. The air compressor comprises at least two separate cylinder housings, a pair of pistons, a distribution valve unit. Each cylinder housing may define a cylinder with an axis. The axes are parallel and spaced apart. Each piston is reciprocable in a corresponding one of the cylinders so as to reciprocate along the axis of the corresponding cylinder to vary a working volume of the cylinder. The motor has an output shaft. The pulley is on the output shaft of the motor. The drive belt connects the pulley and flywheel. The drive belt transmits torque from said output shaft to said flywheel so as to rotate said flywheel about said axis upon rotation of said output shaft. The crank shaft interconnects said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to illustrate the technical solutions more clearly in the embodiments of the present disclosure or the exemplary techniques, the drawings to be used in the embodiments or the description of the exemplary embodiments will be briefly described below. Obviously, the drawings in the following description are only certain embodiments of the present disclosure, and other drawings may be obtained according to the structures shown in the drawings without any creative work for those skilled in the art.

(2) FIG. 1 is a perspective view of an air compressor by removing covering to show a pulley and a flywheel according to one exemplary embodiment;

(3) FIG. 2 is a perspective view of an air compressor by removing partial covering to show a pulley, drive belt, and a flywheel according to one exemplary embodiment;

(4) FIG. 3 illustrates a cross-sectional view of the air compressor; and

(5) FIG. 4 illustrates an enlarged view of the crankshaft, flywheel as shown in FIG. 3. The implementation, functional features and advantages of the present disclosure will be further described with reference to the accompanying drawings.

DETAILED EMBODIMENTS

(6) The invention is not limited to the particular methodology, protocols, and reagents described herein because they may vary. Further, the terminology used herein is for the purpose of describing particular embodiments only and is not intended to limit the scope of the present invention. As used herein and in the appended claims, the singular forms “a,” “an,” and “the” include plural reference unless the context clearly dictates otherwise.

(7) Unless otherwise indicated, all numbers expressing quantities or qualities, properties used in the specification and claims are to be understood as being modified in all instances by the term “about.” Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of reported significant digits and by applying ordinary rounding techniques.

(8) Notwithstanding that the numerical ranges and parameters set forth the broad scope of the invention are approximations, the numerical values set forth in specific examples are reported as precisely as possible. Any numerical value, however, inherently contain certain errors necessarily resulting from the standard deviation found in their respective testing measures.

(9) As used herein, the term “about” means plus or minus 10% of the numerical value of the number with which it is being used. Therefore, about 50 means in the range of 45-55.

(10) Unless defined otherwise, all technical and scientific terms and any acronyms used herein have the same meanings as commonly understood by one of ordinary skill in the art in the field of the invention. Although any methods and materials similar or equivalent to those described herein can be used in the practice of the present invention, the preferred methods, devices, and materials are described herein. The technical means, creative features, objectives, and effects of the patent application may be easy to understand, the following embodiments will further illustrate the patent application. However, the following embodiments are only the preferred embodiments of the utility patent application, not all of them. Based on the examples in the implementation manners, other examples obtained by those skilled in the art without creative work shall fall within the protection scope of the present invention. The experimental methods in the following examples are conventional methods unless otherwise specified. The materials used in the following examples can be obtained from commercial sources unless otherwise specified.

(11) Embodiments of the present invention are directed to an air compressor for a source of compressed air on motor vehicles, and method for designing a more efficient reciprocating piston compressor.

(12) The present disclosure relates to a two-cylinder piston compressor for generating compressed air. The piston compressor has a crankcase for rotatably mounting a crankshaft on which a number of connecting rods are rotatably mounted so as to run counter to one another. The number of connecting rods corresponds to the number of pistons with associated cylinders.

(13) On account of the associated very high compressed air demand, two-stage piston compressors are usually used here, which are correspondingly of two-cylinder design. With two-cylinder piston compressors of the above type, the required compressed air demand can be generated within short periods of time.

(14) The present disclosure relates to a two-cylinder piston compressor for generating compressed air. The piston compressor includes a crankcase having an interior, and a crankshaft rotatably mounted in the crankcase. Also included are two connecting rods mounted in the crankshaft and configured to run counter to one another. Further included are two cylinders mounted in the crankcase and a piston arranged at an end of each of the connecting rods and configured to run in a respective one of the two cylinders.

(15) The present disclosure encompasses the technical teaching that, in order to assist the pumping effect, each piston operates in a separate cylinder. The separate cylinders are generated by separating means which are arranged in the crankcase and which surround the crankshaft, so that different pressure conditions are generated in the chambers. The air compressor is constructed in accordance with the invention, and operates to supply a storage chamber with compressed air. An outlet hose (not shown) may extend from the air compressor to a pneumatically powered tool (not shown) such a hand-held nail gun, impact wrench, or the like.

(16) As shown in FIGS. 1-4, the air compressor **100** comprises a motor **130**, a pair of pistons **122** and **124**, a flywheel **160**, a pulley **150**, a crankshaft **350**. Each piston **122** or **124** is reciprocable in a corresponding one of the cylinders **180**, and **170** so as to reciprocate along the axis C-C' and B-B' (shown in FIG. 3) of the corresponding cylinder **180** and **170** respectively, to vary a working volume of the cylinder **180** and **170**.

(17) The motor **130** comprises an output shaft **140**. Attached onto the output shaft **140** is a bearing **142** to support the pulley **150**. The pulley **150** may transmit torque from said output shaft **140** to said flywheel **160** so as to rotate said flywheel **160** about said axis D-D' (shown in FIG. 3) upon rotation of said output shaft **140**. The crankshaft **350** interconnects said flywheel **160** with said piston **122** or **124** so as to reciprocate said piston **122** or **124** in said cylinder **180** or **170** upon rotation of said flywheel **160**. The diameter of the pulley **150** is smaller than that of said flywheel **160**.

(18) In one embodiment, the ratio between the diameter of the pulley **150** and that of flywheel **160** may be about 27:104. The gear ratio between the pulley **150** and the flywheel **160** may be about 27:104. In one embodiment, the drive belt **210** may be used to transmit torque from the output shaft **140** to the flywheel **160**.

(19) The motor **130** has an output shaft **140** with a longitudinal central axis E-E' (shown in FIG. 3). A first end portion **310** of the output shaft **140** projects a distance from the motor **130** at one side of the air compressor **100**. A second end portion **320** of the output shaft **140** projects oppositely from the motor **130** and is opposite from the first end portion **310**. A cooling fan **132** is mounted on the second end portion **320** of the output shaft **140**. Also mounted on the second end portion **310** is a pulley **150** for a drive belt **210** that transmits torque from the output shaft **140** to the flywheel **160**.

(20) The bearings **162** and **164** support the shaft **72** and the flywheel **160** for rotation about an axis D-D' parallel to the axis E-E' of the output shaft **140** (FIG. 2).

(21) The piston **122** is supported for reciprocating movement along an axis C-C' perpendicular to the axes D-D' and E-E'. Similarly, the piston **124** is supported for reciprocating movement along an

axis B-B' perpendicular to the axes D-D' and E-E'.

(22) The piston **122** or **124** in one embodiment is part of a linkage member **120** or **110** that is connected to the flywheel **160**. The linkage member **120** may comprise a connecting rod **126** and bearing A4 (FIG. 3) supports the linkage member **120**. The linkage member **110** may comprise a connecting rod **112** and bearing A3 (FIG. 3) which supports the linkage member **110** on a support member **330** that projects from the flywheel **160**. The support member **330**, in one embodiment, is screw, for example. The screw may be a flat head screw.

(23) When the flywheel **160** rotates about the axis D-D', the screw **330** moves along a circular path extending around the axis D-D'. This causes the linkage member **110** also to move around the axis D-D', and simultaneously to move back and forth along the axis B-B'. The piston **124** then reciprocates along the axis B-B', and thus pumps compressed air to an outlet port, upon rotation of the flywheel **160** under the influence of the output shaft **140** at the motor **130**.

(24) Similarly, the flywheel **160**'s rotation about the axis D-D' also causes the linkage member **120** to move around the axis D-D', and simultaneously to move back and forth along the axis C-C'. The piston **122** then reciprocates along the axis C-C', and thus pumps compressed air to the outlet port **182**, upon rotation of the flywheel **160** under the influence of the output shaft **140** at the motor **130**. In one embodiment, cylinder **180** may be a low pressure cylinder. Cylinder **170** may be a high pressure cylinder.

(25) Furthermore, the compressed air is released from the outlet port **182** of the cylinder **180** to the cylinder **170** via a conduit **190**, wherein the conduit **190** forms a plurality of bends. As shown in FIG. 2, the conduit **190** may be used to connect the low pressure cylinder **180** and the high pressure cylinder **170**. The conduit **190** may comprise a one way valve (not shown), which help air to move from the low pressure to high pressure. The conduit **190** is designed as a plurality of continuously bent pipes, which can extend the flow path of the compressed air, thereby achieving the effect of heat dissipation. Preferably, the conduit **190** is a copper pipe, for example.

(26) In the embodiment of the present invention, the cylinder **170** is connected to an air storage tank (not marked in the figure) via an air outlet. The air storage tank is used to store compressed air. Generally, an aluminum tank or other metal tanks that can bear a certain pressure are selected, and a one-way guide valve is provided between the cylinder **170** and the air storage tanks.

(27) More specific features of the air compressor **100** are shown in FIGS. 3-4. For example, as shown in FIG. 3, the air compressor **100** further comprise bearings **162** and **164** supporting the flywheel **160** for rotation about an axis D-D'. The air compressor **100** may further comprise a shaft extending along said axis D-D' between said flywheel **160** and said bearing **164**. The shaft has a first end portion and a second end portion. The first end portion may be journaled in the bearing **164** for rotation about the axis D-D'.

(28) The flywheel **160** has an inner surface **430** defining a bore **420** in which the second portion of the shaft **166** is received. In one embodiment, the inner surface **100** may be parallel to the axis D-D', for example. In another embodiment, the inner surface **430** may be frustoconical shape and is tapered uniformly along its length such that an inner end of the bore **420** may have a diameter that is slightly less than the diameter at an outer end. The shaft **166** may be equally tapered at its outer surface, and is received within the bore **420** in an interference fit with the flywheel **160**.

(29) The outer surface of the shaft **166** is engaged in an interference fit with the first bearing **162** in the same manner. The shaft **166** has a cylindrical outer surface which is likewise engaged in an interference fit with the second bearing **164**.

(30) The shaft **166** is machined such that the outer surface complies with close dimensional tolerances. However, the inner surface **430** of the flywheel **160** may not machined to close dimensional tolerances, but instead has the original configuration attained upon formation of the flywheel **160** as a cast metal part. The tapered or non-tapered of the adjoining surfaces **430** and cylindrical outer surface of the shaft **166** enables the interference fit to be established without the need for precision machining at the inner surface **430**. The manufacturing process is simplified, and

a corresponding cost savings are achieved, by forming the torque-transmitting connection between the flywheel **160** and the shaft **166** in this manner.

(31) The linkage member **120** is an elongated part with a longitudinal central axis C-C' (FIG. 3). A first end portion of the linkage member **120** is configured as a circular disk with a diameter generally perpendicular to the axis D-D'. The second end portion of the linkage member **120** defines the piston **122** (FIG. 1), as noted above.

(32) Similarly, the linkage member **110** is an elongated part with a longitudinal central axis B-B' (FIG. 3). A first end portion of the linkage member **110** is configured as a circular disk with a diameter generally perpendicular to the axis D-D'. The second end portion of the linkage member **110** defines the piston **170** (FIG. 1), as noted above.

(33) The bearing **A3** at the other end of the linkage member **110** is mounted on the linkage member **110** in an interference fit. Specifically, the elongated body of the linkage member **110** has an opening, which comprises a pocket for the bearing **A3**, and is defined by an inner edge surface **450**.

(34) The two bearings **A3** and **A4** are kept on a crankshaft **350**, and the driving shaft **140** of the motor **130** is connected with the crankshaft **350** through a driving belt **210**. The output torque of the crankshaft part portion is greater than the input torque of the driving shaft **140**. The motor **130** may be a brush inner rotor type motor, for example, fixed on one side of the crankshaft **350**. In this case, the driving shaft **140** of the motor **130** is connected with the crankshaft **350** through a transmission component, such as the driving belt **210** and the torque output by the eccentric shaft portion is greater than the torque input by the driving shaft **140**, so that the low-torque motor can work in a high-load working condition by changing the torque of the driving shaft **140** and the crankshaft within an adjustable range without increasing the cost of the motor.

(35) Furthermore, the output end of the driving shaft **140** is provided with the pulley **150**; the flywheel **160** may be arranged on the side far away from the pulley **150**, and one end of the crankshaft **160** is constructed in the flywheel **160**. The transmission component may comprise the driving belt **210**, and the pulley **150** and the flywheel **160** which is transmitted by the driving belt **210**.

(36) Further, the gear ratio between the pulley **150** and the flywheel **160** may be 27:104. This makes it possible to reduce the rotational speed of the flywheel **160** by a predetermined gear ratio to achieve the effect of reducing the rotational speed to increase the torque.

(37) In the embodiment of the present invention, the rotation axis of the bearings **A3** and **A4** held on the crankshaft **160** and the axis D-D' of the flywheel **160** have different eccentricities d_2 and d_1 . As shown in FIG. 3, the eccentric distance between the bearing **A3** and the axis D-D' of the flywheel **160** is d_2 , and the eccentric distance between the bearing **A4** and the transmission axis of the flywheel **160** is d_1 , so that the connecting rod **112** matched with the bearing **A3**. the connecting rod **126** matched with the bearing **A4** have different compression strokes. The compression stroke of the pistons **124** and **122** can be more conveniently and flexibly adjusted.

(38) The inner edge surface **450** extends continuously in a closed loop around an axis F-F' which intersects the axis B-B' orthogonally. A major section of the inner edge surface **450** has an annular contour centered on the axis F-F', and thus defines a circular portion of the opening.

(39) The bearing **A4** at the other end of the linkage member **120** is mounted on the linkage member **120** in an interference fit. Specifically, the elongated body of the linkage member **120** has an opening, which comprises a pocket for the bearing **A4**, and is defined by an inner edge surface **460**. The inner edge surface **460** extends continuously in a closed loop around an axis G-G' which intersects the axis B-B' orthogonally. A section of the inner edge surface **460** has an annular contour centered on the axis F-F', and thus defines a circular portion of the opening.

(40) In accordance with a particular feature of the invention, the linkage member **110** or **120** may be a cast metal part. A washer **410** may be used for tightly sealing the screw **330** to the bearing **A3**. Similarly, a washer **430** may be used for tightly sealing the bearing **A3** and the bearing **A4**.

(41) In the embodiment of the present invention, according to FIGS. 1-4, the bearings **A3** and **A4**

are locked to the axial direction of the crankshaft **160** through the screw **330**. And a threaded hole (not marked in the figure) capable of being screwed by the screw **330** is formed on the crankshaft **350**, so that the screw **330** can be locked into the bolt hole. And the washer **410** is arranged between the bolt head and the bearing **A3**. And another washer **430** is arranged between the bearings **A3** and **A4**, particularly at the position shown in FIG. **4**, so that the bearings **A3** and **A4** can respectively keep a predetermined distance to work in the working process without causing mutual interference, and one end of the shaft **166** is kept in the crankshaft **350**.

(42) One end of the shaft **166** can be held in the bore **420** of the crankshaft **350** by means of an interference fit, and the other end is held on the crankshaft **350** by means of two bearings **A1**, **A2**. In the embodiment of the present invention, the crankshaft **350** and the flywheel **160** may be preferably integrally formed to maintain a certain structural strength. It is also possible to manufacture the crankshaft **350** and the flywheel **160** separately and then assemble them if the manufacturing process does not permit or the cost is considered.

(43) It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

(44) The above shows and describes the basic principles, main features and advantages of the patent application. Those skilled in the industry should understand that the present patent application is not limited by the above-mentioned embodiments. The above-mentioned embodiments and the description are only preferred examples of the present patent application and are not intended to limit the present patent application, without departing from the present utility patent application. Under the premise of spirit and scope, the present utility patent application will have various changes and improvements, and these changes and improvements fall within the scope of the claimed utility patent application. The scope of protection claimed by the utility patent application is defined by the appended claims and their equivalents.

Claims

1. An air compressor comprising: a pair of pistons, each piston being reciprocable in a corresponding one of two cylinders so as to reciprocate along a first axis of the corresponding cylinder to vary a working volume of the corresponding cylinder; a motor having an output shaft; a flywheel; a pulley which transmits torque from said output shaft to said flywheel so as to rotate said flywheel about a second axis upon rotation of said output shaft; a bearing supporting said flywheel for rotation about the second axis; a shaft extending along the second axis between said flywheel and said bearing, wherein said shaft has a first end portion and a second end portion; and a crankshaft interconnecting said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel; wherein diameter of the pulley is smaller than that of said flywheel.
2. The air compressor of claim 1, wherein the ratio between the diameter of the pulley and that of flywheel is about 27:104.
3. The air compressor of claim 1 further comprising a drive belt transmitting torque from said output shaft to said flywheel.
4. The air compressor of claim 1, wherein said first end portion is journaled in said bearing for rotation about said second axis.
5. The air compressor of claim 1, wherein the second end portion is received within a bore in said flywheel.
6. The air compressor of claim 1 further comprising a connecting rod, wherein each piston is configured to connect to one end of the connecting rod.
7. The air compressor of claim 1, wherein the cylinders have at least one low pressure cylinder and

a high pressure cylinder.

8. The air compressor of claim 7 further comprises a conduit connecting the low pressure cylinder and the high pressure cylinder.

9. An air compressor, comprising: a motor having an output shaft; a flywheel; a pulley on the output shaft of the motor, a bearing supporting said flywheel for rotation about an axis; a shaft extending along the second axis between said flywheel and said bearing; and a drive belt connecting the pulley and flywheel, wherein the drive belt transmits torque from said output shaft to said flywheel so as to rotate said flywheel about said axis upon rotation of said output shaft, wherein diameter of the pulley is smaller than that of said flywheel; and a crank shaft interconnecting said flywheel with a piston so as to reciprocate said piston in a cylinder upon rotation of said flywheel.

10. An air compressor, comprising: a pair of pistons, each piston being reciprocable in a corresponding one of two cylinders so as to reciprocate along a first axis of the corresponding cylinder to vary a working volume of the cylinder; a motor having an output shaft; a flywheel; a pulley on the output shaft of the motor; a drive belt connecting the pulley and flywheel, wherein the drive belt transmits torque from said output shaft to said flywheel so as to rotate said flywheel about a second axis upon rotation of said output shaft; a bearing supporting said flywheel for rotation about the second axis; a shaft extending along the second axis between said flywheel and said bearing; and a crank shaft interconnecting said flywheel with said piston so as to reciprocate said piston in said cylinder upon rotation of said flywheel.

11. The air compressor of claim 10, wherein the diameter of the pulley is smaller than that of said flywheel.

12. The air compressor of claim 11, wherein the ratio between the diameter of the pulley and that of flywheel is about 27:104.
