

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389147
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Girotti; Luca et al.

Loudspeaker and housing configuration

Abstract

A loudspeaker system includes a housing, a coaxial loudspeaker driver, and illuminating elements wherein at least one of the illuminating elements, for example a front light diffuser, is sufficiently robust to carry the weight of the coaxial loudspeaker driver. The entire structure is constructed in such a way to prevent water or air leakages. The coaxial loudspeaker driver has a single magnetic assembly with a first axial annular air gap for the low-frequency moving coil and a second annular air gap for the high-frequency moving coil. The loudspeaker driver is supported and maintained in position within the housing by at least one illuminating element. The housing is provided with a water proof light and sound-transmitting front grille and a water proof light and sound transmitting rear cap. The loudspeaker driver and illuminating elements are dimensioned to fit tightly within the housing.

Inventors:	Girotti; Luca (Morrovalle, IT), Pantaleone; Pietro (Potenza Picena, IT)
Applicant:	Girotti; Luca (Morrovalle, IT); Pantaleone; Pietro (Potenza Picena, IT)
Family ID:	93844053
Assignee:	Elettromedia s.p.a. (Potenza Picena, IT)
Appl. No.:	18/336591
Filed:	June 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240422463 A1	Dec. 19, 2024

Publication Classification

Int. Cl.: H04R1/02 (20060101); H04R9/02 (20060101)

U.S. Cl.:

CPC **H04R1/028** (20130101); **H04R9/025** (20130101);

Field of Classification Search

CPC: H04R (1/028); H04R (9/025); H04R (1/023)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4256930	12/1980	Garner	381/340	H04R 1/24
8831270	12/2013	Dimitrov	381/401	H04R 1/30
9084056	12/2014	Flavignard	N/A	H04R 1/30
10506331	12/2018	Baird	N/A	H04R 9/06
12047733	12/2023	Ren	N/A	H04R 1/24
12156008	12/2023	Ren	N/A	H04R 1/24
2005/0175209	12/2004	Powers	381/355	H04R 1/028
2008/0143495	12/2007	Haase	340/815.69	F21K 9/00
2015/0237449	12/2014	Papp	381/398	H04R 7/02
2016/0052017	12/2015	Weber	156/60	H04R 1/023
2020/0363054	12/2019	Wilson	N/A	F21S 10/023
2024/0080594	12/2023	Williamson	N/A	H04R 5/02
2024/0187769	12/2023	Jepsen	N/A	F21V 14/08
2024/0284092	12/2023	Linghu	N/A	H04R 9/063

Primary Examiner: Ojo; Oyesola C

Attorney, Agent or Firm: LADAS & PARRY LLP

Background/Summary

FIELD OF INVENTION

(1) The present invention relates to loudspeaker lighting and housing configurations including a coaxial loudspeaker driver where the inner structure of the housing and of the coaxial loudspeaker driver are protected from splashing water and other external particles.

DESCRIPTION OF THE RELATED ART

(2) Marine sound systems may be exposed to splashing water and other impacting external particles. Existing loudspeaker configurations address several issues, but do not introduce elements for protecting the inner structure of the loudspeaker driver.

(3) U.S. Pat. No. 10,924,844 describes a double concentric horn to achieve better sound output and clarity over distance. U.S. Pat. No. 10,841,689 describes a housing with a three-way coaxial loudspeaker driver where the central axis of the driver offset from the central axis of the housing to improve directionality. U.S. Pat. No. 11,149,939 describes a housing for a loudspeaker unit that may be selectively illuminated to enhance decorative effect.

BRIEF SUMMARY OF THE INVENTION

- (4) Disclosed and claimed here is a loudspeaker and housing configuration. A loudspeaker system includes a housing, a coaxial loudspeaker driver, and illuminating elements wherein at least one of the illuminating elements, for example a front light diffuser, is sufficiently robust to carry the weight of the coaxial loudspeaker driver. The entire structure is constructed in such a way to prevent water or air leakages.
- (5) The coaxial loudspeaker driver is a coaxial moving coil loudspeaker having a single magnetic assembly with a first axial annular air gap for the low-frequency moving coil and a second annular air gap for the high-frequency moving coil. A central yoke is formed in such a way to define an internal axial air passage. A low-frequency diaphragm provides an internal axial air passage as a continuation for the yoke's air passage. The air passage from the input section of the yoke's air passage to the outer section of the diaphragm's air passage defines a horn. A cap fixed on the low frequency diaphragm enables the output of acoustic energy through the horn while preventing water and other particles from entering the first annular air gap and the magnetic assembly.
- (6) Other aspects, features, and techniques will be apparent to one skilled in the relevant art in view of the following detailed description.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 depicts the exploded view of a loudspeaker and housing configuration according to the implementation of the disclosure.
- (2) FIG. 2 depicts a cross-section of a coaxial loudspeaker driver according to the implementation of the disclosure.
- (3) FIG. 3 depicts a longitudinal cross-section of the loudspeaker and lighting elements assembled in a housing.

DETAILED DESCRIPTION OF THE INVENTION

- (4) The present disclosure generally pertains to systems for providing sound and light. The sound system includes a coaxial moving coil loudspeaker driver to achieve higher sound output and more controlled directionality than conventional loudspeaker arrangements, which may emit sound in an unfocused and less efficient manner. The lighting system includes one or two illuminating elements to achieve a decorative effect. Each such illuminating element is conveniently formed by a combination of an LED strip and a light diffuser although other forms of illumination such as CFL bulbs may be used in some situations. When two illuminating elements are used, it is convenient for one such element to be collocated with the coaxial loudspeaker driver and the other to be located to the rear of the coaxial loudspeaker driver.
- (5) The sound system and the lighting system are fixed within the housing, in such a way to: provide an air tight volume defined by the hollow cavity of the housing and the rear surface of the coaxial loudspeaker driver, said volume defining an acoustic load for the low frequency diaphragm; and prevent water and other particles from entering the magnetic assembly. Air and water tightness are achieved by arrangement of the components within the housing in such manner that use of gaskets or interlocking connections between the housing and front and rear elements, such as a front grille and a rear cap, and location of gaskets between components within the housing can achieve the desired objective.
- (6) Conveniently the illuminating elements, the front grille, the housing and the rear cap, are dimensioned and shaped such that gaskets can be located between the front illuminating element and the front grille, between the front illuminating element and the housing and also, in case of two illuminating elements, between the rear illuminating element, the rear cap and the housing.
- (7) Typically, the loudspeaker driver comprises a pair of coaxial voice coils operating in air gaps within the driver structure, one of which drives a cone for lower frequencies and is located on one

side of an annular magnet and the other drives a high frequency diaphragm which is located on the second side of the annular magnet.

(8) Advantageously, one of the illuminating elements encircles part of the loudspeaker assembly, for example the frame or magnet, and is sufficiently robust that it can bear the weight of the coaxial loudspeaker driver and maintain its position within the housing. For example, this light diffuser may be made of polycarbonate or any other material that may be used to manufacture transparent plates and attached to the frame or other parts of the loudspeaker driver by means of screws or glue. If desired additional support, for example mounted on the housing, may be used to ensure that the loudspeaker driver remains in its correct position within the housing. The assembly within the housing may include gaskets at suitable locations, for example on each side of the loudspeaker driver to optimize the protection against water intrusion into the area surrounding the loudspeaker driver.

(9) The components are so dimensioned as to fit tightly within the housing while providing for the air gaps noted above.

(10) Referring now to the figures, FIG. 1 depicts the exploded view of a loudspeaker and housing. A system **100** includes a housing **101** fixed with a front light diffuser **102** using a plurality of screws and a gasket **103**, where a LED strip **104** is fixed with the front light diffuser. A coaxial loudspeaker driver **200** is fixed with the front light diffuser **102** using a plurality of screws. A front grille **106** is fixed with the front light diffuser **102** using a plurality of screws and a gasket **107**, said front grille including a plurality of bars to protect the coaxial loudspeaker driver from impacting objects.

(11) A rear cap **108** is fixed with the rear portion of the housing using a plurality of screws and a double gasket **109**, where the screws pack together a LED strip **110** and a rear light diffuser **111**.

(12) With reference to FIG. 2, said coaxial loudspeaker driver includes: a common magnetic assembly **200** having an annular magnet **201**, a front plate **202**, a rear plate **203**, a central yoke **204** formed in such a way to define an internal axial air passage **205** where the yoke **204** and the plates form a first annular air gap for the low-frequency moving coil **206** and a second annular air gap for the high-frequency moving coil **207**; the low frequency moving coil **206** is connected to a diaphragm **208**, said diaphragm formed in such a way to define an internal axial air passage coaxial to the central yoke air passage, said central yoke air passage with said diaphragm air passage forming the internal air volume of an acoustic horn **209**; a cap **210** realized with a perforated material which is desirably hydrophobic, for example made of an acrylic. The diaphragm **208** and part of the horn **209** are surrounded by a frame **211** that can be attached to an illuminating element. The horn **209** is preferably treated with a waterproofing material such as epoxy or acrylic. The frame **211** may be made of plastic, steel or aluminum.

(13) FIG. 3 shows the cross-sectional view of an assembled loudspeaker, illuminating elements and housing. The parts have the same numbering as in FIGS. 1 and 2. In the embodiment shown, the frame **211** of the loudspeaker driver **200** is attached to the front light diffuser **102** by screws.

(14) Tuning and calibration of the parts may, if desired, permit omission of a non-magnetic spacing ring, as is commonly used from the loudspeaker driver assembly.

Claims

1. A loudspeaker system comprising a housing containing a coaxial loudspeaker driver, and illuminating elements; wherein the coaxial loudspeaker driver is a coaxial moving coil loudspeaker having a single magnetic assembly with a first axial annular air gap for a low-frequency moving coil and a second annular air gap for a high-frequency moving coil; said loudspeaker driver being supported and maintained in position within the housing by at least one illuminating element; said housing being provided with a water proof light and sound-transmitting front grille and a water proof light and sound transmitting rear cap; and said loudspeaker driver and illuminating elements

being dimensioned to fit tightly within the housing; wherein a front light diffuser is attached to said housing and a LED strip is fixed to the front light diffuser; a front grille is attached to the front light diffuser, said front grille including a plurality of bars; a rear cap fixed to the rear portion of the housing using a plurality of screws and a double gasket, where the screws pack together a LED strip and a rear light diffuser with the rear cap; and the coaxial loudspeaker driver is attached to the front light diffuser using a plurality of screws and a gasket.

2. A loudspeaker system as claimed in claim 1 wherein said coaxial loudspeaker driver: comprises an annular magnet, a central yoke formed in such a way to define an internal axial air passage where the yoke and plates form a first annular air gap for the low-frequency moving coil and a second annular air gap for the high-frequency moving coil said low frequency moving coil being connected to a diaphragm, said diaphragm formed in such a way to define an internal axial air passage coaxial to the central yoke air said central yoke air passage with said diaphragm air passage forming the internal air volume of an acoustic horn; and a second annular air gap for the high-frequency moving coil.

3. A loudspeaker system as claimed in claim 1 wherein said illuminating elements comprise an LED strip and a light diffuser.

4. A loudspeaker system as claimed in claim 1 wherein a part of said loudspeaker driver is mounted within a light diffuser forming part of an illuminating element.

5. A loudspeaker system as claimed in claim 4 wherein said system comprises two illuminating elements and the loudspeaker driver is mounted within the light diffuser of the forward illuminating element.
