

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385795
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Ichikawa; Hiromitsu et al.

Tire air pressure monitoring system and tire air pressure monitoring program

Abstract

A tire air pressure monitoring system includes: a data acquisition unit that acquires tire air pressure data at each fixed detection period; a storage unit that stores newly acquired air pressure data P(0), and air pressure data P(1) to P(N) acquired 1 to N periods prior to the air pressure data P(0); a determination unit that determines a state in which air pressure has decreased, on the basis of air pressure data; and a communication unit that transmits a determination result of the determination unit to an external device, in which the determination unit compares each piece of the air pressure data P(1) to P(n) with the air pressure data P(0) to calculate decrease values, compares the decrease values with a preset first threshold value (th1), and determines that tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value.

Inventors:	Ichikawa; Hiromitsu (Tokyo, JP), Fukumori; Hajime (Tokyo, JP)
Applicant:	BRIDGESTONE CORPORATION (Tokyo, JP)
Family ID:	81208056
Assignee:	BRIDGESTONE CORPORATION (Tokyo, JP)
Appl. No.:	18/031694
Filed (or PCT Filed):	October 07, 2021
PCT No.:	PCT/JP2021/037098
PCT Pub. No.:	WO2022/080221
PCT Pub. Date:	April 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240019328 A1	Jan. 18, 2024

Foreign Application Priority Data

JP

2020-174380

Oct. 16, 2020

Publication Classification

Int. Cl.: **B60C23/00** (20060101); **B60C23/04** (20060101); **G01L17/00** (20060101); **G01L19/08** (20060101)

U.S. Cl.:

CPC **G01L17/00** (20130101); **B60C23/0479** (20130101); **G01L19/086** (20130101);

Field of Classification Search

CPC: B60C (23/0408); B60C (23/0496); B60C (23/061); B60C (23/0494); B60C (23/0416); B60C (23/0433); B60C (23/0493); B60C (19/00); B60C (23/04); B60C (23/0462); B60C (23/20); B60C (23/041); B60C (23/0411); B60C (23/0479); B60C (23/0444); B60C (11/246); B60C (23/064); B60C (23/0488); B60C (11/24); B60C (23/007); B60C (23/062); B60C (23/0401); B60C (23/0413); B60C (23/06); B60C (23/043); B60C (23/0452); B60C (23/0498); B60C (23/02); B60C (23/0467); B60C (99/006); B60C (2019/004); B60C (23/0428); B60C (23/0442); B60C (11/243); B60C (23/009); B60C (23/0425); B60C (23/00354); B60C (23/004); B60C (23/045); B60C (23/0464); B60C (23/04985); B60C (23/003); B60C (23/00318); B60C (23/0403); B60C (23/0406); B60C (23/0472); B60C (23/066); B60C (23/00); B60C (23/00372); B60C (29/02); B60C (23/006); B60C (11/00); B60C (23/0454); B60C (23/044); B60C (23/0455); B60C (23/008); B60C (23/0483); B60C (25/002); B60C (23/0461); B60C (23/0474); B60C (23/0489); B60C (23/0491); B60C (29/064); B60C (23/0415); B60C (23/00363); B60C (23/0459); B60C (23/0471); B60C (23/0481); B60C (23/0476); B60C (11/0318); B60C (23/0477); B60C (2200/02); B60C (23/002); B60C (23/0437); B60C (2019/005); B60C (23/042); B60C (23/0405); B60C (23/0422); B60C (23/0423); B60C (23/0466); B60C (13/001); B60C (29/06); B60C (23/0447); B60C (25/132); B60C (23/0427); B60C (23/0449); B60C (9/18); B60C (25/00); B60C (23/065); B60C (23/0484); B60C (23/0486); B60C (19/003); B60C (13/00); B60C (23/00336); B60C (23/00345); B60C (23/08); B60C (17/00); B60C (2019/006); B60C (23/001); B60C (25/142); B60C (5/004); B60C (17/02); B60C (23/0445); B60C (23/0457); B60C (29/00); B60C (11/0083); B60C (25/145); B60C (9/02); B60C (11/0332); B60C (25/18); B60C (29/066); B60C (11/13); B60C (23/0418); B60C (23/0469); B60C (23/068); B60C (23/12); B60C (99/00); B60C (23/0432); B60C (25/138); B60C (5/14); B60C (11/03); B60C (23/005); B60C (25/005); B60C (25/007); B60C (25/0554); B60C (3/00); B60C (11/11); B60C (17/04); B60C (17/06); B60C (23/0435); B60C (23/063); B60C (23/10); B60C (25/14); B60C (29/005); B60C (29/062); B60C (99/003); B60C (11/032); B60C (11/12); B60C (13/003); B60C (15/06); B60C (19/001); B60C (23/126); B60C (23/127); B60C (23/16); B60C (29/068); B60C (3/04); B60C (9/20); B60C (11/01); B60C (11/0302); B60C (13/02); B60C (25/056); B60C (29/04); B60C (5/142); B60C (1/0016); B60C (11/0304); B60C (11/0306); B60C (19/08); B60C (2009/2038); B60C (2011/0374); B60C (2011/0388); B60C (2011/1213); B60C (2011/1231); B60C (2011/1245); B60C (2200/04); B60C (2200/065); B60C (23/00305); B60C (23/067); B60C (23/131); B60C (23/135); B60C (23/137); B60C (23/18); B60C (25/02); B60C (11/02); B60C (17/009); B60C (19/002);

B60C (19/12); B60C (2019/007); B60C (23/00347); B60C (25/05); B60C (5/001); B60C (5/22); B60C (1/0008); B60C (11/0058); B60C (11/0311); B60C (11/033); B60C (11/1218); B60C (11/124); B60C (11/1384); B60C (13/04); B60C (15/0036); B60C (15/024); B60C (17/041); B60C (17/066); B60C (2007/005); B60C (2009/0071); B60C (2009/2022); B60C (2009/2025); B60C (2011/0358); B60C (2011/1254); B60C (2017/068); B60C (2200/06); B60C (2200/12); B60C (2200/14); B60C (23/121); B60C (23/123); B60C (23/133); B60C (25/0503); B60C (25/0515); B60C (25/0521); B60C (25/0551); B60C (25/15); B60C (25/16); B60C (29/007); B60C (3/06); B60C (5/002); B60C (5/02); B60C (5/20); B60C (7/00); B60C (7/12); B60C (9/005); B60C (9/1807); B60C (9/28); B60C (11/0041); B60C (11/04); B60C (2009/0276); B60C (2011/0033); B60C (2011/0346); B60C (2015/0617); B60C (2015/0678); B60C (2015/0682); B60C (2200/00); B60C (23/085); B60C (25/0548); B60C (25/185); B60C (7/105); B60C (7/107); G01M (17/02); G01M (17/022); G01M (17/027); G01M (17/021); G01M (17/024); G01M (17/025); G01M (17/013); G01M (17/007); G01M (1/045); G01M (17/06); G01M (1/326); G01M (1/02); G01M (1/30); G01M (17/0074); G01M (5/0058); G01M (1/26); G01M (17/04); G01M (1/225); G01M (17/065); G01M (17/0072); G01M (17/10); G01M (7/00); G01M (1/16); G01M (99/00); G01M (7/08); G01M (1/34); G01M (17/028); G01M (17/045); G01M (3/3218); G01M (3/40); G01M (1/04); G01M (17/08); G01M (17/03); G01M (5/0091); G01M (1/365); G01M (13/04); G01M (5/0066); G01M (1/08); G01M (1/22); G01M (13/027); G01M (5/0033); G01M (1/00); G01M (15/044); G01M (17/00); G01M (3/24); G01M (3/2876); G01M (5/0075); G01M (1/06); G01M (1/12); G01M (1/122); G01M (1/24); G01M (1/32); G01M (1/36); G01M (11/081); G01M (13/023); G01M (13/025); G01M (17/0076); G01M (3/022); G01M (3/042); G01M (3/045); G01M (3/147); G01M (3/227); G01M (3/3236); G01M (5/0016); G01M (5/0025); G01M (5/0083); G01M (7/022); G01M (7/025); G01M (7/04); G01M (7/06); G01M (9/02); G01M (9/04); G01M (99/002); G01M (99/004); G01M (1/14); G01M (1/28); G01M (3/002); G01M (3/04); G01M (7/02); G01M (9/06); G01L (17/00); G01L (19/086)

USPC: 73/146-146

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8248224	12/2011	Fujita	340/444	B60C 23/061
8738308	12/2013	Kitano	73/146	B60C 23/061
12128715	12/2023	Ozono	N/A	B60C 23/0474
2006/0047469	12/2005	Fabre et al.	N/A	N/A
2012/0197551	12/2011	Kitano	702/50	B60C 23/061
2015/0091720	12/2014	Graf et al.	N/A	N/A
2017/0368893	12/2016	Kodama et al.	N/A	N/A
2024/0326523	12/2023	Matsuda	N/A	B60C 23/0477

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0 989 001	12/1999	EP	N/A

1 092 570	12/2000	EP	N/A
1798077	12/2013	EP	B60C 23/061
2006-71642	12/2005	JP	N/A
2006-168457	12/2005	JP	N/A
2007331752	12/2006	JP	B60C 23/061
2012-171463	12/2011	JP	N/A
2012-171464	12/2011	JP	N/A
2017-87941	12/2016	JP	N/A
2008/007531	12/2007	WO	N/A
2016/103453	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report of PCT/JP2021/037098 dated Nov. 22, 2021 [PCT/ISA/210]. cited by applicant

Extended European Search Report dated Feb. 23, 2024, issued in European Application No. 21879961.7. cited by applicant

Primary Examiner: Allen; Andre J

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage of International Application No. PCT/JP2021/037098 filed on Oct. 7, 2021, claiming priority based on Japanese Patent Application No. 2020-174380 filed on Oct. 16, 2020.

TECHNICAL FIELD

(2) The present invention relates to a tire air pressure monitoring system and a tire air pressure monitoring program that monitor the air pressure of a pneumatic tire.

BACKGROUND ART

(3) Various technologies have been proposed for detecting and providing notification (warning) of a decrease in tire air pressure.

(4) In particular, a technology has been proposed to more reliably provide notification of a decrease in tire air pressure on the basis of a warning threshold value that follows changes in air pressure within a tire as a vehicle travels (Patent Literature 1).

CITATION LIST

Patent Literature

(5) Patent Literature 1: Japanese Unexamined Patent Application Publication No. 2012-171463

SUMMARY OF THE INVENTION

(6) Here, in the technology for providing notification of a decrease in tire air pressure according to the related art, when the value of the air pressure value in a fixed period has decreased by a certain proportion or more, it is determined that the tire air pressure has decreased.

(7) However, in the related art, there has been a problem in that it is difficult to detect a decrease in air pressure when the tire air pressure detection period is short and the rate of decrease in air pressure is gradual.

(8) Thus, the present invention has been made in view of the above problem, and an object of the present invention is to provide a tire air pressure monitoring system and a tire air pressure

monitoring program that can accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when the rate of decrease in air pressure is gradual.

(9) A tire air pressure monitoring system (S1a) according to an aspect of the present invention includes: a data acquisition unit that acquires tire air pressure data at each fixed detection period; a storage unit that stores newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a determination unit that determines a state in which air pressure has decreased, on the basis of the air pressure data; and a communication unit that transmits a determination result of the determination unit to an external device, in which the determination unit compares each piece of the air pressure data $P(1)$ to $P(n)$ (where n is a natural number from 1 to N) with the air pressure data $P(0)$ to calculate decrease values, compares the decrease values with a preset first threshold value, and determines that tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value.

(10) According to such a configuration, it becomes possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(11) A tire air pressure monitoring system. (S1b) according to another aspect of the present invention includes: a data acquisition unit that acquires tire air pressure data at each fixed detection period; a storage unit that stores newly acquired air pressure data. $P(0)$, and data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a determination unit that determines a state in which air pressure has decreased, on the basis of the air pressure data; and a communication unit that transmits a determination result of the determination unit to an external device, in which, in a case where the determination unit has determined that tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ (where k is a natural number from 1 to N) and the air pressure data $P(0)$, when all pieces of the air pressure data $P(k+1)$ to $P(N)$ are greater than a sum of the air pressure data $P(0)$ and a preset second threshold value, it is determined that the tire air pressure is decreasing.

(12) According to such a configuration, it becomes possible to suppress the effect of a temporary decrease in pressure such as when a tire has ridden up a curb, and more accurately detect a decrease in air pressure.

(13) Furthermore, it is also possible to implement a configuration in which, in a case where the determination unit has determined that the tire air pressure is decreasing according to a decrease value between the air pressure data $P(k)$ and the air pressure data $P(0)$, with regard to hypothetical air pressure data P' when it is assumed that air pressure has decreased by a certain proportion from the air pressure data $P(k)$ to $P(0)$, when air pressure data. $P(k-1)$ to $P(1)$ and the hypothetical air pressure data $P'(k-1)$ to $P'(1)$ are compared in a same period and all are within a certain range, it is determined that the tire air pressure is decreasing.

(14) In this case, it becomes possible to prevent erroneous determination, and more accurately detect a decrease in air pressure.

(15) Furthermore, a tire air pressure monitoring program executed by a computer provided in a tire air pressure monitoring system according to another aspect of the present invention includes: a step of acquiring tire air pressure data at each fixed detection period; a step of storing newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a step of determining a state in which air pressure has decreased, on the basis of the air pressure data; and a step of transmitting a determination result to an external device, in which, in the step of determining the state in which air pressure has decreased, each piece of the air pressure data $P(1)$ to $P(n)$ (where n is a natural number from 1 to N) is compared with the air pressure data $P(0)$ to calculate decrease values, the decrease values are compared with a preset first threshold value, and it is determined that tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value.

(16) According to such a configuration, it becomes possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(17) Furthermore, a tire air pressure monitoring program executed by a computer provided in a tire air pressure monitoring system according to another aspect of the present invention includes: a step of acquiring tire air pressure data at each fixed detection period; a step of storing newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a step of determining a state in which air pressure has decreased, on the basis of the air pressure data; and a step of transmitting a determination result to an external device, in which, in the step of determining the state in which air pressure has decreased, in a case where it is determined that tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ (where k is a natural number from 1 to N) and the air pressure data $P(0)$, when all pieces of the air pressure data $P(k+1)$ to $P(N)$ are greater than a sum of the air pressure data $P(0)$ and a preset second threshold value, it is determined that the tire air pressure is decreasing.

(18) According thereto, it becomes possible to suppress the effect of a temporary decrease in pressure such as when a tire has ridden up a curb, and more accurately detect a decrease in air pressure.

(19) Furthermore, in the step of determining the state in which air pressure has decreased, in a case where it is determined that the tire air pressure is decreasing according to a decrease value between the air pressure data $P(k)$ and the air pressure data $P(0)$, with regard to hypothetical air pressure data P' when it is assumed that air pressure has decreased by a certain proportion from the air pressure data $P(k)$ to $P(0)$, when air pressure data $P(k-1)$ to $P(1)$ and the hypothetical air pressure data $P'(k-1)$ to $P'(1)$ are compared in a same period and all are within a certain range, it may be determined that the tire air pressure is decreasing.

(20) In this case, it becomes possible to prevent erroneous determination, and more accurately detect a decrease in air pressure.

(21) According to the embodiments herein, it is possible to provide a tire air pressure monitoring system and a tire air pressure monitoring program which can accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when the rate of decrease in air pressure is gradual.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic configuration diagram illustrating a schematic configuration of a tire air pressure monitoring system according to a first embodiment.

(2) FIG. 2 is a functional block diagram illustrating a functional configuration of the tire air pressure monitoring system according to the first embodiment.

(3) FIG. 3 is a flow chart illustrating a processing procedure for determination processing (part 1) executed by the tire air pressure monitoring system according to the first embodiment.

(4) FIG. 4A is a flow chart illustrating a processing procedure for determination processing (part 2) executed by a tire air pressure monitoring system according to a second embodiment.

(5) FIG. 4B is a flow chart illustrating the continuation of the processing procedure for determination processing (part 2) executed by the tire air pressure monitoring system according to the second embodiment.

(6) FIG. 5 consists of graphs (a) and (b) supplementing the processing content of the determination processing (part 2).

(7) FIG. 6 is a flowchart illustrating a processing procedure for determination processing (part 3).

(8) FIG. 7 is a schematic configuration diagram illustrating a modified example of a tire air pressure monitoring system according to an embodiment.

DESCRIPTION OF EMBODIMENTS

First Embodiment

(9) A tire air pressure monitoring system **S1a** according to a first embodiment of the present invention will be described with reference to FIGS. 1 to 3.

(10) Note that the same or similar portions are denoted by the same or similar reference numerals in the following descriptions of the drawings. However, it should be noted that the drawings are schematic and ratios of dimensions and the like are different from those in reality.

(11) Accordingly, specific dimensions and the like should be determined in consideration of the following descriptions. Furthermore, the drawings include portions having dimensional relationships and ratios that are different from each other, as a matter of course.

(12) (Schematic Configuration of Tire Air Pressure Monitoring System)

(13) A schematic configuration of the tire air pressure monitoring system **S1a** according to the first embodiment will be described with reference to the schematic configuration diagram of FIG. 1.

(14) The tire air pressure monitoring system **S1a** includes a sensor unit **SU** provided on a pneumatic tire (hereafter referred to simply as a tire) **10** side.

(15) FIG. 1 illustrates a cross-sectional shape along a tire width direction of a tire **10** mounted on a rim wheel **90**.

(16) Furthermore, a tread portion **20** is a portion where the tire **10** attached to a vehicle, which is not illustrated, comes into contact with a road surface when rolling on the road surface. A tread pattern corresponding to the type of vehicle and the required performance is formed in the tread portion **20**.

(17) The sensor unit **SU**, which detects internal pressure information of the tire **10**, is provided on an inner surface **10a** of the tire **10** to which the tire air pressure monitoring system **S1a** can be applied. Although not directly related to the present embodiment, note that the sensor unit **SU** may be capable of acquiring temperature information and the like.

(18) In the configuration example illustrated in FIG. 1, the sensor unit **SU** is provided on the inner surface **10a** facing the tread portion **20**. More specifically, the sensor unit **SU** is attached to the surface of an inner liner (not illustrated) that prevents leakage of gases such as air filled in the internal space of the pneumatic tire **10** mounted on the rim wheel **90**.

(19) Note that the sensor unit **SU** is not limited to the inner surface **10a** facing the tread portion **20**, and may be provided on an inner surface at a sidewall **30** side of the tire **10**.

(20) The sensor unit **SU** is preferably provided on each tire **10** attached to the vehicle. This is because it is desirable to monitor the leak situation or the like of each tire **10** so as to ensure the safety of the vehicle.

(21) In addition, the sensor unit **SU** need not necessarily be attached to the inner side surface of the tire **10**. For example, a configuration may be adopted in which a part or all of the sensor unit **SU** is embedded inside the tire **10**.

(22) Furthermore, the sensor unit **SU** may be attached to the wheel to which the tire **10** is attached.

(23) (Functional Configuration of Tire Air Pressure Monitoring System)

(24) As illustrated in the functional block diagram of FIG. 2, the sensor unit **SC** includes an internal pressure sensor **SN** that detects internal pressure (air pressure) of the tire, a transmitter **150** that transmits detection data at each fixed detection period (for example, 12 sec, 30 sec, 60 sec, or the like) to an external device (in-vehicle device (ECU) or the like), a processor **100**, and a battery **151** that feeds the internal pressure sensor **SN**, the processor **100**, and the transmitter **150**.

(25) By providing the processor **100** in the sensor unit **SU**, it is possible to determine a state in which air pressure has decreased, in a manner that is well-balanced with processing efficiency without increasing the frequency of transmitting data for which power consumption is high.

(26) The processor **100** is provided with a storage unit **102** configured of a flash memory or the like

that stores newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more).

(27) Note that “ N ” in $P(N)$ can be 3 to 5. It is thereby possible to achieve balance between handling a gradual leak in air pressure and processing efficiency.

(28) In addition, the processor **100** is provided with a determination unit **103** configured of a CPU or the like that determines a state in which air pressure has decreased, on the basis of the air pressure data.

(29) Furthermore, the transmitter **150** transmits the determination result of the determination unit **103** to an external device **250** such as an ECU, via a communication line $N1$.

(30) Here, the determination unit **103** compares each piece of the air pressure data $P(1)$ to $P(n)$ (where n is a natural number from 1 to N) with the air pressure data $P(0)$ to calculate decrease values.

(31) Next, the decrease values are compared with a preset first threshold value $th1$, and when at least one decrease value is greater than or equal to the first threshold value $th1$, it is determined that the tire air pressure is decreasing.

(32) It is thereby possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(33) Note that an example of determination processing that realizes the aforementioned processing described hereinafter.

(34) (Determination Processing (Part 1))

(35) The processing procedure for the determination processing (part 1) executed by the tire air pressure monitoring system $S1a$ will be described with reference to the flowchart illustrated in FIG. 3.

(36) When this processing is started, in step $S10$, tire air pressure data is acquired at each fixed detection period, and the processing moves to step $S11$.

(37) In step $S11$, newly acquired air pressure data $P(0)$ and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more) are stored by the storage unit **102**, and the processing moves to step $S12$.

(38) In step $S12$, each piece of the air pressure data $P(1)$ to $P(n)$ (where n is a natural number from 1 to N) is compared with the air pressure data $P(0)$ to calculate decrease values (for example, $P(0)-P(1)$ and the like), and the processing moves to step $S13$.

(39) In step $S13$, a comparison is made with a preset first threshold value ($th1$), and the processing moves to step $S14$.

(40) Here, the first threshold value $th1$ is a threshold value for an LSB difference of the sensor that is considered to have a significant difference, taking into account errors of a sensor element constituting the internal pressure sensor SN . Furthermore, it is understood that when there is a decrease greater than or equal to the first threshold value $th1$, a sudden decrease in internal pressure can be determined.

(41) The first threshold value $th1$ depends on the measurement period, and can be 3 LSB (approximately 3 to 10 kPa) in 30 sec or less, or 4 LSB (approximately 5 to 15 kPa) in 60 sec, for example.

(42) In step $S14$, if at least one decrease value is greater than or equal to the first threshold value ($th1$) (in other words, for example, if $P(0)-P(1) \geq th1$ or the like), it is determined that the tire air pressure is decreasing, and the processing moves to step $S15$.

(43) In step $S15$, the determination result is transmitted to the external apparatus (ECU or the like) **250**, and the processing ends.

(44) It is thereby possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

Second Embodiment

(45) A tire air pressure monitoring system **S1b** according to a second embodiment of the present invention will be described with reference to FIGS. 1, 2, 4A, 4B, and 5.

(46) Here, the functional configuration and the like of the tire air pressure monitoring system **S1b** according to the second embodiment are the same as those of the tire air pressure monitoring system **S1a** according to the first embodiment, and therefore duplicate descriptions are omitted.

(47) In the tire air pressure monitoring system **S1b**, in a case where the determination unit **103** has determined that the tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ (where k is a natural number from 1 to N) and the air pressure data $P(0)$, when all pieces of the air pressure data $P(k+1)$ to $P(N)$ are greater than the sum of the air pressure data $P(0)$ and a preset second threshold value, it is determined that the tire air pressure is decreasing.

(48) It thereby becomes possible to suppress the effect of a temporary decrease in pressure such as when the tire has ridden up a curb, and more accurately detect a decrease in air pressure.

(49) Furthermore, in a case where the determination unit **103** has determined that the tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ and the air pressure data $P(0)$, with regard to hypothetical air pressure data P' when it is assumed that air pressure has decreased by a certain proportion from the air pressure data $P(k)$ to $P(0)$, when air pressure data $P(k-1)$ to $P(1)$ and the hypothetical air pressure data $P'(k-1)$ to $P'(1)$ are compared in the same period and all are within a certain range, it can be determined that the tire air pressure is decreasing.

(50) In this case, it becomes possible to prevent erroneous determination, and more accurately detect a decrease in air pressure.

(51) (Determination Processing (Part 2))

(52) The processing procedure for the determination processing (part 2) executed by the tire air pressure monitoring system **S1b** will be described with reference to the flowcharts illustrated in FIGS. 4A and 4B.

(53) This determination processing, in addition to detecting a decrease in air pressure such as when there is a gradual leak in air pressure, makes it possible to more reliably provide notification (warning) of a decrease in air pressure by suppressing the effect of a temporary decrease in pressure such as when the tire has ridden up a curb.

(54) More specifically, when determining a state in which air pressure has decreased, in a case where the tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ (where k is a natural number from 1 to N) and the air pressure data $P(0)$, and all pieces of air pressure data $P(k+1)$ to $P(N)$ are greater than the sum of the air pressure data $P(0)$ and the preset second threshold value ($th2$), it is determined that the tire air pressure is decreasing.

(55) When this processing is started, in step **S101**, it is determined whether or not $P(0) - P(1) \geq th1$.

(56) More specifically, the same processing as that in steps **S10** to **S15** in the aforementioned determination processing (part 1) is executed.

(57) Then, if it is determined that the air pressure is decreasing (if “Yes”), the processing moves to **S102**.

(58) In step **S102**, it is determined whether or not $P(2 \text{ to } 5) > P(0) + th2$.

(59) Here, the second threshold value $th2$ is an upper limit for errors of the sensor element constituting the internal pressure sensor **SN**, and can be a value that is approximately twice the error **LSB** relative to the actual value (in other words, the maximum difference **LSP** between measurement samples when there is no change in pressure).

(60) Note that the second threshold value $th2$ can be approximately 5 to 10 kPa, for example.

(61) Then, if the determination result of step **S102** is “No”, the processing moves to step **S111**, and the processing ends without a warning being provided.

(62) Furthermore, if the determination result is “Yes”, the processing moves to step **S110**, a warning is provided that there has been a sudden decrease in tire pressure due to the tire riding up a

curb or the like, and the processing ends.

(63) However, if “No” is determined in step **S101**, the processing moves to step **S103**.

(64) In step **S103**, it is determined whether or not $P(0)-P(2) \geq th1$ and $P(1)$ is within a predetermined range.

(65) Here, $P(0)-P(2) \geq th1$ refers to a case such as being in the range **R1** ($>th1$) in the graph (vertical axis: LSB, horizontal axis: measurement period) illustrated in FIG. 5(a), for example.

(66) Furthermore, $P(1)$ being within a predetermined range refers to a case such as $P(1)$ being within the range **P2** in the graph illustrated in FIG. 5(a), for example.

(67) Then, if “Yes” is determined in step **S103**, the processing moves to step **S104**.

(68) In step **S104**, it is determined whether or not $P(3 \text{ to } 5) > P(0) + th2$.

(69) If the determination result is “No”, the processing moves to step **S111**, and the processing ends without a warning being provided.

(70) Furthermore, if the determination result is “Yes”, the processing moves to step **S110**, a warning is provided that there has been a sudden decrease in tire pressure due to the tire riding up a curb or the like, and the processing ends.

(71) However, if “No” is determined in step **S103**, the processing moves to step **S105**.

(72) In step **S105**, it is determined whether or not $P(0)-P(3) \geq th1$ and $P(1, 2)$ are within a predetermined range.

(73) Here, $P(0)-P(3) \geq th1$ refers to a case such as being within the range **R4** in the graph (vertical axis: LSB, horizontal axis: measurement period) illustrated in FIG. 5(b), for example.

(74) Furthermore, $P(1, 2)$ being within a predetermined range refers to a case such as $P(1, 2)$ being within the range **R8** or **R7** in the graph illustrated in FIG. 5(b), for example.

(75) Then, if “Yes” is determined in step **S105**, the processing moves to step **S106**.

(76) In step **S106**, it is determined whether or not $P(4, 5) > P(0) + th2$.

(77) If the determination result is “No”, the processing moves to step **S111**, and the processing ends without a warning being provided.

(78) Furthermore, if the determination result is “Yes”, the processing moves to step **S110**, a warning is provided that there has been a sudden decrease in tire pressure due to the tire riding up a curb or the like, and the processing ends.

(79) However, if “No” is determined in step **S105**, the processing moves to step **S107**.

(80) In step **S107**, it is determined whether or not $P(0)-P(4) \geq th1$ and $P(1 \text{ to } 3)$ are within a predetermined range.

(81) Here, $P(0)-P(4) \geq th1$ refers to a case such as being within the range **R4** in the graph illustrated in FIG. 5(b), for example.

(82) Furthermore, $P(1 \text{ to } 3)$ being within a predetermined range refers to a case such as $P(1 \text{ to } 3)$ being within the ranges **R6** to **R8** in the graph illustrated in FIG. 5(b), for example.

(83) Then, if the determination result in step **S107** is “Yes”, the processing moves to step **S108**.

(84) In step **S108**, it is determined whether or not $P(5) > P(0) + th2$.

(85) If the determination result is “No”, the processing moves to step **S111**, and the processing ends without a warning being provided.

(86) Furthermore, if the determination result is “Yes”, the processing moves to step **S110**, a warning is provided that there has been a sudden decrease in tire pressure due to the tire riding up a curb or the like, and the processing ends.

(87) However, if “No” is determined in step **S107**, the processing moves to step **S109**.

(88) In step **S109**, it is determined whether or not $P(0)-P(5) \geq th1$ and $P(1 \text{ to } 4)$ are within a predetermined range.

(89) Here, $P(0)-P(5) \geq th1$ refers to a case such as being within the range **R4** in the graph illustrated in FIG. 5(b), for example.

(90) Furthermore, $P(1 \text{ to } 4)$ being within a predetermined range refers to a case such as $P(1 \text{ to } 4)$ being within the ranges **R5** to **R8** in the graph illustrated in FIG. 5(b), for example.

(91) Then, if the determination result is “No”, the processing moves to step **S111**, and the processing ends without a warning being provided.

(92) Furthermore, if the determination result is “Yes”, the processing moves to step **S110**, a warning is provided that there has been a sudden decrease in tire pressure due to the tire riding up a curb or the like, and the processing ends.

(93) As described above, according to this processing, it is possible to detect a decrease in pressure even when there is a gradual leak in the air pressure of the tire **10**.

(94) Furthermore, it becomes possible to suppress the effect of a temporary decrease in pressure such as when the tire **10** has ridden up a curb, and more accurately detect a decrease in air pressure.

(95) Furthermore, there is also the merit that it becomes possible to prevent erroneous determinations, and more accurately detect a decrease in air pressure.

(96) In addition, it is also possible to obtain the effect of it becoming possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(97) (Determination Processing (Part 3))

(98) The processing procedure for the determination processing (part 3) executed by the tire air pressure monitoring system **S1a** (**S1b**) will be described with reference to the flowchart illustrated in FIG. 6.

(99) When this processing is started, in step **S201**, it is determined whether or not $P(0) - P(1) \geq th3$. Here, $P(0)$ is newly acquired air pressure data, $P(1)$ is air pressure data acquired one period before, and $th3$ is a preset third threshold value.

(100) The third threshold value $th3$ is a threshold value for an LSB difference of the internal pressure sensor SN at which a sudden decrease will surely occur even when the tire has ridden up a curb or the like. Furthermore, it is understood that when there is a decrease greater than or equal to the third threshold value $th3$, a sudden decrease in internal pressure can be determined.

(101) The third threshold value $th3$ can be approximately 10 to 30 kPa, for example.

(102) Then, if the determination result is “Yes”, the processing moves to step **S202**. In step **S202**, a warning such as “The tire pressure is decreasing. Please perform tire maintenance.” is notified to the driver or the like, and the processing ends.

(103) It thereby becomes possible to more reliably provide notification of a decrease in tire air pressure. In particular, it becomes possible to accurately detect and provide notification of a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(104) However, if “No” is determined in step **S201**, the processing moves to step **S203**, and the processing ends without a warning being provided.

(105) It is thereby possible to detect and provide notification (warning) of a burst tire **10** or the like.

(106) Note that the determination unit **103** illustrated in FIG. 2 may be implemented such that the air pressure data $P(1)$ and $P(0)$ are compared and a decrease value is calculated, the decrease value is compared with the third threshold value $th3$, and it is determined that the tire air pressure is decreasing when the decrease value is greater than or equal to the third threshold value $th3$.

(107) It thereby becomes possible to detect, at an early stage, a decrease in pressure that is greater than or equal to a certain threshold value such as that of a burst tire.

(108) As described above, the tire air pressure monitoring program in which determination processing is executed can have: a step of acquiring tire air pressure data at each fixed detection period; a step of storing newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ that is acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a step of determining a state in which air pressure has decreased, on the basis of the air pressure data; and a step of transmitting a determination result to the external device (ECU or the like) **250**.

(109) Also, in the step of determining a state in which air pressure has decreased, it is possible to

compare each piece of air pressure data $P(1)$ to $P(n)$ (where n is a natural number from 1 to N) with the air pressure data $P(0)$ to calculate decrease values, compare the decrease values with the preset first threshold value $th1$, and determine that the tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value $th1$.

(110) It thereby becomes possible to accurately detect a decrease in air pressure even when the tire air pressure detection period is short or when there is a slow leak in which the rate of decrease in air pressure is gradual.

(111) Furthermore, a tire air pressure monitoring program according to another configuration can have: a step of acquiring tire air pressure data at each fixed detection period; a step of storing newly acquired air pressure data $P(0)$, and air pressure data $P(1)$ to $P(N)$ acquired 1 to N periods prior to the air pressure data $P(0)$ (where N is a natural number of 2 or more); a step of determining a state in which air pressure has decreased, on the basis of the air pressure data; and a step of transmitting a determination result to the external device (ECU or the like) **250**.

(112) Also, in the step of determining a state in which air pressure has decreased, when it is determined that the tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ (where k is a natural number from 1 to N) and the air pressure data $P(0)$, and all pieces of air pressure data $P(k+1)$ to $P(N)$ are greater than the sum of the air pressure data $P(0)$ and the preset second threshold value $th2$, it can be determined that the tire air pressure is decreasing.

(113) It thereby becomes possible to suppress the effect of a temporary decrease in pressure such as when the tire **10** has ridden up a curb, and more accurately detect a decrease in air pressure.

(114) Furthermore, the step of determining a state in which air pressure has decreased may be implemented such that, in a case where it is determined that the tire air pressure is decreasing according to a decrease value between air pressure data $P(k)$ and the air pressure data $P(0)$, with regard to hypothetical air pressure data P' when it is assumed that air pressure has decreased by a certain proportion from the air pressure data $P(k)$ to $P(0)$, when air pressure data $P(k-1)$ to $P(1)$ and the hypothetical air pressure data $P'(k-1)$ to $P'(1)$ are compared in the same period and all are within a certain range, it is determined that the tire air pressure is decreasing.

(115) It thereby becomes possible to prevent erroneous determination, and more accurately detect a decrease in air pressure.

(116) Furthermore the rate of the detection period may be changed. A decrease in pressure can thereby be detected at an early stage according to the situation.

(117) Furthermore, the value of $P(0)$ may be copied to $P(1)$ to $P(N)$ when the detection period changes. This can prevent an erroneous determination by resetting a stored value.

(118) Furthermore, the second threshold value $th2$ may be changed according to the detection period.

Modified Example

(119) A tire air pressure monitoring system **S1c** according to a modified example will be described with reference to FIG. 7.

(120) FIG. 7 is a schematic configuration diagram illustrating the tire air pressure monitoring system **S1c** according to the modified example.

(121) As illustrated in FIG. 7 the tire air pressure monitoring system **S1c**, a configuration is adopted in which the external device (ECU or the like) **250** mounted in each vehicle communicates wirelessly with the sensor unit **SU** attached to the pneumatic tire **10** via the wireless line **N1**, and also communicates with an external cloud system **300** via a wireless line **N2**. Furthermore, the cloud system **300** is connected to a management server **200**.

(122) The external device of each vehicle then transmits temperature data, internal pressure data, and the like acquired from the sensor unit **SU** to the cloud system **300**.

(123) Furthermore, the sensor unit **SU** may be configured to communicate directly with the external cloud system **300**.

(124) It is thereby possible for the cloud system **300** or the management server **200** to perform

some or all of the aforementioned determination processing executed by the sensor unit SU. It is thereby possible to reduce the processing load of the sensor unit SU.

(125) The tire air pressure monitoring system and tire air pressure monitoring program of the present invention have been described above based on the illustrated embodiments; however, the present invention is not limited thereto, and the configuration of each part can be replaced with any other configurations having equivalent functions.

(126) For example, some of the processing functions of the sensor unit SU in the embodiments herein may be mounted within the external device **250**.

EXPLANATION OF THE REFERENCE NUMERALS

(127) **S1a, S1b, S1c** Tire air pressure monitoring system **SU** Sensor unit **SN** Internal pressure sensor **100** Processor **101** Data acquisition unit **102** Storage unit **103** Determination unit **150** Transmitter **151** Battery **250** External device

Claims

1. A tire air pressure monitoring system comprising: a data acquisition unit that acquires tire air pressure data at each fixed detection period; a storage unit that stores newly acquired air pressure data **P(0)**, and air pressure data **P(1)** to **P(N)** acquired 1 to N periods prior to the air pressure data **P(0)** (where N is a natural number of 2 or more); a determination unit that determines a state in which air pressure has decreased, on the basis of the air pressure data; and a communication unit that transmits a determination result of the determination unit to an external device, wherein the determination unit compares each piece of the air pressure data **P(1)** to **P(n)** (where n is a natural number from 1 to N) with the air pressure data **P(0)** to calculate decrease values, compares the decrease values with a preset first threshold value, and determines that tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value.
2. The tire air pressure monitoring system according to claim 1, wherein, in a case where the determination unit has determined that the tire air pressure is decreasing according to a decrease value between air pressure data **P(k)** and the air pressure data **P(0)**, with regard to hypothetical air pressure data **P'** when it is assumed that air pressure has decreased by a certain proportion from the air pressure data **P(k)** to **P(0)**, when air pressure data **P(k-1)** to **P(1)** and the hypothetical air pressure data **P'(k-1)** to **P'(1)** are compared in a same period and all are within a certain range, it is determined that the tire air pressure is decreasing.
3. A tire air pressure monitoring program executed by a computer provided in a tire air pressure monitoring system, the program comprising: a step of acquiring tire air pressure data at each fixed detection period; a step of storing newly acquired air pressure data **P(0)**, and air pressure data **P(1)** to **P(N)** acquired 1 to N periods prior to the air pressure data **P(0)** (where N is a natural number of 2 or more); a step of determining a state in which air pressure has decreased, on the basis of the air pressure data; and a step of transmitting a determination result to an external device, wherein, in the step of determining the state in which air pressure has decreased, each piece of the air pressure data **P(1)** to **P(n)** (where n is a natural number from 1 to N) is compared with the air pressure data **P(0)** to calculate decrease values, the decrease values are compared with a preset first threshold value, and it is determined that tire air pressure is decreasing when at least one decrease value is greater than or equal to the first threshold value.
4. The tire air pressure monitoring program according to claim 3, wherein, in the step of determining the state in which air pressure has decreased, in a case where it is determined that the tire air pressure is decreasing according to a decrease value between air pressure data **P(k)** and the air pressure data **P(0)**, with regard to hypothetical air pressure data **P'** when it is assumed that air pressure has decreased by a certain proportion from the air pressure data **P(k)** to **P(0)**, when air pressure data **P(k-1)** to **P(1)** and the hypothetical air pressure data **P'(k-1)** to **P'(1)** are compared in

a same period and all are within a certain range, it is determined that the tire air pressure is decreasing.
