

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386354
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Vandike; Nathan R. et al.

Predictive power map generation and control system

Abstract

One or more information maps are obtained by an agricultural work machine. The one or more information maps map one or more agricultural characteristic values at different geographic locations of a field. An in-situ sensor on the agricultural work machine senses an agricultural characteristic as the agricultural work machine moves through the field. A predictive map generator generates a predictive map that predicts a predictive agricultural characteristic at different locations in the field based on a relationship between the values in the one or more information maps and the agricultural characteristic sensed by the in-situ sensor. The predictive map can be output and used in automated machine control.

Inventors:	Vandike; Nathan R. (Geneseo, IL), Palla; Bhanu Kiran Reddy (Bettendorf, IA), Anderson; Noel W. (Fargo, ND)
Applicant:	Deere & Company (Moline, IL)
Family ID:	81044851
Assignee:	Deere & Company (Moline, IL)
Appl. No.:	17/067609
Filed:	October 09, 2020

Prior Publication Data

Document Identifier	Publication Date
US 2020113733 A1	Apr. 14, 2022

Publication Classification

Int. Cl.: G05D1/00 (20240101); A01B69/04 (20060101); A01D41/06 (20060101); A01D41/127 (20060101); G06N5/04 (20230101); G06N20/00 (20190101)

U.S. Cl.:

CPC G05D1/0217 (20130101); A01B69/008 (20130101); A01D41/06 (20130101); A01D41/127 (20130101); A01D41/1278 (20130101); G05D1/0219 (20130101); G06N5/04 (20130101); G06N20/00 (20190101);

Field of Classification Search

CPC: G05D (1/0217); G05D (1/0219); G06N (20/00); G06N (5/04); A01B (68/008); A01D (41/06); A01D (41/127); A01D (41/1278)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3568157	12/1970	Downing et al.	N/A	N/A
3580257	12/1970	Teague	N/A	N/A
3599543	12/1970	Norman	N/A	N/A
3775019	12/1972	Konig et al.	N/A	N/A
3856754	12/1973	Habermeier et al.	N/A	N/A
4129573	12/1977	Bellus et al.	N/A	N/A
4166735	12/1978	Pilgram et al.	N/A	N/A
4183742	12/1979	Sasse et al.	N/A	N/A
4268679	12/1980	Lavanish	N/A	N/A
4349377	12/1981	Durr et al.	N/A	N/A
4360677	12/1981	Doweyko et al.	N/A	N/A
4435203	12/1983	Funaki et al.	N/A	N/A
4493726	12/1984	Burdeska et al.	N/A	N/A
4527241	12/1984	Sheehan et al.	N/A	N/A
4566901	12/1985	Martin et al.	N/A	N/A

4584013	12/1985	Brunner	N/A	N/A
4687505	12/1986	Sylling et al.	N/A	N/A
4857101	12/1988	Musco et al.	N/A	N/A
4911751	12/1989	Nyffeler et al.	N/A	N/A
5059154	12/1990	Reyenga	N/A	N/A
5089043	12/1991	Hayase et al.	N/A	N/A
5246164	12/1992	McCann et al.	N/A	N/A
5246915	12/1992	Lutz et al.	N/A	N/A
5250690	12/1992	Turner et al.	N/A	N/A
5296702	12/1993	Beck et al.	N/A	N/A
5300477	12/1993	Tice	N/A	N/A
5416061	12/1994	Hewett et al.	N/A	N/A
5477459	12/1994	Clegg et al.	N/A	N/A
5488817	12/1995	Paquet et al.	N/A	N/A
5563112	12/1995	Barnes III	N/A	N/A
5585626	12/1995	Beck et al.	N/A	N/A
5586033	12/1995	Hall	N/A	N/A
5592606	12/1996	Myers	N/A	N/A
5606821	12/1996	Sadjadi et al.	N/A	N/A
5666793	12/1996	Bottinger	N/A	N/A
5712782	12/1997	Weigelt et al.	N/A	N/A
5721679	12/1997	Monson	N/A	N/A
5767373	12/1997	Ward et al.	N/A	N/A
5771169	12/1997	Wendte	N/A	N/A
5789741	12/1997	Kinter et al.	N/A	N/A
5809440	12/1997	Beck et al.	N/A	N/A
5841282	12/1997	Christy et al.	N/A	N/A
5849665	12/1997	Gut et al.	N/A	N/A
5878821	12/1998	Flenker et al.	N/A	N/A
5899950	12/1998	Milender et al.	N/A	N/A
5902343	12/1998	Hale et al.	N/A	N/A
5915492	12/1998	Yates et al.	N/A	N/A
5957304	12/1998	Dawson	N/A	N/A
5974348	12/1998	Rocks	N/A	N/A
5978723	12/1998	Hale et al.	N/A	N/A
5991687	12/1998	Hale et al.	N/A	N/A
5991694	12/1998	Gudat et al.	N/A	N/A
5995859	12/1998	Takahashi	N/A	N/A
5995894	12/1998	Wendte	N/A	N/A
5995895	12/1998	Watt	56/10.2 G	G05D 1/0274
6004076	12/1998	Cook et al.	N/A	N/A
6016713	12/1999	Hale	N/A	N/A
6029106	12/1999	Hale et al.	N/A	N/A
6041582	12/1999	Tiede et al.	N/A	N/A
6073070	12/1999	Diekhans	N/A	N/A
6073428	12/1999	Diekhans	N/A	N/A
6085135	12/1999	Steckel	N/A	N/A
6119442	12/1999	Hale	N/A	N/A
6119531	12/1999	Wendte et al.	N/A	N/A
6128574	12/1999	Diekhans	N/A	N/A
6141614	12/1999	Janzen et al.	N/A	N/A
6178253	12/2000	Hendrickson et al.	N/A	N/A
6185990	12/2000	Missotten et al.	N/A	N/A
6188942	12/2000	Corcoran et al.	N/A	N/A
6199000	12/2000	Keller et al.	N/A	N/A
6204856	12/2000	Wood et al.	N/A	N/A
6205381	12/2000	Motz et al.	N/A	N/A
6205384	12/2000	Diekhans	N/A	N/A
6216071	12/2000	Motz	N/A	N/A
6236924	12/2000	Motz et al.	N/A	N/A
6272819	12/2000	Wendte et al.	N/A	N/A
6327569	12/2000	Reep	N/A	N/A
6374173	12/2001	Ehlbeck	N/A	N/A
6380745	12/2001	Anderson et al.	N/A	N/A
6431790	12/2001	Anderegg et al.	N/A	N/A
6451733	12/2001	Pidskalny et al.	N/A	N/A
6505146	12/2002	Blackmer	N/A	N/A
6505998	12/2002	Bullivant	N/A	N/A
6539102	12/2002	Anderson et al.	N/A	N/A
6549849	12/2002	Lange et al.	N/A	N/A
6584390	12/2002	Beck	N/A	N/A
6591145	12/2002	Hoskinson et al.	N/A	N/A
6591591	12/2002	Coers et al.	N/A	N/A
6592453	12/2002	Coers et al.	N/A	N/A

6604432	12/2002	Hamblen et al.	N/A	N/A
6681551	12/2003	Sheidler et al.	N/A	N/A
6682416	12/2003	Behnke et al.	N/A	N/A
6687616	12/2003	Peterson et al.	N/A	N/A
6729189	12/2003	Paakkinen	N/A	N/A
6735568	12/2003	Buckwalter et al.	N/A	N/A
6834550	12/2003	Upadhyaya et al.	N/A	N/A
6838564	12/2004	Edmunds et al.	N/A	N/A
6846128	12/2004	Sick	N/A	N/A
6932554	12/2004	Isfort et al.	N/A	N/A
6999877	12/2005	Dyer et al.	N/A	N/A
7073374	12/2005	Berkman	N/A	N/A
7167797	12/2006	Faivre et al.	N/A	N/A
7167800	12/2006	Faivre et al.	N/A	N/A
7191062	12/2006	Chi et al.	N/A	N/A
7194965	12/2006	Hickey et al.	N/A	N/A
7211994	12/2006	Mergen et al.	N/A	N/A
7248968	12/2006	Reid	N/A	N/A
7255016	12/2006	Burton	N/A	N/A
7261632	12/2006	Pirro et al.	N/A	N/A
7302837	12/2006	Wendt	N/A	N/A
7308326	12/2006	Maertens et al.	N/A	N/A
7313478	12/2006	Anderson et al.	N/A	N/A
7318010	12/2007	Anderson	N/A	N/A
7347168	12/2007	Reckels et al.	N/A	N/A
7408145	12/2007	Holland	N/A	N/A
7480564	12/2008	Metzler et al.	N/A	N/A
7483791	12/2008	Kozan et al.	N/A	N/A
7537519	12/2008	Huster et al.	N/A	N/A
7557066	12/2008	Hills et al.	N/A	N/A
7628059	12/2008	Scherbring	N/A	N/A
7687435	12/2009	Witschel et al.	N/A	N/A
7703036	12/2009	Satterfield et al.	N/A	N/A
7725233	12/2009	Hendrickson et al.	N/A	N/A
7733416	12/2009	Gal	N/A	N/A
7756624	12/2009	Diekhans et al.	N/A	N/A
7798894	12/2009	Isfort	N/A	N/A
7827042	12/2009	Jung et al.	N/A	N/A
7915200	12/2010	Epp et al.	N/A	N/A
7945364	12/2010	Schricker et al.	N/A	N/A
7993188	12/2010	Ritter	N/A	N/A
8024074	12/2010	Stelford et al.	N/A	N/A
8060283	12/2010	Mott et al.	N/A	N/A
8107681	12/2011	Gaal	N/A	N/A
8145393	12/2011	Foster et al.	N/A	N/A
8147176	12/2011	Coers et al.	N/A	N/A
8152610	12/2011	Harrington	N/A	N/A
8190335	12/2011	Vik et al.	N/A	N/A
8195342	12/2011	Anderson	N/A	N/A
8195358	12/2011	Anderson	N/A	N/A
8213964	12/2011	Fitzner et al.	N/A	N/A
8224500	12/2011	Anderson	N/A	N/A
8252723	12/2011	Jakobi et al.	N/A	N/A
8254351	12/2011	Fitzner et al.	N/A	N/A
8321365	12/2011	Anderson	N/A	N/A
8329717	12/2011	Minn et al.	N/A	N/A
8332105	12/2011	Laux	N/A	N/A
8338332	12/2011	Hacker et al.	N/A	N/A
8340862	12/2011	Baumgarten et al.	N/A	N/A
8407157	12/2012	Anderson et al.	N/A	N/A
8428829	12/2012	Brunnert et al.	N/A	N/A
8478493	12/2012	Anderson	N/A	N/A
8488865	12/2012	Hausmann et al.	N/A	N/A
8494727	12/2012	Green et al.	N/A	N/A
8527157	12/2012	Imhof et al.	N/A	N/A
8544397	12/2012	Bassett	N/A	N/A
8577561	12/2012	Green et al.	N/A	N/A
8606454	12/2012	Wang et al.	N/A	N/A
8626406	12/2013	Schleicher et al.	N/A	N/A
8635903	12/2013	Oetken et al.	N/A	N/A
8649940	12/2013	Bonefas	N/A	N/A
8656693	12/2013	Madsen et al.	N/A	N/A
8662972	12/2013	Behnke et al.	N/A	N/A
8671760	12/2013	Wallrath et al.	N/A	N/A

8677724	12/2013	Chaney et al.	N/A	N/A
8738238	12/2013	Rekow	N/A	N/A
8738244	12/2013	Lenz	N/A	N/A
8755976	12/2013	Peters et al.	N/A	N/A
8781692	12/2013	Kormann	N/A	N/A
8789563	12/2013	Wenzel	N/A	N/A
8814640	12/2013	Behnke et al.	N/A	N/A
8843269	12/2013	Anderson et al.	N/A	N/A
8868304	12/2013	Bonefas	N/A	N/A
8909389	12/2013	Meyer	N/A	N/A
D721740	12/2014	Schmaltz et al.	N/A	N/A
8942860	12/2014	Morselli	N/A	N/A
8962523	12/2014	Rosinger et al.	N/A	N/A
8972090	12/2014	Weslati	903/930	B60W 10/26
9002591	12/2014	Wang et al.	N/A	N/A
9008918	12/2014	Missotten et al.	N/A	N/A
9009087	12/2014	Mewes et al.	N/A	N/A
9011222	12/2014	Johnson et al.	N/A	N/A
9014901	12/2014	Wang et al.	N/A	N/A
9043096	12/2014	Zielke et al.	N/A	N/A
9043129	12/2014	Bonefas et al.	N/A	N/A
9066465	12/2014	Hendrickson et al.	N/A	N/A
9072227	12/2014	Wenzel	N/A	N/A
9095090	12/2014	Casper et al.	N/A	N/A
9119342	12/2014	Bonefas	N/A	N/A
9127428	12/2014	Meier	N/A	N/A
9131644	12/2014	Osborne	N/A	N/A
9152938	12/2014	Lang et al.	N/A	N/A
9173339	12/2014	Sauder et al.	N/A	N/A
9179599	12/2014	Bischoff	N/A	N/A
9188518	12/2014	Snyder et al.	N/A	N/A
9188986	12/2014	Baumann	N/A	N/A
9226449	12/2015	Bischoff	N/A	N/A
9234317	12/2015	Chi	N/A	N/A
9235214	12/2015	Anderson	N/A	N/A
9301447	12/2015	Kormann	N/A	N/A
9301466	12/2015	Kelly	N/A	N/A
9313951	12/2015	Herman et al.	N/A	N/A
9326443	12/2015	Zametzner et al.	N/A	N/A
9326444	12/2015	Bonefas	N/A	N/A
9392746	12/2015	Darr et al.	N/A	N/A
9405039	12/2015	Anderson	N/A	N/A
9410840	12/2015	Acheson et al.	N/A	N/A
9439342	12/2015	Pasquier	N/A	N/A
9457971	12/2015	Bonefas et al.	N/A	N/A
9463939	12/2015	Bonefas et al.	N/A	N/A
9485905	12/2015	Jung et al.	N/A	N/A
9489576	12/2015	Johnson et al.	N/A	N/A
9497898	12/2015	Dillon	N/A	N/A
9510508	12/2015	Jung	N/A	N/A
9511633	12/2015	Anderson et al.	N/A	N/A
9511958	12/2015	Bonefas	N/A	N/A
9516812	12/2015	Baumgarten et al.	N/A	N/A
9521805	12/2015	Muench et al.	N/A	N/A
9522791	12/2015	Bonefas et al.	N/A	N/A
9522792	12/2015	Bonefas et al.	N/A	N/A
9523180	12/2015	Deines	N/A	N/A
9529364	12/2015	Foster et al.	N/A	N/A
9532504	12/2016	Herman et al.	N/A	N/A
9538714	12/2016	Anderson	N/A	N/A
9563492	12/2016	Bell et al.	N/A	N/A
9563848	12/2016	Hunt	N/A	N/A
9563852	12/2016	Wiles et al.	N/A	N/A
9578808	12/2016	Dybro et al.	N/A	N/A
9629308	12/2016	Schøler et al.	N/A	N/A
9631964	12/2016	Gelinske et al.	N/A	N/A
9642305	12/2016	Nykamp et al.	N/A	N/A
9648807	12/2016	Escher et al.	N/A	N/A
9675008	12/2016	Rusciolelli et al.	N/A	N/A
9681605	12/2016	Noonan et al.	N/A	N/A
9694712	12/2016	Healy	N/A	N/A
9696162	12/2016	Anderson	N/A	N/A
9699967	12/2016	Palla et al.	N/A	N/A
9714856	12/2016	Myers	N/A	N/A

9717178	12/2016	Sauder et al.	N/A	N/A
9721181	12/2016	Guan et al.	N/A	N/A
9723790	12/2016	Berry et al.	N/A	N/A
9740208	12/2016	Sugumaran et al.	N/A	N/A
9767521	12/2016	Stuber et al.	N/A	N/A
9807934	12/2016	Rusciollelli et al.	N/A	N/A
9807940	12/2016	Roell et al.	N/A	N/A
9810679	12/2016	Kimmel	N/A	N/A
9829364	12/2016	Wilson et al.	N/A	N/A
9848528	12/2016	Werner et al.	N/A	N/A
9856609	12/2017	Dehmel	N/A	N/A
9856612	12/2017	Oetken	N/A	N/A
9861040	12/2017	Bonefas	N/A	N/A
9872433	12/2017	Acheson et al.	N/A	N/A
9903077	12/2017	Rio	N/A	N/A
9903979	12/2017	Dybro et al.	N/A	N/A
9904963	12/2017	Rupp et al.	N/A	N/A
9915952	12/2017	Dollinger et al.	N/A	N/A
9922405	12/2017	Sauder et al.	N/A	N/A
9924636	12/2017	Lisouski et al.	N/A	N/A
9928584	12/2017	Jens et al.	N/A	N/A
9933787	12/2017	Story	N/A	N/A
9974226	12/2017	Rupp et al.	N/A	N/A
9982397	12/2017	Korb et al.	N/A	N/A
9984455	12/2017	Fox et al.	N/A	N/A
9992931	12/2017	Bonefas et al.	N/A	N/A
9992932	12/2017	Bonefas et al.	N/A	N/A
10004176	12/2017	Mayerle	N/A	N/A
10015928	12/2017	Nykamp et al.	N/A	N/A
10019018	12/2017	Hulin	N/A	N/A
10019790	12/2017	Bonefas et al.	N/A	N/A
10025983	12/2017	Guan et al.	N/A	N/A
10028435	12/2017	Anderson et al.	N/A	N/A
10028451	12/2017	Rowan et al.	N/A	N/A
10034427	12/2017	Krause et al.	N/A	N/A
10039231	12/2017	Anderson et al.	N/A	N/A
10053100	12/2017	Foster	N/A	B60W 10/119
10064331	12/2017	Bradley	N/A	N/A
10064335	12/2017	Byttebier et al.	N/A	N/A
10078890	12/2017	Tagestad et al.	N/A	N/A
10085372	12/2017	Noyer et al.	N/A	N/A
10091925	12/2017	Aharoni et al.	N/A	N/A
10126153	12/2017	Bischoff et al.	N/A	N/A
10129528	12/2017	Bonefas et al.	N/A	N/A
10143132	12/2017	Inoue et al.	N/A	N/A
10152035	12/2017	Reid et al.	N/A	N/A
10154624	12/2017	Guan et al.	N/A	N/A
10165725	12/2018	Sugumaran et al.	N/A	N/A
10178823	12/2018	Kovach et al.	N/A	N/A
10183667	12/2018	Anderson et al.	N/A	N/A
10188037	12/2018	Bruns et al.	N/A	N/A
10201121	12/2018	Wilson	N/A	N/A
10209179	12/2018	Hollstein	N/A	N/A
10231371	12/2018	Dillon	N/A	N/A
10254147	12/2018	Vermue et al.	N/A	N/A
10254765	12/2018	Rekow	N/A	N/A
10255670	12/2018	Wu et al.	N/A	N/A
10275550	12/2018	Lee	N/A	N/A
10295703	12/2018	Dybro et al.	N/A	N/A
10310455	12/2018	Blank et al.	N/A	N/A
10314232	12/2018	Isaac et al.	N/A	N/A
10315655	12/2018	Blank et al.	N/A	N/A
10317272	12/2018	Bhavsar et al.	N/A	N/A
10351364	12/2018	Green et al.	N/A	N/A
10368488	12/2018	Becker et al.	N/A	N/A
10398084	12/2018	Ray et al.	N/A	N/A
10408545	12/2018	Blank et al.	N/A	N/A
10412889	12/2018	Palla et al.	N/A	N/A
10426086	12/2018	Van de Wege et al.	N/A	N/A
10437243	12/2018	Blank et al.	N/A	N/A
10464547	12/2018	Park	N/A	B60W 20/40
10477756	12/2018	Richt et al.	N/A	N/A
10485178	12/2018	Mayerle	N/A	N/A
10521526	12/2018	Haaland et al.	N/A	N/A

10537061	12/2019	Farley et al.	N/A	N/A
10568316	12/2019	Gall et al.	N/A	N/A
10631462	12/2019	Bonefas	N/A	N/A
10677637	12/2019	Von Muenster	N/A	N/A
10681872	12/2019	Viaene et al.	N/A	N/A
10703277	12/2019	Schroeder	N/A	N/A
10729067	12/2019	Hammer et al.	N/A	N/A
10740703	12/2019	Story	N/A	N/A
10745868	12/2019	Laugwitz et al.	N/A	N/A
10760946	12/2019	Meier et al.	N/A	N/A
10809118	12/2019	Von Muenster	N/A	N/A
10813288	12/2019	Laugen	N/A	A01D 57/20
10830634	12/2019	Blank et al.	N/A	N/A
10866109	12/2019	Madsen et al.	N/A	N/A
10890922	12/2020	Ramm et al.	N/A	N/A
10909368	12/2020	Guo et al.	N/A	N/A
10912249	12/2020	Wilson	N/A	N/A
11140813	12/2020	Morrison	N/A	G06N 20/00
11574465	12/2022	Chen	N/A	G06N 20/00
11908025	12/2023	Nissing	N/A	G06N 20/00
2002/0011061	12/2001	Lucand et al.	N/A	N/A
2002/0083695	12/2001	Behnke et al.	N/A	N/A
2002/0091458	12/2001	Moore	N/A	N/A
2002/0099471	12/2001	Benneweis	N/A	N/A
2002/0133309	12/2001	Hardt	N/A	N/A
2002/0173893	12/2001	Blackmore et al.	N/A	N/A
2002/0193928	12/2001	Beck	N/A	N/A
2002/0193929	12/2001	Beck	N/A	N/A
2002/0198654	12/2001	Lange et al.	N/A	N/A
2003/0004630	12/2002	Beck	N/A	N/A
2003/0014171	12/2002	Ma et al.	N/A	N/A
2003/0015351	12/2002	Goldman et al.	N/A	N/A
2003/0024450	12/2002	Juptner	N/A	N/A
2003/0060245	12/2002	Coers et al.	N/A	N/A
2003/0069680	12/2002	Cohen et al.	N/A	N/A
2003/0075145	12/2002	Sheidler et al.	N/A	N/A
2003/0174207	12/2002	Alexia et al.	N/A	N/A
2003/0182144	12/2002	Pickett et al.	N/A	N/A
2003/0187560	12/2002	Keller et al.	N/A	N/A
2003/0216158	12/2002	Bischoff	N/A	N/A
2003/0229432	12/2002	Ho et al.	N/A	N/A
2003/0229433	12/2002	van den Berg et al.	N/A	N/A
2003/0229435	12/2002	Van der Lely	N/A	N/A
2004/0004544	12/2003	William Knutson	N/A	N/A
2004/0054457	12/2003	Kormann	N/A	N/A
2004/0073468	12/2003	Vyas et al.	N/A	N/A
2004/0193348	12/2003	Gray et al.	N/A	N/A
2005/0059445	12/2004	Niermann et al.	N/A	N/A
2005/0066738	12/2004	Moore	N/A	N/A
2005/0149235	12/2004	Seal et al.	N/A	N/A
2005/0150202	12/2004	Quick	N/A	N/A
2005/0197175	12/2004	Anderson	N/A	N/A
2005/0241285	12/2004	Maertens et al.	N/A	N/A
2005/0283314	12/2004	Hall	N/A	N/A
2005/0284119	12/2004	Brunnert	N/A	N/A
2006/0014489	12/2005	Fitzner et al.	N/A	N/A
2006/0014643	12/2005	Hacker et al.	N/A	N/A
2006/0047377	12/2005	Ferguson et al.	N/A	N/A
2006/0058896	12/2005	Pokorny et al.	N/A	N/A
2006/0074560	12/2005	Dyer et al.	N/A	N/A
2006/0155449	12/2005	Dammann	N/A	N/A
2006/0162631	12/2005	Hickey et al.	N/A	N/A
2006/0196158	12/2005	Faivre et al.	N/A	N/A
2006/0200334	12/2005	Faivre et al.	N/A	N/A
2007/0005209	12/2006	Fitzner et al.	N/A	N/A
2007/0021948	12/2006	Anderson	N/A	N/A
2007/0056258	12/2006	Behnke	N/A	N/A
2007/0068238	12/2006	Wendte	N/A	N/A
2007/0073700	12/2006	Wippersteg et al.	N/A	N/A
2007/0089390	12/2006	Hendrickson et al.	N/A	N/A
2007/0135190	12/2006	Diekhans et al.	N/A	N/A
2007/0185749	12/2006	Anderson et al.	N/A	N/A
2007/0199903	12/2006	Denney	N/A	N/A
2007/0208510	12/2006	Anderson et al.	N/A	N/A

2007/0233348	12/2006	Diekhans et al.	N/A	N/A
2007/0233374	12/2006	Diekhans et al.	N/A	N/A
2007/0239337	12/2006	Anderson	N/A	N/A
2007/0282523	12/2006	Diekhans et al.	N/A	N/A
2007/0298744	12/2006	Fitzner et al.	N/A	N/A
2008/0030320	12/2007	Wilcox et al.	N/A	N/A
2008/0063473	12/2007	Congdon	404/75	E01C 19/288
2008/0098035	12/2007	Wippersteg et al.	N/A	N/A
2008/0140431	12/2007	Anderson et al.	N/A	N/A
2008/0177449	12/2007	Pickett et al.	N/A	N/A
2008/0248843	12/2007	Birrell et al.	N/A	N/A
2008/0268927	12/2007	Farley et al.	N/A	N/A
2008/0269052	12/2007	Rosinger et al.	N/A	N/A
2008/0289308	12/2007	Brubaker	N/A	N/A
2008/0312085	12/2007	Kordes et al.	N/A	N/A
2009/0044505	12/2008	Huster et al.	N/A	N/A
2009/0074243	12/2008	Missotten et al.	N/A	N/A
2009/0143941	12/2008	Tarasinski et al.	N/A	N/A
2009/0192654	12/2008	Wendte et al.	N/A	N/A
2009/0216410	12/2008	Allen et al.	N/A	N/A
2009/0226036	12/2008	Gaal	N/A	N/A
2009/0259483	12/2008	Hendrickson et al.	N/A	N/A
2009/0265098	12/2008	Dix	N/A	N/A
2009/0306835	12/2008	Ellermann et al.	N/A	N/A
2009/0311084	12/2008	Coers et al.	N/A	N/A
2009/0312919	12/2008	Foster et al.	N/A	N/A
2009/0312920	12/2008	Boenig et al.	N/A	N/A
2009/0325658	12/2008	Phelan et al.	N/A	N/A
2010/0036696	12/2009	Lang et al.	N/A	N/A
2010/0042297	12/2009	Foster et al.	N/A	N/A
2010/0063626	12/2009	Anderson	N/A	N/A
2010/0063648	12/2009	Anderson	N/A	N/A
2010/0063651	12/2009	Anderson	N/A	N/A
2010/0063664	12/2009	Anderson	N/A	N/A
2010/0063954	12/2009	Anderson	N/A	N/A
2010/0070145	12/2009	Foster et al.	N/A	N/A
2010/0071329	12/2009	Hindryckx et al.	N/A	N/A
2010/0094481	12/2009	Anderson	N/A	N/A
2010/0121541	12/2009	Behnke et al.	N/A	N/A
2010/0137373	12/2009	Hungenberg et al.	N/A	N/A
2010/0145572	12/2009	Steckel et al.	N/A	N/A
2010/0152270	12/2009	Suty-Heinze et al.	N/A	N/A
2010/0152943	12/2009	Matthews	N/A	N/A
2010/0217474	12/2009	Baumgarten et al.	N/A	N/A
2010/0268562	12/2009	Anderson	N/A	N/A
2010/0268679	12/2009	Anderson	N/A	N/A
2010/0285964	12/2009	Waldrapp et al.	N/A	N/A
2010/0317517	12/2009	Rosinger et al.	N/A	N/A
2010/0319941	12/2009	Peterson	N/A	N/A
2010/0332051	12/2009	Kormann	N/A	N/A
2011/0056178	12/2010	Sauerwein et al.	N/A	N/A
2011/0059782	12/2010	Harrington	N/A	N/A
2011/0072773	12/2010	Schroeder et al.	N/A	N/A
2011/0084851	12/2010	Peterson et al.	N/A	N/A
2011/0086684	12/2010	Luellen et al.	N/A	N/A
2011/0160961	12/2010	Wollenhaupt et al.	N/A	N/A
2011/0213531	12/2010	Farley et al.	N/A	N/A
2011/0224873	12/2010	Reeve et al.	N/A	N/A
2011/0227745	12/2010	Kikuchi et al.	N/A	N/A
2011/0257850	12/2010	Reeve et al.	N/A	N/A
2011/0270494	12/2010	Imhof et al.	N/A	N/A
2011/0270495	12/2010	Knapp	N/A	N/A
2011/0295460	12/2010	Hunt et al.	N/A	N/A
2011/0307149	12/2010	Pighi	N/A	N/A
2012/0004813	12/2011	Baumgarten et al.	N/A	N/A
2012/0029732	12/2011	Meyer	N/A	N/A
2012/0087771	12/2011	Wenzel	N/A	N/A
2012/0096827	12/2011	Chaney et al.	N/A	N/A
2012/0143642	12/2011	O'Neil	N/A	N/A
2012/0215378	12/2011	Sprock et al.	N/A	N/A
2012/0215379	12/2011	Sprock et al.	N/A	N/A
2012/0253611	12/2011	Zielke et al.	N/A	N/A
2012/0263560	12/2011	Diekhans et al.	N/A	N/A
2012/0265412	12/2011	Diekhans et al.	N/A	N/A

2012/0271489	12/2011	Roberts et al.	N/A	N/A
2012/0323452	12/2011	Green et al.	N/A	N/A
2013/0019580	12/2012	Anderson et al.	N/A	N/A
2013/0022430	12/2012	Anderson et al.	N/A	N/A
2013/0046419	12/2012	Anderson et al.	N/A	N/A
2013/0046439	12/2012	Anderson et al.	N/A	N/A
2013/0046525	12/2012	Ali et al.	N/A	N/A
2013/0103269	12/2012	Meyer Zu Helligen et al.	N/A	N/A
2013/0124239	12/2012	Rosa et al.	N/A	N/A
2013/0184944	12/2012	Missotten et al.	N/A	N/A
2013/0197767	12/2012	Lenz	N/A	N/A
2013/0205733	12/2012	Peters et al.	N/A	N/A
2013/0210505	12/2012	Bischoff	N/A	N/A
2013/0231823	12/2012	Wang et al.	N/A	N/A
2013/0319941	12/2012	Schneider	N/A	N/A
2013/0325242	12/2012	Cavender-Bares et al.	N/A	N/A
2013/0332003	12/2012	Murray et al.	N/A	N/A
2014/0002489	12/2013	Sauder et al.	N/A	N/A
2014/0019017	12/2013	Wilken et al.	N/A	N/A
2014/0021598	12/2013	Sutardja	N/A	N/A
2014/0050364	12/2013	Brueckner et al.	N/A	N/A
2014/0067745	12/2013	Avey	N/A	N/A
2014/0121882	12/2013	Gilmore et al.	N/A	N/A
2014/0129048	12/2013	Baumgarten et al.	N/A	N/A
2014/0172222	12/2013	Nickel	N/A	N/A
2014/0172224	12/2013	Matthews et al.	N/A	N/A
2014/0172225	12/2013	Matthews et al.	N/A	N/A
2014/0208870	12/2013	Quaderer et al.	N/A	N/A
2014/0215984	12/2013	Bischoff	N/A	N/A
2014/0230391	12/2013	Hendrickson et al.	N/A	N/A
2014/0230392	12/2013	Dybro et al.	N/A	N/A
2014/0236381	12/2013	Anderson et al.	N/A	N/A
2014/0236431	12/2013	Hendrickson et al.	N/A	N/A
2014/0257911	12/2013	Anderson	N/A	N/A
2014/0262547	12/2013	Acheson et al.	N/A	N/A
2014/0277960	12/2013	Blank et al.	N/A	N/A
2014/0297242	12/2013	Sauder et al.	N/A	N/A
2014/0303814	12/2013	Burema et al.	N/A	N/A
2014/0324272	12/2013	Madsen et al.	N/A	N/A
2014/0331631	12/2013	Sauder et al.	N/A	N/A
2014/0338298	12/2013	Jung et al.	N/A	N/A
2014/0350802	12/2013	Biggerstaff et al.	N/A	N/A
2014/0360148	12/2013	Wienker et al.	N/A	N/A
2015/0049088	12/2014	Snyder et al.	N/A	N/A
2015/0088785	12/2014	Chi	N/A	N/A
2015/0095830	12/2014	Massoumi et al.	N/A	N/A
2015/0101519	12/2014	Blackwell et al.	N/A	N/A
2015/0105984	12/2014	Birrell et al.	N/A	N/A
2015/0124054	12/2014	Darr et al.	N/A	N/A
2015/0168187	12/2014	Myers	N/A	N/A
2015/0211199	12/2014	Corcoran et al.	N/A	N/A
2015/0230403	12/2014	Jung et al.	N/A	N/A
2015/0242799	12/2014	Seki et al.	N/A	N/A
2015/0243114	12/2014	Tanabe et al.	N/A	N/A
2015/0254800	12/2014	Johnson et al.	N/A	N/A
2015/0264863	12/2014	Muench et al.	N/A	N/A
2015/0276794	12/2014	Pistrol et al.	N/A	N/A
2015/0278640	12/2014	Johnson et al.	N/A	N/A
2015/0285647	12/2014	Meyer zu Helligen et al.	N/A	N/A
2015/0293029	12/2014	Acheson et al.	N/A	N/A
2015/0302305	12/2014	Rupp et al.	N/A	N/A
2015/0305238	12/2014	Klausmann et al.	N/A	N/A
2015/0305239	12/2014	Jung	N/A	N/A
2015/0327440	12/2014	Dybro et al.	N/A	N/A
2015/0351320	12/2014	Takahara et al.	N/A	N/A
2015/0370935	12/2014	Starr	N/A	N/A
2015/0373902	12/2014	Pasquier	N/A	N/A
2015/0379785	12/2014	Brown,, Jr. et al.	N/A	N/A
2016/0025531	12/2015	Bischoff et al.	N/A	N/A
2016/0029558	12/2015	Dybro et al.	N/A	N/A
2016/0052525	12/2015	Tuncer et al.	N/A	N/A
2016/0057922	12/2015	Freiberg et al.	N/A	N/A
2016/0066505	12/2015	Bakke et al.	N/A	N/A
2016/0073573	12/2015	Ethington et al.	N/A	N/A

2016/0078375	12/2015	Ethington et al.	N/A	N/A
2016/0078570	12/2015	Ethington et al.	N/A	N/A
2016/0084813	12/2015	Anderson et al.	N/A	N/A
2016/0088794	12/2015	Baumgarten et al.	N/A	N/A
2016/0106038	12/2015	Boyd et al.	N/A	N/A
2016/0146611	12/2015	Matthews	N/A	N/A
2016/0202227	12/2015	Mathur et al.	N/A	N/A
2016/0203657	12/2015	Bell et al.	N/A	N/A
2016/0212939	12/2015	Ouchida et al.	N/A	N/A
2016/0215994	12/2015	Mewes et al.	N/A	N/A
2016/0232621	12/2015	Ethington et al.	N/A	N/A
2016/0247075	12/2015	Mewes et al.	N/A	N/A
2016/0247082	12/2015	Stehling	N/A	N/A
2016/0260021	12/2015	Marek	N/A	N/A
2016/0286720	12/2015	Heitmann et al.	N/A	N/A
2016/0286721	12/2015	Heitmann et al.	N/A	N/A
2016/0286722	12/2015	Heitmann et al.	N/A	N/A
2016/0309656	12/2015	Wilken et al.	N/A	N/A
2016/0327535	12/2015	Cotton et al.	N/A	N/A
2016/0330906	12/2015	Acheson et al.	N/A	N/A
2016/0338267	12/2015	Anderson et al.	N/A	N/A
2016/0342915	12/2015	Humphrey	N/A	N/A
2016/0345485	12/2015	Acheson et al.	N/A	N/A
2016/0360697	12/2015	Diaz	N/A	N/A
2017/0013773	12/2016	Kirk et al.	N/A	N/A
2017/0031365	12/2016	Sugumaran et al.	N/A	N/A
2017/0034997	12/2016	Mayerle	N/A	N/A
2017/0049045	12/2016	Wilken et al.	N/A	N/A
2017/0055433	12/2016	Jamison	N/A	N/A
2017/0082442	12/2016	Anderson	N/A	N/A
2017/0083024	12/2016	Reijersen Van Buuren	N/A	N/A
2017/0086381	12/2016	Roell et al.	N/A	N/A
2017/0089741	12/2016	Takahashi et al.	N/A	N/A
2017/0089742	12/2016	Bruns et al.	N/A	N/A
2017/0090068	12/2016	Xiang et al.	N/A	N/A
2017/0105331	12/2016	Herlitzius et al.	N/A	N/A
2017/0105335	12/2016	Xu et al.	N/A	N/A
2017/0112049	12/2016	Weisberg et al.	N/A	N/A
2017/0112061	12/2016	Meyer	N/A	N/A
2017/0115862	12/2016	Stratton et al.	N/A	N/A
2017/0118915	12/2016	Middelberg et al.	N/A	N/A
2017/0124463	12/2016	Chen et al.	N/A	N/A
2017/0127606	12/2016	Horton	N/A	N/A
2017/0160916	12/2016	Baumgarten et al.	N/A	N/A
2017/0161627	12/2016	Xu et al.	N/A	N/A
2017/0185086	12/2016	Sauder et al.	N/A	N/A
2017/0188515	12/2016	Baumgarten et al.	N/A	N/A
2017/0192431	12/2016	Foster et al.	N/A	N/A
2017/0208742	12/2016	Ingibergsson et al.	N/A	N/A
2017/0213141	12/2016	Xu et al.	N/A	N/A
2017/0215330	12/2016	Missotten et al.	N/A	N/A
2017/0223947	12/2016	Gall et al.	N/A	N/A
2017/0227969	12/2016	Murray et al.	N/A	N/A
2017/0235471	12/2016	Scholer et al.	N/A	N/A
2017/0245434	12/2016	Jung et al.	N/A	N/A
2017/0251600	12/2016	Anderson et al.	N/A	N/A
2017/0270446	12/2016	Starr et al.	N/A	N/A
2017/0270616	12/2016	Basso	N/A	N/A
2017/0316692	12/2016	Rusciollelli et al.	N/A	N/A
2017/0318743	12/2016	Sauder et al.	N/A	N/A
2017/0322550	12/2016	Yokoyama	N/A	N/A
2017/0332551	12/2016	Todd et al.	N/A	N/A
2017/0336787	12/2016	Pichlmaier et al.	N/A	N/A
2017/0370765	12/2016	Meier et al.	N/A	N/A
2018/0000011	12/2017	Schleusner et al.	N/A	N/A
2018/0014452	12/2017	Starr	N/A	N/A
2018/0022559	12/2017	Knutson	N/A	N/A
2018/0024549	12/2017	Hurd	N/A	N/A
2018/0035622	12/2017	Gresch et al.	N/A	N/A
2018/0054955	12/2017	Oliver	N/A	N/A
2018/0060975	12/2017	Hassanzadeh	N/A	N/A
2018/0070534	12/2017	Mayerle	N/A	N/A
2018/0077865	12/2017	Gallmeier	N/A	N/A
2018/0084709	12/2017	Wieckhorst et al.	N/A	N/A

2018/0084722	12/2017	Wieckhorst et al.	N/A	N/A
2018/0092301	12/2017	Vandike et al.	N/A	N/A
2018/0092302	12/2017	Vandike et al.	N/A	N/A
2018/0108123	12/2017	Baurer et al.	N/A	N/A
2018/0120133	12/2017	Blank et al.	N/A	N/A
2018/0121821	12/2017	Parsons et al.	N/A	N/A
2018/0124992	12/2017	Koch et al.	N/A	N/A
2018/0128933	12/2017	Koch et al.	N/A	N/A
2018/0129879	12/2017	Achtelik et al.	N/A	N/A
2018/0132422	12/2017	Hassanzadeh et al.	N/A	N/A
2018/0136664	12/2017	Tomita et al.	N/A	N/A
2018/0146612	12/2017	Sauder et al.	N/A	N/A
2018/0146624	12/2017	Chen et al.	N/A	N/A
2018/0153084	12/2017	Calleija et al.	N/A	N/A
2018/0177125	12/2017	Takahara et al.	N/A	N/A
2018/0181893	12/2017	Basso	N/A	N/A
2018/0196438	12/2017	Newlin et al.	N/A	N/A
2018/0196441	12/2017	Muench et al.	N/A	N/A
2018/0211156	12/2017	Guan et al.	N/A	N/A
2018/0232674	12/2017	Bilde	N/A	N/A
2018/0242523	12/2017	Kirchbeck et al.	N/A	N/A
2018/0249641	12/2017	Lewis et al.	N/A	N/A
2018/0257657	12/2017	Blank et al.	N/A	N/A
2018/0271015	12/2017	Redden et al.	N/A	N/A
2018/0271016	12/2017	Milano	N/A	A01D 33/14
2018/0279599	12/2017	Struve	N/A	N/A
2018/0295771	12/2017	Peters	N/A	N/A
2018/0310474	12/2017	Posselius et al.	N/A	N/A
2018/0317381	12/2017	Bassett	N/A	N/A
2018/0317385	12/2017	Wellensiek et al.	N/A	N/A
2018/0325012	12/2017	Ferrari et al.	N/A	N/A
2018/0325014	12/2017	Debbaut	N/A	N/A
2018/0332767	12/2017	Muench et al.	N/A	N/A
2018/0338422	12/2017	Brubaker	N/A	N/A
2018/0340845	12/2017	Rhodes et al.	N/A	N/A
2018/0359917	12/2017	Blank et al.	N/A	N/A
2018/0359919	12/2017	Blank et al.	N/A	N/A
2018/0364726	12/2017	Foster et al.	N/A	N/A
2019/0021226	12/2018	Dima et al.	N/A	N/A
2019/0025175	12/2018	Laugwitz	N/A	N/A
2019/0041813	12/2018	Horn et al.	N/A	N/A
2019/0050948	12/2018	Perry et al.	N/A	N/A
2019/0057460	12/2018	Sakaguchi et al.	N/A	N/A
2019/0066234	12/2018	Bedoya et al.	N/A	N/A
2019/0069470	12/2018	Pfeiffer	N/A	A01B 79/005
2019/0075727	12/2018	Duke et al.	N/A	N/A
2019/0085785	12/2018	Abolt	N/A	N/A
2019/0090423	12/2018	Escher et al.	N/A	N/A
2019/0098825	12/2018	Neitemeier et al.	N/A	N/A
2019/0104722	12/2018	Slaughter et al.	N/A	N/A
2019/0108413	12/2018	Chen et al.	N/A	N/A
2019/0114847	12/2018	Wagner et al.	N/A	N/A
2019/0124819	12/2018	Madsen et al.	N/A	N/A
2019/0129430	12/2018	Madsen et al.	N/A	N/A
2019/0136491	12/2018	Martin	N/A	N/A
2019/0138962	12/2018	Ehlmann et al.	N/A	N/A
2019/0147094	12/2018	Zhan et al.	N/A	N/A
2019/0147249	12/2018	Kiepe et al.	N/A	N/A
2019/0156255	12/2018	Carroll	N/A	N/A
2019/0174667	12/2018	Gresch et al.	N/A	N/A
2019/0183047	12/2018	Dybro et al.	N/A	N/A
2019/0200522	12/2018	Hansen et al.	N/A	N/A
2019/0230855	12/2018	Reed et al.	N/A	N/A
2019/0239416	12/2018	Green et al.	N/A	N/A
2019/0261550	12/2018	Damme et al.	N/A	N/A
2019/0261559	12/2018	Heitmann et al.	N/A	N/A
2019/0261560	12/2018	Jelenkovic	N/A	N/A
2019/0313570	12/2018	Owechko	N/A	N/A
2019/0327889	12/2018	Borgstadt	N/A	N/A
2019/0327892	12/2018	Fries et al.	N/A	N/A
2019/0335662	12/2018	Good et al.	N/A	N/A
2019/0335674	12/2018	Basso	N/A	N/A
2019/0343035	12/2018	Smith et al.	N/A	N/A
2019/0343043	12/2018	Bormann et al.	N/A	N/A

2019/0343044	12/2018	Bormann et al.	N/A	N/A
2019/0343048	12/2018	Farley et al.	N/A	N/A
2019/0351765	12/2018	Rabusic	N/A	N/A
2019/0354081	12/2018	Blank et al.	N/A	N/A
2019/0364733	12/2018	Laugen et al.	N/A	N/A
2019/0364734	12/2018	Kriebel et al.	N/A	N/A
2020/0000006	12/2019	McDonald et al.	N/A	N/A
2020/0008351	12/2019	Zielke et al.	N/A	N/A
2020/0015416	12/2019	Barther et al.	N/A	N/A
2020/0019159	12/2019	Kocer et al.	N/A	N/A
2020/0024102	12/2019	Brill et al.	N/A	N/A
2020/0029488	12/2019	Bertucci et al.	N/A	N/A
2020/0034759	12/2019	Dumstorff et al.	N/A	N/A
2020/0037491	12/2019	Schoeny et al.	N/A	N/A
2020/0053961	12/2019	Dix et al.	N/A	N/A
2020/0064144	12/2019	Tomita et al.	N/A	N/A
2020/0064863	12/2019	Tomita et al.	N/A	N/A
2020/0074023	12/2019	Nizami et al.	N/A	N/A
2020/0084963	12/2019	Gururajan et al.	N/A	N/A
2020/0084966	12/2019	Corban et al.	N/A	N/A
2020/0090094	12/2019	Blank	N/A	N/A
2020/0097851	12/2019	Alvarez et al.	N/A	N/A
2020/0113142	12/2019	Coleman et al.	N/A	N/A
2020/0125822	12/2019	Yang et al.	N/A	N/A
2020/0128732	12/2019	Chaney	N/A	N/A
2020/0128733	12/2019	Vandike et al.	N/A	N/A
2020/0128734	12/2019	Brammeier et al.	N/A	N/A
2020/0128735	12/2019	Bonefas et al.	N/A	N/A
2020/0128737	12/2019	Anderson et al.	N/A	N/A
2020/0128738	12/2019	Suleman et al.	N/A	N/A
2020/0128740	12/2019	Suleman	N/A	N/A
2020/0133262	12/2019	Suleman et al.	N/A	N/A
2020/0141784	12/2019	Lange et al.	N/A	N/A
2020/0146203	12/2019	Deng	N/A	N/A
2020/0150631	12/2019	Friberg et al.	N/A	N/A
2020/0154639	12/2019	Takahara et al.	N/A	N/A
2020/0163277	12/2019	Cooksey et al.	N/A	N/A
2020/0183406	12/2019	Borgstadt	N/A	N/A
2020/0187409	12/2019	Meyer Zu Helligen	N/A	N/A
2020/0196526	12/2019	Koch et al.	N/A	N/A
2020/0202596	12/2019	Kitahara et al.	N/A	N/A
2020/0221632	12/2019	Strnad et al.	N/A	N/A
2020/0221635	12/2019	Hendrickson et al.	N/A	N/A
2020/0221636	12/2019	Boydens et al.	N/A	N/A
2020/0265527	12/2019	Rose et al.	N/A	N/A
2020/0278680	12/2019	Schultz et al.	N/A	N/A
2020/0317114	12/2019	Hoff	N/A	N/A
2020/0319632	12/2019	Desai et al.	N/A	N/A
2020/0319655	12/2019	Desai et al.	N/A	N/A
2020/0323133	12/2019	Anderson et al.	N/A	N/A
2020/0323134	12/2019	Darr et al.	N/A	N/A
2020/0326674	12/2019	Palla et al.	N/A	N/A
2020/0326727	12/2019	Palla et al.	N/A	N/A
2020/0333278	12/2019	Locken et al.	N/A	N/A
2020/0337232	12/2019	Blank et al.	N/A	N/A
2020/0352099	12/2019	Meier et al.	N/A	N/A
2020/0359547	12/2019	Sakaguchi et al.	N/A	N/A
2020/0359549	12/2019	Sakaguchi et al.	N/A	N/A
2020/0363256	12/2019	Meier et al.	N/A	N/A
2020/0375083	12/2019	Anderson et al.	N/A	N/A
2020/0375084	12/2019	Sakaguchi et al.	N/A	N/A
2020/0378088	12/2019	Anderson	N/A	N/A
2020/0404842	12/2019	Dugas et al.	N/A	N/A
2021/0015041	12/2020	Bormann et al.	N/A	N/A
2021/0129853	12/2020	Appleton et al.	N/A	N/A
2021/0176916	12/2020	Sidon et al.	N/A	N/A
2021/0176918	12/2020	Franzen et al.	N/A	N/A
2021/0289687	12/2020	Heinold et al.	N/A	N/A
2021/0321567	12/2020	Sidon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108898	12/2017	AR	N/A
20100224431	12/2010	AU	N/A
MU6800140	12/1988	BR	N/A

PI0502658	12/2006	BR	N/A
PI0802384	12/2009	BR	N/A
PI1100258	12/2013	BR	N/A
102014007178	12/2015	BR	N/A
1165300	12/1983	CA	N/A
2283767	12/2000	CA	N/A
2330979	12/2000	CA	N/A
2629555	12/2008	CA	N/A
135611	12/2010	CA	N/A
2451633	12/2000	CN	N/A
101236188	12/2007	CN	N/A
100416590	12/2007	CN	N/A
101303338	12/2007	CN	N/A
101363833	12/2008	CN	N/A
201218789	12/2008	CN	N/A
101839906	12/2009	CN	N/A
101929166	12/2009	CN	N/A
102080373	12/2010	CN	N/A
102138383	12/2010	CN	N/A
102277867	12/2010	CN	N/A
202110103	12/2011	CN	N/A
202119772	12/2011	CN	N/A
202340435	12/2011	CN	N/A
103088807	12/2012	CN	N/A
103181263	12/2012	CN	N/A
203053961	12/2012	CN	N/A
203055121	12/2012	CN	N/A
203206739	12/2012	CN	N/A
203275401	12/2012	CN	N/A
203613525	12/2013	CN	N/A
203658201	12/2013	CN	N/A
103954738	12/2013	CN	N/A
203741803	12/2013	CN	N/A
204000818	12/2013	CN	N/A
204435344	12/2014	CN	N/A
204475304	12/2014	CN	N/A
105205248	12/2014	CN	N/A
204989174	12/2015	CN	N/A
105432228	12/2015	CN	N/A
105741180	12/2015	CN	N/A
106053330	12/2015	CN	N/A
106198877	12/2015	CN	N/A
106198879	12/2015	CN	N/A
106226470	12/2015	CN	N/A
106248873	12/2015	CN	N/A
106290800	12/2016	CN	N/A
106327349	12/2016	CN	N/A
106644663	12/2016	CN	N/A
206330815	12/2016	CN	N/A
206515118	12/2016	CN	N/A
206515119	12/2016	CN	N/A
206616118	12/2016	CN	N/A
206696107	12/2016	CN	N/A
206696107	12/2016	CN	N/A
107576674	12/2017	CN	N/A
107576674	12/2017	CN	N/A
206906093	12/2017	CN	N/A
206941558	12/2017	CN	N/A
206941558	12/2017	CN	N/A
107736088	12/2017	CN	N/A
107795095	12/2017	CN	N/A
207079558	12/2017	CN	N/A
107941286	12/2017	CN	N/A
107957408	12/2017	CN	N/A
108009542	12/2017	CN	N/A
108304796	12/2017	CN	N/A
207567744	12/2017	CN	N/A
108614089	12/2017	CN	N/A
208013131	12/2017	CN	N/A
108881825	12/2017	CN	N/A
208047351	12/2017	CN	N/A
109357804	12/2018	CN	N/A
109485353	12/2018	CN	N/A
109633127	12/2018	CN	N/A

109763476	12/2018	CN	N/A
109961024	12/2018	CN	N/A
110262287	12/2018	CN	N/A
110720302	12/2019	CN	N/A
111201879	12/2019	CN	N/A
210585958	12/2019	CN	N/A
111406505	12/2019	CN	N/A
247426	12/1985	CS	N/A
248318	12/1986	CS	N/A
17266	12/2006	CZ	N/A
20252	12/2008	CZ	N/A
4415970	12/1926	DE	N/A
504035	12/1929	DE	N/A
2354828	12/1974	DE	N/A
152380	12/1980	DE	N/A
3728669	12/1988	DE	N/A
4431824	12/1995	DE	N/A
19509496	12/1995	DE	N/A
19528663	12/1996	DE	N/A
19718455	12/1996	DE	N/A
19705842	12/1997	DE	N/A
19828355	12/1999	DE	N/A
10050224	12/2001	DE	N/A
10120173	12/2001	DE	N/A
202004015141	12/2003	DE	N/A
102005000770	12/2005	DE	N/A
102005000771	12/2005	DE	N/A
102008021785	12/2008	DE	N/A
102009041646	12/2010	DE	N/A
102010004648	12/2010	DE	N/A
102010038661	12/2011	DE	N/A
102011005400	12/2011	DE	N/A
202012103730	12/2011	DE	N/A
102011052688	12/2012	DE	N/A
102012211001	12/2013	DE	N/A
102012220109 2	12/2013	DE	N/A
102012223768	12/2013	DE	N/A
102013212151	12/2013	DE	N/A
102013019098	12/2014	DE	N/A
102014108449	12/2014	DE	N/A
2014201203	12/2014	DE	N/A
102014208068	12/2014	DE	N/A
102015006398	12/2015	DE	N/A
102015109799	12/2015	DE	N/A
112015002194	12/2016	DE	N/A
102017204511	12/2017	DE	N/A
102019206734	12/2019	DE	N/A
102019114872	12/2019	DE	N/A
0070219	12/1983	EP	N/A
0355049	12/1989	EP	N/A
0532146	12/1997	EP	N/A
1444879	12/2003	EP	N/A
1219159	12/2004	EP	N/A
1219153	12/2005	EP	N/A
1692928	12/2005	EP	N/A
1574122	12/2007	EP	N/A
1943877	12/2007	EP	N/A
1598586	12/2008	EP	N/A
1731983	12/2008	EP	N/A
2146307	12/2009	EP	N/A
0845198	12/2009	EP	N/A
2186389	12/2009	EP	N/A
2267566	12/2009	EP	N/A
3491192	12/2009	EP	N/A
2057884	12/2010	EP	N/A
2146307	12/2011	EP	N/A
2446732	12/2011	EP	N/A
2524586	12/2011	EP	N/A
2529610	12/2011	EP	N/A
2243353	12/2012	EP	N/A
2174537	12/2012	EP	N/A
2592919	12/2012	EP	N/A
1674324	12/2013	EP	N/A
2759829	12/2013	EP	N/A

2764764	12/2013	EP	N/A
2267566	12/2013	EP	N/A
2191439	12/2014	EP	N/A
2586286	12/2014	EP	N/A
2592919	12/2014	EP	N/A
2921042	12/2014	EP	N/A
2944725	12/2014	EP	N/A
2510777	12/2015	EP	N/A
2997805	12/2015	EP	N/A
3000302	12/2015	EP	N/A
2868806	12/2015	EP	N/A
3085221	12/2015	EP	N/A
3095310	12/2015	EP	N/A
3097759	12/2015	EP	N/A
2452551	12/2016	EP	N/A
3175691	12/2016	EP	N/A
3195719	12/2016	EP	N/A
3195720	12/2016	EP	N/A
3259976	12/2016	EP	N/A
3262934	12/2017	EP	N/A
3491192	12/2017	EP	N/A
3287007	12/2017	EP	N/A
3298876	12/2017	EP	N/A
3300579	12/2017	EP	N/A
3315005	12/2017	EP	N/A
3316208	12/2017	EP	N/A
2829171	12/2017	EP	N/A
2508057	12/2017	EP	N/A
2508057	12/2017	EP	N/A
3378298	12/2017	EP	N/A
3378299	12/2017	EP	N/A
3384754	12/2017	EP	N/A
3289853	12/2018	EP	N/A
3456167	12/2018	EP	N/A
3466239	12/2018	EP	N/A
3469878	12/2018	EP	N/A
3289852	12/2018	EP	N/A
3494770	12/2018	EP	N/A
3498074	12/2018	EP	N/A
3000302	12/2018	EP	N/A
3533314	12/2018	EP	N/A
3569049	12/2018	EP	N/A
3000307	12/2018	EP	N/A
3586592	12/2019	EP	N/A
3593613	12/2019	EP	N/A
3593620	12/2019	EP	N/A
3613272	12/2019	EP	N/A
3243374	12/2019	EP	N/A
3626038	12/2019	EP	N/A
3259976	12/2019	EP	N/A
3635647	12/2019	EP	N/A
3378298	12/2019	EP	N/A
3646699	12/2019	EP	N/A
3662741	12/2019	EP	N/A
3685648	12/2019	EP	N/A
2995191	12/2019	EP	N/A
2997805	12/2020	EP	A01B 67/00
3626038	12/2021	EP	A01B 67/00
2116215	12/1997	ES	N/A
2311322	12/2008	ES	N/A
5533	12/1912	FI	N/A
1451480	12/1965	FR	N/A
2817344	12/2001	FR	N/A
2901291	12/2006	FR	N/A
2901291	12/2006	FR	N/A
901081	12/1961	GB	N/A
201519517	12/2016	GB	N/A
01632	12/2015	IN	N/A
1632DE2014	12/2015	IN	N/A
201641027017	12/2015	IN	N/A
202041039250	12/2019	IN	N/A
7079681	12/1981	JP	N/A
S60253617	12/1984	JP	N/A
S63308110	12/1987	JP	N/A

H02196960	12/1989	JP	N/A
H02215311	12/1989	JP	N/A
H0779681	12/1994	JP	N/A
H1066436	12/1997	JP	N/A
H10191762	12/1997	JP	N/A
2000352044	12/1999	JP	N/A
2001057809	12/2000	JP	N/A
2002186348	12/2001	JP	N/A
2005227233	12/2004	JP	N/A
2006166871	12/2005	JP	N/A
2011205967	12/2010	JP	N/A
2015070812	12/2014	JP	N/A
2015151826	12/2014	JP	N/A
2015219651	12/2014	JP	N/A
2016071726	12/2015	JP	N/A
2016160808	12/2015	JP	N/A
6087258	12/2016	JP	N/A
2017136035	12/2016	JP	N/A
2017137729	12/2016	JP	N/A
2017195804	12/2016	JP	N/A
2018068284	12/2017	JP	N/A
2018102154	12/2017	JP	N/A
2018151388	12/2017	JP	N/A
2019004796	12/2018	JP	N/A
2019129744	12/2018	JP	N/A
2019146506	12/2018	JP	N/A
2019216744	12/2018	JP	N/A
2020018255	12/2019	JP	N/A
2020031607	12/2019	JP	N/A
2020113062	12/2019	JP	N/A
2020127405	12/2019	JP	N/A
100974892	12/2009	KR	N/A
100974892	12/2009	KR	N/A
20110018582	12/2010	KR	N/A
101067576	12/2010	KR	N/A
101067576	12/2010	KR	N/A
101134075	12/2011	KR	N/A
101447197	12/2013	KR	N/A
101653750	12/2015	KR	N/A
20170041377	12/2016	KR	N/A
200485051	12/2016	KR	N/A
200485051	12/2016	KR	N/A
101873657	12/2017	KR	N/A
06000012	12/2007	MX	N/A
178299	12/1999	PL	N/A
130713	12/2014	RO	N/A
1791767	12/1992	RU	N/A
2005102554	12/2005	RU	N/A
2421744	12/2010	RU	N/A
2421744	12/2010	RU	N/A
2447640	12/2011	RU	N/A
2502047	12/2012	RU	N/A
2502047	12/2012	RU	N/A
164128	12/2015	RU	N/A
2017114139	12/2017	RU	N/A
2017114139	12/2018	RU	N/A
834514	12/1980	SU	N/A
887717	12/1980	SU	N/A
1052940	12/1982	SU	N/A
1134669	12/1984	SU	N/A
1526588	12/1988	SU	N/A
1540053	12/1990	SU	N/A
1761864	12/1991	SU	N/A
1986005353	12/1985	WO	N/A
2001052160	12/2000	WO	N/A
2002015673	12/2001	WO	N/A
2003005803	12/2002	WO	N/A
2007050192	12/2006	WO	N/A
2009156542	12/2008	WO	N/A
2010003421	12/2009	WO	N/A
2011104085	12/2010	WO	N/A
2012041621	12/2011	WO	N/A
2012110508	12/2011	WO	N/A
2012110544	12/2011	WO	N/A

2013063106	12/2012	WO	N/A
2013079247	12/2012	WO	N/A
2013086351	12/2012	WO	N/A
2013087275	12/2012	WO	N/A
2014046685	12/2013	WO	N/A
2014093814	12/2013	WO	N/A
2014195302	12/2013	WO	N/A
2015038751	12/2014	WO	N/A
2015153809	12/2014	WO	N/A
16020595	12/2015	WO	N/A
2016020595	12/2015	WO	N/A
2016118686	12/2015	WO	N/A
2017008161	12/2016	WO	N/A
2017060168	12/2016	WO	N/A
2017077113	12/2016	WO	N/A
2017096489	12/2016	WO	N/A
2017099570	12/2016	WO	N/A
2017116913	12/2016	WO	N/A
2017170507	12/2016	WO	N/A
2017205406	12/2016	WO	N/A
2017205410	12/2016	WO	N/A
2018043336	12/2017	WO	N/A
2018073060	12/2017	WO	N/A
2018081759	12/2017	WO	N/A
2018112615	12/2017	WO	N/A
2018116772	12/2017	WO	N/A
2018142768	12/2017	WO	N/A
2018200870	12/2017	WO	N/A
2018206587	12/2017	WO	N/A
2018220159	12/2017	WO	N/A
2018226139	12/2017	WO	N/A
2018235486	12/2017	WO	N/A
2018235942	12/2017	WO	N/A
WO18235486	12/2017	WO	N/A
2019034213	12/2018	WO	N/A
2019079205	12/2018	WO	N/A
2019081349	12/2018	WO	N/A
2019091535	12/2018	WO	N/A
2019109191	12/2018	WO	N/A
2019124174	12/2018	WO	N/A
2019124217	12/2018	WO	N/A
2019124225	12/2018	WO	N/A
2019124273	12/2018	WO	N/A
2019129333	12/2018	WO	N/A
2019129334	12/2018	WO	N/A
2019129335	12/2018	WO	N/A
2019215185	12/2018	WO	N/A
2019230358	12/2018	WO	N/A
2020026578	12/2019	WO	N/A
2020026650	12/2019	WO	N/A
2020026651	12/2019	WO	N/A
2020031473	12/2019	WO	N/A
2020038810	12/2019	WO	N/A
2020039312	12/2019	WO	N/A
2020039671	12/2019	WO	N/A
2020044726	12/2019	WO	N/A
2020082182	12/2019	WO	N/A
2020100810	12/2019	WO	N/A
2020110920	12/2019	WO	N/A
2020195007	12/2019	WO	N/A
2020206941	12/2019	WO	N/A
2020206942	12/2019	WO	N/A
2020210607	12/2019	WO	N/A
2020221981	12/2019	WO	N/A
2021262500	12/2020	WO	N/A

OTHER PUBLICATIONS

“Chlingaryan A, et al.; Machine Learning Approaches for crop yield prediction and nitrogen status estimation in precision agriculture : A review; 2018; Computers and Electronics in Agriculture; 151; 61-69” (Year: 2018). cited by examiner

Extended European Search Report and Written Opinion issued in European Patent Application No. 20208171.7, dated May 11, 2021, in 05 pages. cited by applicant

Cordoba, M.A., Bruno, C.I. Costa, J.L. Peralta, N.R. and Balzarini, M.G., 2016, Protocol for multivariate homegeneous zone delineation in precision agriculture, biosystems engineering, 143, pp. 95-107. cited by applicant

Pioneer Estimator, “Corn Yield Estimator” accessed on Feb. 13, 2018, 1 page. retrieved from: <https://www.pioneer.com/home/site/us/tools-apps/growing->

tools/corn-yield-estimator/. cited by applicant

Guindin, N. "Estimating Maize Grain Yield From Crop Biophysical Parameters Using Remote Sensing", Nov. 4, 2013, 19 pages. cited by applicant

EP Application No. 19203883.4-1004 Office Action dated May 3, 2021, 4 pages. cited by applicant

Iowa State University Extension and Outreach, "Harvest Weed Seed Control", Dec. 13, 2018, 6 pages. <https://crops.extension.iastate.edu/blog/bob-hartzler/harvest-weed-seed-control>. cited by applicant

Getting Rid of Weeds Through Integrated Weed Management, accessed on Jun. 25, 2021, 10 pages. <https://integratedweedmanagement.org/index.php/iwm-toolbox/the-harrington-seed-destructor>. cited by applicant

The Importance of Reducing Weed Seeds, Jul. 2018, 2 pages. https://www.aphis.usda.gov/plant_health/soybeans/soybean-handouts.pdf. cited by applicant

Alternative Crop Guide, Published by the Jefferson Institute, "Buckwheat", Revised Jul. 2002. 4 pages. cited by applicant

Prosecution History for U.S. Appl. No. 16/380,691 including: Notice of Allowance dated Mar. 10, 2021 and Application and Drawings, filed Apr. 10, 2019, pages. cited by applicant

U.S. Appl. No. 16/831,216 Application and Drawings, filed Mar. 26, 2020, 56 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/380,531 dated Apr. 5, 2021, 5 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 16/171,978, filed Oct. 26, 2018, 53 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/432,557 dated Mar. 22, 2021, 9 pages. cited by applicant

Zhao, L., Yang, J., Li, P. and Zhang, L., 2014. Characteristics analysis and classification of crop harvest patterns by exploiting high-frequency multipolarization SAR data. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 7(9), pp. 3773-3783. cited by applicant

Feng-jie, X., Er-da, W. and Feng-yuan, X., Crop area yield risk evaluation and premium rates calculation-Based on nonparametric kernel density estimation. In 2009 International Conference on Management Science and Engineering, 7 pages. cited by applicant

Liu, R. and Bai, X., 2014, May. Random fuzzy production and distribution plan of agricultural products and its PSO algorithm. In 2014 IEEE International Conference on Progress in Informatics and Computing (pp. 32-36). IEEE. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/171,978 dated Mar. 31, 2021, 6 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 17/067,383, filed Oct. 9, 2020, 61 pages. cited by applicant

Martin et al. Breakage Susceptibility and Hardness of Corn Kernels of Various Sizes and Shapes, vol. 3(3): May 1087, 10 pages. <https://pdfs.semanticscholar.org/e579/1b5363b6a78efd44adfb9775580cdd1417ca.pdf>. cited by applicant

Hoff, "Combine Adjustments" (<https://smallfarmersjournal.com/combine-adjustments/>). Mar. 1943. 9 pages. cited by applicant

Optimizing Crop Profit Across Multiple Grain Attributes and Stover. Electronic Publication Date May 26, 2009. 17 pages. cited by applicant

Unglesbee, Soybean Pod Shatter—Bad Enough to Scout Before Harvest—DTN. Oct. 17, 2016, 11 pages, Susceptibility to shatter (<https://agfax.com/2018/10/17/soybean-pod-shatter-bad-enough-to-scout-before-harvest-dtn/>). cited by applicant

GIS Maps for Agricultural, accessed on May 10, 2022, 7 pages. <https://www.satimagingcorp.com/services/geographic-information-systems/gis-maps-agriculture-mapping>. cited by applicant

<https://wingtra.com/drone-mapping-applications/use-of-drones-in-agriculture>, accessed on May 10, 2022, 19 pages. cited by applicant

Energy Requirement Model for a Combine Harvester: Part 1: Development of Component Models, Published online Dec. 22, 2004, 17 pages. cited by applicant

Energy Requirement Model for a Combine Harvester, Part 2: Integration of Component Models, Published online Jan. 18, 2005, 11 pages. cited by applicant

Pioneer on reducing soybean harvest losses including combine adjustments (last accessed Jul. 23, 2020) (https://www.pioneer.com/us/agronomy/reducing_harvest_losses_in_soybeans.html). 5 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 16/175,993, filed Oct. 31, 2018, 28 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 16/380,623, filed Apr. 10, 2019, 36 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 16/783,511, filed Feb. 6, 2020, 55 pages. cited by applicant

"Automated Weed Detection With Drones" dated May 25, 2017, retrieved at: <<<https://www.precisionhawk.com/blog/media/topic/automated-weed-identification-with-drones>>>, retrieved on Jan. 21, 2020, 4 pages. cited by applicant

F. Forcella, "Estimating the Timing of Weed Emergence", Site-Specific Management Guidelines, retrieved at: <<[http://www.ipni.net/publication/ssmg.nsf/0/D26EC9A906F9B8C9852579E500773936/\\$FILE/SSMG-20.pdf](http://www.ipni.net/publication/ssmg.nsf/0/D26EC9A906F9B8C9852579E500773936/$FILE/SSMG-20.pdf)>>, retrieved on Jan. 21, 2020, 4 pages. cited by applicant

Chauhan et al., "Emerging Challenges and Opportunities for Education and Research in Weed Science", *frontiers in Plant Science*. Published online Sep. 5, 2017, 22 pages. cited by applicant

Apan, A., Wells, N., Reardon-Smith, K., Richardson, L., McDougall, K., and Basnet, B.B., 2008. Predictive mapping of blackberry in the Condamine Catchment using logistic regression and spatial analysis. In *Proceedings of the 2008 Queensland Spatial Conference: Global Warning: What's Happening in Paradise*. Spatial Sciences Institute, 11 pages. cited by applicant

Jarnevich, C.S., Holcombe, T.R., Barnett, D.T., Stohlgren, T.J. and Kartesz, J.T., 2010. Forecasting weed distributions using climate data: a GIS early warning tool. *Invasive Plant Science and Management*. 3(4), pp. 365-375. cited by applicant

Sa et al., "WeedMap: A Large-Scale Semantic Weed Mapping Framework Using Aerial Multispectral Imaging and Deep Neural Network for Precision Farming", Sep. 6, 2018, 25 pages. cited by applicant

Pflanz et al., "Weed Mapping with UAS Imagery and a Bag of Visual Words Based Image Classifier", Published Sep. 24, 2018, 28 pages. cited by applicant

Provisional Application and Drawings for U.S. Appl. No. 62/928,964, filed Oct. 31, 2019, 14 pages. cited by applicant

Application and Drawings for U.S. Appl. No. 16/783,475, filed Feb. 6, 2020, 55 pages. cited by applicant

U.S. Appl. No. 17/067,483 Application and Drawings, filed Oct. 9, 2020, 63 pages. cited by applicant

U.S. Appl. No. 17/066,442 Application and Drawings, filed Oct. 8, 2020, 65 pages. cited by applicant

U.S. Appl. No. 16/380,550, filed Apr. 10, 2019, Application and Drawings, 47 pages. cited by applicant

U.S. Appl. No. 17/066,999 Application and Drawings, filed Oct. 9, 2020, 67 pages. cited by applicant

U.S. Appl. No. 17/066,444 Application and Drawings, filed Oct. 8, 2020, 102 pages. cited by applicant

Extended Search Report for European Patent Application No. 20167930.5 dated Sep. 15, 2020, 8 pages. cited by applicant

Extended Search Report for European Patent Application No. 19205901.2 dated Mar. 17, 2020, 6 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/171,978, dated Dec. 15, 2020, 21 pages. cited by applicant

Zhigen et al., "Research of the Combine Harvester Load Feedback Control System Using Multi-Signal Fusion Method and Fuzzy Algorithm," 2010, Publisher: IEEE, 5 pages. cited by applicant

Dan et al., "On-the-go Throughput Prediction in a Combine Harvester Using Sensor Fusion," 2017, Publisher: IEEE, 6 pages. cited by applicant

Fernandez-Quintanilla et al., "Is the current state of the art of weed monitoring suitable for site-specific weed management in arable crops?", First Published May 1, 2018, 4 pages. cited by applicant

Dionysis Bochtis et al. "Field Operations Planning for Agricultural Vehicles: A Hierarchical Modeling Framework." *Agricultural Engineering International: the CIGR Ejournal*. Manuscript PM 06 021. vol. IX. Feb. 2007, pp. 1-11. cited by applicant

U.S. Appl. No. 16/432,557, filed Jun. 5, 2019, 61 pages. cited by applicant

European Search Report issued in counterpart European Patent Application No. 19205142.3 dated Feb. 28, 2020 (6 pages). cited by applicant

Mei-Ju et al., "Two paradigms in cellular Internet-of-Things access for energy-harvesting machine-to-machine devices: push-based versus pull-based," 2016 vol. 6, 9 pages. cited by applicant

Yi et al., "An Efficient MAC Protocol With Adaptive Energy Harvesting for Machine-to-Machine Networks," 2015, vol. 3, Publisher: IEEE, 10 pages. cited by applicant

European Search Report issued in European Patent Application No. 19203883.4 dated Mar. 23, 2020 (10 pages). cited by applicant

Notice of Allowance for U.S. Appl. No. 16/171,978 dated Oct. 28, 2020, 5 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/171,978, dated Aug. 7, 2020, 9 pages. cited by applicant

K.R. Manjunath et al., "Developing Spectral Library of Major Plant Species of Western Himalayas Using Ground Observations", J. Indian Soc Remote Sens (Mar. 2014) 42(a):201-216, 17 pages. cited by applicant

U.S. Appl. No. 16/380,564 Application and Drawings, filed Apr. 10, 2019, 55 pages. cited by applicant

S. Veenadhari et al., "Machine Learning Approach For Forecasting Crop Yield Based on Climatic Parameters", 2014 International Conference on Computer Communication and Informatics (ICCCI-2014) Jan. 3-6, 2014, Coimbatore, India, 5 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/380,531 dated Oct. 21, 2020, 10 pages. cited by applicant

U.S. Appl. No. 16/380,531 Application and Drawings, filed Apr. 10, 2019, 46 pages. cited by applicant

Leu et al., Grazing Corn Residue Using Resources and Reducing Costs, Aug. 2009, 4 pages. cited by applicant

"No-Till Soils", Soil Heath Brochure, 2 pages, last accessed Jul. 14, 2020. cited by applicant

Strickland et al., "Nitrate Toxicity in Livestock" Oklahoma State University, Feb. 2017, 2 pages. cited by applicant

Strickland et al., "Nitrate Toxicity in Livestock" Oklahoma State University, 8 pages, Feb. 2017. cited by applicant

Brownlee, "Neural Networks are Function Approximation Algorithms", Mar. 18, 2020, 13 pages. cited by applicant

Thompson, "Morning glory can make it impossible to harvest corn", Feb. 19, 2015, 3 pages. cited by applicant

Tumlison, "Monitoring Growth Development and Yield Estimation of Maize Using Very High-Resolution Uavimages in Gronau, Germany", Feb. 2017, 63 pages. cited by applicant

Hunt, "Mapping Weed Infestations Using Remote Sensing", 8 pages, Jul. 19, 2005. cited by applicant

Wright, et al., "Managing Grain Protein in Wheat Using Remote Sensing", 12 pages, 2003. cited by applicant

"Malting Barley in Pennsylvania", Agronomy Facts 77, 6 pages, Code EE0179 Jun. 2016. cited by applicant

"Green stem syndrome in soybeans", Agronomy eUpdate Issue 478 Oct. 10, 2014, 3 pages. cited by applicant

"Keep Weed Seed Out of Your Harvest", Aug. 8, 2019, 1 pages. cited by applicant

Hodrius et al., "The Impact of Multi-Sensor Data Assimilation on Plant Parameter Retrieval and Yield Estimation for Sugar Beet", The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences, vol. XL-7/W3, 2015, 36th International Symposium on Remote Sensing of Environment, May 11-15, 2015, Berlin, Germany, 7 pages. cited by applicant

Fernandez-Quintanilla et al., "Is the current state of the art of weed monitoring suitable for site-specific weed management in arable crops?", Feb. 2018, 35 pages. cited by applicant

Anonymously, "Improved System and Method for Controlling Agricultural Vehicle Operation Using Historical Data", Dec. 16, 2009, 8 pages. cited by applicant

Anonymously, "System and Method for Controlling Agricultural Vehicle Operation Using Historical Data", Jun. 30, 2009, 8 pages. cited by applicant

"Leafsnap, a new mobile app that identifies plants by leaf shape, is launched by Smithsonian and collaborators", May 2, 2011, 5 pages. cited by applicant

Insect Gallery, Department of Entomology, Kansas State University, Oct. 19, 2020, 8 pages. cited by applicant

Licht, "Influence of Corn Seeding Rate, Soil Attributes, and Topographic Characteristics on Grain Yield, Yield Components, and Grain Composition", 2015, 107 pages. cited by applicant

"Notice of Retraction Virtual simulation of plant with individual stem based on crop growth model", Mar. 5, 2017, 7 pages. cited by applicant

Ma et al., "Identification of Fusarium Head Blight in Winter Wheat Ears Using Continuous Wavelet Analysis", Dec. 19, 2019, 15 pages. cited by applicant

Leland, "Who Did that? Identifying Insect Damage", Apr. 1, 2015, 4 pages. cited by applicant

"How to improve maize protein content" <https://www.yara.co.uk/crop-nutrition/forage-maize/improving-maize-protein-content>, Sep. 30, 2020, 10 pages. cited by applicant

Hafemeister, "Weed control at harvest, combines are ideal vehicles for spreading weed seeds", Sep. 25, 2019, 3 pages. cited by applicant

"Harvesting Tips", Northern Pulse Growers Association, 9 pages, Jan. 31, 2001. cited by applicant

Wortmann et al., "Harvesting Crop Residues", Aug. 10, 2020, 8 pages. cited by applicant

"Harvesting", Oklahoma State University, Canola Swathing Guide, 2010, 9 pages, last accessed Jul. 14, 2020. cited by applicant

Hanna, "Harvest Tips for Lodged Corn", Sep. 6, 2011, 3 pages. cited by applicant

"Green Weeds Complicate Harvest", Crops, Slider, Sep. 26, 2012, 2 pages. cited by applicant

"Agrowatch Green Vegetation Index", Retrieved Dec. 11, 2020, 4 pages. cited by applicant

"Grazing Corn Residues" (<http://www.ca.uky.edu>), 3 pages, Aug. 24, 2009. cited by applicant

Jarnevech et al., Forecasting Weed Distributions Using Climate Data: A GIS Early Warning Tool, Downloaded on Jul. 13, 2020, 12 pages. cited by applicant

Combine Cutting and Feeding Mechanisms in the Southeast, By J-K Park, Agricultural Research Service, U.S. Dept. of Agriculture, 1963, 1 page. cited by applicant

Hartzler, "Fate of weed seeds in the soil", 4 pages, Jan. 31, 2001. cited by applicant

Digman, "Combine Considerations for a Wet Corn Harvest", Extension Specialist UW—Madison, 3 pages, oct. 29, 2009. cited by applicant

S-Series Combine and Front End Equipment Optimization, John Deere Harvester Works, 20 pages Date: Oct. 9, 2017. cited by applicant

Determining yield monitoring system delay time with geostatistical and data segmentation approaches (<https://www.ars.usda.gov/ARSUserFiles/50701000/cswq-0036-128359.pdf>) Jul. 2002, 13 pages. cited by applicant

Precision Agriculture: Yield Monitors (dated Nov. 1998—metadata; last accessed Jul. 16, 2020) (<https://extensiondata.missouri.edu/pub/pdf/envqual/wq0451.pdf>) 4 pages. cited by applicant

Paul et al., "Effect of soil water status and strength on trafficability" (1979) (<https://www.nrcresearchpress.com/doi/pdfplus/10.4141/cjss79-035>), 12 pages, Apr. 23, 1979. cited by applicant

Sick, "Better understanding corn hybrid characteristics and properties can impact your seed decisions" (<https://emergence.fbn.com/agronomy/corn-hybrid-characteristics-and-properties-impact-seed-decisions>) By Steve Sick, FBN Breeding Project Lead | Sep. 21, 2018, 8 pages. cited by applicant

Robertson et al., "Maize Stalk Lodging: Morphological Determinants of Stalk Strength" Mar. 2017, 10 pages. cited by applicant

Martin, et al., "Breakage Susceptibility and Hardness of Corn Kernels of Various Sizes and Shapes", May 1987, 10 Pages. cited by applicant

7 Combine Tweaks to Boost Speed (https://www.agriculture.com/machinery/harvest-equipment/7-combine-tweaks-to-boost-speed_203-ar33059) 8 pages, Aug. 19, 2018. cited by applicant

Managing corn harvest this fall with variable corn conditions (<https://www.ocj.com/2019/10/managing-corn-harvest-this-fall-with-variable-corn-conditions/>) 4 pages, Oct. 10, 2019. cited by applicant

Reducing Aflatoxin in Corn During Harvest and Storage (<https://extension.uga.edu/publications/detail.html?number=B1231&title=Reducing%20Aflatoxin%20in%20Corn%20During%20Harvest%20and%20Storage>), 9 pages, Published with Full Review on Apr. 15, 2019. cited by applicant

2017. cited by applicant

Variable Rate Applications to Optimize Inputs (<https://www.cotton.org/tech/physiology/cpt/miscpubs/upload/CPT-v9No2-98-REPOP.pdf>), 8 pages, Nov. 2, 1998. cited by applicant

Robin Booker, VIDEO: Canadian cage mill teams up with JD (<https://www.producer.com/2019/12/video-canadian-cage-mill-teams-up-with-jd/>), 6 pages, Dec. 19, 2019. cited by applicant

Jarnevich, et al. “Forecasting Weed Distributions using Climate Data: A GIS Early Warning Tool”, *Invasive Plant Science and Management*, 11 pages, Jan. 2017. cited by applicant

Burks, “Classification of Weed Species Using Color Texture Features and Discriminant Analysis” (<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.468.5833&rep=rep1&type=pdf>), 8 pages, 2000. cited by applicant

John Deere, <https://www.youtube.com/watch?v=1Gq77CfdG14&list=PL1KGsSJ4CWk4rShNb3-sTMOliL8meHBL5> (last accessed Jul. 14, 2020), Jun. 15, 2020, 5 pages. cited by applicant

Combine Adjustments (<http://corn.agronomy.wisc.edu/Management/L036.aspx>), 2 pages, Originally written Feb. 1, 2006; last updated Oct. 18, 2018. cited by applicant

Ardekani, “Off- and on-ground GPR techniques for field-scale soil moisture mapping” Jun. 2013, 13 pages. cited by applicant

Does an Adaptive Gearbox Really Learn How You Drive? (<https://practicalmotoring.com.au/voices/does-an-adaptive-gearbox-really-learn-how-you-drive/>), Oct. 30, 2019, 8 pages. cited by applicant

https://www.researchgate.net/publication/222527694_Energy_Requirement_Model_for_a_Combine_Harvester_Part_I_Development_of_Component_Model

Abstract Only, Jan. 2005. cited by applicant

<http://canola.okstate.edu/cropproduction/harvesting>, 8 pages, Aug. 2011. cited by applicant

“Tips and Tricks of Harvesting High Moisture Grain”, <https://www.koenigequipment.com/blog/tips-and-tricks-of-harvesting-highmoisture-grain>, 5 pages, last accessed Feb. 11, 2021. cited by applicant

Hoff, Combine Adjustments, Mar. 1943, 8 pages. cited by applicant

Haug et al., “Accurate Weed Mapping and Prescription Map Generation Based on Fully Convolutional Networks Using UAV Imagery”, 14 pages, Oct. 1, 2018. cited by applicant

Thompson, “Morning glory can make it impossible to harvest corn”, Feb. 19, 2015, 4 pages. cited by applicant

Lamsal et al. “Sugarcane Harvest Logistics in Brazil” *Iowa Research Online*, Sep. 11, 2013, 27 pages. cited by applicant

Jensen, “Algorithms for Operational Planning of Agricultural Field Operations”, *Mechanical Engineering Technical Report ME-TR-3*, Nov. 9, 2012, 23 pages. cited by applicant

Chauhan, “Remote Sensing of Crop Lodging”, Nov. 16, 2020, 16 pages. cited by applicant

Apan et al., “Predictive Mapping of Blackberry in the Condamine Catchment Using Logistic Regression and Spatial Analysis”, Jan. 2008, 12 pages. cited by applicant

Robson, “Remote Sensing Applications for the Determination of Yield, Maturity and Aflatoxin Contamination in Peanut”, Oct. 2007, 275 pages. cited by applicant

Bhattarai et al., “Remote Sensing Data to Detect Hessian Fly Infestation in Commercial Wheat Fields”, Apr. 16, 2019, 8 pages. cited by applicant

Towery, et al., “Remote Sensing of Crop Hail Damage”, Jul. 21, 1975, 31 pages. cited by applicant

Sa et al., “WeedMap: A Large-Scale Semantic Weed Mapping Framework Using Aerial Multispectral Imaging and Deep Neural Network for Precision Farming”, Sep. 7, 2018, 25 pages. cited by applicant

Mathyam et al., “Remote Sensing of Biotic Stress in Crop Plants and Its Applications for Pest Management”, Dec. 2011, 30 pages. cited by applicant

Martinez-Feria et al., “Evaluating Maize and Soybean Grain Dry-Down in the Field With Predictive Algorithms and Genotype-by-Environmental Analysis”, May 9, 2019, 13 pages. cited by applicant

“GIS Maps for Agriculture”, *Precision Agricultural Mapping*, Retrieved Dec. 11, 2020, 6 pages. cited by applicant

Paul, “Scabby Wheat Grain? Increasing Your Fan Speed May Help”, <https://agcrops.osu.edu/newsletter/corn-newsletter/2015-20/scabby-wheat-grain-increasing-yourfan-speed-may-help>, *C.O.R.N Newsletter* //2015-20, 3 pages. cited by applicant

Clay et al., “Scouting for Weeds”, *SSMG-15*, 4 pages, 2002. cited by applicant

Taylor et al., “Sensor-Based Variable Rate Application for Cotton”, 8 pages, 2010. cited by applicant

Christiansen et al., “Designing and Testing a UAV Mapping System for Agricultural Field Surveying”, Nov. 23, 2017, 19 pages. cited by applicant

Haug et al., “Accurate Weed Mapping and Prescription Map Generation Based on Fully Convolutional Networks Using UAV Imagery”, Oct. 1, 2018, 12 pages. cited by applicant

Morrison, “Should You Use Tillage to Control Resistant Weeds”, Aug. 29, 2014, 9 pages. cited by applicant

Morrison, “Snow Trapping Snags Water”, Oct. 13, 2005, 3 pages. cited by applicant

“Soil Zone Index”, <https://www.satimagingcorp.com/applications/natural-resources/agriculture> . . . , Retrieved Dec. 11, 2020, 5 pages. cited by applicant

Malvic, “Soybean Cyst Nematode”, *University of Minnesota Extension*, Oct. 19, 2020, 3 pages. cited by applicant

Unglesbee, “Soybean Pod Shatter—Bad Enough to Scout Before Harvest?—DTN”, Oct. 17, 2018, 4 pages. cited by applicant

Tao, “Standing Crop Residue Can Reduce Snow Drifting and Increase Soil Moisture”, 2 pages, last accessed Jul. 14, 2020. cited by applicant

Berglund, et al., “Swathing and Harvesting Canola”, Jul. 2019, 8 pages. cited by applicant

Bell et al., “Synthetic Aperture Radar and Optical Remote Sensing of Crop Damage Attributed to Severe Weather in the Central United States”, Jul. 25, 2018, 1 page. cited by applicant

Rosencrance, “Tabletop Grapes in India to Be Picked by Virginia Tech Robots”, Jul. 23, 2020, 8 pages. cited by applicant

Lofton, et al., The Potential of Grazing Grain Sorghum Residue Following Harvest, May 13, 2020, 11 pages. cited by applicant

Beal et al., “Time Shift Evaluation to Improve Yield Map Quality”, Published in *Applied Engineering in Agriculture* vol. 17(3): 385-390 (© 2001 American Society of Agricultural Engineers), 9 pages. cited by applicant

“Tips and Tricks of Harvesting High Moisture Grain”, <https://www.koenigequipment.com/blog/tips-and-tricks-of-harvesting-highmoisture-grain>, 7 pages, last accessed Jul. 14, 2020. cited by applicant

Ransom, “Tips for Planting Winter Wheat and Winter Rye (for Grain) (Aug. 15, 2019)”, 2017, 3 pages. cited by applicant

AgroWatch Tree Grading Maps, “The Grading Maps and Plant Count Reports”, <https://www.satimagingcorp.com/applications/natural-resources/agriculture> . . . , Retrieved Dec. 11, 2020, 4 pages. cited by applicant

Ackley, “Troubleshooting Abnormal Corn Ears”, Jul. 23, 2020, 25 pages. cited by applicant

Smith, “Understanding Ear Flex”, Feb. 25, 2019, 17 pages. cited by applicant

Carroll et al., “Use of Spectral Vegetation Indices Derived from Airborne Hyperspectral Imagery For Detection of European Corn Borer Infestation in Iowa Corn Plots”, Nov. 2008, 11 pages. cited by applicant

Agriculture, “Using drones in agriculture and capturing actionable data”, Retrieved Dec. 11, 2020, 18 pages. cited by applicant

Bentley et al., “Using Landsat to Identify Thunderstorm Damage in Agricultural Regions”, Aug. 28, 2001, 14 pages. cited by applicant

Duane Grant and the Idaho Wheat Commission, “Using Remote Sensing to Manage Wheat Grain Protein”, Jan. 2, 2003, 13 pages. cited by applicant

Zhang et al., “Using satellite multispectral imagery for damage mapping of armyworm (*Spodoptera frugiperda*) in maize at a regional scale”, Apr. 10, 2015, 10 pages. cited by applicant

14 pages. cited by applicant

Booker, "VIDEO: Canadian cage mill teams up with JD", Dec. 19, 2019, 6 pages. cited by applicant

AgTalk Home, "Best Combine to Handle Weeds", Posted Nov. 23, 2018, 9 pages. cited by applicant

"Volunteer corn can be costly for soybeans", Jun. 2, 2016, 1 page. cited by applicant

Pflanz, et al., "Weed Mapping with UAS Imagery and a Bag of Visual Words Based Image Classifier", Published Sep. 24, 2018, 17 pages. cited by applicant

Hartzler, "Weed seed predation in agricultural fields", 9 pages, 2009. cited by applicant

Sa et al., "Weedmap: A Large-Scale Sematnic Weed Mapping Framework Using Aerial Multispectral Imaging and Deep Neural Netowrk for Precision Farming", Sep. 6, 2018, 25 pages. cited by applicant

Nagelkirk, Michigan State University-Extension, "Wheat Harvest: Minimizing the Risk of Fusarium Head Scab Losses", Jul. 11, 2013, 4 pages. cited by applicant

Saskatchewan, "Wheat: Winter Wheat", (<https://www.saskatchewan.ca/business/agriculture-natural-resources-and-industry/agribusiness-farmers-and-ranchers/crops-and-irrigation/field-crops/cereals-barley-wheat-oats-triticale/wheat-winter-wheat>) 5 pages, last accessed Jul. 14, 2020. cited by applicant

Quora, "Why would I ever use sport mode in my automatic transmission car? Will this incrase fuel efficiency or isit simply a feature that makes form more fun when driving?", Aug. 10, 2020, 5 pages. cited by applicant

Wade, "Using a Drone's Surface Model to Estimate Crop Yields & Assess Plant Health", Oct. 19, 2015, 14 pages. cited by applicant

Mathyam et al., "Remote Sensing of Biotic Stress in Crop Plants and Its Applications for Pest Stress", Dec. 2011, 30 pages. cited by applicant

"Four Helpful Weed-Management Tips for Harvest Time", 2 pages, Sep. 4, 2019. cited by applicant

Franz et al., "The role of topography, soil, and remotely sensed vegetation condition towards predicting crop yield", University of Nebraska—Lincoln, Mar. 23, 2020, 44 pages. cited by applicant

Peiffer et al., "The Genetic Architecture of Maize Stalk Strength", Jun. 20, 2013, 14 pages. cited by applicant

Martin et al., "Breakage Susceptibility and Harness of Corn Kernels of Various Sizes and Shapes", May 1987, 10 pages. cited by applicant

Jones et al., "Brief history of agricultural systems modeling" Jun. 21, 2016, 15 pages. cited by applicant

Dan Anderson, "Brief history of agricultural systems modeling" 1 pages. Aug. 13, 2019. cited by applicant

A.Y. eflek, "Determining the Physico-Mechanical Characteristics of Maize Stalks Fordesigning Harvester", The Journal of Animal & Plant Sciences, 27(3): 2017, p. 855-860 ISSN: 1018-7081, Jun. 1, 2017. cited by applicant

Carmody, Paul, "Windrowing and harvesting", 8 pages Date: Feb. 3, 2010. cited by applicant

Dabney, et al., "Forage Harvest Representation in RUSLE2", Published Nov. 15, 2013, 17 pages. cited by applicant

John Deere S-Series Combines S760, S770, S780, S790 Brochure, 44 pages, Nov. 15, 2017. cited by applicant

Sekhon et al., "Stalk Bending Strength is Strongly Assoicated with Maize Stalk Lodging Incidence Across Multiple Environments", Jun. 20, 2019, 23 pages. cited by applicant

Thomison et al. "Abnormal Corn Ears", Apr. 28, 2015, 1 page. cited by applicant

Anderson, "Adjust your Combine to Reduce Damage to High Moisture Corn", Aug. 13, 2019, 11 pages. cited by applicant

Sumner et al., "Reducing Aflatoxin in Corn During Harvest and Storage", Reviewed by John Worley, Apr. 2017, 6 pages. cited by applicant

Sick, "Better understanding corn hybrid characteristics and properties can impact your seed decisions", 8 pages, Sep. 21, 2018. cited by applicant

TraCI/Change Vehicle State—SUMO Documentation, 10 pages, Retrieved Dec. 11, 2020. cited by applicant

Arnold, et al., Chapter 8. "Plant Growth Component", Jul. 1995, 41 pages. cited by applicant

Humburg, Chapter: 37 "Combine Adjustments to Reduce Harvest Losses", 2019, South Dakota Board of Regents, 8 pages. cited by applicant

Hoff, "Combine Adjustments", Cornell Extension Bulletin 591, Mar. 1943, 10 pages. cited by applicant

University of Wisconsin, Corn Agronomy, Originally written Feb. 1, 2006 | Last updated Oct. 18, 2018, 2 pages. cited by applicant

University of Nebraska-Lincoln, "Combine Adjustments for Downed Corn—Crop Watch", Oct. 27, 2017, 5 pages. cited by applicant

"Combine Cleaning: Quick Guide to Removing Resistant Weed Seeds (Among Other Things)", Nov. 2006, 5 pages. cited by applicant

Dekalb, "Corn Drydown Rates", 7 pages, Aug. 4, 2020. cited by applicant

Mahmoud et al. Iowa State University, "Corn Ear Orientation Effects on Mechanical Damage and Forces on Concave", 1975, 6 pages. cited by applicant

Sindelar et al., Kansas State University, "Corn Growth & Development" Jul. 17, 2017, 9 pages. cited by applicant

Pannar, "Manage the Growth Stages of the Maize Plant With Pannar", Nov. 14, 2016, 7 pages. cited by applicant

He et al., "Crop residue harvest impacts wind erodibility and simulated soil loss in the Central Great Plains", Sep. 27, 2017, 14 pages. cited by applicant

Blanken, "Designing a Living Snow Fence for Snow Drift Control", Jan. 17, 2018, 9 pages. cited by applicant

Jean, "Drones give aerial boost to ag producers", Mar. 21, 2019, 4 pages. cited by applicant

Zhao et al., "Dynamics modeling for sugarcane sucrose estimation using time series satellite imagery", Jul. 27, 2017, 11 pages. cited by applicant

Brady, "Effects of Cropland Conservation Practices on Fish and Wildlife Habitat", Sep. 1, 2007, 15 pages. cited by applicant

Jasa, et al., "Equipment Adjustments for Harvesting Soybeans at 13%-15% Moisture", Sep. 15, 2017, 2 pages. cited by applicant

Bendig et al., "Estimating Biomass of Barley Using Crop Surface Models (CSMs) Derived from UAV-Based RGB Imaging", Oct. 21, 2014, 18 pages. cited by applicant

Robertson, et al., "Maize Stalk Lodging: Morphological Determinants of Stalk Strength", Mar. 3, 2017, 10 pages. cited by applicant

MacGowan et al. Purdue University, Corn and Soybean Crop Deprediation by Wildlife, Jun. 2006, 14 pages. cited by applicant

Martinez-Feria et al., Iowa State University, "Corn Grain Dry Down in Field From Maturity to Harvest", Sep. 20, 2017, 3 pages. cited by applicant

Wrona, "Precision Agriculture's Value" Cotton Physiology Today, vol. 9, No. 2, 1998, 8 pages. cited by applicant

Zhang et al., "Design of an Optical Weed Sensor Using Plant Spectral Characteristics" Sep. 2000, 12 pages. cited by applicant

Hunt, et al., "What Weeds Can Be Remotely Sensed?", 5 pages, May 2016. cited by applicant

Pepper, "Does an Adaptive Gearbox Really Learn How You Drive?", Oct. 30, 2019, 8 pages. cited by applicant

Eggerl, "Optimization of Combine Processes Using Expert Knowledge and Methods of Artificial Intelligence", Oct. 7, 1982, 143 pages. cited by applicant

Sheely et al., "Image-Based, Variable Rate Plant Growth Regulator Application in Cotton at Sheely Farms in California", Jan. 6-10, 2003 Beltwide Cotton Conferences, Nashville, TN, 17 pages. cited by applicant

Kovacs et al., "Physical characteristics and mechanical behaviour of maize stalks for machine development", Apr. 23, 2019, 1-pages. cited by applicant

Anonymously, "Optimizing Crop Profit Across Multiple Grain Attributes and Stover", ip.com, May 26, 2009, 17 pages. cited by applicant

Breen, "Plant Identification: Examining Leaves", Oregon State University, 2020, 8 pages. cited by applicant

Caglayan et al., A Plant Recognition Approach Using Shape and Color Features in Leaf Images, Sep. 2013, 11 pages. cited by applicant

Casady et al., "Precision Agriculture" Yield Monitors University of Missouri-System, 4 pages, 1998. cited by applicant

Apan et al., "Predicting Grain Protein Content in Wheat Using Hyperspectral Sensing of In-season Crop Canopies and Partial Least Squares Regression" 18 pages, 2006. cited by applicant

Xu et al., "Prediction of Wheat Grain Protein by Coupling Multisource Remote Sensing Imagery and ECMWF Data", Apr. 24, 2020, 21 pages. cited by applicant

Day, "Probability Distributions of Field Crop Yields," American Journal of Agricultural Economics, vol. 47, Issue 3, Aug. 1965, Abstract Only, 1 page. cited by applicant

Primary Examiner: Nolan; Peter D

Assistant Examiner: Cardimino; Christopher R

Attorney, Agent or Firm: Kelly, Holt & Christenson

Background/Summary

FIELD OF THE DESCRIPTION

(1) The present description relates to agricultural machines, forestry machines, construction machines and turf management machines.

BACKGROUND

(2) There are a wide variety of different types of agricultural machines. Some agricultural machines include harvesters, such as combine harvesters, sugar cane harvesters, cotton harvesters, self-propelled forage harvesters, and windrowers. Some harvesters can also be fitted with different types of heads to harvest different types of crops.

(3) Agricultural harvesters typically include an engine or other power source which produces a finite amount of power which is provided to the various subsystems of the agricultural harvester. Maintaining an efficient power distribution to the various subsystems from a finite amount of power can be difficult to attain across changing field conditions.

(4) The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

SUMMARY

(5) One or more information maps are obtained by an agricultural work machine. The one or more information maps map one or more agricultural characteristic values at different geographic locations of a field. An in-situ sensor on the agricultural work machine senses an agricultural characteristic as the agricultural work machine moves through the field. A predictive map generator generates a predictive map that predicts a predictive agricultural characteristic at different locations in the field based on a relationship between the values in the one or more information maps and the agricultural characteristic sensed by the in-situ sensor. The predictive map can be output and used in automated machine control.

(6) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to examples that solve any or all disadvantages noted in the background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a partial pictorial, partial schematic illustration of one example of a combine harvester.

(2) FIG. 2 is a block diagram showing some portions of an agricultural harvester in more detail, according to some examples of the present disclosure.

(3) FIGS. 3A-3B (collectively referred to herein as FIG. 3) show a flow diagram illustrating an example of operation of an agricultural harvester in generating a map.

(4) FIG. 4 is a block diagram showing one example of a predictive model generator and a predictive metric map generator.

(5) FIG. 5 is a flow diagram showing an example of operation of an agricultural harvester in receiving a vegetative index, crop moisture, soil property, topography, predictive yield or predictive biomass map, detecting a power characteristic, and generating a functional predictive power map for use in controlling the agricultural harvester during a harvesting operation.

(6) FIG. 6A is a block diagram showing one example of a predictive model generator and a predictive map generator.

(7) FIG. 6B is a block diagram showing some examples of in-situ sensors.

(8) FIG. 7 shows a flow diagram illustrating one example of operation of an agricultural harvester involving generating a functional predictive map using a prior information map and an in-situ sensor input.

(9) FIG. 8 is a block diagram showing one example of a control zone generator.

(10) FIG. 9 is a flow diagram illustrating one example of the operation of the control zone generator shown in FIG. 8.

(11) FIG. 10 illustrates a flow diagram showing an example of operation of a control system in selecting a target settings value to control an agricultural harvester.

(12) FIG. 11 is a block diagram showing one example of an operator interface controller.

(13) FIG. 12 is a flow diagram illustrating one example of an operator interface controller.

(14) FIG. 13 is a pictorial illustration showing one example of an operator interface display.

(15) FIG. 14 is a block diagram showing one example of an agricultural harvester in communication with a remote server environment.

(16) FIGS. 15-17 show examples of mobile devices that can be used in an agricultural harvester.

(17) FIG. 18 is a block diagram showing one example of a computing environment that can be used in an agricultural harvester.

DETAILED DESCRIPTION

(18) For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the examples illustrated in the drawings, and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is intended. Any alterations and further modifications to the described devices, systems, methods, and any further application of the principles of the present disclosure are fully contemplated as would normally occur to one skilled in the art to which the disclosure relates. In particular, it is fully contemplated that the features, components, steps, or a combination thereof described with respect to one example may be combined with the features, components, steps, or a combination thereof described with respect to other examples of the present disclosure.

(19) The present description relates to using in-situ data taken concurrently with an agricultural operation, in combination with prior data, to generate a predictive map and, more particularly, a predictive power map. In some examples, the predictive power map can be used to control an agricultural work machine, such as an agricultural harvester. As discussed above, the power generation of a harvester has a finite limit and overall performance may be degraded when one or more subsystems have increased power demands.

(20) Performance of a harvester may be deleteriously affected based on a number of different criteria. For example, areas of dense crop plants, weeds, or combinations thereof, may have deleterious effects on the operation of the harvester because subsystems require more power to process larger amounts of material, which includes crop plants and weeds. Vegetative index may signal where areas of dense crop plants, weeds, or combinations thereof may exist. Or for example, crop plants or weeds that have higher moisture content also take more power to process. Or for example, soil properties, such as type or moisture, can affect the power usage by the steering and propulsion systems. For instance, wet clay soils can cause additional slippage compared to dry soils which reduces the efficiency of the drive train. Or for example, topography of the field can change the power characteristics of an agricultural harvester. For instance, as the harvester ascends a hill some power needs to be diverted to the propulsion system to maintain a constant speed. Or for example, an area of the field having a higher grain yield may require that more power be diverted to the crop processing subsystems. Or for example, an area of the field containing a large biomass may require that more power be diverted to the crop processing subsystems.

(21) Some current systems provide vegetative index maps. A vegetative index map illustratively maps vegetative index values (which may be indicative of vegetative growth) across different geographic locations in a field of interest. One example of a vegetative index includes a normalized difference vegetation index (NDVI). There are many other vegetative indices that are within the scope of the present disclosure. In some examples, a vegetative index may be derived from sensor readings of one or more bands of electromagnetic radiation reflected by the plants. Without limitations, these bands may be in the microwave, infrared, visible or ultraviolet portions of the electromagnetic spectrum.

(22) A vegetative index map can be used to identify the presence and location of vegetation. In some examples, these maps enable weeds to be identified and georeferenced in the presence of bare soil, crop residue, or other plants, including crop or other weeds. For instance, at the end of a growing season, when a crop is mature, the crop plants may show a relatively low level of live, growing vegetation. However, weeds often persist in a growing state after the maturity of the crop. Therefore, if a vegetative index map is generated relatively late in the growing season, the vegetative index map may be indicative of the location of weeds in the field.

(23) Some current systems provide crop moisture maps. A crop moisture map illustratively maps crop moisture across different geographic locations in a field of interest. In one example, crop moisture can be sensed prior to a harvesting operation by an unmanned aerial vehicle (UAV) equipped with a moisture sensor. As the UAV travels across the field, the crop moisture readings are geolocated to create a crop moisture map. This is an example only and the crop moisture map can be created in other ways as well, for example, the crop moisture across a field can be predicted based on precipitation, soil moisture or combinations thereof.

(24) Some current systems provide topographic maps. A topographic map illustratively maps elevations, or other topographical characteristics of the ground across different geographic locations in a field of interest. Since ground slope is indicative of a change in elevation, having two or more elevation values allows for calculation of slope across the areas having known elevation values. Greater granularity of slope can be accomplished by having more areas with known elevation values. As an agricultural harvester travels across the terrain in known directions, the pitch and roll of the agricultural harvester can be determined based on the slope of the ground (i.e., areas of changing elevation). Topographical characteristics, when referred to below, can include, but are not limited to, the elevation, slope (e.g., including the machine orientation relative to the slope), and ground profile (e.g., roughness).

(25) Some current systems provide soil property maps. A soil property map illustratively maps soil property values (which may be indicative of topographic characteristics, soil type, soil moisture, soil cover, soil structure, as well as various other soil properties) across different geographic locations in a field of interest. The soil property maps thus provide geo-referenced soil properties across a field of interest. Topographic characteristics can include, for example, elevation data of the field, including elevation of different locations across the field, for instance, an elevation of a particular location in the field relative to a reference, such as sea level. Topographic characteristics can also include slope data of the field, including slope data of different locations across the field, for instance, slope gradient of a particular location in the field. Topographic characteristics can include various other topographic data. Soil type can refer to taxonomic units in soil science, wherein each soil type includes defined sets of shared properties. Soil types can include, for example, sandy soil, clay soil, silt soil, peat soil, chalk soil, loam soil, and various other soil types. Soil moisture can refer to the amount of water that is held or otherwise contained in the soil. Soil moisture can also be referred to as soil wetness. Soil cover can refer to the amount of items or materials covering the soil, including, vegetation material, such as crop residue or cover crop, debris, as well as various other items or materials. Commonly, in agricultural terms, soil cover includes a measure of remaining crop residue, such as a remaining mass of plant stalks, as well as a measure of cover crop. Soil structure can refer to the arrangement of solid parts of the soil and the pore space located between the solid parts of the soil. Soil structure can include the way in which individual particles, such as individual particles of sand, silt, and clay, are assembled. Soil structure can be described in terms of grade (degree of aggregation), class (average size of aggregates), and form (types of aggregates), as well as a variety of other descriptions. These are merely examples. Various other characteristics and properties of the soil can be mapped as soil property values on a soil property map.

(26) These soil property maps can be generated on the basis of data collected during another operation corresponding to the field of interest, for example, previous agricultural operations in the same season, such as planting operations or spraying operations, as well as previous agricultural operations performed in past seasons, such as a previous harvesting operation. The agricultural machines performing those agricultural operations can have on-board sensors that detect characteristics indicative of soil properties, for example, characteristics indicative of soil type, soil moisture, soil cover, soil structure, as well as various other characteristics indicative of various other soil properties. Additionally, operating characteristics, machine settings, or machine performance characteristics of the agricultural machines during previous operations along with other data can be used to generate a soil property map. For instance, header height data indicative of a height of an agricultural harvester's header across different geographic locations in the field of interest during a previous harvesting operation along with weather data that indicates weather conditions such as precipitation data or wind data during an interim period (such as the period since the time of the previous harvesting operation and the generation of the soil property map) can be used to generate a soil moisture map. For example, by knowing the height of the header, the amount of remaining plant residue, such as crop stalks, can be known or estimated and, along with precipitation data, a level of soil moisture can be predicted. This is merely an example.

(27) The present discussion also includes predictive maps that predict a characteristic based on a prior information map and a relationship to an in-situ sensor. Two of these maps include a predictive yield map and a predictive biomass map. In one example, the predictive yield map is generated by receiving a prior vegetative index map and sensing a yield during a harvesting operation and determining a relationship between the prior vegetative index map and the yield sensor signal, and using the relationship to generate the predictive yield map based on the relationship and the prior vegetative index map. In one example, the predictive biomass map is generated by receiving a prior vegetative index map and sensing a biomass and determining a relationship between the prior vegetative index map and the biomass sensor signal, and using the relationship to generate the predictive biomass map based on the relationship and the prior vegetative index map. The predictive yield and biomass maps can be created based on other prior information maps or generated in other ways as well. For example, the predictive yield and biomass maps can be generated based on a satellite or growth model.

(28) The present discussion thus proceeds with respect to examples in which a system receives one or more of a vegetative index, crop moisture, soil property, topography, predictive yield or predictive biomass map, and also uses an in-situ sensor to detect a variable indicative of a power characteristic, during a harvesting operation. The system generates a model that models a relationship between the vegetative index values, crop moisture values, soil property values, predictive yield values, or predictive biomass values from the maps and the in-situ data from the in-situ sensor. The model is used to generate a functional predictive power map that predicts an anticipated power characteristic of the agricultural

harvester **100** in the field. The functional predictive power characteristic map, generated during the harvesting operation, can be presented to an operator or other user or used in automatically controlling an agricultural harvester during the harvesting operation, or both.

(29) FIG. **1** is a partial pictorial, partial schematic, illustration of a self-propelled agricultural harvester **100**. In the illustrated example, agricultural harvester **100** is a combine harvester. Further, although combine harvesters are provided as examples throughout the present disclosure, it will be appreciated that the present description is also applicable to other types of harvesters, such as cotton harvesters, sugarcane harvesters, self-propelled forage harvesters, windrowers, or other agricultural work machines. Consequently, the present disclosure is intended to encompass the various types of harvesters described and is, thus, not limited to combine harvesters. Moreover, the present disclosure is directed to other types of work machines, such as agricultural seeders and sprayers, construction equipment, forestry equipment, and turf management equipment where generation of a predictive map may be applicable. Consequently, the present disclosure is intended to encompass these various types of harvesters and other work machines and is, thus, not limited to combine harvesters.

(30) As shown in FIG. **1**, agricultural harvester **100** illustratively includes an operator compartment **101**, which can have a variety of different operator interface mechanisms, for controlling agricultural harvester **100**. Agricultural harvester **100** includes front-end equipment, such as a header **102**, and a cutter generally indicated at **104**. Agricultural harvester **100** also includes a feeder house **106**, a feed accelerator **108**, and a thresher generally indicated at **110**. The feeder house **106** and the feed accelerator **108** form part of a material handling subsystem **125**. Header **102** is pivotally coupled to a frame **103** of agricultural harvester **100** along pivot axis **105**. One or more actuators **107** drive movement of header **102** about axis **105** in the direction generally indicated by arrow **109**. Thus, a vertical position of header **102** (the header height) above ground **111** over which the header **102** travels is controllable by actuating actuator **107**. While not shown in FIG. **1**, agricultural harvester **100** may also include one or more actuators that operate to apply a tilt angle, a roll angle, or both to the header **102** or portions of header **102**. Tilt refers to an angle at which the cutter **104** engages the crop. The tilt angle is increased, for example, by controlling header **102** to point a distal edge **113** of cutter **104** more toward the ground. The tilt angle is decreased by controlling header **102** to point the distal edge **113** of cutter **104** more away from the ground. The roll angle refers to the orientation of header **102** about the front-to-back longitudinal axis of agricultural harvester **100**.

(31) Thresher **110** illustratively includes a threshing rotor **112** and a set of concaves **114**. Further, agricultural harvester **100** also includes a separator **116**. Agricultural harvester **100** also includes a cleaning subsystem or cleaning shoe (collectively referred to as cleaning subsystem **118**) that includes a cleaning fan **120**, chaffer **122**, and sieve **124**. The material handling subsystem **125** also includes discharge beater **126**, tailings elevator **128**, clean grain elevator **130**, as well as unloading auger **134** and spout **136**. The clean grain elevator moves clean grain into clean grain tank **132**. Agricultural harvester **100** also includes a residue subsystem **138** that can include chopper **140** and spreader **142**. Agricultural harvester **100** also includes a propulsion subsystem that includes an engine that drives ground engaging components **144**, such as wheels or tracks. In some examples, a combine harvester within the scope of the present disclosure may have more than one of any of the subsystems mentioned above. In some examples, agricultural harvester **100** may have left and right cleaning subsystems, separators, etc., which are not shown in FIG. **1**.

(32) In operation, and by way of overview, agricultural harvester **100** illustratively moves through a field in the direction indicated by arrow **147**. As agricultural harvester **100** moves, header **102** (and the associated reel **164**) engages the crop to be harvested and gathers the crop toward cutter **104**. An operator of agricultural harvester **100** can be a local human operator, a remote human operator, or an automated system. An operator command is a command from an operator. The operator of agricultural harvester **100** may determine one or more of a height setting, a tilt angle setting, or a roll angle setting for header **102**. For example, the operator inputs a setting or settings to a control system, described in more detail below, that controls actuator **107**. The control system may also receive a setting from the operator for establishing the tilt angle and roll angle of the header **102** and implement the inputted settings by controlling associated actuators, not shown, that operate to change the tilt angle and roll angle of the header **102**. The actuator **107** maintains header **102** at a height above ground **111** based on a height setting and, where applicable, at desired tilt and roll angles. Each of the height, roll, and tilt settings may be implemented independently of the others. The control system responds to header error (e.g., the difference between the height setting and measured height of header **104** above ground **111** and, in some examples, tilt angle and roll angle errors) with a responsiveness that is determined based on a selected sensitivity level. If the sensitivity level is set at a greater level of sensitivity, the control system responds to smaller header position errors, and attempts to reduce the detected errors more quickly than when the sensitivity is at a lower level of sensitivity.

(33) Returning to the description of the operation of agricultural harvester **100**, after crops are cut by cutter **104**, the severed crop material is moved through a conveyor in feeder house **106** toward feed accelerator **108**, which accelerates the crop material into thresher **110**. The crop material is threshed by rotor **112** rotating the crop against concaves **114**. The threshed crop material is moved by a separator rotor in separator **116** where a portion of the residue is moved by discharge beater **126** toward the residue subsystem **138**. The portion of residue transferred to the residue subsystem **138** is chopped by residue chopper **140** and spread on the field by spreader **142**. In other configurations, the residue is released from the agricultural harvester **100** in a windrow. In other examples, the residue subsystem **138** can include weed seed eliminators (not shown) such as seed baggers or other seed collectors, or seed crushers or other seed destroyers.

(34) Grain falls to cleaning subsystem **118**. Chaffer **122** separates some larger pieces of material from the grain, and sieve **124** separates some of finer pieces of material from the clean grain. Clean grain falls to an auger that moves the grain to an inlet end of clean grain elevator **130**, and the clean grain elevator **130** moves the clean grain upwards, depositing the clean grain in clean grain tank **132**. Residue is removed from the cleaning subsystem **118** by airflow generated by cleaning fan **120**. Cleaning fan **120** directs air along an airflow path upwardly through the sieves and chaffers. The airflow carries residue rearwardly in agricultural harvester **100** toward the residue handling subsystem **138**.

(35) Tailings elevator **128** returns tailings to thresher **110** where the tailings are re-threshed. Alternatively, the tailings also may be passed to a separate re-threshing mechanism by a tailings elevator or another transport device where the tailings are re-threshed as well.

(36) FIG. **1** also shows that, in one example, agricultural harvester **100** includes ground speed sensor **146**, one or more separator loss sensors **148**, a clean grain camera **150**, a forward looking image capture mechanism **151**, which may be in the form of a stereo or mono camera, and one or more loss sensors **152** provided in the cleaning subsystem **118**.

(37) Ground speed sensor **146** senses the travel speed of agricultural harvester **100** over the ground. Ground speed sensor **146** may sense the travel speed of the agricultural harvester **100** by sensing the speed of rotation of the ground engaging components (such as wheels or tracks), a drive shaft, an axle, or other components. In some instances, the travel speed may be sensed using a positioning system, such as a global positioning system (GPS), a dead reckoning system, a long range navigation (LORAN) system, or a wide variety of other systems or sensors that provide an indication of travel speed.

(38) Loss sensors **152** illustratively provide an output signal indicative of the quantity of grain loss occurring in both the right and left sides of the cleaning subsystem **118**. In some examples, sensors **152** are strike sensors which count grain strikes per unit of time or per unit of distance traveled to provide an indication of the grain loss occurring at the cleaning subsystem **118**. The strike sensors for the right and left sides of the cleaning subsystem **118** may provide individual signals or a combined or aggregated signal. In some examples, sensors **152** may include a single sensor as opposed to separate sensors provided for each cleaning subsystem **118**.

(39) Separator loss sensor **148** provides a signal indicative of grain loss in the left and right separators, not separately shown in FIG. **1**. The separator loss sensors **148** may be associated with the left and right separators and may provide separate grain loss signals or a combined or aggregate signal. In some instances, sensing grain loss in the separators may also be performed using a wide variety of different types of sensors as well.

(40) Agricultural harvester **100** may also include other sensors and measurement mechanisms. For instance, agricultural harvester **100** may include

one or more of the following sensors: a header height sensor that senses a height of header **102** above ground **111**; stability sensors that sense oscillation or bouncing motion (and amplitude) of agricultural harvester **100**; a residue setting sensor that is configured to sense whether agricultural harvester **100** is configured to chop the residue, produce a windrow, etc.; a cleaning shoe fan speed sensor to sense the speed of fan **120**; a concave clearance sensor that senses clearance between the rotor **112** and concaves **114**; a threshing rotor speed sensor that senses a rotor speed of rotor **112**; a chaffer clearance sensor that senses the size of openings in chaffer **122**; a sieve clearance sensor that senses the size of openings in sieve **124**; a material other than grain (MOG) moisture sensor that senses a moisture level of the MOG passing through agricultural harvester **100**; one or more machine setting sensors configured to sense various configurable settings of agricultural harvester **100**; a machine orientation sensor that senses the orientation of agricultural harvester **100**; and crop property sensors that sense a variety of different types of crop properties, such as crop type, crop moisture, and other crop properties. Crop property sensors may also be configured to sense characteristics of the severed crop material as the crop material is being processed by agricultural harvester **100**. For example, in some instances, the crop property sensors may sense grain quality such as broken grain, MOG levels; grain constituents such as starches and protein; and grain feed rate as the grain travels through the feeder house **106**, clean grain elevator **130**, or elsewhere in the agricultural harvester **100**. The crop property sensors may also sense the feed rate of biomass through feeder house **106**, through the separator **116** or elsewhere in agricultural harvester **100**. The crop property sensors may also sense the feed rate as a mass flow rate of grain through elevator **130** or through other portions of the agricultural harvester **100** or provide other output signals indicative of other sensed variables.

(41) Examples of sensors used to detect or sense the power characteristics include, but are not limited to, a voltage sensor, a current sensor, a torque sensor, a hydraulic pressure sensor, a hydraulic flow sensor, a force sensor, a bearing load sensor and a rotational sensor. Power characteristics can be measured at varying levels of granularity. For instance, power usage can be sensed machine-wide, subsystem-wide or by individual components of the subsystems.

(42) Prior to describing how agricultural harvester **100** generates a functional predictive power map, and uses the functional predictive power map for control, a brief description of some of the items on agricultural harvester **100**, and their operation, will first be described. The description of FIGS. **2** and **3** describe receiving a general type of prior information map and combining information from the prior information map with a georeferenced sensor signal generated by an in-situ sensor, where the sensor signal is indicative of a characteristic in the field, such as power characteristics of the agricultural harvester. Characteristics of the field may include, but are not limited to, characteristics of a field such as slope, weed intensity, weed type, soil moisture, surface quality; characteristics of crop properties such as crop height, crop moisture, crop density, crop state; characteristics of grain properties such as grain moisture, grain size, grain test weight; and characteristics of machine performance such as loss levels, job quality, fuel consumption, and power utilization. A relationship between the characteristic values obtained from in-situ sensor signals and the prior information map values is identified, and that relationship is used to generate a new functional predictive map. A functional predictive map predicts values at different geographic locations in a field, and one or more of those values may be used for controlling a machine, such as one or more subsystems of an agricultural harvester. In some instances, a functional predictive map can be presented to a user, such as an operator of an agricultural work machine, which may be an agricultural harvester. A functional predictive map may be presented to a user visually, such as via a display, haptically, or audibly. The user may interact with the functional predictive map to perform editing operations and other user interface operations. In some instances, a functional predictive map can be used for one or more of controlling an agricultural work machine, such as an agricultural harvester, presentation to an operator or other user, and presentation to an operator or user for interaction by the operator or user.

(43) After the general approach is described with respect to FIGS. **2** and **3**, a more specific approach for generating a functional predictive power characteristic map that can be presented to an operator or user, or used to control agricultural harvester **100**, or both is described with respect to FIGS. **4** and **5**. Again, while the present discussion proceeds with respect to the agricultural harvester and, particularly, a combine harvester, the scope of the present disclosure encompasses other types of agricultural harvesters or other agricultural work machines.

(44) FIG. **2** is a block diagram showing some portions of an example agricultural harvester **100**. FIG. **2** shows that agricultural harvester **100** illustratively includes one or more processors or servers **201**, data store **202**, geographic position sensor **204**, communication system **206**, and one or more in-situ sensors **208** that sense one or more agricultural characteristics of a field concurrent with a harvesting operation. An agricultural characteristic can include any characteristic that can have an effect of the harvesting operation. Some examples of agricultural characteristics include characteristics of the harvesting machine, the field, the plants on the field, and the weather. Other types of agricultural characteristics are also included. An agricultural characteristic can include any characteristic that can have an effect of the harvesting operation. Some examples of agricultural characteristics include characteristics of the harvesting machine, the field, the plants on the field, the weather among others. The in-situ sensors **208** generate values corresponding to the sensed characteristics. The agricultural harvester **100** also includes a predictive model or relationship generator (collectively referred to hereinafter as “predictive model generator **210**”), predictive map generator **212**, control zone generator **213**, control system **214**, one or more controllable subsystems **216**, and an operator interface mechanism **218**. The agricultural harvester **100** can also include a wide variety of other agricultural harvester functionality **220**. The in-situ sensors **208** include, for example, on-board sensors **222**, remote sensors **224**, and other sensors **226** that sense characteristics of a field during the course of an agricultural operation. Predictive model generator **210** illustratively includes a prior information variable-to-in-situ variable model generator **228**, and predictive model generator **210** can include other items **230**. Control system **214** includes communication system controller **229**, operator interface controller **231**, a settings controller **232**, path planning controller **234**, feed rate controller **236**, header and reel controller **238**, draper belt controller **240**, deck plate position controller **242**, residue system controller **244**, machine cleaning controller **245**, zone controller **247**, and system **214** can include other items **246**. Controllable subsystems **216** include machine and header actuators **248**, propulsion subsystem **250**, steering subsystem **252**, residue subsystem **138**, machine cleaning subsystem **254**, and subsystems **216** can include a wide variety of other subsystems **256**.

(45) FIG. **2** also shows that agricultural harvester **100** can receive prior information map **258**. As described below, the prior information map **258** includes, for example, a vegetative index map or a vegetation map from a prior operation. However, prior information map **258** may also encompass other types of data that were obtained prior to a harvesting operation or a map from a prior operation. FIG. **2** also shows that an operator **260** may operate the agricultural harvester **100**. The operator **260** interacts with operator interface mechanisms **218**. In some examples, operator interface mechanisms **218** may include joysticks, levers, a steering wheel, linkages, pedals, buttons, dials, keypads, user actuable elements (such as icons, buttons, etc.) on a user interface display device, a microphone and speaker (where speech recognition and speech synthesis are provided), among a wide variety of other types of control devices. Where a touch sensitive display system is provided, operator **260** may interact with operator interface mechanisms **218** using touch gestures. These examples described above are provided as illustrative examples and are not intended to limit the scope of the present disclosure. Consequently, other types of operator interface mechanisms **218** may be used and are within the scope of the present disclosure.

(46) Prior information map **258** may be downloaded onto agricultural harvester **100** and stored in data store **202**, using communication system **206** or in other ways. In some examples, communication system **206** may be a cellular communication system, a system for communicating over a wide area network or a local area network, a system for communicating over a near field communication network, or a communication system configured to communicate over any of a variety of other networks or combinations of networks. Communication system **206** may also include a system that facilitates downloads or transfers of information to and from a secure digital (SD) card or a universal serial bus (USB) card or both.

(47) Geographic position sensor **204** illustratively senses or detects the geographic position or location of agricultural harvester **100**. Geographic position sensor **204** can include, but is not limited to, a global navigation satellite system (GNSS) receiver that receives signals from a GNSS satellite transmitter. Geographic position sensor **204** can also include a real-time kinematic (RTK) component that is configured to enhance the

precision of position data derived from the GNSS signal. Geographic position sensor **204** can include a dead reckoning system, a cellular triangulation system, or any of a variety of other geographic position sensors.

(48) In-situ sensors **208** may be any of the sensors described above with respect to FIG. **1**. In-situ sensors **208** include on-board sensors **222** that are mounted on-board agricultural harvester **100**. Such sensors may include, for instance, a perception sensor (e.g., a forward looking mono or stereo camera system and image processing system), image sensors that are internal to agricultural harvester **100** (such as the clean grain camera or cameras mounted to identify weed seeds that are exiting agricultural harvester **100** through the residue subsystem or from the cleaning subsystem). The in-situ sensors **208** also include remote in-situ sensors **224** that capture in-situ information. In-situ data include data taken from a sensor on-board the harvester or taken by any sensor where the data are detected during the harvesting operation.

(49) Predictive model generator **210** generates a model that is indicative of a relationship between the values sensed by the in-situ sensor **208** and a metric mapped to the field by the prior information map **258**. For example, if the prior information map **258** maps a vegetative index value to different locations in the field, and the in-situ sensor **208** is sensing a value indicative of header power usage, then prior information variable-to-in-situ variable model generator **228** generates a predictive power model that models the relationship between the vegetative index value and the header power usage value. The predictive power model can also be generated based on vegetative index values from the prior information map **258** and multiple in-situ data values generated by in-situ sensors **208**. Then, predictive map generator **212** uses the predictive power model generated by predictive model generator **210** to generate a functional predictive power map that predicts the value of a power characteristic, such as power usage by a subsystem, sensed by the in-situ sensors **208** at different locations in the field based upon the prior information map **258**.

(50) In some examples, the type of values in the functional predictive map **263** may be the same as the in-situ data type sensed by the in-situ sensors **208**. In some instances, the type of values in the functional predictive map **263** may have different units from the data sensed by the in-situ sensors **208**. In some examples, the type of values in the functional predictive map **263** may be different from the data type sensed by the in-situ sensors **208** but have a relationship to the type of data type sensed by the in-situ sensors **208**. For example, in some examples, the data type sensed by the in-situ sensors **208** may be indicative of the type of values in the functional predictive map **263**. In some examples, the type of data in the functional predictive map **263** may be different than the data type in the prior information map **258**. In some instances, the type of data in the functional predictive map **263** may have different units from the data in the prior information map **258**. In some examples, the type of data in the functional predictive map **263** may be different from the data type in the prior information map **258** but has a relationship to the data type in the prior information map **258**. For example, in some examples, the data type in the prior information map **258** may be indicative of the type of data in the functional predictive map **263**. In some examples, the type of data in the functional predictive map **263** is different than one of, or both of, the in-situ data type sensed by the in-situ sensors **208** and the data type in the prior information map **258**. In some examples, the type of data in the functional predictive map **263** is the same as one of, or both of, of the in-situ data type sensed by the in-situ sensors **208** and the data type in prior information map **258**. In some examples, the type of data in the functional predictive map **263** is the same as one of the in-situ data type sensed by the in-situ sensors **208** or the data type in the prior information map **258**, and different than the other.

(51) Continuing with the preceding example, in which prior information map **258** is a vegetative index map and in-situ sensor **208** senses a value indicative of header power usage, predictive map generator **212** can use the vegetative index values in prior information map **258**, and the model generated by predictive model generator **210**, to generate a functional predictive map **263** that predicts the header power usage at different locations in the field. Predictive map generator **212** thus outputs predictive map **264**.

(52) As shown in FIG. **2**, predictive map **264** predicts the value of a sensed characteristic (sensed by in-situ sensors **208**), or a characteristic related to the sensed characteristic, at various locations across the field based upon a prior information value in prior information map **258** at those locations and the predictive model. For example, if predictive model generator **210** has generated a predictive model indicative of a relationship between a vegetative index value and header power usage, then, given the vegetative index value at different locations across the field, predictive map generator **212** generates a predictive map **264** that predicts the value of the header power usage at different locations across the field. The vegetative index value, obtained from the vegetative index map, at those locations and the relationship between vegetative index value and header power usage, obtained from the predictive model, are used to generate the predictive map **264**.

(53) Some variations in the data types that are mapped in the prior information map **258**, the data types sensed by in-situ sensors **208**, and the data types predicted on the predictive map **264** will now be described.

(54) In some examples, the data type in the prior information map **258** is different from the data type sensed by in-situ sensors **208**, yet the data type in the predictive map **264** is the same as the data type sensed by the in-situ sensors **208**. For instance, the prior information map **258** may be a vegetative index map, and the variable sensed by the in-situ sensors **208** may be a power characteristic. The predictive map **264** may then be a predictive power characteristic map that maps predicted power characteristic values to different geographic locations in the field. predictive map **264**

(55) Also, in some examples, the data type in the prior information map **258** is different from the data type sensed by in-situ sensors **208**, and the data type in the predictive map **264** is different from both the data type in the prior information map **258** and the data type sensed by the in-situ sensors **208**. For instance, the prior information map **258** may be a topographic map, and the variable sensed by the in-situ sensors **208** may be a thresher power characteristic. The predictive map **264** may then be a predictive biomass map that maps predicted biomass values to different geographic locations in the field. predictive map **264**

(56) In some examples, the prior information map **258** is from a prior pass through the field during a prior operation and the data type is different from the data type sensed by in-situ sensors **208**, yet the data type in the predictive map **264** is the same as the data type sensed by the in-situ sensors **208**. For instance, the prior information map **258** may be a topographic map generated during planting or spraying, and the variable sensed by the in-situ sensors **208** may be a power characteristic. The predictive map **264** may then be a predictive power characteristic map that maps predicted power characteristic values to different geographic locations in the field. predictive map **264**

(57) In some examples, the prior information map **258** is from a prior pass through the field during a prior operation and the data type is the same as the data type sensed by in-situ sensors **208**, and the data type in the predictive map **264** is also the same as the data type sensed by the in-situ sensors **208**. For instance, the prior information map **258** may be a power characteristic map generated during a previous year, and the variable sensed by the in-situ sensors **208** may be a power characteristic. The predictive map **264** may then be a predictive power characteristic map that maps predicted power characteristic values to different geographic locations in the field. In such an example, the relative power characteristic differences in the georeferenced prior information map **258** from the prior year can be used by predictive model generator **210** to generate a predictive model that models a relationship between the relative power characteristic differences on the prior information map **258** and the power characteristic values sensed by in-situ sensors **208** during the current harvesting operation. The predictive model is then used by predictive map generator **210** to generate a predictive power characteristic map.

(58) In another example, the prior information map **258** may be a threshing/separating subsystem power usage map generated during a prior operation, and the variable sensed by the in-situ sensors **208** may be threshing/separating subsystems power usage. The predictive map **264** may then be a predictive threshing/separating subsystems power usage map that maps predicted threshing/separating subsystems power usage values to different geographic locations in the field.

(59) In some examples, predictive map **264** can be provided to the control zone generator **213**. Control zone generator **213** groups adjacent portions of an area into one or more control zones based on data values of predictive map **264** that are associated with those adjacent portions. A control zone may include two or more contiguous portions of an area, such as a field, for which a control parameter corresponding to the control zone for

controlling a controllable subsystem is constant. For example, a response time to alter a setting of controllable subsystems **216** may be inadequate to satisfactorily respond to changes in values contained in a map, such as predictive map **264**. In that case, control zone generator **213** parses the map and identifies control zones that are of a defined size to accommodate the response time of the controllable subsystems **216**. In another example, control zones may be sized to reduce wear from excessive actuator movement resulting from continuous adjustment. In some examples, there may be a different set of control zones for each controllable subsystem **216** or for groups of controllable subsystems **216**. The control zones may be added to the predictive map **264** to obtain predictive control zone map **265**. Predictive control zone map **265** can thus be similar to predictive map **264** except that predictive control zone map **265** includes control zone information defining the control zones. Thus, a functional predictive map **263**, as described herein, may or may not include control zones. Both predictive map **264** and predictive control zone map **265** are functional predictive maps **263**. In one example, a functional predictive map **263** does not include control zones, such as predictive map **264**. In another example, a functional predictive map **263** does include control zones, such as predictive control zone map **265**. In some examples, multiple crops may be simultaneously present in a field if an intercrop production system is implemented. In that case, predictive map generator **212** and control zone generator **213** are able to identify the location and characteristics of the two or more crops and then generate predictive map **264** and predictive control zone map **265** accordingly.

(60) It will also be appreciated that control zone generator **213** can cluster values to generate control zones and the control zones can be added to predictive control zone map **265**, or a separate map, showing only the control zones that are generated. In some examples, the control zones may be used for controlling or calibrating agricultural harvester **100** or both. In other examples, the control zones may be presented to the operator **260** and used to control or calibrate agricultural harvester **100**, and, in other examples, the control zones may be presented to the operator **260** or another user or stored for later use.

(61) Predictive map **264** or predictive control zone map **265** or both are provided to control system **214**, which generates control signals based upon the predictive map **264** or predictive control zone map **265** or both. In some examples, communication system controller **229** controls communication system **206** to communicate the predictive map **264** or predictive control zone map **265** or control signals based on the predictive map **264** or predictive control zone map **265** to other agricultural harvesters that are harvesting in the same field. In some examples, communication system controller **229** controls the communication system **206** to send the predictive map **264**, predictive control zone map **265**, or both to other remote systems.

(62) Operator interface controller **231** is operable to generate control signals to control operator interface mechanisms **218**. The operator interface controller **231** is also operable to present the predictive map **264** or predictive control zone map **265** or other information derived from or based on the predictive map **264**, predictive control zone map **265**, or both to operator **260**. Operator **260** may be a local operator or a remote operator. As an example, controller **231** generates control signals to control a display mechanism to display one or both of predictive map **264** and predictive control zone map **265** for the operator **260**. Controller **231** may generate operator actuatable mechanisms that are displayed and can be actuated by the operator to interact with the displayed map. The operator can edit the map by, for example, correcting a power characteristic displayed on the map, based on the operator's observation. Settings controller **232** can generate control signals to control various settings on the agricultural harvester **100** based upon predictive map **264**, the predictive control zone map **265**, or both. For instance, settings controller **232** can generate control signals to control machine and header actuators **248**. In response to the generated control signals, the machine and header actuators **248** operate to control, for example, one or more of the sieve and chaffer settings, concave clearance, rotor settings, cleaning fan speed settings, header height, header functionality, reel speed, reel position, draper functionality (where agricultural harvester **100** is coupled to a draper header), corn header functionality, internal distribution control and other actuators **248** that affect the other functions of the agricultural harvester **100**. Path planning controller **234** illustratively generates control signals to control steering subsystem **252** to steer agricultural harvester **100** according to a desired path. Path planning controller **234** can control a path planning system to generate a route for agricultural harvester **100** and can control propulsion subsystem **250** and steering subsystem **252** to steer agricultural harvester **100** along that route. Feed rate controller **236** can control various subsystems, such as propulsion subsystem **250** and machine actuators **248**, to control a feed rate based upon the predictive map **264** or predictive control zone map **265** or both. For instance, as agricultural harvester **100** approaches an area having a predicted subsystem power usage value above a selected threshold, feed rate controller **236** may reduce the speed of agricultural harvester **100** to maintain power allocation to the predicted power usage requirements of the one or more subsystems. Header and reel controller **238** can generate control signals to control a header or a reel or other header functionality. Draper belt controller **240** can generate control signals to control a draper belt or other draper functionality based upon the predictive map **264**, predictive control zone map **265**, or both. Deck plate position controller **242** can generate control signals to control a position of a deck plate included on a header based on predictive map **264** or predictive control zone map **265** or both, and residue system controller **244** can generate control signals to control a residue subsystem **138** based upon predictive map **264** or predictive control zone map **265**, or both. Machine cleaning controller **245** can generate control signals to control machine cleaning subsystem **254**. For instance, based upon the different predicted power usage of agricultural harvester **100**, a particular type of machine cleaning operation or a frequency with which a cleaning operation is performed may be controlled. Other controllers included on the agricultural harvester **100** can control other subsystems based on the predictive map **264** or predictive control zone map **265** or both as well.

(63) FIGS. 3A and 3B (collectively referred to herein as FIG. 3) show a flow diagram illustrating one example of the operation of agricultural harvester **100** in generating a predictive map **264** and predictive control zone map **265** based upon prior information map **258**.

(64) At **280**, agricultural harvester **100** receives prior information map **258**. Examples of prior information map **258** or receiving prior information map **258** are discussed with respect to blocks **281**, **282**, **284** and **286**. As discussed above, prior information map **258** maps values of a variable, corresponding to a first characteristic, to different locations in the field, as indicated at block **282**. As indicated at block **281**, receiving the prior information map **258** may involve selecting one or more of a plurality of possible prior information maps that are available. For instance, one prior information map may be a vegetative index map generated from aerial imagery. Another prior information map may be a map generated during a prior pass through the field which may have been performed by a different machine performing a previous operation in the field, such as a sprayer or other machine. The process by which one or more prior information maps are selected can be manual, semi-automated, or automated. The prior information map **258** is based on data collected prior to a current harvesting operation. This is indicated by block **284**. For instance, the data may be collected based on aerial images taken during a previous year, or earlier in the current growing season, or at other times. As indicated by block **285**, the prior information map can be a predictive map that predicts a characteristic based on a prior information map and a relationship to an in-situ sensor. A process of generating a predictive map is presented in FIG. 5. This process could also be performed with other sensors and other prior maps to generate, for example, predictive yield maps or predictive biomass maps. These predictive maps can be used as prior maps in other predictive processes, as indicated by block **285**. The data may be based on data detected in ways other than using aerial images. For instance, the data for the prior information map **258** can be transmitted to agricultural harvester **100** using communication system **206** and stored in data store **202**. The data for the prior information map **258** can be provided to agricultural harvester **100** using communication system **206** in other ways as well, and this is indicated by block **286** in the flow diagram of FIG. 3. In some examples, the prior information map **258** can be received by communication system **206**.

(65) Upon commencement of a harvesting operation, in-situ sensors **208** generate sensor signals indicative of one or more in-situ data values indicative of a characteristic, for example, a power characteristic, such as a power usage by one or more subsystems, as indicated by block **288**. Examples of in-situ sensors **208** are discussed with respect to blocks **222**, **290**, and **226**. As explained above, the in-situ sensors **208** include on-board sensors **222**; remote in-situ sensors **224**, such as UAV-based sensors flown at a time to gather in-situ data, shown in block **290**; or other types

of in-situ sensors, designated by sensor **226**. In some examples, data from on-board sensors is georeferenced using position, heading, or speed data from geographic position sensor **204**.

(66) Predictive model generator **210** controls the prior information variable-to-in-situ variable model generator **228** to generate a model that models a relationship between the mapped values contained in the prior information map **258** and the in-situ values sensed by the in-situ sensors **208** as indicated by block **292**. The characteristics or data types represented by the mapped values in the prior information map **258** and the in-situ values sensed by the in-situ sensors **208** may be the same characteristics or data type or different characteristics or data types.

(67) The relationship or model generated by predictive model generator **210** is provided to predictive map generator **212**. Predictive map generator **212** generates a predictive map **264** that predicts a value of the characteristic sensed by the in-situ sensors **208** at different geographic locations in a field being harvested, or a different characteristic that is related to the characteristic sensed by the in-situ sensors **208**, using the predictive model and the prior information map **258**, as indicated by block **294**.

(68) It should be noted that, in some examples, the prior information map **258** may include two or more different maps or two or more different map layers of a single map. Each map layer may represent a different data type from the data type of another map layer or the map layers may have the same data type that were obtained at different times. Each map in the two or more different maps or each layer in the two or more different map layers of a map maps a different type of variable to the geographic locations in the field. In such an example, predictive model generator **210** generates a predictive model that models the relationship between the in-situ data and each of the different variables mapped by the two or more different maps or the two or more different map layers. Similarly, the in-situ sensors **208** can include two or more sensors each sensing a different type of variable. Thus, the predictive model generator **210** generates a predictive model that models the relationships between each type of variable mapped by the prior information map **258** and each type of variable sensed by the in-situ sensors **208**. Predictive map generator **212** can generate a functional predictive map **263** that predicts a value for each sensed characteristic sensed by the in-situ sensors **208** (or a characteristic related to the sensed characteristic) at different locations in the field being harvested using the predictive model and each of the maps or map layers in the prior information map **258**.

(69) Predictive map generator **212** configures the predictive map **264** so that the predictive map **264** is actionable (or consumable) by control system **214**. Predictive map generator **212** can provide the predictive map **264** to the control system **214** or to control zone generator **213** or both. Some examples of different ways in which the predictive map **264** can be configured or output are described with respect to blocks **296**, **295**, **299** and **297**. For instance, predictive map generator **212** configures predictive map **264** so that predictive map **264** includes values that can be read by control system **214** and used as the basis for generating control signals for one or more of the different controllable subsystems of the agricultural harvester **100**, as indicated by block **296**.

(70) Control zone generator **213** can divide the predictive map **264** into control zones based on the values on the predictive map **264**. Contiguously-geolocated values that are within a threshold value of one another can be grouped into a control zone. The threshold value can be a default threshold value, or the threshold value can be set based on an operator input, based on an input from an automated system, or based on other criteria. A size of the zones may be based on a responsiveness of the control system **214**, the controllable subsystems **216**, based on wear considerations, or on other criteria as indicated by block **295**. Predictive map generator **212** configures predictive map **264** for presentation to an operator or other user. Control zone generator **213** can configure predictive control zone map **265** for presentation to an operator or other user. This is indicated by block **299**. When presented to an operator or other user, the presentation of the predictive map **264** or predictive control zone map **265** or both may contain one or more of the predictive values on the predictive map **264** correlated to geographic location, the control zones on predictive control zone map **265** correlated to geographic location, and settings values or control parameters that are used based on the predicted values on map **264** or zones on predictive control zone map **265**. The presentation can, in another example, include more abstracted information or more detailed information. The presentation can also include a confidence level that indicates an accuracy with which the predictive values on predictive map **264** or the zones on predictive control zone map **265** conform to measured values that may be measured by sensors on agricultural harvester **100** as agricultural harvester **100** moves through the field. Further where information is presented to more than one location, an authentication and authorization system can be provided to implement authentication and authorization processes. For instance, there may be a hierarchy of individuals that are authorized to view and change maps and other presented information. By way of example, an on-board display device may show the maps in near real time locally on the machine, or the maps may also be generated at one or more remote locations, or both. In some examples, each physical display device at each location may be associated with a person or a user permission level. The user permission level may be used to determine which display markers are visible on the physical display device and which values the corresponding person may change. As an example, a local operator of agricultural harvester **100** may be unable to see the information corresponding to the predictive map **264** or make any changes to machine operation. A supervisor, such as a supervisor at a remote location, however, may be able to see the predictive map **264** on the display but be prevented from making any changes. A manager, who may be at a separate remote location, may be able to see all of the elements on predictive map **264** and also be able to change the predictive map **264**. In some instances, the predictive map **264** accessible and changeable by a manager located remotely may be used in machine control. This is one example of an authorization hierarchy that may be implemented. The predictive map **264** or predictive control zone map **265** or both can be configured in other ways as well, as indicated by block **297**.

(71) At block **298**, input from geographic position sensor **204** and other in-situ sensors **208** are received by the control system. Particularly, at block **300**, control system **214** detects an input from the geographic position sensor **204** identifying a geographic location of agricultural harvester **100**. Block **302** represents receipt by the control system **214** of sensor inputs indicative of trajectory or heading of agricultural harvester **100**, and block **304** represents receipt by the control system **214** of a speed of agricultural harvester **100**. Block **306** represents receipt by the control system **214** of other information from various in-situ sensors **208**.

(72) At block **308**, control system **214** generates control signals to control the controllable subsystems **216** based on the predictive map **264** or predictive control zone map **265** or both and the input from the geographic position sensor **204** and any other in-situ sensors **208**. At block **310**, control system **214** applies the control signals to the controllable subsystems. It will be appreciated that the particular control signals that are generated, and the particular controllable subsystems **216** that are controlled, may vary based upon one or more different things. For example, the control signals that are generated and the controllable subsystems **216** that are controlled may be based on the type of predictive map **264** or predictive control zone map **265** or both that is being used. Similarly, the control signals that are generated and the controllable subsystems **216** that are controlled and the timing of the control signals can be based on various latencies of crop flow through the agricultural harvester **100** and the responsiveness of the controllable subsystems **216**.

(73) By way of example, a generated predictive map **264** in the form of a predictive power map can be used to control one or more subsystems **216**. For instance, the predictive power map can include power usage requirement values georeferenced to locations within the field being harvested. The power usage requirement values from the predictive power map can be extracted and used to control the steering and propulsion subsystems **252** and **250**. By controlling the steering and propulsion subsystems **252** and **250**, a feed rate of material moving through the agricultural harvester **100** can be controlled. Similarly, the header height can be controlled to take in more or less material, and, thus, the header height can also be controlled to control feed rate of material through the agricultural harvester **100**. In other examples, if the predictive map **264** maps predicted header power usage to positions in the field, power allocation to the header can be implemented. For example, if the values present in the predictive power map indicate one or more areas having higher power usage requirements for the header subsystems, then header and reel controller **238** can allocate more power from the engine to the header subsystems, this may require allocating less power to other subsystems, such as by reducing

speed and reducing power to the propulsion subsystem. The preceding example involving header control using a predictive power map is provided merely as an example. Consequently, a wide variety of other control signals can be generated using values obtained from a predictive power map or other type of predictive map to control one or more of the controllable subsystems **216**.

(74) At block **312**, a determination is made as to whether the harvesting operation has been completed. If harvesting is not completed, the processing advances to block **314** where in-situ sensor data from geographic position sensor **204** and in-situ sensors **208** (and perhaps other sensors) continue to be read.

(75) In some examples, at block **316**, agricultural harvester **100** can also detect learning trigger criteria to perform machine learning on one or more of the predictive map **264**, predictive control zone map **265**, the model generated by predictive model generator **210**, the zones generated by control zone generator **213**, one or more control algorithms implemented by the controllers in the control system **214**, and other triggered learning.

(76) The learning trigger criteria can include any of a wide variety of different criteria. Some examples of detecting trigger criteria are discussed with respect to blocks **318**, **320**, **321**, **322** and **324**. For instance, in some examples, triggered learning can involve recreation of a relationship used to generate a predictive model when a threshold amount of in-situ sensor data are obtained from in-situ sensors **208**. In such examples, receipt of an amount of in-situ sensor data from the in-situ sensors **208** that exceeds a threshold triggers or causes the predictive model generator **210** to generate a new predictive model that is used by predictive map generator **212**. Thus, as agricultural harvester **100** continues a harvesting operation, receipt of the threshold amount of in-situ sensor data from the in-situ sensors **208** triggers the creation of a new relationship represented by a predictive model generated by predictive model generator **210**. Further, new predictive map **264**, predictive control zone map **265**, or both can be regenerated using the new predictive model. Block **318** represents detecting a threshold amount of in-situ sensor data used to trigger creation of a new predictive model.

(77) In other examples, the learning trigger criteria may be based on how much the in-situ sensor data from the in-situ sensors **208** are changing, such as over time or compared to previous values. For example, if variations within the in-situ sensor data (or the relationship between the in-situ sensor data and the information in prior information map **258**) are within a selected range or is less than a defined amount, or below a threshold value, then a new predictive model is not generated by the predictive model generator **210**. As a result, the predictive map generator **212** does not generate a new predictive map **264**, predictive control zone map **265**, or both. However, if variations within the in-situ sensor data are outside of the selected range, are greater than the defined amount, or are above the threshold value, for example, then the predictive model generator **210** generates a new predictive model using all or a portion of the newly received in-situ sensor data that the predictive map generator **212** uses to generate a new predictive map **264**. At block **320**, variations in the in-situ sensor data, such as a magnitude of an amount by which the data exceeds the selected range or a magnitude of the variation of the relationship between the in-situ sensor data and the information in the prior information map **258**, can be used as a trigger to cause generation of a new predictive model and predictive map. Keeping with the examples described above, the threshold, the range, and the defined amount can be set to default values; set by an operator or user interaction through a user interface; set by an automated system; or set in other ways.

(78) Other learning trigger criteria can also be used. For instance, if predictive model generator **210** switches to a different prior information map (different from the originally selected prior information map **258**), then switching to the different prior information map may trigger re-learning by predictive model generator **210**, predictive map generator **212**, control zone generator **213**, control system **214**, or other items. In another example, transitioning of agricultural harvester **100** to a different topography or to a different control zone may be used as learning trigger criteria as well.

(79) In some instances, operator **260** can also edit the predictive map **264** or predictive control zone map **265** or both. The edits can change a value on the predictive map **264**, change a size, shape, position, or existence of a control zone on predictive control zone map **265**, or both. Block **321** shows that edited information can be used as learning trigger criteria.

(80) In some instances, it may also be that operator **260** observes that automated control of a controllable subsystem, is not what the operator desires. In such instances, the operator **260** may provide a manual adjustment to the controllable subsystem reflecting that the operator **260** desires the controllable subsystem to operate in a different way than is being commanded by control system **214**. Thus, manual alteration of a setting by the operator **260** can cause one or more of predictive model generator **210** to relearn a model, predictive map generator **212** to regenerate map **264**, control zone generator **213** to regenerate one or more control zones on predictive control zone map **265**, and control system **214** to relearn a control algorithm or to perform machine learning on one or more of the controller components **232** through **246** in control system **214** based upon the adjustment by the operator **260**, as shown in block **322**. Block **324** represents the use of other triggered learning criteria.

(81) In other examples, relearning may be performed periodically or intermittently based, for example, upon a selected time interval such as a discrete time interval or a variable time interval, as indicated by block **326**.

(82) If relearning is triggered, whether based upon learning trigger criteria or based upon passage of a time interval, as indicated by block **326**, then one or more of the predictive model generator **210**, predictive map generator **212**, control zone generator **213**, and control system **214** performs machine learning to generate a new predictive model, a new predictive map, a new control zone, and a new control algorithm, respectively, based upon the learning trigger criteria. The new predictive model, the new predictive map, and the new control algorithm are generated using any additional data that has been collected since the last learning operation was performed. Performing relearning is indicated by block **328**.

(83) If the harvesting operation has been completed, operation moves from block **312** to block **330** where one or more of the predictive map **264**, predictive control zone map **265**, and predictive model generated by predictive model generator **210** are stored. The predictive map **264**, predictive control zone map **265**, and predictive model may be stored locally on data store **202** or sent to a remote system using communication system **206** for later use.

(84) It will be noted that while some examples herein describe predictive model generator **210** and predictive map generator **212** receiving a prior information map in generating a predictive model and a functional predictive map, respectively, in other examples, the predictive model generator **210** and predictive map generator **212** can receive, in generating a predictive model and a functional predictive map, respectively, other types of maps, including predictive maps, such as a functional predictive map generated during the harvesting operation. The other types of maps, including predictive maps, such as a functional predictive map generated during the harvesting operation, can be used by the predictive model generator **210** and the predictive map generator **212** similarly as the prior information map, in that a predictive model and a predictive map can be generated using the other types of maps, including predictive map, such as a functional predictive map generated during the harvesting operation, as an input.

(85) FIG. 4 is a block diagram of a portion of the agricultural harvester **100** shown in FIG. 1. Particularly, FIG. 4 shows, among other things, examples of the predictive model generator **210** and the predictive map generator **212** in more detail. FIG. 4 also illustrates information flow among the various components shown. The predictive model generator **210** receives one or more of a vegetative index map **332**, a crop moisture map **335**, a topographic map **337**, a soil property map **339**, a predictive yield map **341**, or a predictive biomass map **343** as a prior information map. Vegetative index map **332** includes georeferenced vegetative index values. Crop moisture map **335** includes georeferenced crop moisture values. Topographic map **337** includes georeferenced topographic characteristic values. Soil property map **339** includes georeferenced soil property values.

(86) Predictive yield map **341** includes georeferenced predictive yield values. Predictive yield map **341** can be generated using a process described in FIGS. 2 and 3, where the prior information map includes a vegetative index map or a historical yield map and the in-situ sensor includes a yield sensor. Predictive yield map **341** can be generated in other ways as well.

(87) Predictive biomass map **343** includes georeferenced predictive biomass values. Predictive biomass map **343** can be generated using a process described in FIGS. 2 and 3, where the prior information map includes a vegetative index map the in-situ sensor includes a rotor drive pressure or optical sensor, that generate sensor signals indicative of biomass. Predictive biomass map **343** can be generated in other ways as well.

(88) Predictive model generator **210** also receives a geographic location **334**, or an indication of a geographic location, from geographic position sensor **204**. In-situ sensors **208** illustratively include a power characteristic sensor, such as power sensor **336**, as well as a processing system **338**. Power sensor **336** senses one or more power characteristics of one or more components of agricultural harvester **100**. In some instances, power sensor **336** may be located on board the agricultural harvester **100**. The processing system **338** processes sensor data generated from power sensor **336** to generate processed data, some examples of which are described below. Power sensor **336** can include, but is not limited to, one or more of a voltage sensor, a current sensor, a torque sensor, a fluid pressure sensor, a fluid flow sensor, a force sensor, a bearing load sensor and a rotational sensor. The outputs of one or more of these or other sensors can be combined to determine one or more power characteristics.

(89) The present discussion proceeds with respect to an example in which power sensor **336** is one or more of the above listed. It will be appreciated that these are just examples, and other examples of power sensor **336**, are contemplated herein as well. As shown in FIG. **4**, the example predictive model generator **210** includes one or more of a vegetative index-power characteristic model generator **342**, crop moisture-power characteristic model generator **343**, topographic-power characteristic model generator **344**, soil property characteristic-power characteristic model generator **345**, yield-power characteristic model generator **346**, biomass-power characteristic model generator **347**. In other examples, the predictive model generator **210** may include additional, fewer, or different components than those shown in the example of FIG. **4**. Consequently, in some examples, the predictive model generator **210** may include other items **348** as well, which may include other types of predictive model generators to generate other types of power models.

(90) Model generator **342** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and vegetative index values from the vegetative index map **332** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **342**, model generator **342** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the georeferenced vegetative index values contained in the vegetative index map **332** at the same locations in the field.

(91) Model generator **343** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and crop moisture values from the crop moisture map **335** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **343**, model generator **343** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the georeferenced crop moisture values contained in the crop moisture map **335** at the same locations in the field.

(92) Model generator **344** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and a topographic feature value from the topographic map **337** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **344**, model generator **344** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the georeferenced topographic feature values contained in the topographic map **337** at the same locations in the field.

(93) Model generator **345** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and a soil property value from the soil property map **339** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **345**, model generator **345** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the soil property values contained in the soil property map **339** at the same locations in the field.

(94) Model generator **346** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and a yield value from the yield map **341** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **346**, model generator **346** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the yield value contained in the predictive yield map **341** at the same locations in the field.

(95) Model generator **347** identifies a relationship between a power characteristic, at a geographic location corresponding to where power sensor **336** sensed the characteristic, and a biomass value from the biomass map **343** corresponding to the same location in the field where the power characteristic was sensed. Based on this relationship established by model generator **347**, model generator **347** generates a predictive power model **350**. The predictive power model **350** is used by predictive map generator **212** to predict power characteristics at different locations in the field based upon the biomass value contained in the predictive biomass map **343** at the same locations in the field.

(96) In light of the above, the predictive model generator **210** is operable to produce a plurality of predictive power models, such as one or more of the predictive power models generated by model generators **342**, **343**, **344**, **345**, **346**, and **347**. In another example, two or more of the predictive power models described above may be combined into a single predictive power model that predicts two or more power characteristics based upon the different values at different locations in the field. Any of these power models, or combinations thereof, are represented collectively by power model **350** in FIG. **4**.

(97) The predictive power model **350** is provided to predictive map generator **212**. In the example of FIG. **4**, predictive map generator **212** includes a crop engaging component map generator **351**, a header power map generator **352**, a feeder power map generator **353**, a threshing power map generator **354**, a separator power map generator **355**, a residue handling power map generator **356**, and a propulsion power map generator **357**. In other examples, the predictive map generator **212** may include additional, fewer, or different map generators. Thus, in some examples, the predictive map generator **212** may include other items **358** which may include other types of map generators to generate power maps for other types of power characteristics.

(98) Crop engaging component map generator **351** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of a crop engaging component at different locations in the field. For example, the crop engaging components could include a cutter and a reel and the crop engaging component map generator **351** generates a map of estimated power usage by the reel and cutter based on a predictive power model **350** that defines a relationship between crop moisture and power usage by the reel and cutter.

(99) Header power map generator **352** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the header at different locations in the field. For example, the crop engaging components could include one or more of: a cutter, a reel, draper belts, augers, and header positioning actuators and the header power map generator **352** generates a map of estimated power usage by one or more of: the reel, the cutter, draper belts, augers, and header positioning actuators based on a predictive power model **350** that defines a relationship between crop moisture and topography, and power usage by one or more of the reel, the cutter, draper belts, auger, and header positioning actuators.

(100) Feeder power map generator **353** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the feeder at different locations in the field.

(101) Threshing power map generator **354** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or

predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the threshing subsystems at different locations in the field. For example, the threshing subsystems could include one or more threshing drums, concave adjustment actuators, and beaters, and the threshing power map generator **352** generates a map of estimated power usage by the one or more threshing drums, concave adjustment actuators, and beaters based on a predictive power model **350** that defines a relationship between vegetative index, and power usage by the one or more threshing drums, concave adjustment actuators, and beaters. Or for example, the threshing subsystems could include a threshing drum and a set of concaves at a given clearance, and the threshing power map generator **352** generates a map of estimated power usage by the threshing drum with the set of concaves at the given clearance based on a predictive power model **350** that defines a relationship between predictive biomass, and power usage by the threshing drum with the set of concaves at the given clearance. Or for example, the threshing subsystems could include one or more beaters at a given configuration, and the threshing power map generator **352** generates a map of estimated power usage by the one or more beaters at the given configuration based on a predictive power model **350** that defines a relationship between predictive biomass, and power usage by the one or more beaters at the given configuration. Separator power map generator **355** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the separator subsystems at different locations in the field. For example, the separator subsystems could include one or more fans, sieves, chaffers, and straw walkers, and the separator power map generator **355** generates a map of estimated power usage by the one or more fans, sieves, chaffers, and straw walkers based on a predictive power model **350** that defines a relationship between predictive yield value, and power usage by the one or more fans, sieves, chaffers, and straw walkers. For example, the separator subsystems could include one or more fans running at a given speed and sieves, chaffers, and straw walkers in a given configuration, and the separator power map generator **355** generates a map of estimated power usage by the one or more fans running at the given speed and sieves, chaffers, and straw walkers in the given configuration based on a predictive power model **350** that defines a relationship between predictive yield value, and power usage by the one or more fans running at the given speed and sieves, chaffers, and straw walkers in the given configuration.

(102) Residue handling power map generator **356** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the residue handling subsystems at different locations in the field. For example, the residue handling power map generator **356** generates a map of estimated power usage by a residue spreader based on a predictive power model **350** that defines a relationship between predictive biomass value, and power usage by the residue spreader. For example, the residue handling power map generator **356** generates a map of estimated power usage by a residue chopper based on a predictive power model **350** that defines a relationship between predictive yield value, and power usage by the residue chopper.

(103) Propulsion power map generator **357** receives the predictive power model **350**, which predicts power characteristics based upon values in one or more of the vegetative index map **332**, crop moisture map **335**, topographic map **337**, soil property map **339**, predictive yield map **341**, or predictive biomass map **343**, and generates a predictive map that predicts the power characteristics of the propulsion subsystems at different locations in the field. For example, the propulsion power map generator **357** generates a map of estimated power usage by the propulsion subsystem based on a predictive power model **350** that defines a relationship between topographic map value, and power usage by the propulsion system.

(104) Predictive map generator **212** outputs one or more predictive power maps **360** that are predictive of one or more power characteristics. Each of the predictive power maps **360** predicts the respective power characteristic at different locations in a field. Each of the generated predictive power maps **360** may be provided to control zone generator **213**, control system **214**, or both. Control zone generator **213** generates control zones and incorporates those control zones into the functional predictive map, i.e., predictive map **360**, to provide a predictive map **360** with control zones. The functional predictive map **360** (with or without control zones) may be provided to control system **214**, which generates control signals to control one or more of the controllable subsystems **216** based upon the functional predictive map **360** (with or without control zones).

(105) FIG. 5 is a flow diagram of an example of operation of predictive model generator **210** and predictive map generator **212** in generating the predictive power model **350** and the predictive power map **360**. At block **362**, predictive model generator **210** and predictive map generator **212** receives one or more of a prior vegetative index map **332**, a crop moisture map **335**, a topographic map **337**, a soil property map **339**, a predictive yield map **341**, a predictive biomass map **343**, or some other map **363**. At block **364**, processing system **338** receives one or more sensor signals from power sensor **336**. As discussed above, the power sensor **336** may include one or more of a voltage sensor **371**, a current sensor **373**, a torque sensor **375**, a hydraulic pressure sensor **377**, a hydraulic flow sensor **379**, a force sensor **381**, a bearing load sensor **383**, a rotational sensor **385**, or another type of power sensor **370**. The outputs of one or more of these or other sensors can be combined to determine one or more power characteristics

(106) At block **372**, processing system **338** processes the one or more received sensor signals to generate data indicative of a power characteristic. As indicated by block **374**, the power characteristic may be identified at a machine wide level. For example, the entire power usage by the entire agricultural harvester. A power usage at this level can be used to calculate fuel consumption, efficiency, etc. As indicated by block **376**, the power characteristic may be identified at a subsystem level. A characteristic at this level, for instance, can be used to allocate power across subsystems. As indicated by block **378**, the power characteristic may be identified at a component level. The sensor data can include other data at other levels as well as indicated by block **380**.

(107) At block **382**, predictive model generator **210** also obtains the geographic location corresponding to the sensor data. For instance, the predictive model generator **210** can obtain the geographic position from geographic position sensor **204** and determine, based upon machine delays, machine speed, etc., a precise geographic location where the sensor data **340** was captured or derived.

(108) At block **384**, predictive model generator **210** generates one or more predictive power models, such as power model **350**, that model a relationship between a vegetative index value, a crop moisture value, a soil property value, a predictive yield value, or a predictive biomass value obtained from a prior information map, such as prior information map **258**, and a power characteristic being sensed by the in-situ sensor **208** or a related characteristic. For instance, predictive model generator **210** may generate a predictive power model that models the relationship between a vegetative index value and a sensed characteristic including power usage indicated by the sensor data obtained from in-situ sensor **208**.

(109) At block **386**, the predictive power model, such as predictive power model **350**, is provided to predictive map generator **212** which generates a predictive power map **360** that maps a predicted power characteristic based on a vegetative index map, a crop moisture map, a soil property map, a predictive yield map, or a predictive biomass map, and the predictive power model **350**. For instance, in some examples, the predictive power map **360** predicts power usage/requirements of various subsystems. Further, the predictive power map **360** can be generated during the course of an agricultural operation. Thus, as an agricultural harvester is moving through a field performing an agricultural operation, the predictive power map **360** is generated as the agricultural operation is being performed.

(110) At block **394**, predictive map generator **212** outputs the predictive power map **360**. At block **391** predictive power map generator **212** outputs the predictive power map for presentation to and possible interaction by operator **260**. At block **393**, predictive map generator **212** may configure the map for consumption by control system **214**. At block **395**, predictive map generator **212** can also provide the map **360** to control zone generator **213** for generation and incorporation of control zones. At block **397**, predictive map generator **212** configures the map **360** in other ways as well. The predictive power map **360** (with or without the control zones) is provided to control system **214**. At block **396**, control system **214** generates control signals to control the controllable subsystems **216** based upon the predictive power map **360** (with or without control zones).

(111) It can thus be seen that the present system takes a prior information map that maps a characteristic such as a vegetative index value, a crop moisture value, a soil property value, a predictive yield value, or a predictive biomass value or information from a prior operation pass to different locations in a field. The present system also uses one or more in-situ sensors that sense in-situ sensor data that is indicative of a power characteristic, such as power usage, power requirement, or power loss, and generates a model that models a relationship between the characteristic sensed using the in-situ sensor, or a related characteristic, and the characteristic mapped in the prior information map. Thus, the present system generates a functional predictive map using a model, in-situ data, and a prior information map and may configure the generated functional predictive map for consumption by a control system, for presentation to a local or remote operator or other user, or both. For example, the control system may use the map to control one or more systems of a combine harvester.

(112) FIG. 6A is a block diagram of an example portion of the agricultural harvester 100 shown in FIG. 1. Particularly, FIG. 6A shows, among other things, examples of predictive model generator 210 and predictive map generator 212. In the illustrated example, the prior information map 258 is one or more of a historical power map 333, a soil property map 339, or a prior operation map 400. Prior operation map 400 may include power characteristic values at various locations in the field. FIG. 6A also shows that predictive model generator 210 and predictive map generator 212 can receive, in addition to prior information map 258, functional predictive power map 360. Functional predictive power map 360 can be used similarly as prior information map 258 in that model generator 210 models a relationship between information provided by functional predictive power map 360 and characteristics sensed by in-situ sensors 208, and map generator 212 can thus use the model to generate a functional predictive map that predicts the characteristics sensed by the in-situ sensors 208, or a characteristic indicative of the sensed characteristic, at different locations in the field based upon one or more of the values in the functional predictive power map 360 at those locations in the field and based on the predictive model. As illustrated in FIG. 6A, predictive model generator 210 and predictive map generator 212 can also receive other maps 401, for instance other prior information maps or other predictive maps, such as other predictive power maps generated in ways other than functional predictive power map 360.

(113) Also, in the example shown in FIG. 6A, in-situ sensor 208 can include one or more of an agricultural characteristic sensor 402, power sensor 336, an operator input sensor 405, and a processing system 406. In-situ sensors 208 can include other sensors 408 as well.

(114) Agricultural characteristic sensor 402 senses values indicative of agricultural characteristics. As discussed above, power sensor 336 senses power characteristics of one or more components of agricultural harvester 100. For example, power sensor 336 senses power characteristics of propulsion subsystem 250 and generates sensor signals indicative of those power characteristics. For example, power sensor 336 can sense a power consumption or power utilization of propulsion subsystem 250 as the agricultural harvester 100 travels across the field and generate a sensor signal indicative thereof.

(115) Operator input sensor 405 illustratively senses various operator inputs. The inputs can be setting inputs for controlling the settings on agricultural harvester 100 or other control inputs, such as steering inputs and other inputs. Thus, when operator 260 changes a setting or provides a commanded input through an operator interface mechanism 218, such an input is detected by operator input sensor 405, which provides a sensor signal indicative of that sensed operator input.

(116) Processing system 406 may receive the sensor signals from one or more of agricultural characteristic sensor 402, power sensor 336, and operator input sensor 405 and generate an output indicative of the sensed variable. For instance, processing system 406 may receive a sensor input from agricultural characteristic sensor 402 and generate an output indicative of an agricultural characteristic. Processing system 406 may also receive an input from operator input sensor 405 and generate an output indicative of the sensed operator input.

(117) Predictive model generator 210 may include power characteristic-to-agricultural characteristic model generator 410, soil property-to-power characteristic model generator 412, and power characteristic-to-command model generator 414. In other examples, predictive model generator 210 can include additional, fewer, or other model generators 415. Predictive model generator 210 may receive a geographic location indicator 334 from geographic position sensor 204 and generate a predictive model 426 that models a relationship between the information in one or more of the prior information maps 258 or the information in functional predictive power map 360 and one or more of: the agricultural characteristic sensed by agricultural characteristic sensor 402; the power characteristic sensed by power sensor 336; and operator input commands sensed by operator input sensor 405.

(118) Power characteristic-to-agricultural characteristic model generator 410 generates a relationship between power characteristic values (which may be on historical power map 333, on predictive power map 360, or on prior operation map 400) and the agricultural characteristic sensed by agricultural characteristic sensor 402. Power characteristic-to-agricultural characteristic model generator 410 generates a predictive model 426 that corresponds to this relationship.

(119) Soil property-to-power characteristic model generator 412 generates a relationship between soil property values (which may be on soil property map 339) and the power characteristic sensed by power sensor 336. Soil property-to-power characteristic model generator 412 generates a predictive model 426 that corresponds to this relationship. In some examples, soil property-to-power characteristic model generator 415 may generate a relationship between specific soil properties, such as soil moisture or soil type, and power characteristics, or specific power characteristics, such as power characteristics of the propulsion subsystem 250, and, thus, soil property-to-power characteristic model generator 412 generates a corresponding predictive model 426.

(120) Power characteristic-to-operator command model generator 414 generates a model that models the relationship between a power characteristic as reflected on historical power map 333, on predictive power map 360, or on prior operation map 400, or any combination thereof and operator input commands that are sensed by operator input sensor 405. Power-to-operator command model generator 414 generates a predictive model 426 that corresponds to this relationship.

(121) Other model generators 415 may include, for example, specific power characteristic model generators, such as propulsion subsystem power characteristics, for instance, a propulsion subsystem power characteristic-to-agricultural characteristic model generator, a propulsion subsystem power characteristic-to-command model generator, or a soil property-to-propulsion subsystem power characteristic. In some examples, other model generators 415 may include specific soil property model generators, such as a soil type-to-power characteristic model generator, a soil moisture-to-power characteristic model generator. In yet other examples, other model generators 415 may include one or more specific soil property-to-specific power characteristic model generators, such as a soil type-to-propulsion subsystem power characteristic model generator or a soil moisture-to-propulsion subsystem power characteristic model generator.

(122) Predictive model 426 generated by the predictive model generator 210 can include one or more of the predictive models that may be generated by power characteristic-to-agricultural characteristic model generator 410, soil property-to-power characteristic model generator 412, and power characteristic-to-operator command model generator 414, and other model generators that may be included as part of other items 415.

(123) In the example of FIG. 6A, predictive map generator 212 includes predictive agricultural characteristic map generator 416, predictive propulsion power map generator 357, and a predictive operator command map generator 422. In other examples, predictive map generator 212 can include additional, fewer, or other map generators 424.

(124) Predictive agricultural characteristic map generator 416 receives a predictive model 426 that models the relationship between a power characteristic and an agricultural characteristic sensed by agricultural characteristic 402 (such as a predictive model generated by power characteristic-to-agricultural characteristic model generator 410), and one or more of the prior information maps 258 or functional predictive power map 360. Predictive agricultural characteristic map generator 416 generates a functional predictive agricultural characteristic map 427 that predicts agricultural characteristic values (or the agricultural characteristics the values are indicative of) at different locations in the field based upon one or

more of the power characteristics in one or more of the prior information power map 258 (such as historical power map 333) or the functional predictive power map 360, or other maps 401, at those locations in the field and based on predictive model 426.

(125) Predictive propulsion power map generator 357 receives a predictive model 426 that models the relationship between a soil property and a power characteristic sensed by power sensor 336 (such as a predictive model generated by soil property-to-power characteristic model generator 412), and one or more of the prior information maps 258. Predictive propulsion power map generator 357 generates a functional predictive propulsion power map 428 that predicts a likely propulsion power characteristic at different locations in the field based upon one or more of the soil properties in one or more of the prior information maps 258 (such as soil property map 339) at those locations in the field and based on predictive model 426.

(126) Predictive operator command map generator 422 receives a predictive model 426 that models the relationship between the power characteristic and operator command inputs detected by operator input sensor 405 (such as a predictive model generated by power characteristic-to-command model generator 414), and one or more of the prior information maps 258 or the functional predictive power map 360, or other map 401. Predictive operator command map generator 422 generates a functional predictive operator command map 440 that predicts operator command inputs at different locations in the field based upon the power characteristic values from the prior information map 258 (such as historical power map 333) or the functional predictive power map 360, or other maps 401, at those locations in the field and based on the predictive model 426.

(127) Predictive map generator 212 outputs one or more of the functional predictive maps 427, 428, and 440. Each of the functional predictive maps 427, 428, and 440 may be provided to control zone generator 213, control system 214, or both. Control zone generator 213 generates and incorporates control zones to provide one or more of a functional predictive map 427 with control zones, a functional predictive map 428 with control zones, or a functional predictive map 440 with control zones. Any or all of functional predictive maps 427, 428, and 440, with or without control zones, may be provided to control system 214, which generates control signals to control one or more of the controllable subsystems 216 based upon one or all of the functional predictive maps 427, 428, and 440, with or without control zones. Any or all of the maps 427, 428, and 440, with or without control zones, may be presented to operator 260 or another user.

(128) FIG. 6B is a block diagram showing some examples of in-situ sensors 208. Some of the sensors shown in FIG. 6B, or different combinations of them, may have both a sensor 402 and a processing system 406, while others may act as sensor 402 described with respect to FIGS. 6A and 7 where the processing system 406 is separate. Some of the possible in-situ sensors 208 shown in FIG. 6B are shown and described above with respect to previous FIGS. and are similarly numbered. FIG. 6B shows that in-situ sensors 208 can include operator input sensors 480, machine sensors 482, harvested material property sensors 484, field and soil property sensors 485, environmental characteristic sensors 487, and they may include a wide variety of other sensors 226. Operator input sensors 480 may be sensors that sense operator inputs through operator interface mechanisms 218. Therefore, operator input sensors 480 may sense user movement of linkages, joysticks, a steering wheel, buttons, dials, or pedals. Operator input sensors 480 can also sense user interactions with other operator input mechanisms, such as with a touch sensitive screen, with a microphone where speech recognition is utilized, or any of a wide variety of other operator input mechanisms.

(129) Machine sensors 482 may sense different characteristics of agricultural harvester 100. For instance, as discussed above, machine sensors 482 may include machine speed sensors 146, separator loss sensor 148, clean grain camera 150, forward looking image capture mechanism 151, loss sensors 152 or geographic position sensor 204, examples of which are described above. Machine sensors 482 can also include machine setting sensors 491 that sense machine settings. Some examples of machine settings were described above with respect to FIG. 1. Front-end equipment (e.g., header) position sensor 493 can sense the position of the header 102, reel 164, cutter 104, or other front-end equipment relative to the frame of agricultural harvester 100. For instance, sensors 493 may sense the height of header 102 above the ground. Machine sensors 482 can also include front-end equipment (e.g., header) orientation sensors 495. Sensors 495 may sense the orientation of header 102 relative to agricultural harvester 100, or relative to the ground. Machine sensors 482 may include stability sensors 497. Stability sensors 497 sense oscillation or bouncing motion (and amplitude) of agricultural harvester 100. Machine sensors 482 may also include residue setting sensors 499 that are configured to sense whether agricultural harvester 100 is configured to chop the residue, produce a windrow, or deal with the residue in another way. Machine sensors 482 may include cleaning shoe fan speed sensor 551 that senses the speed of cleaning fan 120. Machine sensors 482 may include concave clearance sensors 553 that sense the clearance between the rotor 112 and concaves 114 on agricultural harvester 100. Machine sensors 482 may include chaffer clearance sensors 555 that sense the size of openings in chaffer 122. The machine sensors 482 may include threshing rotor speed sensor 557 that senses a rotor speed of rotor 112. Machine sensors 482 may include rotor pressure sensor 559 that senses the pressure used to drive rotor 112. Machine sensors 482 may include sieve clearance sensor 561 that senses the size of openings in sieve 124. The machine sensors 482 may include MOG moisture sensor 563 that senses a moisture level of the MOG passing through agricultural harvester 100. Machine sensors 482 may include machine orientation sensor 565 that senses the orientation of agricultural harvester 100. Machine sensors 482 may include material feed rate sensors 567 that sense the feed rate of material as the material travels through feeder house 106, clean grain elevator 130, or elsewhere in agricultural harvester 100. Machine sensors 482 can include biomass sensors 569 that sense the biomass traveling through feeder house 106, through separator 116, or elsewhere in agricultural harvester 100. The machine sensors 482 may include fuel consumption sensor 571 that senses a rate of fuel consumption over time of agricultural harvester 100. Machine sensors 482 may include power utilization sensor 573 that senses power utilization in agricultural harvester 100, such as which subsystems are utilizing power, or the rate at which subsystems are utilizing power, or the distribution of power among the subsystems in agricultural harvester 100. Machine sensors 482 may include tire pressure sensors 577 that sense the inflation pressure in tires 144 of agricultural harvester 100. Machine sensor 482 may include a wide variety of other machine performance sensors, or machine characteristic sensors, indicated by block 575. The machine performance sensors and machine characteristic sensors 575 may sense machine performance or characteristics of agricultural harvester 100.

(130) Harvested material property sensors 484 may sense characteristics of the severed crop material as the crop material is being processed by agricultural harvester 100. The crop properties may include such things as crop type, crop moisture, grain quality (such as broken grain), MOG levels, grain constituents such as starches and protein, MOG moisture, and other crop material properties. Other sensors could sense straw “toughness”, adhesion of corn to ears, and other characteristics that might be beneficially used to control processing for better grain capture, reduced grain damage, reduced power consumption, reduced grain loss, etc.

(131) Field and soil property sensors 485 may sense characteristics of the field and soil. The field and soil properties may include soil moisture, soil compactness, the presence and location of standing water, soil type, and other soil and field characteristics.

(132) Environmental characteristic sensors 487 may sense one or more environmental characteristics. The environmental characteristics may include such things as wind direction and wind speed, precipitation, fog, dust level or other obscurants, or other environmental characteristics.

(133) FIG. 7 shows a flow diagram illustrating one example of the operation of predictive model generator 210 and predictive map generator 212 in generating one or more predictive models 426 and one or more functional predictive maps 427, 428, and 440. At block 442, predictive model generator 210 and predictive map generator 212 receive a map. The map received by predictive model generator 210 or predictive map generator in generating one or more predictive models 426 and one or more functional predictive maps 427, 427, and 440 may be prior information map 258, such as historical power map 333, soil property map 339, or a prior operation map 400 created using data obtained during a prior operation in a field. The map received by predictive model generator 210 or predictive map generator in generating one or more predictive models 426 and one or more functional predictive maps 427, 427, and 440 may be functional predictive power map 360. Other maps can be received as well as indicated by block 401, such as other prior information maps or other predictive maps, for instance, other predictive power maps.

(134) At block 444, predictive model generator 210 receives a sensor signal containing sensor data from an in-situ sensor 208. The in-situ sensor

can be one or more of an agricultural characteristic sensor **402**, a power sensor **336**, and an operator input sensor **406**. Agricultural characteristic sensor **402** senses an agricultural characteristic. Power characteristic sensor **336** senses a power characteristic, such as a power characteristic of propulsion subsystem **250**. Operator input sensor **406** senses an operator input command. Predictive model generator **210** can receive other in-situ sensor inputs as well, as indicated by block **408**. Some other examples of in-situ sensors **208** are shown in FIG. **6B** and discussed elsewhere herein. (135) At block **454**, processing system **406** processes the data contained in the sensor signal or signals received from the in-situ sensor or sensors **208** to obtain processed data **409**, shown in FIG. **6A**. The data contained in the sensor signal or signals can be in a raw format that is processed to receive processed data **409**. For example, a temperature sensor signal includes electrical resistance data, this electrical resistance data can be processed into temperature data. In other examples, processing may comprise digitizing, encoding, formatting, scaling, filtering, or classifying data. The processed data **409** may be indicative of one or more of an agricultural characteristic, a power characteristic, or an operator input command. The processed data **409** is provided to predictive model generator **210**.

(136) Returning to FIG. **7**, at block **456**, predictive model generator **210** also receives a geographic location **334** from geographic position sensor **204**, as shown in FIG. **6A**. The geographic location **334** may be correlated to the geographic location from which the sensed variable or variables, sensed by in-situ sensors **208**, were taken. For instance, the predictive model generator **210** can obtain the geographic location **334** from geographic position sensor **204** and determine, based upon machine delays, machine speed, etc., a precise geographic location from which the processed data **409** was derived.

(137) At block **458**, predictive model generator **210** generates one or more predictive models **426** that model a relationship between a mapped value in a received map and a characteristic represented in the processed data **409**. For example, in some instances, the mapped value in a received map may be a power characteristic and the predictive model generator **210** generates a predictive model using the mapped value of a received map and a characteristic sensed by in-situ sensors **208**, as represented in the processed data **409**, or a related characteristic, such as a characteristic that correlates to the characteristic sensed by in-situ sensors **208**.

(138) The one or more predictive models **426** are provided to predictive map generator **212**. At block **466**, predictive map generator **212** generates one or more functional predictive maps. The functional predictive maps may be functional predictive agricultural characteristic map **427**, functional predictive propulsion power map **428**, and a functional predictive operator command map **440**, or any combination of these maps. Functional predictive agricultural characteristic map **427** predicts agricultural characteristic values (or agricultural characteristics indicated by the values) at different locations in the field. Functional predictive propulsion power map **428** predicts likely propulsion power at different locations in the field. Functional predictive operator command map **440** predicts desired or likely operator command inputs at different locations in the field. Further, one or more of the functional predictive maps **427**, **428**, and **440** can be generated during the course of an agricultural operation. Thus, as agricultural harvester **100** is moving through a field performing an agricultural operation, the one or more predictive maps **427**, **428**, and **440** are generated as the agricultural operation is being performed.

(139) At block **468**, predictive map generator **212** outputs the one or more functional predictive maps **427**, **428**, and **440**. At block **470**, predictive map generator **212** may configure the map for presentation to and possible interaction by an operator **260** or another user. At block **472**, predictive map generator **212** may configure the map for consumption by control system **214**. At block **474**, predictive map generator **212** can provide the one or more predictive maps **427**, **428**, and **440** to control zone generator **213** for generation and incorporation of control zones. At block **476**, predictive map generator **212** configures the one or predictive maps **427**, **428**, and **440** in other ways. One or more functional predictive maps **427**, **428**, and **440**, with or without control zones, may be presented to operator **260** or another user or provided to control system **214** as well.

(140) At block **478**, control system **214** then generates control signals to control the controllable subsystems based upon the one or more functional predictive maps **427**, **428** and **440** (or the functional predictive maps **427**, **428**, and **440** having control zones) as well as an input from the geographic position sensor **204**.

(141) In an example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the path planning controller **234** controls steering subsystem **252** to steer agricultural harvester **100**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the residue system controller **244** controls residue subsystem **138**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the settings controller **232** controls thresher settings of thresher **110**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the settings controller **232** or another controller **246** controls material handling subsystem **125**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the settings controller **232** controls crop cleaning subsystem **118**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the machine cleaning controller **245** controls machine cleaning subsystem **254** on agricultural harvester **100**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the communication system controller **229** controls communication system **206**. In another example in which control system **214** receives a functional predictive map or a functional predictive map with control zones added, the operator interface controller **231** controls operator interface mechanisms **218** on agricultural harvester **100**. In another example in which control system **214** receives the functional predictive map or the functional predictive map with control zones added, the deck plate position controller **242** controls machine/header actuators to control a deck plate on agricultural harvester **100**. In another example in which control system **214** receives the functional predictive map or the functional predictive map with control zones added, the draper belt controller **240** controls machine/header actuators to control a draper belt on agricultural harvester **100**. In another example in which control system **214** receives the functional predictive map or the functional predictive map with control zones added, the other controllers **246** control other controllable subsystems **256** on agricultural harvester **100**.

(142) In one example, control system **214** may receive a functional predictive map or a functional predictive map with control zones added, feed rate controller **236** can control various subsystems, such as propulsion subsystem **250** and header or other machine actuators **248**, to control a feed rate based upon the functional predictive map (with or without control zones). For instance, feed rate controller **236** can control propulsion subsystem **250** to adjust a speed of agricultural harvester **100** to control a feed rate. In another example, feed rate controller **236** can control header or other machine actuators **248** to control a height of header **102** above the field to control a feed rate.

(143) FIG. **8** shows a block diagram illustrating one example of control zone generator **213**. Control zone generator **213** includes work machine actuator (WMA) selector **486**, control zone generation system **488**, and regime zone generation system **490**. Control zone generator **213** may also include other items **492**. Control zone generation system **488** includes control zone criteria identifier component **494**, control zone boundary definition component **496**, target setting identifier component **498**, and other items **520**. Regime zone generation system **490** includes regime zone criteria identification component **522**, regime zone boundary definition component **524**, settings resolver identifier component **526**, and other items **528**. Before describing the overall operation of control zone generator **213** in more detail, a brief description of some of the items in control zone generator **213** and the respective operations thereof will first be provided.

(144) Agricultural harvester **100**, or other work machines, may have a wide variety of different types of controllable actuators that perform different functions. The controllable actuators on agricultural harvester **100** or other work machines are collectively referred to as work machine actuators (WMAs). Each WMA may be independently controllable based upon values on a functional predictive map, or the WMAs may be controlled as sets based upon one or more values on a functional predictive map. Therefore, control zone generator **213** may generate control zones corresponding to each individually controllable WMA or corresponding to the sets of WMAs that are controlled in coordination with one another.

(145) WMA selector **486** selects a WMA or set of WMAs for which corresponding control zones are to be generated. Control zone generation system **488** then generates the control zones for the selected WMA or set of WMAs. For each WMA or set of WMAs, different criteria may be used in identifying control zones. For example, for one WMA, the WMA response time may be used as the criteria for defining the boundaries of the control zones. In another example, wear characteristics (e.g., how much a particular actuator or mechanism wears as a result of movement thereof) may be used as the criteria for identifying the boundaries of control zones. Control zone criteria identifier component **494** identifies particular criteria that are to be used in defining control zones for the selected WMA or set of WMAs. Control zone boundary definition component **496** processes the values on a functional predictive map under analysis to define the boundaries of the control zones on that functional predictive map based upon the values in the functional predictive map under analysis and based upon the control zone criteria for the selected WMA or set of WMAs.

(146) Target setting identifier component **498** sets a value of the target setting that will be used to control the WMA or set of WMAs in different control zones. For instance, if the selected WMA is propulsion system **250** or header or other machine actuators **248** and the functional predictive map under analysis is a functional predictive power map **360** (with control zones) or functional predictive propulsion power map **428** (with control zones), then the target setting in each control zone may be a target speed setting or a target header height setting based on power values contained in the functional predictive power map **360** or functional predictive propulsion power map **428**, within the identified control zone.

(147) In some examples, where agricultural harvester **100** is to be controlled based on a current or future location of the agricultural harvester **100**, multiple target settings may be possible for a WMA at a given position. In that case, the target settings may have different values and may be competing. Thus, the target settings need to be resolved so that only a single target setting is used to control the WMA. For example, where the WMA is an actuator in propulsion system **250** that is being controlled in order to control the speed of agricultural harvester **100**, multiple different competing sets of criteria may exist that are considered by control zone generation system **488** in identifying the control zones and the target settings for the selected WMA in the control zones. For instance, different target settings for controlling machine speed may be generated based upon, for example, a detected or predicted power characteristic value (such as a power characteristic value of the propulsion subsystem), a detected or predicted agricultural characteristic value, a detected or predicted soil property value (such as a soil type value or a soil moisture value), a detected or predicted feed rate value, a detected or predictive fuel efficiency value, a detected or predicted grain loss value, or a combination of these. It will be noted that these are merely example and target settings for various WMAs can be based on various other values or combinations of values. However, at any given time, the agricultural harvester **100** cannot travel over the ground at multiple speeds simultaneously or have multiple header heights simultaneously. Rather, at any given time, the agricultural harvester **100** travels at a single speed and has a single header height. Thus, one of the competing target settings is selected to control the speed or header height of agricultural harvester **100**.

(148) Therefore, in some examples, regime zone generation system **490** generates regime zones to resolve multiple different competing target settings. Regime zone criteria identification component **522** identifies the criteria that are used to establish regime zones for the selected WMA or set of WMAs on the functional predictive map under analysis. Some criteria that can be used to identify or define regime zones include, for example, power characteristics, such as power characteristics (e.g., power consumption or power utilization) machine wide (e.g., power characteristics of all power consuming or power utilizing subsystems of agricultural harvester **100**) or power characteristics of one or more particular subsystems of agricultural harvester **100** (such as power characteristics of the propulsion subsystem), agricultural characteristics, soil properties (such as soil type or soil moisture), operator command inputs, crop type or crop variety (for example based on an as-planted map or another source of the crop type or crop variety), weed type, weed intensity, or crop state (such as whether the crop is down, partially down or standing). These are merely some examples of the criteria that can be used to identify or define regime zones. Just as each WMA or set of WMAs may have a corresponding control zone, different WMAs or sets of WMAs may have a corresponding regime zone. Regime zone boundary definition component **524** identifies the boundaries of regime zones on the functional predictive map under analysis based on the regime zone criteria identified by regime zone criteria identification component **522**.

(149) In some examples, regime zones may overlap with one another. For instance, a propulsion power regime zone may overlap with a portion of or an entirety of a crop state regime zone. In such an example, the different regime zones may be assigned to a precedence hierarchy so that, where two or more regime zones overlap, the regime zone assigned with a greater hierarchical position or importance in the precedence hierarchy has precedence over the regime zones that have lesser hierarchical positions or importance in the precedence hierarchy. The precedence hierarchy of the regime zones may be manually set or may be automatically set using a rules-based system, a model-based system, or another system. As one example, where a downed crop regime zone overlaps with a propulsion power regime zone, the downed crop regime zone may be assigned a greater importance in the precedence hierarchy than the propulsion power regime zone so that the downed crop regime zone takes precedence.

(150) In addition, each regime zone may have a unique settings resolver for a given WMA or set of WMAs. Settings resolver identifier component **526** identifies a particular settings resolver for each regime zone identified on the functional predictive map under analysis and a particular settings resolver for the selected WMA or set of WMAs.

(151) Once the settings resolver for a particular regime zone is identified, that settings resolver may be used to resolve competing target settings, where more than one target setting is identified based upon the control zones. The different types of settings resolvers can have different forms. For instance, the settings resolvers that are identified for each regime zone may include a human choice resolver in which the competing target settings are presented to an operator or other user for resolution. In another example, the settings resolver may include a neural network or other artificial intelligence or machine learning system. In such instances, the settings resolvers may resolve the competing target settings based upon a predicted or historic quality metric corresponding to each of the different target settings. As an example, an increased vehicle speed setting may reduce the time to harvest a field and reduce corresponding time-based labor and equipment costs but may increase grain losses. A reduced vehicle speed setting may increase the time to harvest a field and increase corresponding time-based labor and equipment costs but may decrease grain losses. When grain loss or time to harvest is selected as a quality metric, the predicted or historic value for the selected quality metric, given the two competing vehicle speed settings values, may be used to resolve the speed setting. In some instances, the settings resolvers may be a set of threshold rules that may be used instead of, or in addition to, the regime zones. An example of a threshold rule may be expressed as follows: If predicted biomass values within 20 feet of the header of the agricultural harvester **100** are greater than x kilograms (where x is a selected or predetermined value), then use the target setting value that is chosen based on feed rate over other competing target settings, otherwise use the target setting value based on grain loss over other competing target setting values.

(152) The settings resolvers may be logical components that execute logical rules in identifying a target setting. For instance, the settings resolver may resolve target settings while attempting to minimize harvest time or minimize the total harvest cost or maximize harvested grain or based on other variables that are computed as a function of the different candidate target settings. A harvest time may be minimized when an amount to complete a harvest is reduced to at or below a selected threshold. A total harvest cost may be minimized where the total harvest cost is reduced to at or below a selected threshold. Harvested grain may be maximized where the amount of harvested grain is increased to at or above a selected threshold.

(153) FIG. 9 is a flow diagram illustrating one example of the operation of control zone generator **213** in generating control zones and regime zones for a map that the control zone generator **213** receives for zone processing (e.g., for a map under analysis).

(154) At block **530**, control zone generator **213** receives a map under analysis for processing. In one example, as shown at block **532**, the map under analysis is a functional predictive map. For example, the map under analysis may be one of the functional predictive maps **360**, **427**, **428**, or **440**. Block **534** indicates that the map under analysis can be other maps as well.

(155) At block 536, WMA selector 486 selects a WMA or a set of WMAs for which control zones are to be generated on the map under analysis. At block 538, control zone criteria identification component 494 obtains control zone definition criteria for the selected WMAs or set of WMAs. Block 540 indicates an example in which the control zone criteria are or include wear characteristics of the selected WMA or set of WMAs. Block 542 indicates an example in which the control zone definition criteria are or include a magnitude and variation of input source data, such as the magnitude and variation of the values on the map under analysis or the magnitude and variation of inputs from various in-situ sensors 208. Block 544 indicates an example in which the control zone definition criteria are or include physical machine characteristics, such as the physical dimensions of the machine, a speed at which different subsystems operate, or other physical machine characteristics. Block 546 indicates an example in which the control zone definition criteria are or include a responsiveness of the selected WMA or set of WMAs in reaching newly commanded setting values. Block 548 indicates an example in which the control zone definition criteria are or include machine performance metrics. Block 550 indicates an example in which the control zone definition criteria are or include operator preferences. Block 552 indicates an example in which the control zone definition criteria are or include other items as well. Block 549 indicates an example in which the control zone definition criteria are time based, meaning that agricultural harvester 100 will not cross the boundary of a control zone until a selected amount of time has elapsed since agricultural harvester 100 entered a particular control zone. In some instances, the selected amount of time may be a minimum amount of time. Thus, in some instances, the control zone definition criteria may prevent the agricultural harvester 100 from crossing a boundary of a control zone until at least the selected amount of time has elapsed. Block 551 indicates an example in which the control zone definition criteria are based on a selected size value. For example, control zone definition criteria that are based on a selected size value may preclude definition of a control zone that is smaller than the selected size. In some instances, the selected size may be a minimum size.

(156) At block 554, regime zone criteria identification component 522 obtains regime zone definition criteria for the selected WMA or set of WMAs. Block 556 indicates an example in which the regime zone definition criteria are based on a manual input from operator 260 or another user. Block 558 illustrates an example in which the regime zone definition criteria are based on power characteristics such as power characteristics (e.g., power consumption or power utilization) machine wide (e.g., power characteristics across all power consuming or power utilizing subsystems of agricultural harvester 100) or power characteristics of one or more particular subsystems of agricultural harvester 100 (such as power characteristics of propulsion subsystem 250). Block 560 illustrates an example in which the regime zone definition criteria are based on soil properties (such as soil type or soil moisture, or both). Block 564 indicates an example in which the regime zone definition criteria are or include other criteria as well.

(157) At block 566, control zone boundary definition component 496 generates the boundaries of control zones on the map under analysis based upon the control zone criteria. Regime zone boundary definition component 524 generates the boundaries of regime zones on the map under analysis based upon the regime zone criteria. Block 568 indicates an example in which the zone boundaries are identified for the control zones and the regime zones. Block 570 shows that target setting identifier component 498 identifies the target settings for each of the control zones. The control zones and regime zones can be generated in other ways as well, and this is indicated by block 572.

(158) At block 574, settings resolver identifier component 526 identifies the settings resolver for the selected WMAs in each regime zone defined by regimes zone boundary definition component 524. As discussed above, the regime zone resolver can be a human resolver 576, an artificial intelligence or machine learning system resolver 578, a resolver 580 based on predicted or historic quality for each competing target setting, a rules-based resolver 582, a performance criteria-based resolver 584, or other resolvers 586.

(159) At block 588, WMA selector 486 determines whether there are more WMAs or sets of WMAs to process. If additional WMAs or sets of WMAs are remaining to be processed, processing reverts to block 436 where the next WMA or set of WMAs for which control zones and regime zones are to be defined is selected. When no additional WMAs or sets of WMAs for which control zones or regime zones are to be generated are remaining, processing moves to block 590 where control zone generator 213 outputs a map with control zones, target settings, regime zones, and settings resolvers for each of the WMAs or sets of WMAs. As discussed above, the outputted map can be presented to operator 260 or another user; the outputted map can be provided to control system 214; or the outputted map can be output in other ways.

(160) FIG. 10 illustrates one example of the operation of control system 214 in controlling agricultural harvester 100 based upon a map that is output by control zone generator 213. Thus, at block 592, control system 214 receives a map of the worksite. In some instances, the map can be a functional predictive map that may include control zones and regime zones, as represented by block 594. In some instances, the received map may be a functional predictive map that excludes control zones and regime zones. Block 596 indicates an example in which the received map of the worksite can be a prior information map having control zones and regime zones identified on it. Block 598 indicates an example in which the received map can include multiple different maps or multiple different map layers. Block 610 indicates an example in which the received map can take other forms as well.

(161) At block 612, control system 214 receives a sensor signal from geographic position sensor 204. The sensor signal from geographic position sensor 204 can include data that indicates the geographic location 614 of agricultural harvester 100, the speed 616 of agricultural harvester 100, the heading 618 or agricultural harvester 100, or other information 620. At block 622, zone controller 247 selects a regime zone, and, at block 624, zone controller 247 selects a control zone on the map based on the geographic position sensor signal. At block 626, zone controller 247 selects a WMA or a set of WMAs to be controlled. At block 628, zone controller 247 obtains one or more target settings for the selected WMA or set of WMAs. The target settings that are obtained for the selected WMA or set of WMAs may come from a variety of different sources. For instance, block 630 shows an example in which one or more of the target settings for the selected WMA or set of WMAs is based on an input from the control zones on the map of the worksite. Block 632 shows an example in which one or more of the target settings is obtained from human inputs from operator 260 or another user. Block 634 shows an example in which the target settings are obtained from an in-situ sensor 208. Block 636 shows an example in which the one or more target settings is obtained from one or more sensors on other machines working in the same field either concurrently with agricultural harvester 100 or from one or more sensors on machines that worked in the same field in the past. Block 638 shows an example in which the target settings are obtained from other sources as well.

(162) At block 640, zone controller 247 accesses the settings resolver for the selected regime zone and controls the settings resolver to resolve competing target settings into a resolved target setting. As discussed above, in some instances, the settings resolver may be a human resolver in which case zone controller 247 controls operator interface mechanisms 218 to present the competing target settings to operator 260 or another user for resolution. In some instances, the settings resolver may be a neural network or other artificial intelligence or machine learning system, and zone controller 247 submits the competing target settings to the neural network, artificial intelligence, or machine learning system for selection. In some instances, the settings resolver may be based on a predicted or historic quality metric, on threshold rules, or on logical components. In any of these latter examples, zone controller 247 executes the settings resolver to obtain a resolved target setting based on the predicted or historic quality metric, based on the threshold rules, or with the use of the logical components.

(163) At block 642, with zone controller 247 having identified the resolved target setting, zone controller 247 provides the resolved target setting to other controllers in control system 214, which generate and apply control signals to the selected WMA or set of WMAs based upon the resolved target setting. For instance, where the selected WMA is a machine or header actuator 248, zone controller 247 provides the resolved target setting to settings controller 232 or header/real controller 238 or both to generate control signals based upon the resolved target setting, and those generated control signals are applied to the machine or header actuators 248. At block 644, if additional WMAs or additional sets of WMAs are to be controlled at the current geographic location of the agricultural harvester 100 (as detected at block 612), then processing reverts to block 626 where the next WMA or set of WMAs is selected. The processes represented by blocks 626 through 644 continue until all of the WMAs or sets of WMAs

to be controlled at the current geographic location of the agricultural harvester **100** have been addressed. If no additional WMAs or sets of WMAs are to be controlled at the current geographic location of the agricultural harvester **100** remain, processing proceeds to block **646** where zone controller **247** determines whether additional control zones to be considered exist in the selected regime zone. If additional control zones to be considered exist, processing reverts to block **624** where a next control zone is selected. If no additional control zones are remaining to be considered, processing proceeds to block **648** where a determination as to whether additional regime zones are remaining to be consider. Zone controller **247** determines whether additional regime zones are remaining to be considered. If additional regimes zone are remaining to be considered, processing reverts to block **622** where a next regime zone is selected.

(164) At block **650**, zone controller **247** determines whether the operation that agricultural harvester **100** is performing is complete. If not, the zone controller **247** determines whether a control zone criterion has been satisfied to continue processing, as indicated by block **652**. For instance, as mentioned above, control zone definition criteria may include criteria defining when a control zone boundary may be crossed by the agricultural harvester **100**. For example, whether a control zone boundary may be crossed by the agricultural harvester **100** may be defined by a selected time period, meaning that agricultural harvester **100** is prevented from crossing a zone boundary until a selected amount of time has transpired. In that case, at block **652**, zone controller **247** determines whether the selected time period has elapsed. Additionally, zone controller **247** can perform processing continually. Thus, zone controller **247** does not wait for any particular time period before continuing to determine whether an operation of the agricultural harvester **100** is completed. At block **652**, zone controller **247** determines that it is time to continue processing, then processing continues at block **612** where zone controller **247** again receives an input from geographic position sensor **204**. It will also be appreciated that zone controller **247** can control the WMAs and sets of WMAs simultaneously using a multiple-input, multiple-output controller instead of controlling the WMAs and sets of WMAs sequentially.

(165) FIG. **11** is a block diagram showing one example of an operator interface controller **231**. In an illustrated example, operator interface controller **231** includes operator input command processing system **654**, other controller interaction system **656**, speech processing system **658**, and action signal generator **660**. Operator input command processing system **654** includes speech handling system **662**, touch gesture handling system **664**, and other items **666**. Other controller interaction system **656** includes controller input processing system **668** and controller output generator **670**. Speech processing system **658** includes trigger detector **672**, recognition component **674**, synthesis component **676**, natural language understanding system **678**, dialog management system **680**, and other items **682**. Action signal generator **660** includes visual control signal generator **684**, audio control signal generator **686**, haptic control signal generator **688**, and other items **690**. Before describing operation of the example operator interface controller **231** shown in FIG. **11** in handling various operator interface actions, a brief description of some of the items in operator interface controller **231** and the associated operation thereof is first provided.

(166) Operator input command processing system **654** detects operator inputs on operator interface mechanisms **218** and processes those inputs for commands. Speech handling system **662** detects speech inputs and handles the interactions with speech processing system **658** to process the speech inputs for commands. Touch gesture handling system **664** detects touch gestures on touch sensitive elements in operator interface mechanisms **218** and processes those inputs for commands.

(167) Other controller interaction system **656** handles interactions with other controllers in control system **214**. Controller input processing system **668** detects and processes inputs from other controllers in control system **214**, and controller output generator **670** generates outputs and provides those outputs to other controllers in control system **214**. Speech processing system **658** recognizes speech inputs, determines the meaning of those inputs, and provides an output indicative of the meaning of the spoken inputs. For instance, speech processing system **658** may recognize a speech input from operator **260** as a settings change command in which operator **260** is commanding control system **214** to change a setting for a controllable subsystem **216**. In such an example, speech processing system **658** recognizes the content of the spoken command, identifies the meaning of that command as a settings change command, and provides the meaning of that input back to speech handling system **662**. Speech handling system **662**, in turn, interacts with controller output generator **670** to provide the commanded output to the appropriate controller in control system **214** to accomplish the spoken settings change command.

(168) Speech processing system **658** may be invoked in a variety of different ways. For instance, in one example, speech handling system **662** continuously provides an input from a microphone (being one of the operator interface mechanisms **218**) to speech processing system **658**. The microphone detects speech from operator **260**, and the speech handling system **662** provides the detected speech to speech processing system **658**. Trigger detector **672** detects a trigger indicating that speech processing system **658** is invoked. In some instances, when speech processing system **658** is receiving continuous speech inputs from speech handling system **662**, speech recognition component **674** performs continuous speech recognition on all speech spoken by operator **260**. In some instances, speech processing system **658** is configured for invocation using a wakeup word. That is, in some instances, operation of speech processing system **658** may be initiated based on recognition of a selected spoken word, referred to as the wakeup word. In such an example, where recognition component **674** recognizes the wakeup word, the recognition component **674** provides an indication that the wakeup word has been recognized to trigger detector **672**. Trigger detector **672** detects that speech processing system **658** has been invoked or triggered by the wakeup word. In another example, speech processing system **658** may be invoked by an operator **260** actuating an actuator on a user interface mechanism, such as by touching an actuator on a touch sensitive display screen, by pressing a button, or by providing another triggering input. In such an example, trigger detector **672** can detect that speech processing system **658** has been invoked when a triggering input via a user interface mechanism is detected. Trigger detector **672** can detect that speech processing system **658** has been invoked in other ways as well.

(169) Once speech processing system **658** is invoked, the speech input from operator **260** is provided to speech recognition component **674**. Speech recognition component **674** recognizes linguistic elements in the speech input, such as words, phrases, or other linguistic units. Natural language understanding system **678** identifies a meaning of the recognized speech. The meaning may be a natural language output, a command output identifying a command reflected in the recognized speech, a value output identifying a value in the recognized speech, or any of a wide variety of other outputs that reflect the understanding of the recognized speech. For example, the natural language understanding system **678** and speech processing system **568**, more generally, may understand of the meaning of the recognized speech in the context of agricultural harvester **100**.

(170) In some examples, speech processing system **658** can also generate outputs that navigate operator **260** through a user experience based on the speech input. For instance, dialog management system **680** may generate and manage a dialog with the user in order to identify what the user wishes to do. The dialog may disambiguate a user's command; identify one or more specific values that are needed to carry out the user's command; or obtain other information from the user or provide other information to the user or both. Synthesis component **676** may generate speech synthesis which can be presented to the user through an audio operator interface mechanism, such as a speaker. Thus, the dialog managed by dialog management system **680** may be exclusively a spoken dialog or a combination of both a visual dialog and a spoken dialog.

(171) Action signal generator **660** generates action signals to control operator interface mechanisms **218** based upon outputs from one or more of operator input command processing system **654**, other controller interaction system **656**, and speech processing system **658**. Visual control signal generator **684** generates control signals to control visual items in operator interface mechanisms **218**. The visual items may be lights, a display screen, warning indicators, or other visual items. Audio control signal generator **686** generates outputs that control audio elements of operator interface mechanisms **218**. The audio elements include a speaker, audible alert mechanisms, horns, or other audible elements. Haptic control signal generator **688** generates control signals that are output to control haptic elements of operator interface mechanisms **218**. The haptic elements include vibration elements that may be used to vibrate, for example, the operator's seat, the steering wheel, pedals, or joysticks used by the operator. The haptic elements may include tactile feedback or force feedback elements that provide tactile feedback or force feedback to the operator through

operator interface mechanisms 218, the tactile elements may include a wide variety of other haptic elements as well.

(172) FIG. 12 is a flow diagram illustrating one example of the operation of operator interface controller 231 in generating an operator interface display on an operator interface mechanism 218, which can include a touch sensitive display screen. FIG. 12 also illustrates one example of how operator interface controller 231 can detect and process operator interactions with the touch sensitive display screen.

(173) At block 692, operator interface controller 231 receives a map. Block 694 indicates an example in which the map is a functional predictive map, and block 696 indicates an example in which the map is another type of map. At block 698, operator interface controller 231 receives an input from geographic position sensor 204 identifying the geographic location of the agricultural harvester 100. As indicated in block 700, the input from geographic position sensor 204 can include the heading, along with the location, of agricultural harvester 100. Block 702 indicates an example in which the input from geographic position sensor 204 includes the speed of agricultural harvester 100, and block 704 indicates an example in which the input from geographic position sensor 204 includes other items.

(174) At block 706, visual control signal generator 684 in operator interface controller 231 controls the touch sensitive display screen in operator interface mechanisms 218 to generate a display showing all or a portion of a field represented by the received map. Block 708 indicates that the displayed field can include a current position marker showing a current position of the agricultural harvester 100 relative to the field. Block 710 indicates an example in which the displayed field includes a next work unit marker that identifies a next work unit (or area on the field) in which agricultural harvester 100 will be operating. Block 712 indicates an example in which the displayed field includes an upcoming area display portion that displays areas that are yet to be processed by agricultural harvester 100, and block 714 indicates an example in which the displayed field includes previously visited display portions that represent areas of the field that agricultural harvester 100 has already processed. Block 716 indicates an example in which the displayed field displays various characteristics of the field having georeferenced locations on the map. For instance, if the received map is a power map, such as functional predictive map 360 or 428, the displayed field may show the different power characteristics existing in the field georeferenced within the displayed field. The mapped characteristics can be shown in the previously visited areas (as shown in block 714), in the upcoming areas (as shown in block 712), and in the next work unit (as shown in block 710). Block 718 indicates an example in which the displayed field includes other items as well.

(175) FIG. 13 is a pictorial illustration showing one example of a user interface display 720 that can be generated on a touch sensitive display screen. In other implementations, the user interface display 720 may be generated on other types of displays. The touch sensitive display screen may be mounted in the operator compartment of agricultural harvester 100 or on the mobile device or elsewhere. User interface display 720 will be described prior to continuing with the description of the flow diagram shown in FIG. 12.

(176) In the example shown in FIG. 13, user interface display 720 illustrates that the touch sensitive display screen includes a display feature for operating a microphone 722 and a speaker 724. Thus, the touch sensitive display may be communicably coupled to the microphone 722 and the speaker 724. Block 726 indicates that the touch sensitive display screen can include a wide variety of user interface control actuators, such as buttons, keypads, soft keypads, links, icons, switches, etc. The operator 260 can actuate the user interface control actuators to perform various functions.

(177) In the example shown in FIG. 13, user interface display 720 includes a field display portion 728 that displays at least a portion of the field in which the agricultural harvester 100 is operating. The field display portion 728 is shown with a current position marker 708 that corresponds to a current position of agricultural harvester 100 in the portion of the field shown in field display portion 728. In one example, the operator may control the touch sensitive display in order to zoom into portions of field display portion 728 or to pan or scroll the field display portion 728 to show different portions of the field. A next work unit 730 is shown as an area of the field directly in front of the current position marker 708 of agricultural harvester 100. The current position marker 708 may also be configured to identify the direction of travel of agricultural harvester 100, a speed of travel of agricultural harvester 100 or both. In FIG. 13, the shape of the current position marker 708 provides an indication as to the orientation of the agricultural harvester 100 within the field which may be used as an indication of a direction of travel of the agricultural harvester 100.

(178) The size of the next work unit 730 marked on field display portion 728 may vary based upon a wide variety of different criteria. For instance, the size of next work unit 730 may vary based on the speed of travel of agricultural harvester 100. Thus, when the agricultural harvester 100 is traveling faster, then the area of the next work unit 730 may be larger than the area of next work unit 730 if agricultural harvester 100 is traveling more slowly. In another example, the size of the next work unit 730 may vary based on the dimensions of the agricultural harvester 100, including equipment on agricultural harvester 100 (such as header 102). For example, the width of the next work unit 730 may vary based on a width of header 102. Field display portion 728 is also shown displaying previously visited area 714 and upcoming areas 712. Previously visited areas 714 represent areas that are already harvested while upcoming areas 712 represent areas that still need to be harvested. The field display portion 728 is also shown displaying different characteristics of the field. In the example illustrated in FIG. 13, the map that is being displayed is a predictive power map, such as functional predictive map 360 or functional predictive map 428. Therefore, a plurality of power characteristic markers are displayed on field display portion 728. There are a set of power characteristic display markers 732 shown in the already visited areas 714. There are also a set of power characteristic display markers 732 shown in the upcoming areas 712, and there are a set of power characteristic display markers 732 shown in the next work unit 730. FIG. 13 shows that the ear size display markers 732 are made up of different symbols that indicate an area of similar power characteristics. In the example shown in FIG. 14, the ! symbol represents areas of high power utilization; the * symbol represents areas of medium power utilization; and the # symbol represents an area of low power utilization. Power utilization is merely one example, other power characteristics, including power characteristics of particular subsystems, can also be displayed. The field display portion 728 shows different measured or predicted values (or characteristics indicated by the values) that are located at different areas within the field and represents those measured or predicted values (or characteristics indicated by or derived from the values) with a variety of display markers 732. As shown, the field display portion 728 includes display markers, particularly power characteristic display markers 732 in the illustrated example of FIG. 13, at particular locations associated with particular locations on the field being displayed. In some instances, each location of the field may have a display marker associated therewith. Thus, in some instances, a display marker may be provided at each location of the field display portion 728 to identify the nature of the characteristic being mapped for each particular location of the field. Consequently, the present disclosure encompasses providing a display marker, such as the power characteristic display marker 732 (as in the context of the present example of FIG. 13), at one or more locations on the field display portion 728 to identify the nature, degree, etc., of the characteristic being displayed, thereby identifying the characteristic at the corresponding location in the field being displayed. As described earlier, the display markers 732 may be made up of different symbols, and, as described below, the symbols may be any display feature such as different colors, shapes, patterns, intensities, text, icons, or other display features. In some instances, each location of the field may have a display marker associated therewith. Thus, in some instances, a display marker may be provided at each location of the field display portion 728 to identify the nature of the characteristic being mapped for each particular location of the field. Consequently, the present disclosure encompasses providing a display marker, such as the loss level display marker 732 (as in the context of the present example of FIG. 11), at one or more locations on the field display portion 728 to identify the nature, degree, etc., of the characteristic being displayed, thereby identifying the characteristic at the corresponding location in the field being displayed.

(179) In other examples, the map being displayed may be one or more of the maps described herein, including information maps, prior information maps, the functional predictive maps, such as predictive maps or predictive control zone maps, or a combination thereof. Thus, the markers and characteristics being displayed will correlate to the information, data, characteristics, and values provided by the one or more maps being displayed.

(180) In the example of FIG. 13 user interface display 720 also has a control display portion 738. Control display portion 738 allows the operator to

view information and to interact with user interface display 720 in various ways.

(181) The actuators and display markers in portion 738 may be displayed as, for example, individual items, fixed lists, scrollable lists, drop down menus, or drop down lists. In the example shown in FIG. 13, display portion 738 shows information for the three different ear size categories that correspond to the three symbols mentioned above. Display portion 738 also includes a set of touch sensitive actuators with which the operator 260 can interact by touch. For example, the operator 260 may touch the touch sensitive actuators with a finger to activate the respective touch sensitive actuator. As shown in FIG. 13, display portion 738 also includes interactive tabs, such as machine wide tab 762, propulsion tab 764, threshing/separating tab 766, residue tab 768, and other tab 770. Activating one of the tabs can modify which values are displayed in portions 728 and 738. For instance, as shown, propulsion tab 764 is activated and thus the values mapped on portion 728 and shown in portion 738 correspond to power characteristics (shown as power utilization) across propulsion subsystem 250 of agricultural harvester 100. When the operator 260 touches the tab 762, touch gesture handling system 664 updates portion 728 and 738 to display characteristics relating to all subsystems of agricultural harvester 100. When the operator 260 touches the tab 766, touch gesture handling system 664 updates portion 728 and 738 to display characteristics relating to threshing and separating subsystems. When the operator 260 touches the tab 768, touch gesture handling system 664 updates portion 728 and 738 to display characteristics relating to residue subsystem 138. When the operator 260 touches the tab 770, touch gesture handling system 664 updates portion 728 and 738 to display characteristics relating to another set of components of agricultural harvester 100.

(182) As shown in FIG. 13, display portion 738 includes an interactive flag display portion, indicated generally at 741. Interactive flag display portion 741 includes a flag column 739 that shows flags that have been automatically or manually set. Flag actuator 740 allows operator 260 to mark a location, such as the current location of the agricultural harvester, or another location on the field designated by the operator and add information indicating the characteristic, such as power utilization, found at the current location. For instance, when the operator 260 actuates the flag actuator 740 by touching the flag actuator 740, touch gesture handling system 664 in operator interface controller 231 identifies the current location as one where agricultural harvester 100 encountered high power utilization. When the operator 260 touches the button 742, touch gesture handling system 664 identifies the current location as a location where agricultural harvester 100 encountered medium power utilization. When the operator 260 touches the button 744, touch gesture handling system 664 identifies the current location as a location where agricultural harvester 100 encountered low power utilization. Upon actuation of one of the flag actuators 740, 742, or 744, touch gesture handling system 664 can control visual control signal generator 684 to add a symbol corresponding to the identified characteristic on field display portion 728 at a location the user identifies. In this way, areas of the field where the predicted value did not accurately represent an actual value can be marked for later analysis, and can also be used in machine learning. In other examples, the operator may designate areas ahead of or around the agricultural harvester 100 by actuating one of the flag actuators 740, 742, or 744 such that control of the agricultural harvester 100 can be undertaken based on the value designated by the operator 260.

(183) Display portion 738 also includes an interactive marker display portion, indicated generally at 743. Interactive marker display portion 743 includes a symbol column 746 that displays the symbols corresponding to each category of values or characteristics (in the case of FIG. 13, power utilization) that is being tracked on the field display portion 728. Display portion 738 also includes an interactive designator display portion, indicated generally at 745. Interactive designator display portion 745 includes a designator column 748 that shows the designator (which may be a textual designator or other designator) identifying the category of values or characteristics (in the case of FIG. 13, power utilization). Without limitation, the symbols in symbol column 746 and the designators in designator column 748 can include any display feature such as different colors, shapes, patterns, intensities, text, icons, or other display features, and can be customizable by interaction of an operator of agricultural harvester 100.

(184) Display portion 738 also includes an interactive value display portion, indicated generally at 747. Interactive value display portion 747 includes a value display column 750 that displays selected values. The selected values correspond to the characteristics or values being tracked or displayed, or both, on field display portion 728. The selected values can be selected by an operator of the agricultural harvester 100. The selected values in value display column 750 define a range of values or a value by which other values, such as predicted values, are to be classified. Thus, in the example in FIG. 13, a predicted or measured propulsion subsystem power utilization meeting or greater than 45% is classified as “high power utilization” and a predicted or measured propulsion subsystem power utilization meeting or less than 35% is classified as “low power utilization.” In some examples, the selected values may include a range, such that a predicted or measured value that is within the range of the selected value will be classified under the corresponding designator. As shown in FIG. 13, “medium power utilization” includes a range of 36%-44% such that a predicted or measured power utilization falling within the range of 36%-44% is classified as “medium power utilization”. The selected values in value display column 750 are adjustable by an operator of agricultural harvester 100. In one example, the operator 260 can select the particular part of field display portion 728 for which the values in column 750 are to be displayed. Thus, the values in column 750 can correspond to values in display portions 712, 714 or 730.

(185) Display portion 738 also includes an interactive threshold display portion, indicated generally at 749. Interactive threshold display portion 749 includes a threshold value display column 752 that displays action threshold values. Action threshold values in column 752 may be threshold values corresponding to the selected values in value display column 750. If the predicted or measured values of characteristics being tracked or displayed, or both, satisfy the corresponding action threshold values in threshold value display column 752, then control system 214 takes an action identified in column 754. In some instances, a measured or predicted value may satisfy a corresponding action threshold value by meeting or exceeding the corresponding action threshold value. In one example, operator 260 can select a threshold value, for example, in order to change the threshold value by touching the threshold value in threshold value display column 752. Once selected, the operator 260 may change the threshold value. The threshold values in column 752 can be configured such that the designated action is performed when the measured or predicted value of the characteristic exceeds the threshold value, equals the threshold value, or is less than the threshold value. In some instances, the threshold value may represent a range of values, or range of deviation from the selected values in value display column 750, such that a predicted or measured characteristic value that meets or falls within the range satisfies the threshold value. For instance, in the example of propulsion subsystem power utilization, a predicted propulsion subsystem power utilization that falls within 10% of 45% power utilization will satisfy the corresponding action threshold value (of within 10% of 45% power utilization) and an action, such as reducing the vehicle speed, will be taken by control system 214. In other examples, the threshold values in column threshold value display column 752 are separate from the selected values in value display column 750, such that the values in value display column 750 define the classification and display of predicted or measured values, while the action threshold values define when an action is to be taken based on the measured or predicted values. For example, while a predicted or measured propulsion subsystem power utilization of 40% may be designated as a “medium power utilization” for purposes of classification and display, the action threshold value may be 41% power utilization such that no action will be taken until the propulsion subsystem power utilization satisfies the threshold value. In other examples, the threshold values in threshold value display column 752 may include distances or times. For instance, in the example of a distance, the threshold value may be a threshold distance from the area of the field where the measured or predicted value is georeferenced that the agricultural harvester 100 must be before an action is taken. For example, a threshold distance value of 5 feet would mean that an action will be taken when the agricultural harvester is at or within 5 feet of the area of the field where the measured or predicted value is georeferenced. In an example where the threshold value is time, the threshold value may be a threshold time for the agricultural harvester 100 to reach the area of the field where the measured or predictive value is georeferenced. For instance, a threshold value of 5 seconds would mean that an action will be taken when the agricultural harvester 100 is 5 seconds away from the area of the field where the measured or predicted value is georeferenced. In such an example, the current location and travel speed of the agricultural harvester can be accounted for.

(186) Display portion 738 includes an interactive action display portion 751 that includes an action display column 754 that displays action identifiers that indicate actions to be taken when a predicted or measured value satisfies an action threshold value in threshold value display column 752. Operator 260 can touch the action identifiers in column 754 to change the action that is to be taken. When a threshold is satisfied, an action may be taken. For instance, at the bottom of column 754, an increase travel speed action, a decrease travel speed action, and an adjust header position action (such as adjusting a header height, a header pitch, or a header roll, relative to the surface or relative to the frame of agricultural harvester 100) are identified as actions that will be taken if the measured or predicted value meets the threshold value in column 752. In some examples, when a threshold is met, multiple actions may be taken. For instance, a header position may be adjusted, a power output to one or more subsystems may be adjusted, and a speed of the agricultural machine may be adjusted. These are merely some examples.

(187) The actions that can be set in column 754 can be any of a wide variety of different types of actions. For example, the actions can include a keep out action which, when executed, inhibits agricultural harvester 100 from further harvesting in an area. The actions can include a speed change action which, when executed, changes the travel speed of agricultural harvester 100 through the field. The actions can include a setting change action for changing a setting of an internal actuator or another WMA or set of WMAs or for implementing a settings change action that changes a setting, such as a header position setting along with various other settings. These are examples only, and a wide variety of other actions are contemplated herein.

(188) The items shown on user interface display 720 can be visually controlled. Visually controlling the interface display 720 may be performed to capture the attention of operator 260. For instance, the items can be controlled to modify the intensity, color, or pattern with which the items are displayed. Additionally, the items may be controlled to flash. The described alterations to the visual appearance of the items are provided as examples. Consequently, other aspects of the visual appearance of the items may be altered. Therefore, the items can be modified under various circumstances in a desired manner in order, for example, to capture the attention of operator 260. Additionally, while a particular number of items are shown on user interface display 720, this need not be the case. In other examples, more or less items, including more or less of a particular item can be included on user interface display 720.

(189) Returning now to the flow diagram of FIG. 12, the description of the operation of operator interface controller 231 continues. At block 760, operator interface controller 231 detects an input setting a flag and controls the touch sensitive user interface display 720 to display the flag on field display portion 728. The detected input may be an operator input, as indicated at 762, or an input from another controller, as indicated at 764. At block 766, operator interface controller 231 detects an in-situ sensor input indicative of a measured characteristic of the field from one of the in-situ sensors 208. At block 768, visual control signal generator 684 generates control signals to control user interface display 720 to display actuators for modifying user interface display 720 and for modifying machine control. For instance, block 770 represents that one or more of the actuators for setting or modifying the values in columns 739, 746, and 748 can be displayed. Thus, the user can set flags and modify characteristics of those flags. Block 772 represents that action threshold values in column 752 are displayed. Block 776 represents that the actions in column 754 are displayed, and block 778 represents that the selected value in column 750 is displayed. Block 780 indicates that a wide variety of other information and actuators can be displayed on user interface display 720 as well.

(190) At block 782, operator input command processing system 654 detects and processes operator inputs corresponding to interactions with the user interface display 720 performed by the operator 260. Where the user interface mechanism on which user interface display 720 is displayed is a touch sensitive display screen, interaction inputs with the touch sensitive display screen by the operator 260 can be touch gestures 784. In some instances, the operator interaction inputs can be inputs using a point and click device 786 or other operator interaction inputs 788.

(191) At block 790, operator interface controller 231 receives signals indicative of an alert condition. For instance, block 792 indicates that signals may be received by controller input processing system 668 indicating that detected or predicted values satisfy threshold conditions present in column 752. As explained earlier, the threshold conditions may include values being below a threshold, at a threshold, or above a threshold. Block 794 shows that action signal generator 660 can, in response to receiving an alert condition, alert the operator 260 by using visual control signal generator 684 to generate visual alerts, by using audio control signal generator 686 to generate audio alerts, by using haptic control signal generator 688 to generate haptic alerts, or by using any combination of these. Similarly, as indicated by block 796, controller output generator 670 can generate outputs to other controllers in control system 214 so that those controllers perform the corresponding action identified in column 754. Block 798 shows that operator interface controller 231 can detect and process alert conditions in other ways as well.

(192) Block 900 shows that speech handling system 662 may detect and process inputs invoking speech processing system 658. Block 902 shows that performing speech processing may include the use of dialog management system 680 to conduct a dialog with the operator 260. Block 904 shows that the speech processing may include providing signals to controller output generator 670 so that control operations are automatically performed based upon the speech inputs.

(193) Table 1, below, shows an example of a dialog between operator interface controller 231 and operator 260. In Table 1, operator 260 uses a trigger word or a wakeup word that is detected by trigger detector 672 to invoke speech processing system 658. In the example shown in Table 1, the wakeup word is "Johnny".

(194) TABLE-US-00001 TABLE 1 Operator: "Johnny, tell me about current power utilization" Operator Interface Controller: "Propulsion Power Utilization is currently 40%" Operator: "Johnny, what should I do at the current power utilization?" Operator Interface Controller: "Power utilization can be increased to 45% if the machine speed is increased 1 MPH."

(195) Table 2 shows an example in which speech synthesis component 676 provides an output to audio control signal generator 686 to provide audible updates on an intermittent or periodic basis. The interval between updates may be time-based, such as every five minutes, or coverage or distance-based, such as every five acres, or exception-based, such as when a measured value is greater than a threshold value.

(196) TABLE-US-00002 TABLE 2 Operator Interface Controller: "Over last 10 minutes, propulsion power utilization has averaged 43%" Operator Interface Controller: "Next 1 acre predicted propulsion power utilization is 41%." Operator Interface Controller: "Caution: power utilization falling below 35%. Machine speed increasing."

(197) The example shown in Table 3 illustrates that some actuators or user input mechanisms on the touch sensitive display 720 can be supplemented with speech dialog. The example in Table 3 illustrates that action signal generator 660 can generate action signals to automatically mark a power utilization area in the field being harvested.

(198) TABLE-US-00003 TABLE 3 Human: "Johnny, mark high power utilization area." Operator Interface Controller: "High power utilization area marked."

(199) The example shown in Table 4 illustrates that action signal generator 660 can conduct a dialog with operator 260 to begin and end marking of a power utilization area.

(200) TABLE-US-00004 TABLE 4 Human: "Johnny, start marking high power utilization area." Operator Interface Controller: "Marking high power utilization area." Human: "Johnny, stop marking high power utilization area." Operator Interface Controller: "High power utilization area marking stopped."

(201) The example shown in Table 5 illustrates that action signal generator 160 can generate signals to mark a power utilization area in a different way than those shown in Tables 3 and 4.

(202) TABLE-US-00005 TABLE 5 Human: "Johnny, mark next 100 feet as a low power utilization area." Operator Interface Controller: "Next 100 feet marked as a low power utilization area."

(203) Returning again to FIG. 12, block 906 illustrates that operator interface controller 231 can detect and process conditions for outputting a message or other information in other ways as well. For instance, other controller interaction system 656 can detect inputs from other controllers indicating that alerts or output messages should be presented to operator 260. Block 908 shows that the outputs can be audio messages. Block 910 shows that the outputs can be visual messages, and block 912 shows that the outputs can be haptic messages. Until operator interface controller 231 determines that the current harvesting operation is completed, as indicated by block 914, processing reverts to block 698 where the geographic location of harvester 100 is updated and processing proceeds as described above to update user interface display 720.

(204) Once the operation is complete, then any desired values that are displayed, or have been displayed on user interface display 720, can be saved. Those values can also be used in machine learning to improve different portions of predictive model generator 210, predictive map generator 212, control zone generator 213, control algorithms, or other items. Saving the desired values is indicated by block 916. The values can be saved locally on agricultural harvester 100, or the values can be saved at a remote server location or sent to another remote system.

(205) It can thus be seen that one or more maps are obtained by an agricultural harvester that show agricultural characteristic values at different geographic locations of a field being harvested. An in-situ sensor on the harvester senses a characteristic that has values indicative of an agricultural characteristic as the agricultural harvester moves through the field. A predictive map generator generates a predictive map that predicts control values for different locations in the field based on the values of the agricultural characteristic in the map and the agricultural characteristic sensed by the in-situ sensor. A control system controls controllable subsystem based on the control values in the predictive map.

(206) A control value is a value upon which an action can be based. A control value, as described herein, can include any value (or characteristics indicated by or derived from the value) that may be used in the control of agricultural harvester 100. A control value can be any value indicative of an agricultural characteristic. A control value can be a predicted value, a measured value, or a detected value. A control value may include any of the values provided by a map, such as any of the maps described herein, for instance, a control value can be a value provided by an information map, a value provided by prior information map, or a value provided predictive map, such as a functional predictive map. A control value can also include any of the characteristics indicated by or derived from the values detected by any of the sensors described herein. In other examples, a control value can be provided by an operator of the agricultural machine, such as a command input by an operator of the agricultural machine.

(207) The present discussion has mentioned processors and servers. In some examples, the processors and servers include computer processors with associated memory and timing circuitry, not separately shown. The processors and servers are functional parts of the systems or devices to which the processors and servers belong and are activated by and facilitate the functionality of the other components or items in those systems.

(208) Also, a number of user interface displays have been discussed. The displays can take a wide variety of different forms and can have a wide variety of different user actuatable operator interface mechanisms disposed thereon. For instance, user actuatable operator interface mechanisms may include text boxes, check boxes, icons, links, drop-down menus, search boxes, etc. The user actuatable operator interface mechanisms can also be actuated in a wide variety of different ways. For instance, the user actuatable operator interface mechanisms can be actuated using operator interface mechanisms such as a point and click device, such as a track ball or mouse, hardware buttons, switches, a joystick or keyboard, thumb switches or thumb pads, etc., a virtual keyboard or other virtual actuators. In addition, where the screen on which the user actuatable operator interface mechanisms are displayed is a touch sensitive screen, the user actuatable operator interface mechanisms can be actuated using touch gestures. Also, user actuatable operator interface mechanisms can be actuated using speech commands using speech recognition functionality. Speech recognition may be implemented using a speech detection device, such as a microphone, and software that functions to recognize detected speech and execute commands based on the received speech.

(209) A number of data stores have also been discussed. It will be noted the data stores can each be broken into multiple data stores. In some examples, one or more of the data stores may be local to the systems accessing the data stores, one or more of the data stores may all be located remote from a system utilizing the data store, or one or more data stores may be local while others are remote. All of these configurations are contemplated by the present disclosure.

(210) Also, the figures show a number of blocks with functionality ascribed to each block. It will be noted that fewer blocks can be used to illustrate that the functionality ascribed to multiple different blocks is performed by fewer components. Also, more blocks can be used illustrating that the functionality may be distributed among more components. In different examples, some functionality may be added, and some may be removed.

(211) It will be noted that the above discussion has described a variety of different systems, components, logic, and interactions. It will be appreciated that any or all of such systems, components, logic and interactions may be implemented by hardware items, such as processors, memory, or other processing components, including but not limited to artificial intelligence components, such as neural networks, some of which are described below, that perform the functions associated with those systems, components, logic, or interactions. In addition, any or all of the systems, components, logic and interactions may be implemented by software that is loaded into a memory and is subsequently executed by a processor or server or other computing component, as described below. Any or all of the systems, components, logic and interactions may also be implemented by different combinations of hardware, software, firmware, etc., some examples of which are described below. These are some examples of different structures that may be used to implement any or all of the systems, components, logic and interactions described above. Other structures may be used as well.

(212) FIG. 14 is a block diagram of agricultural harvester 600, which may be similar to agricultural harvester 100 shown in FIG. 2. The agricultural harvester 600 communicates with elements in a remote server architecture 500. In some examples, remote server architecture 500 provides computation, software, data access, and storage services that do not require end-user knowledge of the physical location or configuration of the system that delivers the services. In various examples, remote servers may deliver the services over a wide area network, such as the internet, using appropriate protocols. For instance, remote servers may deliver applications over a wide area network and may be accessible through a web browser or any other computing component. Software or components shown in FIG. 2 as well as data associated therewith, may be stored on servers at a remote location. The computing resources in a remote server environment may be consolidated at a remote data center location, or the computing resources may be dispersed to a plurality of remote data centers. Remote server infrastructures may deliver services through shared data centers, even though the services appear as a single point of access for the user. Thus, the components and functions described herein may be provided from a remote server at a remote location using a remote server architecture. Alternatively, the components and functions may be provided from a server, or the components and functions can be installed on client devices directly, or in other ways.

(213) In the example shown in FIG. 14, some items are similar to those shown in FIG. 2 and those items are similarly numbered. FIG. 14 specifically shows that predictive model generator 210 or predictive map generator 212, or both, may be located at a server location 502 that is remote from the agricultural harvester 600. Therefore, in the example shown in FIG. 14, agricultural harvester 600 accesses systems through remote server location 502.

(214) FIG. 14 also depicts another example of a remote server architecture. FIG. 14 shows that some elements of FIG. 2 may be disposed at a remote server location 502 while others may be located elsewhere. By way of example, data store 202 may be disposed at a location separate from location 502 and accessed via the remote server at location 502. Regardless of where the elements are located, the elements can be accessed directly by agricultural harvester 600 through a network such as a wide area network or a local area network; the elements can be hosted at a remote site by a service; or the elements can be provided as a service or accessed by a connection service that resides in a remote location. Also, data may be stored in any location, and the stored data may be accessed by, or forwarded to, operators, users, or systems. For instance, physical carriers may be used instead of, or in addition to, electromagnetic wave carriers. In some examples, where wireless telecommunication service

coverage is poor or nonexistent, another machine, such as a fuel truck or other mobile machine or vehicle, may have an automated, semi-automated, or manual information collection system. As the combine harvester **600** comes close to the machine containing the information collection system, such as a fuel truck prior to fueling, the information collection system collects the information from the combine harvester **600** using any type of ad-hoc wireless connection. The collected information may then be forwarded to another network when the machine containing the received information reaches a location where wireless telecommunication service coverage or other wireless coverage—is available. For instance, a fuel truck may enter an area having wireless communication coverage when traveling to a location to fuel other machines or when at a main fuel storage location. All of these architectures are contemplated herein. Further, the information may be stored on the agricultural harvester **600** until the agricultural harvester **600** enters an area having wireless communication coverage. The agricultural harvester **600**, itself, may send the information to another network.

(215) It will also be noted that the elements of FIG. 2, or portions thereof, may be disposed on a wide variety of different devices. One or more of those devices may include an on-board computer, an electronic control unit, a display unit, a server, a desktop computer, a laptop computer, a tablet computer, or other mobile device, such as a palm top computer, a cell phone, a smart phone, a multimedia player, a personal digital assistant, etc.

(216) In some examples, remote server architecture **500** may include cybersecurity measures. Without limitation, these measures may include encryption of data on storage devices, encryption of data sent between network nodes, authentication of people or processes accessing data, as well as the use of ledgers for recording metadata, data, data transfers, data accesses, and data transformations. In some examples, the ledgers may be distributed and immutable (e.g., implemented as blockchain).

(217) FIG. 15 is a simplified block diagram of one illustrative example of a handheld or mobile computing device that can be used as a user's or client's hand held device **16**, in which the present system (or parts of it) can be deployed. For instance, a mobile device can be deployed in the operator compartment of agricultural harvester **100** for use in generating, processing, or displaying the maps discussed above. FIGS. 16-17 are examples of handheld or mobile devices.

(218) FIG. 15 provides a general block diagram of the components of a client device **16** that can run some components shown in FIG. 2, that interacts with them, or both. In the device **16**, a communications link **13** is provided that allows the handheld device to communicate with other computing devices and under some examples provides a channel for receiving information automatically, such as by scanning. Examples of communications link **13** include allowing communication through one or more communication protocols, such as wireless services used to provide cellular access to a network, as well as protocols that provide local wireless connections to networks.

(219) In other examples, applications can be received on a removable Secure Digital (SD) card that is connected to an interface **15**. Interface **15** and communication links **13** communicate with a processor **17** (which can also embody processors or servers from other FIGS.) along a bus **19** that is also connected to memory **21** and input/output (I/O) components **23**, as well as clock **25** and location system **27**.

(220) I/O components **23**, in one example, are provided to facilitate input and output operations. I/O components **23** for various examples of the device **16** can include input components such as buttons, touch sensors, optical sensors, microphones, touch screens, proximity sensors, accelerometers, orientation sensors and output components such as a display device, a speaker, and or a printer port. Other I/O components **23** can be used as well.

(221) Clock **25** illustratively comprises a real time clock component that outputs a time and date. It can also, illustratively, provide timing functions for processor **17**.

(222) Location system **27** illustratively includes a component that outputs a current geographical location of device **16**. This can include, for instance, a global positioning system (GPS) receiver, a LORAN system, a dead reckoning system, a cellular triangulation system, or other positioning system. Location system **27** can also include, for example, mapping software or navigation software that generates desired maps, navigation routes and other geographic functions.

(223) Memory **21** stores operating system **29**, network settings **31**, applications **33**, application configuration settings **35**, data store **37**, communication drivers **39**, and communication configuration settings **41**. Memory **21** can include all types of tangible volatile and non-volatile computer-readable memory devices. Memory **21** may also include computer storage media (described below). Memory **21** stores computer readable instructions that, when executed by processor **17**, cause the processor to perform computer-implemented steps or functions according to the instructions. Processor **17** may be activated by other components to facilitate their functionality as well.

(224) FIG. 16 shows one example in which device **16** is a tablet computer **600**. In FIG. 16, computer **601** is shown with user interface display screen **602**. Screen **602** can be a touch screen or a pen-enabled interface that receives inputs from a pen or stylus. Tablet computer **600** may also use an on-screen virtual keyboard. Of course, computer **601** might also be attached to a keyboard or other user input device through a suitable attachment mechanism, such as a wireless link or USB port, for instance. Computer **601** may also illustratively receive voice inputs as well.

(225) FIG. 17 is similar to FIG. 16 except that the device is a smart phone **71**. Smart phone **71** has a touch sensitive display **73** that displays icons or tiles or other user input mechanisms **75**. Mechanisms **75** can be used by a user to run applications, make calls, perform data transfer operations, etc. In general, smart phone **71** is built on a mobile operating system and offers more advanced computing capability and connectivity than a feature phone.

(226) Note that other forms of the devices **16** are possible.

(227) FIG. 18 is one example of a computing environment in which elements of FIG. 2 can be deployed. With reference to FIG. 18, an example system for implementing some embodiments includes a computing device in the form of a computer **810** programmed to operate as discussed above. Components of computer **810** may include, but are not limited to, a processing unit **820** (which can comprise processors or servers from previous FIGS.), a system memory **830**, and a system bus **821** that couples various system components including the system memory to the processing unit **820**. The system bus **821** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. Memory and programs described with respect to FIG. 2 can be deployed in corresponding portions of FIG. 18.

(228) Computer **810** typically includes a variety of computer readable media. Computer readable media may be any available media that can be accessed by computer **810** and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media is different from, and does not include, a modulated data signal or carrier wave. Computer readable media includes hardware storage media including both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer **810**. Communication media may embody computer readable instructions, data structures, program modules or other data in a transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

(229) The system memory **830** includes computer storage media in the form of volatile and/or nonvolatile memory or both such as read only memory (ROM) **831** and random access memory (RAM) **832**. A basic input/output system **833** (BIOS), containing the basic routines that help to transfer information between elements within computer **810**, such as during start-up, is typically stored in ROM **831**. RAM **832** typically contains data or program modules or both that are immediately accessible to and/or presently being operated on by processing unit **820**. By way of example,

and not limitation, FIG. 18 illustrates operating system 834, application programs 835, other program modules 836, and program data 837.

(230) The computer 810 may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 18 illustrates a hard disk drive 841 that reads from or writes to non-removable, nonvolatile magnetic media, an optical disk drive 855, and nonvolatile optical disk 856. The hard disk drive 841 is typically connected to the system bus 821 through a non-removable memory interface such as interface 840, and optical disk drive 855 are typically connected to the system bus 821 by a removable memory interface, such as interface 850.

(231) Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-specific Integrated Circuits (e.g., ASICs), Application-specific Standard Products (e.g., ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

(232) The drives and their associated computer storage media discussed above and illustrated in FIG. 18, provide storage of computer readable instructions, data structures, program modules and other data for the computer 810. In FIG. 18, for example, hard disk drive 841 is illustrated as storing operating system 844, application programs 845, other program modules 846, and program data 847. Note that these components can either be the same as or different from operating system 834, application programs 835, other program modules 836, and program data 837.

(233) A user may enter commands and information into the computer 810 through input devices such as a keyboard 862, a microphone 863, and a pointing device 861, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 820 through a user input interface 860 that is coupled to the system bus, but may be connected by other interface and bus structures. A visual display 891 or other type of display device is also connected to the system bus 821 via an interface, such as a video interface 890. In addition to the monitor, computers may also include other peripheral output devices such as speakers 897 and printer 896, which may be connected through an output peripheral interface 895.

(234) The computer 810 is operated in a networked environment using logical connections (such as a controller area network—CAN, local area network—LAN, or wide area network WAN) to one or more remote computers, such as a remote computer 880.

(235) When used in a LAN networking environment, the computer 810 is connected to the LAN 871 through a network interface or adapter 870. When used in a WAN networking environment, the computer 810 typically includes a modem 872 or other means for establishing communications over the WAN 873, such as the Internet. In a networked environment, program modules may be stored in a remote memory storage device. FIG. 18 illustrates, for example, that remote application programs 885 can reside on remote computer 880.

(236) It should also be noted that the different examples described herein can be combined in different ways. That is, parts of one or more examples can be combined with parts of one or more other examples. All of this is contemplated herein.

(237) Example 1 is the agricultural work machine of any or all previous examples, comprising:

(238) a communication system that receives a map that includes values of a power characteristic corresponding to different geographic locations in a field;

(239) a geographic position sensor that detects a geographic location of the agricultural work machine;

(240) an in-situ sensor that detects a value of an agricultural characteristic corresponding to the geographic location;

(241) a predictive map generator that generates a functional predictive agricultural map of the field that maps predictive control values to the different geographic locations in the field based on the values of the power characteristic in the map and based on the value of the agricultural characteristic;

(242) a controllable subsystem; and

(243) a control system that generates a control signal to control the controllable subsystem based on the geographic location of the agricultural work machine and based on the control values in the functional predictive agricultural map.

(244) Example 2 is the agricultural work machine of any or all previous examples, wherein the map is a predictive power characteristic map generated based on values from a map and values of a power characteristic detected in-situ.

(245) Example 3 is the agricultural work machine of any or all previous examples, wherein the predictive map generator comprises:

(246) a predictive agricultural characteristic map generator that generates, as the functional predictive agricultural map, a functional predictive agricultural characteristic map that maps, as the predictive control values, predictive values of the agricultural characteristic to the different geographic locations in the field.

(247) Example 4 is the agricultural work machine of any or all previous examples, wherein the in-situ sensor detects, as the value of the agricultural characteristic, a value of an operator command indicative of a commanded action of the agricultural work machine.

(248) Example 5 is the agricultural work machine of any or all previous examples, wherein the predictive map generator comprises:

(249) a predictive operator command map that generates, as the functional predictive agricultural map, a functional predictive operator command map that maps, as the predictive control values, predictive operator command values to the different geographic locations in the field.

(250) Example 6 is the agricultural work machine of any or all previous examples, wherein the control system comprises:

(251) a settings controller that generates an operator command control signal indicative of an operator command based on the detected geographic location and the functional predictive operator command map and controls the controllable subsystem based on the operator command control signal to execute the operator command.

(252) Example 7 is the agricultural work machine of any or all previous examples, wherein the control system generates the control signal to control the control subsystem to adjust a feed rate of material through the agricultural work machine.

(253) Example 8 is the agricultural work machine of any or all previous examples, and further comprising:

(254) a predictive model generator that generates a predictive agricultural model that models a relationship between the power characteristic and the agricultural characteristic based on a value of the power characteristic in the map at the geographic location and the value of the agricultural characteristic detected by the in-situ sensor corresponding to the geographic location, wherein the predictive map generator generates the functional predictive agricultural map based on the values of the power characteristic in the map and based on the predictive agricultural model.

(255) Example 9 is the agricultural work machine of any or all previous examples, wherein the control system further comprises:

(256) an operator interface controller that generates a user interface map representation of the functional predictive agricultural map, the user interface map representation comprising a field portion with one or more markers indicating the predictive control values at one or more geographic locations on the field portion.

(257) Example 10 is the agricultural work machine of any or all previous examples, wherein the operator interface controller generates the user interface map representation to include an interactive display portion that displays a value display portion indicative of a selected value, an interactive threshold display portion indicative of an action threshold, and an interactive action display portion indicative of a control action to be taken when one of the predictive control values satisfies the action threshold in relation to the selected value, the control system generating the control signal to control the controllable subsystem based on the control action.

(258) Example 11 is an example including any or all previous examples, comprising:

(259) obtaining a map that includes values of a power characteristic corresponding to different geographic locations in a field;

(260) detecting a geographic location of the agricultural work machine;

(261) detecting, with an in-situ sensor, a value of an agricultural characteristic corresponding to the geographic location;

(262) generating a functional predictive agricultural map of the field that maps predictive control values to the different geographic locations in the

field based on the values of the power characteristic in the map and based on the value of the agricultural characteristic; and

(263) controlling a controllable subsystem based on the geographic location of the agricultural work machine and based on the control values in the functional predictive agricultural map.

(264) Example 12 is an example including any or all previous examples, wherein obtaining the map comprises:

(265) obtaining a predictive power characteristic map that includes, as values of the power characteristic, predictive values of the power characteristic corresponding to different geographic locations in the field.

(266) Example 13 is an example including any or all previous examples, wherein generating the functional predictive agricultural map comprises:

(267) generating a functional predictive agricultural characteristic map that maps, as the predictive control values, predictive values of the agricultural characteristic to the different geographic locations in the field.

(268) Example 14 is an example including any or all previous examples, wherein detecting, with an in-situ sensor, the value of an agricultural characteristic comprises:

(269) detecting, with the in-situ sensor, as the value of the agricultural characteristic, an operator command indicative of a commanded action of the agricultural work machine.

(270) Example 15 is an example including any or all previous examples, wherein generating the functional predictive agricultural map comprises:

(271) generating a functional predictive operator command map that maps, as the predictive control values, predictive operator command values to the different geographic locations in the field.

(272) Example 16 is an example including any or all previous examples, wherein controlling the controllable subsystem comprises:

(273) generating an operator command control signal indicative of an operator command based on the detected geographic location and the functional predictive operator command map; and

(274) controlling the controllable subsystem based on the operator command control signal to execute the operator command.

(275) Example 17 is an example including any or all previous examples, wherein controlling the controllable subsystem comprises:

(276) controlling the controllable subsystem to adjust a feed rate of material through the agricultural work machine.

(277) Example 18 is an example including any or all previous examples, and further comprising:

(278) generating a predictive agricultural model that models a relationship between the power characteristic and the agricultural characteristic based on a value of the power characteristic in the map at the geographic location and the value of the agricultural characteristic detected by the in-situ sensor corresponding to the geographic location, wherein generating the functional predictive agricultural map comprises generating the functional predictive agricultural map based on the values of the power characteristic in the map and based on the predictive agricultural model.

(279) Example 19 is the agricultural work machine of any or all previous examples comprising, a communication system that receives a map that includes values of a power characteristic corresponding to different geographic locations in a field;

(280) a geographic position sensor that detects a geographic location of the agricultural work machine

(281) an in-situ sensor that detects a value of an agricultural characteristic corresponding to the geographic location;

(282) a predictive model generator that generates a predictive agricultural model that models a relationship between the power characteristic and the agricultural characteristic based on a value of the power characteristic in the map at the geographic location and the value of the agricultural characteristic detected by the in-situ sensor corresponding to the geographic location;

(283) a predictive map generator that generates a functional predictive agricultural map of the field that maps predictive control values to the different geographic locations in the field based on the values of the power characteristic in the map and based on the predictive agricultural model;

(284) a controllable subsystem; and

(285) a control system that generates a control signal to control the controllable subsystem based on the geographic position of the agricultural work machine and based on the control values in the functional predictive agricultural map.

(286) Example 20 is the agricultural work machine of any or all previous examples, wherein the control system comprises at least one of:

(287) a feed rate controller that generates a feed rate control signal based on the detected geographic location and the functional predictive agricultural map and controls the controllable subsystem based on the feed rate control signal to control a feed rate of material through the agricultural work machine;

(288) a settings controller that generates a speed control signal based on the detected geographic location and the functional predictive agricultural map and controls the controllable subsystem based on the speed control signal to control a speed of the agricultural work machine;

(289) a header controller that generates a header control signal based on the detected geographic location and the functional predictive agricultural map and controls the controllable subsystem based on the header control signal to control a distance of at least a portion of a header on the agricultural work machine from a surface of the field; and

(290) a settings controller that generates an operator command control signal indicative of an operator command based on the detected geographic location and the functional predictive agricultural map and controls the controllable subsystem based on the operator command control signal to execute the operator command.

(291) Although the subject matter has been described in language specific to structural features or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of the claims.

Claims

1. An agricultural system, comprising: a communication system that receives an information map that includes values of a power characteristic, as a first agricultural characteristic, corresponding to different geographic locations in a field; a geographic position sensor that detects a geographic location of an agricultural work machine; an in-situ sensor that detects a value of a second agricultural characteristic corresponding to a geographic location, wherein the second agricultural characteristic is different than the first agricultural characteristic; a predictive map generator that generates a functional predictive agricultural map of the field that maps predictive values of the second agricultural characteristic to the different geographic locations in the field based on a value of the first agricultural characteristic in the information map corresponding to the geographic location and based on the value of the second agricultural characteristic detected by the in-situ sensor corresponding to the geographic location; and a control system configured to control a controllable subsystem of the agricultural work machine based on the geographic location of the agricultural work machine and based on the predictive values of the second agricultural characteristic in the functional predictive agricultural map.
2. The agricultural system of claim 1, wherein the functional predictive agricultural map is a functional predictive power map that maps, as the values of the power characteristic, predictive values of the power characteristic corresponding to the different geographic locations in the field, the functional predictive power map generated based on values of a third agricultural characteristic in the information map and values of the power characteristic detected in-situ.
3. The agricultural system of claim 1, wherein the in-situ sensor detects, as the value of the second agricultural characteristic, a value of an operator command indicative of a commanded action of the agricultural work machine.
4. The agricultural system of claim 3, wherein the predictive map generator comprises: a predictive operator command map generator that generates, as the functional predictive agricultural map, a functional predictive operator command map that maps, as the predictive values of the

- second agricultural characteristic, predictive operator command values to the different geographic locations in the field.
5. The agricultural system of claim 4, wherein the control system comprises: a settings controller that generates an operator command control signal indicative of an operator command based on the detected geographic location of the agricultural work machine and the functional predictive operator command map and controls the controllable subsystem based on the operator command control signal to execute the operator command.
6. The agricultural system of claim 1, wherein the control system generates the control signal to control the control subsystem to adjust a feed rate of material through the agricultural work machine.
7. The agricultural system of claim 1 and further comprising: a predictive model generator that generates a predictive agricultural model that models a relationship between the first agricultural characteristic and the second agricultural characteristic based on the value of the first agricultural characteristic in the information map corresponding to the geographic location and the value of the first agricultural characteristic detected by the in-situ sensor corresponding to the geographic location, wherein the predictive map generator generates the functional predictive agricultural map based on the value of the first agricultural characteristic in the information map corresponding to the geographic location and based on the predictive agricultural model.
8. The agricultural system of claim 1, wherein the control system further comprises; an operator interface controller that generates a user interface map representation of the functional predictive agricultural map, the user interface map representation comprising a field portion with one or more markers indicating the predictive values of the second agricultural characteristic at one or more geographic locations on the field portion.
9. The agricultural system of claim 8, wherein the operator interface controller generates the user interface map representation to include an interactive display portion that displays a value display portion indicative of a selected value, an interactive threshold display portion indicative of an action threshold, and an interactive action display portion indicative of a control action to be taken when one of the predictive values of the second agricultural characteristic satisfies the action threshold in relation to the selected value, the control system generating the control signal to control the controllable subsystem based on the control action.
10. A computer implemented method of controlling an agricultural work machine comprising: obtaining an information map that includes values of a power characteristic, as a first agricultural characteristic, corresponding to different geographic locations in a field; detecting a geographic location of the agricultural work machine; detecting, with an in-situ sensor, a value of a second agricultural characteristic corresponding to a geographic location, wherein the second agricultural characteristic is different than the first agricultural characteristic; generating a functional predictive agricultural map of the field that maps predictive values of the second agricultural characteristic to the different geographic locations in the field based on a value of the first agricultural characteristic in the information map corresponding to the geographic location and based on the value of the second agricultural characteristic detected by the in-situ sensor corresponding to the geographic location; and controlling a controllable subsystem of the agricultural work machine based on the geographic location of the agricultural work machine and based on the predictive values of the second agricultural characteristic in the functional predictive agricultural map.
11. The computer implemented method of claim 10, wherein obtaining the information map comprises: obtaining a predictive power characteristic map that includes, as values of the power characteristic, predictive values of the power characteristic corresponding to different geographic locations in the field.
12. The computer implemented method of claim 10, wherein detecting, with an in-situ sensor, the value of the second agricultural characteristic comprises: detecting, with the in-situ sensor, as the value of the second agricultural characteristic, an operator command indicative of a commanded action of the agricultural work machine.
13. The computer implemented method of claim 12, wherein generating the functional predictive agricultural map comprises: generating a functional predictive operator command map that maps, as the predictive values of the second agricultural characteristic, predictive operator command values to the different geographic locations in the field.
14. The computer implemented method of claim 13, wherein controlling the controllable subsystem comprises: generating an operator command control signal indicative of an operator command based on the detected geographic location of the agricultural work machine and the functional predictive operator command map; and controlling the controllable subsystem based on the operator command control signal to execute the operator command.
15. The computer implemented method of claim 10, wherein controlling the controllable subsystem comprises: controlling the controllable subsystem to adjust a feed rate of material through the agricultural work machine.
16. The computer implemented method of claim 10 and further comprising: generating a predictive agricultural model that models a relationship between the first agricultural characteristic and the second agricultural characteristic based on a value of the first agricultural characteristic in the map at the geographic location and the value of the second agricultural characteristic detected by the in-situ sensor corresponding to the geographic location, wherein generating the functional predictive agricultural map comprises generating the functional predictive agricultural map based on the values of the first agricultural characteristic in the map and based on the predictive agricultural model.
17. The computer implemented method of claim 10, wherein obtaining the information map comprises obtaining the information map as the agricultural work machine operates at the field during a current operation, and wherein the controlling the controllable subsystem of the agricultural work machine comprises controlling the controllable subsystem as the agricultural work machine operates at the field.
18. The computer implemented method of claim 17, wherein the information map, is a functional predictive power characteristic map that includes, as the values of the power characteristic corresponding to the different geographic locations of the field, predictive values of the power characteristic corresponding to the different geographic locations in the field, the method further comprising: obtaining an additional information map that includes values of a third agricultural characteristic corresponding to the different geographic locations in the field, the third agricultural characteristic different than both the first agricultural characteristic and the second agricultural characteristic; detecting, with an in-situ power sensor, a value of the power characteristic corresponding to an additional geographic location; and generating the functional predictive power characteristic map that maps the predictive values of the power characteristic corresponding to the different geographic locations in the field based on a value of the third agricultural characteristic in the additional information map corresponding to the additional geographic location and based on the value of the power characteristic detected by the in-situ power sensor corresponding to the additional geographic location.
19. An agricultural system comprising: a communication system that receives an information map that includes values of a power characteristic, as a first agricultural characteristic, corresponding to different geographic locations in a field; a geographic position sensor that detects a geographic location of an agricultural work machine an in-situ sensor that detects a value of a second agricultural characteristic corresponding to a geographic location, wherein the second agricultural characteristic is different than the first agricultural characteristic; a predictive model generator that generates a predictive agricultural model that models a relationship between the first agricultural characteristic and the second agricultural characteristic based on a value of the first agricultural characteristic in the information map at the geographic location to which the value of the second agricultural characteristic detected by the in-situ sensor corresponds and the value of the second agricultural characteristic detected by the in-situ sensor corresponding to the geographic location; a predictive map generator that generates a functional predictive agricultural map of the field that maps predictive values of the second agricultural characteristic to the different geographic locations in the field based on a value of the first agricultural characteristic in the information map corresponding to the geographic location and based on the predictive agricultural model; a control system that controls a controllable subsystem of the agricultural work machine based on the geographic location of the agricultural work machine and based on the predictive values of the second agricultural characteristic in the functional predictive agricultural map.
20. The agricultural system of claim 19, wherein the control system comprises at least one of: a feed rate controller that generates a feed rate

control signal based on the detected geographic location of the agricultural work machine and the functional predictive agricultural map and controls the controllable subsystem based on the feed rate control signal to control a feed rate of material through the agricultural work machine; a settings controller that generates a speed control signal based on the detected geographic location of the agricultural work machine and the functional predictive agricultural map and controls the controllable subsystem based on the speed control signal to control a speed of the agricultural work machine; a header controller that generates a header control signal based on the detected geographic location of the agricultural work machine and the functional predictive agricultural map and controls the controllable subsystem based on the header control signal to control a distance of at least a portion of a header on the agricultural work machine from a surface of the field; and a settings controller that generates an operator command control signal indicative of an operator command based on the detected geographic location of the agricultural work machine and the functional predictive agricultural map and controls the controllable subsystem based on the operator command control signal to execute the operator command.
