

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387175
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Cupala; Shiraz J. et al.

Object for pre- to post-meeting collaboration

Abstract

Traditionally, meetings are widely utilized in business and personal communications, whether in-person and/or virtual. Organizing such meetings typically involves multiple exchanges of content and messages between users before, during, and after the meeting. In some cases, meetings may occur impromptu and may result in inefficient and unproductive collaboration. A collaboration object configured to enable users to dynamically collaborate before, during, and after a meeting is provided. In aspects, the collaboration object links content generated before, during, and after the meeting in a single location and provides functionality for concurrent multi-user interaction and synchronization of the content across applications. The collaboration object may be available from a variety of application platforms, enabling and persisting real-time editing and collaboration before, during and after the meeting.

Inventors: Cupala; Shiraz J. (Snohomish, WA), Hull; Eric (Seattle, WA), Morrison; Kevin Daniel (Arlington, MA), Ye; Lan (Redmond, WA), Prabhakar; Shivaram (Bothell, WA), Foran; Julia (Kirkland, WA), Kardos, Jr.; James Paul (Sammamish, WA), Madejczyk; Szymon (Sammamish, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 80626359

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 18/527633

Filed: December 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240112142 A1	Apr. 04, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06Q10/00** (20230101); **G06Q10/101** (20230101); **G06Q10/1093** (20230101);
G06F3/04847 (20220101)

U.S. Cl.:

CPC **G06Q10/101** (20130101); **G06Q10/1095** (20130101); G06F3/04847 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7958453	12/2010	Taing	709/204	H04L 12/1827
10389769	12/2018	Gudipaty et al.	N/A	N/A
11824670	12/2022	Jin	N/A	N/A
2009/0006982	12/2008	Curtis	715/753	G06Q 10/10
2009/0222741	12/2008	Shaw	709/248	G06Q 10/109
2011/0035323	12/2010	Hamilton	N/A	N/A
2013/0091205	12/2012	Kotler	709/204	H04L 67/54
2014/0310345	12/2013	Megiddo	709/204	G06Q 10/101
2016/0112476	12/2015	Gudipaty	715/753	G06F 3/04842
2016/0342571	12/2015	Lane	N/A	H04W 4/18
2017/0315974	12/2016	Kong	N/A	G06F 40/166
2017/0364866	12/2016	Steplyk	N/A	G06Q 10/063114
2018/0260790	12/2017	Connolly et al.	N/A	N/A
2019/0288968	12/2018	Chilakamarri	N/A	H04L 65/403
2019/0312742	12/2018	Albrecht	N/A	H04L 12/1822
2020/0410457	12/2019	Sexauer	N/A	G06Q 10/109
2021/0168177	12/2020	Henderson	N/A	N/A
2024/0378566	12/2023	Cupala	N/A	N/A
2024/0380626	12/2023	Cupala	N/A	N/A

OTHER PUBLICATIONS

14. H Nguyen, T Bednarz et al. (User experience in collaborative extended reality: overview study)—Virtual Reality and Augmented Reality: 17th . . . 2020—Springer (Year: 2020). cited by examiner

15. SH Cho, SH Kim et al. (Suggestion for collaboration-based UI/UX development model through risk analysis)—Journal of Information Processing Systems, 2020—koreascience.kr (Year: 2020) cited by examiner

Notice of Allowance mailed on Jul. 10, 2024, in U.S. Appl. No. 18/154,514, 08 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No.

PCT/US2024/027329, Jul. 19, 2024, 17 pages. cited by applicant

Non-Final Office Action mailed on Aug. 1, 2024, in U.S. Appl. No. 18/144,538, 27 pages. cited by applicant

Non-Final Office Action mailed on Aug. 1, 2024, in U.S. Appl. No. 18/348,310, 28 pages. cited by applicant

Final Office Action mailed on Dec. 4, 2024, in U.S. Appl. No. 18/348,310, 29 pages. cited by applicant

Non-Final Office Action mailed on Mar. 21, 2024, in U.S. Appl. No. 18/154,514, 10 pages. cited by applicant

Notice of Allowance mailed on Dec. 18, 2023, in U.S. Appl. No. 17/179,186, 9 pages. cited by applicant

Primary Examiner: Kassim; Hafiz A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a division of U.S. patent application Ser. No. 17/179,151, filed on Feb. 18, 2021, now U.S. Pat. No. 11,836,679, the disclosure of which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) Meetings, whether in-person and/or virtual, are widely utilized in business and personal communications. Organizing such meetings typically involves multiple exchanges of content and messages between users before, during, and after the meeting. In some cases, meetings may occur impromptu or ad hoc, increasing the potential for unproductive or wasted time due to lack of planning and organization. However, even pre-scheduled meetings fall prey to disorganization or miscommunication regarding agenda items, participant roles, time allotments, and the like. For pre-scheduled meetings, for example, an organizer may send a sample agenda, suggested presenters, documents, and the like, via a message (e.g., an email or a chat message) to multiple invitees. The invitees and the meeting organizer may then communicate via a message thread (or threads) in which users may exchange multiple messages regarding suggested agenda or action items, notes or suggestions, new or revised documents, and the like. The meeting organizer and the attendees must then sift through multiple messages to collate information for an organized discussion during the meeting. Not only so, but whether or not a meeting is pre-scheduled, attendees often maintain separate notetaking during the meeting, which may result in disparate impressions and objectives both during and after the meeting. As a result, collaboration between users before, during, and after a meeting is often inefficient and unproductive.

(2) It is with respect to these and other general considerations that embodiments have been described. Also, although relatively specific problems have been discussed, it should be understood that the embodiments should not be limited to solving the specific problems identified in the background.

SUMMARY

(3) In accordance with examples of the present disclosure, a persistent collaboration object may be configured to enable users to dynamically collaborate before, during, and after a meeting. The collaboration object may provide a single location for creating a meeting request and a meeting agenda; attaching meeting documents, links, apps, recordings, whiteboard sessions, transcripts, and the like; collaborating and co-authoring content; providing an entry point for joining the meeting; and the like.

(4) The methods and systems described herein provide for generating a collaboration object to persistently capture content and collaboration related to meetings. Once generated, the collaboration object may comprise a portable interface having functionality for concurrent multi-user interaction with the content. A “meeting” may be pre-scheduled or may occur as a result of impromptu collaboration between users. In a first aspect, a pre-scheduled meeting may be defined by an organizer via a meeting request or invitation. In aspects, the meeting request may automatically be populated with an object template for generating a collaboration object. The object template may be in the form of a structured framework including meeting components for receiving and organizing meeting content, including an agenda component, a note component, and an action item component, for instance. Once the meeting invitation is sent to invitees, the organizer and invitees may collaborate on the collaboration object persistently and in real-time before, during, and after the meeting. For instance, in addition to receiving user input into data fields of the meeting components (e.g., agenda items, notes, action items), any content discussed or shared before, during, or after the meeting may automatically be associated with the collaboration object. Such content may include, for example, presentations, word processing documents, spreadsheets, images, videos, hyperlinks, linked applications, whiteboard sessions, and the like.

(5) In a second aspect, an impromptu collaboration among users may be detected and a collaboration object may automatically be generated. Impromptu collaboration may involve phone calls (e.g., IP-based calls), chat threads, email threads, channel conversations, and the like. For instance, data indicative of a call between users or a series of communications within a channel or chat thread may be detected. In response to detecting the collaboration, a collaboration object may automatically be generated and linked to the collaboration, e.g., within a group channel of a collaborative platform. Similar to the above example, the collaboration object may comprise a structured framework for receiving content input such as agenda items, notes, action items, and the like. Content may also be attached to the collaboration object, such as presentations, documents, spreadsheets, images, videos, and the like. In addition to receiving user input and/or attachment, any content discussed or shared during the collaboration may automatically be associated with the collaboration object, e.g., hyperlinks, whiteboard sessions, mind maps, and the like. In this way, although the meeting was not pre-scheduled, users are able to quickly organize the discussion by inputting agenda items, notes, and action items into the common collaboration object. After the meeting, users are able to continue to add content and collaborate.

(6) In aspects, whether a meeting was pre-scheduled or impromptu, the collaboration object may be made available across multiple applications, including a collaborative meeting platform, a calendar/messaging application, a planner application, a notebook application, and the like. During either pre-scheduled or impromptu meetings, additional applications or application functionality may be made available for collaboration, such as a chat board, recording capability, whiteboard application, graphics, mind maps, etc. After the meeting, an overall summary or digest of meeting content may be compiled and automatically associated with the collaboration object, including recordings, transcripts, one or more whiteboard sessions, an attendance list, and the like. The collaboration object may be persisted such that all of the associated content and collaboration for the meeting is available thereafter from a single location.

(7) In an example, a system comprising at least one processing unit and at least one memory storing computer-executable instructions that, when executed by the at least one processor, cause the at least one processor to perform operations. The operations include collecting data to detect an intention to collaborate. The operations further include automatically generating a prompt for scheduling a collaboration and, in response to a selection, automatically generating a meeting invitation comprising a collaboration object. Additionally, the operations include receiving content to the collaboration object from a first user, where the collaboration object provides functionality for concurrent multi-user interaction with the content, and causing the meeting invitation including the collaboration object to be sent to at least a second user. The operations also include causing the

collaboration object to be automatically updated at a first device associated with the first user at substantially the same time as a change to the content is received at a second device associated with the second user.

(8) In another example, a method for generating a collaboration object is provided. The method includes detecting an impromptu collaboration between at least two users and automatically launching a collaborative interface including a collaboration object, where the collaboration object provides functionality for concurrent multi-user interaction. The method further includes receiving user input to the collaboration object by a first participant at a first user device and automatically causing the user input to the collaboration object to be reflected in near real-time at a second user device associated with a second participant. Additionally, the method includes detecting content shared by the second participant during the collaboration and automatically causing the shared content to be reflected in near real-time in the collaboration object across at least the collaborative interface and a second application. The method also includes persisting the collaboration object to enable concurrent multi-user interaction with the collaboration object after the collaboration.

(9) In yet another example, a computer storage medium is provided. The computer storage medium stores computer-executable instructions that when executed cause at least one processor to perform operations. The operations include detecting an impromptu collaboration between at least two users and automatically launching a first application including a collaboration object, where the collaboration object comprises functionality for concurrent multi-user interaction. The operations further include detecting content shared by a participant via a second application during the collaboration and automatically causing the shared content to be reflected in near real-time in the collaboration object across at least the first application and the second application. Additionally, the operations include persisting the collaboration object to enable concurrent multi-user interaction with the collaboration object via at least the first application and the second application after the collaboration.

(10) Any of the one or more above aspects in combination with any other of the one or more aspects. Any of the one or more aspects as described herein.

(11) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Non-limiting and non-exhaustive examples are described with reference to the following Figures.

(2) FIG. 1 is a block diagram of a system for implementing a collaboration object associated with one or more collaborative user experiences (UXs), in accordance with an embodiment of the present disclosure.

(3) FIGS. 2A-D depict a user interface of a calendar/messaging application for generating a collaboration object, in accordance with examples of the present disclosure.

(4) FIGS. 3A-C depict user interfaces of different applications that provide a collaboration object for enabling users to collaborate before a meeting, in accordance with examples of the present disclosure.

(5) FIGS. 4A-G depict user interfaces of different applications that provide a collaboration object for enabling users to collaborate during a meeting, in accordance with examples of the present disclosure.

(6) FIGS. 5A-B depict user interfaces of different applications that provide a collaboration object

for enabling users to collaborate after a meeting, in accordance with examples of the present disclosure.

(7) FIGS. 6A-C illustrate an example method for generating and utilizing a collaboration object, in accordance with aspects of the present disclosure.

(8) FIGS. 7A-B illustrate an example method for receiving a meeting invitation including a collaboration object, in accordance with aspects of the present disclosure.

(9) FIGS. 8A-B depict a user interface of a collaborative platform for identifying and implementing a user objective to schedule a meeting, in accordance with examples of the present disclosure.

(10) FIGS. 9A-E depict different user interfaces of different applications for identifying and implementing a user objective to schedule a call, in accordance with examples of the present disclosure.

(11) FIGS. 10A-C depict a user interface of a collaborative platform for detecting a user collaboration and automatically generating a collaboration object, in accordance with examples of the present disclosure.

(12) FIG. 11 illustrates an example method for detecting and implementing a user objective to schedule a collaboration, in accordance with aspects of the present disclosure.

(13) FIG. 12 illustrates an example method for detecting a user collaboration and automatically generating a collaboration object, in accordance with aspects of the present disclosure.

(14) FIG. 13 is a block diagram illustrating physical components (e.g., hardware) of a computing device with which aspects of the disclosure may be practiced.

(15) FIGS. 14A-B illustrate a mobile computing device with which embodiments of the disclosure may be practiced.

DETAILED DESCRIPTION

(16) In the following detailed description, references are made to the accompanying drawings that form a part hereof, and in which are shown by way of illustrations specific embodiments or examples. These aspects may be combined, other aspects may be utilized, and structural changes may be made without departing from the present disclosure. Embodiments may be practiced as methods, systems, or devices. Accordingly, embodiments may take the form of a hardware implementation, an entirely software implementation, or an implementation combining software and hardware aspects. The following detailed description is therefore not to be taken in a limiting sense, and the scope of the present disclosure is defined by the appended claims and their equivalents.

(17) Traditionally, meetings are widely utilized in business and personal communications, whether in-person and/or virtual. Organizing such meetings typically involves multiple exchanges of content and messages between users before, during, and after the meeting. In some cases, meetings may occur impromptu or ad hoc, increasing the potential for unproductive or wasted time due to lack of planning and organization. However, even pre-scheduled meetings fall prey to disorganization or miscommunication regarding agenda items, participant roles, time allotments, and the like. For pre-scheduled meetings, for example, an organizer may send a sample agenda, suggested presenters, documents, and the like, via a message (e.g., an email or a chat message) to multiple invitees before the meeting. The invitees and the meeting organizer may then communicate via a message thread (or threads) in which users may exchange multiple messages regarding suggested agenda or action items, notes or suggestions, new or revised documents, and the like. The meeting organizer and the attendees must then sift through multiple messages to collate information for an organized discussion during the meeting. Not only so, but whether or not a meeting is pre-scheduled, attendees often maintain separate notetaking during the meeting, which may result in disparate impressions and objectives both during and after the meeting. As a result, collaboration between users before, during, and after a meeting is often inefficient and unproductive.

(18) A collaboration object configured to enable users to dynamically collaborate before, during,

and after a meeting is provided. In aspects, the collaboration object links content generated before, during, and after the meeting in a single location, where content may broadly include linked apps (e.g., third-party apps such as Trello™, Salesforce™, etc.), linked content (e.g., YouTube videos, websites, webpages, shared documents, etc.), static content (e.g., attached documents, presentations, images, videos, etc.), created content (e.g., meeting recordings, whiteboard sessions, etc.), dynamic content (e.g., collaboration-enabled notebook documents, agendas, notes, etc.), text content (e.g., chat threads, call transcripts, etc.), and the like. The collaboration object may be available from a variety of application platforms, enabling and persisting real-time editing and collaboration before, during and after the meeting.

(19) In aspects, dynamic content may refer to content that is collaboration enabled and static content may refer to content that is not collaboration enabled. Edits (e.g., additions, deletions, changes) to collaboration-enabled content may be reflected in near real-time across user systems. For example, while an edit is being made to dynamic content on one user system, the edit may be reflected at substantially (or nearly) the same time on another user system. “Near” real-time (or substantially real-time) may account for a minimal delay associated with transmission and synchronization of changes due to resource availability, processing speeds, network bandwidth, and the like. In contrast, edits to static content are not reflected in near real-time across user systems. This is not to be confused with the nature of the content itself, however. For instance, a video may be referred to herein as “static content” if the video is not collaboration enabled, regardless of whether the video could be referred to as dynamic in other contexts.

(20) It should be appreciated that although, for exemplary purposes, described embodiments generally relate to messaging applications, e.g., such as email applications, chat applications, collaborative platforms, and the like, the present methods and systems are not so limited. For example, interactive components described herein may be used to provide collaborative experiences in applications other than messaging applications, such as word processing applications, spreadsheet applications, notebook applications, presentation applications, instant messaging or chat applications, social networking platforms, and the like.

(21) FIG. 1 is a block diagram of a system for implementing a collaboration object associated with one or more collaborative user experiences (UXs), in accordance with an embodiment of the present disclosure.

(22) In particular, FIG. 1 illustrates an overview of an example system **100** through which an object template **118** may be automatically included in a meeting invite **112** being composed via a first user interface **116A** associated with a first application **104A** (e.g., a calendar/messaging application). In aspects, a meeting organizer (e.g., user **110A**) may add content **124** to the object template **118**, where content **124** may include documents, agenda items, action items, notes, or the like. A collaboration object **132** may be generated based on the object template **118** including content **124**. Collaboration object **132** may comprise a portable interface having functionality for concurrent multi-user interaction with the content **124**. Content **124** associated with collaboration object **132** may be updated by one or more users via the first application **104** or at least a second application **138** in a collaborative environment.

(23) The collaboration object **132** may be associated with metadata for generating one or more collaborative user experiences (UXs), e.g., first collaborative UX **130** and second collaborative UX **142**. A collaborative UX may customize the portable interface and functionality of the collaboration object **132** for a particular hosting application, e.g., the first application **104** and/or the second application **138**. In aspects, while first collaborative UX **130** and second collaborative UX **142** may exhibit similar functionality for supporting collaborative user interactions, first collaborative UX **130** may be customized so as to exhibit a similar look and/or feel (e.g., theming, color scheme, layout, design elements, etc.) to first user interface **116** associated with first application **104** and second collaborative UX **142** may exhibit a similar look and/or feel to second user interface **140** associated with second application **138**. That is, the first collaborative UX **130** may appear to be

native to the first application **104** and second collaborative UX **142** may appear to be native to the second application **138**. In aspects, the first collaborative UX **130** may be different from the second collaborative UX **142**, e.g., based on different functionality, theming, color scheme, layout, design elements, and the like.

(24) In aspects, interactions with other users and/or the collaboration object **132** via the one or more collaborative UXs may occur before, during and/or after a meeting associated with the collaboration object **132**. Such interactions may involve concurrent editing of content **124**, instant messaging (e.g., chatting) regarding the meeting and/or the content **124**, a virtual meeting regarding content **124** (e.g., hosted by a second application), and the like. User interactions with collaboration object **132** may be received and synchronized across the collaborative UX **130** and collaborative UX **142** in near real-time, for example. That is, regardless of the application used to access the collaboration object **132**, a current state of content **124** may be provided. As noted above, content **124** may be updated before, during, or after an associated meeting. In aspects, updating content **124** may involve editing, adding, deleting, or otherwise changing the content **124**. For example, updating content **124** may include associating (e.g., attaching or linking) additional content with collaboration object **132**, e.g., a recording of the virtual meeting, a transcript of the recording, content created during the meeting (e.g., a whiteboard session), a meeting recap, and the like. Updating content **124** may also include concurrent editing of content **124** before, during, or after the meeting, such as by adding to a chat thread, or editing agenda items, notes, action items, and the like. In still further aspects, individual portions of content **124** may be shared and collaborated on. That is, the agenda may be shared in a chat thread and any updates to the agenda items by participants may be reflected not only in the chat thread, but in an agenda section of the collaboration object **132** across collaborative UXs for each hosting application.

(25) The system **100** may include a plurality of user devices **102A-B** configured to run or otherwise execute first application **104A-B** and/or second application **138**. The user devices **102A-B** may include, but are not limited to laptops, tablets, desktop computers, wearable devices, smartphones, and the like. The first application **104A-B** and second application **138** (“hosting applications”) may include applications having messaging functionality, such as email applications, chat applications, calendaring applications, collaborative platforms (e.g., including virtual meeting functionality), instant messengers, and the like, and/or may include other types of applications, such as notebook applications. Non-limiting examples of first application **104** and/or second application **138** include Microsoft Outlook™, Gmail™, Microsoft Teams™, Google Hangouts™, Facebook Messenger™, Microsoft Office™ suite, Microsoft 365™, Google Drive™, and the like. In some examples, the first application **104A-B** and second application **138** may include web applications, such as but not limited to Microsoft Outlook Web Access™ (OWA) or Gmail™ web applications, where such first application **104A-B** and second application **138** may run or otherwise execute instructions on servers in the cloud via web browsers. In some examples, the first application **104A-B** and second application **138** may additionally or alternatively include native client applications residing on the user devices **102A-B**.

(26) The plurality of user devices **102A-B** may be communicatively coupled to one or more servers **136A-B** and/or a data host **106** associated with one or more storage components **120** via a communication network **108**. In aspects servers **136A-B** may comprise a single server **136** (e.g., associated with multiple virtual servers) or multiple servers **136**, such as a server farm or multiple server farms. The servers **136A-B** may perform the same or different processes. For example, one server **136A** may evaluate host first application **104A-B** and/or second application **138** and another server **136B** may interact with data host **106** to manage the one or more data storage components **120**. In another example, a single server **136** may perform multiple of the processes above. A storage component **120** may be, for example, a file in a user drive that may be associated with the user **110A** (e.g., meeting organizer) on data host **106**. Alternatively, a storage component **120** may comprise any suitable data structure or partitioned memory other than a file for storing data

associated with generating one or more collaborative UXs (e.g., first collaborative UX **130** and/or second collaborative UX **142**).

(27) Communication network **108** may enable communication between the first application **104A-B**, servers **136A-B**, and data host **106**, as well as communication between different ones of the first application **104A-B** and second application **138**. The communication network **108** may be a wide area network (WAN) such as the Internet, a local area network (LAN), or any other suitable type of communication network. Additionally or alternatively, communication network **108** may operate over distributed systems (e.g., cloud-based computing systems), where application functionality, memory, data storage and retrieval, and various processing functions may be operated remotely from each other over a distributed system, such as the Internet or an intranet. In some embodiments, communication network **108** may be a single communication network or may be made up of multiple different communication networks. Non-limiting examples of data host **106** include Microsoft SharePoint™, Microsoft OneDrive™, Google Drive™, Amazon Web Services™ (AWS), and DropBox.™ In some embodiments, the data host **106** may be shared and accessible by at least first application **104A-B** in a suitable manner other than via the communication network **108**. In some examples, the data host **106** may be included in or directly coupled to user devices **102A-B**, and may be locally accessible by first application **104A-B** and/or second application **138** executing on the user devices **102A-B**, or first application **104A-B** and/or second application **138** executing on user devices **102A-B** may access the data host **106** by way of the communication network **108**.

(28) The first application **104A-B** and second application **138** may allow users **110A-B** associated with user devices **102A-B** to communicate via messages (e.g., email messages, text messages, instant messages), virtual meetings involving video and/or audio, or otherwise interact, over the communication network **108**. In one embodiment, first application **104A** may be configured to receive content **124** to an object template **118** associated with a compose meeting invite **112A** (e.g., a meeting invitation prior to sending). As described above, collaboration object **132** may be generated based on the object template **118** including content **124**. In aspects, the collaboration object **132** may comprise a portable interface having functionality for concurrent multi-user interaction with the content **124**. The collaboration object **132** may also be associated with metadata for generating one or more collaborative user experiences (UXs), e.g., first collaborative UX **130** and second collaborative UX **142**. The metadata may include information for retrieving content **124** (e.g., stored within a storage component **120** on data host **106**) and for rendering the first collaborative UX **130**, such as a code pointer to custom code for generating the first collaborative UX **130** and a load pointer to a code loader for ingesting the metadata and loading the first collaborative UX **130**, for example. Similarly, the metadata may include information for rendering the second collaborative UX **142**, such as a code pointer to custom code for generating the second collaborative UX **142** and a load pointer to a code loader for ingesting the metadata and loading the second collaborative UX **142**. In aspects, the metadata may provide information for customizing the first collaborative UX **130** for the first application **104A-B** and customizing the second collaborative UX **142** for the second application **138**.

(29) In aspects, based on the metadata, first application **104A** associated with first user **110A** (meeting organizer) may be configured to automatically convert object template **118** (including content **124**) into first collaborative UX **130A** (including collaboration object **132A**) within the compose meeting invite **112A** (e.g., prior to sending). After sending the meeting invite **112A**, first collaborative UX **130A** may also be reflected within a scheduled meeting **114** on a calendar of first user **110A**. Similarly, after sending meeting invite **112A**, first application **104B** associated with second user **110B** (recipient or attendee) may be configured to render a first collaborative UX **130B** within received meeting invite **112B**, whether or not the second user **110B** “accepts” the meeting invite **112B** to schedule a meeting on a calendar associated with the second user **110B**. In aspects, first collaborative UXs **130A-B** may be considered “in-line” within the context of first application

104A-B such that users **110A-B** need not navigate away from first application **104A-B** to interactive with other users and/or collaboration object **132A-B**.

(30) In some aspects, compose meeting invite **112A** may be sent in a message (e.g., an email or chat message) from first user **110A** (sender, meeting organizer) to second user **110B** (recipient, attendee). The first user **110A** may interact with the collaboration object **132A** via collaborative UX **130A** within the meeting invite **112A** and/or the scheduled meeting **114**. Additionally, first user **110A** may interact with collaborative UX **130A** within the sent message associated with meeting invite **112A**. Similarly, second user **110B** may interact with the collaboration object **132B** via collaborative UX **130B** within the received meeting invite **112B** associated with a received message. In aspects, second user **110B** is also able to interact with the collaboration object **132B** via collaborative UX **130B** within a scheduled meeting in a calendar of the second user **110B** (not shown). In this example, users **110A-B** may collaborate via collaborative UX **130A-B** without exchanging further messages and without navigating away from the first application **104A-B** (e.g., host application such as a calendar/messaging application).

(31) In other aspects, metadata associated with the collaboration object **132** may also provide information for rendering collaborative UXs in the contexts of applications other than calendar/messaging applications (e.g., second application **138**). The second application **138** may comprise, for example, a collaborative platform (e.g., Microsoft Teams™, ZOOM™ conferencing platform, WebEx™ conferencing platform, Slack™, Google Hangouts™, etc.), a productivity application (e.g., OneNote™), and the like. In this case, in addition to accessing the collaboration object **132** via collaborative UX **130** customized for first application **104A-B**, the first user **110A** and/or the second user **110B** may access the collaboration object **132** via collaborative UX **142** customized for the second application **138**.

(32) In some embodiments, the first collaborative UX **130** and/or collaborative UX **142** may be configured to receive one or more changes to content **124** of the collaboration object **132** from a user (e.g., first user **110A** or second user **110B**). The received change may then be communicated to server **136B** and/or directly to data host **106**. The data associated with the collaboration object **132** (e.g., content **124**) in storage component **120** (e.g., a file in memory) may be updated in near real-time with the received change. Further, the updated data may be synchronized across the first collaborative UX **130A** in scheduled meeting **114** and/or a sent message comprising meeting invite **112A**, the first collaborative UX **130B** associated with received message invite **112B**, and/or the second collaborative UX **142** associated with second application **138**. In this way, both the meeting organizer and one or more recipients (e.g., attendees) are able to collaborate in near real-time before the meeting. Additionally or alternatively, first user **110A** and second user **110B** are able to collaborate regarding collaboration object **132** during the meeting (e.g., via a collaborative platform) or after the meeting (e.g., via a notebook application). In aspects, while first application **104** may be a calendar/messaging application, second application **138** may be a collaborative platform, a planner application and/or a productivity application (such as a notebook application). In aspects, users **110A-B** may collaborate in near real-time before, during, and/or after the meeting via either first collaborative UX **130** associated with the first application **104** and/or the second collaborative UX **142** associated with the second application **138**. In an example, “near” real-time may account for any minimal time associated with receiving a change, transmitting the change to data host **106**, updating the data in storage component **120**, and synchronizing the updated data on the first collaborative UXs **130A-B** and second collaborative UX **142** via the communication network **108**, for example.

(33) As should be appreciated, while only a first application **104** and a second application **138** are described, the users **110A-B** may collaborate via additional applications provided such applications support a collaborative UX. In aspects, an application configured to support a collaborative UX may be configured to consume the metadata associated with the collaboration object **132** (e.g., associated with a meeting invite) and to render a collaborative UX (either within a

calendar/messaging application or another application). Additionally, while only two users are described, any number of users (e.g., at least one meeting organizers and one or more meeting attendees) may collaborate via different collaborative UXs customized for different applications.

(34) As should be appreciated, since updates to content **124** associated with collaboration object **132** are synchronized across first collaborative UXs **130A-B** and/or second collaborative UX **142**, the meeting organizer and one or more recipients (who may or may not attend the meeting) are able to collaborate in near real-time from within different applications before, during or after the meeting. Accordingly, the most current collaborative data associated with collaboration object **132** may be displayed to each user, which may be accessed via different collaborative UXs associated with different applications. In this way, one user (e.g., recipient) may be accessing the collaboration object **132B** via a first application **104B** (e.g., within a received message invite **112B**) while another user (e.g., meeting organizer or another recipient) may be accessing the collaboration object **132C** via a second application **138** (e.g., notebook application or collaborative platform). Any changes made by either the recipient via collaborative UX **130B** or the sender/other recipient via collaborative UX **142** may be visible, in near real-time, to the other user(s).

(35) It should be appreciated that although first application **104A** is generally described herein as being used by a meeting organizer to compose and send a meeting invite, and first application **104B** is generally described herein as being used by a recipient/attendee to view the received meeting invite, the first application **104A-B** can generally be used to compose, send, and receive meeting invitations with collaborative UXs associated with a collaboration object. The first application **104A** may generally be the same as or similar to first application **104B** (e.g., first application **104A-B** may be a calendar/messaging application such as Outlook Web Access (OWA) executing on both first and second user devices **102A-B**) and second application **138** may generally be a different application that supports a collaborative UX (e.g., a collaborative platform such as Microsoft Teams™ or a web-based productivity application such as Microsoft OneNote™).

(36) As should be appreciated, the various systems, devices, applications, features, etc., described with respect to FIG. 1 are not intended to limit the system **100** to being performed by the particular applications and features described. Accordingly, additional configurations may be used to practice the methods and systems herein and/or features and applications described may be excluded without departing from the methods and systems disclosed herein.

(37) FIGS. 2A-D depict a user interface of a calendar/messaging application for generating a collaboration object, in accordance with examples of the present disclosure. In aspects, the calendar/messaging application depicted in FIGS. 2A-D may be the same as or similar to the first application **104A-B** depicted in FIG. 1.

(38) FIG. 2A depicts a user interface **200A** of a calendar/messaging application for receiving an indication to compose a meeting invitation. The user interface **200A** of the calendar/messaging application depicts a calendar interface associated with a first user **202** (e.g., Dan Mander). As illustrated, first user **202** is composing a meeting invitation based on meeting invitation template **204**. The meeting invitation template **204** comprises one or more input fields and/or selections for receiving parameters associated with a proposed meeting. For instance, the meeting invitation template **204** may comprise a title field, an attendee field, a time/date field, a location field, a reminder selection, a collaborative platform selection, and a meeting repeat selection, and the like.

(39) The meeting invitation template **204** may further comprise an object template **206**. Object template **206** may include a description field **208** for inputting a meeting description and tool bar **209** having controls for attaching documents and/or images, adjusting text formatting, and the like. Additionally, a notebook document **210** may automatically be generated and associated with the object template **206**. In aspects, at least portions of notebook document **210** may be enabled for collaboration (e.g., dynamic content). That is, notebook document **210** may be configured to enable multiple users to concurrently edit or collaborate on notebook document **210**. Notebook document **210** is associated with a pseudo file extension, “collab,” to identify it as a collaborative document.

In this case, since a meeting title has not yet been entered by first user **202**, notebook document **210** displays a generic file title, “Meeting Notes.” As illustrated, the object template **206** is further prepopulated with content categories **212** that may be associated with a meeting, such as an agenda, notes, and action items. In aspects, the content categories **212** may be collaboration enabled and configured with fields for receiving content items (e.g., specific agenda items, notes, action items) associated with the proposed meeting.

(40) FIG. 2B depicts a user interface **200B** of a calendar/messaging application for receiving parameters in a meeting invitation template and content in an object template, in accordance with examples of the present disclosure.

(41) Similar to FIG. 2A, FIG. 2B illustrates user interface **200B** of a calendar/messaging application. As illustrated, first user **202** has entered parameters into meeting invitation template **204**. For instance, first user **202** has input a meeting title **224** (“Marketing Sync”) for the proposed meeting and has input invitees **226**, including Beth Davis, Karen Lee, Ed Kale, and Tom Wo. A collaborative platform for a virtual meeting has been selected (e.g., “Teams meeting”) and date/time **228** (“Tues 12/29/2020” from “10:00 AM to 11:00”) has been entered.

(42) Additionally, first user **202** has added content to the object template **206**. For example, documents **214A-B** have been attached, including a presentation document **214A** and a spreadsheet document **214B**. A meeting description **216** is shown as being partially entered, as illustrated by cursor **230** at the end of the input text. Notebook document **210** has also been populated with a file title (“Marketing Sync 2020 Dec. 29”) corresponding the meeting title and the date of the proposed meeting. In aspects, notebook document **210** maintains the generic “collab” file extension, indicating that the notebook document **210** is collaboration enabled. That is, the notebook document **210** is configured to support concurrent editing and/or collaboration by a plurality of users. In this example, object template **206** is not fully visible in user interface **200B**.

(43) FIG. 2C depicts a user interface **200C** of a calendar/messaging application for receiving content in an object template, in accordance with examples of the present disclosure.

(44) In this example, as indicated by navigation bar **232** located toward a lower edge of user interface **200C**, object template **206** is more fully displayed. Object template **206** comprises a completed meeting description **216** and agenda category **212A** has been expanded to display preformatted entry fields **218** for inputting agenda items. The entry fields **218** may comprise items associated with an agenda, such as a topic, presenter designation, and presentation period. An agenda item may be added by selecting “+ Add agenda item” and inputting the topic, presenter, and allotted time, for example.

(45) FIG. 2D depicts a user interface **200D** of a calendar/messaging application including a meeting invitation with a collaboration object, in accordance with examples of the present disclosure.

(46) As illustrated by FIGS. 2A-D, as first user **202** composes a meeting invitation for a proposed meeting via a calendar/messaging application, a meeting invitation template and an object template are progressively populated with various data. In general, a meeting invitation template is populated with meeting parameters and an object template is populated or associated with various content. As illustrated, content may comprise a meeting description **216**, attached documents **214A-B**, collaborative notebook document **210**, content categories **212A-C**, and agenda items **220A-C**. When a meeting organizer has finished entering content associated with a particular meeting in an object template, the meeting invitation may be saved or sent to one or more invitees and the object template may be converted to an “collaboration object” (e.g., collaboration object **234**) within the meeting invitation. The collaboration object **234** may comprise content and a portable interface (e.g., interface **236**) having functionality for concurrent multi-user interaction with the content from different applications and/or user devices.

(47) Once a meeting invitation is saved or sent by a meeting organizer (e.g., first user **202**), the meeting organizer may access the collaboration object **234** from a calendar of the meeting

organizer (shown), from a sent folder of a messaging application (not shown), and/or from one or more other collaboration-enabled applications (e.g., a planner application, a notebook application, a collaborative platform, etc.) (not shown). Similarly, the collaboration object **234** may be accessed by the one or more invitees from within the received meeting invitation, from a calendar, and/or from other collaboration-enabled applications. In aspects, changes made to a collaboration object by the meeting organizer and/or the one or more invitees may be reflected for each of the other users within each of the various collaboration-enabled applications. If the changes are made by one user while other users are concurrently accessing the collaboration object, the changes may be synchronized across applications and user devices in near real-time such that the other users are able to view the changes as they are being made to the collaboration object.

(48) As illustrated by user interface **200D**, first user **202** has saved the meeting invitation to a calendar and the object template has been converted into collaboration object **234**. In aspects, collaboration object **234** comprises an interface **236** (highlighted by shading). Content updated within interface **236** may be reflected in near real-time across applications and user devices. For example, first user **202** may open a notebook application, open a notebook document for a meeting entitled “Marketing Sync,” and input additional content into the interface of the collaboration object in the notebook document (not shown). As illustrated by FIG. 2D, as first user **202** types a third agenda item **220C** in the notebook application (not shown), the third agenda item **220C** may be reflected in near real-time (illustrated by cursor **240**) in the calendar of first user **202** (shown).

(49) In aspects, collaboration object **234** may be associated with both dynamic content and static content. Dynamic content (e.g., dynamic content **238** within interface **234**) may be content that is configured for concurrent editing, access, and/or collaboration by multiple users. Static content may be content that is associated with (or attached to) collaboration object **234** (e.g., attached documents **214A-B**) but that is not collaboration enabled. That is, while attached documents **214A-B** may be accessed (e.g., opened) from the collaboration object **234**, changes to documents **214A-B** made by one user may not be reflected in documents **214A-B** accessed by another user, for instance.

(50) In some aspects, collaborative notebook document **210** may not be included with dynamic content **238** within interface **236**. That is, while notebook document **210** may be collaboration enabled, the collaborative content of notebook document **210** may be accessed via a user interface associated with a notebook application (not shown) rather than via interface **236**. Even so, collaborative content within notebook document **210** that corresponds to dynamic content **238** may be edited from either the notebook interface or interface **236**. In this way, any updates received to corresponding content via the notebook interface (not shown) are reflected in the dynamic content **238**. Similarly, if dynamic content **238** is edited within interface **236**, updates to the corresponding content are reflected within the notebook document **210**.

(51) As described above, metadata may be associated with a collaboration object. The metadata may comprise instructions or pointers for generating one or more collaborative user experiences (UXs) customized for one or more applications. A collaborative UX may customize the portable interface and functionality of the collaboration object for a particular application. As illustrated in FIG. 2D, collaboration object **234** is provided with a collaborative UX **242** customized for a calendar/messaging application. That is, the collaborative UX **242** may be customized so as to exhibit a similar look and/or feel (e.g., theming, color scheme, layout, design elements, etc.) to interface **200D** of a calendaring/messaging application.

(52) Upon completing the meeting invitation, first user **202** (e.g., meeting organizer) may send the meeting invitation including the collaboration object **234** and associated metadata to one or more recipients (e.g., invitees, attendees) via the calendar/messaging application (e.g., within an email message).

(53) As should be appreciated, the various user interfaces, methods, devices, applications, features, etc., described with respect to FIGS. 2A-D are not intended to limit the user interface **200** to the

particular features described. Accordingly, additional configurations may be used to practice the methods and systems herein and/or features and applications described may be excluded without departing from the methods and systems disclosed herein.

(54) FIGS. 3A-C depict user interfaces of different applications that provide a collaboration object for enabling users to collaborate before a meeting, in accordance with examples of the present disclosure.

(55) FIG. 3A depicts a user interface **300** of a calendar/messaging application associated with a second user **308**. In aspects, second user **308** (e.g., “Beth Davis”) is a recipient (or invitee) of a meeting invitation **312** from the first user **202**.

(56) The user interface **300** of the calendar/messaging application depicts an inbox **310** of second user **308**. As illustrated, meeting invitation **312** is received as a message and displays a number of parameters associated with proposed meeting **338** (entitled “Marketing Sync”), including a date/time and a location. From meeting invitation **312**, second user **308** may accept, decline, or respond tentative to the proposed meeting **338** using controls **314**. Additionally, meeting invitation **312** includes a collaboration object **320** corresponding to collaboration object **234** of FIG. 2D. Collaboration object **320** comprises attached documents **316A-B**, meeting description **318**, collaborative notebook document **328**, and interface **326** (identified by shaded boundary) including dynamic content **344**.

(57) In aspects, when meeting invitation **312** is received, the calendar/messaging application of second user **308** may retrieve metadata associated with collaboration object **320**. The metadata may enable the calendar/messaging application to follow pointers to custom code and a code loader for rendering collaborative UX **322A**. In aspects, the custom code may specific to a particular interface or application, enabling collaborative UX **322A** to be customized for a calendar/messaging application. In further aspects, the metadata may provide a pointer or other reference for retrieving the dynamic content **344** from storage (e.g., associated with a data host). The dynamic content **344**, in at least some examples, may be synchronized across different applications and different user devices such that the dynamic content **344** retrieved from storage reflects any updates in near real-time.

(58) As discussed above, a collaborative UX may customize the portable interface and functionality of a collaboration object for concurrent multi-user access, editing, sharing, attaching, and/or collaborating regarding content. Here, while user interface **300** is associated with a calendar/messaging application of second user **308** (“Beth Davis”), interface **236** within meeting invitation **312** illustrates at least two other users accessing the dynamic content **344**. For instance, a user **324A** (“EK”) and a user **324B** (“TW”) are shown concurrently editing agenda items **342A** and **342B**, respectively. Similarly, although not shown, second user **308** may also edit dynamic content **344** via interface **236** and such edits would be reflected in collaboration objects associated with at least users **324A-B**. As should be appreciated, when a collaboration object **320** is provided within a meeting invitation, the meeting organizer and one or more invitees are able to collaborate before a pre-scheduled meeting regarding associated content (such as attached documents, an agenda, notes, actions items, and the like).

(59) FIG. 3B depicts a user interface **332** of a collaborative platform associated with second user **308**. In aspects, user interface **332** displays a calendar tab **334** associated with meeting **338**.

(60) As illustrated, user interface **332** displays the meeting invitation **312** received by second user **308**. As with FIG. 3A, meeting invitation **312** displays a number of parameters associated with the proposed meeting **338** (entitled “Marketing Sync”), including a date/time and a location. Additionally, meeting invitation **312** includes collaboration object **320** associated with attached documents **316A-B**, meeting description **318**, collaborative notebook document **328**, and interface **326** including dynamic content **344**.

(61) Similar to FIG. 3A, the collaborative platform may retrieve metadata associated with collaboration object **320**. The metadata may enable the collaborative platform to follow pointers to

custom code and a code loader for rendering the collaborative UX **322B**. In aspects, custom code may enable collaborative UX **322B** to be customized for the collaborative platform. Here, although the meeting invitation **312** is provided in a different interface (e.g., user interface **332**) associated with a different application (e.g., collaborative platform), collaborative UX **322B** may be similar to collaborative UX **322A**, but may include a different layout and/or functionality customized for the collaborative platform. For instance, collaborative UX **322B** may include an expanded tracking panel **346** for meeting attendance and/or a “join” control **350** for joining the pre-scheduled meeting from the collaborative platform. Collaborative UX **322B** also provides information for meeting room scheduling under rooms header **348**. Here again, interface **326** of the collaboration object **320** displayed in interface **332** of the collaborative platform shows users **324A-B** accessing the dynamic content **344** at a same or similar time as displayed in interface **300** of the calendar/messaging application illustrated in FIG. **3A**.

(62) FIG. **3C** depicts a user interface **336** of a notebook application associated with second user **308**. In aspects, the notebook document **328** associated with a pre-scheduled meeting is displayed in user interface **336**.

(63) In this case, notebook document **328** is entitled, “Marketing Sync,” and includes information regarding a pre-scheduled meeting (e.g., meeting **338** of FIG. **3A**). However, collaborative UX **322C** is different from collaborative UX **322A** (customized for a calendar/messaging application) and collaborative UX **322B** (customized for a collaborative platform). Here, while notebook document **328** includes a date/time and a location for the meeting, a meeting description (e.g., meeting description **318** of FIG. **3A**) is not provided. Additionally, collaborative UX **322C** provides controls **340** for joining the meeting or chatting about the meeting. As with collaborative UXs **322A-B**, collaborative UX **322C** includes collaboration object **320** with attached documents **316A-B**, interface **326**, and dynamic content **344**. Here again, users **324A-B** are illustrated accessing the dynamic content **344** at a same or similar time as illustrated by FIGS. **3A-B**. Since a corresponding notebook document **328** is open, the notebook document **328** is not shown as attached to the collaboration object **320** (see FIGS. **3A-3B**).

(64) As shown by FIGS. **3A-C**, invitees are able to collaborate before a proposed meeting based on a collaboration object received via a meeting invitation.

(65) As should be appreciated, the various user interfaces, methods, devices, applications, features, etc., described with respect to FIGS. **3A-C** are not intended to limit the user interfaces to the particular features described. Accordingly, additional configurations may be used to practice the methods and systems herein and/or features and applications described may be excluded without departing from the methods and systems disclosed herein.

(66) FIGS. **4A-G** depict user interfaces of different applications that provide a collaboration object for enabling users to collaborate during a meeting, in accordance with examples of the present disclosure.

(67) FIG. **4A** depicts a user interface **400** of a calendar/messaging application associated with a second user **402** (e.g., invitee) displaying a meeting invitation **406**. Similar to meeting invitation **312**, meeting invitation **406** includes information regarding a meeting **408**, such as a date/time and a location. Additionally, meeting invitation **406** includes collaboration object **428A**, including attached documents **418A-B**, a meeting description **430**, a collaborative notebook document **414**, and dynamic content **416** associated with an interface **434**.

(68) Collaboration object **428A** is provided in a collaborative UX **458A** customized for the calendar/messaging application. Collaborative UX **458A** comprises an attendance tracker **460** and a control **404A** for joining the meeting **408** and a control **404B** for chatting regarding meeting **408**. In aspects, in response to selecting join control **404A**, a collaborative platform may be launched enabling the second user **402** to virtually join meeting **408**.

(69) FIG. **4B** depicts a user interface **410** of a collaborative platform associated with second user **402** displaying a first time capture **420A** (e.g., 00:22:06) during virtual meeting **408**.

(70) As shown, attendees **412A-C** and icon representing second user **402** are displayed in a main pane **422** and a first page of document **418A** is provided in an overlay pane **424** of user interface **410**. According to functionality of the collaborative platform, a recording **462** of virtual meeting **408** has been initiated. Here, collaboration object **428B** is provided in side pane **426** via collaborative UX **458B**, which is customized for the collaborative platform. For instance, the layout and background of collaborative UX **458B** are customized according to a theme and/or color scheme of the collaborative platform. In aspects, collaboration object **428B** within user interface **410** of the collaborative platform is similar to collaboration object **428A** within meeting invitation **406** of the calendar/messaging application of FIG. 4A.

(71) In particular, collaboration object **428B** includes attached documents **418A-B**, collaborative notebook document **414**, and dynamic content **416**. However, collaboration object **428B** does not include meeting description **430** provided by collaboration object **428A**; nor does collaboration object **428B** explicitly show an interface (e.g., interface **434**) for interacting with dynamic content **416**. Even so, dynamic content **416** is enabled for concurrent multi-user interaction during meeting **408**. As illustrated by user **432A**, who is editing dynamic content **416**, collaboration object **428B** is collaboration enabled within the side pane **426** of user interface **410**. In particular, first user **432A** (“DM”), corresponding to attendee **412A** (“Dan Mandera”), is in the process of editing dynamic content **416** to add a first note **438A** to the note category during meeting **408**; and third user **432B** (“KT”), corresponding to attendee **412B** (“Karen Lee”), is accessing a first agenda item **440** of the agenda category.

(72) As further illustrated by FIG. 4B, when attached document **418A** is selected **436**, the first page of document **418A** is rendered in overlay pane **424**. In this way, content associated with a collaboration object within a meeting invitation (e.g., collaboration object **428A**) can be available for collaboration and editing before a meeting (as discussed with reference to FIGS. 3A-3C) and can be available during the meeting (such as collaboration object **428B** within a different application) to facilitate sharing attached content (e.g., application **418A**), taking notes, adding action items, and the like. In this way, everything associated with a particular meeting can be found in one place (e.g., the collaboration object) and can be accessed by the meeting organizer and the invitees before, during, and after the meeting (even in cases in which an invitee is unable to attend the meeting).

(73) FIG. 4C depicts user interface **410** of the collaborative platform associated with second user **402** displaying a second time capture **420B** (e.g., 00:35:21) during virtual meeting **408**.

(74) In this case, the first page of document **418A** is shared in the main pane **422** of user interface **410** and collaboration object **428B** remains in the side pane **426** of user interface **410**. According to functionality of the collaborative platform, the recording **462** of virtual meeting **408** continues.

(75) As with FIG. 4B, collaboration object **428B** includes attached documents **418A-B**, collaborative notebook document **414**, and dynamic content **416**. However, at the second time capture **420B** during meeting **408**, first agenda item **440** is identified as completed **442A**, first note **438A** has been added, and fourth user **432C** (“EK”) is in the process of adding a second note **438B** to the note category. As should be appreciated, making collaboration object **428B** available during the meeting **408** (even within a different application) has facilitated sharing attached content (e.g., application **418A**), adding notes **438A** and **438B**, and indicating a progress of meeting **408** with respect to the agenda, for instance.

(76) FIG. 4D depicts a user interface **444** of a notebook application displaying collaborative notebook document **414** overlaying user interface **410** of the collaborative platform. In aspects, the user interface **444** may also be associated with the second time capture **420B** (e.g., 00:35:21) during virtual meeting **408**.

(77) As illustrated, a selection **446** of collaborative notebook document **414** within collaboration object **428B** of interface **410** may launch collaborative notebook document **414** within overlay user interface **444**. As can be seen, dynamic content **416** associated with collaboration object **428B**

corresponds to dynamic content **416** within collaborative notebook document **414**. Similarly, as can be seen, edits to the dynamic content **416** received to collaboration object **428B** within user interface **410** at the second time capture **420B** are reflected in collaborative notebook document **414** within user interface **444**. That is, first note **438A** has been added and fourth user **432C** (“EK”) is in the process of adding a second note **438B** to the note category.

(78) FIG. 4E depicts user interface **410** of the collaborative platform associated with second user **402** displaying a third time capture **420C** (e.g., 00:38:02) during virtual meeting **408**.

(79) As with FIG. 4C, the first page of document **418A** is shared in the main pane **422** of user interface **410**. In this case, selection **448** provides a drop-down menu **452** for presenting (e.g., sharing) content in the virtual meeting **408**. The drop-down menu **452** displays various options for presenting, as well as additional applications for selection, such as whiteboard application **450**. Drop-down menu **452** also provides documents **418A-B** for selection and sharing.

(80) FIG. 4F depicts user interface **410** of the collaborative platform associated with second user **402** displaying a fourth time capture **420D** (e.g., 00:42:07) during virtual meeting **408**.

(81) As illustrated, whiteboard application **450** has been selected from drop-down menu **452** and a whiteboard session **454** has been launched in main pane **422** of user interface **410**. As illustrated, results of brainstorming **456** were captured in the whiteboard session **454** during meeting **408** between second user **402** and attendees **412A-D** (see FIG. 4B).

(82) FIG. 4G depicts a user interface **410** of a collaborative platform associated with second user **402** displaying a fifth time capture **420E** (e.g., 00:54:48) during virtual meeting **408**.

(83) As shown, attendees **412A-C** and icon representing second user **402** are displayed in main pane **422** of user interface **410**. Further, collaboration object **428B** is provided in side pane **426** and whiteboard session **454** is provided in overlay pane **424** of user interface **410**. Collaboration object **428B** has been updated to show each of the three agenda items as completed **442A-C** and whiteboard session **454** has been added to the content attached to collaboration object **428B** (e.g., documents **418A-B**).

(84) FIGS. 5A-B depict user interfaces of different applications that provide a collaboration object for enabling users to collaborate after a meeting, in accordance with examples of the present disclosure.

(85) FIG. 5A depicts a user interface **500** of a collaborative platform associated with second user **502**. In aspects, user interface **500** of the collaborative platform displays a chat tab **510** associated with meeting **508**. In this case, the chat thread **512** involves invitees of meeting **508** (whether or not they attended). In addition to chats **514A-C** of chat thread **512**, a collaboration object **516** has been delivered to the chat thread **512**.

(86) Collaboration object **516** may be similar to the collaboration objects described with respect to FIGS. 2A-4G above; however, since meeting **508** has already occurred, collaboration object **516** includes at least some additional content. For instance, collaboration object **516** includes a recording **526** of meeting **508**, a transcript **528** of meeting **508**, and an attendance **522** for the meeting **508**. As with previously-described collaboration objects, collaboration object **516** includes collaborative notebook document **524** and documents **518A-B**. Additionally, the whiteboard session **520** captured during meeting **508** has been attached as content. Collaboration object **516** may further be provided via a collaborative UX **544A**, which is customized or suitable for inclusion in a chat thread. For example, the collaboration object **516** may be provided with a compact layout where content may be accessed by selecting various thumbnail previews of the content. For example, upon selecting a thumbnail preview for collaborative notebook document **524**, dynamic content regarding the meeting (e.g., dynamic content **416** of FIGS. 4A-D) may be accessed and updated (e.g., an action item may be marked complete).

(87) In some cases, a meeting recording and transcript, and any content shared during the meeting, may automatically be linked to the collaboration object. In further aspects, one or more items of content may be permission protected. For instance, some content may be available only to

attendees whereas other content may be available to all invitees (whether or not they attended). Such permissions may be manually assigned (e.g., by the meeting organizer) or may be automatically assigned (e.g., based on attendance, membership in a group, organizational title or role, and the like). As should be appreciated, by associating content and collaboration associated with a meeting **508** in the collaboration object **516**, the meeting organizer and invitees (whether or not they were able to attend) may continue to collaborate after the meeting. Moreover, with everything in one place, users are able to easily and efficiently access content and information associated with meeting **508**.

(88) FIG. **5B** depicts a user interface **500** of a collaborative platform associated with second user **502**. In aspects, user interface **500** of the collaborative platform displays a calendar tab **530** associated with meeting **508**.

(89) As illustrated, user interface **500** displays a collaboration object **532** via collaborative UX **544B**. Collaboration object **532** may be similar to collaboration object **516**; however, collaborative UX **544B** is customized such that collaboration object **532** has a different layout and is expanded to display additional content. For example, similar to collaboration object **516**, collaboration object **532** may include recording **526**, transcript **528**, and an attendance **522** for the meeting **508**. Additionally, collaboration object **532** may include attached documents **518A-B**, meeting description **534**, collaborative notebook document **524**, and whiteboard session **520** captured during meeting **508**.

(90) In this case, collaboration object **532** may be expanded within collaborative UX **544B** to provide dynamic content **536**, which may include updates following meeting **508**. For instance, first user **538A** (“DM”) (corresponding to first user **432A**) has added action item **540**; fourth user **538B** (“EK”) (corresponding to fourth user **432C**) has completed second note **542B**; and fifth user **538C** (“TW”) (who declined meeting **508**) has completed third note **542C**. As illustrated, the first user, fourth user and fifth user are editing dynamic content **536** substantially concurrently, as indicated by cursors representing where each user is editing. In this case, users are able to continue collaboration regarding meeting **508** after the meeting is over by updating collaboration object **532**.

(91) As should be appreciated, collaboration objects **516** and **532** have been described in an example of a chat tab and a calendar tab of a collaborative platform; however, corresponding collaboration objects associated with meeting **508** may be synchronized across all applications supporting the meeting **508**, such as a calendar/messaging application, a notebook application, a planner application, and the like. In fact, collaboration objects provided across a plurality of applications (such as the applications described herein and any other applications supporting collaboration) may enable a meeting organizer and one or more invitees to collaborate at any time before, during, or after a meeting.

(92) FIGS. **6A-C** illustrate an example method for generating and utilizing a collaboration object, in accordance with aspects of the present disclosure.

(93) A general order of the operations for the method **600** is shown in FIGS. **6A-C**. The method **600** may include more or fewer steps and/or may progress in a different order of steps from those shown in FIGS. **6A-C**. The method **600** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **600** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **600** shall be explained with reference to the systems, components, devices, user interfaces, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. **1-5B** and **7A-14B**.

(94) At receive operation **602**, an indication to schedule a meeting is received via a first application. In aspects, the indication to schedule the meeting may correspond to an organizer initiating a meeting invitation template for scheduling a meeting with one or more invitees via a calendar/messaging application.

(95) At provide operation **604**, a meeting invitation template including an object template may be provided. In aspects, a meeting invitation template for scheduling a meeting via a calendar/messaging application may be provided with an object template. An object template may include a predetermined structure for accepting content, such as fields for receiving meeting descriptions, a tool bar having controls for attaching documents and/or images, adjusting text formatting, and the like. Additionally, a collaborative notebook document may automatically be generated and associated with the object template. The object template may further be prepopulated with content categories that may be associated with a meeting, such as an agenda, notes, and action items. In aspects, the content categories may be collaboration enabled and configured with fields for receiving content items (e.g., specific agenda items, notes, action items) associated with the proposed meeting. In aspects, “collaboration enabled” refers to content enabled to support concurrent editing and/or collaboration by a plurality of users.

(96) At receive content operation **606**, content may be received to the object template. For instance, such content may include input such as a meeting description, attached documents or images, and an associated collaborative notebook document. Additionally, the content may include content input to dynamic content categories such as agenda items, notes, action items, and the like.

(97) At generate operation **608**, a collaboration object including the received content may be generated. For instance, when a meeting organizer has finished entering content associated with a particular meeting into the object template and the meeting organizer either saves or sends the meeting invitation, the object template may be converted to an “collaboration object” within the meeting invitation. In aspects, a collaboration object may result from an object template that is populated with content.

(98) At cause operation **612**, a meeting invitation including the collaboration object may be caused to be sent to at least one recipient (e.g., invitee). In aspects, the meeting invitation may be sent to the at least one recipient in a message via the first application (e.g., a calendar/messaging application).

(99) At schedule operation **614**, a meeting may be scheduled in a calendar of the organizer via the first application. In aspects, the meeting may be scheduled in the organizer's calendar when the meeting invitation including the collaboration object is sent to the at least one recipient. In other aspects, the meeting may be scheduled in the organizer's calendar when the meeting invitation including the collaboration object is saved, whether or not the organizer has initiated sending the meeting invitation. In aspects, the meeting is scheduled based on the meeting invitation and includes the collaboration object and any associated content.

(100) At update operation **628**, the collaboration object associated with the scheduled meeting provided by the first application of the organizer may automatically be updated at substantially the same time as changes are made to the collaboration object by the at least one recipient via the second application. In aspects, a change may be received as input to dynamic content when the at least one recipient accesses the collaboration object via a second application before, during, or after the meeting. In other aspects, a change may be content shared by the at least one recipient via the second application before, during, or after the meeting. The second application may be a collaborative platform, a notebook application, a planner application, or the like, for accessing the meeting associated with the meeting invitation generated by the first application. In aspects, the collaboration object may be updated across user devices and applications regardless of the application through which the change is received.

(101) In aspects, receive content operation **606** and generate operation **608** are detailed further with respect to FIG. **6B** (as indicated by “A”) and update operation **628** is detailed further with respect to FIG. **6C** (as indicated by “B”).

(102) FIG. **6B** illustrates an example method for generating and utilizing a collaboration object further detailing receive content operation **606** and generate operation **608** of FIG. **6A**, in accordance with aspects of the present disclosure.

(103) At enable operation **605**, which may follow provide operation **604**, the object template may be enabled for receiving dynamic content and static content. For instance, as noted above, the object template may include a predetermined structure for accepting content, including attached content (e.g., documents, images, whiteboard sessions, recordings, transcripts, and the like) and dynamic content (e.g., collaboration-enabled dynamic content, such as a collaborative notebook document or dynamic content categories within the object template). In aspects, dynamic content refers to content enabled to support concurrent multi-user interactions (e.g., adding, editing, deleting, and the like) that are synchronized across applications and/or user systems in near real-time. Static content may be content that is associated with (or attached to) a collaboration object (e.g., attached or shared documents, images, whiteboard sessions, recordings, transcripts, and the like) but that is not collaboration enabled. That is, while attached documents may be accessed (e.g., opened) from the collaboration object, changes to the documents made by one user are not reflected in the same documents accessed by another user, for instance. While static content itself may not be collaboration-enabled, the attachment (or sharing or linking) of the content to a collaboration object may be reflected in near real-time across each application and each user system.

(104) At receive content operation **606**, content may be received to the object template. For instance, such content may include static content (e.g., attached documents, images, whiteboard sessions, recordings, transcripts, and the like) and dynamic content (e.g., a collaborative notebook document or content input to dynamic content categories within the object template, such as agenda items, notes, action items, and the like).

(105) At generate operation **608**, a collaboration object including the received content may be generated. For instance, when a meeting organizer has finished entering content associated with a particular meeting into the object template, and the meeting organizer either saves or sends the meeting invitation, the object template may be converted to an “collaboration object” within the meeting invitation. In aspects, the generated collaboration object may comprise the dynamic content and the static content received to the object template.

(106) At associate operation **609**, metadata may be associated with the collaboration object. The metadata may include information for retrieving content (e.g., stored within a storage component on data host) and for rendering a collaborative user experience (UX), such as pointers to custom code for generating the collaborative UX and a code loader for ingesting the metadata and loading the collaborative UX, for example. A collaborative UX may customize the portable interface and/or functionality of the collaboration object for a particular application. For example, a collaborative UX may be customized so as to exhibit a similar look and/or feel (e.g., theming, color scheme, layout, design elements, etc.) to an interface associated with an application.

(107) At render operation **610**, based on the metadata, a collaborative UX associated with the collaboration object may be rendered within the meeting invitation. In aspects, the metadata may enable a first application (e.g., a calendar/messaging application) to follow pointers to custom code and a code loader for rendering the collaborative UX. In aspects, the custom code may specific to a particular interface or application, enabling collaborative UX to be customized for the first application. In further aspects, the metadata may provide a pointer or other reference for retrieving the dynamic content from storage (e.g., associated with a data host). The dynamic content, in at least some examples, may be synchronized across different applications and different user devices such that the dynamic content retrieved from storage reflects any updates in near real-time.

(108) FIG. **6C** illustrates an example method for generating and utilizing a collaboration object further detailing update operation **628** of FIG. **6A**, in accordance with aspects of the present disclosure.

(109) At launch operation **616**, a second application may be launched during the meeting associated with the meeting invitation. In an example, the second application may be a collaborative platform for hosting the meeting. In some aspects, the second application may provide video functionality such that the organizer and the at least one recipient (e.g., attendee) may view one another during

the meeting. In other examples, the second application may be a collaboration-enabled notebook application, a planner application, or a task application accessed by the at least one recipient during the meeting. Regardless of the type of collaboration-enabled application, the collaboration object may be available via the second application during the meeting. In some aspects, the collaboration object may be provided via a collaborative UX customized for the second application.

(110) At receive input operation **618**, input to the collaboration object by the at least one recipient may be received. For instance, the recipient may input content into dynamic content categories associated with the collaboration object, such as an agenda item, a note, or an action item.

(111) At reflect operation **620**, the input received from the at least one recipient may be reflected in near real-time across user devices. For example, the input of the agenda item, note, or action item may be reflected in the collaboration object on the device of at least the organizer and any other recipients. The input may be reflected across the user devices at substantially (or nearly) the same time as it is received by the at least one recipient. In some cases, where the second application is hosting the meeting, the input may be reflected in the collaboration object provided by the second application during the meeting. In other cases, where the second application is a collaboration enabled notebook application, planner application, or task application, for example, the input may still be reflected in near real-time in the collaboration object provided by a third application hosting the meeting. That is, regardless of the application that receives the input to the collaboration object, the input may be reflected across the other collaboration-enabled applications and user devices accessing the collaboration object.

(112) At detect operation **622**, the at least one recipient may share content via the second application during the meeting. Sharing content may involve sharing a presentation (e.g., via the video capabilities of the second application) with the meeting participants. Sharing content may also include examples such as sharing a link to content (e.g., to a video or website) within a chat thread or otherwise during the meeting. In aspects, the second application may detect the content being shared by the at least one recipient.

(113) At associate operation **624**, the shared content may be automatically associated (e.g., linked or attached) to the collaboration object. For example, if a presentation is shared during the meeting, the presentation may automatically be associated with the collaboration object (e.g., as a link or an attachment). In another example, if a link to content is shared during the meeting, the link may be associated with collaboration object. In yet another example, when a link to content is shared, the link may be followed and the content may be retrieved and associated with the collaboration object.

(114) At reflect operation **626**, the content shared by the at least one recipient may be reflected in near real-time across user devices. For example, the shared content may be reflected in the collaboration object on the device of at least the organizer and any other recipients. The content may be reflected across the user devices at substantially (or nearly) the same time as it is shared by the at least one recipient. In some cases, where the second application is hosting the meeting, the shared content may be reflected as linked to the collaboration object as it is shared via the second application during the meeting. In other cases, where the second application is a collaboration enabled notebook application, planner application, or task application, for example, the shared content may still be reflected in near real-time as linked to the collaboration object provided by a third application hosting the meeting. For instance, the at least one recipient may share a link to content within the notebook application and the link may be automatically associated with the collaboration object provided by the third application hosting the meeting. That is, regardless of the application through which the content is shared, the shared content may be reflected across the other collaboration-enabled applications and user devices accessing the collaboration object.

(115) At update operation **628**, the collaboration object associated with the scheduled meeting provided by the first application of the organizer may automatically be updated with change(s) made to the collaboration object by the at least one recipient via the second application. In aspects, a change may be received as input to dynamic content when the at least one recipient accesses the

collaboration object via a second application before, during, or after the meeting. In other aspects, a change may be content shared by the at least one recipient via the second application before, during, or after the meeting. The second application may be a collaborative platform, a notebook application, a planner application, or the like, for accessing the meeting associated with the meeting invitation generated by the first application. In aspects, the collaboration object may be updated across user devices and applications regardless of the application through which the change is received.

(116) As should be appreciated, operations **602-628** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

(117) FIGS. 7A-B illustrate an example method for receiving a meeting invitation including a collaboration object, in accordance with aspects of the present disclosure.

(118) A general order of the operations for the method **700** is shown in FIGS. 7A-B. The method **700** may include more or fewer steps and/or may progress in a different order of steps from those shown in FIGS. 7A-B. The method **700** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **700** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **700** shall be explained with reference to the systems, components, devices, user interfaces, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. 1-6B and 8A-14B.

(119) At receive meeting invitation operation **702**, a meeting invitation may be received by a first application (e.g., calendar/messaging application) of at least one recipient (e.g., an invitee to a meeting). In aspects, the meeting invitation may include a collaboration object and associated metadata.

(120) At retrieve operation **704**, the metadata may be retrieved from the collaboration object by the first application (e.g., calendar/messaging application).

(121) At first render operation **706**, the first application of the invitee may follow pointers in the metadata to custom code and a code loader for rendering a first collaborative UX associated with the collaboration object. In aspects, the custom code may specific to particular interfaces or functionality of the first application, enabling the first collaborative UX to be customized for the first application. Additionally, the first application may follow a data pointer associated with the metadata to retrieve content associated with the collaboration object. In aspects, the content may include attached content (such as documents, images, whiteboard sessions, videos, presentations, and the like), a collaborative notebook document associated with the meeting, and/or dynamic content associated with the collaboration object. For example, dynamic content refers to content enabled to support concurrent editing and/or collaboration by a plurality of users.

(122) At launch operation **708**, a second application may be launched. For instance, the second application may be a collaborative platform for joining a meeting associated with the meeting invitation. In other aspects, the second application may be a planner application or a notebook application for viewing and/or interacting with the collaboration object associated with the meeting. In aspects, the second application may be launched before, during, or after the meeting.

(123) At second render operation **710**, the collaboration object may be accessed via the second application (e.g., a collaborative platform, planning application, notebook application, and the like) to render a second collaborative UX. In this case, the second application may retrieve the metadata associated with the collaboration object and follow pointers to custom code and a code loader for rendering the second collaborative UX. In aspects, the custom code may specific to particular interfaces or functionality of the second application, enabling the second collaborative UX to be customized for the second application. Additionally, the second application may follow the data

pointer associated with the metadata to retrieve content associated with the collaboration object.

(124) At receive change operation **712**, a change may be received to the content associated with the collaboration object via the second collaborative UX. In an example, the change may include edits, additions, or deletions to dynamic content. For example, the at least one recipient may add an agenda item, a note, or an action item to the collaborative categories of the collaboration object via the second collaborative UX. Additionally or alternatively, the at least one recipient may attach, share, or otherwise link static content with the meeting (e.g., by sharing content within a message thread). This static content may automatically be associated with the collaboration object. In other aspects, the change may involve deleting static content from the collaboration object (e.g., by deleting an attachment from the meeting). In aspects, the at least one recipient may make the change before, during, or after the meeting.

(125) At cause update operation **716**, the collaboration object associated with a scheduled meeting on the meeting organizer's calendar may be updated in near real-time with the received change. That is, in response to receiving the change to content associated with the collaboration object via the second collaborative UX rendered by the second application, the change may be synchronized across applications (e.g., at least the first application and the second application) and across user systems (e.g., of at least the meeting organizer and the at least one recipient) to cause the collaboration object for the meeting to be updated in near real-time on an organizer's calendar associated with the first application.

(126) In aspects, cause operation **716** is detailed further with respect to FIG. 7B (as indicated by "A").

(127) FIG. 7B illustrates an example method for receiving a meeting invitation including a collaboration object and further detailing cause operation **716** of FIG. 7A, in accordance with aspects of the present disclosure.

(128) At follow operation **713**, which may follow receive change operation **710**, the second application may follow a pointer or other reference to content associated with the collaboration object in storage (e.g., associated with a data host). In some cases, the content may be dynamic content (e.g., content enabled for concurrent multi-user interaction) or static content (e.g., content attached or otherwise associated with a collaboration object that is not enabled for concurrent multi-user interaction).

(129) At cause operation **714**, the change may update the content associated with the collaboration object in the shared storage. As noted above, the change may comprise edits, additions, or deletions to dynamic content or sharing, attaching, linking, or deleting static content.

(130) At cause synchronize operation **715**, the updated content may be synchronized across different applications and different user devices such that the content associated with the collaboration object may reflect current content in near real-time. That is, an update to dynamic content (e.g., addition of an agenda item) and/or an update to static content (e.g., attachment of a revised document) may be reflected in the collaboration object across each of the different applications and user devices in near real-time.

(131) At cause update operation **716**, the collaboration object associated with a scheduled meeting on the meeting organizer's calendar may be updated with the received change. That is, in response to receiving the change to content associated with the second collaborative UX rendered by the second application, the change may be synchronized across applications (e.g., at least the first application and the second application) and across user systems (e.g., of at least the meeting organizer and the at least one recipient) to cause the collaboration object for the meeting to be updated on an organizer's calendar associated with the first application. In aspects, the meeting organizer's calendar may be updated with the received change in near real-time. That is, the meeting organizer's calendar may be updated with the received change at substantially (or nearly) the same time as the change is received by the second application. In aspects, substantially or nearly the same time may include a minimal time associated with synchronizing the change across

the different applications and user devices based on resource availability, network bandwidth, processing speeds, and the like.

(132) As should be appreciated, operations **702-716** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

(133) FIGS. **8A-B** depict a user interface of a collaborative platform for identifying and implementing a user objective to schedule a meeting, in accordance with examples of the present disclosure.

(134) FIG. **8A** depicts a user interface **800A** of a collaborative platform associated with a user **802**. In aspects, user interface **800A** of the collaborative platform displays a chat tab **804** associated with a collaboration team **806** (e.g., “Marketing Team”). A chat thread **810** involves members of collaboration team **806**. A conversation (e.g., chat thread **810**) involves a number of chats **812A-D** between members of the team, including user **826A** (“Dan”), user **826B** (“Ed”), and user **802** (“Beth”).

(135) As illustrated by chat **812D**, user **802** (“Beth Davis”) asks other members if they “have time to sync” on a presentation. In aspects, the collaborative platform (or other associated application) may monitor user correspondence to detect a user objective or desire to schedule a meeting. User statements may range from explicit requests to meet to more implicit indications of a desire to connect or collaborate. For example, user statements or queries indicative of an intention to schedule a meeting may include but are not limited to: “Can we set a meeting?”; “Let’s schedule something soon?”; “How does your calendar look tomorrow?”; “What’s your availability next week?”; “Can we sync up?”; “When are you free?”; “Let’s get something on the calendar”; “How’s your afternoon?”; and the like. In aspects, the system may parse various user statements to identify certain words and/or phrases, such as “meet,” “free,” “availability,” “calendar,” “when,” “sync,” “schedule,” “let’s chat,” and the like. Based on natural language processing and/or machine learning techniques, for example, the system may be trained to recognize such words and/or phrases that indicate a user intention or objective to collaborate. In aspects, collaboration may involve an in-person meeting, a virtual meeting, a phone call, a video call, or the like.

(136) In some cases, the system may determine that the user desires a meeting, e.g., based on a statement such as, “Let’s get something on the calendar.” In other cases, the system may determine that the user desires a phone call, e.g., based on a statement such as, “Do you have time to chat?” In still other cases, the system may detect a user intention to collaborate, but may not be able to determine a particular collaboration venue, e.g., based on a statement such as, “Can we sync up?” In aspects, the system may also be able to identify a topic of the collaboration, timing for the collaboration, required attendees, or other details (or parameters). For instance, in a chat thread between a first user, e.g., “Dan,” and a second user, e.g., “Ed,” Ed may state: “Can we chat about the presentation tomorrow?” Based on context (e.g., a chat between Dan and Ed) and the user statement, the system may determine that “Dan” is a required attendee, the topic of the desired collaboration is a “presentation,” and the timing of desired collaboration is “tomorrow.”

(137) In the illustrated example, user **802** (“Beth Davis”) poses query **814**: “do you guys have time to sync on the presentation to corporate?” From the query **814**, the system may determine that user **802** would like to meet with the other users in the chat thread, user **826A** (“Dan”) and user **826B** (“Ed”). Additionally, the system may determine that user **802** wishes to collaborate regarding the “presentation to corporate.” Based on these determinations, the system may issue prompt **816**. Prompt **816** may be automatically populated with free times on Dan and Ed’s schedules, such as proposed time **818A** and proposed time **818B**. Additionally, prompt **816** may provide control **820** to “meet now” and control **822** to “find time.” In response to selection of control **820**, a meeting between user **802** and users **826A-B** may automatically be launched. FIGS. **10A-C** further describe this example. In response to selection of control **822**, user **802** may be directed to a meeting

invitation template to find a time to schedule the meeting. See FIG. 2A. In response to selection **824** of either proposed time **818A** or **818B**, user **802** may be directed to a meeting invitation template prepopulated with the selected time. In some cases, the meeting invitation template may be prepopulated with the subject title, “Sync on presentation,” based on a system determination of the meeting topic. The meeting invitation template may also comprise an object template. Examples of meeting invitation templates and object templates are illustrated with respect to FIGS. 2A-2D.

(138) FIG. 8B depicts user interface **800B** of the collaborative platform associated with user **802**. As with FIG. 8A, user interface **800B** of the collaborative platform displays chat tab **804** associated with collaboration team **806** (e.g., “Marketing Team”). Chat thread **810** involves chats **812A-D** between members of the team.

(139) In this case, in response to prompt **816** (not shown), user **802** scheduled meeting **828** at proposed time **818A**. The meeting title **830** is “Sync on presentation,” which may have been auto-populated by the system or manually input into the meeting invitation template by user **802** (see FIG. 2B, reference **224**). In aspects, meeting **828** may comprise a collaboration object, as described above. In response to selecting control **832**, either user **802** or invitees **826A-B** may edit the collaboration object, e.g., by adding agenda items, notes, action items. These edits will automatically be reflected across user devices and across applications (e.g., within each user's calendar) in near real-time, as described above. As shown, presentation **836** is attached to the meeting **828** and can be accessed from the collaboration object before, during, or after the meeting. In response to selecting control **834**, attendees can join the meeting from interface **800B** of the collaborative platform.

(140) FIGS. 9A-E depict different user interfaces of different applications for identifying and implementing a user objective to schedule a call, in accordance with examples of the present disclosure.

(141) FIG. 9A depicts a user interface **900A** of a collaborative platform associated with a user **902**. In aspects, user interface **900A** of the collaborative platform displays a chat tab **904** associated with a collaboration team **906** (e.g., “Marketing Team”). A chat thread **908** involves members of collaboration team **906**. A conversation (e.g., chat thread **908**) involves a number of chats **910A-D** between members of the team, including user **922A** (“Dan”), user **922B** (“Ed”), and user **902** (“Beth”).

(142) As illustrated by chat **910D**, user **902** (“Beth Davis”) poses query **912**: “do you guys have time for a call on the presentation to corporate?” From the query **912**, the system may determine that user **902** would like to schedule a call with the other users in the chat thread, user **922A** (“Dan”) and user **922B** (“Ed”). Additionally, the system may determine that user **902** wishes to collaborate regarding the “presentation to corporate.” Based on these determinations, the system may issue prompt **914**. Prompt **914** may be automatically populated with contact information (e.g., phone numbers, email addresses, @mentions) for Dan and Ed, such as phone numbers **916A-B**. Additionally, prompt **914** may provide control **918** to “call now” and control **920** to “find time.” In response to selection of control **918**, user **902** may initiate a call with users **922A-B**. FIGS. 10A-C further describe this example. In response to selection of control **920**, user **902** may be directed to a call invitation template to find a time to schedule the call, as described further with respect to FIG. 9B. In response to selection of either or both phone numbers **916A-B**, user **902** may be directed to a call invitation template prepopulated with the selected phone number(s).

(143) FIG. 9B depicts a user interface **924** of a calendar/messaging application launched based on a selection to schedule a call. For instance, as described with reference to FIG. 9A, a user **902** may have made selections from prompt **914** (not shown), such as phone numbers **916A-B** and/or control **920** (“find time”). The user interface **924** of the calendar/messaging application depicts a calendar interface associated with user **902** (e.g., “Beth Davis”). As illustrated, call invitation template **926** comprises one or more input fields and/or selections for receiving parameters associated with a

proposed call. For instance, the call invitation template **926** may comprise a title field, a phone number field, a time/date field, a reminder selection, and the like. Based on system determinations and selections made from prompt **914** (not shown), the call invitation template **926** has been populated with a title **930**, “Call re: presentation to corporate,” and phone numbers **916A-B**. As detailed above, based on query **912**, the system may determine that the topic of the proposed call is the “presentation to corporate” and may prepopulate call invitation template **926** with title **930**. User **902** may input (or select from a drop-down menu) the time/date **932** for the call.

(144) The call invitation template **926** may further comprise an object template **928**. Similar to object templates described above, object template **928** may include a description field **934** for inputting a call description and tool bar **936** having controls for attaching documents and/or images, including emojis, adjusting text formatting, and the like. As illustrated, a presentation **940** entitled “Sales Analysis” has been attached to the object template **928**. The object template **928** is further prepopulated with content categories **938** that may be associated with a call, such as an agenda, notes, and action items. In aspects, the content categories **938** may be collaboration enabled and configured with fields for receiving content items (e.g., specific agenda items, notes, action items) associated with the proposed call.

(145) FIG. **9C** depicts user interface **900B** of the collaborative platform associated with user **902**. As with FIG. **9A**, user interface **800B** of the collaborative platform displays chat tab **904** associated with collaboration team **906** (e.g., “Marketing Team”). Chat thread **908** involves chats **910A-D** between members of the team.

(146) In this case, in response to activating prompt **914** (not shown) and completing call invitation template **926** (not shown), user **902** scheduled call **942**. Call **942** is scheduled for time/date **932** and comprises title **930** is “Call re: presentation to corp.” As described above, title **930** may have been auto-populated by the system or manually input into the call invitation template **926** by user **902** (see FIG. **9B**). In aspects, the title **930** may be shortened for the minimized representation of call **942** in chat thread **908**. Call **942** may comprise an a collaboration object, as described above. In response to selecting control **944**, either user **902** or invitees **922A-B** may edit the collaboration object, e.g., by adding agenda items, notes, action items. These edits will automatically be reflected across user devices and across applications (e.g., within each user's calendar) in near real-time, as described above. As shown, presentation **940** is attached to the call **942** and can be accessed from the collaboration object before, during, or after the call. In response to selecting control **946**, attendees can join the call (or call in) from interface **900B** of the collaborative platform.

(147) FIG. **9D** depicts a user interface **948** of a mobile device **950**. In aspects, when a scheduled call **942** is ready to begin at date/time **932**, a notification **952** may be sent to devices associated with the selected phone numbers **916A-B** (see FIG. **9B**). In response to selection **954** of the notification **952**, an attendee may join the call.

(148) FIG. **9E** depicts user interface **948** of mobile device **950**. In aspects, at a time **956**, after a scheduled call has ended, a notification **958** may be sent to devices associated with attendees. Notification **958** may include a link to a call recap **960**. The call recap **960** may provide the same or similar information regarding the completed call **942** as collaboration object **516** depicted in FIG. **5A**. For example, in response to selection **962**, the attendee may gain access to a collaboration object corresponding to the completed call. In this way, attendees may continue to collaborate and access dynamic content (e.g., content categories **938** of FIG. **9B**) or static content (e.g., presentation **940**) after the call. For instance, attendees may mark an action item complete, attach a revised presentation, and the like, and these updates may be automatically reflected across applications and user devices in near real-time. Additionally, a call recording and/or transcript, and any content shared during the call, may automatically be linked to the collaboration object.

(149) FIGS. **10A-C** depict a user interface of a collaborative platform for detecting a user collaboration and automatically generating a collaboration object, in accordance with examples of the present disclosure.

(150) FIG. 10A depicts a user interface **1000** of a collaborative platform associated with a user **1002**. In aspects, user interface **1000** of the collaborative platform displays a chat tab **1004** associated with a collaboration team **1006** (e.g., “Marketing Team”). A chat thread **1008** involves members of collaboration team **1006**. A conversation (e.g., chat thread **1008**) involves a number of chats **1010A-D** between members of the team, including user **1016A** (“Dan”), user **1016B** (“Ed”), and user **1002** (“Beth”). As illustrated by chat **1010D**, user **1002** (“Beth Davis”) makes a statement **1012**: “Hey, that reminds me, I’ll give you a call.” In this case, rather than scheduling a meeting or a call, user **1002** simply calls **1014** the other members of the collaboration team **1006**. While call **1014** is shown as a call made within a collaborative platform, other calls between collaborative team members may also be detected. For instance, based on a mapping of user phone numbers to user identities, user **1002** may call the other members of collaboration team **1006** using a cell phone. Based on detecting the impromptu call, the system may automatically launch a user interface and collaboration object for quickly organizing the call and memorializing any content or action items resulting from the impromptu call, as described with respect to FIG. 10B.

(151) FIG. 10B depicts a user interface **1018** of a collaborative platform associated with user **1002**. In aspects, when user **1002** calls the other members of the collaboration team **1006**, the user interface **1018** may launch automatically. As illustrated, call **1014** is a video call which is just starting at time capture **1024** (e.g., 00:01:15). Although not shown, call **1014** may also be a voice call.

(152) In main pane **1020**, user interface **1018** displays video images of user **1016A** (“Dan Mandera”) and user **1002** (“Beth Davis”) and a masked simulation of user **1016B** (“Ed Kale”). In examples where call **1014** is a voice call, masked simulations of all users may be provided in main pane **1020**. According to functionality of the collaborative platform, a recording **1026** of call **1014** has been initiated. Additionally, a collaboration object **1028** has been automatically generated in side pane **1022**. That is, in response to user **1002** calling members of collaboration team **1006**, the system detected the call and automatically provided the collaboration object **1028** to aid the users in organizing and memorializing the impromptu call **1014**. In aspects, collaboration object **1028** is similar to the collaboration objects described above.

(153) For example, collaboration object **1028** includes dynamic content categories **1030**, including an agenda component, a note component, and an action item component. Although collaboration object **1028** was not created prior to the call **1014**, providing the dynamic content categories **1030** enables participants to quickly and efficiently input an agenda to organize the impromptu call, as well as memorialize notes and action items. As illustrated by user **1002**, who is adding agenda item **1032** to the dynamic content categories **1030**, collaboration object **1028** is collaboration enabled within the side pane **1022** of user interface **1018**. Similarly, user **1016A** (“DM”), corresponding to attendee **1016A** (“Dan Mandera”), is in the process of adding a note to the dynamic note category. That is, all of the users are able to see the concurrent entries of other users during the call **1014**. Additionally, the collaboration object **1028** may be updated across other applications (e.g., calendar/messaging application, notebook application, planner application, etc.) during the call and thereafter in near real-time. In this way, an impromptu call may be automatically organized and results and action items for the impromptu call may be memorialized for future collaboration.

(154) As further illustrated by FIG. 10B, suggestions for attaching content may be made to the attendees of the impromptu call. In some aspects, suggestions for content may be made based on data collected prior to initiation of the impromptu call. For instance, as illustrated by FIGS. 8A and 9A, users may be involved in a chat thread regarding a particular topic (e.g., a presentation to corporate) when the call is initiated. In other aspects, suggestions for content may be based on a current project assigned to the group, a revised document that has been shared among the group, and the like. As illustrated, presentation **1034** is provided as suggested content. In aspects, an attendee may click or otherwise activate presentation **1034** so as to link it to the collaboration object **1028**. Additionally, as with the collaboration objects described above, any content shared or

created during the call **1014** (e.g., videos, whiteboard session, mind maps, etc.) may automatically be linked to the collaboration object **1028**. In this way, content associated with collaboration object **1028** may be available for collaboration and editing during an impromptu call to facilitate creating an agenda, taking notes, adding action items, and the like. The collaboration object **1028** may be persisted such that everything associated with the impromptu call can be found in one place (e.g., the collaboration object) and can be accessed during the meeting and afterwards from the collaborative platform or from a variety of other collaboration-enabled applications (e.g., calendar/messaging application, notebook application, planner application, task application, and the like).

(155) FIG. **10C** illustrates a user interface **1036** of a collaborative platform associated with user **1002**. In aspects, user **1002** may access a history tab **1038** of the user's calendar **1040** from a collaborative platform. History tab **1038** may provide a listing of past meetings and/or calls. Alternatively, user **1002** may search the collaborative platform for past meetings and/or calls (e.g., based on title, date, attendees, and the like) and a similar list of results may be presented (not shown). In some cases, meetings and calls may be provided in the same listing, e.g., ordered by date and time; in other cases, separate listings of meetings and calls may be provided. User interface **1036** may further include abbreviated information about each result. For instance, icons **1046A-B** may be provided for differentiating meeting from calls, icon **1048** may indicate that the meeting or call is recurring, icon **1050** may indicate whether the meeting or call was associated with content, icon **1052** may indicate whether (and how many) action items were associated with the meeting or call, and icon **1054** may indicate whether the meeting or call was recorded. In some aspects, a duration of the meeting or call may also be provided.

(156) Additionally, in response to selecting a result, e.g., result **1042**, additional details and/or content associated with the meeting or call may be provided. For instance, the collaboration object **1044** associated with the meeting or call may be provided. As with other collaboration objects described above (as well as interactive collaborative objects), the collaboration object **1044** may be collaboration enabled. That is, although the meeting or call has already occurred, users may continue to collaborate and add or remove content from the collaboration object. Any edits or changes made to dynamic content categories (e.g., agenda, notes, action items) may be reflected across any other application or user device associated with the meeting or call. As illustrated, result **1042** is also associated with static content, including a whiteboard session **1056**, a presentation **1058**, and a spreadsheet **1060**. While this static content is accessible from collaboration object **1044**, the static content may not be collaboration enabled. That is, if one user opens presentation **1058** and makes changes, these changes may not be reflected across other applications and user systems in near real-time (e.g., as the user is making the changes). However, if the user attaches the revised version of presentation **1058** to the collaboration object within user interface **1036**, the collaboration object **1044** may be updated across applications and user devices to reflect attachment of the revised presentation **1058**. Similarly, if the spreadsheet **1060** is removed from the collaboration object of **1044**, the collaboration object **1044** may be updated across applications and user devices to reflect removal of the spreadsheet **1060**.

(157) FIG. **11** illustrates an example method for detecting and implementing a user objective to schedule a collaboration, in accordance with aspects of the present disclosure.

(158) A general order of the operations for the method **1100** is shown in FIG. **11**. The method **1100** may include more or fewer steps and/or may progress in a different order of steps from those shown in FIG. **11**. The method **1100** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **1100** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **1100** shall be explained with reference to the systems, components, devices, user interfaces, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with

FIGS. 1-10C and 12-14B.

(159) At collection operation **1102**, data may be collected to detect indications of an intention to collaborate. For instance, data may be collected from chat threads, SMS texts, email messages, and the like. Based on natural language processing and/or machine learning techniques, for example, the system may be trained to recognize words and/or phrases that indicate a user intention or objective to collaborate.

(160) At detect intention operation **1104**, an intention to collaborate may be detected based on the collected data. The intention to collaborate may be detected, for instance, based on explicit requests to meet to more implicit indications of a desire to connect or collaborate. For example, queries indicative of an intention to collaborate may include but are not limited to: “Can we set a meeting?”; “Let's schedule something soon?”; “How does your calendar look tomorrow?”; “What's your availability next week?”; “Can we sync up?”; “When are you free?”; “Let's get something on the calendar”; “How's your afternoon?”; and the like. In aspects, the system may parse various data (e.g., verbal or written text) to identify certain words and/or phrases, such as “meet,” “free,” “availability,” “calendar,” “when,” “sync,” “schedule,” “let's chat,” and the like. Based on natural language processing and/or machine learning techniques, for example, the system may be trained to recognize such words and/or phrases that indicate a user intention or objective to collaborate. In aspects, collaboration may involve an in-person meeting, a virtual meeting, a phone call, a video call, or the like. In some cases, the system may determine that the user desires a meeting, e.g., based on a phrase such as, “Let's get something on the calendar.” In other cases, the system may determine that the user desires a phone call, e.g., based on a phrase such as, “Do you have time to chat?” In still other cases, the system may detect a user intention to collaborate, but may not be able to determine a particular collaboration venue, e.g., based on a phrase such as, “Can we sync up?”

(161) At parse operation **1106**, collected data indicating an intention or objective to collaborate may be further parsed to determine parameters regarding the desired collaboration. In aspects, based on natural language processing and/or machine learning techniques, the system may be able to identify a venue, topic, timing, attendees, and the like, for an intended collaboration. For instance, in a chat thread between a first user and a second user, the first user may query: “Can we chat about the presentation tomorrow?” Based on context (e.g., a chat between the first and second users) and the first user's query, the system may determine that the second user is a required attendee, the topic of the desired collaboration is a “presentation,” and the timing of desired collaboration is “tomorrow.” Additionally, based on the term “chat,” the system may determine that the collaboration may be a phone call as opposed to an in-person meeting, for example.

(162) At provide operation **1108**, a prompt for scheduling a collaboration may be provided. Based on a determination of a venue for the collaboration, the prompt may suggest scheduling a meeting or a call, for instance. In some cases, free times on attendee calendars may be evaluated and the prompt may provide an indication of one or more free times. If the anticipated collaboration is a call, the prompt may provide the phone numbers of attendees. Additionally or alternatively, the prompt may provide selectable controls for “call now” or “meet now.” In this case, rather than scheduling a collaboration, the user may be able to connect directly with anticipated attendees. Additionally or alternatively, the free times and/or phone numbers of the prompt may be selectable to initiate a meeting or call invitation.

(163) At optional prepopulate operation **1110**, additional parameters may be added to the prompt. For example, if the system determined that the topic of the anticipated collaboration is a presentation, the prompt may state: “Would you like to schedule a meeting with Bill regarding the presentation?” or “Would you like to schedule a call to discuss the presentation?” Additionally or alternatively, if the system determined timing for the anticipated collaboration, the prompt may state: “Would you like to schedule a meeting with Bill tomorrow?” In this case, the prompt may also provide free times on the attendee's calendars for the next day. As should be appreciated, the prompt may provide more or less information for scheduling a collaboration based on

determinations of user intentions.

(164) At receive operation **1112**, a selection of the prompt may be received. For instance, the user may click the prompt itself or a control provided by the prompt (e.g., a free time on attendee calendars). If the user selects a “meet now” or “call now” control, the method may end at operation **1116**.

(165) At provide operation **1114**, in response to receiving a selection of the prompt, a meeting invitation template (or a call invitation template) may be provided for scheduling the collaboration. In aspects, the meeting invitation template may be prepopulated with parameters for the collaboration, such as a topic. Additionally, if the system determined that the topic was to discuss a presentation, for example, the presentation may be suggested as an attachment (or automatically attached) to the meeting invitation template. If a free time (or one or more phone numbers) were selected in the prompt, these selections may also be prepopulated in the meeting invitation template. As described above, the meeting invitation template may include an object template. An object template may include a predetermined structure for accepting content, such as fields for receiving meeting descriptions, a tool bar having controls for attaching documents and/or images, adjusting text formatting, and the like. The object template may further be prepopulated with content categories that may be associated with a meeting, such as an agenda, notes, and action items. In aspects, the content categories may be collaboration enabled and configured with fields for receiving content items (e.g., specific agenda items, notes, action items) associated with the proposed meeting. Following provide operation **1114**, the method **1100** may progress in substantially a same manner as method **600** at receive content operation **606**.

(166) At end operation **1116**, the method may be terminated if the user selects a “meet now” or “call now” control from the prompt.

(167) As should be appreciated, operations **1102-1116** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

(168) FIG. **12** illustrates an example method for detecting a user collaboration and automatically generating a collaboration object, in accordance with aspects of the present disclosure.

(169) A general order of the operations for the method **1200** is shown in FIG. **12**. The method **1200** may include more or fewer steps and/or may progress in a different order of steps from those shown in FIG. **12**. The method **1200** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **1200** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **1200** shall be explained with reference to the systems, components, devices, user interfaces, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. **1-11** and **13-14B**.

(170) At detect call operation **1202**, an impromptu collaboration between at least two users may be detected. For instance, data indicative of a call between users or data indicative of textual interactions such as a channel thread, an email thread, or a chat thread may be detected. In aspects, a call may be Internet protocol (IP)-based and may be made within a collaborative platform, but other calls between collaborative team members may also be detected. For instance, based on a mapping of user phone numbers to user identities, a call using one or more cell phones between members of a collaboration team may be detected. In further aspects, a a channel thread, an email thread, or a chat thread that centers around a new project or topic may be detected.

(171) At launch operation **1204**, in response to detecting the impromptu collaboration, a collaborative platform or interface for hosting the collaboration may be launched. For example, the collaborative platform may provide video functionality such that participants may view one another during the collaboration. The collaborative platform may further automatically provide a

collaboration object for facilitating the impromptu meeting. As described above, a collaboration object may be the same or similar to a collaboration object. The collaboration object may be in the form of a structured framework including meeting components for receiving and organizing content, including an agenda component, a note component, and an action item component, for instance. The collaboration object may comprise a portable interface having functionality for concurrent multi-user interaction with the content (e.g., dynamic content). Additionally, static content may be attached, shared, or otherwise linked to the collaboration object (either manually by participants or automatically by the system). In some aspects, the collaboration object may be provided via a collaborative UX customized for the collaborative platform.

(172) At receive input operation **1206**, input to the collaboration object may be received. For instance, one or more collaboration participants may input content via the collaborative platform into dynamic content categories associated with the collaboration object, such as an agenda item, a note, or an action item. In aspects, although the collaboration was not pre-schedule but occurred ad hoc, other collaboration enabled applications may be update to reflect the collaboration. That is, the calendars of the participants may automatically be updated with a meeting including the current collaboration object at time “now.” In this case, input may be received to the collaboration object from another application (e.g., a calendar/messaging application).

(173) At reflect operation **1208**, the input received from one or more participants may be reflected in near real-time across user devices and applications. For example, the input of the agenda item, note, or action item may be reflected in the collaboration object on the devices of other participants. The input may be reflected across the user devices at substantially (or nearly) the same time as it is received by the participant. In some examples, the input may be received and reflected in the collaboration object provided by the collaborative platform during the meeting. In other examples, input may be received to another collaboration enabled application, for example, but the input may still be reflected in near real-time in the collaboration object provided by collaborative platform hosting the meeting. That is, regardless of the application that receives the input to the collaboration object, the input may be reflected across the other collaboration-enabled applications and user devices accessing the collaboration object.

(174) At detect operation **1210**, a participant may share content via the collaborative platform during the meeting. Sharing content may involve sharing a presentation (e.g., via the video capabilities of the second application) with the meeting participants. Sharing content may also include sharing a link to content (e.g., to a video or website) within a chat thread (within the collaborative platform or another collaboration-enabled application) during the meeting. In aspects, the content shared by the participant may be detected by the collaborative platform (or the another collaboration-enabled application).

(175) At associate operation **1212**, the shared content may be automatically associated (e.g., linked or attached) to the collaboration object. For example, if a presentation is shared during the meeting, the presentation may automatically be associated with the collaboration object (e.g., as a link or an attachment). In another example, if a link to content is shared during the meeting, the link may be associated with collaboration object. In yet another example, when a link to content is shared, the link may be followed and the content may be retrieved and associated with the collaboration object.

(176) At reflect operation **1214**, the content shared by the participant may be reflected in near real-time across user devices and applications. For example, the shared content may be reflected in the collaboration object within the collaborative platform on the devices of the other participants. The content may be reflected across the user devices at substantially (or nearly) the same time as it is shared by the participant. Additionally, the shared content may be reflected in near real-time as linked to the collaboration object within other collaboration-enabled applications, e.g., a notebook application, calendar/messaging application, and the like. For instance, the participant may share a link to content within a notebook application and the link may automatically be associated with the collaboration object provided by the collaborative platform in near real-time. That is, regardless of

the application through which the content is shared, the shared content may be reflected across the other collaboration-enabled applications and user devices accessing the collaboration object.

(177) As should be appreciated, operations **1202-1214** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

(178) FIGS. **13-14B** and the associated descriptions provide a discussion of a variety of operating environments in which aspects of the disclosure may be practiced. However, the devices and systems illustrated and discussed with respect to FIGS. **13-14B** are for purposes of example and illustration and are not limiting of a vast number of computing device configurations that may be utilized for practicing aspects of the disclosure, described herein

(179) FIG. **13** is a block diagram illustrating physical components (e.g., hardware) of a computing device **1300** with which aspects of the disclosure may be practiced. The computing device components described below may have computer executable instructions for implementing one or more collaboration-enabled applications **1320** on a computing device, including computer executable instructions for the one or more collaboration-enabled applications **1320** that can be executed to employ the methods disclosed herein. In a basic configuration, the computing device **1300** may include at least one processing unit **1302** and a system memory **1304**. Depending on the configuration and type of computing device, the system memory **1304** may comprise, but is not limited to, volatile storage (e.g., random access memory), non-volatile storage (e.g., read-only memory), flash memory, or any combination of such memories. The system memory **1304** may include an operating system **1305** and one or more program modules **1306** suitable for running the one or more collaboration-enabled applications **1320**, such as object generator **1311**, object customizer **1313**, content receiver **1315**, or change synchronizer **1317**. The operating system **1305**, for example, may be suitable for controlling the operation of the computing device **1300**. Furthermore, embodiments of the disclosure may be practiced in conjunction with a graphics library, other operating systems, or any other application program and is not limited to any particular application or system. This basic configuration is illustrated in FIG. **13** by those components within a dashed line **1313**. The computing device **1300** may have additional features or functionality. For example, the computing device **1300** may also include additional data storage devices (removable and/or non-removable) such as, for example, magnetic disks, optical disks, or tape. Such additional storage is illustrated in FIG. **13** by a removable storage device **1309** and a non-removable storage device **1310**.

(180) As stated above, a number of program modules and data files may be stored in the system memory **1304**. While executing on the processing unit **1302**, the program modules **1306** (e.g., the one or more collaboration-enabled applications **1320**) may perform processes including, but not limited to, the aspects, as described herein. Other program modules that may be used in accordance with aspects of the present disclosure, and in particular for providing a messaging application interface, may include object generator **1311**, object customizer **1313**, content receiver **1315**, or change synchronizer **1317**, etc.

(181) Furthermore, embodiments of the disclosure may be practiced in an electrical circuit comprising discrete electronic elements, packaged or integrated electronic chips containing logic gates, a circuit utilizing a microprocessor, or on a single chip containing electronic elements or microprocessors. For example, embodiments of the disclosure may be practiced via a system-on-a-chip (SOC) where each or many of the components illustrated in FIG. **13** may be integrated onto a single integrated circuit. Such an SOC device may include one or more processing units, graphics units, communications units, system virtualization units and various application functionality all of which are integrated (or “burned”) onto the chip substrate as a single integrated circuit. When operating via an SOC, the functionality, described herein, with respect to the capability of client to switch protocols may be operated via application-specific logic integrated with other components

of the computing device **1300** on the single integrated circuit (chip). Embodiments of the disclosure may also be practiced using other technologies capable of performing logical operations such as, for example, AND, OR, and NOT, including but not limited to mechanical, optical, fluidic, and quantum technologies. In addition, embodiments of the disclosure may be practiced within a general purpose computer or in any other circuits or systems.

(182) The computing device **1300** may also have one or more input device(s) **1312** such as a keyboard, a mouse, a pen, a sound or voice input device, a touch or swipe input device, etc. The output device(s) **1314** such as a display, speakers, a printer, etc. may also be included. The aforementioned devices are examples and others may be used. The computing device **1300** may include one or more communication connections **1316** allowing communications with other computing devices **1350**. Examples of suitable communication connections **1316** include, but are not limited to, radio frequency (RF) transmitter, receiver, and/or transceiver circuitry; universal serial bus (USB), parallel, and/or serial ports.

(183) The term computer readable media may include computer storage media. Computer storage media may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, or program modules. The system memory **1304**, the removable storage device **1309**, and the non-removable storage device **1310** are all computer storage media examples (e.g., memory storage). Computer storage media may include RAM, ROM, electrically erasable read-only memory (EEPROM), flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other article of manufacture which can be used to store information and which can be accessed by the computing device **1300**. Any such computer storage media may be part of the computing device **1300**. Computer storage media does not include a carrier wave or other propagated or modulated data signal.

(184) Communication media may be embodied by computer readable instructions, data structures, program modules, or other data in a modulated data signal, such as a carrier wave or other transport mechanism, and includes any information delivery media. The term “modulated data signal” may describe a signal that has one or more characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, radio frequency (RF), infrared, and other wireless media.

(185) FIGS. **14A** and **14B** illustrate a mobile computing device **1400**, for example, a mobile telephone, a smart phone, wearable computer (such as a smart watch), a tablet computer, a laptop computer, and the like, with which embodiments of the disclosure may be practiced. In some aspects, the client may be a mobile computing device. With reference to FIG. **14A**, one aspect of a mobile computing device **1400** for implementing the aspects is illustrated. In a basic configuration, the mobile computing device **1400** is a handheld computer having both input elements and output elements. The mobile computing device **1400** typically includes a display **1405** and one or more input buttons **1410** that allow the user to enter information into the mobile computing device **1400**. The display **1405** of the mobile computing device **1400** may also function as an input device (e.g., a touch screen display). If included, an optional side input element **1415** allows further user input. The side input element **1415** may be a rotary switch, a button, or any other type of manual input element. In alternative aspects, mobile computing device **1400** may incorporate more or less input elements. For example, the display **1405** may not be a touch screen in some embodiments. In yet another alternative embodiment, the mobile computing device **1400** is a portable phone system, such as a cellular phone. The mobile computing device **1400** may also include an optional keypad **1435**. Optional keypad **1435** may be a physical keypad or a “soft” keypad generated on the touch screen display. In various embodiments, the output elements include the display **1405** for showing a graphical user interface (GUI), a visual indicator **1420** (e.g., a light emitting diode), and/or an audio

transducer **1425** (e.g., a speaker). In some aspects, the mobile computing device **1400** incorporates a vibration transducer for providing the user with tactile feedback. In yet another aspect, the mobile computing device **1400** incorporates input and/or output ports, such as an audio input (e.g., a microphone jack), an audio output (e.g., a headphone jack), and a video output (e.g., a HDMI port) for sending signals to or receiving signals from an external device.

(186) FIG. **14B** is a block diagram illustrating the architecture of one aspect of a mobile computing device. That is, the mobile computing device **1400** can incorporate a system (e.g., an architecture) **1402** to implement some aspects. In one embodiment, the system **1402** is implemented as a “smart phone” capable of running one or more applications (e.g., browser, e-mail, calendaring, contact managers, messaging clients, games, and media clients/players). In some aspects, the system **1402** is integrated as a computing device, such as an integrated personal digital assistant (PDA) and wireless phone.

(187) One or more application programs **1466** may be loaded into the memory **1462** and run on or in association with the operating system **1464**. Examples of the application programs include phone dialer programs, e-mail programs, personal information management (PIM) programs, word processing programs, spreadsheet programs, Internet browser programs, messaging programs, and so forth. The system **1402** also includes a non-volatile storage area **1468** within the memory **1462**. The non-volatile storage area **1468** may be used to store persistent information that should not be lost if the system **1402** is powered down. The application programs **1466** may use and store information in the non-volatile storage area **1468**, such as e-mail or other messages used by an e-mail application, and the like. A synchronization application (not shown) also resides on the system **1402** and is programmed to interact with a corresponding synchronization application resident on a host computer to keep the information stored in the non-volatile storage area **1468** synchronized with corresponding information stored at the host computer. As should be appreciated, other applications may be loaded into the memory **1462** and run on the mobile computing device **1400**, including the instructions for providing various collaboration-enabled applications as described herein (e.g., object generator, object customizer, content receiver, or change synchronizer, etc.).

(188) The system **1402** has a power supply **1470**, which may be implemented as one or more batteries. The power supply **1470** might further include an external power source, such as an AC adapter or a powered docking cradle that supplements or recharges the batteries.

(189) The system **1402** may also include a radio interface layer **1472** that performs the function of transmitting and receiving radio frequency communications. The radio interface layer **1472** facilitates wireless connectivity between the system **1402** and the “outside world,” via a communications carrier or service provider. Transmissions to and from the radio interface layer **1472** are conducted under control of the operating system **1464**. In other words, communications received by the radio interface layer **1472** may be disseminated to the application programs **1466** via the operating system **1464**, and vice versa.

(190) The visual indicator **1420** may be used to provide visual notifications, and/or an audio interface **1474** may be used for producing audible notifications via the audio transducer **1425**. In the illustrated embodiment, the visual indicator **1420** is a light emitting diode (LED) and the audio transducer **1425** is a speaker. These devices may be directly coupled to the power supply **1470** so that when activated, they remain on for a duration dictated by the notification mechanism even though the processor **1460** and other components might shut down for conserving battery power. The LED may be programmed to remain on indefinitely until the user takes action to indicate the powered-on status of the device. The audio interface **1474** is used to provide audible signals to and receive audible signals from the user. For example, in addition to being coupled to the audio transducer **1425**, the audio interface **1474** may also be coupled to a microphone to receive audible input, such as to facilitate a telephone conversation. In accordance with embodiments of the present disclosure, the microphone may also serve as an audio sensor to facilitate control of notifications, as will be described below. The system **1402** may further include a video interface **1476** that

enables an operation of an on-board camera **1430** to record still images, video stream, and the like. (191) A mobile computing device **1400** implementing the system **1402** may have additional features or functionality. For example, the mobile computing device **1400** may also include additional data storage devices (removable and/or non-removable) such as, magnetic disks, optical disks, or tape. Such additional storage is illustrated in FIG. **14B** by the non-volatile storage area **1468**.

(192) Data/information generated or captured by the mobile computing device **1400** and stored via the system **1402** may be stored locally on the mobile computing device **1400**, as described above, or the data may be stored on any number of storage media that may be accessed by the device via the radio interface layer **1472** or via a wired connection between the mobile computing device **1400** and a separate computing device associated with the mobile computing device **1400**, for example, a server computer in a distributed computing network, such as the Internet. As should be appreciated such data/information may be accessed via the mobile computing device **1400** via the radio interface layer **1472** or via a distributed computing network. Similarly, such data/information may be readily transferred between computing devices for storage and use according to well-known data/information transfer and storage means, including electronic mail and collaborative data/information sharing systems.

(193) Aspects of the present disclosure, for example, are described above with reference to block diagrams and/or operational illustrations of methods, systems, and computer program products according to aspects of the disclosure. The functions/acts noted in the blocks may occur out of the order as shown in any flowchart. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

(194) The description and illustration of one or more aspects provided in this application are not intended to limit or restrict the scope of the disclosure as claimed in any way. The aspects, examples, and details provided in this application are considered sufficient to convey possession and enable others to make and use the best mode of claimed disclosure. The claimed disclosure should not be construed as being limited to any aspect, example, or detail provided in this application. Regardless of whether shown and described in combination or separately, the various features (both structural and methodological) are intended to be selectively included or omitted to produce an embodiment with a particular set of features. Having been provided with the description and illustration of the present application, one skilled in the art may envision variations, modifications, and alternate aspects falling within the spirit of the broader aspects of the general inventive concept embodied in this application that do not depart from the broader scope of the claimed disclosure.

Claims

1. A method for receiving a meeting invitation including a collaboration object, the method comprising: receiving an indication from a user to generate a collaboration object associated with the meeting using a first application, wherein the collaboration object comprises an attendance tracker; generating the collaboration object, the collaboration object comprising a portable interface providing functionality for concurrent multi-user interaction with content of the collaboration object in near real-time; retrieving metadata from the collaboration object, wherein the metadata comprises information for customizing a first collaborative user experience (UX) for the first application and a second collaborative UX for a second application; based on the metadata, causing the first collaborative UX associated with the collaboration object to be rendered via the first application; launching the second application; based on the metadata, causing the second collaborative UX associated with the collaboration object to be rendered via the second application, wherein the first collaborative UX and the second collaborative UX are different; receiving a

change to content associated with the collaboration object via the second application; and automatically causing the change to be reflected in the collaboration object associated with the first application.

2. The method of claim 1, further comprising: automatically causing the change to be reflected in the collaboration object associated with a corresponding meeting in the user's calendar associated with the first application.

3. The method of claim 1, wherein the collaboration object includes one or more content categories for receiving content associated with the meeting.

4. The method of claim 1, wherein the receiving an indication from a user to generate a collaboration object associated with the meeting using a first application comprises receiving content to a content category selected from a plurality of content categories to be added to the collaboration object.

5. The method of claim 1, further comprising: receive a content item shared during the meeting via the second application; automatically cause the shared content item to be associated with the collaboration object via the second application; and automatically cause the shared content item to be reflected in the collaboration object via the first application.

6. A computer storage medium storing computer-executable instructions that when executed cause at least one processor to perform operations, comprising: receiving an indication from a user to generate a collaboration object associated with a meeting using a first application, wherein the collaboration object comprises an attendance tracker and has associated metadata comprising information for customizing a first collaborative user experience (UX) for the collaboration object via the first application and a second collaborative UX for a second application; generating the collaboration object, the collaboration object comprising a portable interface providing functionality for concurrent multi-user interaction with content of the collaboration object in near real-time; launching, based on the metadata, the second application for hosting the meeting, wherein the collaboration object is accessible for concurrent editing via the second collaborative UX by a plurality of meeting participants; detecting content shared by at least one meeting participant during the meeting; automatically causing the shared content to be associated with the collaboration object via the second application; and automatically causing the shared content to be reflected in the collaboration object via the first application.

7. The computer storage medium of claim 6, the operations further comprising: receiving user input to the collaboration object via the second application.

8. The computer storage medium of claim 7, the operations further comprising: automatically causing the user input to be reflected in the collaboration object associated with the first application.

9. The computer storage medium of claim 6, wherein the collaboration object includes one or more content categories for receiving content associated with the meeting.

10. The computer storage medium of claim 6, wherein the receiving an indication from a user to generate a collaboration object associated with the meeting using a first application comprises receiving content to a content category selected from a plurality of content categories to be added to the collaboration object.

11. A system comprising: at least one processing unit; and at least one memory having a plurality of instructions stored thereon that, when executed by the at least one processor, cause the system to: receive an indication from a user to generate a collaboration object associated with the meeting using a first application, wherein the collaboration object comprises an attendance tracker; generate the collaboration object, the collaboration object comprising a portable interface providing functionality for concurrent multi-user interaction with content of the collaboration object in near real-time; retrieve metadata from the collaboration object, wherein the metadata comprises information for customizing a first collaborative user experience (UX) for the first application and a second collaborative UX for a second application; based on the metadata, cause the first

collaborative UX associated with the collaboration object to be rendered via the first application; launch the second application; based on the metadata, cause the second collaborative UX associated with the collaboration object to be rendered via the second application, wherein the first collaborative UX and the second collaborative UX are different; receive a change to content associated with the collaboration object via the second application; and automatically cause the change to be reflected in the collaboration object associated with the first application.

12. The system of claim 11, the plurality of instructions when executed by the at least one processor causing the system to: automatically causing the change to be reflected in the collaboration object associated with a corresponding meeting in the user's calendar associated with the first application.

13. The system of claim 11, wherein the collaboration object includes one or more content categories for receiving content associated with the meeting.

14. The system of claim 11, wherein the receiving an indication from a user to generate a collaboration object associated with the meeting using a first application comprises receiving content to a content category selected from a plurality of content categories to be added to the collaboration object.

15. The system of claim 11, the plurality of instructions when executed by the at least one processor causing the system to: receive a content item shared during the meeting via the second application; automatically cause the shared content item to be associated with the collaboration object via the second application; and automatically cause the shared content item to be reflected in the collaboration object via the first application.
