

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402663
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hu; Ruilong et al.

Atomizing assembly and electronic cigarette

Abstract

The present invention provides an atomizing assembly and an electronic cigarette. The atomizing assembly includes a base and an atomizing core. A liquid storing cavity is disposed inside the base to store liquid tobacco. The atomizing core includes a body and a heater. An atomizing channel is opened and disposed to penetrate through the body. The heater is disposed on an inner wall of the atomizing channel. The body is made from porous materials. An outer sidewall of the body includes at least an absorbing face. A liquid conducting hole or a plurality of liquid conducting holes is opened and disposed on the absorbing face and extends into a wall of the body from the absorbing face. A contact area between the liquid tobacco and the absorbing face is large to facilitate control of an amount of conducted liquid tobacco.

Inventors:	Hu; Ruilong (Shenzhen, CN), Zhao; Senbing (Shenzhen, CN), Xu; Zhongli (Shenzhen, CN), Li; Yonghai (Shenzhen, CN)
Applicant:	SHENZHEN FIRST UNION TECHNOLOGY CO., LTD. (Shenzhen, CN)
Family ID:	67920850
Assignee:	SHENZHEN FIRST UNION TECHNOLOGY CO., LTD. (Shenzhen, CN)
Appl. No.:	17/623242
Filed (or PCT Filed):	June 23, 2020
PCT No.:	PCT/CN2020/097758
PCT Pub. No.:	WO2020/259505
PCT Pub. Date:	December 30, 2020

Prior Publication Data

Foreign Application Priority Data

CN 201910548306.3 Jun. 24, 2019

Publication Classification

Int. Cl.: A24F40/485 (20200101); A24F40/10 (20200101); A24F40/42 (20200101); A24F40/44 (20200101); A24F40/46 (20200101)

U.S. Cl.:

CPC A24F40/485 (20200101); A24F40/10 (20200101); A24F40/42 (20200101); A24F40/44 (20200101); A24F40/46 (20200101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9814269	12/2016	Li et al.	N/A	N/A
2017/0156408	12/2016	Li et al.	N/A	N/A
2017/0215481	12/2016	Li et al.	N/A	N/A
2018/0199631	12/2017	Chen et al.	N/A	N/A
2019/0159524	12/2018	Qiu	N/A	N/A
2020/0163381	12/2019	Qiu	N/A	A24F 40/44
2020/0367564	12/2019	Li	N/A	A24F 40/44
2021/0169144	12/2020	Wensley	N/A	H05B 3/44

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105747278	12/2015	CN	N/A
107951079	12/2017	CN	N/A
207707306	12/2017	CN	N/A
208096012	12/2017	CN	N/A
109068744	12/2017	CN	N/A
109349680	12/2018	CN	N/A
208510082	12/2018	CN	N/A
208550022	12/2018	CN	N/A
110250578	12/2018	CN	N/A
210471007	12/2019	CN	N/A
3469928	12/2018	EP	A24F 47/00
3494811	12/2018	EP	N/A
10-2019-0051787	12/2018	KR	N/A

Primary Examiner: Louie; Philip Y

Assistant Examiner: Buckman; Jeffrey A.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) The present invention is a 35 U.S.C. § 371 National Phase conversion of International (PCT) Patent Application No. PCT/CN2020/097758, filed on Jun. 23, 2020, which claims benefit of Chinese Application No. 201910548306.3, filed on Jun. 24, 2019, the disclosure of which is incorporated by reference herein. The PCT International Patent Application was filed and published in Chinese.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present invention relates to a technical field of electronic cigarette equipment, particularly relates to an atomizing assembly and an electronic cigarette including the atomizing assembly.

Description of Related Art

(3) In some electronic cigarette products, an electronic cigarette includes a battery assembly and an atomization assembly. The battery assembly is electrically connected to the atomization assembly. As a result, the battery assembly supplies power to the atomization assembly.

(4) Liquid tobacco with high viscosity has problem such that a liquid conducting process of the liquid tobacco is slow, and therefore the slow process leads to too little aerosol being generated. However, during a heating and atomization process, a viscosity of the liquid tobacco decreases. As a result, a velocity of conducting the liquid tobacco increases, and the increased conducting velocity leads to problem such as increase of an amount of conducted liquid tobacco, etc. Therefore, the liquid tobacco with high viscosity exhibits a technical problem during its heating and atomization process. The technical problem includes inconvenient control of the amount of conducted liquid tobacco, and an unreasonable amount of conducted liquid tobacco, etc. As a result, the physical feeling experienced while utilizing the products is directly affected by the above problem.

BRIEF SUMMARY OF THE INVENTION

(5) An atomizing assembly and an electronic cigarette having the atomizing assembly are provided in accordance with a preferred embodiment of the present invention. The technical problem of existing technology, that an amount of conducted liquid tobacco is not conveniently controlled, can be solved by the utilization of the above atomizing assembly in accordance with the preferred embodiment of the present invention.

(6) A technical solution in accordance with the preferred embodiment of the present invention is as follows.

(7) An atomizing assembly applicable to electronic cigarettes includes a base and an atomizing core.

(8) A liquid storing cavity is disposed inside the base to store liquid tobacco.

(9) The atomizing core is installed in the base. The atomizing core includes a body and a heater. An atomizing channel is opened and disposed to penetrate through the body. The heater is disposed on an inner wall of the atomizing channel.

(10) The body is made from porous materials. An outer sidewall of the body includes at least an absorbing face. A liquid conducting hole or a plurality of liquid conducting holes is opened and disposed on the absorbing face and extends into a wall of the body from the absorbing face. A bottom of the liquid conducting hole or the plurality of liquid conducting holes is located inside the

wall of the body. The liquid tobacco stored in the liquid storing cavity flows into the body via the absorbing face.

(11) Alternatively, the base is disposed along a longitudinal direction of the atomizing assembly. An extension direction of the atomizing channel is perpendicular to the longitudinal direction of the atomizing assembly.

(12) Alternatively, an airflow channel is further disposed inside the base. The airflow channel is configured to spatially communicate with the atomizing channel.

(13) Alternatively, the atomizing assembly further includes a nozzle shell. A through hole is disposed to penetrate through the nozzle shell. The nozzle shell is installed at a side of the base facing away from the atomizing core. The through hole is configured to spatially communicate with the atomizing channel via the airflow channel.

(14) Alternatively, shortest conducting distances between respective bottoms of the plurality of liquid conducting holes and the inner wall of the atomizing channel are set to be equal to one another.

(15) Alternatively, a hole diameter of each of the liquid conducting hole or the plurality of liquid conducting holes is set to be larger than an average pore diameter of micro pores inside the body.

(16) Alternatively, the absorbing face is disposed corresponding to the liquid storing cavity. The absorbing face is a flat face. The liquid conducting hole or the plurality of liquid conducting holes is a plurality of liquid conducting holes, and the plurality of liquid conducting holes is evenly spaced and distributed on the absorbing face.

(17) Alternatively, the base further includes a liquid filling hole and a liquid outlet.

(18) Alternatively, the liquid filling hole is configured to spatially communicate with the liquid storing cavity. The liquid filling hole and the liquid outlet are respectively located on two opposite lateral walls of the liquid storing cavity. The liquid outlet is configured to spatially communicate with the liquid conducting hole or the plurality of liquid conducting holes.

(19) Alternatively, the atomizing assembly further includes a supporter and an end cover.

(20) The supporter is located at a side of the base. A fixing trough is opened and disposed at a side of the supporter facing toward the base. A part of the body is received in the fixing trough.

(21) The end cover is disposed between the base and the supporter. Another part of the body is covered around by the end cover. The end cover is fixed connected with the supporter. The end cover is engaged with the base. A transfer hole penetrating through the end cover is opened and disposed at the end cover. The liquid outlet is configured to spatially communicate with the liquid conducting hole or the plurality of liquid conducting holes via the transfer hole.

(22) Alternatively, a first installing trough is disposed at a side of the base facing toward the supporter. The liquid outlet is opened and disposed at a bottom of the first installing trough. The end cover is installed in the first installing trough, and the transfer hole is configured to spatially communicate with the liquid outlet.

(23) Alternatively, the atomizing assembly further includes a connecting seat. The connecting seat is installed to the base. A lateral wall of the connecting seat and a lateral wall of the base are fixedly connected with each other. An accommodating space is formed and surrounded between the connecting seat and the base. The atomizing core is accommodated in the accommodating space.

(24) Alternatively, a second installing trough is disposed at a side of the connecting seat facing toward the base. The supporter is installed in the second installing trough. When the connecting seat is installed to the base, the first installing trough and the second installing trough are correspondingly disposed to match with each other in order to fixedly install the atomizing core therebetween.

(25) An electronic cigarette in accordance with a preferred embodiment of the present invention is further provided to include the following.

(26) An atomizing assembly mentioned above is provided.

(27) A battery assembly is installed with the atomizing assembly and is electrically connected with

the atomizing assembly.

(28) In comparison to existing technology, in the atomizing assembly in accordance with a preferred embodiment of the present invention, a liquid conducting hole or a plurality of liquid conducting holes is opened and disposed on the absorbing face of the body. In actual products, liquid conducting holes with various forms can be disposed and opened on a lateral wall of the body based on user's requirement in order to much conveniently control a liquid conducting process of liquid tobacco. Besides, liquid tobacco enters the body through the absorbing face. A contact area between the liquid tobacco and the absorbing face is large to facilitate control of an amount of conducted liquid tobacco.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to much explicitly describe technical solutions in accordance with a preferred embodiment of the present invention, the following will briefly introduce attached drawings required to be used in descriptions of the preferred embodiment of the present invention. Obviously, the attached drawings in the following descriptions show only some embodiments of the present invention. For those of ordinary skill in the art, other attached drawings can be further obtained based on structures shown in these attached drawings without any creative labor or work.
- (2) FIG. 1 shows a schematic perspective view of an electronic cigarette in accordance with a preferred embodiment of the present invention.
- (3) FIG. 2 shows a schematic perspective view of an atomizing assembly shown in FIG. 1 in accordance with a preferred embodiment of the present invention.
- (4) FIG. 3 shows a schematic cross sectional view of the atomizing assembly shown in FIG. 2 in accordance with a preferred embodiment of the present invention.
- (5) FIG. 4 shows a schematic exploded perspective view of the atomizing assembly shown in FIG. 2.
- (6) FIG. 5 shows a schematic exploded perspective view of the atomizing assembly shown in FIG. 4 viewed from another view angle by omitting a nozzle shell and a seal.
- (7) FIG. 6 shows a schematic exploded perspective view of an atomizing core of FIG. 4 showing installation thereof.
- (8) FIG. 7 shows a schematic cross sectional view of the atomizing core shown in FIG. 6.

DETAILED DESCRIPTION OF THE INVENTION

(9) In order to facilitate best understanding of the present invention, the present invention will be illustrated in more detail below in conjunction with the attached drawings and preferred embodiments. It should be noted that when an element is expressed as “being fixed to/being fixedly connected to” another element, this element may be directly on the another element, or there may be one or more intervening elements between this element and the another element. When an element is expressed as “being connected to” another element, this element can be directly connected to the another element, or there may be one or more intervening elements between this element and the another element. Terminology in the specification such as “vertical”, “horizontal”, “left”, “right”, “inside”, “outside”, or similar expressions, etc., is only used for descriptive purposes.

(10) Unless otherwise defined, any technical and scientific terminology used in this specification has the same meaning as commonly understood by those skilled in the technical field of the present invention. Terminology used in this specification of the present invention is only for a purpose of describing specific embodiments, and is not used to limit the present invention. Terminology such as “and/or” used in this specification includes any and all combinations of one or more related listed items.

(11) In addition, technical features involved in different embodiments of the present invention described below can be mutually combined as long as they do not conflict with one another.

(12) In this specification, the term of “installation” means to include methods, such as welding, screwing, clamping, bonding, etc., in order to fix or restrict a certain element or device to a specific position or place. The element or device can be held still in a specific position or place, or can be restricted to move within a limited range. The element or device can be disassembled or cannot be disassembled after being fixed or restricted to a specific position or place. The above is not limited in embodiments of the present application.

(13) Referring to FIG. 1, an electronic cigarette **300** in accordance with a preferred embodiment of the present invention is provided. The electronic cigarette **300** includes a battery assembly **200** and an atomizing assembly **100**. The battery assembly **200** is installed at an end of the atomizing assembly **100** in order to shape the electronic cigarette **300** as a straight-lined structure.

Alternatively, the battery assembly **200** and the atomizing assembly **100** are fixedly installed together via engaging connection and/or screw fixing connection.

(14) Understandably, the battery assembly **200** is electrically connected with the atomizing assembly **100**. The battery assembly **200** is used to supply power to the atomizing assembly **100** so that the atomizing assembly **100** is able to atomize liquid tobacco into aerosols for users to inhale.

(15) Referring to FIGS. 2-3, the atomizing assembly **100** includes a nozzle shell **10**, a base **20** and a connecting seat **30**. The nozzle shell **10**, the base **20** and the connecting seat **30** are fixedly connected in sequence to form a straight-lined structure. The nozzle shell **10**, the base **20** and the connecting seat **30** are all disposed along a longitudinal direction **a** of the atomizing assembly **100**. The battery assembly **200** is installed at an end of the connecting seat **30** spaced away from the base **20**.

(16) The nozzle shell **10** is shaped as a cover. The base **20** is substantially shaped as a hexahedron. The nozzle shell **10** covers around outside an end of the base **20**. A through hole **11** is disposed to penetrate through a top of the nozzle shell **10**. An airflow channel **21** is disposed inside the base **20** or at a lateral side of the base **20**. When the nozzle shell **10** covers around outside the end of the base **20**, the through hole **11** is configured to spatially communicate with the airflow channel **21**. Alternatively, the airflow channel **21** is straightly disposed along a lateral wall of the base **20**. The airflow channel **21** extends along a direction parallel to the longitudinal direction **a** of the atomizing assembly **100**.

(17) In a preferred embodiment of the present invention, a protrusion **22** is disposed to protrude at a lateral side of the base **20**. An engaging notch **12** is disposed at a lateral side of the nozzle shell **10** corresponding to the protrusion **22**. When the nozzle shell **10** covers around on a top of the base **20**, the protrusion **22** is engaged and mated with the engaging notch **12** in order to fixedly install the nozzle shell **10** onto the end of the base **20**, and to therefore spatially communicate the through hole **11** with the airflow channel **21**.

(18) A liquid storing cavity **24** is disposed inside the base **20**. A liquid filling hole **241** is disposed to be opened at the top of the base **20** and is configured to spatially communicate with the liquid storing cavity **24**. Alternatively, the liquid filling hole **241** is located in a position corresponding to the through hole **11**. Understandably, the atomizing assembly **100** further includes a seal **2411**. The seal **2411** is used to seal and block the liquid filling hole **241**. When the nozzle shell **10** is opened and removed by a user, the seal **2411** can be seen by the user. After the seal **2411** is opened and removed by the user, liquid tobacco can be filled into the liquid storing cavity **24** via the liquid filling hole **241**.

(19) A liquid outlet **242** is disposed to be opened at a bottom of the base **20** and to be configured to spatially communicate with the liquid storing cavity **24**. The liquid outlet **242** is used to conduct liquid tobacco in the liquid storing cavity **24** out of the liquid storing cavity **24**. The liquid outlet **242** and the liquid filling hole **241** are respectively located on two opposite lateral walls of the liquid storing cavity **24**.

(20) Referring to FIGS. 4-6, the connecting seat **30** is installed at the bottom of the base **20**. Alternatively, the connecting seat **30** and the base **20** are connected to each other via an engaging fixing connection. A lateral wall of the base **20** and a lateral wall of the connecting seat **30** are engaged and fixedly connected with each other. An accommodating space **40** (As shown in FIG. 3) is surrounded between the base **20** and the connecting seat **30**. In a preferred embodiment of the present invention, a hook or a plurality of hooks **23** is formed to extend from a side of a lateral wall of the base **20** facing toward the connecting seat **30**. A groove or a plurality of groove **33** is disposed to be opened at a lateral wall of the connecting seat **30** corresponding to the hook or the plurality of hooks **23**. The hook or the plurality of hooks **23** and the groove or the plurality of groove **33** are one-to-one corresponded to and mated with each other. The hook or the plurality of hooks **23** is inserted into the groove or the plurality of groove **33** correspondingly to be secured and fixed therein.

(21) The atomizing assembly **100** further includes an atomizing core **50**, an end cover **61** and a supporter **62**. The atomizing core **50** is accommodated in the accommodating space **40**. The atomizing core **50** includes a body **51**. The body **51** is installed on the supporter **62**. The end cover **61** is disposed around the body **51** and is fixedly connected with the supporter **62** in order to seal and fix the body **51**. In some embodiments of the present invention, a connection between the end cover **61** and the supporter **62** can be an integrally formed connection, a fixedly engaging connection, or a screw fixing connection, etc.

(22) In a preferred embodiment of the present invention, a first installing trough **25** is disposed at a side of the bottom of the base **20** facing toward the connecting seat **30**. A second installing trough **34** is disposed at a side of the connecting seat **30** facing toward the base **20**. The first installing trough **25** and the second installing trough are correspondingly disposed to match with each other in order to fixedly install the atomizing core **50** therebetween. In particular, a top of the end cover **61** is shaped similarly to the first installing trough **25**, and the top of the end cover **61** is sealed and installed in the first installing trough **25**. A bottom of the supporter **62** is shaped similarly to the second installing trough **34**, and the bottom of the supporter **62** is installed in the second installing trough **34**. When the base **20** and the connecting seat **30** are engaged and fixed together, the atomizing core **50** is fixedly engaged therebetween.

(23) The liquid outlet **242** is opened and disposed at a bottom of the first installing trough **25**. A transfer hole **611** penetrating through the end cover **61** is opened and disposed at an end of the end cover **61** neighboring the liquid outlet **242**, and the transfer hole **611** is configured to spatially communicate with the liquid outlet **242**. In a preferred embodiment of the present invention, the transfer hole **611** is opened and disposed at the top of the end cover **61**. Liquid tobacco in the liquid storing cavity **24** can flow in sequence through the liquid outlet **242** and the transfer hole **611** to enter the body **51**.

(24) Referring to FIGS. 6-7, an atomizing channel **513** is opened and disposed to penetrate through the body **51**. The atomizing channel **513** extends horizontally. Alternatively, the atomizing channel **513** is shaped as a straight line. Furthermore, the atomizing channel **513** is shaped as a cylinder. The atomizing core **50** further includes a heater **52** disposed in the atomizing channel **513**. For example, the heater **52** is disposed on an inner wall of the atomizing channel **513**. In some embodiments of the present invention, the heater **52** is coiled around on the inner wall of the atomizing channel **513**, is embedded in the inner wall of the atomizing channel **513**, or is partially embedded in the inner wall of the atomizing channel **513** and partially exposed out in the atomizing channel **513**. Understandably, the heater **52** is an electrically powered heating body. In a condition of electrification, the heater **52** is heated to raise its temperature. For example, the heater **52** is an electric heating wire.

(25) In a preferred embodiment of the present invention, the body **51** is made from a porous material having a micro-pore structure. For example, the body **51** is made from micro-pore ceramic, micro-pore glass or expanded foam materials, etc. Liquid tobacco is conducted to the

atomizing channel **513** through porous material via capillary effect. Under heating of the heater **52** to raise its temperature, the liquid tobacco is atomized as aerosols to enter the atomizing channel **513**.

(26) An outer sidewall of the body **51** includes at least an absorbing face **511**. In a preferred embodiment of the present invention, the absorbing face **511** is a flat face. The absorbing face **511** is disposed corresponding to the liquid storing cavity **24**, and faces toward the transfer hole **611**. A liquid conducting hole or a plurality of liquid conducting holes **512** is opened and disposed on the absorbing face **511**, and extends into a wall of the body **51** from the absorbing face **511**. A bottom of the liquid conducting hole or the plurality of liquid conducting holes **512** is located inside the wall of the body **51**. For instance, a plurality of liquid conducting holes **512** is provided and disposed, and is evenly spaced and distributed on the absorbing face **511**. Furthermore, shortest conducting distances between bottoms of the plurality of liquid conducting holes **512** and the atomizing channel **513** are respectively set to be equal or substantially equal to one another. The plurality of liquid conducting holes **512** is used to conduct liquid tobacco in the liquid storing cavity **24** into the body **51**. In a preferred embodiment of the present invention, when the body **51** is transversely disposed, an extension direction of the atomizing channel **513** is perpendicular to the longitudinal direction **a** of the atomizing assembly **100**. In other words, the absorbing face **511** opened and disposed with the liquid conducting hole or the plurality of liquid conducting holes **512** has a large area, i.e., a contact area for the liquid tobacco to enter the atomizing core **50** is large. Conducted liquid tobacco is facilitated to be controlled by the above mentioned structure.

(27) In a preferred embodiment of the present invention, liquid tobacco in the liquid storing cavity **24** flows in sequence through the liquid outlet **242**, the transfer hole **611** and the liquid conducting hole or a plurality of liquid conducting holes **512** to enter the body **51**. Under heating of the heater **52** to raise its temperature, the liquid tobacco is heated and atomized into aerosols to enter the atomizing channel **513**.

(28) In a preferred embodiment of the present invention, the body **51** is made from porous materials having a preset porosity. Porosity of a porous material is decided by pore diameters of micro pores inside the porous material and a distribution density of the micro pores. When the porosity of the porous material is designed to be smaller, performance of the body **51** to prevent liquid tobacco from leaking can therefore be enhanced. However, smaller porosity will lower a conducting velocity of liquid tobacco at the same time. Hence, in physical products, a porous material with a proper porosity is required to be selected. For liquid tobacco with a higher viscosity, the liquid conducting hole or the plurality of liquid conducting holes **512** is opened and disposed on the body **51**, and a hole diameter of the liquid conducting hole or the plurality of liquid conducting holes **512** is set to be larger than an average pore diameter of micro pores inside a material of the body **51**. As a result, the conducting velocity of the liquid tobacco can be raised, and the performance of the body **51** enough to prevent the liquid tobacco from leaking can also be ensured to be enhanced. As a practical solution, the average pore diameter of the micro pores inside the material of the body **51** is $10\ \mu\text{m}\sim 100\ \mu\text{m}$, for example, preferably is $80\ \mu\text{m}$. The hole diameter of the liquid conducting hole or the plurality of liquid conducting holes **512** is $10\ \mu\text{m}\sim 500\ \mu\text{m}$, for example, preferably is $100\ \mu\text{m}$. When the hole diameter of the liquid conducting hole or the plurality of liquid conducting holes **512** is larger than the average pore diameter of the micro pores inside the body **51**, and a viscosity of liquid tobacco is higher, the liquid tobacco can enter the liquid conducting hole or the plurality of liquid conducting holes **512** having a larger hole diameter in order to have the liquid tobacco being conducted smoothly. After the liquid tobacco is heated to raise its temperature, the viscosity of the liquid tobacco is reduced. At this moment, the liquid tobacco enters the micro pores inside the body **51** having a smaller pore diameter. Hence, an amount of conducted liquid tobacco can be effectively controlled. The liquid tobacco is finally atomized by the heater **52** into aerosols to enter the atomizing channel **513**. The body **51** of a preferred embodiment of the present invention is designed to have a better performance to conduct

liquid tobacco into the body **41**. Particularly, for tobacco liquid with a higher viscosity, the body **51** of the present invention has a better liquid conductive effect. Meanwhile, the body **51** of the present invention can achieve a better control on conducting liquid tobacco so as to avoid technical problem of having an excessively large amount of conducted liquid tobacco during a process of heating and atomizing.

(29) A fixing trough **621** is opened and disposed at a top of the supporter **62**. The body **51** is transversely installed in the fixing trough **621**. In other words, the body **51** is transversely installed in the fixing trough **621** and a channel extension direction of the atomizing channel **513** is perpendicular to the longitudinal direction **a** of the atomizing assembly **100**. A first opening **6211** is disposed at an end of the fixing trough **621**, and a second opening **6212** is disposed at another end of the fixing trough **621**. The first opening **6211** is disposed corresponding to an end opening of the atomizing channel **513**. The second opening **6212** is disposed corresponding to another end opening of the atomizing channel **513**. The supporter **62** includes an extending wall **622** formed by extending outwards from an end of the supporter **62** having the first opening **6211**. When the bottom of the supporter **62** is installed in the second installing trough **34**, the extending wall **622** is engaged at a lateral wall of the second installing trough **34**. Besides, a connective trough **6221** (Shown in FIG. 3) is formed and surrounded by the extending wall **622** and the base **20**. Two ends of the connective trough **6221** are respectively configured to spatially communicate with the airflow channel **21** and the first opening **6211**. In other words, the airflow channel **21**, the connective trough **6221**, the first opening **6211**, the atomizing channel **513** and the second opening **6212** are configured to spatially communicate with one another in sequence.

(30) Referring to FIGS. 5-6, a first airflow trough **623** is formed by extending outwards from an end of the supporter **62** having the second opening **6212**. The first airflow trough **623** is configured to spatially communicate with the second opening **6212**. A second airflow trough **32** is disposed in the connecting seat **30**. The second airflow trough **32** is configured to spatially communicate with the first airflow trough **623**. Alternatively, the second airflow trough **32** penetrates through the connecting seat **30**. The second airflow trough **32** is shaped as a straight line, and an extending direction of the second airflow trough **32** is parallel to the longitudinal direction **a** of the atomizing assembly **100**. In a preferred embodiment of the present invention, the second airflow trough **32** and the first airflow trough **623** are located at a same side of the atomizing assembly **100**. The through hole **11**, the airflow channel **21**, the connective trough **6221**, the first opening **6211**, the atomizing channel **513**, the second opening **6212**, the first airflow trough **623** and the second airflow trough **32** are configured to spatially communicate with one another in sequence. Aerosols formed and existing in the atomizing channel **513** can therefore be inhaled by users via the through hole **11**.

(31) Understandably, electrodes **31** are disposed at the connecting seat **30**. The battery assembly **200** is located at an end of the connecting seat **30** spaced away from the base **20**. When the connecting seat **30** is fixedly connected with the base **20**, the battery assembly **200** is electrically connected with the heater **52** via the electrodes **31** in order to supply power to the atomizing assembly **100** so that the atomizing assembly **100** is able to atomize liquid tobacco. In a preferred embodiment of the present invention, two electrodes **31** are disposed at the connecting seat **30**. An end of each of the electrodes **31** is electrically connected with the heater **52**, and another end of each of the electrodes **31** is electrically connected with the battery assembly **200**.

(32) To sum up, a technical solution of the present invention includes, but is not limited to include, the following advantages.

(33) In the atomizing assembly **100** in accordance with a preferred embodiment of the present invention, a liquid conducting hole or a plurality of liquid conducting holes **512** is opened and disposed on the absorbing face **511** of the body **51**. In actual products, liquid conducting holes **512** with various forms can be disposed and opened on a lateral wall of the body **51** based on user's requirement in order to much conveniently control a liquid conducting process of liquid tobacco.

When the body **51** is transversely disposed, an extension direction of the atomizing channel **513** is perpendicular to the longitudinal direction **a** of the atomizing assembly **100**. Liquid tobacco enters the atomizing core **50** through the absorbing face **511**. A contact area between the liquid tobacco and the absorbing face is large to facilitate control of an amount of conducted liquid tobacco.

(34) Finally, it should be noted that the above embodiments are only used to illustrate technical solutions of the present invention, but not to limit them. Under inventive ideas of the present invention, technical features of the above embodiments or different embodiments can also be combined. Steps can be implemented in any order, and there are many other variations in different aspects of the present invention as described above. For the sake of brevity, those variations are not provided in details. Although the present invention has been described in detail with reference to the foregoing embodiments, it should be understood by the ordinary skilled in the art that they can still modify technical solutions recorded in the foregoing embodiments, or equivalently replace some of the technical features. Besides, these modifications or substitutions do not make essence of corresponding technical solutions deviate from the scope of the technical solutions provided in all preferred embodiments of the present invention.

Claims

1. An atomizing assembly applicable to electronic cigarettes comprising a base and an atomizing core; wherein a liquid storing cavity is disposed inside the base to store liquid tobacco; the atomizing core is installed in the base, the atomizing core comprises a body and a heater, a cylindrical atomizing channel is disposed through the body, the heater is disposed on an inner wall of the atomizing channel; the body is made from porous materials, an outer sidewall of the body comprises at least a flat absorbing face facing normally toward the liquid storing cavity, a central line of the absorbing face extends parallel to an extending direction of the atomizing channel, a plurality of liquid conducting holes is opened and disposed on the absorbing face and extends into a wall of the body from the absorbing face toward the inner wall of the atomizing channel, a bottom of each of the plurality of liquid conducting holes is located inside the wall of the body, the liquid tobacco stored in the liquid storing cavity flows into the body via the absorbing face; shortest conducting distances between respective bottoms of the plurality of liquid conducting holes and the inner wall of the atomizing channel are set to be equal, and an extension length of at least one of the plurality liquid conducting holes closer to the central line of the absorbing face is shorter than extension lengths of others of the plurality liquid conducting holes located farther away from the central line of the absorbing face.
2. The atomizing assembly as claimed in claim 1, wherein the base is disposed along a longitudinal direction of the atomizing assembly, and the atomizing channel extends perpendicularly to the longitudinal direction of the atomizing assembly.
3. The atomizing assembly as claimed in claim 1, wherein an airflow channel is further disposed inside the base, the airflow channel is configured to spatially communicate with the atomizing channel.
4. The atomizing assembly as claimed in claim 3, wherein the atomizing assembly further comprises a nozzle shell, a through hole is disposed to penetrate through the nozzle shell, the nozzle shell is installed to the base, the through hole is configured to spatially communicate with the atomizing channel via the airflow channel.
5. The atomizing assembly as claimed in claim 1, wherein a hole diameter of the each of the plurality of liquid conducting holes is set to be larger than an average pore diameter of micro pores inside the body.
6. The atomizing assembly as claimed in claim 1, wherein the absorbing face is disposed corresponding to the liquid storing cavity, and the plurality of liquid conducting holes is evenly spaced and distributed on the absorbing face.

7. The atomizing assembly as claimed in claim 1, wherein the base further comprises a liquid filling hole and a liquid outlet; the liquid filling hole is configured to spatially communicate with the liquid storing cavity, the liquid filling hole and the liquid outlet are respectively located on two opposite lateral walls of the liquid storing cavity, the liquid outlet is configured to spatially communicate with the plurality of liquid conducting holes.

8. The atomizing assembly as claimed in claim 7, wherein the atomizing assembly further comprises a supporter and an end cover; the supporter is located at a side of the base, a fixing trough is opened and disposed at a side of the supporter facing toward the base, a part of the body is received in the fixing trough; the end cover is disposed between the base and the supporter, another part of the body is covered around by the end cover, and the end cover is fixed connected with the supporter, the end cover is engaged with the base, and a transfer hole penetrating through the end cover is opened and disposed at the end cover, the liquid outlet is configured to spatially communicate with the plurality of liquid conducting holes via the transfer hole.

9. The atomizing assembly as claimed in claim 8, wherein a first installing trough is disposed at a side of the base facing toward the supporter, the liquid outlet is opened and disposed at a bottom of the first installing trough, the end cover is installed in the first installing trough, and the transfer hole is configured to spatially communicate with the liquid outlet.

10. The atomizing assembly as claimed in claim 9, wherein the atomizing assembly further comprises a connecting seat, the connecting seat is installed to the base, a lateral wall of the connecting seat and a lateral wall of the base are fixedly connected with each other, and an accommodating space is formed and surrounded between the connecting seat and the base, the atomizing core is accommodated in the accommodating space.

11. The atomizing assembly as claimed in claim 10, wherein a second installing trough is disposed at a side of the connecting seat facing toward the base, the supporter is installed in the second installing trough, when the connecting seat is installed to the base, the first installing trough and the second installing trough are correspondingly disposed to match with each other in order to fixedly install the atomizing core therebetween.

12. An electronic cigarette, comprising: an atomizing assembly as claimed in claim 1; a battery assembly is installed with the atomizing assembly and is electrically connected with the atomizing assembly.
