

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396386
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	McCutcheon, IV; Robert Johnstone et al.

Autonomous lawn mower

Abstract

An autonomous lawn mower is described. The autonomous lawn mower comprises a chassis supporting a podium that is raked forward with respect to a horizontal plane. In some examples, the podium comprises a top portion that may support one or more sensors, antennas and/or cameras that may be used to provide environmental information regarding the surroundings of the autonomous lawn mower. In additional or alternative examples, the podium may facilitate communication services to and/or from the autonomous lawn mower. Such a podium may improve the operation of the mower by a user when manually (or semi-autonomously controlled) while optimizing a field of view of such sensors with respect to the mowable area.

Inventors: McCutcheon, IV; Robert Johnstone (Longmont, CO), Morrison; John Gordon (Longmont, CO), Roberts; Isaac Heath (Longmont, CO), McGlade; Kevin Peter (Denver, CO), Foster; Davis Thorp (Boulder, CO), Kaplan; Matthew Alexander (Fort Collins, CO), Goins; Zachary Austin (Boulder, CO), Quick; Matthew G. (Erie, CO)

Applicant: Scythe Robotics, Inc. (Longmont, CO)

Family ID: 1000008784439

Assignee: Scythe Robotics, Inc. (Longmont, CO)

Appl. No.: 17/342200

Filed: June 08, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220174865 A1	Jun. 09, 2022

Related U.S. Application Data

Publication Classification

Int. Cl.: **A01D34/00** (20060101); **A01D34/78** (20060101); **A01D34/82** (20060101); **A01D69/02** (20060101); **B60Q1/26** (20060101); **B60Q9/00** (20060101); **B60T7/16** (20060101); **B60T7/22** (20060101); **F21S43/14** (20180101); **F21S43/20** (20180101); **G05D1/00** (20060101); **G05D1/245** (20240101); **G05D1/248** (20240101); **G05D1/249** (20240101); **G08C17/02** (20060101); **H04N13/246** (20180101); **H04N23/50** (20230101); A01D34/66 (20060101); A01D101/00 (20060101); F21Y115/10 (20160101)

U.S. Cl.:

CPC **A01D34/008** (20130101); **A01D34/78** (20130101); **A01D34/828** (20130101); **A01D69/02** (20130101); **B60Q1/2611** (20130101); **B60Q9/00** (20130101); **B60T7/16** (20130101); **B60T7/22** (20130101); **F21S43/14** (20180101); **F21S43/26** (20180101); **F21S43/2605** (20240501); **G05D1/0246** (20130101); **G05D1/027** (20130101); **G05D1/0278** (20130101); **G05D1/245** (20240101); **G05D1/248** (20240101); **G05D1/249** (20240101); **G08C17/02** (20130101); **H04N13/246** (20180501); **H04N23/50** (20230101); A01D34/66 (20130101); A01D2101/00 (20130101); F21Y2115/10 (20160801)

Field of Classification Search

CPC: A01D (34/008); A01D (34/78); A01D (34/828); A01D (69/02); A01D (34/66); A01D (2101/00); B60Q (1/2611); B60Q (9/00); B60Q (2800/20); B60Q (1/507); B60T (7/16); B60T (7/22); F21S (43/14); F21S (43/26); G05D (1/0246); G05D (1/027); G05D (1/0278); G08C (17/02); H04N (13/246); H04N (23/50); H04N (13/239); H04N (17/002); H04N (23/698); H04N (23/90); H04N (7/181); F21Y (2115/10); B60K (7/0007); B60K (2007/0092)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8141886	12/2011	Sugden et al.	N/A	N/A
9864376	12/2017	Franzius	N/A	H04N 23/80
11172605	12/2020	Hahn et al.	N/A	N/A
2002/0104300	12/2001	Hunt	N/A	N/A
2003/0144774	12/2002	Trissel et al.	N/A	N/A
2005/0016787	12/2004	Lesesky	N/A	N/A
2006/0072914	12/2005	Arai et al.	N/A	N/A
2007/0024740	12/2006	Strong	N/A	N/A
2008/0304705	12/2007	Pomerleau et al.	N/A	N/A
2011/0071718	12/2010	Norris et al.	N/A	N/A
2013/0074466	12/2012	Zwieg et al.	N/A	N/A
2015/0025755	12/2014	Willgert	N/A	N/A

2015/0296707	12/2014	Fukuda et al.	N/A	N/A
2015/0366134	12/2014	Dollinger et al.	N/A	N/A
2016/0046468	12/2015	Heravi	N/A	N/A
2017/0124781	12/2016	Douillard et al.	N/A	N/A
2017/0139418	12/2016	Hiramatsu	N/A	N/A
2017/0183845	12/2016	Izumikawa	N/A	N/A
2017/0282784	12/2016	Foster et al.	N/A	N/A
2017/0307148	12/2016	Sharrah et al.	N/A	N/A
2017/0344020	12/2016	Grufman et al.	N/A	N/A
2018/0103579	12/2017	Deimert et al.	N/A	N/A
2018/0139896	12/2017	Wahlgren	N/A	N/A
2018/0339409	12/2017	Bal et al.	N/A	N/A
2018/0361584	12/2017	Bal et al.	N/A	N/A
2018/0364045	12/2017	Bal et al.	N/A	N/A
2019/0021226	12/2018	Dima	N/A	A01D 34/008
2019/0049968	12/2018	Dean et al.	N/A	N/A
2019/0248421	12/2018	Jacobsthal	N/A	B62D 25/06
2020/0042009	12/2019	Yang	N/A	A01D 34/008
2020/0062321	12/2019	Redinger	N/A	A01D 34/82
2020/0217932	12/2019	Gilliland et al.	N/A	N/A
2021/0100160	12/2020	Kang	N/A	G05D 1/0234
2021/0232114	12/2020	Stagg	N/A	N/A
2021/0347059	12/2020	Zhang	N/A	N/A
2021/0362718	12/2020	Ikenori	N/A	N/A
2022/0108152	12/2021	Neumann	N/A	G06N 3/08
2022/0108184	12/2021	Neumann	N/A	G06N 3/045
2022/0248599	12/2021	Joo	N/A	A01D 34/008
2023/0263093	12/2022	Suffolk	N/A	N/A
2023/0337577	12/2022	He	N/A	A01D 34/001

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110 326 423	12/2018	CN	N/A
0664018	12/1996	EP	N/A
2884364	12/2014	EP	A01D 34/008
3318170-82	12/2001	JP	N/A
WO-2018000922	12/2015	WO	N/A
WO-2018103065	12/2015	WO	N/A
WO-2018142482	12/2017	WO	N/A
WO-2018163599	12/2017	WO	N/A

WO-2018224678	12/2017	WO	N/A
WO-2019032864	12/2018	WO	N/A
WO-2019157072	12/2018	WO	N/A
WO-2019241923	12/2018	WO	N/A
WO 2021/247790	12/2020	WO	N/A
WO 2022/251088	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for application No. PCT/US2021/061936, date of mailing Feb. 17, 2022. cited by applicant

Primary Examiner: Camby; Richard M

Attorney, Agent or Firm: Moser Taboada

Background/Summary

RELATED APPLICATIONS (1) This application claims benefit to U.S. Provisional Patent Application Ser. No. 63/121,515, filed 4 Dec. 2020 and entitled “Autonomous Lawn Mower,” which is hereby incorporated herein in its entirety by reference.

BACKGROUND

(1) Autonomous systems rely on sensors for performing autonomy. Hybrid systems (e.g., those that allow manual, semi-autonomous, and autonomous control) may suffer from various constraints, limiting the functionality and/or safety of the system. For example, designs optimized for manual control may be made at the cost of sensor coverage and vice versa, thereby impacting the convenience of a manual operator or the ability for the system to detect and operate safely while operating autonomously. Further, such systems may not have adequate means for alerting a user proximate the device regarding the state of the system or to have adequate emergency stop capabilities to protect persons and property from inadvertent damage.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention will now be described, by way of example, with reference to the accompanying drawings, where like numerals denote like elements, a leftmost numeral indicates the original figure in which the element is found, and in which:
- (2) FIG. 1 is a front perspective view of an autonomous lawn mower in accordance with at least one example of the invention;
 - (3) FIG. 2 is a top view of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
 - (4) FIG. 3 is a side view of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
 - (5) FIG. 4 is a bottom view of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
 - (6) FIG. 5 is a rear view of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
 - (7) FIG. 6 is a front view of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;

- (8) FIG. 7 is a detailed top view of a sensor suite of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
- (9) FIG. 8 is a detailed side view of a sensor suite of the autonomous lawn mower of FIG. 1 in accordance with at least one example of the invention;
- (10) FIGS. 9A and 9B depict operation of an operator detector in accordance with at least one example of the invention;
- (11) FIG. 10 depicts a block diagram of an emergency control system for an autonomous lawn mower in accordance with at least one example of the invention;
- (12) FIG. 11 depicts a flow diagram of the operation of the emergency control system of FIG. 11 in accordance with at least one example of the invention;
- (13) FIG. 12 depicts an example flow diagram of processing packet data received from a remote device
- (14) FIG. 13 depicts an example alternative camera assembly;
- (15) FIG. 14 depicts a further example alternative camera assembly; and
- (16) FIGS. 15A-15E depict a sequence of events to remotely calibrate the cameras of an autonomous lawn mower in accordance with at least one example of the invention.

DETAILED DESCRIPTION

- (17) The following detailed description describes techniques (e.g., methods, processes, and systems) that may be used by a lawn mower capable of autonomously mowing grass. In those examples described in detail herein in which one or more autonomous mowers may be used for mowing. If a plurality of autonomous lawn mowers are used in the mowing process, their activity is choreographed such that the mowers work together to complete a mowing task. Each mower comprises a suite of sensors and displays to enable the mower to understand its environment as well as communicate to human operators, technicians, managers, customers, and bystanders.
- (18) Generally speaking, a mower fleet comprises a plurality of individual mowers, which may be combinations of autonomous, semi-autonomous, and/or manually controlled mowers. Depending on the size of the mowing job, one or more mowers are allocated to a given site. On a given job site, the mowing may be performed using a mix of some autonomous mowers, some semi-autonomous mowers (e.g., those mowers which may have some capabilities which are autonomous and/or which are capable of operating autonomously for at least a portion of the time) and some mowers being driven by humans (i.e., manual mowers). Each autonomous or semi-autonomous mower has a suite of sensors to primarily facilitate autonomous or semi-autonomous mowing. Such sensors may comprise, for example, one or more of cameras, radar, pose (position and/or orientation) systems (including Global Positioning System (GPS) receiver and or a Global Navigation Satellite System (GLONASS) receiver), diagnostic sensors, Inertial Measurement Units (IMUs) (which in turn may comprise accelerometers, gyroscopes, magnetometers, etc.), torque sensors, wheel rotation sensors (e.g., rotary encoders, Hall sensors, etc.) or the like. This suite of sensors provides a view of the environment in which the autonomous mower is operating such that the mower can explore the environment to identify obstacles and generate mow patterns.
- (19) In one example, the sensor suite is mounted atop a podium that serves to position the sensor suite high above the ground to provide the sensors an optimal view of the mower surroundings. The podium also forms a control center behind which an operator may stand on a platform and manually control the mower, when necessary. The manual mower controls are positioned atop the podium for easy access by an operator standing on a platform located behind the podium. In additional or alternate examples, such a podium may comprise one or more features to improve both the access by the operator as well as function of the sensors. As a non-limiting example of such, portions of such a podium may be inclined (or raked) to promote a restful position of a user while simultaneously optimizing a field of view of one or more sensors attached thereto. Further, one or more portions of such a podium may extend out over one or more of the sensors (without impinging on a field of view) to eliminate or reduce glare or other interferences. As such, designs

discussed in detail herein may improve the comfort of an operator while operating manually (or semi-autonomously) while optimizing sensor coverage and minimizing environmental impacts to sensor operation (whether in manual, semi-autonomous, or autonomous operation).

(20) In addition, the mower communicates with operators, technicians, managers, customers, and bystanders through a number of communications channels. WiFi and cellular communication channels are used to communicate to local operators and technicians as well as communicate with remote data collection and analysis servers such that technicians, managers and customers may be informed of the mower status and activity. Various personnel may access mower status via mobile and/or desktop applications which connect through wireless communications channels directly to the mower and/or via one or more servers.

(21) In one example, the mower itself may communicate to local personnel as well as bystanders via a visual communication channel. For example, the mower may comprise illuminating devices that change color and/or display graphics/text to indicate the status of the mower. In one particular example, the mower comprises an LED ribbon that circumscribes a portion of the mower such that the indicator ribbon is viewable from all positions surrounding the mower, i.e., a 360 degree indicator. As described below, the indicator displays various colors, text and/or graphics depending upon mower status.

(22) The techniques described herein may provide a technical solution to a technical problem of determining a situational environment in which an autonomous mower is operating or has operated to optimize the behavior of the mower and/or a related mower fleet as well as communicate mower status through various channels to mower operations personnel and/or bystanders. The techniques described herein may improve the functioning of a computer through function optimization, improved processing efficiencies, improved and optimized autonomous behavior of mower(s), improved communications, etc. Such techniques may further improve the safe operation of such a mower when used such that users and others proximate the device may instantaneously recognize a state of the device (e.g., acting autonomously, experiencing a fault, undergoing a loss of communication, update status, etc.) and react accordingly. It would be appreciated that the techniques described herein would be equally applicable to any other service robotics platform and/or fleets thereof such as, but not limited to, other agricultural tasks—harvesting, planting, etc., naval tasks (whether submarine, surface vessel or otherwise), and the like.

(23) FIG. 1 is front perspective schematic view of an autonomous lawn mower **100** in accordance with at least one example of the invention. FIGS. 2, 3, 4, 5, 6 are respectively top, side, bottom, rear and front views of the autonomous lawn mower **100** of FIG. 1 in accordance with at least one example of the invention. In an example of the autonomous mower **100**, the mower may be powered by electricity. In other examples (whether autonomous or otherwise), the mower may have another form of energy source, e.g., gasoline, diesel, natural gas, liquid propane, fuel cell, hydrogen, or the like. The mower has one or more drive mechanisms, e.g., motors, facilitating movement of the mower as well as rotating the cutting blades, where the drive mechanism is of a type commensurate with the energy source.

(24) As shown in FIGS. 1 through 6, the mower **100** may comprise a chassis **102**, front and rear wheels **104** and **106**, mower deck assembly **108**, and a mower body **110**. The mower deck assembly **108** comprises a mower deck **112** and a mower deck control mechanism **114**. The chassis **102** may support the mower body **110**, comprising a podium **116** and a hood **118**, which houses batteries, motors and control electronics (internal to the body **110**, thus not shown in FIGS. 1 through 6). In one example, the mower body **110** is isolated from chassis vibration by resilient members (e.g., rubber bushings, not shown) that couple the body components to the chassis **102**. Such a construction reduces vibration of the sensors that are attached to the body **110**, as described below. In addition, in an example, the podium **116** is modular and can be removed from the chassis through the removal of a limited number of fasteners, e.g., ten bolts.

(25) The mower deck control mechanism **114** couples the chassis **102** to the mower deck **112** may

comprises actuator(s) to raise and lower the mower deck **112** relative to the chassis **102** and ground as well as an actuator (e.g., motor(s) **120A**, **120B**, **120C**) to drive one or more blades (e.g., blades **400A**, **400B**, and **400C** in FIG. 4) within the mower deck **112**.

(26) In an example, each rear wheel **106** may be coupled to a drive mechanism, e.g., at least one motor (e.g., motors **402A** and **402B** in FIG. 4). For example, each wheel may be directly driven by a separate electric motor. In other examples, the drive mechanism may include a transmission and/or other form of gearing between the wheels and the motor(s). The front wheels **104** may be “free-wheeling” in that they are not driven nor are they steered. In such examples, the front wheels **104** comprise, for example, castors. Each wheel **104** may be coupled to the chassis **102** via a wheel mounting assembly **122A** and **122B** (e.g., a wheel mounting fork coupled to a spindle to form a castor). In this manner, steering of the mower is effectuated through applying differential rotation of the rear wheels **106**. Such differential rotation may be created through rotating each wheel at the same speed and braking one wheel relative to the other or rotating each wheel at a different speed through control of independent wheel drive motors. In other examples, the rear wheels may be driven at equal speeds and a steering assembly may be used to steer the front wheels.

(27) The podium **116** may comprise a front access panel **124** and side access panels **126** to facilitate access to an energy source (e.g., batteries or fuel tank) as well as drive mechanism(s), control electronics, communications electronics, sensor electronics or the like. The electronics and processes utilized to operate such an autonomous mower **100** are described in detail in U.S. patent application Ser. No. 16/985,495, filed 5 Aug. 2020 entitled “Autonomous Lawn Mower” (the ‘495 application) which is hereby incorporated herein by reference in its entirety.

(28) The exterior of the podium **116** supports various sensors including but not limited to forward viewing camera(s) **126**, rear viewing camera(s) **128**, side viewing camera(s) **130A** and **130B**, and various radomes **132A**, **132B**, **132C** and **132D** which cover various antennas and sensors. The sensor elements used by the autonomous mower **100** and described in detail in the ‘495 application may include one or more of cameras (whether stereo, RGB, monochromatic, infrared, ultraviolet, hyperspectral, etc.), radar(s), lidar(s), acoustic sensors, accelerometer(s), gyroscope(s), torque sensor(s), magnetometer(s), location system(s), battery management systems, wheel encoder(s), motor sensor(s), orientation sensor(s), and/or the like. These sensors may be located within the radomes **132A**, **132B**, **132C** and **132D** or located elsewhere on the mower **100**.

(29) The sensors gather information regarding the environment surrounding the autonomous lawn mower **100** such that the mower **100** is able to autonomously mow a region of lawn within a specified boundary as well as identify obstacles to be avoided, ignored, or cause the mower to cease operation and request human assistance.

(30) The mower **100** may also comprise an instrument panel **134** for enabling manual control of the mower **100**. The instrument panel **134** may be removable. A description of an embodiment of the instrument panel and its operation is contained in commonly assigned U.S. patent application Ser. No. 16/891,281, filed 3 Jun. 2020, entitled “Control Interface For Autonomy,” which is hereby incorporated herein by reference in its entirety.

(31) The podium **116** comprises four sidewalls **136A**, **136B**, **136C**, **136D** and a top portion **138**. The sidewalls **136B** and **136D** may contain identical access panels **126**. The front sidewall **136A** may contain the access panel **124**. The rear sidewall **136C** supports a resilient pad **140** (typically, a foam pad) upon which an operator may position their knees or thighs while standing upon the platform (**200** in FIG. 2) and manually driving the mower **100**. The podium **116** may comprise gaskets and o-rings to seal all removable panels and seal egress apertures such that the podium **116** is waterproof.

(32) As depicted in the side view of FIG. 3, in one example of the invention, the podium **116** is tilted or raked forward at a defined angle, α , to a horizontal plane. In one example, the angle α is in a range of about seventy to eighty-five degrees. In some examples, the angle may be different for the rear surface of the podium (e.g., about seventy-five degrees) compared to the front surface of

the podium (e.g., about eighty-five degrees). By raking the podium forward, the operator is more comfortably positioned behind pad **140**, the podium front sidewall **136A** is partially shaded by the remainder of the podium **116** and the angle of incidence of sunlight onto the front sidewall **136A** is reduced. Such shading and reduction in the sunlight angle of incidence provides a lower temperature region in which sensitive electronics and/or heat sinks for electronics may be positioned inside the front panel **124**. As such, any angle may be used that promotes comfort to the operator by raking the rear podium surface and/or provides shade for the electronics by raking the front podium surface. In one example, behind the front sidewall **136A** is positioned a heat sink (not shown) for the mower electronics. Such placement maximizes heat dissipation by placing the heat sink in a shaded region as well as places the heat sink where maximum heat dissipating air flow occurs. The hood **118** is also sloped downward from the podium **116** to the front wheels **104** to create aerodynamics that, as the mower **100** moves forward, drives air toward the front sidewall **136A** of the podium **116** to provide further cooling.

(33) In one example, the top portion **138** of the podium **116**, which supports many of the sensors that detect the environment surrounding the mower **100** and supports the communications antennas, is modular, i.e., the top portion **138** is removable from the podium **116**. The top portion **138** comprises a substantially planar plate **150** that supports a plurality of radomes, for example, radomes **132A**, **132B**, **132C**, **132D** that protect various sensors and antennas. The four sides **152** of the top portion **138** also support a plurality of cameras **126**, **128**, **130A** and **130B**. By placing the sensors at the highest point on the mower **100**, the sensors have an optimal view of the surrounding environment and the sky. In at least some examples, one or more portions of the podium may extend over one or more of the sensors (e.g., as illustrated in FIG. 1, the top portion **138** slightly extends over the one or more cameras **130**). In such examples, the extension may prevent stray light, glare, or otherwise from negatively impacting sensor data accumulation. Further, by being slightly inclined, such cameras **130** may be positioned and/or oriented so as to maximize a usable field of view (e.g., such that a majority of the data is used to control the system (proximate terrain, actual and potential obstacles, etc.)). In at least some examples, pairs of cameras **130** may comprise a stereo pair defined by a baseline (distance therebetween) that may be scan line rectified. In such examples, placement of the stereo pair in the podium may allow for wider baselines (and increased depth resolution). In addition, by placing the sensors and antennas at the top of the podium, they are positioned as far away as possible from the internally located motor control circuits. The motor control circuits may be electrically noisy and create electromagnetic signals that interfere with the sensors and communications signal processing, especially weak GPS and GNSS satellite signals. As such, the motor control circuits are mounted low in the podium near the rear wheels. In this position, there are many metallic components (e.g., metallic supports, batteries, and the like) within the podium between the motor control circuits to attenuate the internally generated electromagnetic noise.

(34) FIGS. 7 and 8 respectively depict a top and side views of the top portion **138** of the podium **116** in accordance with one example of invention. The substantially planar plate **150** of the top portion **138** supports the instrument panel **134** and the plurality of radomes **132A**, **132B**, **132C**, and **132D**. The radomes are designed of materials that are transparent to electromagnetic signals and form a protective cover for antennas and sensors that are positioned within the radomes.

(35) In one example, the radomes **132A** and **132D** may contain a plurality of antennas for communication transceivers and position location receivers. For example, each radome **132A** and **132D** may contain two WiFi antennas, two cellular telephone (e.g., LTE antennas) and one GPS antenna. The radomes **132A** and **132D** are spaced apart from one another to reduce interference from objects and mitigate multipath interference.

(36) In one example, the radome **132B** comprises a GNSS antenna and is mounted along a centerline of the mower at a front edge **700** of the podium top portion **138**. Such positioning provides an optimal view of the sky for GNSS functionality and provides spacing between the

operator (when one is onboard) and the GNSS antenna to reduce interference. In another example, the radome **132B** protects an antenna for GNSS receiver (both GPS and GLONASS), an antenna for a cellular communications transceiver (e.g., LTE) and an antenna for a WiFi transceiver. The antennas respectively operate in the 1575.2-1610 MHz band, 1710-2690 MHz band and 4900-5825 MHz band. One exemplary antenna combination is available as a MIMO Combo Outdoor IP67 3m Roof Antenna, Model JCE604LMWM, available from Teltonika.

(37) Positioned behind the radome **132B** and between the radomes **132A** and **132D** is a radome **132C** for a radio antenna. In one example, the radio antenna radome **132C** protects an antenna for a 900-950 MHz radio receiver. This receiver is used to receive a remote broadcast of an emergency stop signal and cause an immediate shutdown. Details of the emergency control system are described with reference to FIGS. **10**, **11** and **12** below.

(38) Mounted to the four sides **152** of the podium top portion **138** are a plurality of stereo cameras **126**, **128**, **130A** and **130B**. Each stereo camera **126**, **128**, **130A** and **130B** may comprise a pair of camera elements **800A** and **800B** mounted to each side **152** of the top portion **138**. In one example, the camera elements **800A** and **800B** are spaced apart by about 88.9 mm to facilitate adequate stereo imaging of the environment. In one example, each side and rear camera **128**, **130A** and **130B** has a 130 degree diagonal field of view angle, while the front camera **126** may have a narrower viewing angle, such as, a 100 degree field of view angle. The front camera **126** has a slightly narrower field of view to improve forward depth perception. With such a field of view from each camera, the cameras provide 360 degree imaging of the surrounding environment. To reduce image distortion, the field of view may be narrowed for each camera, but to maintain a 360 degree view of the surrounding area, the diagonal field of view should not be less than 90 degrees, e.g., 90 degree diagonal field of view may be used. In at least some examples, various combinations of cameras may be used (e.g., wide angle, narrow angle, fish-eye, etc.) to provide for various factors. For example, a wide-angle camera may be better suited for use in determining an obstacle proximate the system as opposed to a narrow field of view lens which may be preferred for determining objects further away. Of course, image data from any such camera may be undistorted, rectified, or otherwise manipulated to provide optimal data for sensing, planning, and control. Each camera element **800A** and **800B** comprises a bezel **802A** and **802B** that retains a lens **804A** and **804B**. Although a rectangular shaped bezel and lens is depicted, other shapes may be used. For example, the bezel and lens may be circular. A charge-coupled device (CCD) sensor (not shown) is mounted behind each lens **804A** and **804B**. In one example, the camera elements **800A** and **800B** have a 130 degree diagonal field of view and are available from D3 Manufacturing as Model 10650 (part number 1001149-27). In one example, the individual cameras in a camera pair are spaced apart by about 88.9 mm, though any spacing is contemplated for a desired depth resolution. As above, in at least some examples, such stereo pairs may be scan line rectified. Each bezel **802A** and **802B** is raked forward by about 20 degrees to provide shading to the CCD sensor and to enable the camera to optimally image the surrounding environment. Such an angle reduces glare on the CCD sensor. The bezzel may comprise an inner circumferential surface and may also include at least one ridge on the inner circumferential surface proximate the lens to reduce reflection. The lens is sealed to the bezzel and the bezzel is sealed to the podium to facilitate waterproofing.

(39) The top plate **150** overhangs, for example, the front and side cameras to provide shade to the cameras and reduce glare. In another example, the top plate **150** may also overhang the rear cameras as well.

(40) FIG. **13** depicts an alternative camera lens assembly **1300** showing a side view **1302**, a perspective view **1304** and an exploded view **1306**. The assembly **1300** comprises a bezzel **1308**, a first o ring **1310**, a lens **1312**, a second o ring **1314**, a baffle **1316** and a third o ring **1318**. The bezzel **1308**, first o ring **1310**, lens **1312**, second o ring **1314** are stacked in that order and screwed onto a threaded protrusion **1320** of the baffle **1316**. A portion of the baffle **1316** surrounding aperture **1324** may be ribbed, or otherwise shaped, to minimize stray light that is able to enter the

aperture from wide angles. An inside surface **1322** of at least a portion of the bezzle **1322** has threads that match the threads on the threaded portion **1320** of the baffle **1316**. The o rings **1310** and **1314** create a waterproof seal for the assembly **1300**. The baffle **1316** is mounted to the top portion of the podium using the o ring **1318** to form a waterproof seal. A camera sensor array (not shown) is mounted in the aperture **1324** behind the lens **1312**. In one example, the lens is formed of Gorilla Glass from Corning Incorporated and may include an antireflective coating. The camera sensor array may comprise a charge coupled device (CCD) array.

(41) In various examples, the lens **1312** may be planar and thin such that distortions are minimized when a commercially available camera is placed behind. In alternative examples, the lens **1312** may be formed as part of the total optical system of an imaging unit. In such examples, the lens may be warped to achieve the desired field of view (among other lens parameters). Regardless, various filters may also be used in any one or more examples. Such filters may be bandpass filters, or otherwise, to optimize for various bands of light impinging upon the final imaging surface.

(42) FIG. **14** depicts an alternative camera lens assembly **1400** where the lens is angled (raked) forward as described above with respect to the corresponding bezzles, such as bezzles **802A** and **802B** illustrated in FIG. **8**. FIG. **14** shows a side view **1402**, perspective view **1404**, and exploded view **1404**. The assembly **1400** comprises a bezzle **1408**, a first o ring **1410**, a lens **1412**, a second o ring **1414**, a baffle **1416** and a third o ring **1418**. The bezzle **1408**, first o ring **1410**, lens **1412**, second o ring **1414** are stacked in that order and screwed onto a threaded protrusion **1420** of the baffle **1416**. An inside surface **1422** of at least a portion of the bezzle **1408** has threads that match the threads on the threaded portion **1420** of the baffle **1416**. The side **1426** of the baffle is thicker at the top of then baffle than at the bottom of the baffle to cause the lens **1412** to point downward from a horizontal plane (i.e., is raked forward). The o rings **1410** and **1414** create a waterproof seal for the assembly **1400**. The baffle **1416** is mounted to the top portion of the podium using the o ring **1418** to form a waterproof seal. The camera array (not shown) is mounted in the aperture **1424** behind the lens **1412** to form a camera. In one example, the lens is formed of Gorilla Glass from Corning Incorporated and may include an antireflective coating. The bezzle **1408** may comprise an inner circumferential surface and may also include at least one ridge on the inner circumferential surface proximate the lens to reduce reflection. The camera array may comprise a CCD array. In various examples, lens shapes, distortions, coatings, filters, and additional lens elements may be used similar to those described with respect to FIG. **13**.

(43) In other examples, additional sensors and/or antennas may be included within the radomes or elsewhere on the top portion **138** or podium **116**. Such sensors include, for example, but not limited to one or more of additional cameras in any combination including stereo, RGB, monochromatic, infrared, ultraviolet, hyperspectral, etc., RADAR antennas, pose (position and/or orientation) systems, diagnostic sensors, Inertial Measurement Units (IMUs) (which in turn may comprise accelerometers, gyroscopes, magnetometers, etc.), LIDAR receptors, ultrasonic sensors, or the like.

(44) In one example, as mentioned previously the top portion **138** of the podium **116** shown in FIGS. **7** and **8** may be modular and may include a navigation system (e.g., GNSS and/or inertial) within the modular top portion **138**. The navigation system may be used to generate a reference location to which the images from the cameras are registered. The reference location may form a reference plane for each camera pair or a reference point for all camera pairs. With a modular top portion, calibration of the cameras may be performed anywhere (i.e., away from the mower location) thus simplifying calibration. As a non-limiting example, the entire top of the unit may be detached (or not yet attached) and calibrated by one or more calibration procedures (which may include moving the unit through a series of fiducials or otherwise determining the relative positions, orientations, and intrinsic parameters of the cameras with respect to one another). Once calibrated, the unit may be attached to any corresponding mower assembly to provide visual and/or visual-inertial tracking.

(45) FIGS. **15A-15E** depict a sequence of events to remove the top portion **138** (also referred to as

the upper portion) of podium **116**, calibrate the cameras, and, post calibration, replace the top portion **138** upon the podium **116** in accordance with at least one example of the invention. FIG. **15A** depicts the podium portion of the mower having a modular top portion **138**. The top portion **138** comprises the cameras **126**, **128**, **130A** and **130B** mounted to the top portion **138** and a navigation system **1500** (shown as dashed) within the top portion **138**. FIG. **15B** depicts the top portion **138** being removed from a lower portion **1502** of the podium **116**. The top portion **138** may be removably retained upon the lower portion using fasteners such as bolts, clips, straps, and the like. Such joining assembly may, in some examples, further comprise gaskets or otherwise to ensure the full assembly (top portion **138** and lower mower unit) is waterproof and/or otherwise rigid with respect to the elements. FIG. **15C** depicts a top view of the top portion **138** being calibrated such that the navigation system **1500** is used to define a reference point, points, plane or planes (e.g., reference point **1504**) for the cameras **126**, **128**, **130A** and **130B**. As described with reference to FIGS. **7** and **8** above, a stereo camera is mounted to each of the four sides of the top portion **138**, though any combination of cameras, lidars, radars, inertial measurement units (IMUs—which include accelerometers, gyroscopes, magnetometers), and GNSS receivers is contemplated. The calibration may be performed anywhere, e.g., away from the mower. FIG. **15D** depicts the top portion being replaced upon the lower portion **1502** of the podium **116**. FIG. **15E** depicts the reassembled podium **116** comprising the lower portion **1502** and the top portion **138**, where the top portion **138** comprises the calibrated cameras **126**, **128**, **130A** and **130B**.

(46) The top portion **138** may contain one or more mower processors and memory (as shown as **1032** and **1034** in FIG. **10**). The memory may store mower control software and calibration software (**1044** and **1046** in FIG. **10**) containing instructions that, when executed by the one or more processors, cause the processor to perform certain operations. Execution of the calibration software causes the processor to calibrate the cameras by determining relative positions and orientations between the plurality of cameras, the inertial measurement unit, and the GNSS receiver, determining intrinsic parameters of the plurality of cameras, and generating a signal indicative of the calibration. This software may be executed while the top portion **138** is not attached to the lower portion **1502** of the podium **116**. In additional or alternate examples, the top portion **138** may be calibrated by a separate system containing additional processors and/or memory. Such calibration may comprise receiving data from the one or more sensors associated with the top portion **138** and generating a calibration file (or other data structure). Such calibration file and/or calibration data may be subsequently transmitted to the relevant processors and/or memory associated with another portion of the mower.

(47) Once the calibrated top portion **138** is positioned on the lower portion **1502**, the one or more mower processors (which may be distributed across one or more of the top portion **138** and/or lower portion **1502**) may execute the mower control software to control the mower motion and mowing operation. In one example, upon coupling the top portion **138** to the lower portion **1502** of the podium **116**, execution of the mower control software causes the mower processor to: receive, upon coupling the upper portion to the lower portion, the signal indicative of calibration; receive sensor data from the plurality of cameras, GNSS, and inertial measurement unit; and control the autonomous lawn mower based at least in part on the sensor data and the signal. A detailed description of the mower control software is described in U.S. patent application Ser. No. 16/985,495, filed 5 Aug. 2020 entitled “Autonomous Lawn Mower” and U.S. patent application Ser. No. 16/894,379, filed 5 Jun. 2020 entitled “Autonomous Lawn Mowing System” which are hereby incorporated herein by reference in their entireties.

(48) In one example, at least one ultrasonic sensor **152** may be used to generate a fail-safe signal. In one example, the ultrasonic sensor is mounted near the front of the mower, e.g., on the front of the hood **118**. In other examples, the sensor **152** or sensors may be mounted elsewhere such as on the podium **116**. The ultrasonic sensor monitors the space in front of the mower such that the sensor may detect objects or persons that are missed by the video imaging system or operates as a backup

to the video system in case of a camera failure. If the ultrasonic sensor detects an object or person proximate the mower, the sensor generates the fail-safe signal that may be used to command the mower to halt and await operator intervention. Of course, in other examples, such a sensor may be used in combination with the cameras (or any other sensor) in any algorithm which relies on sensor fusion. As non-limiting examples, ultrasonic sensor data may be combined with one or more of camera data, radar data, lidar data, etc. to reduce an amount of uncertainty in detections within the environment.

(49) In another example, a physical pressure sensor may replace the ultrasonic sensor or be used in conjunction with the ultrasonic sensor. The pressure sensor, when encountering an object, causes an emergency stop (as described below) procedure to be activated.

(50) In one example, the top portion **138** of the podium **116** provides a means to communicate mower status information to people viewing the mower **100**. For example, one or more illuminating devices **806** may be attached to the mower **100** and illuminated in colors or patterns to indicate mower status. In one example, the illuminating device **806** is a light emitting diode (LED) ribbon that circumscribes the entire podium **116** to provide a 360 degree indicator.

(51) The LED ribbon may present one or more of various colors, graphics, text, and the like to indicate mower status. For example, the ribbon may display different colors for differing status, e.g., operating status such as display green when the mower is operating normally, red when the mower has stopped, and flash yellow as a warning to bystanders that may form an obstacle to the mower. In addition, a specific color, color combination, animation, or other graphic may be displayed to indicate when the mower is charging, e.g., a striped color display, or has discharged to a level that requires a charge. The LED ribbon may also be used to indicate error status (e.g., of the entire unit, a component, a subcomponent, etc.), operating status such as autonomous state or manual state, functional status such as uploading data or software, etc. In other examples, the LED ribbon may comprise an array of LEDs, where each LED may be illuminated separately to facilitate display of graphical icons, text, patterns, animation and the like. Such a display may be used for communicating diagnostic information to operators or technicians, e.g., a text display of "CHARGE REQUIRED," as well as communicating warnings to bystanders, e.g., a text display of "PLEASE STAND BACK." One example of an LED ribbon and drive circuitry is a 2 meter length of ribbon comprising 288 LEDs available from BTF-Lighting. In an example, the drive integrated circuit for the LED ribbon is model SK9822 also available from BTF-Lighting. In various examples, such visual communications may be displayed around the entirety of the system such that any user proximate the device may be able to quickly glean the system state to enhance the safe operation of the system. Also, the LED ribbon may have the graphics segmented such that different colors, text, or graphics may be displayed on different sides of the mower such that the display is directional. Thus, the mower may display an indicator intended to be seen by a person standing at a particular location relative to the mower on a portion of the ribbon facing the person. Further, the mower may utilize dynamic obstacle notification wherein, if the mower detects a person in a particular direction (e.g., 20 degrees off center), a certain color (e.g., red) or graphic may be displayed in that direction. As such, when the mower detects certain objects (e.g., people, animals, and the like) in the environment proximate the mower, specific messages, graphics, colors and the like can be directed in the direction of the object to warn or chase away the object.

(52) At times, the autonomous lawn mower is driven by an operator. The presence of an operator is detected when the operator stands on the operator platform **200** in FIG. 2. FIGS. 9A and 9B depict operation of an operator detector **950** in accordance with at least one example of the invention. As depicted in FIGS. 9A and 9B, the operator platform **200**, without an operator, is positioned in a first position (the operatorless position **900**) and is held in the operatorless position by at least one biased hinge **904**, e.g., one or more springs within a hinge to form a spring loaded hinge. In position **900**, the platform **200** is not proximate an inductive proximity sensor **906** that is located at the side of the platform **200**. In FIG. 9B, the operator **908** stands upon the platform **200** causing the

platform to pivot downward to a second position (the operator position **910**). When in the operator position **910**, the platform is proximate the inductive proximity sensor **906** causing a characteristic of the sensor **906** to change, e.g., the impedance of the sensor changes. In other embodiments, the platform may move vertically when the operator stands on the platform. The detection circuit **912** detects the characteristic change and places the mower in manual control mode. Other forms of sensors may be used in combination with or as a substitute for the inductive proximity sensor, e.g., hall-effect sensors, optical sensors, pressure sensors, and the like. In one example, the sensor(s) is weather resistant (e.g., a sealed enclosure without any moving parts) and does not contact the platform.

(53) In the example where the sensor is an inductive proximity sensor, the platform is generally metallic or has a metallic component that is located proximate the sensor **906** when an operator is present. Conversely, when the operator **908** steps off the platform **200**, the biased hinge **904** moves the platform away from the sensor **906** causing the detection circuit **912** to detect that the operator has departed and then stop the mower. When stopped, the mower may automatically apply the brakes. In this way, the operator detector **950** operates as a “dead man's switch.”

(54) In an example, when an operator steps upon the platform **200**, the detection circuit **912** may also deactivate at least one camera (e.g., the rear facing camera **128**). Since the operator will be blocking the view of the rear facing camera **128** while operating the mower, imagery from that camera is not useful and computational resources can be minimized (e.g., processors, memory, storage, etc.). As an alternative to deactivating the camera, the one or more mower processors that process the camera data may disregard the camera data from the rear facing camera **128**.

(55) FIG. **10** depicts a block diagram of an emergency control system **1000** in accordance with at least one example of the invention. Any block, step, module, or otherwise described below may represent one or more instructions which can be stored on a non-transitory computer readable media as software and/or performed by hardware. Any such block, module, step, or otherwise can be performed by various software and/or hardware combinations in a manner which may be automated, including the use of specialized hardware designed to achieve such a purpose. As above, any number of blocks, steps, or modules may be performed in any order or not at all, including substantially simultaneously, i.e., within tolerances of the systems executing the block, step, or module. Of course, such blocks are presented for illustration purposes only and any one or more block, step, or module may be combined with any other, removed, split, or moved between the various systems and subsystems illustrated.

(56) The emergency control system **1000** enables an operator to control one or more mowers. Control is facilitated using a remote controller **1002** that transmits information to one or more mowers to cause the mower(s) to pause or stop. When paused, the mower comes to a controlled stop that will not harm any of the components of the mower. When stopped in an emergency manner, the mower is immediately halted, the blades may be stopped and power may be disconnected from the electronics without regard for possible damage or data loss that may occur. As described below, the procedure used to stop the mower depends upon the situation causing the stop.

(57) In one example, the system **1000** may comprise two portions: (1) a remote controller **1002** and (2) a mower controller **1004**. The remote controller **1002** continuously transmits packets of data to the mower controller **1004** as a “heartbeat” signal, i.e., packets are transmitted periodically. If the heartbeat signal (i.e., packet reception) is interrupted, delayed, or corrupted, the mower controller **1004** causes the mower to invoke an emergency stop procedure as described with reference to FIG. **12** below. In addition, an operator may use the remote controller **1002** to send specific pause or emergency stop signals to the mower controller **1004** to cause the mower invoke a pause procedure or an emergency stop procedure. The remote controller **1002** may comprise two buttons—one for pause control and one for emergency stop. The pause control button may be depressed and the pause procedure is used for the duration that the button is depressed. Contrastingly, depressing the

emergency button immediately invokes the emergency stop procedure that requires an operator to restart the mower after the emergency is rectified. Of course, any other methods may be provided. As non-limiting examples, a pause may be initiated by a rocker switch, a toggle switch, a press/press interaction, or otherwise such that a user may alternate quickly between an idle state of the mower and autonomous operation. Similarly, the emergency stop may comprise different forms to ensure that once depressed, the mower may not unintentionally restart. In various examples, one or more mechanisms may be used to ensure the operator does not inadvertently hit the emergency stop or pause when the other is desired, and vice versa. In some such examples, different forms of switches may be used that may have different sizes, colorations, notification, or otherwise to emphasize a difference between the two.

(58) Additionally, the mower itself may include an emergency stop button located in a prominent (e.g., button **702** of FIG. 7), easy to access location on the mower. When the emergency stop button is depressed, the mower immediately performs an emergency stop procedure as described in detail below. The mower may stop or pause in response to a number of safety state inputs from operators and/or sensors. The various safety state inputs may include, but are not limited to, detection of a human in the path of or near the mower, detection of a dynamic obstacle (e.g., animals, pets, moving bicycle, etc.), detection of a static obstacle, motor overload or struggling, battery charge state abnormalities, maximum slope allowance is reached, an operator is riding the mower, safety sensors enter a fault state or become unreliable, temperature of the mower reaches a limit, navigation/locomotion data (e.g., GNSS or vision data) reaches a maximum error state or becomes unreliable, blade motors reach a maximum resistance (e.g., blade encounters a tree stump), emergency stop inputs, mobile or web application inputs, tele-op state, tipover protection (e.g., mower senses the mower is at an angle that may cause a tipover condition) and the like.

(59) The remote controller **1002** comprises various data sources **1006**, a packet generator **1016**, a modulator **1020**, a transmitter **1022** and an antenna **1024**. The data **1006** is derived from various sources and comprises a pause button state **1008** generated by the pause button, an emergency button state **1010** generated by an emergency button, a battery state **1012** generated by a battery charge monitor, a group ID **1014** stored in memory, and a sequence number **1016** generated by a sequence number generator. If neither the pause or emergency buttons are depressed, the packet generator periodically produces a packet. In one example, a packet is generated about every 250 ms. In one example, the payload in a packet may be approximately 40 bits comprising, for example, pause button state, emergency stop button state, group ID, a sequence number, and a battery state. The button status expresses whether a button is depressed or not, the group ID identifies a group in which a particular mower is a member, the battery status states whether the battery in the remote controller requires charging, and the sequence number is used by the mower controller **1004** to determine if a packet is dropped during transmission e.g., each packet is sequentially numbered for tracking purposes.

(60) The packet generator **1016** sends the packet to the modulator **1020** and the modulated packet is sent to the transmitter **1022** for transmission via the antenna **1024** to the mower controller **1004**. In those examples in which a 40 bit packet is used, the bandwidth utilized is about 500 kHz, though any other bandwidth is contemplated. As mentioned above, the remote controller sends a packet, for example, about every 250 ms. Other transmission rates, packet sizes and bandwidths may be used. Between packet transmissions the controller **1002** may enter a sleep mode to conserve battery power. If either the pause or emergency buttons are depressed during the sleep mode, the controller **1002** immediately awakes and sends a packet containing the current button state. To enhance security, the packet generator **1016** or modulator **1020** may use encryption and/or frequency hopping techniques. The transmitter **1022** transmits the packet in, for example, the 900 to 950 MHz band using antenna **1024**. The specific frequency used may be selected to communicate with a specific mower. Antenna **1024** may be a dipole antenna. The transmission is generally capable of being received up to approximately 300 meters away from the remote controller **1002** using a line-

of-sight transmission path. The transmission distance depends on transmission interference, transmission power level, antenna type, and the like.

(61) The mower controller **1004** for the emergency control system **1000** comprises an antenna **1026**, a receiver **1028**, and a signal processor **1030**. The antenna **1026** receives the signal transmitted by the remote controller **1002** and couples the signal to the receiver **1028**. The receiver **1028** processes the received signal to remove data packets from the signal. The data packets are coupled to the signal processor **1030** where they are processed to remove the data. The signal processor **1030** check the sequence number to ensure no packets have been dropped and, if packets are dropped, how many have been dropped. If 3 seconds worth of packets (e.g., about 12 packets) are missing, the signal processor **1030** deems the heartbeat signal to have ceased and will generate an emergency stop command. In addition, the signal processor **1030** checks the group ID to ensure the received packet is meant to be received by the particular mower that has received the packet. The group ID may be assigned to a single mower for one-to-one emergency control or may be assigned to a number of mowers in a fleet for one-to-many emergency control. Also, if the signal processor **1030** detects a pause or emergency stop state in the data packet, the signal processor **1030** generates an appropriate command. Lastly, the signal processor **1030** checks the battery state to determine if the battery in the remote controller **1002** requires charge. If a low charge state is detected, the signal processor **1030** generates a low battery command.

(62) The signal processor **1030** is coupled to at least one mower processor **1032** and at least one safety controller **1038**. The mower processor and its general function is described in detail in U.S. patent application Ser. No. 16/985,495, filed 5 Aug. 2020 entitled "Autonomous Lawn Mower" (the '495 application) which is hereby incorporated herein by reference in its entirety. As described in the '495 application, the at least one mower processor **1032** is coupled to a memory **1034** (e.g., non-transitory computer readable media such as random access memory or read only memory) that stores various software and data that is used by the mower processor to operate the mower. In one example, the memory **1034** may further store emergency control system software **1036** that, when executed by the at least one mower processor, performs emergency and pause control functions as described below with respect to FIG. 12. The memory **1034** may also store mower control software **1044** and calibration software **1046**, which operate as described above with respect to FIGS. 15A-15E.

(63) In one example, the signal processor **1030** is separate from the mower processor **1032**. In other examples, the functionality of the signal processor **1030** described above may be completely or partially performed by the mower processor **1032**.

(64) The safety controller **1038** is a simple controller that performs immediate emergency stop functions when a stop request occurs from the emergency stop button on the mower or on the remote controller **1002**. In an emergency stop situation, the safety controller **1038** generates emergency control signals that override any control signals being produced by the mower processor **1032**. As described herein, such an emergency stop may comprise any one or more of immediately stopping motion of the mower and immediately stopping the blades of the mower. For other situations (non-emergency) where the mower pauses (i.e., obstacle avoidance), the mower processor performs a controlled stop of the mower. Such a controlled stop may comprise causing the mower to quickly (i.e., less than a full amount of stopping power) stop motion of the mower while allowing the blades to freely spin without applying additional torque. Such a stopping maneuver may preserve energy with respect to the emergency stop, as well as prevent damage to one or more systems of the mower by the large decelerations involved.

(65) In an alternative embodiment, the transmitter **1022** and receiver **1028** may be transceivers such that information may be sent bidirectionally between the remote controller **1002** and mower controller **1030** (a solid arrow **1042** indicates a transmission path from remote controller **1002** to mower controller **1004** and dashed arrow **1040** indicates an optional transmission path from the mower controller **1004** to the remote controller **1002**. In this bidirectional configuration, the remote

controller **1002** may contain at least one processor **1050** for generating data for transmission and processing received data. As such, mower information (e.g., status) may be transmitted from the mower to the remote controller **1002** for display to the operator. The mower controller **1004** may transmit, for example, but not limited to, mower status (e.g., mowing, stopped, etc.), motor status (e.g., motor overload), terrain information (e.g., ground slope is too great to be traversed), battery charge status, unauthorized user has interfered with the mower or attempted to operate the mower, obstacle reporting, error messages, and the like.

(66) In another embodiment, a single remote controller **1002** may communicate with multiple mower controllers **1004** located on a plurality of mowers. As such, a single operator could control and/or monitor a plurality of mowers.

(67) FIG. **11** depicts a flow diagram of a method **1100** of operation of the emergency control system **1000** of FIG. **10** in accordance with at least one example of the invention. The method **1100** is divided into portion **1102** performed by the remote controller **1002** and portion **1104** performed by the mower controller **1004**. The method **1100** begins at **1106** and proceeds to **1108** where the data packets are generated. As above, such packets may comprise, for example, a timestamp, a group ID, a user ID, an amount or state of charge of the remote, or any other signal or data representative of a particular remote associated with the mower. At **1110**, the packets are transmitted to the mower controller **1004**.

(68) At **1112**, the packets are received by the mower controller **1004**. At **1114**, the method **1100** extracts the group ID from the received packet. If the group ID is correct for the particular mower, the packet is further processed and counts toward fulfilling the heartbeat signal. At **1116**, the method **1100** queries if the “heartbeat signal” has been received, i.e., for example, a plurality of packets with the correct group ID have not been received in a predefined period (e.g., 3 seconds). If a packet arrives at any time during the predefined period, the period is restarted. If packets do not arrive in the designated period (i.e., the heartbeat has been lost), the method **1100** proceeds to **1118** and generates an emergency stop command. If, however, the heartbeat is not lost, the method **1100** proceeds to **1120** to extract other data from the packet. Of course, any other data checks may be implemented including, for example, cyclic redundancy checks (CRCs), bit flip checks, and any other form to determine that the packet data is correct (e.g., from the correct device) or otherwise not corrupted.

(69) At **1120**, the packet is further processed to extract the battery state, the pause state and the emergency stop state. If the battery state indicates the battery charge is low, the method **1100** generates, at **1122**, a battery low command. In various examples, such a battery low command may comprise placing the mower in a pause state, stop state, or emergency stop state as a safety system (e.g., the user's ability to induce an emergency stop) may be imminently impacted. If the pause state indicates the pause button has been depressed on the remote controller **1002**, the method **1100** generates, at **1124**, a pause command. If the emergency stop state indicates the emergency stop button has been depressed on the remote controller **1002**, the method **1100** generates, at **1118**, an emergency stop command. If all states are normal (e.g., no buttons depressed and the battery charge above a low level), the method **1100** proceeds to **1112** to receive and process the next packet. Similarly, once the states are processed and commands generated, the method **1100** proceeds to **1112** to receive and process the next packet.

(70) FIG. **12** depicts a flow diagram of a method **1200** used when the emergency control system software (**1036** in FIG. **10**) is executed by the mower processor in accordance with at least one example of the invention. The method **1200** may operate as an interrupt routine that is only executed upon receiving a command from the mower controller **1004** or a command from another process executing on the mower processor (e.g., the navigation process detects an obstacle that requires the mower to stop). Once a command is received, the method **1200** begins at **1202** and proceeds to **1204** where the method **1200** processes the command. If the command is a pause command, the method **1200** proceeds to **1206** where a pause procedure is invoked. The pause

procedure may comprise one or more of the steps in the following exemplary procedures:

(71) Stop for Dynamic Obstacle:

(72) 1) A dynamic obstacle (an obstacle that is moving such as a person or pet) is detected by the navigation process and a pause command is received by the mower controller 2) All mower autonomy is paused 3) Mower blade controller is instructed to stop the blades as fast as possible 4) Wheel motor controllers are instructed to stop the drive motors as fast as possible 5) The mower processor instructs the safety controller to engage the brakes when the wheels are near zero velocity 6) Wheel drive motors are idled 7) Blade motors are idled when they reach zero velocity 8) The mower processor detects when the blades have stopped and idles the motors 9) The host updates a WebUI to signal that the mower is stopped for an obstacle 10) Autonomous control is automatically resumed once the obstacle clears unless the user intervenes before autonomous control resumes

Stop Because an Operator Manually Paused Autonomy: 1) An operator selects the pause button either on the remote controller or via a mobile application and a pause command is received by the mower controller 2) All mower autonomy is paused 3) Mower blade controller is instructed to stop the blades as fast as possible 4) Wheel motor controllers are instructed to stop at a reasonable negative acceleration rate 5) The mower processor instructs the safety controller to engage the brakes when the wheels are near zero velocity 6) Wheel drive motors are idled 7) Blade motors are idled when they reach zero velocity 8) The mower processor detects when the blades have stopped and idles the motors 9) The host updates the WebUI to signal that autonomy is paused

Stop for Auto Detected Error: 1) An error is detected by the mower processor 2) All mower autonomy is paused 3) Mower blade controller is instructed to stop the blades as fast as possible 4) Wheel motor controllers are instructed to stop as fast as possible 5) The mower processor instructs the safety controller to engage the brakes when the wheels are near zero velocity 6) Wheel drive motors are idled 7) Blade motors are idled when they reach zero velocity 8) The mower processor detects when the blades have stopped and idles the motors 9) The host updates the WebUI to signal that autonomy is stopped because of an error 10) Autonomy is automatically resumed once the error clears unless an operator intervenes before operation resumes

(73) From **1206**, the method ends at **1212**.

(74) If the command is an emergency stop command, the method **1200** proceeds to **1208** where an emergency stop procedure is invoked. The emergency stop procedure immediately stops the mower. The manner in which the mower is stopped in an emergency depends on the emergency situation. The emergency stop (also referred to as an e-stop) procedure may comprise one or more of the steps in the following exemplary procedures:

(75) Category 0 E-Stop:

(76) 1) Stop command received by the safety controller from emergency stop button on the mower 2) Cat0 E-Stop is triggered 3) Safety controller alerts the mower processor 4) Safety controller instructs a power control contactor to open and disconnect power from all wheel drive and blade motors 5) Mower Blades begin to spin down 6) Drive motors begin to spin down 7) Wheel drive motor brakes are engaged 8) Navigation autonomy (if running) is paused 9) The mower processor updates the WebUI to signal an emergency stop has occurred

Category 0 E-Stop (Alternative): 1) Stop command received by the safety controller from emergency stop button on the mower 2) Cat0 E-Stop is triggered 3) Safety controller alerts the mower processor 4) Safety controller interrupts mower operation and overrides all motor commands coming from the mower processor and instructs all motors to spin to zero velocity as fast as possible 5) Drive wheel brakes are engaged when the wheels are spinning at close to zero velocity 6) Safety controller verifies that blades have stopped spinning 7) All motors idled 8) Safety controller instructs the power control contactor to open and cut power to all mower drive and blade systems 9) Navigation autonomy (if running) is paused 10) The mower processor updates the WebUI to signal an E-stop occurred 11) If 3) through 10) do not occur within 2 seconds, open

the power control contactor

Category 1 E-Stop: 1) Stop command received by the safety controller from remote controller E-stop button 2) Cat1 E-Stop is triggered 3) Safety controller alerts the mower processor 4) Safety controller instructs the power control contactor to open 2 seconds after this point 5) Navigation autonomy (if running) is paused 6) The mower processor instructs the wheel drive motors to stop as fast as possible 7) The mower processor instructs the blade motors to stop as fast as possible 8) The mower processor detects when the wheels are near zero velocity, engages the brakes, and idles the wheel drive motors 9) The mower processor detects when the blade motors have stopped and idles the motors 10) If 5) through 9) were accomplished within 2 seconds, the power control contactor opens at this point

(77) From **1208**, the method ends at **1212**.

(78) If the command is a battery low command, the method **1200** proceeds to **1208** where the battery state is communicated to an operator or manager to inform them that the mower controller battery requires charging. Such communication may occur, for example, through the LED ribbon described with reference to FIG. **8**, a text or email message sent from the mower, or any other mode of communication available to the mower. If the battery completely discharges, the heartbeat signal will be lost and an emergency stop will occur. As such, it is important to maintain the battery charge on the mower controller. Consequently, to avoid an emergency stop, upon receiving a low battery command, the mower may enter a pause state.

Example Clauses

(79) A. An autonomous lawn mower comprising: a chassis; a body, supported upon the chassis, comprising a podium raked forward and having a hood; and at least one stereo camera defined by a baseline and positioned proximate a top of the podium. B. The autonomous lawn mower of clause A, wherein an angle of the rake is in a range of about 70 to 85 degrees with respect to a horizontal plane, and wherein the autonomous lawn mower further comprises a resilient pad mounted to a rear sidewall of the podium. C. The autonomous lawn mower of clauses A or B, further comprises a plurality of antennas, and wherein the stereo cameras and plurality of antennas are positioned to reduce interference from at least one of signal multipath, an operator, or internally generated electromagnetic noise. D. The autonomous lawn mower of clauses A through C, wherein the podium further comprises a light emitting portion for communicating at least one of color, text or graphics to indicate a status of the autonomous lawn mower. E. The autonomous lawn mower of clauses A through D, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status. F. The autonomous lawn mower of clauses A through E, further comprising an operator detector comprising an operator platform, the operator detector being moveable from a first position to a second position, and an operator sensor adapted to sense when the operator platform moves from the first position to the second position and causes at least one of the at least one stereo camera to be deactivated when the operator platform is in the second position. G. The autonomous lawn mower of clauses A through F, further comprising a hood positioned in front of the raked front sidewall of the podium and sloped downward to cause air to flow toward the front sidewall when the autonomous lawn mower is moving forward. H. The autonomous lawn mower of clauses A through G, wherein the at least one stereo camera further comprises a bezel surrounding a lens. I. The autonomous lawn mower of clauses A through H, wherein the bezel further comprises an inner circumferential surface and at least one ridge located on the inner circumferential surface proximate the lens. J. The autonomous mower of clauses A through I, wherein the bezel and lens are raked forward. K. The autonomous lawn mower of clauses A through J, further comprising at least one ultrasonic sensor for generating a fail-safe signal upon an object being proximate to the lawn mower, where generation of the fail-safe signal causes the lawn mower to be halted. L. The autonomous lawn mower of clauses A through K, further comprises a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower. M. The autonomous lawn mower of clauses A

through L, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics. N. The autonomous lawn mower of clauses A through M, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status. O. The autonomous lawn mower of clauses A through N, wherein the LED ribbon displays differing messages at locations on the LED ribbon in response to objects detected in an environment proximate the autonomous lawn mower. P. An autonomous lawn mower comprising: a chassis; a body, supported upon the chassis, comprising a podium; and a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower. Q. The autonomous lawn mower of clause P, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics. R. The autonomous lawn mower of clauses P or Q, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status. S. A system comprising: a chassis; a body, supported upon the chassis, comprising a podium; a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower; and at least one camera mounted proximate a top of the podium. T. The autonomous lawn mower of clause S, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics, and the at least one camera is a stereo camera.

CONCLUSION

(80) Here multiple examples have been given to illustrate various features and are not intended to be so limiting. Any one or more of the features may not be limited to the particular examples presented herein, regardless of any order, combination, or connections described. In fact, it should be understood that any combination of the features and/or elements described by way of example above are contemplated, including any variation or modification which is not enumerated, but capable of achieving the same. Unless otherwise stated, any one or more of the features may be combined in any order.

(81) As above, figures are presented herein for illustrative purposes and are not meant to impose any structural limitations, unless otherwise specified. Various modifications to any of the structures shown in the figures are contemplated to be within the scope of the invention presented herein. The invention is not intended to be limited to any scope of claim language.

(82) Where “coupling” or “connection” is used, unless otherwise specified, no limitation is implied that the coupling or connection be restricted to a physical coupling or connection and, instead, should be read to include communicative couplings, including wireless transmissions and protocols.

(83) Any block, step, module, or otherwise described herein may represent one or more instructions which can be stored on a non-transitory computer readable media as software and/or performed by hardware. Any such block, module, step, or otherwise can be performed by various software and/or hardware combinations in a manner which may be automated, including the use of specialized hardware designed to achieve such a purpose. As above, any number of blocks, steps, or modules may be performed in any order or not at all, including substantially simultaneously, i.e. within tolerances of the systems executing the block, step, or module.

(84) Where conditional language is used, including, but not limited to, “can,” “could,” “may” or “might,” it should be understood that the associated features or elements are not required. As such, where conditional language is used, the elements and/or features should be understood as being optionally present in at least some examples, and not necessarily conditioned upon anything, unless otherwise specified.

(85) Where lists are enumerated in the alternative or conjunctive (e.g. one or more of A, B, and/or C), unless stated otherwise, it is understood to include one or more of each element, including any one or more combinations of any number of the enumerated elements (e.g. A, AB, AC, ABC, ABB,

etc.). When “and/or” is used, it should be understood that the elements may be joined in the alternative or conjunctive.

Claims

1. An autonomous lawn mower comprising: a chassis; a body, supported upon the chassis, comprising a podium raked forward and having a hood; at least one stereo camera defined by a baseline and positioned proximate a top of the podium; and an operator detector comprising an operator platform, the operator detector being moveable from a first position to a second position, and an operator sensor adapted to sense when the operator platform moves from the first position to the second position and causes at least one of the at least one stereo camera to be deactivated when the operator platform is in the second position.
2. The autonomous lawn mower of claim 1, wherein an angle of the rake is in a range of about 70 to 85 degrees with respect to a horizontal plane, and wherein the autonomous lawn mower further comprises a resilient pad mounted to a rear sidewall of the podium.
3. The autonomous lawn mower of claim 1, further comprises a plurality of antennas, and wherein the stereo cameras and plurality of antennas are positioned to reduce interference from at least one of signal multipath, an operator, or internally generated electromagnetic noise.
4. The autonomous lawn mower of claim 1, wherein the podium further comprises a light emitting portion for communicating at least one of color, text or graphics to indicate a status of the autonomous lawn mower.
5. The autonomous lawn mower of claim 4, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status.
6. The autonomous lawn mower of claim 1, further comprising a hood positioned in front of the raked front sidewall of the podium and sloped downward to cause air to flow toward the front sidewall when the autonomous lawn mower is moving forward.
7. The autonomous lawn mower of claim 1, wherein the at least one stereo camera further comprises a bezel surrounding a lens.
8. The autonomous lawn mower of claim 7, wherein the bezel further comprises an inner circumferential surface and at least one ridge located on the inner circumferential surface proximate the lens.
9. The autonomous mower of claim 7 wherein the bezel and lens are raked forward.
10. The autonomous lawn mower of claim 1, further comprising at least one ultrasonic sensor for generating a fail-safe signal upon an object being proximate to the lawn mower, where generation of the fail-safe signal causes the lawn mower to be halted.
11. The autonomous lawn mower of claim 1, further comprises a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower.
12. The autonomous lawn mower of claim 11, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics.
13. The autonomous lawn mower of claim 11, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status.
14. The autonomous lawn mower of claim 11 wherein the LED ribbon displays differing messages at locations on the LED ribbon in response to objects detected in an environment proximate the autonomous lawn mower.
15. An autonomous lawn mower comprising: a chassis; a body, supported upon the chassis, comprising a podium; a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower; at least one stereo camera mounted on the podium; and an operator detector comprising an operator platform, the operator detector being moveable from a first position to a second position, and an operator sensor adapted to sense when

the operator platform moves from the first position to the second position and causes at least one of the at least one stereo camera to be deactivated when the operator platform is in the second position.

16. The autonomous lawn mower of claim 15, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics.

17. The autonomous lawn mower of claim 16, wherein the status comprises at least one of operating status, functional status, error status, communication status, update status, or charge status.

18. A system comprising: a chassis; a body, supported upon the chassis, comprising a podium; a light emitting diode (LED) ribbon, circumscribing the podium, for displaying a status of the autonomous lawn mower; at least one camera mounted proximate a top of the podium; and an operator detector comprising an operator platform, the operator detector being moveable from a first position to a second position, and an operator sensor adapted to sense when the operator platform moves from the first position to the second position and causes at least one of the at least one stereo camera to be deactivated when the operator platform is in the second position.

19. The autonomous lawn mower of claim 15, wherein the LED ribbon displays the status as at least one or more of a color, a combination of colors, text, or graphics, and the at least one camera is a stereo camera.
