

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398663
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Bak; Byoung Gu et al.

Gas turbine plant with ammonia decomposition system

Abstract

The present disclosure relates to a gas turbine plant which decomposes ammonia and supplies it as fuel to a combustor of the gas turbine. The gas turbine plant supplies sufficient heat to the ammonia in order to thermally decompose the ammonia effectively, and separates the residual ammonia present in the decomposition gas and supplies it to a combustor of the gas turbine.

Inventors: Bak; Byoung Gu (Suwon-si, KR), Kim; Jin Il (Changwon-si, KR), Kim; Tae Woo (Yongin-si, KR), Ha; Hong Geun (Yongin-si, KR), Bae; Young Hoon (Changwon-si, KR), Seon; Chil Yeong (Yongin-si, KR), Lee; Ki Hyun (Daegu, KR), Jeong; Kwang Hun (Gimhae-si, KR)

Applicant: DOOSAN ENERBILITY CO., LTD. (Changwon-si, KR)

Family ID: 1000008783031

Assignee: Doosan Enerbility Co., Ltd. (Changwon-si, KR)

Appl. No.: 18/677558

Filed: May 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240401503 A1	Dec. 05, 2024

Foreign Application Priority Data

KR	10-2023-0069375	May. 30, 2023
----	-----------------	---------------

Publication Classification

Int. Cl.: F01K23/10 (20060101); F01K11/02 (20060101); F01K21/04 (20060101)

U.S. Cl.:

CPC **F01K23/10** (20130101); **F01K11/02** (20130101); **F01K21/047** (20130101);

Field of Classification Search

CPC: F01K (11/02); F01K (21/047); F01K (23/10); Y02E (20/16); C01B (3/047); C01B (3/04);
 C01C (1/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5852925	12/1997	Prasad et al.	N/A	N/A
11156168	12/2020	Nose	N/A	F02C 3/20
11679977	12/2022	Al-Huwaider	60/39.182	F01K 7/16
11912574	12/2023	Jo	N/A	N/A
11939915	12/2023	Uechi	N/A	F01K 25/103
2007/0214766	12/2006	Obana	N/A	N/A
2009/0133400	12/2008	Callas	60/730	F02C 7/143
2018/0355794	12/2017	Bulat	N/A	N/A
2019/0084831	12/2018	Andersen	N/A	N/A
2019/0107048	12/2018	Bulat	N/A	N/A
2020/0032676	12/2019	Nose	N/A	N/A
2021/0332759	12/2020	Smith	N/A	N/A
2022/0099021	12/2021	Uechi	N/A	N/A
2022/0154646	12/2021	Araki	N/A	N/A
2022/0162989	12/2021	Cocks	N/A	N/A
2022/0162999	12/2021	Cocks	N/A	N/A
2022/0299205	12/2021	MacDonald	N/A	N/A
2023/0129294	12/2022	Cocks	N/A	N/A
2023/0313735	12/2022	Smith	N/A	N/A
2023/0407784	12/2022	Takeishi	N/A	N/A
2024/0019124	12/2023	Ito	N/A	N/A
2024/0068416	12/2023	Hagita	N/A	N/A
2024/0093639	12/2023	Ikeda	N/A	N/A
2024/0117763	12/2023	Ito	N/A	N/A
2024/0166505	12/2023	White	N/A	B01J 8/0005
2024/0167417	12/2023	Lin	N/A	F02C 3/22
2024/0183310	12/2023	Uechi	N/A	N/A
2024/0328358	12/2023	Barth	N/A	N/A
2024/0401519	12/2023	Bak	N/A	C01C 1/12
2024/0401520	12/2023	Bak	N/A	F02C 3/22
2024/0401524	12/2023	Bak	N/A	F02C 6/18

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
119222016	12/2023	CN	N/A
2948351	12/1998	JP	N/A
2015021499	12/2014	JP	N/A

2016085189	12/2015	JP	N/A
2018076794	12/2017	JP	N/A
2020147478	12/2019	JP	N/A
2020148183	12/2019	JP	N/A
20210096274	12/2020	JP	N/A
20130071099	12/2012	KR	N/A
20140001773	12/2013	KR	N/A
20210121192	12/2020	KR	N/A
20220141943	12/2021	KR	N/A
20230060372	12/2022	KR	N/A
2023162600	12/2022	WO	N/A
2024100987	12/2023	WO	N/A

Primary Examiner: Bogue; Jesse S

Attorney, Agent or Firm: Shook, Hardy & Bacon L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application claims priority to Korea Patent Application No. 10-2023-0069375, filed May 30, 2023, the entire contents of which is incorporated herein for all purposes by this reference.

FIELD

(2) The present disclosure relates to a gas turbine plant with an ammonia decomposition system and more particularly to a gas turbine plant which decomposes ammonia and supplies it as fuel to a combustor of the gas turbine.

BACKGROUND

(3) For the purpose of reducing the emission amount of carbon dioxide in order to preserve global environment, it is a promising option to use hydrogen as a fuel which does not emit carbon dioxide even when combusted. However, compared to a fuel such as liquefied natural gas which is widely used as a fuel for a gas turbine, hydrogen is not easy to transport or store. Therefore, it is being considered that ammonia that can be converted to hydrogen is used as a fuel.

(4) Japanese Patent No. 2948351 discloses a gas turbine plant equipped with a decomposition device that heats ammonia and decomposes it into hydrogen and nitrogen. The decomposition device of the gas turbine plant heats ammonia by performing heat exchange between liquid ammonia with pressure increased by a pressure pump and exhaust gas discharged from the gas turbine, thereby thermally decomposing the ammonia into decomposition gas containing hydrogen and nitrogen. This decomposition gas is supplied as it is to a combustor of the gas turbine.

(5) However, the liquid ammonia may not be sufficiently heated by the exhaust gas. In this case, a large amount of ammonia in addition to hydrogen and nitrogen often remains in the decomposition gas. When the decomposition gas is supplied to the combustor of the gas turbine and the residual ammonia is combusted, there is a problem that a large amount of nitrogen oxides (NOx) is generated.

SUMMARY

(6) The purpose of the present disclosure is to provide a gas turbine plant that decomposes ammonia and supplies it as fuel to a combustor of a gas turbine. The gas turbine plant supplies sufficient heat to the ammonia in order to thermally decompose the ammonia effectively, and separates the residual ammonia present in the decomposition gas and supplies it to a combustor of

the gas turbine.

(7) The technical problem to be overcome in this document is not limited to the above-mentioned technical problems. Other technical problems not mentioned can be clearly understood from those described below by a person having ordinary skill in the art.

(8) One embodiment is a gas turbine plant with an ammonia decomposition system. The gas turbine plant includes: a storage tank configured to store liquid ammonia; a supply pump configured to supply the liquid ammonia of the storage tank; a preheater configured to preheat the liquid ammonia supplied by the supply pump; a vaporizer configured to vaporize the liquid ammonia preheated by the preheater; a superheater configured to superheat gaseous ammonia vaporized by the vaporizer; a decomposition reactor configured to thermally decompose the gaseous ammonia superheated by the superheater; a separator configured to separate residual ammonia from decomposition gas decomposed by the decomposition reactor; and a second combustor configured to generate combustion gas in such a way as to supply heat to the decomposition reactor. Synthesis gas consisting of hydrogen and nitrogen with the residual ammonia removed by the separator is supplied to a first combustor of a gas turbine. A heat transfer fluid absorbs heat from the combustion gas or the decomposition gas and supplies the heat to the liquid ammonia, the gaseous ammonia, the synthesis gas supplied to the first combustor, or fuel supplied to the second combustor.

(9) A heat transfer fluid circuit through which the heat transfer fluid flows may include: a pump; a first heat exchanger that absorbs heat by heat exchange with the combustion gas or the decomposition gas; and a second heat exchanger that supplies heat by heat exchange with the liquid ammonia, the gaseous ammonia, the synthesis gas supplied to the first combustor, or fuel supplied to the second combustor.

(10) The second heat exchanger may be any one of the preheater, the vaporizer, and the superheater.

(11) The second heat exchanger may be disposed such that the synthesis gas supplied from the separator to the first combustor passes through the second heat exchanger.

(12) The second heat exchanger may be disposed such that the fuel supplied to the second combustor passes through the second heat exchanger.

(13) A portion of the decomposition gas decomposed by the decomposition reactor or a portion of the synthesis gas from which the residual ammonia has been removed in the separator may be supplied as fuel for the second combustor.

(14) A portion of the synthesis gas from which the residual ammonia has been removed in the separator may be supplied as fuel for the second combustor. The second heat exchanger may be disposed such that the synthesis gas from the separator passes through the second heat exchanger before being branched.

(15) Exhaust gas discharged from the gas turbine may be supplied to the heat recovery steam generator. Steam generated by heat of the exhaust gas in the heat recovery steam generator may be supplied to a steam turbine and may drive the steam turbine, and then may flow into a condenser, and water condensed in the condenser may be supplied back to the heat recovery steam generator. A portion of the water condensed in the condenser may be supplied as the heat transfer fluid to the heat transfer fluid circuit.

(16) The heat transfer fluid circuit may further include an internal heat exchanger in which the water discharged from the condenser and the water entering the condenser exchange heat.

(17) The water discharged from the condenser may absorb heat while passing through the internal heat exchanger, may absorb heat while passing through the first heat exchanger, and then may supply the heat while passing through the second heat exchanger, and may supply the heat while passing through the internal heat exchanger, and then may flow back into the condenser.

(18) The combustion gas may supply heat while passing through the decomposition reactor and the superheater. The heat transfer fluid may absorb heat from the combustion gas that has passed

through the decomposition reactor and the superheater.

(19) Another embodiment is a gas turbine plant with an ammonia decomposition system. The gas turbine plant includes: a storage tank configured to store liquid ammonia; a supply pump configured to supply the liquid ammonia of the storage tank; a preheater configured to preheat the liquid ammonia supplied by the supply pump; a vaporizer configured to vaporize the liquid ammonia preheated by the preheater; a superheater configured to superheat gaseous ammonia vaporized by the vaporizer; a decomposition reactor configured to thermally decompose the gaseous ammonia superheated by the superheater; and a separator configured to separate residual ammonia from decomposition gas decomposed by the decomposition reactor. Synthesis gas consisting of hydrogen and nitrogen with the residual ammonia removed by the separator is supplied to a first combustor of a gas turbine. A heat transfer fluid absorbs heat from the decomposition gas and supplies the heat to the liquid ammonia, the gaseous ammonia, or the synthesis gas supplied to the first combustor.

(20) A heat transfer fluid circuit through which the heat transfer fluid flows may include: a pump; a first heat exchanger that absorbs heat by heat exchange with the decomposition gas; and a second heat exchanger that supplies heat by heat exchange with the liquid ammonia, the gaseous ammonia, or the synthesis gas supplied to the first combustor.

(21) The second heat exchanger may be any one of the preheater, the vaporizer, and the superheater.

(22) The second heat exchanger may be disposed such that the synthesis gas supplied from the separator to the first combustor passes through the second heat exchanger.

(23) Exhaust gas discharged from the gas turbine may be supplied to the heat recovery steam generator. Steam generated by heat of the exhaust gas in the heat recovery steam generator may be supplied to a steam turbine and drives the steam turbine, and then may flow into a condenser, and water condensed in the condenser may be supplied back to the heat recovery steam generator. A portion of the water condensed in the condenser may be supplied as the heat transfer fluid to the heat transfer fluid circuit.

(24) The heat transfer fluid circuit may further include an internal heat exchanger in which the water discharged from the condenser and the water entering the condenser exchange heat.

(25) The water discharged from the condenser may absorb heat while passing through the internal heat exchanger, may absorb heat while passing through the first heat exchanger, and then may supply the heat while passing through the second heat exchanger, and may supply the heat while passing through the internal heat exchanger, and then may flow back into the condenser.

(26) According to the embodiment, as the ammonia decomposition system includes the preheater, the vaporizer, and the superheater, which are for heating the ammonia before the decomposition reactor, sufficient heat can be supplied to the ammonia. Also, when the combustion gas generated by a separate second combustor supplies heat to the decomposition reactor, the ammonia can be thermally decomposed effectively at a high temperature.

(27) Also, ammonia or fuel supplied to the combustor is heated by using the combustion gas or the decomposition gas generated within the plant, so that the efficiency of the plant can be improved. Here, when the fuel (synthesis gas, etc.) entering the combustor is heated, the amount of fuel used for target temperature of the combustion gas can be reduced.

(28) Also, a portion of the ammonia, the decomposition gas, or the synthesis gas present in the ammonia decomposition system is supplied as fuel to the second combustor, so that a separate fuel such as fossil fuel, etc., is not required.

(29) The effect of the present disclosure is not limited to the above effects and should be construed as including all the effects that can be inferred from the configuration of the present disclosure disclosed in the detailed description or claims of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a gas turbine plant with an ammonia decomposition system according to an embodiment;
- (2) FIG. 2 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (3) FIG. 3 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (4) FIG. 4 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (5) FIG. 5 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (6) FIG. 6 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (7) FIG. 7 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (8) FIG. 8 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment;
- (9) FIG. 9 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment; and
- (10) FIG. 10 is a schematic diagram of a gas turbine plan with an ammonia decomposition system according to an embodiment.

DETAILED DESCRIPTION

- (11) Hereinafter, preferable embodiments of a gas turbine plant with an ammonia decomposition system will be described with reference to accompanying drawings.
- (12) Also, the below-mentioned terms are defined in consideration of the functions in the present disclosure and may be changed according to the intention of users or operators or custom. The following embodiments do not limit the scope of the present disclosure and are merely exemplary of the components presented in the claims of the present disclosure.
- (13) Parts irrelevant to the description will be omitted for a clear description of the present disclosure. The same or similar reference numerals will be assigned to the same or similar components throughout this specification. Throughout this specification, when it is mentioned that a portion “includes” an element, it means that the portion does not exclude but further includes other elements unless there is a special opposite mention.
- (14) First, a gas turbine plant including an ammonia decomposition system according to an embodiment of the present disclosure will be described with reference to FIG. 1.
- (15) The gas turbine plant according to the embodiment generally includes an ammonia decomposition system **10**, a gas turbine **20**, a heat recovery steam generator (HRSG) **30**, a steam turbine **40**, a condenser **50**, and a heat transfer fluid circuit **60**.
- (16) The ammonia decomposition system **10** includes a storage tank **100**, a supply pump **120**, a preheater **200**, a vaporizer **300**, a superheater **400**, a decomposition reactor **500**, a separator **600**, and a second combustor **700**.
- (17) The gas turbine **20** includes a compressor **22** for compressing air to high pressure, a first combustor **24** for mixing the air compressed by the compressor **22** with fuel and for combusting, and a turbine **26** for generating power while rotating turbine blades by using high-temperature and high-pressure combustion gas discharged from the first combustor **24**.
- (18) In the embodiment of the present disclosure, synthesis gas based on hydrogen decomposed in the ammonia decomposition system **10** as a main component is supplied as fuel for the first

combustor **24**. It is shown in the drawing that only the synthesis gas is supplied. However, in some cases, it is also possible that the synthesis gas and natural gas are supplied to the first combustor **24** together and mixed and combusted.

(19) Exhaust gas (EG) discharged from the turbine **26** of the gas turbine **20** is supplied to the heat recovery steam generator **30** and vaporizes water into steam within the heat recovery steam generator **30**. The steam generated by heat of the exhaust gas (EG) in the heat recovery steam generator **30** is supplied to the steam turbine **40** and drives the steam turbine to produce electric power. After driving the steam turbine **40**, the steam flows into the condenser **50** and is condensed by cooling water, and the water condensed in the condenser **50** is supplied back to the heat recovery steam generator **30**.

(20) Hereinafter, each component of the ammonia decomposition system **10** will be described in detail. FIG. **1** shows a flow of ammonia or ammonia-decomposed gas passing through the components of the ammonia decomposition system **10**, and adjacent components will be connected to each other through connection pipes, etc.

(21) The storage tank **100** stores liquid ammonia, and the supply pump **120** increases the pressure of the liquid ammonia of the storage tank **100** and supplies the liquid ammonia to the preheater **200**.

(22) Subsequently, the preheater **200**, the vaporizer **300**, and the superheater **400** are configured to vaporize and heat the liquid ammonia prior to the decomposition reactor **500**. Specifically, the preheater **200** preheats the liquid ammonia supplied by the supply pump **120**. The vaporizer **300** vaporizes the liquid ammonia preheated by the preheater **200**. The superheater **400** superheats the gaseous ammonia vaporized by the vaporizer **300**.

(23) As one example, when the supply pump **120** increases the pressure of the liquid ammonia to 40 atm, a boiling point of the ammonia at 40 atm is around 100° C. In this case, the preheater **200** heats the liquid ammonia to below the boiling point, and the vaporizer **300** heats the liquid ammonia to the boiling point and generates gaseous ammonia. The superheater **400** additionally heats the gaseous ammonia.

(24) The decomposition reactor **500** thermally decomposes the gaseous ammonia superheated by the superheater **400** and generates decomposition gas (DG) containing hydrogen, nitrogen, and residual ammonia. A catalyst that promotes the thermal decomposition of the ammonia may be filled in the decomposition reactor **500**. The catalyst has a catalyst component that activates a decomposition reaction, and a carrier that supports the catalyst component. An example of the catalyst component includes particles of precious metal such as Ru, etc., and metal particles including transition metals such as Ni, Co, and Fe, etc. The carrier includes a metal oxide such as Al₂O₃, ZrO₂, Pr₂O₃, La₂O₃, MgO, etc. The catalyst is not limited to the catalysts exemplified above as long as the catalyst activates the decomposition reaction of ammonia.

(25) The separator **600** separates residual ammonia from the decomposition gas (DG) decomposed in the decomposition reactor **500**. Then, the residual ammonia is removed in the separator **600**, the synthesis gas (SG) consisting of hydrogen and nitrogen is supplied to the first combustor **24** of the gas turbine. Here, the residual ammonia separated by the separator **600** may be mixed with the gaseous ammonia vaporized by the vaporizer **300** and may be supplied to the superheater **400**. Since ammonia is highly soluble in water, the separator **600** can remove the residual ammonia by dissolving the residual ammonia in water. Also, ammonia is easier to evaporate than water. Therefore, when ammonia water that is obtained by dissolving the residual ammonia in water is heated, gaseous ammonia can be separated again.

(26) Here, a reaction temperature for the thermal decomposition of the ammonia (depending on the catalyst, generally 400° C. to 700° C.) is much higher than a boiling point of ammonia. Therefore, the superheater **400** and the decomposition reactor **500** requires a higher temperature heat source than the preheater **200** and the vaporizer **300**.

(27) To this end, the ammonia decomposition system **10** includes the second combustor **700** that

generates combustion gas (CG) such that heat is supplied to the decomposition reactor **500**. In the embodiment, the combustion gas (CG) generated by the second combustor **700** supplies heat while passing through the decomposition reactor **500** and the superheater **400**. However, the embodiment is not limited to this, and the combustion gas (CG) may additionally pass through the preheater **200** or the vaporizer **300**.

(28) The combustion gas (CG) generated from the second combustor **700** generally has a temperature of about 1000° C., which is higher than that of the exhaust gas (EG) discharged from the gas turbine **20**. Therefore, by using the combustion gas (CG) with the inclusion of the separate second combustor **700**, the ammonia can be effectively thermally decomposed by the decomposition reactor **500** even without using a high-performance catalyst, and the efficiency of the decomposition reactor **500** can be improved.

(29) However, according to the embodiment, when the separate second combustor **700** is not included, at least a portion of the exhaust gas (EG) discharged from the gas turbine **20** may supply heat while passing through the decomposition reactor **500** and the superheater **400**. In this case, the exhaust gas (EG) discharged from the gas turbine **20** is branched and a portion of the exhaust gas (EG) may be supplied to the decomposition reactor **500**, and the other portion may be supplied to the heat recovery steam generator **30**. Alternatively, the exhaust gas (EG) discharged from the gas turbine **20** may supply heat while passing through the decomposition reactor **500** and the superheater **400** in turn, and then may be supplied to the heat recovery steam generator **30**.

(30) As such, the ammonia decomposition system **10** may include the preheater **200**, the vaporizer **300**, and the superheater **400**, which are for heating the ammonia before the decomposition reactor **500**, and the exhaust gas (EG) or the combustion gas (CG) generated by the separate second combustor **700** supplies heat to the decomposition reactor **500**. Accordingly, sufficient heat can be supplied to the ammonia and the ammonia can be thermally decomposed effectively.

(31) Accordingly, there is not much residual ammonia in the decomposition gas (DG), and the residual ammonia is reliably removed through the separator **600** and the decomposition gas (DG) is supplied to the first combustor **24**, thereby reducing nitrogen oxides in the exhaust gas (EG).

(32) Next, the heat transfer fluid circuit **60** will be described in detail.

(33) In the embodiment of the present invention, a heat transfer fluid absorbs heat from the combustion gas (CG) or the decomposition gas (DG) and supplies the heat to the liquid ammonia, the gaseous ammonia, the synthesis gas supplied to the first combustor **24**, or fuel supplied to the second combustor **700**. In this way, ammonia or fuel supplied to the combustor is heated by using the combustion gas (CG) or the decomposition gas (DG) generated within the plant, so that the efficiency of the plant can be improved.

(34) In FIG. **1**, the description will be made based on the fact that the heat transfer fluid absorbs heat from the combustion gas (CG) and supplies the heat to the synthesis gas (SG) supplied to the first combustor **24**.

(35) Specifically, the heat transfer fluid circuit **60** through which the heat transfer fluid flows includes a pump **62**, a first heat exchanger **64a** that absorbs heat by heat exchange with the combustion gas (CG), and a second heat exchanger **66a** that supplies heat by heat exchange with the synthesis gas (SG) supplied to the first combustor **24**. That is, in the first heat exchanger **64a**, direct heat exchange occurs between the heat transfer fluid and the combustion gas (CG), so that the heat may be transferred from the combustion gas (CG) to the heat transfer fluid. In the second heat exchanger **66a**, direct heat exchange occurs between the heat transfer fluid and the synthesis gas (SG), so that the heat may be transferred from the heat transfer fluid to the synthesis gas (SG). In this case, the second heat exchanger **66a** serves as a fuel heater that heats the fuel (synthesis gas) entering the first combustor **24**, which results in the reduction of the amount of fuel used for target temperature of the combustion gas in the first combustor **24**. In FIG. **1**, the two second heat exchangers **66a** disposed on the heat transfer fluid circuit and on the path of the synthesis gas (SG) are the same components and are shown separately for the simplification of the drawing.

(36) The first heat exchanger **64a** may be disposed downstream of the superheater **400** such that the combustion gas (CG) that has passed through the decomposition reactor **500** and the superheater **400** can pass through the first heat exchanger **64a**. Also, the second heat exchanger **66a** may be disposed on the path of the synthesis gas (SG) such that the synthesis gas (SG) supplied from the separator **600** to the first combustor **24** can pass through the second heat exchanger **66a**. In particular, in the embodiment, a portion of the synthesis gas (SG) from which the residual ammonia has been removed in the separator **600** is supplied as fuel for the second combustor **700**, and accordingly, the synthesis gas (SG) from the separator **600** is branched and then supplied to the first combustor **24** and the second combustor **700**, respectively. In this case, the second heat exchanger **66a** may be disposed on a path through which the synthesis gas (SG) is branched and then supplied to the first combustor **24**, in order to heat the fuel supplied to the first combustor **24**.

(37) Here, a separate fluid (for example, antifreeze) unrelated to the plant may be supplied as the heat transfer fluid. However, in the embodiment, a portion of the water condensed in the condenser **50** is supplied as a heat transfer fluid to the heat transfer fluid circuit **60**.

(38) While the temperature of the water discharged after being condensed in the condenser **50** is generally about 15° C., the temperature of the water discharged from the second heat exchanger **66a** and entering the condenser **50** is still high, so that there is a burden of having to significantly lower the temperature in the condenser **50**. To this end, the heat transfer fluid circuit **60** may further include an internal heat exchanger **68** in which the water discharged from the condenser **50** and the water entering the condenser **50** exchange heat. That is, as shown in FIG. 1, the water discharged from the condenser **50** may absorb heat while passing through the internal heat exchanger **68**, may absorb heat while passing through the first heat exchanger **64a**, and then may supply the heat while passing through the second heat exchanger **66a**, and may supply heat while passing through the internal heat exchanger **68**. Then, the water may flow back into the condenser **50**. According to this, the water discharged from the second heat exchanger **66a** can transfer heat to the water entering the first heat exchanger **64a**, thereby reducing the burden on the condenser **50** and improving efficiency.

(39) The following embodiments will focus on differences from the embodiment shown in FIG. 1.

(40) According to the embodiment shown in FIG. 2, the gas turbine plant includes the heat transfer fluid circuit **60**, and the heat transfer fluid absorbs heat from the combustion gas (CG) and supplies the heat to the fuel supplied to the second combustor **700**. In the embodiment, a portion of the synthesis gas (SG) from which residual ammonia has been removed in the separator **600** is supplied as fuel for the second combustor **700**, so that the fuel supplied to the second combustor **700** corresponds to the synthesis gas (SG).

(41) Specifically, the heat transfer fluid circuit **60** through which the heat transfer fluid flows includes the pump **62**, the first heat exchanger **64a** that absorbs heat by heat exchange with the combustion gas (CG), and a second heat exchanger **66b** that supplies heat by heat exchange with the synthesis gas (SG) supplied to the second combustor **700**, and the internal heat exchanger **68**. That is, in the first heat exchanger **64a**, direct heat exchange occurs between the heat transfer fluid and the combustion gas (CG), so that the heat may be transferred from the combustion gas (CG) to the heat transfer fluid. In the second heat exchanger **66b**, direct heat exchange occurs between the heat transfer fluid and the synthesis gas (SG), so that the heat may be transferred from the heat transfer fluid to the synthesis gas (SG). In this case, the second heat exchanger **66b** serves as a fuel heater that heats the fuel (synthesis gas) entering the second combustor **700**, which results in the reduction of the amount of fuel used for target temperature of the combustion gas in the second combustor **700**. In FIG. 2, the two second heat exchangers **66b** disposed on the heat transfer fluid circuit and on the path of the synthesis gas (SG) are the same components and are shown separately for the simplification of the drawing.

(42) The second heat exchanger **66b** may be disposed on the path of the synthesis gas (SG) such that the synthesis gas (SG) supplied from the separator **600** to the second combustor **700** can pass

through the second heat exchanger **66b**. In particular, in the embodiment, since the synthesis gas (SG) from the separator **600** is branched and then supplied to the first combustor **24** and the second combustor **700**, respectively, the second heat exchanger **66b** may be disposed on the path through which the synthesis gas (SG) is branched and then supplied to the second combustor **700**.

(43) According to the embodiment, as shown in FIG. 3, when a portion of the decomposition gas (DG) decomposed in the decomposition reactor **500** is supplied as fuel for the second combustor **700**, it is also possible that the second heat exchanger **66c** may be disposed on the path of the decomposition gas (DG) such that the decomposition gas (DG) supplied from the decomposition reactor **500** to the second combustor **700** can pass the second heat exchanger **66c**.

(44) Also, according to the embodiments shown in FIGS. 4 and 5, the heat transfer fluid absorbs heat from the combustion gas (CG) and supplies the heat both to the synthesis gas supplied to the first combustor **24** and the fuel supplied to the second combustor **700**. In FIGS. 4 and 5, a portion of the synthesis gas (SG) from which residual ammonia has been removed in the separator **600** is supplied as fuel for the second combustor **700**, so that the fuel supplied to the second combustor **700** also corresponds also to the synthesis gas (SG).

(45) To this end, in FIG. 4, the heat transfer fluid circuit **60** includes the pump **62**, the first heat exchanger **64a**, the internal heat exchanger **68**, and two second heat exchangers **66a** and **66b**. Within the heat transfer fluid circuit **60**, the two second heat exchangers **66a** and **66b** may be arranged in parallel or in series. The synthesis gas (SG) from the separator **600** is branched and then supplied to the first combustor **24** and the second combustor **700**, respectively. Also, one second heat exchanger **66a** may be disposed on the path through which the synthesis gas (SG) is branched and then supplied to the first combustor **24**, and the other second heat exchanger **66b** may be disposed on the path through which the synthesis gas (SG) is branched and then supplied to the second combustor **700**. Accordingly, the two second heat exchangers **66a** and **66b** serve as fuel heaters that heat the fuel (synthesis gas) entering the first combustor **24** and the second combustor **700**, respectively.

(46) Alternatively, in FIG. 5, the heat transfer fluid circuit **60** includes the pump **62**, the first heat exchanger **64a**, the internal heat exchanger **68**, and one second heat exchanger **66d**. The synthesis gas (SG) from the separator **600** is branched and then supplied to the first combustor **24** and the second combustor **700**, respectively. The one second heat exchanger **66d** may be disposed such that the synthesis gas (SG) from the separator **600** passes through the second heat exchanger **66d** before being branched. Accordingly, the second heat exchanger **66d** serves as a fuel heater that heats all the fuel (synthesis gas) entering the first combustor **24** and the second combustor **700** before being branched.

(47) Next, according to the embodiment shown in FIG. 6, the gas turbine plant includes the heat transfer fluid circuit **60**, and the heat transfer fluid absorbs heat from the combustion gas (CG) and supplies the heat to the liquid ammonia.

(48) Specifically, the heat transfer fluid circuit **60** through which the heat transfer fluid flows includes the pump **62**, the first heat exchanger **64a** that absorbs heat by heat exchange with the combustion gas (CG), and the second heat exchanger that supplies heat by heat exchange with the liquid ammonia, and the internal heat exchanger **68**. Here, the second heat exchanger corresponds to the vaporizer **300**, and the heat transfer fluid heats the liquid ammonia to the boiling point by supplying heat to the liquid ammonia in the vaporizer **300**, so that the liquid ammonia can be vaporized. That is, in the first heat exchanger **64a**, direct heat exchange occurs between the heat transfer fluid and the combustion gas (CG), so that the heat may be transferred from the combustion gas (CG) to the heat transfer fluid. In the vaporizer **300**, direct heat exchange occurs between the heat transfer fluid and the liquid ammonia, so that the heat may be transferred from the heat transfer fluid to the liquid ammonia.

(49) However, the embodiment is not limited to this. The second heat exchanger may correspond to the preheater **200** or the superheater **400**, and the heat transfer fluid may also supply heat to the

liquid ammonia or the gaseous ammonia.

(50) Next, according to the embodiment shown in FIG. 7, the gas turbine plant includes the heat transfer fluid circuit **60**, and the heat transfer fluid absorbs heat from the decomposition gas (DG) and supplies the heat to the synthesis gas (SG) supplied to the first combustor **24**.

(51) Specifically, the heat transfer fluid circuit **60** through which the heat transfer fluid flows includes the pump **62**, a first heat exchanger **64b** that absorbs heat by heat exchange with the decomposition gas (DG), and the second heat exchanger **66a** that supplies heat by heat exchange with the synthesis gas (SG) supplied to the first combustor **24**. That is, in the first heat exchanger **64b**, direct heat exchange occurs between the heat transfer fluid and the decomposition gas (DG), so that the heat may be transferred from the decomposition gas (DG) to the heat transfer fluid. In the second heat exchanger **66a**, direct heat exchange occurs between the heat transfer fluid and the synthesis gas (SG), so that the heat may be transferred from the heat transfer fluid to the synthesis gas (SG). The first heat exchanger **64b** may be disposed downstream of the decomposition reactor **500** such that decomposition gas (DG) from the decomposition reactor **500** can pass through the first heat exchanger **64b**.

(52) Likewise, a separate fluid (for example, antifreeze) unrelated to the plant may be supplied as the heat transfer fluid. However, in the embodiment, a portion of the water condensed in the condenser **50** is supplied as a heat transfer fluid to the heat transfer fluid circuit **60**. Therefore, the heat transfer fluid circuit **60** may further include the internal heat exchanger **68** in which the water discharged from the condenser **50** and the water entering the condenser **50** exchange heat. In the internal heat exchanger **68**, the water discharged from the second heat exchanger **66a** can transfer heat to the water entering the first heat exchanger **64b**, thereby reducing the burden on the condenser **50** and improving efficiency.

(53) The embodiment shows the second heat exchanger **66a** for heating the synthesis gas (SG) supplied to the first combustor **24**. However, as already described above, the second heat exchanger **66a** may be replaced by the second heat exchangers **66b** and **66c** for heating the fuel supplied to the second combustor **700** or the second heat exchanger **66d** for simultaneously heating the fuel supplied to the first combustor **24** and the second combustor **700**.

(54) Finally, according to the embodiment shown in FIG. 8, the gas turbine plant includes the heat transfer fluid circuit **60**, and the heat transfer fluid absorbs heat from the decomposition gas (DG) and supplies heat to the liquid ammonia.

(55) Specifically, the heat transfer fluid circuit **60** through which the heat transfer fluid flows includes the pump **62**, the first heat exchanger **64b** that absorbs heat by heat exchange with the decomposition gas (DG), the second heat exchanger that supplies heat by heat exchange with the liquid ammonia, and the internal heat exchanger **68**. Here, the second heat exchanger corresponds to the vaporizer **300**, and the heat transfer fluid heats the liquid ammonia to the boiling point by supplying heat to the liquid ammonia in the vaporizer **300**, so that the liquid ammonia can be vaporized. That is, in the first heat exchanger **64b**, direct heat exchange occurs between the heat transfer fluid and the decomposition gas (DG), so that the heat may be transferred from the decomposition gas (DG) to the heat transfer fluid. In the vaporizer **300**, direct heat exchange occurs between the heat transfer fluid and the liquid ammonia, so that the heat may be transferred from the heat transfer fluid to the liquid ammonia.

(56) However, the embodiment is not limited to this. The second heat exchanger may correspond to the preheater **200** or the superheater **400**, and the heat transfer fluid may also supply heat to the liquid ammonia or the gaseous ammonia.

(57) The present invention is not limited to the described specific embodiments and descriptions described above. Various modifications can be made by anyone skilled in the art without departing from the subject matter of the present invention as defined by the appended claims. Such modifications fall within the scope of protection of the present invention.

REFERENCE NUMERALS

(58) **10**: Ammonia Decomposition System **20**: Gas Turbine **22**: Compressor **24**: First Combustor **26**: Turbine **30**: Heat Recovery Steam Generator **40**: Steam Turbine **50**: Condenser **60**: Heat Transfer Fluid Circuit **62**: Pump **64a**, **64b**: First Heat Exchanger **66a**, **66b**, **66c**, **66d**: Second Heat Exchanger **68**: Internal Heat Exchanger **100**: Storage Tank **120**: Supply Pump **200**: Preheater **300**: Vaporizer **400**: Superheater **500**: Decomposition Reactor **600**: Separator **700**: Second Combustor EG: Exhaust Gas DG: Decomposition Gas SG: Synthesis Gas CG: Combustion Gas

Claims

1. A gas turbine plant with an ammonia decomposition system, the gas turbine plant comprising: a storage tank configured to store liquid ammonia; a supply pump configured to supply the liquid ammonia of the storage tank; a preheater configured to preheat the liquid ammonia supplied by the supply pump; a vaporizer configured to vaporize the liquid ammonia preheated by the preheater; a superheater configured to superheat gaseous ammonia vaporized by the vaporizer; a decomposition reactor configured to thermally decompose the gaseous ammonia superheated by the superheater; a separator configured to separate residual ammonia from decomposition gas decomposed by the decomposition reactor; and a second combustor configured to generate combustion gas in such a way as to supply heat to the decomposition reactor, wherein synthesis gas consisting of hydrogen and nitrogen with the residual ammonia removed by the separator is supplied to a first combustor of a gas turbine, wherein a heat transfer fluid absorbs heat from the combustion gas or the decomposition gas and supplies the heat to the liquid ammonia, the gaseous ammonia, the synthesis gas supplied to the first combustor, or fuel supplied to the second combustor; wherein a heat transfer fluid circuit through which the heat transfer fluid flows comprises: a pump; a first heat exchanger that absorbs heat by heat exchange with the combustion gas or the decomposition gas; and a second heat exchanger that supplies heat by heat exchange with the liquid ammonia, the gaseous ammonia, the synthesis gas supplied to the first combustor, or fuel supplied to the second combustor; wherein exhaust gas discharged from the gas turbine is supplied to a heat recovery steam generator, wherein steam generated by heat of the exhaust gas in the heat recovery steam generator is supplied to a steam turbine and drives the steam turbine, and then flows into a condenser, and water condensed in the condenser is supplied back to the heat recovery steam generator, wherein a portion of the water condensed in the condenser is supplied as the heat transfer fluid to the heat transfer fluid circuit, and wherein the heat transfer fluid circuit further comprises an internal heat exchanger in which the water discharged from the condenser and the water entering the condenser exchange heat.

2. The gas turbine plant with an ammonia decomposition system of claim 1, wherein the second heat exchanger is any one of the preheater, the vaporizer, and the superheater.

3. The gas turbine plant with an ammonia decomposition system of claim 1, wherein the second heat exchanger is disposed such that the synthesis gas supplied from the separator to the first combustor passes through the second heat exchanger.

4. The gas turbine plant with an ammonia decomposition system of claim 1, wherein the second heat exchanger is disposed such that the fuel supplied to the second combustor passes through the second heat exchanger.

5. The gas turbine plant with an ammonia decomposition system of claim 4, wherein a portion of the decomposition gas decomposed by the decomposition reactor or a portion of the synthesis gas from which the residual ammonia has been removed in the separator is supplied as fuel for the second combustor.

6. The gas turbine plant with an ammonia decomposition system of claim 1, wherein a portion of the synthesis gas from which the residual ammonia has been removed in the separator is supplied as fuel for the second combustor, and wherein the second heat exchanger is disposed such that the synthesis gas from the separator passes through the second heat exchanger before being branched.

7. The gas turbine plant with an ammonia decomposition system of claim 1, wherein the water discharged from the condenser absorbs heat while passing through the internal heat exchanger, absorbs heat while passing through the first heat exchanger, and then supplies the heat while passing through the second heat exchanger, and supplies the heat while passing through the internal heat exchanger, and then flows back into the condenser.
8. The gas turbine plant with an ammonia decomposition system of claim 1, wherein the combustion gas supplies heat while passing through the decomposition reactor and the superheater, and wherein the heat transfer fluid absorbs heat from the combustion gas that has passed through the decomposition reactor and the superheater.
9. A gas turbine plant with an ammonia decomposition system, the gas turbine plant comprising: a storage tank configured to store liquid ammonia; a supply pump configured to supply the liquid ammonia of the storage tank; a preheater configured to preheat the liquid ammonia supplied by the supply pump; a vaporizer configured to vaporize the liquid ammonia preheated by the preheater; a superheater configured to superheat gaseous ammonia vaporized by the vaporizer; a decomposition reactor configured to thermally decompose the gaseous ammonia superheated by the superheater; and a separator configured to separate residual ammonia from decomposition gas decomposed by the decomposition reactor, wherein synthesis gas consisting of hydrogen and nitrogen with the residual ammonia removed by the separator is supplied to a first combustor of a gas turbine, wherein a heat transfer fluid absorbs heat from the decomposition gas and supplies the heat to the liquid ammonia, the gaseous ammonia, or the synthesis gas supplied to the first combustor, wherein a heat transfer fluid circuit through which the heat transfer fluid flows comprises: a pump; a first heat exchanger that absorbs heat by heat exchange with the decomposition gas; and a second heat exchanger that supplies heat by heat exchange with the liquid ammonia, the gaseous ammonia, or the synthesis gas supplied to the first combustor; wherein exhaust gas discharged from the gas turbine is supplied to a heat recovery steam generator, wherein steam generated by heat of the exhaust gas in the heat recovery steam generator is supplied to a steam turbine and drives the steam turbine, and then flows into a condenser, and water condensed in the condenser is supplied back to the heat recovery steam generator, wherein a portion of the water condensed in the condenser is supplied as the heat transfer fluid to the heat transfer fluid circuit; and wherein the heat transfer fluid circuit further comprises an internal heat exchanger in which the water discharged from the condenser and the water entering the condenser exchange heat.
10. The gas turbine plant with an ammonia decomposition system of claim 9, wherein the second heat exchanger is any one of the preheater, the vaporizer, and the superheater.
11. The gas turbine plant with an ammonia decomposition system of claim 9, wherein the second heat exchanger is disposed such that the synthesis gas supplied from the separator to the first combustor passes through the second heat exchanger.
12. The gas turbine plant with an ammonia decomposition system of claim 9, wherein the water discharged from the condenser absorbs heat while passing through the internal heat exchanger, absorbs heat while passing through the first heat exchanger, and then supplies the heat while passing through the second heat exchanger, and supplies the heat while passing through the internal heat exchanger, and then flows back into the condenser.
-