

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12398837
B2
August 26, 2025
Zhou; Jianshu et al.

Robots for water tunnel inspection and systems thereof

Abstract

In some embodiments, provided is a robot for water tunnel inspection, comprising: (a) a shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) a camera system, configured to capture an image or video of a field of view of surrounding; (c) a lighting system, configured to provide illumination at least partially for the field of view; (d) a propulsion system, configured to provide propulsion force to the robot in water; and (e) a controlling system, configured to provide power and control operation of the robot, wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center. Other example embodiments are described herein. In certain embodiments, the robots provide safe and efficient tunnel inspections without human operation.

Inventors: Zhou; Jianshu (Hong Kong, CN), Huang; Junda (Hong Kong, CN), Liu; Yunhui (Hong Kong, CN)

Applicant: Hong Kong Centre for Logistics Robotics Limited (Hong Kong, CN)

Family ID: 1000008783099

Assignee: HONG KONG CENTRE FOR LOGISTICS ROBOTICS LIMITED (Hong Kong, CN)

Appl. No.: 18/447334

Filed: August 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250052356 A1	Feb. 13, 2025

Publication Classification

Int. Cl.: **F16L55/32** (20060101); **B63G8/00** (20060101); **B63G8/04** (20060101); **B63G8/08** (20060101); **B63G8/39** (20060101); **F16L55/46** (20060101); **G01N21/88** (20060101); **G05D1/00** (20060101); **H04N23/56** (20230101); **H04N23/68** (20230101); F16L101/30 (20060101); G01S15/89 (20060101); H04N23/698 (20230101)

U.S. Cl.:

CPC **F16L55/32** (20130101); **B63G8/001** (20130101); **B63G8/04** (20130101); **B63G8/08** (20130101); **B63G8/39** (20130101); **F16L55/46** (20130101); **G01N21/8806** (20130101); **G05D1/0206** (20130101); **H04N23/56** (20230101); **H04N23/685** (20230101); B63G2008/004 (20130101); F16L2101/30 (20130101); G01S15/89 (20130101); H04N23/698 (20230101)

Field of Classification Search

CPC: F16L (55/32); F16L (2101/30); H04N (23/685); H04N (23/56); H04N (23/698); B63G (8/001); B63G (8/04); B63G (8/08); B63G (8/39); G01N (21/8806); G05D (1/0206); G01S (15/89)

USPC: 701/21

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3973469	12/1975	Humen	N/A	N/A
6289263	12/2000	Mukherjee	N/A	N/A
8028660	12/2010	Troy	N/A	N/A
8099189	12/2011	Kaznov et al.	N/A	N/A
8316970	12/2011	Tran	N/A	N/A
2006/0225634	12/2005	Cho et al.	N/A	N/A
2015/0159846	12/2014	Hollinger	362/183	H05B 47/19
2018/0335176	12/2017	Wu	N/A	B25J 18/00
2022/0234704	12/2021	Liu	N/A	B63C 11/52
2024/0141611	12/2023	Tofte	N/A	G01M 3/005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2692026	12/2004	CN	N/A
103726480	12/2013	CN	N/A

Primary Examiner: Ismail; Mahmoud S
Attorney, Agent or Firm: EAGLE IP LIMITED

Background/Summary

FIELD OF INVENTION
(1) This application relates to devices and systems for inspecting tunnels. More specifically, the

present disclosure relates robots and system thereof for water tunnel inspection.

BACKGROUND OF INVENTION

(2) Underground water tunnels are integral parts of a city's infrastructure and they are responsible for ensuring that the effluents from sewage treatment plants are safely discharged into the environment without causing harm to public health or the ecosystem. Without proper functioning of the water tunnels, untreated effluent could potentially contaminate waterways, polluting the surrounding environment and posing a significant risk to human and animal health. Additionally, underground water tunnels are critical components in managing water resources, ensuring that the treated effluents are effectively distributed to its destination while minimizing the impact on the environment. Therefore, proper maintenance and regular inspection of underground water tunnels are essential to ensure their effective operation, promoting the importance of innovation and engineering solutions for environmental sustainability.

(3) Before the development of technologies, human beings (i.e., manual inspection) were the primary means of inspecting underground water tunnels. This process was extremely dangerous as it required individuals to be lowered into the tunnels with safety wire connections to visually detect any issues. However, this method is highly risky due to the unknown conditions within the tunnels, such as the presence of hazardous gases or volatile water flow, and the difficulty in escaping in the event of an emergency. With the advancement of technologies, remotely operated vehicles have been attempted for water tunnel inspections, but various problems have been encountered during long tunnel inspections because of harsh environments and unknown conditions, such as harsh illumination and impurities, within water tunnels. And limited access points etc. Therefore, there is a great need for alternative solutions that can ensure safety and efficiency of tunnel inspections, without human operation during the inspection.

SUMMARY OF INVENTION

(4) In light of the foregoing background, in certain embodiments, it is an object to provide a tumbler robot inspection system, which is a cutting-edge solution specifically designed to address the challenges of inspecting water tunnels. In certain embodiments, the system consists of or includes a tumbler robot, which is engineered to move seamlessly in high-speed water flows, and a releasing and retrieving system. During the inspection process, the robot is released from an access point using the releasing and retrieving system.

(5) Accordingly, in one aspect, provided is a robot for water tunnel inspection, comprising: a shell, a camera system, a lighting system, a propulsion system and a controlling system. The shell comprises an upper shell and a lower shell. The upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin. The camera system is configured to capture an image or video of a field of view of surrounding. The lighting system is configured to provide illumination at least partially for the field of view. The propulsion system is configured to provide propulsion force to the robot in water. The controlling system is configured to provide power and control operation of the robot. The robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is substantially maintained above the water, and at least a portion of the lower shell is substantially maintained under water.

(6) In another aspect, provided is a system for water tunnel inspection, comprising a robot as claimed in any one of the preceding claims; and a releasing and retrieving system, configured to release the robot to, and retrieve from the water tunnel.

(7) Other example embodiments will be described below.

(8) There are many advantages of the present disclosure. In certain embodiments, the provided devices and systems thereof are designed to work autonomously, without human operation, as it can operate in harsh underground water tunnel environments and provide accurate and detailed inspection data without putting any human life at risk.

(9) In certain embodiments, the provided devices and systems thereof provide unique design that

ensures stability, with an arc-shaped structure that prevents the devices from getting stuck in the tunnel or in sediment and a low center of gravity that prevent the same from flipping over even in unknown environments. In certain embodiments, the camera system module features panorama camera and gimbal stabilizer that provide high-resolution video records of the tunnel, while the triple stabilization system for the camera ensures stable video capture.

(10) In certain embodiments, once the inspection is completed, the robot is retrieved using the retrieving system, where it can be restored for the next assignment.

(11) In certain embodiments, the tumbler robot and inspection system thereof provide a comprehensive and efficient solution for water tunnel inspections that is safer, more reliable, and less time-consuming than traditional inspection methods.

(12) In certain embodiments, the tumbler robot and inspection system thereof represent a breakthrough solution for water tunnel inspections, leveraging innovative and efficient data collection capabilities without the need for human operation or wired connections. In certain embodiments, the seamless integration of the system's modules effectively overcomes the limitations of traditional inspection methods, while simultaneously enhancing the safety and efficiency of inspections. In certain embodiments, the system's reliable and efficient inspection capabilities enable the early identification of potential issues, facilitating timely maintenance and minimizing the risk of environmental hazards. With its pioneering design and advanced features, in certain embodiments, the tumbler robot inspection system has set a new standard for inspection technology, paving the way for a safer, cleaner, and healthier environment in the city and beyond.

(13) In certain embodiments, the interior components of the robot work in tandem to enable the tumbler robot to perform efficient and reliable inspections in water tunnel environments, providing valuable data and contributing to the maintenance and safety of critical infrastructure.

(14) In certain embodiments, the provided releasing and retrieving (RR) system is to ensure the success of the tunnel inspection by the robot, by enabling the safe and efficient operation of the tumbler robot for the inspection of water tunnel. The RR system enables the robot to be safely lowered into the tunnel for inspection and then retrieved back to the surface after completion. By implementing a robust and reliable RR system, in certain embodiments, the robot can be used to gather accurate and high-quality data for identifying defects or issues in the tunnel, ultimately ensuring the safe and efficient operation of the sewage treatment facilities. This system ensures that the robot can be operated in a controlled and safe manner, minimizing the risk of damage to the robot or to the tunnel itself.

Description

BRIEF DESCRIPTION OF FIGURES

(1) FIG. 1 is a perspective view of an example tumbler robot, according to an example embodiment.

(2) FIG. 2 is a top view of the tumbler robot, according to the same example embodiment of FIG. 1.

(3) FIG. 3 is a bottom view of the tumbler robot, according to the same example embodiment of FIG. 1.

(4) FIG. 4 is a left view of the tumbler robot, according to the same example embodiment of FIG. 1.

(5) FIG. 5 is a front view of the tumbler robot, according to the same example embodiment of FIG. 1.

(6) FIG. 6 is a perspective view of the interior of the tumbler robot, according to the same example embodiment of FIG. 1.

(7) FIG. 7 is a top view of the interior of the tumbler robot, according to the same example

embodiment of FIG. 1.

(8) FIG. 8 is a front view of the interior of the tumbler robot, according to the same example embodiment of FIG. 1.

(9) FIG. 9 is a left view of the interior of the tumbler robot, according to the same example embodiment of FIG. 1.

(10) FIG. 10 is a perspective view of the main metal structure of the tumbler robot, according to the same example embodiment of FIG. 1.

(11) FIG. 11 is a top view of the main metal structure of the tumbler robot, according to the same example embodiment of FIG. 1, showing a gimbal stabilizer connector is horizontally installed on the partition plate.

(12) FIG. 12 is a right view of the main metal structure of the tumbler robot, according to the same example embodiment of FIG. 1.

(13) FIG. 13 is a top view of the lower shell of the tumbler robot, according to the same example embodiment of FIG. 1, showing two metal connectors are designed to secure the partition plate in the lower shell.

(14) FIG. 14 is a bottom view of the lower shell of the tumbler robot, according to the same example embodiment of FIG. 1.

(15) FIG. 15 is a perspective view of the lower shell of the tumbler robot, according to the same example embodiment of FIG. 1, the sealing rubber ring and fiberglass plate of the tumbler robot, with base plate removed.

(16) FIG. 16 is a perspective view of the example LED module, according to an example embodiment.

(17) FIG. 17 is an explosion view of the LED module of FIG. 16.

(18) FIG. 18 is a perspective view of the example camera system, according to an example embodiment.

(19) FIG. 19 is a perspective view of the underwater motor with the protective frame, according to an example embodiment.

(20) FIG. 20 is a perspective view of a RR system, according to an example embodiment.

(21) FIG. 21 is a perspective view of the RR system, according to the same example embodiment of FIG. 20.

(22) FIG. 22A is a perspective view of a sliding rail track of the RR system, according to an example embodiment.

(23) FIG. 22B is a perspective view of a lifting frame of the RR system, according to an example embodiment.

(24) FIG. 22C is a perspective view of a main frame of the RR system, according to an example embodiment.

DETAILED DESCRIPTION

Definitions

(25) As used herein and in the claims, the terms “comprising” (or any related form such as “comprise” and “comprises”), “including” (or any related forms such as “include” or “includes”), “containing” (or any related forms such as “contain” or “contains”), means including the following elements but not excluding others. It shall be understood that for every embodiment in which the term “comprising” (or any related form such as “comprise” and “comprises”), “including” (or any related forms such as “include” or “includes”), or “containing” (or any related forms such as “contain” or “contains”) is used, this disclosure/application also includes alternate embodiments where the term “comprising”, “including,” or “containing,” is replaced with “consisting essentially of” or “consisting of”. These alternate embodiments that use “consisting of” or “consisting essentially of” are understood to be narrower embodiments of the “comprising”, “including,” or “containing,” embodiments.

(26) For the sake of clarity, “comprising”, “including”, “containing” and “having”, and any related

forms are open-ended terms which allows for additional elements or features beyond the named essential elements, whereas “consisting of” is a closed end term that is limited to the elements recited in the claim and excludes any element, step, or ingredient not specified in the claim.

(27) For the sake of clarity, “characterized by” or “characterized in” (together with their related forms as described above), does not limit or change the nature of whether the list of terms following it are open or closed. For example, in a claim directed towards “a device comprising A, B, C, and characterized by D, E, and F”, the elements D, E, and F are still open-ended terms and the claim is meant to include other elements due to the use of the word “comprising” earlier in the claim.

(28) As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Where a range is referred in the specification, the range is understood to include each discrete point within the range. For example, 1-7 means 1, 2, 3, 4, 5, 6, and 7.

(29) As used herein, the term “about” is understood as within a range of normal tolerance in the art and not more than $\pm 10\%$ of a stated value. By way of example only, about 50 means from 45 to 55 including all values in between. As used herein, the phrase “about” a specific value also includes the specific value, for example, about 50 includes 50. As used herein and in the claims, the terms “general” or “generally”, or “substantial” or “substantially” mean that the recited characteristic, angle, shape, state, structure, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to those of skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide. For example, an object that has a “generally” cylindrical shape would mean that the object has either an exact cylindrical shape or a nearly exact cylindrical shape. In another example, an object that is “substantially” perpendicular to a surface would mean that the object is either exactly perpendicular to the surface or nearly exactly perpendicular to the surface, e.g., has a 5% deviation.

(30) It is to be understood that terms such as “top”, “upper”, “bottom”, “lower”, “middle”, “side”, “length”, “inner”, “outer”, “interior”, “exterior”, “outside”, “vertical”, “horizontal” and the like as may be used herein, merely describe points of reference and do not limit the present invention to any particular orientation or configuration. Further, terms such as “first,” “second,” “third,” etc., merely identify one of a number of portions, components and/or points of reference as disclosed herein, and likewise do not limit the present invention to any particular configuration or orientation.

(31) As used herein and in the claims, the term “connect” refers to directly or indirectly linking or joining two or more elements or systems together, either physically, electronically or functionally.

(32) As used herein and in the claims, the term “attach” refers to link or connect one object to another, using some form of physical or mechanical connection, or to make fast, such as by tying or gluing, etc.

(33) As used herein and in the claims, the term “fix” refers to link or connect one object to another securely, using some form of physical or mechanical connection, or to make firm, stable, or stationary of an object(s) to another.

(34) As used herein and in the claims, the terms “robot”, or “tumbler robot” are interchangeable, and refer to a device designed to move through a tunnel and perform inspection tasks automatically such as collecting an image or video of the tunnel surrounding. In some examples, the robot is configured to float on water and has a low center of gravity that prevents it from flipping over, and thus can be described as tumbler.

(35) As used herein and in the claims, the term “image” are visual signal or information that covers both one or more moving pictures (videos) and/or one or more still pictures alike. A signal or information representing an image or a video will be sometimes referred to herein as “imaging data” or “data”. For clarity's sake, data may also include other types of signal or information.

(36) As used herein and in the claims, the term “camera” refers to a device that captures images

and/or videos and optionally recording the captured images or videos. In some examples, the camera contains built-in image stabilizing systems or algorithms.

(37) As used herein and in the claims, the term “center of gravity” is the point in an object or system where the weight of the object or system can be considered to be concentrated, determining the object's balance and stability.

(38) As used herein and in the claims, the term “electronic speed controller (ESC)” is a component that regulates the speed and/or direction of an electric motor (such as underwater motor) based on signals received from controlling system.

(39) As used herein and in the claims, the term “geometric center” of an object or system is the point that represents the average location of all the points in the object or system.

(40) As used herein and in the claims, the term “tunnel” or “water tunnel” refers to a structure such as pipes or channels that may be used for transporting water, wastewater or sewage water or the like. In some examples, the tunnel may be underground. The term water refers to liquids that contains water, water bodies or alike, or wastewater that may or may not include a variety of contaminants and pollutants, and may include semi-solids or solids.

(41) As used herein and in the claims, the term “operatively connects with” or “operatively connects to” refers to a functional or operational connection between two components or systems that allows them to work together or interact with each other in a specific manner. Such connection may be direct or indirect.

(42) As used herein and in the claims, “edge” refers to a boundary of a closed curve. In some examples, the edge of an opening refers to the physical boundary of an outer-shell that forms the circumference of the opening. Although the description referred to particular embodiments, the disclosure should not be construed as limited to the embodiments set forth herein.

(43) The use of “adapted to” or “configured to” herein is meant as open and inclusive language that does not foreclose devices adapted to or configured to perform additional tasks or steps.

NUMBERED EMBODIMENTS

(44) 1. A robot for water tunnel inspection, comprising: (a) a shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) a camera system, configured to capture an image or video of a field of view of surrounding; (c) a lighting system, configured to provide illumination at least partially for the field of view; (d) a propulsion system, configured to provide propulsion force to the robot in water; and (e) a controlling system, configured to provide power and control operation of the robot,

wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is substantially maintained above the water, and at least a portion of the lower shell is substantially maintained under water.

(45) 2. The robot of embodiment 1, further comprising an inertial measurement unit (IMU) operatively connected with the controlling system.

(46) 3. The robot of any one of preceding embodiments, wherein the upper shell is at least partially transparent.

(47) 4. The robot of any one of preceding embodiments, wherein density of the lower shell is higher than that of the upper shell.

(48) 5. The robot of any one of preceding embodiments, wherein the camera system further comprising: a panorama camera that provides a panoramic image of the surrounding; and/or an underwater sonar that captures an underwater image.

(49) 6. The robot of any one of preceding embodiments, further comprising an image stabilizing system that operatively connects with the camera system to improve stability of the image.

(50) 7. The robot of embodiment 6, wherein the image stabilizing system comprises: an image stabilization module that stabilizes the image from the panorama camera; and/or a gimbal stabilizer

module that is operatively connected with the panorama camera.

(51) 8. The robot of any one of preceding embodiments, wherein the controlling system further comprises a power supply system and a processing unit.

(52) 9. The robot of embodiment 8, wherein the power supply system comprises a rechargeable battery and a voltage regulator.

(53) 10. The robot of any one of preceding embodiments, wherein the propulsion system further comprises an underwater motor attached on the lower shell.

(54) 11. The robot of embodiment 10, wherein the underwater motor is operatively connected with an electronic speed controller.

(55) 12. The robot of any one of preceding embodiments, further comprising a base plate, sized and shaped to attach with the shell.

(56) 13. The robot of any one of preceding embodiments, wherein the lighting system further comprises a plurality of LED modules that are disposed on the base plate.

(57) 14. The robot of embodiment 13, wherein individual LED module comprises a LED array, a heat sink and a waterproof LED shell.

(58) 15. The robot of any one of preceding embodiments, wherein the overall shape of the shell is substantially spherical.

(59) 16. A tumbler robot for water tunnel inspection, comprising: (a) a spherical shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) a camera system, configured to capture an image or video of a field of view of surrounding; (c) a lighting system, configured to provide illumination at least partially for the field of view; (d) a propulsion system, configured to provide propulsion force to the robot in water; (e) a controlling system, configured to provide power and control operation of the robot; (f) an inertial measurement unit (IMU), operatively connected with the controlling system; and (g) a base plate, attached to the shell, wherein the camera system further comprising:

two vs that are orthogonally arranged to provide a panoramic image of the surrounding;

a gimbal stabilizer that is operatively connected with the two panorama cameras; and

an underwater sonar that captures an underwater image; wherein the lighting system further comprises a plurality of LED modules that are disposed on the base plate; wherein the propulsion system further comprises two underwater motors attached on the lower shell; and wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is substantially maintained above the water, and at least a portion of the lower shell is substantially maintained under water.

(60) 17. A system for water tunnel inspection, comprising: a robot as described in any one of the preceding embodiments; and a releasing and retrieving system, configured to release the robot to, and retrieve from the water tunnel.

(61) 18. The system of embodiment 17, wherein the releasing and retrieving system comprises: a lifting frame, configured to receive the robot; a sliding rail track, configured to be fixable on a substrate; a main frame, configured to at least partially receive the lifting frame and to be movable along the sliding rail track; and a winch system, configured to be connectable with the robot, wherein the winch system is configured to release the robot to, and retrieve from the water tunnel.

(62) 19. The system of embodiment 18, wherein the lifting frame is configured to be switchable between an upper position and a lower position relative to the main frame, such that the robot is lifted from or lowered towards the water tunnel, respectively.

(63) 20. The system of embodiment 17 or embodiment 18, wherein the main frame is configured to be switchable between a working position and a preparing position relative to the sliding rail track, such that the robot is moved closer to or away from the water tunnel, respectively.

EXAMPLES

(64) Provided herein are examples that describe in more detail certain embodiments of the present

disclosure. The examples provided herein are merely for illustrative purposes and are not meant to limit the scope of the invention in any way. All references given below and elsewhere in the present application are hereby included by reference.

(65) Overview of the System Architecture

(66) In certain embodiments, the tumbler robot and system thereof are complex and multi-functional systems designed to perform tunnel inspection such as in underground water tunnels. In certain embodiments, it contains various subsystems, including the structural shells, lighting system, camera system, rotation stabilization system, power supply system, supportive designs, and releasing and retrieving (RR) system, etc.

(67) Description of the Major Subsystems

(68) In certain embodiments, the structural shells, which consist of or contains an upper shell, a base plate with an impact-resistant rubber, and a lower shell. These structures are used for protecting the electronic components of the robot from water damage and collision. In some embodiments, the upper shell is made of transparent and hard materials such as acrylic, providing transparency and durability for the interior camera system. In some embodiments, the base plate is fabricated from metals or alloys such as aluminum alloy, offering a lightweight yet sturdy foundation for the placement of LED modules within the lighting system. In some embodiments, the lower shell is made of metals or alloys such as stainless steel, providing the necessary strength and impact resistance to protect the electronics.

(69) In certain embodiments, the lighting system is configured to provide illumination for the camera system to capture high-quality video footage. In certain embodiments, the lighting system includes eight high-power LED module that are substantially, equidistantly positioned on the base plate, around the circumference of the robot to provide uniform illumination across the entire field of view of the camera. In certain embodiments, each LED module is embedded with a heat sink and connected to a heat dissipation plate to prevent heat from transmitting into the inspection robot.

(70) In certain embodiments, the camera system is configured to capture high-resolution video footage of the tunnel interior. In certain embodiments, the camera system includes two high-resolution panorama cameras that can provide a panoramic view without blind spots, a gimbal stabilizer, and an underwater sonar that captures precise and detailed underwater image. This configuration ensures a comprehensive video capture regardless of the tunnel's harsh conditions.

(71) In certain embodiments, the rotation stabilization system is designed to address the six degrees of freedom motion and sudden changes in speed due to various jolts and collisions encountered in the tunnel. In certain embodiments, the rotation stabilization system includes a triple stabilization system that consists of or contains a camera's built-in video stabilization algorithms, a high-performance three-axis rotation gimbal stabilizer algorithm, and an underwater propulsion system. It includes two underwater motors with Electronic Speed Controllers (ESCs), an Inertial Measurement Unit (IMU), and an industrial computer to resist the yaw rotation of the tumbler robot and keep it stable in high-speed water flow.

(72) In certain embodiments, the power supply system provides power control of the tumbler robot. In certain embodiments, the power supply system contains a rechargeable battery pack and voltage regulator. In certain embodiments, the battery pack provides energy for at least the lighting system and rotation stabilization system of the robot. In certain embodiments, the voltage regulator is responsible for distributing the voltage from the battery pack to the subsystems of the tumbler robot.

(73) In certain embodiments, the above mentioned modules (including the lighting system, the camera system, the rotation stabilization system, the power supply system) are constructed and arranged to provide the best position of the center of mass to improve the control performance and topple resistance capability of the robot. In certain embodiments, a sealing rubber is optionally employed to effectively seal the connection between the upper shell and the base plate, providing a watertight seal. In certain embodiments, waterproof gaskets and sealants are optionally applied to

screw openings, and a pressure relief valve is used to control the pressure inside the robot and prevent damage due to potential battery pack failure. Waterproof connectors facilitate convenient data transmission and debugging processes. Mechanical fasteners are provided ensure security during the releasing and retrieval procedure of the robot.

(74) In certain embodiments, the provided system contains the robot and additionally a RR system, providing a safe and efficient means of lowering the robot into the tunnel for inspection and retrieving it back to the surface. In certain embodiments, the RR system contains a sliding rail track, a main frame, a lifting frame, and a winch system. The structural components (a sliding rail track, a main frame, a lifting frame) provide a stable and secure platform for the robot to move vertically and horizontally, while the winch system provides the necessary force to release and retrieve the robot. In certain embodiments, the RR system is designed to withstand the harsh environment of the tunnel while ensuring the safety of personnel and the environment.

Example 1

(75) FIGS. **1-19** show an example device **1000** for water tunnel inspection. The example robot **1000** contains various interconnected subsystems that collaborate to achieve efficient and innovative data collection in water tunnel inspections. The robot **1000** generally contains a shell **1100**, a camera system **1600**, a lighting system **1700**, a propulsion system **1800** and a controlling system **1900**. FIGS. **1-5** show different views of the overview of the example robot **1000**. FIGS. **6-9** show the interior components inside the robot **1000** after the upper shell **1110** is removed. FIGS. **10-14** show the supporting elements after the upper shell **1110**, the camera system **1600** and controlling system **1900** are removed. FIG. **15** shows the lower shell **1120**, the sealing rubber ring **1124** and fiberglass plate **1300** of the tumbler robot, with the base plate **1400** removed. FIGS. **16-19** show the details of LED module **1710**, camera system **1600** and motor, respectively. Details of each component will be described in more detail below.

(76) Shell

(77) FIGS. **1-5** show a perspective view of the tumbler robot **1000**. The shell **1100** is formed from an upper shell **1110** and a lower shell **1120**, which provides safeguarding and support for the robot's interior components such as electronic elements from water/moisture damage and collisions, and also provides a support for fixing or attaching various exterior components, such as the base plate **1400**, lighting system **1700** and propulsion system **1800**, etc. The upper shell **1110** and the lower shell **1120** are sized and shaped to fit for engaging with each other, together defining a closed cavity therewithin. The closed cavity is a substantially watertight compartment used for accommodating the interior components of the robot, such as panorama cameras **1610** of the camera system **1600** and the controlling system **1900**.

(78) In this example, the upper shell **1110** and the lower shell **1120** are generally hemispherical-shaped, thereby forming a generally spherical-shaped shell when they are connected with each other. The engaging edges of the upper shell **1110** and the lower shell **1120** are configured to match each other. In this example, the upper shell **1110** is made of acrylic and is substantially transparent, allowing the camera system **1600** disposed within the shell to capture an image or video of a field of view of surrounding. The upper shell **1110** acts as a protective outer layer, shielding the interior components from external elements. In this example, the lower shell **1120** is made of stainless steel. Such combination of using a plastic upper shell **1110** and a metal lower shell **1120** makes the overall shell has a center of gravity closer to the lower shell **1120** than the upper shell **1110**, and thus lower than the geometric center. Now referring to FIG. **15**, additionally, the lower shell **1120** includes a sealing rubber **1124** ring along the open end to seal the engaging edges between the upper shell **1110** and the lower shell **1120**, thereby enhancing water resistance, safeguarding the interior components from potential damage caused by water infiltration.

(79) Now referring to FIGS. **4-5**, the lower shell **1120** further comprises multiple waterproof connectors **1121** that are disposed closer to the open end of the lower shell **1120**, beneath the base plate **1400** when installed. In this example, the lower shell **1120** of the robot houses three

waterproof connectors **1121** that are evenly distributed and are configured to operatively and electronically connect with the interior electronic components such as the controlling system **1900**. These connectors **1121** serve the purpose of debugging and transmitting collected data from the robot to external devices. Such positioning of the waterproof connectors **1121** on the lower shell **1120**, beneath the base plate **1400**, facilitates convenient access and reliable data transfer from the robot **1000**.

(80) Now referring to FIG. **12**, showing the right view of the metal structure (including the lower shell **1120**) of the tumbler robot **1000**. The lower shell **1120** further contains a pressure relief valve **1122** that is disposed closer to the open end of the lower shell **1120** and below the base plate **1400**, facing parallel to the underwater motors **1810**. The pressure relief valve **1122** controls the pressure inside the robot and prevents damage due to potential battery pack **1910** failure. The lower shell **1120** further contains an empty space **1123** which is designed for housing the underwater sonar **1620**.

(81) Now referring to FIGS. **12-14**, the lower shell **1120** further contains a lip portion **1128** horizontally extended away from the open end. The lip portion **1128** is configured to engage with the upper shell **1110** and attaching or fixing the base plate **1400**, respectively.

(82) Now referring to FIG. **13**, showing the top view of the lower shell **1120** of the tumbler robot, with the partition plate **1200** removed. Two metal partition plate connectors **1126** are provided in the interior of the lower shell **1120**, configured to fix a partition plate **1200** to the lower shell **1120**, ensuring structural stability and integrity. IMU connector **1011** that is configured to connect the IMU **1010** and an empty space **1127** are also provided in the interior of the lower shell **1120**.

(83) FIG. **14** shows the bottom view of the lower shell **1120** of the example robot **1000**. Two underwater motor connectors **1125** are provided on the lower shell **1120** and configured to attach the protective shells of the underwater motors **1810**, respectively.

(84) Other Supporting Structures

(85) FIGS. **10-11** show the main supporting structures of the tumbler robot. In addition to the shell, the main supporting structures contain a base plate **1400**, a partition plate **1200**, multiple heat-dissipation plates **1301**, an underwater motor protective frame **1820**, and a gimbal stabilizer connector **1521**. In this example, these main supporting structures (except the upper shell **1110**) are made of metals or alloys. Additionally, the main supporting structures contains a controlling system connector that facilitates a stable connection between the metal structure (partition plate **1200**) and the controlling system **1900**, enabling a stable operation of the robot. In this example, the controlling system connector is or contains an industrial computer connector and the controlling system **1900** is or contains an industrial computer **1920**. The careful design and arrangement of these main supporting structures guarantee the structural integrity of the tumbler robot.

(86) Base Plate

(87) FIGS. **1-7, 10-12** show the base plate **1400** connected with the lower shell **1120** of the robot. In this example, the base plate **1400** is generally a ring-shaped metal sheet containing multiple holes to minimize weight while maintaining structural integrity. In this example, the base plate **1400** is made of aluminum alloy. The base plate **1400** is sized and shaped to match the outer rim close to or at the open end of the lower shell **1120**. The base plate **1400** further contains a mechanical fastener **1402** configured to connect with a rope for the RR system. The base plate **1400** serves as a robust foundation, providing stability and support to the entire structure of the robot. In this example, an impact-resistant rubber **1401** ring is provided which is attached around the outer rim of the base plate **1400**, to provide additional protection for the robot **1000**. The base plate **1400** contributes to the structural integrity of the robot and provides support to the lighting system **1700**. The base plate **1400** also provides support to the lighting system **1700**. In this example, the lighting system **1700** is disposed on the base plate **1400**.

(88) Partition Plate

(89) FIGS. **7, 9-11** show the partition plate **1200**, which is one of the interior components that

provides structural support and organization for other interior components within the robot. In this example, the partition plate **1200** is a flat metal sheet containing multiple holes, being horizontally positioned inside the lower shell **1120** of the tumbler robot. In this example, the partition plate **1200** is fixed onto the lower shell **1120** by two partition plate connectors **1126** (FIG. **13**). The horizontally positioned partition plate **1200** serves as a fundamental reference point or support, ensuring a stable and level base for the other systems or components within the robot. For example, the controlling system **1900** including the battery pack **1910** and industrial computer **1920** are fixed to the partition plate **1200**. The strategic positioning of the battery pack **1910** and industrial computer **1920** onto the partition plate **1200** guarantees that the weight distribution is centered directly beneath the robot's geometry center, promoting optimal stability and balance during operation. The partition plate **1200** also helps organizing and segregating the interior components, ensuring an efficient layout of the interior components.

(90) In this example, the partition plate **1200** further contains an empty space **1127** for housing an underwater sonar, facilitating the installation and placement of the underwater sonar. The partition plate **1200** further connects with an IMU connector **1011** (FIG. **13**) which is configured and positioned to facilitate the connection of the IMU **1010** to the partition plate **1200**.

(91) FIGS. **10-11** show the top view of the metal structure of the tumbler robot **1000**. The gimbal stabilizer connector **1521** is sized and shaped to connect with gimbal stabilizer **1520** and is horizontally installed on the partition plate **1200**, with an opening below for placing the underwater sonar. The gimbal stabilizer connector **1521** serves as the connecting element that integrates the gimbal stabilizer **1520**, securely attaching it to the partition plate **1200** and thus to the robot. Below the gimbal stabilizer connector **1521**, there is a designated empty space **1123** that accommodates the placement of the underwater sonar, ensuring optimal positioning for capturing precise underwater imaging data.

(92) Other Interior Components

(93) FIGS. **6-11** show various views of the interior of the example robot **1000**, with the upper shell **1110** removed. In addition to the partition plate **1200**, the interior of the tumbler robot includes various interior components, including the controlling system **1900** and part of the camera system **1600**. For example, interior components include panorama cameras **1610**, three batteries, two ESCs **1930** for underwater motors **1810**, an industrial computer **1920**, an IMU **1010**, etc. Details will be described further in detail below.

(94) Camera System

(95) FIGS. **6-9** and **18** show the camera system **1600** of the example robot **1000**. In this example, the camera system **1600** contains one or more panorama cameras **1610**, which are connected through the panorama camera connector **1611**, which is further connected with a three-axis rotation gimbal stabilizer **1520**, ensuring stable and high-resolution image (or video) capture. In this example, the image capture is a video capture. The camera system **1600** is operatively connected with the controlling system **1900**. In some examples, the camera system **1600** is configured to capture clear 3k resolution videos of the tunnel at about 60 FPS. In some examples, the panorama cameras **1610** in the camera system **1600** contains built-in stabilizing algorithms and is regarded as image stabilization module, a part of the rotation stabilization system.

(96) Now referring to FIG. **8**, the gimbal stabilizer **1520** is connected to the partition plate **1200** by a gimbal stabilizer connector **1521**. In this example, the camera system **1600** contains two high-performance panorama cameras **1610** strategically positioned to capture a wide field of view. To ensure stable and steady footage, a gimbal stabilizer **1520** is employed, which is connected to the panorama cameras **1610** by the panorama camera connector **1611**, ensuring a secure attachment while allowing for smooth movement and adjustment. The gimbal stabilizer **1520** is positioned near the center of gravity of the robot, enhancing balance and minimizing camera vibrations during operation. In some examples, the gimbal stabilizer **1520** is regarded as a gimbal stabilizer module, part of the rotation stabilization system.

(97) Now referring to FIG. 9, the two panoramic cameras are positioned orthogonally to provide a comprehensive, panoramic view to avoid blind spots. This configuration enables the robot to capture a wide range of visual data during inspections. The two panorama cameras **1610** are connected to the gimbal stabilizer **1520** through the specialized panorama camera connector **1611**, ensuring precise alignment and stability of the cameras during operation.

(98) Now referring to FIG. 18, showing the details of camera system **1600** of the tumbler robot. The top panorama camera **1610** is seamlessly connected to the bottom panorama camera **1610**, and together they form a comprehensive imaging setup. The bottom panoramic camera is closely attached to the gimbal stabilizer **1520** using a plate connector (panorama camera connector) **1611**, ensuring stability positioning during operation. This integrated camera system **1600** enables the tumbler robot to capture panoramic views and maintain stable recording, enhancing its effectiveness in inspection.

(99) Underwater Sonar

(100) FIGS. 3-5 show the underwater sonar **1620** positioned at the bottom of the lower shell **1120**. FIG. 3 shows that the underwater sonar **1620** contains an emitting array **1621** and a receiving array **1622**, which work together to accurately transmit and process sonar signals, providing high-quality underwater imaging. The underwater sonar **1620** can be regarded as part of the camera system **1600** to provide additional images such as sonar images. The underwater sonar **1620** is operatively connected with the controlling system **1900**. The main body of the underwater sonar **1620** and its communication port **1623** enable underwater imaging capabilities. The underwater sonar **1620** is positioned directly beneath the lower shell **1120** of the robot (as exterior component) to provide underwater image information. Directly beneath the robot, the underwater sonar **1620** captures precise and detailed image information for thorough inspections of water tunnels.

(101) Now referring to FIG. 5, showing a front view of the tumbler robot. The underwater sonar system **1620** is positioned directly beneath the robot. The underwater sonar **1620** further includes a main body **1620** and a communication port **1623**. The main body of the sonar **1620** captures sonar imaging data during inspection operations. The communication port **1623** of the sonar **1623** serves as a seamless data transmission link between the sonar system and the robot's interior industrial computer **1920**. Now referring back to FIGS. 3-5. The underwater sonar **1620** is firmly fixed to the partition plate **1200** using dedicated metal underwater sonar connectors **1202** (FIG. 14) received in the empty space **1123**, enhancing the overall structural stability of the sensor. A waterproof connector **1203** (FIG. 14) is also operatively connected with the underwater sonar **1620**, guaranteeing reliable and watertight connectivity.

(102) Lighting System

(103) FIGS. 1-11 show the lighting system **1700** of the robot **1000**. The lighting system **1700** contains multiple light modules **1710** within the lighting system **1700** ensure sufficient illumination to the field of view, facilitating clear visibility for the camera system **1600** to capture high-resolution video frames. In this example, the light modules are LED modules **1710** and the lighting system **1700** is operatively connected with the controlling system **1900**.

(104) Now referring to FIG. 2, showing the top view of the tumbler robot. In this example, the tumbler robot includes eight LED modules **1710**, with each light module is evenly disposed on the upper surface of the base plate **1400** to provide uniform illumination to the surroundings. To prevent overheating and optimize performance, each LED module **1710** is equipped with a heat sink **1714** that are fixed on the bottom side of the base plate **1400** to efficiently dissipate generated heat by the LED module **1710**. This configuration allows the tumbler robot to offer consistent and well-balanced illumination, significantly enhancing visibility during its operational tasks.

(105) Now referring to FIG. 4, showing the left view of the tumbler robot. A heat-dissipation plate **1301** is provided beneath each LED module **1710** to enhance heat dissipation, ensuring the LED modules **1710** perform optimally and have an extended lifespan. In this example, the heat-dissipation plate **1301** (FIG. 15) is fixed on the bottom surface of the base plate **1400**, juxtaposing

the corresponding LED module **1710** disposed on the opposing, upper surface of the base plate **1400**.

(106) Now referring to FIG. **15**, showing a perspective view of the lower shell **1120** of the tumbler robot without base plate **1400**. The opposing ends of each heat-dissipation plate **1301** are connected to the base plate **1400** through two fiberglass plates **1300**. The heat-dissipation plate **1301** acts as a robust mounting base for each LED module **1710**, ensuring effective heat dissipation for optimal performance. The heat-dissipation plate **1301** is firmly attached to the base plate **1400** using two fiberglass plates **1300**, creating a sturdy structure that enables efficient heat transfer and dissipation.

(107) Now referring to FIGS. **16-17**, showing an example LED module **1710** of the tumbler robot **1000**. Each LED module **1710** contains a high-power LED array **1713**, a heat sink **1714**, and a waterproof LED shell **1716** having a glass cover **1712**. The heat sink **1714** helps dissipate the heat generated by the LED array **1713**, while the waterproof LED shell **1716** together with the glass cover **1712** provides protection to the LED module **1710** against water ingress, ensuring reliable operation in challenging environments. The high-power LED array **1713** delivers powerful and efficient illumination for various applications. To ensure optimal performance and longevity, a heat sink **1714** is incorporated to additionally dissipate the heat generated during operation. FIG. **17** shows the explosion view of LED module **1710**. The LED circuit board **1711** is securely adhered to the glass cover **1712**, forming LED light. The components on the LED circuit board **1711** are directly attached to the heat sink **1714**, while the LED light is protected by a waterproof LED shell **1716**.

(108) Propulsion System

(109) FIGS. **1, 3, 4-6, 8-10** and **19** show a propulsion system **1800**. FIG. **1** shows the propulsion system **1800** containing two underwater motors **1810**, each having a protective frame **1820** work in tandem to propel and stabilize the robot's movement. Mechanical motor fasteners are provided **1402** (FIG. **10**) to secure the components together. These modular elements synergistically overcome the limitations of traditional inspection methods, ensuring safe and efficient inspections in the water tunnels. Now referring to FIGS. **3** and **5**, showing the bottom view and the front view of the tumbler robot, respectively. Two underwater motors **1810** are symmetrically distributed underneath the lower shell **1120** of the tumbler robot and secured by the protective frames **1820**, ensuring stability and reliable performance in challenging underwater environments.

(110) The two underwater motors **1810** are symmetrically placed on the lower shell **1120**, with their orientation extending away from the lower shell **1120**.

(111) Now referring to FIG. **19**, showing a detailed view of an example underwater motor **1810** with the protective frame **1820** of the tumbler robot. The main body of the underwater motor **1810** is protected by a metal protective frame **1820**, which is connected to the lower shell **1120** through a motor connector **1814** to ensure structural stability. The main body of the underwater motor **1810**, comprising the rotor **1811** and blades **1812**, is received by a robust metal protective frame **1820**. This protective frame **1820** ensures the structural stability and integrity of the underwater motor **1810**, safeguarding it from potential impacts and external forces. The protective frame **1820** is securely connected to the lower shell **1120** through a dedicated connector **1814**, forming a reliable and rigid structure during operations.

(112) Controlling System

(113) FIGS. **6-7** show a controlling system **1900**, which is configured to provide power and control operation of the robot **1000**. In this example, the controlling system **1900** contains a power supply system **1940** and processing unit, electronically and operatively connects with each other and other systems. In this example, the power supply system **1940** contains a rechargeable battery pack **1910** and a voltage regulator (not shown). The processing unit contains an industrial computer **1920**. The battery pack **1910** and the industrial computer **1920** are positioned such that the overall weight is centered closer to the lower portion of the robot, and thus lower than the geometric center. The voltage regulator is configured for distributing the voltage from the battery pack **1910** to the

subsystems of the tumbler robot.

(114) In this example, the battery pack **1910** houses three rechargeable batteries, supplying the necessary power to other systems such as camera system **1600**, lighting system **1700** and the propulsion system **1800**, for prolonged operation. The rechargeable battery pack **1910** in the power supply system **1940** can support prolonged hours of operation of the robot without external electrical supply. The power supply unit is also equipped with a battery connector, either to recharge the battery pack **1910** or to allow the user to replace the discharged battery with a spare fully charged battery during extended use.

(115) The industrial computer **1920** serves as the central processing unit (e.g., microprocessors, ASICs, FPGAs, GPUs, CPUs, processing cores, or the like), facilitating receiving, storing, processing and/or transmitting data (such as images, videos and/or sonar data) and system control. For example, the operating system is optionally integrated one or more wired or wireless communication interfaces, such as local area network (LAN), USB, Wi-fi, Bluetooth, Zigbee or the like etc., for data transmission, debugging and/or system update. For example, the processing unit further includes a non-transitory computer readable medium to store computer readable programs such that when it is executed by the microprocessor or industrial computer **1920**, it gives signals and control the propulsion system **1800**, lighting system **1700** and/or camera system **1600** of the robot to perform and operate. For example, the non-transitory computer readable medium includes any known type of data storage and/or transmission media, including magnetic media, optical media, random access memory (RAM), read-only memory (ROM), a data cache, a data object, etc. Moreover, memory may reside at a single physical location, comprising one or more types of data storage, or be distributed across a plurality of physical systems in various forms. For example, the processing unit further includes one or more input/output (I/O) devices, one or more programming (e.g., I/O) interfaces, and one or more communication buses for interconnecting these and various other components. In some examples, the one or more communication buses include circuitry that interconnects and controls communications between system components.

(116) In this example, two electronic speed controller (ESCs) **1930** are electronically connected with the controlling system **1900** and the underwater motors **1810** to operate and control the underwater motors **1810**, enabling precise and controlled movement of the robot in water tunnels.

(117) In this example, an inertial measurement unit (IMU) **1010** is provided and is operatively connected with the controlling system **1900**, to ensure accurate orientation and motion sensing capabilities, enhancing the robot's stability and maneuverability. For example, IMU **1010** is configured to provide accurate orientation and motion data to controlling system **1900**, so as to operate the propulsion system **1800** in response to orientation and motion data. In this example, the IMU **1010** is disposed proximate to the underwater sonar, connected to the partition plate **1200** by the IMU connector **1011**. The IMU **1010** is positioned near the robot's center of gravity, enabling precise motion sensing and accurate orientation determination. In some examples, IMU **1010** is regarded as part of the rotation stabilization system.

(118) Releasing and Retrieving (RR) System

(119) FIGS. **20-21** and **22A-C** show an example configuration of the RR system. The RR system contains a main frame, lifting frame **2100**, sliding rail track **2200** and a winch system **2400**. The sliding rail track **2200**, main frame **2300**, and lifting frame **2100** are designed to provide a stable and secure platform for the robot to move vertically, and to support the winch system **2400** to release and retrieve the robot. The design of the structure provides the necessary degree of freedom for the robot to move horizontally, which is necessary for successful release and retrieval of the robot on the work platform. Now referring to FIGS. **20**, **21** and **22C**, the main frame **2300** contains a vertical sliding track **2310**, and a winch receiving portion **2320** to install the winch system **2400**. The vertical sliding track **2310** is sized and shaped to receive at least a portion of the lifting frame **2100**, enabling the lifting frame **2100** to move or slide vertically within the vertical sliding track **2310**, thereby providing precise adjustments to the vertical release position of the robot. The main

frame **2300** is also configured to be able to slide along the rail track horizontally, enabling adjustment of the horizontal release position of the robot and be switchable between a working position and a preparing position.

(120) Now referring to FIGS. **20**, **21** and **22B**, the lifting frame **2100** contains a rectangular head portion **2110** and a triangular cylindrical portion **2120**. The lifting frame **2100** is sized and shaped such that it can be switchable between an upper position and a lower position relative to the main frame **2300**, such that the robot can be lifted from or lowered towards the water tunnel, respectively. The lifting frame **2100** is configured to receive the robot and provides flexibility in adjusting the release height of the robot. In this example, the lifting frame **2100** is configured to securely fix with the robot during releasing or retrieval processes by a rope or wire through the mechanical fastener. In some examples, the rope is a floating nylon synthetic rope. The lifting frame **2100** is configured for the secure attachment and release of the tumbler robot. To guarantee structural integrity and safety, the lifting frame **2100** is constructed using a robust, triangular cylindrical structure and made of durable materials such as metals or alloys such as stainless steel, ensuring exceptional structural integrity and safety. This construction choice guarantees the lifting frame's ability to withstand the rigors of its intended use and ensures the safety of the tumbler robot during its deployment and retrieval processes.

(121) Now referring to FIGS. **20**, **21** and **22C**, the winch system **2400** is disposed on the main frame **2300** away from the vertical sliding track **2310** and configured to release the robot to, and retrieve from the water tunnel by controlling winding state of the rope. The lifting frame **2100** offers flexibility in adjusting the release height of the robot, facilitating efficient deployment of the robot. The winch system **2400** enables smooth and controlled movements of releasing and retrieving the robot. The winch system **2400** is constructed using durable materials to withstand prolonged usage and resist wear and tear, ensuring long-term reliability.

(122) Now referring to FIGS. **20**, **21** and **22A**, the sliding rail track **2200** is supported by multiple sleepers **2220** and secured onto a substrate such as the ground or concrete platform with anchor bolts **2230**, ensuring robustness and reliability. For example, the anchor bolts **2230** are metal bolts such as expansion screws.

(123) Now referring to FIG. **20**, showing Retrieve state of the RR system. In the retrieve state, the main frame **2300** is positioned at a preparing position on the sliding rail track **2200**, away from the release site (near the water tunnel), while the robot (not shown) is securely positioned at an upper position in the lifting frame **2100**.

(124) Now referring to FIG. **21**, showing Release state of the RR system. In the release state, the main frame **2300** is firmly attached to the sliding rail track **2200** at the working position, while the robot (not shown) is securely positioned at the end of the lifting frame **2100**, ready for deployment. The vertical movement of the robot is achieved through the lifting frame **2100**, utilizing the vertical sliding track **2310** of the main frame **2300**. Prior to the release or retrieval operation, the horizontal movement is adjusted to ensure precise positioning. The smooth and controlled movements of the system are supported by the winch system **2400**, enabling reliable and controlled operations. The sliding rail track **2200**, secured by metal bolts **2230** and sleepers **2220**, maintains stability and robustness throughout the operation, ensuring the system operates safely and effectively.

(125) In some examples, the RR system further contains a crane and a manual forklift. The crane is configured for transporting materials from the work site to the working area, while the manual forklift is configured for moving materials within the substrate such as cement platform.

(126) General Operation of Robots and Systems

(127) The operation of the robot and system thereof will be described. In some examples, provided is methods of using the robots and systems thereof in water tunnel inspection. In some examples, provided is methods of water tunnel inspection. Such operations and methods generally include the following steps: 1. Installing the robot onto the RR system at a retrieve state; 2. Releasing the robot into the water tunnel from the RR system at a release state, allowing the robot to operate so as to

collect imaging data; and 3. Retrieving the robot from the water tunnel from the RR system at the retrieve state.

(128) In some examples, the releasing and retrieving steps are performed with the RR system.

(129) Releasing and Retrieving of the Inspection Robot by the RR System

(130) The detailed steps of releasing and retrieving of the robot will be described. The general process involves the steps of: releasing the robot into the water, allowing it to complete its mission, and then retrieving it from the water, such as using the winch system **2400**. In some examples, the release process includes the steps of: 1. lifting the robot to the designated release height using the lifting frame **2100**; 2. lowering the robot into the water by the winch system **2400**, with the floating nylon synthetic rope providing the necessary buoyancy; 3. allowing the robot to move freely to complete its mission, while maintaining tension on the rope by the winch system **2400** to ensure control and stability; 4. once the mission is complete, retrieving the robot by the winch system **2400**, pulling it back to the release height using the floating nylon synthetic rope; 5. raising the robot to the main frame **2300** by the lifting frame **2100**, where it can be safely secured and prepared for the next mission.

(131) By following these steps, the RR system can release and retrieve the inspection robot safely and efficiently, ensuring the success of the site trial.

(132) In some examples, the process of releasing the robot further involves steps of: 1. positioning it in the lifting frame **2100** at an upper position and binding the rope to the ring when the main frame **2300** is in the preparing position; 2. moving the main frame **2300** to the working position (close to the tunnel) along the sliding rail, lowering the robot under the beam and releasing the same to a desired distance; 3. moving the lifting frame **2100** to the lower position so that the rope is close to the beam, and fixing the main frame **2300** to the substrate by screws; 4. releasing the robot into the tunnel entrance at a lower position (such as about 200 meters below the beam). 5. optionally recording a video during these processes to confirm that the robot is in working condition.

(133) By following these steps, the robot can be deployed safely and efficiently, ensuring the success of the site trial.

(134) In some examples, the process of retrieving the robot further includes the following steps: 1. after the inspection work is completed, pulling the robot back slowly by rewinding the rope by the winch system **2400**; 2. optionally lowering the lifting frame **2100** to the lower position 3. lifting the lifting frame **2100** together with the robot to the upper position 4. releasing the main frame **2300** from the sliding rail by removing the screws and moving the same to preparing position (away from the tunnel). 5. releasing the robot such as for cleaning and data collection

(135) By following these steps, the robot can be retrieved safely and efficiently, minimizing the potential for any damage to the robot or harm to personnel involved in the operation.

(136) The exemplary embodiments of the present invention are thus fully described. Although the description referred to particular embodiments, it will be clear to one skilled in the art that the present invention may be practiced with variation of these specific details. Hence this invention should not be construed as limited to the embodiments set forth herein.

(137) Devices, systems and methods discussed within different figures and paragraphs can be added to or exchanged with other devices, systems and methods in other figures or paragraphs. Further, specific numerical data values (such as specific quantities, numbers, categories, etc.) or other specific information should be interpreted as illustrative for discussing example embodiments. Such specific information is not provided to limit example embodiment.

(138) For example, in certain embodiments, lighting system comprises eight LED modules, but different types of lighting elements, other numbers (e.g., one, two, three, four, five, six, seven, eight, nine, ten or more), sizes and shapes (oval, circular, triangular) at various locations may be used.

(139) For example, in certain embodiments, the upper shell in the described examples are made of

acrylic, but other types of durable transparent or semi transparent materials may be used. For example, in certain embodiments, the upper shell in the described examples are substantially transparent, but in other examples, only the area within the field of view of the panoramic camera is substantially transparent and the rest of the area may be semi-transparent or opaque, colored or colorless, and may be made in different materials. For example, in certain embodiments, the robot moves by underwater motors, but other forms of propulsion mechanisms may be used.

(140) For example, in certain embodiments, main frame is configured to be movable along a transverse axis relative to the sliding rail, but may be configured to be movable along multiple directions and axes according to the practical need.

(141) For example, in certain embodiments, lifting frame is configured to be movable along a vertical axis relative to the main frame, but may be configured to be movable along multiple directions and axes according to the practical need.

(142) For example, in certain embodiments, the shell generally is in spherical shape, but other shapes with round edges (such as ellipsoid, egg, pear, mushroom, etc.) may also be used. For example, in certain embodiments, the tumbler robot includes three waterproof connectors, but different types of connectors, other numbers (e.g., one, two, three, four, five, six, seven, eight, nine, ten or more), sizes and shapes (oval, circular, triangular) at various locations may be used.

(143) For example, in certain embodiments, various main structural components are made of metals or alloys such as aluminum alloy or stainless steel, but other durable materials known in the art may be used.

(144) For example, in certain embodiments, certain systems such as the lighting system in some examples are operatively connected with the controlling system, but separate power supply and controlling unit may be used instead.

(145) For example, in certain embodiments, the robot is released and retrieved by the RR system, but the robot can be used independently without the RR system, or can be used by other suitable systems to retrieve and release the robot.

(146) For example, in certain embodiments, the lighting system is disposed on the base plate, but it can be disposed at other locations such as directly on the upper shell or inside the cavity.

(147) For example, in certain embodiments, the base plate is in ring-shaped, but other shapes may be used, such as oval, egg, etc.

(148) For example, in certain embodiments, two panoramic cameras orthogonally arranged are used, but different types of cameras, other numbers (e.g., one, two, three, four, five, six, seven, eight, nine, ten or more), sizes and shapes (oval, circular, triangular) at various locations and different arrangements may be used.

Claims

1. A robot for water tunnel inspection, comprising: (a) a shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) one or more panorama cameras that capture an image or video of a field of view of surrounding; (c) a plurality of light modules that provide illumination at least partially for the field of view; (d) one or more underwater motors that provide propulsion force to the robot in water; and (e) a power supply and processing unit that provide power and control operation of the robot, wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is maintained above the water, and at least a portion of the lower shell is maintained under water.

2. The robot of claim 1, further comprising an inertial measurement unit (IMU) operatively connected with the controlling system.

3. The robot of claim 1, wherein the upper shell is at least partially transparent.

4. The robot of claim 1, wherein density of the lower shell is higher than that of the upper shell.
5. The robot of claim 1, wherein the robot further comprises an underwater sonar that captures an underwater image.
6. The robot of claim 1, wherein the one or more panorama cameras further operatively connect with a gimbal stabilizer.
7. The robot of claim 1, wherein the power supply comprises a rechargeable battery and a voltage regulator.
8. The robot of claim 1, wherein the one or more underwater motors are attached on the lower shell.
9. The robot of claim 8, wherein the one or more underwater motors are operatively connected with an electronic speed controller.
10. The robot of claim 1, further comprising a base plate, sized and shaped to attach with the shell.
11. The robot of claim 1, wherein the plurality of light modules comprises a plurality of LED modules that are disposed on the base plate.
12. The robot of claim 11, wherein individual LED module comprises a LED array, a heat sink and a waterproof LED shell.
13. The robot of claim 1, wherein the overall shape of the shell is substantially spherical with at most a 5% deviation.
14. A tumbler robot for water tunnel inspection, comprising: (a) a spherical shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) two panorama cameras that are orthogonally arranged to provide a panoramic image or video of a field of view of the surrounding; (c) a gimbal stabilizer that is operatively connected with the one or more panorama cameras; (d) an underwater sonar that captures an underwater image; (e) a plurality of light modules that provide illumination at least partially for the field of view; (f) two underwater motors that provide propulsion force to the robot in water; (g) a power supply and processing unit that provide power and control operation of the robot; (h) an inertial measurement unit (IMU), operatively connected with the controlling system; (i) a base plate, attached to the shell, wherein the plurality of light modules are disposed on the base plate; wherein the two underwater motors attached on the lower shell; and wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is maintained above the water, and at least a portion of the lower shell is maintained under water.
15. A system for water tunnel inspection, comprising: a robot for water tunnel inspection, comprising: (a) a shell, comprising an upper shell and a lower shell; wherein the upper shell and the lower shell are sized and shaped to match each other, together defining a closed cavity therewithin; (b) one or more panorama cameras that capture an image or video of a field of view of surrounding; (c) a plurality of light modules that provide illumination at least partially for the field of view; (d) one or more underwater motors that provide propulsion force to the robot in water; and (e) a power supply and processing unit that provide power and control operation of the robot, wherein the robot is configured to float on water and to have a center of gravity positioned lower than geometric center, such that during operation, at least a portion of the upper shell is maintained above the water, and at least a portion of the lower shell is maintained under water; and a releasing and retrieving system, configured to release the robot to, and retrieve from the water tunnel.
16. The system of claim 15, wherein the releasing and retrieving system comprises: a lifting frame, configured to receive the robot; a sliding rail track, configured to be fixable on a substrate; a main frame that is at least partially receive the lifting frame and to be movable along the sliding rail track; and a winch that is connectable with the robot, wherein the winch system is configured to release the robot to, and retrieve from the water tunnel.
17. The system of claim 16, wherein the lifting frame is configured to be switchable between an

upper position and a lower position relative to the main frame, such that the robot is lifted from or lowered towards the water tunnel, respectively.

18. The system of claim 16, wherein the main frame is configured to be switchable between a working position and a preparing position relative to the sliding rail track, such that the robot is moved closer to or away from the water tunnel, respectively.
