

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398978
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Crye; Caleb

Mobile munition assembly and apparatus, systems, and methods of executing a mission for the mobile munition assembly

Abstract

A method of executing a mission for at least one mobile munition assembly in a mission environment is provided, the at least one mobile munition assembly having a container that encloses one or more launchers configured to receive and launch a munition. One or more electronic devices in communicatively coupling with one another in the mission environment form a secure network. A status of a situational awareness (SA) corresponding to each of the one or more electronic devices in the mission environment is transmitted. An input of parameters of the mission for the at least one mobile munition assembly is enabled, the parameters having one or more predefined rules associated therewith and configured to be applied to the parameters based on at least the status of the situational awareness (SA). An authorization or a denial of the mission for the at least one mobile munition assembly is requested.

Inventors:	Crye; Caleb (Brooklyn, NY)
Applicant:	Crye; Caleb (Brooklyn, NY)
Family ID:	1000008784420
Assignee:	BLKBOX LLC (Naples, FL)
Appl. No.:	17/703157
Filed:	March 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230010309 A1	Jan. 12, 2023

Related U.S. Application Data

us-provisional-application US 63220656 20210712

Publication Classification

Int. Cl.: **F41G7/30** (20060101); **B64C39/02** (20230101); **B64U70/00** (20230101); **B64U101/60** (20230101); **G05D1/00** (20240101); **H04L9/40** (20220101)

U.S. Cl.:

CPC **F41G7/306** (20130101); **B64C39/024** (20130101); **G05D1/101** (20130101); **H04L63/20** (20130101); B64U70/00 (20230101); B64U2101/60 (20230101)

Field of Classification Search

CPC: F41G (7/306)

USPC: 89/1.8; 89/1.815; 89/37.05; 89/40.01

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6244535	12/2000	Felix	N/A	N/A
7249730	12/2006	Flippen, Jr.	N/A	N/A
7526403	12/2008	Hogan	345/440.1	F41G 3/08
8115149	12/2011	Manole	244/45R	F42B 10/18
8266999	12/2011	Sisemore	N/A	N/A
8397613	12/2012	Skurdal et al.	N/A	N/A
8525088	12/2012	Ell et al.	N/A	N/A
9157717	12/2014	Carroll et al.	N/A	N/A
9354029	12/2015	Mace et al.	N/A	N/A
9593913	12/2016	Wright	N/A	F41A 27/30
9772155	12/2016	Schechter	N/A	N/A
10029791	12/2017	Roerman et al.	N/A	N/A
10648781	12/2019	Behiel	N/A	N/A
10757000	12/2019	Gelvin et al.	N/A	N/A
11105589	12/2020	Bilbrey et al.	N/A	N/A
11198519	12/2020	Seeley	N/A	N/A
11355021	12/2021	Miao	N/A	N/A
2010/0000463	12/2009	Root, Jr.	N/A	N/A
2010/0320312	12/2009	Bril et al.	N/A	N/A
2011/0059421	12/2010	Hickman	N/A	N/A
2012/0024136	12/2011	Mccants, Jr.	N/A	N/A
2016/0223278	12/2015	Schechter	N/A	N/A
2017/0176157	12/2016	Steiert	N/A	F41G 7/306
2017/0286654	12/2016	Nicoll	N/A	N/A
2017/0372617	12/2016	Bruno et al.	N/A	N/A
2019/0137219	12/2018	Bockmon	N/A	F41G 5/16
2019/0220039	12/2018	Wu et al.	N/A	N/A
2019/0316879	12/2018	Fougnes	N/A	N/A
2020/0088887	12/2019	Garcia et al.	N/A	N/A

2021/0070440	12/2020	Abeles et al.	N/A	N/A
2021/0094703	12/2020	Catledge et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109447398	12/2018	CN	N/A
112783195	12/2020	CN	N/A
3081892	12/2015	EP	N/A
4239277	12/2022	EP	N/A
1020150104323	12/2014	KR	N/A
102021595	12/2018	KR	N/A
2213315	12/2002	RU	N/A
2016024921	12/2015	WO	N/A
2021014101	12/2020	WO	N/A
2021156634	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for corresponding PCT/US2022/036760, dated Oct. 28, 2022, 12 pages. cited by applicant

European Patent Office Search Report for Patent Application No. 22842733.2, dated Apr. 11, 2025, 9 pages. cited by applicant

Primary Examiner: Tillman, Jr.; Reginald S

Attorney, Agent or Firm: Patterson Intellectual Property Law, PC

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. Provisional Patent Application No. 63/220,656, filed Jul. 12, 2021, and which is hereby incorporated by reference.

(1) A portion of the disclosure of this patent document contains material that is subject to copyright protection. The copyright owner has no objection to the reproduction of the patent document or the patent disclosure, as it appears in the U.S. Patent and Trademark Office (USPTO) patent file or records, but otherwise reserves all copyright rights whatsoever.

FIELD OF THE DISCLOSURE

(2) The present disclosure relates to a mobile munition assembly, and more particularly to apparatus, systems, and methods of executing a mission for the mobile munition assembly.

BACKGROUND

(3) Launching and/or controlling a flight of a munition subsequent to launch, and executing a mission thereof, are generally known. While some munition assemblies, such as tactical mortars, may be portably transported by one or more users in a mission environment, these munition assemblies are generally not operated with mission execution systems in connection with a launch of the munition from the munition assemblies, nor do they enable a control of precision-guided munitions. Plus, where such munition assemblies (and the mission execution systems therewith) do enable a control of a precision-guided munition, a warhead must be uniquely tailored to the precision-guided munition, thereby preventing interchangeability of munitions (and the warheads therein) for the munition assemblies. Such a loss of interchangeability denies a user—who is operating within the mission environment—the capacity to cycle through munitions having

different characteristics associated with the warhead, including whether the warhead is anti-armor, anti-personnel, anti-vehicle (e.g., anti-tank), anti-bunker, smoke-based, etc.

(4) Moreover, current munition assemblies, which are operated with mission executions systems, must be transported by way of vehicle or heavy-duty equipment or machinery, thereby rendering these munition assemblies not practically transportable by a human user in the mission environment. For example, current munition assemblies, such as artillery cannons and tactical mortars, are difficult to maneuver once established in a fixed location, given the weight associated with said munition assemblies and a locking mechanism affixing the munition assemblies to the fixed location. And, current munition assemblies, such as artillery cannons and tactical mortars, must be man-operated by a human user in the mission environment, thereby preventing a user from launching or firing a munition from the munition assembly from a location in the mission environment that is distant or remote from the munition assembly.

(5) Furthermore, current mission execution systems for munition assemblies, the systems of which are configured to detect, identify, and/or target one or more targets in the mission environment, are limited by industry-standard specifications for mission safety, including (without limitation) the MIL-STD-882, DO-178, and other safety-critical standards. Due to these limitations, mission execution systems are generally not implemented on electronic devices made available to a layperson (i.e., a consumer), such as a smart cellular device employing an Apple- or Android-based operating system (OS). These safety-critical standards are generally not met with conventional versions of the aforementioned electronic devices or equivalents thereof because the software, or other executable algorithm, effectuating the process of executing the mission are not independent of hardware or software natively provided for in these electronic devices. Accordingly, because of the lack of independence of the hardware or software natively provided for in these electronic devices, users (or autonomous systems) must rely on costly electronic devices having specially configured hardware and software specifications that provide safety criticality and fail-safe execution, such as a lightweight handheld mortar ballistic computer (LHMBC).

(6) In addition to the foregoing drawbacks, current mission execution systems, even on electronic devices having specially configured hardware and software (as described above), fail to provide real-time feedback of mission approval, whether caused by significant delays in a mission-rejection feedback loop, or through communication errors leading to a failure to reject (or accept) missions for the munition assembly. These failures limit the one or more devices to advising whether to accept or to reject the mission for the munition assembly, but do not, or cannot, authorize an acceptance or a rejection of the mission, such that the mission for the munition assembly may execute the mission in the mission environment. Moreover, current munition execution systems necessitate or require user monitoring or intervention after a mission is approved, thereby preventing an autonomous execution of the mission. And, current mission execution systems generally necessitate or require a centralized authority or hierarchical system, whereby the centralized authority or the hierarchical system provide one or more users with information, data, and analytics on location, nature, or character of the one or more targets in the mission environment. As a result, one or more munition assemblies may not be coordinated in an efficient manner because the one or more munition assemblies require the authorization of mission execution systems by the centralized authority or the hierarchical system, rather than by users operating within the mission environment in which the one or more munition assemblies are deployed. And further, users operating within the mission environment in which the one or more munition assemblies are deployed must provide additional feedback or input to the mission execution systems after the mission is approved, including a designation of a target or a programming of a fuze within the warhead of the munition. Such additionally required actions by the user decrease the efficiency and effectiveness of coordinating and executing mission execution systems for munition assemblies in the mission environment. Thus, there is a need to provide apparatuses, methods, or systems that overcome the foregoing limitations.

BRIEF SUMMARY

(7) The present disclosure provides a novel mobile munition assembly. Specifically, the present disclosure provides a novel mobile munition assembly, as well as a method and a system for executing a mission for the mobile munition assembly.

(8) Embodiments of apparatus, methods, and systems of the present disclosure provide a solution to the shortcomings above. In particular, this disclosure provides a mobile munition assembly for use in a mission environment. The mobile munition assembly may have a container with a stabilizer supported to a frame of the container, the stabilizer of which permits a user of the mobile munition assembly to rapidly and efficiently deploy the mobile munition assembly in the mission environment. Such rapid and efficient deployment of the mobile munition assembly may enable a munition to be launched from the mobile munition assembly with minimal interruption or interference due to a construction thereof. The disclosure also provides a method and system of executing a mission for at least one mobile munition assembly. One or more electronic devices may be communicatively coupled to, and in association with, one another, thereby forming a secure network, such as a mobile ad-hoc network (MANET). Across the one or more electronic devices, signals representative of a situational awareness (SA), such as position location information (PLI), and mission parameters may be entered and received on the one more electronic devices vis-à-vis an electronic controller executing a mission execution unit. The mission execution unit may comprise at least two modules—a mission module and a safety module—that operate independently of one another to define the mission for the at least one mobile munition assembly, and to determine whether to authorize the mission for the at least one mobile munition assembly.

(9) In the context of executing a mission for a mobile munition assembly, certain embodiments of a method for executing a mission for at least one mobile munition assembly are disclosed. The at least one mobile munition assembly may include a container having a container frame, the container frame having a first end distally located from a second end. The container frame may enclose one or more launchers, and each of the one or more launchers may be configured to receive a munition. A stabilizer, which is associated with the at least one mobile munition assembly, may be operated from a first configuration, wherein a plurality of legs are folded up adjacent to the container frame, to a second configuration, wherein the plurality of legs are pivoted away from the container frame to place the container in an upright position such that an axis defined along the container frame from the first end to the second end is generally orthogonal to a surface of a launch terrain upon which the container is mounted. One or more electronic devices may form a secure network with one another in a mission environment when the one or more electronic devices are communicatively coupled to, and in association with, one another. At least one of the one or more electronic devices may be associated with one or more of the at least one mobile munition assembly. A status of a situational awareness (SA) may be transmitted to each of the one or more electronic devices in the mission environment. An input of parameters of the mission for the at least one mobile munition assembly in the mission environment may be enabled. The parameters of the mission may have one or more predefined rules associated therewith, and the parameters of the mission may be configured to be applied to the parameters of the mission based on at least the status of the situational awareness (SA). An authorization or a denial of the mission for the at least one mobile munition assembly may be requested.

(10) In the context of executing a mission in a mission environment, certain embodiments of a system for executing a mission for at least one mobile munition assembly are disclosed. The at least one mobile munition assembly may comprise a container having a container frame. The container frame may have a first end distally located from a second end, and the container frame may enclose one or more launchers. Each of the one or more launchers may be configured to receive a munition. One or more electronic devices may have a communication unit, and at least one of the one or more electronic devices may be associated with one or more of the at least one mobile munition assembly. A secure network may be formed by the communication unit of the one

or more electronic devices communicatively coupled to another of the communication unit of the one or more electronic devices. Each of the one or more electronic devices may be configured to transmit a status of a situational awareness (SA) corresponding to each of the one or more electronic devices in the mission environment. Each of the one or more electronic devices may additionally be configured to enable an input of parameters of the mission for the at least one mobile munition assembly in the mission environment. The parameters of the mission may have one or more predefined rules associated therewith, and the one or more predefined rules may be configured to be applied to the parameters based on at least the status of the situational awareness (SA). And, each of the one or more electronic devices may be further configured to request an authorization or a denial of the mission for the at least one mobile munition assembly.

(11) In one particular and exemplary embodiment, a method of executing a mission for at least one mobile munition assembly in a mission environment is provided. The at least one mobile munition assembly comprises a container having a container frame. The container frame has a first end distally located from a second end, and the container frame encloses one or more launchers. Each of the one or more launchers are configured to receive a munition. The method commences with an operation of operating a stabilizer associated with the at least one mobile munition assembly from a first configuration to a second configuration. In the first configuration, a plurality of legs are folded up adjacent to the container frame, and in the second configuration, the plurality of legs are pivoted away from the container frame to place the container in an upright position, such that an axis defined along the container frame from the first end to the second end is generally orthogonal to a surface of a launch terrain upon which the container is mounted. The method continues with an operation of forming a secure network of one or more electronic devices with one another in the mission environment when the one or more electronic devices are communicatively coupled to, and in association with, one another. At least one of the one or more electronic devices is associated with one or more of the at least one mobile munition assembly. The method continues with an operation of transmitting a status of a situational awareness (SA) corresponding to each of the one or more electronic devices in the mission environment. The method continues with an operation of enabling an input of parameters of the mission for the at least one mobile munition assembly in the mission environment. The parameters have one or more predefined rules associated therewith, and the one or more predefined rules are configured to be applied to the parameters based on at least the status of the situational awareness (SA). The method continues with an operation of requesting an authorization or a denial of the mission for the at least one mobile munition assembly.

(12) In one exemplary aspect according to the above-referenced embodiment, the method may further continue with an operation of deploying the at least one mobile munition assembly on the surface of the launch terrain the mission environment.

(13) In another exemplary aspect according to the above-referenced embodiment, the method may further continue with an operation of identifying one or more targetable assets and one or more non-targetable assets in the mission environment based at least on the parameters of the mission for the at least one mobile munition assembly and an application of the one or more predefined rules to the parameters of the mission.

(14) In another exemplary aspect according to the above-referenced embodiment, the one or more non-targetable assets may include locations corresponding to the one or more electronic devices in the mission environment.

(15) In another exemplary aspect according to the above-referenced embodiment, the one or more predefined rules related to the parameters of the mission may include at least one of information corresponding to at least to one of a location of the one or more electronic devices in the mission environment, a location of the at least one mobile munition assembly in the mission environment, an identification of one or more targetable assets in the mission environment, an identification of one or more non-targetable assets in the mission environment, an altitude of the munition when launched from the at least one mobile munition assembly, a trajectory of the munition when

launched from the at least one mobile munition assembly, a flight path of the munition when launched from the at least mobile munition assembly, a type of warhead located within the munition, an impact radius of the munition, or a time constraint on the mission.

(16) In another exemplary aspect according to the above-referenced embodiment, the method may continue with an operation of receiving the authorization of the mission for the at least one mobile munition assembly in the mission environment.

(17) In another exemplary aspect according to the above-referenced embodiment, the method may continue with an operation of selecting one or more of the at least one mobile munition assembly to launch the munition from the one or more of the at least one mobile munition assembly in the mission environment.

(18) In another exemplary aspect according to the above-referenced embodiment, the method may continue with an operation of commanding the one or more of the at least one mobile munition assembly to launch the munition from the one or more of the at least one mobile munition assembly in the mission environment.

(19) In another exemplary aspect according to the above-referenced embodiment, the method may continue with an operation of reporting whether there is a mission error detected by the one or more electronic devices in the mission environment.

(20) In another exemplary aspect according to the above-referenced embodiment, the mission error detected by the one or more electronic devices in the mission environment may include at least one of a loss of communication, on the secure network, of the one or more electronic devices in the mission environment, an uncertainty of a location of the one or more electronic devices in the mission environment, an uncertainty of a location of the at least one mobile munition assembly in the mission environment, a latency in the secure network, an identification of one or more unauthorized devices on the secure network, an alert that the munition is not configured to be launched from one of the one or more launchers in the mobile munition assembly, an alert that at least one of the one or more launchers does not have sufficient power to enable a launch of the munition in the mission environment, an alert that a warhead located with the munition does not conform with the parameters of the mission, or an alert that at least one of the one or more launchers is not arranged in an orientation to enable a vertical launch of the munition.

(21) In another exemplary aspect according to the above-referenced embodiment, the munition may include a warhead having a length ranging from about ten (10) inches to about twenty (20) inches and a weight between about eight (8) pounds and fifteen (15) pounds.

(22) In another exemplary aspect according to the above-referenced embodiment, the secure network may comprise a mobile ad-hoc network (MANET) or a wireless mesh network (WMN).

(23) In another embodiment, a system for executing a mission in a mission environment is provided. The system includes at least one mobile munition assembly comprising a container having a container frame. The container frame has a first end distally located from a second end, and the container frame encloses one or more launchers. Each of the one or more launchers are configured to receive a munition. One or more electronic devices have a communication unit, and at least one of the one or more electronic devices are associated with one or more of the at least one mobile munition assembly. A secure network is formed by the communication unit of the one or more electronic devices communicatively coupled to another of the communication unit of the one or more electronic devices. The one or more electronic devices are configured to transmit a status of a situational awareness (SA) corresponding to each of the one or more electronic devices in the mission environment. The one or more electronic devices are also configured to enable an input of parameters of the mission for the at least one mobile munition assembly in the mission environment. The parameters have one or more predefined rules associated therewith, and the one or more predefined rules are configured to be applied to the parameters based on at least the status of the situational awareness (SA). The one or more electronic devices are further configured to request an authorization or a denial of the mission for the at least one mobile munition assembly.

(24) In one particular and exemplary aspect of the above-referenced embodiment, the munition may have a munition frame, and the munition frame includes a nose, a body, and a tail. The nose may be distally located from the tail, and the body may be positioned between the nose and the tail. Two or more fins may be supported from the munition frame on a location of the body or the tail. Two or more wings may be supported from the munition frame on a location of the body proximate to the nose. A warhead may be located within the munition frame at the nose.

(25) In other particular and exemplary aspects of the above-referenced embodiment, the one or more electronic devices are configured to direct performance of remaining operations from the above-referenced method embodiment and optionally any of the described exemplary aspects thereof.

(26) Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. The present invention may be embodied in other specific forms without departing from the spirit or essential attributes thereof, and it is therefore desired that the present embodiment be considered in all aspects as illustrative and not restrictive. Any headings utilized in the description are for convenience only and no legal or limiting effect. Numerous objects, features, and advantages of the embodiments set forth herein will be readily apparent to those skilled in the art upon reading of the following disclosure when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Hereinafter, various exemplary embodiments of the disclosure are illustrated in more detail with reference to the drawings.

(2) FIGS. 1A-1C illustrate exemplary embodiments of a partial diagram of a system for executing a mission for at least one mobile munition assembly, the system comprising one or more electronic devices in communicative coupling to, and in association with, one another, in accordance with aspects of the present disclosure.

(3) FIG. 1D illustrates an exemplary embodiment of a partial network diagram of a system for executing a mission for at least one mobile munition assembly, in accordance with aspects of the present disclosure.

(4) FIG. 2A illustrates an exemplary embodiment of a partial block diagram of an electronic device, in accordance with aspects of the present disclosure.

(5) FIG. 2B illustrates an exemplary embodiment of a partial block diagram of the electronic device in association with a mobile munition assembly, in accordance with aspects of the present disclosure.

(6) FIGS. 3A-3B illustrate perspective views of an exemplary embodiment of a mobile munition assembly, where a stabilizer is operated in a first configuration and a second configuration, in accordance with aspects of the present disclosure.

(7) FIG. 3C illustrates a perspective view of another embodiment of the mobile munition assembly, wherein a lid of a container is operated in an open configuration, in accordance with aspects of the present disclosure.

(8) FIG. 4 illustrates a perspective view of an exemplary embodiment of a munition, in accordance with aspects of the present disclosure.

(9) FIG. 5 illustrates a flowchart providing an exemplary embodiment of a method for executing a mission for at least one mobile munition assembly, in accordance with aspects of the present disclosure.

(10) FIG. 6 illustrates an exemplary embodiment of a partial block diagram of a system for executing a mission for at least one mobile munition assembly, the system comprising one or more

electronic devices having a safety module and a mission module, in accordance with aspects of the present disclosure.

(11) FIG. 7 illustrates another exemplary embodiment of a partial block diagram of a system for executing a mission for at least one mobile munition assembly, the system comprising one or more electronic devices having a safety module and a mission module, in accordance with aspects of the present disclosure.

(12) FIG. 8 illustrates an exemplary embodiment of a mission environment, wherein there are one or more targetable assets and one or more non-targetable assets identified by the system for executing a mission for at least one mobile munition assembly, in accordance with aspects of the present disclosure.

(13) FIG. 9 illustrates an exemplary embodiment of a mission environment, wherein there are more than one of at least one mobile munition assembly, and a targetable asset has been identified by the system for executing a mission for that at least one mobile munition assembly, in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

(14) Reference will now be made in detail to embodiments of the present disclosure, one or more drawings of which are set forth herein. Each drawing is provided by way of explanation of the present disclosure and is not a limitation. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made to the teachings of the present disclosure without departing from the scope of the disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment.

(15) Thus, it is intended that the present disclosure covers such modifications and variations as come within the scope of the appended claims and their equivalents. Other objects, features, and aspects of the present disclosure are disclosed in, or are obvious from, the following detailed description. It is to be understood by one of ordinary skill in the art that the present discussion is a description of exemplary embodiments only and is not intended as limiting the broader aspects of the present disclosure. Referring generally to FIGS. 1-9, various exemplary embodiments may now be described of apparatuses, systems, and methods for authorizing a mission for at least one mobile munition assembly 10. Various embodiments may now be described of the mobile munition assembly 10, or one or more mobile munition assemblies 10, and methods and systems of implementation thereof, including a mission execution system 100. Specifically, various embodiments may now be described of the mobile munition assembly 10, the mission execution system 100, and a method 200 of executing a mission for at least one mobile munition assembly 10 in a mission environment 90. Where the various figures describe embodiments sharing various common elements and features with other embodiments, similar elements and features are given the same reference numerals and redundant description thereof may be omitted below.

(16) FIGS. 1A-1C illustrate an exemplary embodiment of a partial diagram of the system 100 for executing a mission for at least one mobile munition assembly 10, the mission authorization system 100 comprising one or more electronic devices 110. The one or more electronic devices 110, such as one or more user devices 110, may be associated with one or more of at least one mobile munition assembly 10, the at least one mobile munition assembly 10 having one or more launchers 30 configured to launch a munition 70 from a surface 97 of a launch terrain 96 into an airspace, and subsequently onto or against one or more targetable assets 92 in the mission environment 90, as illustratively conveyed in FIGS. 8-9.

(17) Referring to FIG. 1A, the system 100 may comprise one of one or more electronic devices 110, the one of the one or more electronic devices 110 in association with the at least one mobile munition assembly 10, and the one or more electronic devices 110 establishing a secure network 102. The secure network 102 may comprise a closed network 102 comprising only the one of the one or more electronic devices 110, the closed network 102 having the capability of recruiting and/or accepting another of the one or more electronic devices 110 into the closed network 102,

such as by and through authentication keys or access credentials inputted vis-à-vis a user interface (UI) on a display unit **117**. Referring to FIG. **1B**, the system **100** may comprise a plurality of the one or more electronic devices **110**, wherein at least one of the one or more electronic devices **110** is associated with one or more of the at least one mobile munition assembly **10**. The plurality of the one or more electronic devices **110** may be communicatively coupled to one another vis-à-vis a communication unit **114** (as further described herein), such that each of the one or more electronic devices **110** are in communicative association with one another. The plurality of the one or more electronic devices **110** may establish, or form, the secure network **102** when the one or more electronic devices **110** are communicatively coupled to, and in association with, one another. Referring to FIG. **1C**, the system **100** may comprise a plurality of the one or more electronic devices **110**, wherein at least one of the one or more electronic devices **110** is associated with the one or more of the at least one mobile munition assembly **10**. The one or more electronic devices **110** communicatively coupled to, and in association with, one another may be recruited or accepted to the secure network **102** by an administrator **104**. The administrator **104** may comprise another of the one or more electronic devices **110**, or the administrator may comprise a server, a centralized host, or the like, capable of providing and/or maintaining the secure network **102** for the one or more electronic devices **110**. For the purpose of the disclosure herein, the system **100** may authorize the mission for the at least one mobile munition assembly **10** vis-à-vis any (one or more) of the one or more electronic devices **110** or the administrator **104**, and combinations thereof.

(18) FIG. **1D** illustrates an exemplary embodiment of a partial network diagram of the system **100** for authorizing the mission for at least one mobile munition assembly **10**. The system **100** may comprise a plurality of the one or more electronic devices **110** communicatively coupled to, and in association with one another, wherein at least one of the one or more electronic devices **110** is associated with one or more of the at least one mobile munition assembly **10**. The communicatively coupling and association of the one or more electronic devices **110** may form, or establish, the secure network **102**, including by and through wired or wireless communication (e.g., cellular communication). The secure network **102** may be configured to recruit other of the one or more electronic devices **110n**, whether by and through any of the one or more electronic devices **110** or through the administrator **104**, or a combination of the foregoing. One or more of the at least one mobile munition assembly **10n** may be associated with any (one or more) of the one or more electronic devices **110n** recruited to the secure network **102**.

(19) As depicted in FIGS. **1A-1D**, the system **100** may comprise the one or more electronic devices **110** communicatively coupled to, and in association with, one another in a given area, such as the mission environment **90** (as exemplarily illustrated in FIGS. **8-9**). Within the secure network **102**, the one or more electronic devices **110** of the system **100** may function in accordance with the method **200**, as depicted in FIG. **5** and as discussed further herein, either alone (e.g., independently), or in concert with one another, such that the one or more electronic devices **110** of the system **100** may function as decentralized or distributed nodes in the secure network **102**. Where the one or more electronic devices **110** act in concert with one another, each of the one or more electronic devices **110** may act as nodes to relay, transmit, and/or exchange communications, inputs (e.g., mission parameters), or data among the one or more electronic devices **110** in the system **100**. As shown in FIGS. **1A-1D**, directional arrows convey the communicative couplings, and associations, of the one or more electronic devices **110** of the system **100**, wherein at least one of the one or more electronic devices **110** is associated with one or more of the at least one mobile munition assembly **10**. In optional embodiments of the system **100**, each of the one or more electronic devices **110** may be communicatively coupled to, and in association with, one another, as well as the administrator **104**. The administrator **104** may comprise another network of devices, such as another of the secure network **102**, or the administrator **104** may include a master administrator with one or more slave administrators, wherein each of the master administrator or the one or more slave administrators may be communicatively coupled to, and in association with,

the one or more electronic devices **110**. In other optional embodiments, the secure network **102** may comprise a mobile ad-hoc network (MANET) or a wireless mesh network (WMN). In embodiments where the secure network **102** comprises a mobile ad-hoc network (MANET) or a wireless mesh network (WMN), the one or more electronic devices **110** may be communicatively coupled to, and in association with, one another based upon geographical or physical proximity within the mission environment **90**. Other of the one or more electronic devices **110**, one of which may be associated with one or more of the at least one mobile munition assembly **10**, may be recruited or accepted by the secure network **102** when the one or more electronic devices **110** are moved within a geographical proximity or physical range of the then-existing secure network **102** of the one or more electronic devices **110**.

(20) FIGS. 2A-2B depict an exemplary embodiment of the electronic device **110**, wherein one of the one or more electronic devices **110** may be associated with at least one mobile munition assembly **10** having one or more launchers **30** configured to launch the munition **70**. Any of the one or more electronic devices **110** may be lightweight, portable, and/or rugged, and may preferably be a hand-held computer, such as a personal data assistant (PDA), cellular phone, or a smart cellular device, including a smart cellular device or portable computer employing an Android-based operating system (OS), an Apple-based OS, or a Linux-based OS. In optional embodiments, any of the one or more electronic devices **110** may be portable laptop computer, or a notebook- or tablet-type computer. The one or more electronic devices **110** may include one or more of a power source **112**, a processor **113**, a communication unit **114**, a location unit **115**, a sensor unit **116**, the display unit **117**, a storage (or a storage medium) **118**, and a controller **120** configured to execute a mission execution unit **130**. The power source **112**, which drives operability of the one or more electronic devices **110**, may include at least one of a modular battery, a battery backup, an uninterrupted power supply (UPS), or any battery commercially provided in connection with a smart cellular device or portable computer employing an Apple-based OS, an Android-based OS, or a Linux-based OS, or the like. The processor **113** may be a generic hardware processor, a special-purpose hardware processor, or a combination thereof. In embodiments having a generic hardware processor (e.g., as a central processing unit (CPU) available from manufacturers such as Intel and AMD), the generic hardware processor is configured to be converted to a special-purpose processor by means of being programmed to execute and/or by executing a particular algorithm in the manner discussed herein, e.g., the method **200**, for providing a specific operation or result. It should be appreciated that the processor **113** may be any type of hardware and/or software processor and is not strictly limited to a microprocessor or any operation(s) only capable of execution by a microprocessor, in whole or in part.

(21) The communication unit **114** of the one or more electronic devices **110** may be configured to permit communication—for example via the secure network **102**, as depicted in FIGS. 1A-1D—by a wired interface, wireless interface, or a combination thereof. In optional embodiments, the communication unit **114** may include wireless communication components, such as cellular modem, radio waves, Wi-Fi, or Bluetooth, and combinations thereof. In other embodiments, the communication unit **114** may include a transceiver (not shown), or other two-way radio, which may be functionally linked to the controller **120**, the transceiver (not shown) configured to send and receive communications vis-à-vis radio waves, such as among the one or more electronic devices **110** or between the one or more electronic devices **110** and a communication section (not shown) associated with the one or more launchers **30** of the at least one mobile munition assembly **10**. In optional embodiments, the transceiver (not shown), or the two-way radio, may be a single channel ground/airborne radio system (SINCGARS) or advanced systems improvement program (ASIP) radio with external antenna. The communication unit **114** may enable the one or more electronic devices **110** to communicatively couple to, and associate with, one another, or in optional embodiments, the administrator **104**. The communication unit **114** may also be functionally communicable with other aspects of the one or more electronic devices **110**, including the location

unit **115** and the sensor unit **116**. In optional embodiments, the communication unit **114** of the one or more electronic devices **110** may include a radio-frequency (RF) unit, which may comprise an antenna configured to transmit single- or multi-directional signals to other RF units in the communication unit **114** of the other of the one or more electronic devices **110**.

(22) The location unit **115** of the one or more electronic devices **110** may include a global positioning system (GPS) unit (not shown), the GPS unit (not shown) configured to provide location data of the one or more electronic devices **110** or the at least one mobile munition assembly **10**, wherein one of the one or more electronic devices **10** is associated therewith. Such location data may correspond to position location information (PLI) of the one or more electronic devices **110**, particularly the PLI of the one or more electronic devices **110** in the mission environment **90**. The sensor unit **116** of the one or more electronic devices **110** may comprise a number of sensors, such as inertial measurement units (IMUs). In optional embodiments, the IMUS may include a number of sensors including, but not limited to, accelerometers, which measure (among other things) velocity and acceleration, gyroscopes, which measure (among other things) angular velocity and angular acceleration, and magnetometers, which measure (among other things) strength and direction of a magnetic field. In optional embodiments, directional data provided by the location unit **115**, or position-based data provided by the sensor unit **116**, may be merged (or otherwise used in combination) by the controller **120** to ascertain a location or motion of the one or more electronic devices **110** (and any of the at least one mobile munition assembly **10** associated therewith) in the mission environment **90**.

(23) The one or more electronic devices **10** may store one or more sets of instructions, including instructions corresponding to the method **200**, in the storage **118**, which may be either volatile or non-volatile. The one or more sets of instructions, including instructions corresponding to the method **200**, may be configured to be executed by the processor **113** to perform at least one operation corresponding to the one or more sets of instructions. The one or more electronic devices **110** may also have a display unit **117** as part of a user interface (UI), which may include one or more UI tools, such as a keyboard, keypad, joystick, toggle, touchscreen, or other tool, which are configured to enable input of instructions to the controller **120**, including parameters of the mission, as further described herein.

(24) The one or more electronic devices **110** may comprise a standalone device (as described previously) or may be used with at least one external component, such as another of the one or more electronic devices **110** or the administrator **104**, either locally or remotely communicatively couplable with the one or more electronic devices **110**—for example via the secure network **102**, as depicted in FIGS. **1A-1D**. The one or more electronic devices **110** may be configured to store, access, or provide at least a portion of information usable to permit one or more operations described herein, including operations set forth in the method **200**, and as illustratively conveyed in FIGS. **5-7**. Alternatively, or in addition, the one or more electronic devices **110** may be configured to store content data and/or metadata to enable one or more operations described herein.

(25) FIGS. **3A-3B** illustrate perspective views of an exemplary embodiment of the mobile munition assembly **10**. The mobile munition assembly **10** may have a container **20** and a stabilizer **40**. A container frame **22** of the container **20**, which generally defines an exterior of the container **20**, may have a first end **23** distally located from a second end **24**. The container **20** may have a length defined from the first end **23** to the second end **24** of the container frame **22**, the length ranging up to about sixty (60) inches, though in other embodiments the length may be greater than the foregoing. The container **20** may be formed by a material including at least one of steel, aluminum, titanium, nickel, and other metals and metallic alloys, as well as composite-based or polymer-based materials, including fiber reinforced plastic (FRP), polyvinyl chloride (PVC), and combinations thereof. The container frame **22** may enclose one or more launchers **30**. Each of the one or more launchers **30** may be configured to receive a munition receptacle **32**. In optional embodiments, the mobile munition assembly **10** may include or otherwise have one or more of the container **20** with

a corresponding one or more of the container frame **22**.

(26) The munition receptacle **32** may be capable of receiving the munition **70**, as illustratively conveyed in FIG. **4**. The munition receptacle **32** may be formed by a material including at least one of a high-pressure laminate, high-pressure laminate with a phenolic resin formulation or other flame-retardant additive, steel, such as managing or stainless steel, aluminum, titanium, or other metals and metallic alloys, as well as composite-based or polymer-based materials, or other pyrotechnic materials, and combinations thereof. In optional embodiments, the munition receptacle **32** may include a receptacle frame **34**. The receptacle frame **34** may have a top end **36** and a bottom end **38**, the top end **36** distally located from the bottom end **38**. The top end **36** may correspond to the first end **23** of the container frame **22** and the bottom end **38** may correspond to the second end **24** of the container frame **22**. The receptacle frame **34** may taper beginning from the top end **36** to the bottom end **38**, thereby rendering the receptacle frame **34** seamlessly and/or slidably removable from the container **20**. In further optional embodiments, one or more receptacle holes (not shown) may be disposed on about the receptacle frame **34** and corresponding to one or more container holes (not shown) disposed on and about the container frame **22**. Each of the corresponding one or more receptacle holes (not shown) and the one or more container holes may receive a threaded fastener (not shown) to secure the container **20** to the munition receptacle **32**.

(27) In other embodiments of the munition receptacle **32**, the munition receptacle **32** may have a receptacle handle (not shown) supported from the receptacle frame **34**. The receptacle handle (not shown) may be pivotable between a collapsed position and an extended position. In the extended position, the receptacle handle (not shown) may be pivoted away from the receptacle frame **34**; and, in the collapsed position, the receptacle handle (not shown) may be folded up adjacent to the receptacle frame **34**. In optional embodiments, a hinge may be configured to allow pivotable movement of the receptacle handle (not shown) relative to the receptacle frame **34**. In further optional embodiments, a spring (not shown) may be configured to bias the receptacle handle (not shown) to the extended position.

(28) Referring to FIGS. **3A-3B**, the stabilizer **40** may be supported from the container frame **22**. The stabilizer **40** may include a plurality of pivotable legs **41**. The stabilizer **40** may be operable between a first configuration **42** and a second configuration **43**. In the first configuration **42**, the plurality of pivotable legs **41** may be folded up adjacent to the container frame **22**; and, in the second configuration **43**, the plurality of pivotable legs **41** may be pivoted away from the container frame **22**. Where the stabilizer **40** is operated to the second configuration **43**, the container **20** may be placed in an upright position, such that an axis **26** from the first end **23** to the second end **24** of the container frame **22** may be generally orthogonal to a surface **97** of a launch terrain **96**, as illustratively conveyed in FIGS. **8-9**. In optional embodiments, where the stabilizer **40** is operated to the second configuration **43**, the container may be placed in a semi-upright position, such that the axis **26** from the first end **23** to the second end **24** may form an angle relative to the surface **97** of the launch terrain **96**, ranging from between about 30 degrees to 90 degrees. By placing the container **20** generally orthogonal to the surface **97** of the launch terrain **96**, however, the mobile munition assembly **10** need not be positioned or displaced at an angle relative to the surface **97** of the launch terrain **96**, thereby increasing the speed and efficiency in a deployment of the mobile munition assembly **10**. The launch terrain **96** may include any number of environmental or geographical terrains, lands, grounds, or landscapes, as well as any artificial or man-made structure, including vehicles or heavy equipment or machinery.

(29) Referring to FIGS. **3A-3B**, a stabilizer handle **44** may be attached to the stabilizer **40**. The stabilizer handle **44** may be configured to operate the stabilizer **40** between the first configuration **42** and the second configuration **43**. The stabilizer **40** may be operated to the first configuration **44** by moving the stabilizer handle **44** proximate to the first end **23** of the container frame **22**. The stabilizer **40** may be operated to the second configuration **43** by moving the stabilizer handle **44** to an intermediate location **46** between the first end **23** and the second end **24** of the container frame

22. In optional embodiments, the intermediate location 46 of the stabilizer handle 44 may be generally equidistant from the first end 23 to the second end 24 of the container frame 22.

(30) FIG. 3C illustrates a perspective view of another embodiment of the mobile munition assembly 10. In this embodiment, the mobile munition assembly 10 may include the container 22, the container 22 of which includes peripheral walls 52—such as a front peripheral wall 52A, a back peripheral wall 52B, a left peripheral wall 52C, and a right peripheral wall 52D—a bottom 50, and a lid 54. The peripheral walls 52 may extend from the bottom 50 to define an interior of the mobile munition assembly 10—the peripheral walls 52 defining the container frame 22 in this embodiment. The one or more launchers 30 may be housed within the container frame 22, where the one or more launchers 30 are capable of receiving one or more munition 70. The lid 54 may be movable between a collapsed configuration (not depicted), wherein the lid 54 is engaged against the peripheral walls 52 to otherwise seal the interior of the container frame 22, and an open configuration 56, wherein the lid 54 is pivoted away from the peripheral walls 52 to expose the one or more launchers 30 (and the one or more munitions 70 received therein). Supported from the peripheral walls 52 and/or the bottom 50 may be one or more track units 58, such as wheels, crawlers, or other units, capable of moving the mobile munition assembly 10 across the surface 97 of the launch terrain 96. The mobile munition assembly 10 may be movable across the surface 97 of the launch terrain 96 where a user grabs or grips a handle 59 attached to the peripheral wall 52, which may be used in conjunction with the track units 58 to portably move the munition assembly 10 across the mission environment 90. When placed atop the surface 97 of the launch terrain 96, the container 22 may be configured in an upright position, such that an axis defined through each of the munition 70 received in the one or more launchers 30 (or an axis defined through each of the one or more munition receptacles 30 (not depicted) disposed within the container frame 22) may be generally orthogonal to the surface 97 of the launch terrain 96, thereby enabling a vertical launch of the munition 70 from the surface 97.

(31) In optional embodiments, the one or more launchers 30 of the at least on mobile munition system 10, in association with at least one of the one or more electronic devices 110, may include a controller (not shown) as part of a launcher device 60, as illustratively conveyed in FIGS. 3A-3C. The controller (not shown) may be associated with a processor (not shown), a computer readable medium (not shown), a data storage (not shown), and in optional embodiments a user interface (not shown) having a display (not shown). In other optional embodiments, an input/output device (not shown), such as a keyboard, keypad, touchscreen, joystick, or other user interface tool, is provided so that a human user may input instructions to the controller (not shown) of the one or more launchers 30. A communication unit (not shown) of the controller (not shown) of the one or more launchers 30 may support or provide communications between the controller (not shown) of the one or more launchers 30 and the one or more communication unit 114 of the one or more electronic devices 110. The communication unit (not shown) of the one or more launchers 30 may also a location unit (not shown) having a global positioning system (GPS) unit with an antenna, wherein the GPS unit may be configured to provide location data of the at least one mobile munition assembly 10 in the mission environment 90. An example of the GPS unit or receiver may be a defense advanced global positioning system receiver (DAGR) with the antenna. The communication unit (not shown) of the one or more launchers 30, on the launcher device 60, may also include a transceiver (not depicted), or other two-way radio, which may be configured to send and receive communications vis-à-vis radio waves from other of the one or more launchers 30 or the one or more electronic devices 110. In optional embodiments, the transceiver (not shown) or the two-way radio, may be a single channel ground/airborne radio system (SINCGARS) or advanced systems improvement program (ASIP) radio with external antenna. Moreover, the one or more launchers 30 may be driven by a power supply (not shown), which may include at least one of a modular battery, a solar panel, a battery backup, an uninterruptible, power supply (UPS), or any combination thereof.

(32) The controller (not shown) of the one or more launchers **30**, through a central processing unit (not shown), may process data received from sensor units (not shown) associated within the one or more launchers **30**, such as inertial measurement units (IMUs). The IMUs may be configured to provide output signals as to the relative position, velocity, and orientation of the one or more launchers **30**, and by extension the container **20** of the mobile munition assembly **10**. The IMUs may be associated with the controller (not shown) of the one or more launchers **30**, wherein the output signals are processed and conveyed on a display (not shown) to show and demonstrate the relative position, velocity, and orientation of the container **20** enclosing the one or more launchers **30**. The central processing unit (not shown) may also process data received from various sensors positioned within or located within the one or more launchers **30** and/or the munition receptacle **32**, the sensors of which may be configured to detect a loading of the munition **70** into the munition receptacle **32** or an inserting of the munition receptacle **32** into at least one of the one or more launchers **30**. The controller (not shown) may further process data received from motion-detection sensors (not shown) disposed on or about the container frame **22**, the motion-detection sensors (not shown) of which may flag, signal, or indicate a physical presence or geographical proximity of a user of the mobile munition assembly **10**, third-party persons, or heavy equipment or machinery, such as vehicles. The controller (not shown) may receive output signals on motion within a radius of about up to about twenty-five (25) meters from the motion-detection sensors (not shown), through the radius may be greater or lesser.

(33) Referring to FIG. **4**, an exemplary embodiment of the munition **70** is illustratively conveyed. The munition **70** may be propelled out of the munition receptacle **32** in which the munition **70** is loaded and from one of the one or more launchers **30** in which the munition receptacle **32** is inserted. The munition **70** may be propelled by an impulse or reaction. In optional embodiments, the munition **70** may be ejected by an expansion of high-pressure gases from a compressed air supply or from an ignition of a propellant charge. In other optional embodiments, the munition **70** may be launched from the one or more launchers **30** through activation and combustion of a motor (not shown) housed within a munition frame **71** of the munition **70**. In further optional embodiments, the munition **70** may be an indirect-fire munition or a barrel-expelled munition. The munition **70** may be launched through activation or combustion of the motor (not shown) by a remote controller, including the controller **120** of the one or more electronic devices **110** associated with the mobile munition assembly **10** or through the controller (not shown) of the one or more launchers **30**.

(34) The munition **70** may have an exterior defined by the munition frame **71**, the munition frame of which may be generally divided into at least the following sections: a nose **72**, a body **74**, and a tail **76**. The nose **72** may be distally located from the tail **76**, and the body **74** may be positioned between the nose **72** and the tail **76**. The munition **70** may have a length defined from an end **73** of the nose **72** to an end **77** of the tail **76**, the length ranging from about thirty-two (32) inches to about forty-eight (48) inches, though in other embodiments the length may be greater or lesser than the foregoing. Two or more fins, such as first fins **80** and second fins **82** may be supported from and/or disposed about the munition frame **71**. The two or more fins may be static or controllable. For example, the first fins **80** and/or the second fins **82** may be actuated by a motor (not shown) housed within the munition frame **71**. When not actuated, the first fins **80** and/or the second fins **82** may be operated to a launch configuration **88**, wherein the first fins **80** and/or the second fins **82** are folded up adjacent to the munition frame **71**; and when actuated, the first fins **80** and/or the second fins **82** may be operated to a flight configuration **89**, wherein the first fins **80** and/or the second fins **82** may be pivoted away from the munition frame **71**. In optional embodiments, the first fins **80** may be static or controllable fins supported from and/or disposed about the munition frame **71** at the end **77** of the tail **76**, and the first fins **80** may be articulated with respect to an axis **78** defined along the munition **70** from the end **77** to the end **73**. In other optional embodiments, the second fins **82** may be static or controllable fins supported from and/or disposed about the munition

frame **71** at a location on the body **74** proximate to the tail **76**, and the second fins **72** may be articulated with respect to the axis **78**. Two or more wings **86** may be supported and/or disposed about from the munition frame **71** on a location on the body **74** proximate to the nose **72**. The two or more wings **86** may be operable between a launch configuration **88** and a flight configuration **89**, as illustratively conveyed in FIGS. **4** and **9**. In the launch configuration **88**, the two or more wings **86** may be folded up adjacent to the munition frame **71**. In the flight configuration **89**, the two or more wings **86** may be pivoted away from the munition frame **71**. Where the two or more wings **86** are operated to the flight configuration **89**, the two or more wings **86** may be perpendicular to the axis **78**.

(35) A warhead **84**, a guidance system **87**, and a fuze (not shown) may be housed within the munition frame **71**, including at a location within the munition frame **71** at the nose **72**. The fuze (not shown) may be initiated to cause detonation of the munition **70** upon impact, in proximity, by time delay, or remotely (such as by and through the one or more electronic devices **110**). In optional embodiments, the warhead **84** may have a length ranging from about ten (10) inches about twenty (20) inches, though the length may be greater or lesser. In other optional embodiments, the warhead **84** may have a weight between about eight (8) pounds and fifteen (15) pounds, though the weight may be greater or lesser. In further optional embodiments, the warhead **84** may constitute any one of the following warheads: M151, M156, M229, M247, M255, M255E1/A1, M257, M259, M261, M264, M267, M274, M278, M282, M229, WTU-1/B, WDU-4/A, or WDU-4A/A, or other warheads, including those configured to provide surface-to-air or surface-to-surface capability. In yet further optional embodiments, the warhead **84** may be comprise any warhead having a threaded interface that allows for interchangeability with the one or more launchers **30** and/or the munition receptacle **32** of the at least one mobile munition assembly **10**. Where the munition **70** is loaded into the munition receptacle **32**, and is thereby inserted into the container **20**, a total weight of the container **20**, the munition receptacle **32**, and the munition **70** (including the warhead **84** therein) may range up to about fifty (50) pounds, though in other embodiments the total weight may be greater than the foregoing.

(36) The guidance system **87** of the munition **70** may include global positioning system (GPS) navigation or inertial guidance system (IGS) navigation. The GPS may determine a location of the munition **70** during a flight path **99** of the munition **70**, the flight path **99** of which is illustratively conveyed in FIG. **9**. GPS preferably comprises an antenna (not shown) and a processor (not shown), the processor of which provides position- and velocity-based data and analytics for suitable navigational coordinates. The GPS, which is associated with a data interface of a controller (not shown) for receiving from an external source, such as a satellite, location data pertaining to the mission environment **90** and one or more targetable assets **92**, may calculate expected relative location data of the munition **70** with respect to the one or more targetable assets **92** within the mission environment **90**.

(37) In other embodiments of the munition **70**, the IGS of the guidance system **87** may include one or more inertial measurement units (IMUs). IMUs may include a number of sensors including, but not limited to, accelerometers, which measure (among other things) velocity and acceleration, gyroscopes, which measure (among other things) angular velocity and angular acceleration, and magnetometers, which measure (among other things) strength and direction of a magnetic field. Generally, an accelerometer provides measurements, with respect to (among other things) force due to gravity, while a gyroscope provides measurements, with respect to (among other things) rigid body motion. The magnetometer provides measurements of the strength and the direction of the magnetic field, with respect to (among other things) known internal constants, or with respect to a known, accurately measured magnetic field. The magnetometer provides measurements of a magnetic field to yield information on positional, or angular, orientation of the IMU; similar to that of the magnetometer, the gyroscope yields information on a positional, or angular, orientation of the IMU. Accordingly, the magnetometer may be used in lieu of the gyroscope, or in combination

with the gyroscope, and complementary to the accelerometer, in order to produce local information and coordinates on the position, motion, and orientation of the IMU. Principally, the IMU may provide kinematic- or position-based data, including position, velocity, yaw, pitch, and roll. In optional embodiments, the IMU may constitute a micro electro-mechanical system (MEMS) in which the gyroscope and the accelerometer provide accurate information on attitude, azimuth, relative position, and velocity of the munition **70** during a trajectory or an altitude **98** of a launch of the munition **70** or the flight path **99** of the munition **70** in the mission environment **90**.

(38) Within the guidance system **87** of the munition **70**, a processing and control unit, such as a munition avionics processor (not shown), may be configured to process the data received from the IMU or the GPS to determine or estimate a location and orientation of the munition **70** in the mission environment **90**. The processing and control unit (not shown) of the guidance system **87** may be further configured to control the erection of the two or more wings **86**, the first fins **80**, and/or the second fins **82**, during the flight configuration **89**. Such erection of the two or more wings **86** during the flight configuration **89** may be actuated by the motor (not shown) housed within the munition frame **71**. In optional embodiments, the motor (not shown) may be electrically driven. The guidance system **87** may receive a requisite voltage to operate the motor (not shown) from a power source (not shown) and the processing and control unit (not shown) of the munition **70**. The processing and control unit (not shown) of the munition **70** may include a communication unit (not shown), configured to provide wireless communication between the processing control unit (not shown) of the munition **70** and the controller of the one or more launchers **30** or one of the one or more electronic devices **110**.

(39) FIG. 5 illustrates a flowchart providing an exemplary embodiment of the method **200** of executing a mission for the at least one mobile munition assembly **10**, in accordance with aspects of the present disclosure. The method **200** may commence with an operation **202** of deploying at least one mobile munition assembly **10** in the mission environment **90**. The stabilizer **40** may be operated from the first configuration **42** to the second configuration **43**, wherein the plurality of legs **41** are pivoted away from the container frame **22** of the container **20**. The second configuration **43** may place the container **20** in the upright position, such that the axis **26** defined along the container frame **22** from the first end **23** to the second end **24** is generally orthogonal to the surface **97** of the launch terrain **96**. Alternatively, where the stabilizer **40** is operated to the second configuration **43**, the container may be placed in a semi-upright position, such that the axis **26** from the first end **23** to the second end **24** may form an angle relative to the surface **97** of the launch terrain **96**, ranging from between about 30 degrees to 90 degrees. The munition **70** may be loaded into the munition receptacle **32**, and the munition receptacle inserted into at least one of the one or more launchers **30** of the at least one mobile munition assembly **10**.

(40) The method **200** may continue with an operation **204** of communicatively coupling one or more electronic devices **110**, by and through the communication unit **114**, with one another in the mission environment **90**, such that each of the one or more electronic devices **110** are in association with one another, and at least one of the one or more electronic devices **110** is associated with one or more of the at least one mobile munition assembly **10**. The one or more electronic devices **110** may form, or establish, the secure network **102** when the one or more electronic devices **110** are communicatively coupled to, and in association with, one another, as illustratively conveyed in FIGS. 1A-1D. In other optional embodiments, the one or more electronic devices **110** communicatively coupled to, and in association with, one another may be recruited to the secure network **102** by another of the one or more electronic devices **110** or by a remote system, such as the administrator **104**. In further optional embodiments, one or more electronic devices **110** may be communicatively connected to one another, wherein at least one of the one or more electronic devices **110** may be associated with one or more of the at least one mobile munition assembly **10**. As described previously, the secure network **102** may comprise a mobile ad-hoc network (MANET) or a wireless mesh network (WMN).

(41) The method **200** may continue with an operation **206** of transmitting at least signals representative of a situational awareness (SA) corresponding to each of the one or more electronic devices **110**, including those of the one or more electronic devices **110** associated with the at least one mobile munition assembly **10**. The signals representative of the situational awareness (SA) may be received and outputted by the location unit **115** and/or the sensor unit **116** to the controller **120**, the location unit **115** and/or the sensor unit **161** of which may be couplable to the communication **114**, as described above. For the purpose of the disclosure herein, signals representative of a situational awareness (SA) may include (without limitation) position location information (PLI) of the one or more electronic devices **110**, or any directional-, position-, or movement-related information pertaining to the one or more electronic devices **110** (including those associated with the at least one mobile munition assembly **10**) in the mission environment **90**. Situational awareness (SA) may also encompass environmental factors or other external conditions pertaining to, or affecting, the one or more electronic devices **110**, the at least one mobile munition assembly **10**, and/or the mission environment **90**, including any perception or monitoring of a targetable range **91**, one or more targetable assets **92**, one or more non-targetable assets **94**, or the munition **70** (and the altitude **98** or the flight path **99** of the munition **70**). Situational awareness (SA) may also include characteristics or features pertaining to the mission environment **90**, including a type of the launch terrain **96** (e.g., mountainous, rocky, desert- or tundra-like, wooded, forested, hilled, etc.) and the surface **97** of the launch terrain **96**. As depicted in FIG. 7, the signal representative of the situational awareness (SA) may be received, on or thorough the communication **114** of the one or more electronic devices **110**, by a communication (or “COMMO”) object **142** provided by the mission module **140** of the mission execution unit **130**, executable by the controller **120**. The COMMO object **142** may use device-specific libraries residing on the one or more electronic devices **110**, for the purpose of sending the information corresponding to the situational awareness (SA) of the one or more electronic devices **110** to a plug-in **144**, or other software application **144**, downloadable and implementable by the one or more electronic devices **110**. The plug-in **44** may include a cursor-on-target (CoT) Listener **146**, the CoT Listener **146** of which may be configured to filter the information corresponding to the situational awareness (SA) of the one or more electronic devices **110** (or information corresponding to the network **102**), including the one or more electronic devices **110** associated with one or more of the at least one mobile munition assembly **10**.

(42) The method **200** may continue with an operation **208** of enabling an input of parameters of the mission for the at least one mobile munition assembly **10**. The parameters of the mission for the at least one mobile munition assembly **10** may be inputted, manually or otherwise, on the display unit **117** on at least one of the one or more electronic devices **110** vis-à-vis a user interface on the display unit **117**. Accordingly, the system **100** may initiate with the entry (and receipt) of the parameters of the mission by and through the mission module **140** of the mission approval unit **130**, as depicted in FIGS. 5-6. The mission module **140** of the mission approval unit **130** may be executable by the controller **120** of any one of the one or more electronic devices **110**. The plug-in **144**, or the other software application **144**, may be configured to receive the parameters of the mission for the at least one mobile munition assembly **10**, whether provided by a user of the one or more electronic devices **110**, or provided by a centralized entity, such as the administrator **104**. In optional embodiments, the plug-in **144** may further include a content provider **148**, the content provider **148** of which may comprise a structured query language (SQL) database instantiated by the plug-in **144**. The plug-in **144** may receive the parameters of the mission, as illustratively conveyed in FIG. 7, by and through the display unit **117** having the user interface (UI) associated therewith, and the content provider **148** may receive, from the CoT Listener **146**, filtered information corresponding to the situational awareness (SA) of the one or more electronic devices **110**. Parameters of the mission may comprise any instructions, directions, or other guidance for the at least one mobile munition assembly **10** or the munition **70** launched therefrom, including an

instruction to launch the munition **70** at the one or more targetable assets **92** in the mission environment **90**, as illustratively conveyed in FIGS. **8-9**. Other parameters of the mission may include an instruction to select more than one of the at least one mobile munition assembly **10**, the function of which is to launch a plurality of munitions **70** at the one or more targetable assets **92** from a plurality of the at least one mobile munition assembly **10** in the mission environment **90**.

(43) One or more predefined rules **210** may be related to the parameters and may be configured to be applied to the parameters of the mission based on at least the status of the situational awareness (SA). The content provider **148** of the plug-in **144** may have stored thereon one or more predefined rules **210** related to at least the parameters of the mission. The one or more predefined rules **210** may comprise a rule set that is deterministic, presented in human-readable syntax, and/or may include static or dynamic elements pertaining to the mission. In optional embodiments, the one or more predefined rules **210** may include at least one of information corresponding to at least to one of a location of the one or more electronic devices **110** in the mission environment **90**, a location of the at least one mobile munition assembly **10** in the mission environment **90**, an identification of one or more targetable assets **92** in the mission environment **90**, an identification of one or more non-targetable assets **94** in the mission environment **90**, the altitude **98** of the munition **70** when launched from the at least one mobile munition assembly **10**, a trajectory of the munition **70** when launched from the at least one mobile munition assembly **10**, the flight path **99** of the munition **70** when launched from the at least mobile munition assembly **10**, a type of the warhead **84** located within the munition **70**, an impact radius of the munition **70**, or a time constraint on the mission. The one or more predefined rules **210** may also include at least one of a height, roughness, or other characteristic of the surface **97** of the launch terrain **96** provided in the mission environment **90**, nominal trajectory data associated with the munition **70** launched from the at least one mobile munition assembly **10**, or trajectory dispersions associated with the munition **70** launched from the at least one mobile munition assembly **10**, and combinations thereof. In other embodiments, the one or more predefined rules **210** may comprise a rule set presenting criteria for which the mission for the at least one mobile munition assembly **10** is at least one of the following: safe or unsafe conditions in the mission (e.g., presence of one or more non-targetable assets **94** in the mission environment **90**), too soon or too late for a duration of the mission, or too close or too far within the mission environment. In other optional embodiments, the one or more predefined rules **210** may include criteria pertaining to a proximity to third-party entities or assets, including individuals, structures, or vehicles, all of which may be classified as the non-targetable assets **94**, or areas otherwise geofenced or kept out within the mission environment **90**.

(44) In further optional embodiments, the one or more predefined rules **210** may comprise preloaded data pertaining to the mission for the at least one mobile munition assembly **10**, including (without limitation): latitudes, longitudes, and altitudes with respect to a common coordinate system as it pertains to the mission environment **90**; the type of munition **70** to be launched from the one or more launchers **30**; a propellant charge for the munition **70**, as well as the type and function of the fuze for the munition **70**; or a number of munitions **70** to be launched from the one or more launchers **30**, an azimuth of a launch of the munition **70**, or a method of control of the munition **70** subsequent to a launch and during the flight path **99**; and combinations thereof, or the like. Other preloaded data pertaining the to the mission for the at least one mobile munition assembly **10** may include mission data exchanged across the secure network **102** among the one or more electronic devices **110** (including those associated with the at least one mobile munition assembly **10**), including, but not limited to, command-to-launch messages, denial-of-mission messages, end-of-mission messages, check-fire messages, cancel-check-fire messages, and other support data exchanged across the network **102** of the one or more electronic devices **110** (including those associated with the at least one mobile munition assembly **10**).

(45) Application of the one or more predefined rules **210** to the parameters of the mission based at least on the signals representative of the situational awareness (SA) corresponding to each of the

one or more electronic devices **110** may be carried out by the safety module **150**, which is executable by the mission approval unit **130** of the controller **120**. The safety module **150** may receive, from the content provider **148** of the plug-in **144**, information corresponding to the situational awareness (SA) and the parameters of the mission, as well as the one or more predefined rules **210** related to at least the parameters of the mission. The application of the one or more predefined rules **210** by the safety module **150** may ascertain or determine whether the parameters of the mission comport with limitations or instructions provided by criteria of the one or more predefined rules **210**.

(46) The method **200** may continue with an operation **212** identifying the one or more targetable assets **92** and the one or more non-targetable assets **94** in the mission environment **90** based at least on the parameters of the mission for the at least one mobile munition assembly **10** and an application of the one or more predefined rules to the parameters of the mission. In optional embodiments, identification of the one or more targetable assets **92** and the one or more non-targetable assets **94** in the mission environment **90** may be carried out or effectuated by geo-based position locating or by a user manually identifying one or more non-targetable assets **94** and the one or more targetable assets **92** in the mission environment **90**; and, in other optional embodiments, the operation **212** of identifying the one or more targetable assets **92** within the mission environment may be carried out or effectuated by a laser-based rangefinder, such as FLIR's Recon V® rangefinder, where the laser-based rangefinder is configured to communicate with the one or more electronic devices **110** and provide position locator information to the one or more electronic devices **110** in the mission environment **90**.

(47) Referring to FIG. 8, the operation **212** of identifying the one or more targetable assets **92** in the mission environment **90** is illustratively depicted. The one or more targetable assets **92** may include a first targetable asset **92A**, a second targetable asset **92B**, a third targetable asset **92C**, and a fourth targetable asset **92D**. A first mobile munition assembly **10A**, a second mobile munition assembly **10B**, a third mobile munition assembly **10C**, and a fourth mobile munition assembly **10D** may be configured to identify one or more targetable assets **92** and one or more non-targetable assets **94** within a targetable range **91** corresponding to each of the at least one mobile munition assembly **10**. As depicted in FIG. 8, a first of the targetable range **91** may overlap or intersect with a second of the targetable range **91** (and so forth), given the physical proximity of the at least one mobile munition assembly **10** in the mission environment **90**. The targetable range **91** may have a radius ranging from about 500 meters to about 5 kilometers, the radius measured outwardly from a position of each of the at least one mobile munition assembly **10** in the mission environment **90**, or otherwise defined by the flight path **99** of the munition **70**. In optional embodiments, the one or more non-targetable assets **94** may include the least one mobile munition assembly **10** in the mission environment **90** and/or the one or more electronic devices **110**. The one or more non-targetable assets **94** may also include human users, observers, heavy equipment or machinery, vehicles, or other undesirable areas or assets that are not intended to be targeted by one or more of the at least one mobile munition assembly **10**.

(48) The method **200** may also continue with an operation **214** of reporting whether there is a mission error **216** (or mission fault **216**) detected by the one or more electronic devices **110** in the mission environment **90**. The mission error **216** may be detected by sending, at periodic intervals, a plurality test messages, to detect whether there is an error or fault with the one or more electronic devices **110** in communicatively coupling to, and in association with, one another, or whether there is an error (or a fault) in the secure network **102**. The safety module **150** of the mission approval unit **130**, executing independently of the mission module **140** of the mission approval unit **130**, allows for a detection of the mission error **216** with the one or more electronic devices **110** (including the one or more electronic devices **110** associated with at least one mobile munition assembly **10**) and/or the secure network **102**, as conveyed in FIG. 7. By sending, or injecting, the plurality test messages, at periodic intervals, the safety module **150** may determine the mission

error **216** in any component of the mission module **140**, including the communications and/or data exchanges among COMMO object **142**, the plug-in **144**, the CoT Listener **146**, or the content provider **148**, or the safety module **150** may determine other errors or faults with the one or more electronic devices **110**, the at least one mobile munition assembly **10**, and/or (in some embodiments) the munition **70**. The plurality of test messages—otherwise referred to as cursor-on-target (CoT) schema—may be generated by the safety module **50** and transmitted to the CoT Listener **146** of the plug-in **144**. The plug-in **144** may record the plurality of the test messages in the content provider **148**, which is thereby read by the safety module **150**. To the extent the mission error **216** is detected, such data is validated or ignored, for the purpose of otherwise reliably executing the mission for the at least one mobile munition assembly **10**. To execute the mission for the at least one mobile munition assembly **10**, a detection of the mission error **216** may require a consensus among the safety module **150** of each of the one or more electronic devices **110** in the secure network **102**, wherein a consensus mechanism may be employed to evaluate each safety module **150** against other of the safety module **150**, for the purpose of shifting decision-making to the most reliable safety module **150** among the one or more electronic devices **110**.

(49) In optional embodiments, the mission error **216** detected by the one or more electronic devices **110** may include at least one of a loss of communication, on the secure network **102**, of the one or more electronic devices **110** in the mission environment **90**, an uncertainty of a location of the one or more electronic devices **110** in the mission environment, an uncertainty of a location of the at least one mobile munition assembly **10** in the mission environment, a latency in the secure network **102**, an identification of one or more unauthorized devices on the secure network **102**, an alert that the munition **70** is not configured to be launched from one of the one or more launchers **30** in the mobile munition assembly **10**, an alert that at least one of the one or more launchers **30** does not have sufficient power to enable a launch of the munition **70** in the mission environment **90**, an alert that the warhead **84** located with the munition **70** does not conform with the parameters of the mission, or an alert that at least one of the one or more launchers **30** is not arranged in an orientation to enable a vertical launch of the munition **70** from the surface **97** of the launch terrain **96**. In other optional embodiments, the mission error **216** detected by the one or more electronic devices **110** may include at least one of an alert that the munition receptacle **32** is not properly or sufficiently inserted into the at least one of the one or more launchers **30**, or an alert that the munition **70** is not properly loaded into the munition receptacle **32** inserted into the at least one of the one or more launchers **30**. In further optional embodiments, the mission error **216** may include at least one of invalid or incorrectly formatted data in at least one of the one or more electronic devices **110**, a loss of data, such as data on the content provider **148** of at least one of the one or more electronic devices **110**, missing (or absent) entries of parameters or the one or more predefined rules **210** in the content provider **148** indicating a loss of signal among the one or more electronic devices **110** or the network **102**, out-of-sequence entries of parameters in the content provider **148** indicating clock- or time-related errors, missing (or absent) or misconfigured test messages injected into the mission module **140**, or an overflow of at least one or more electronic devices **110** or the network **102** caused by, for example, a denial-of-service or distributed denial-of-service, out-of-sequence entries, or simultaneous updating of more than one of the one or more electronic devices **110**, such as updating the mission module **140** or another routine software component residing on the one or more electronic devices **110**.

(50) Where the plurality of test messages have been sent (or injected), at periodic intervals, from the safety module **150** to the mission module **140** of the mission approval unit **130**, such that the mission error **216** is detected or not detected (and otherwise ignored or acknowledged), the method may **200** may continue with an operation **218** of requesting an authorization or a denial of the mission for the at least one mobile munition assembly **10**. Such a request of the authorization or the denial of the mission for the at least one mobile munition assembly **10** may be communicated from the plug-in **144** of the mission module **140** to the safety module **150**, wherein the safety module

150 evaluates whether to accept or to reject the request for the authorization of the mission for the at least one mobile munition assembly **10**. Evaluation may be effectuated through an evaluation, by the safety module **150**, of the application of the one or more predefined rules **210** to the parameters of the mission, including two-dimensional or three-dimensional assessments of the one or more targetable assets **92**, the one or more non-targetable assets **94**, locations of the one or more electronic devices **110** and the at least one mobile munition assembly **10**, and/or the mission environment **90**. Application of the one or more predefined rules **210** may be based on at least the status of the situational awareness (SA) corresponding to the one or more electronic devices **110**, as previously set forth herein. The method **200** may continue with an operation **220** of receiving the authorization of the mission for the at least one mobile munition assembly **10** in the mission environment **90**. The plug-in **144** of the mission module **140** may receive the authorization from the safety module **150**; but, to the extent the denial of the mission for the at least one mobile munition assembly **10** is received, the method **200** may return to the operation **218** of requesting the authorization of the mission for the at least one mobile munition assembly **10** until the mission is authorized to be executed in the mission environment **90**. To the extent the authorization of the mission for the at least one mobile munition assembly **10** is accepted, the mission may be signed, or otherwise authenticated, such as through public/private two-path authentication exchanged among the one or more electronic devices **110**. Each such signature or authentication of the mission for the at least one mobile munition assembly **10** may be unique to each of the one or more electronic devices **110**.

(51) Referring to FIG. 5, the method **200** may proceed with an operation **222** of selecting one or more of the at least one mobile munition assembly **10** to launch the munition **70** from the one or more of the at least one mobile munition assembly **10** in the mission environment **90**. The mission module **140** of the mission execution unit **130** of each of the one or more electronic devices **110** may select, whether by user input or through autonomous selection of the at least one mobile munition assembly **10**, which of the at least one mobile munition assembly **10** should be selected to launch the munition **70** in the mission environment **90**. Such selection may be based upon, among other things, geographical proximity or physical proximity of the at least one mobile munition assembly **10** to the one or more targetable assets **92**, the one or more non-targetable assets **94**, the altitude **98** of the launch of the munition **70**, a distance of the flight path **99** of the munition **70**, or other characteristics pertaining to the mission environment **90**, as previously discussed.

(52) Referring to FIG. 5, the method **200** may proceed with an operation **224** of commanding the one or more of the at least one mobile munition assembly **10** to launch the munition **70** from the one or more of the at least one mobile munition assembly **10** in the mission environment **90**. The operation **224** of commanding the one or more of the at least one mobile munition assembly **10**, having been selected in accordance with the operation **222**, may be remotely effectuated by the one or more electronic devices **110**, or by a one of the one or more electronic devices **110** associated with the at least one mobile munition assembly **10**. Such command may be made by a transceiver, or two-way radio, residing with the communication unit **114** of the one or more electronic devices **110**, and sent to another transceiver, or other two-way radio, of the one or more launchers **30**, so as to initiate a launch of the munition **70** from the at least one mobile munition assembly **10**.

(53) Referring to FIGS. 5 and 9, the method **200** may continue with an operation **226** of launching the munition **70** from the at least one mobile munition assembly **10**. The munition **70** may be configured to strike one or more targetable assets **92** in the mission environment **90** within a targetable range **91** of one or more of the at least one mobile munition assembly **10**, such as the first mobile munition assembly **10A**, the second mobile munition assembly **10B**, and/or the third mobile munition assembly **10C**. The operation **226** of launching the munition **70** may vertically launch the munition **70**, in its launch configuration **88**, to the altitude **98** (or the height **98**) from the surface **97** of the launch terrain **96** in the mission environment, including a height of up to about eight (8) kilometers. In optional embodiments of the method **200**, the method **200** may continue

with a step **228** of guiding the munition **70** in the flight path **99**, in its flight configuration **89**, to one of the one or more targetable assets **92** within the mission environment **90**. In optional embodiments, the flight path **99** may achieve a horizontal distance beginning from the launch terrain **96** to the one or more targetable assets **92** in the mission environment **90**, the horizontal distance ranging up to about 100 kilometers. In optional embodiments, the step **228** of guiding the munition **70** in the flight path **228** may be effectuated by global positioning system (GPS) navigation or inertial guidance system (IGS) navigation, and combinations thereof, or alternatively by inertial guidance system (IGS) navigation where global positioning system is denied by obstruction with the external source, such as the satellite.

(54) Referring to FIGS. **5** and **9**, the method **200** may continue with an operation **230** of impacting the munition **70** against or on one of the one or more targetable assets **92** in the mission environment **90**, or the method **200** may continue with an operation **232** of disabling the flight path **99** of the munition **70** in the mission environment **90** such that the munition **70** does not make impact with or against the one of the one or more targetable assets **92** in the mission environment **90**. Continuing with the operation **230**, the munition **90** may proceed along the flight path **99** (guided or not) in the direction of the one or more targetable assets **92**, eventually terminating in an impact on the one or more targetable assets **92** in the mission environment **90**. At impact, the warhead **84** within the munition **70** may be detonated by the fuze, wherein the fuze is any one of a time-based fuze, a proximity-based fuze, an impact-based fuze, a distance-measuring fuze, or an electronic-time fuze. Continuing with the operation **232** of disabling the flight path **99**, the one or more electronic devices **110** may remotely terminate the flight path **99** of the munition **70** where any one of the following conditions are met or triggered: the munition **70** is disabled by a user-initiated event, either by remotely terminating the motor of the munition **70** or remotely altering the flight path **99** by and through the guidance system **87** of the munition **70**; the one or more targetable assets **92** are identified within, or become located in proximity to, the one or more non-targetable assets **94** during the flight path **99** of the munition **70**; or at least one of the two or more fins, such as the first fins **80** and/or the second fins **82**, or at least one of the two or more wings **86**, and combinations thereof, are detached from the munition frame **71** or are otherwise damaged or rendered unworkable.

(55) To facilitate the understanding of the embodiments described herein, a number of terms have been defined above. The terms defined herein have meanings as commonly understood by a person of ordinary skill in the areas relevant to the present invention. The terminology herein is used to describe specific embodiments of the invention, but their usage does not delimit the invention, except as set forth in the claims.

(56) The term “user” as used herein unless otherwise stated may refer to an operator, such as a soldier or other individual operating in the mission environment **90**, an autonomous system, or any other person or entity as may be, e.g., associated with the electronic device **110**, the at least one mobile munition assembly **10**, the system **100**, the network **102**, and/or the administrator **104**.

(57) The term “mobile,” as used in connection with the at least one mobile munition assembly **10**, should be interpreted to mean portable, movable, mobile, haulable, transportable, or wieldy, such that a human-user (e.g., soldier or other individual operating in the mission environment **90**) may manageably lift, carry, and/or transport the at least one mobile munition assembly **10** in the mission environment **90**.

(58) The term “processor” as used herein may refer to at least general-purpose or specific-purpose processing devices, such as a central processing unit, and/or logic as may be understood by one of skill in the art, including but not limited to a microprocessor, a microcontroller, a state machine, and the like. The processor can also be implemented as a combination of computing devices, e.g., a combination of a digital signal processor (DSP) and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

(59) The terms “connected,” “attached,” “mounted,” “fixed,” “supported,” “engaged,” and the like, or any variation thereof, when referring to any mechanical, structural, physical, or tangible construction or configuration, should be interpreted to mean any manner of joining two objects including, but not limited to, the use of any fasteners such as screws, nuts and bolts, bolts, pin and clevis, and the like allowing for a stationary, translatable, or pivotable relationship; being integrally formed as a single part together; any mechanical fit such as a friction fit, interference fit, slidable fit, rotatable fit, pivotable fit, and the like; any combination thereof; and the like.

(60) It is understood that various operations, steps, or algorithms, including the method **200**, as described in connection with the system **100**, including (without limitation) the one or more electronic devices **110** (including those of the one or more electronic devices **110** associated with the at least one mobile munition assembly **10**), the administrator **104**, or alternative devices or computer structures or hierarchies, can be embodied directly in hardware, in a computer program product such as a software module executed by the processor **13** or any process related to, or embodied by, the foregoing. The computer program product can reside in the storage **18**, which may include RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, or any other form of computer-readable medium known in the art.

(61) Terms such as “a,” “an,” and “the” are not intended to refer to only a singular entity, but rather include the general class of which a specific example may be used for illustration.

(62) The phrases “in one embodiment,” “in optional embodiment(s),” and “in an exemplary embodiment,” or variations thereof, as used herein does not necessarily refer to the same embodiment, although it may.

(63) As used herein, the phrases “one or more,” “at least one,” “at least one of,” and “one or more of,” or variations thereof, when used with a list of items, means that different combinations of one or more of the items may be used and only one of each item in the list may be needed. For example, “one or more of” item A, item B, and item C may include, for example, without limitation, item A or item A and item B. This example also may include item A, item B, and item C, or item B and item C.

(64) Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements, and/or states. The conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. Thus, such conditional language is not generally intended to imply that features, elements, and/or states are in any way required for one or more embodiments, whether these features, elements, and/or states are included or are to be performed in any particular embodiment.

(65) The previous detailed description has been provided for the purposes of illustration and description. Thus, although there have been described particular embodiments of a new and useful invention, it is not intended that such references be construed as limitations upon the scope of this disclosure except as set forth in the following claims. Thus, it is seen that the apparatus of the present disclosure readily achieves the ends and advantages mentioned as well as those inherent therein. While certain preferred embodiments of the disclosure have been illustrated and described for present purposes, numerous changes in the arrangement and construction of parts and steps may be made by those skilled in the art, which changes are encompassed within the scope and spirit of the present disclosure as defined by the appended claims.

Claims

1. A method of executing a mission for at least one mobile munition assembly in a mission environment, the at least one mobile munition assembly comprising a container having a container frame, the container frame having a first end distally located from a second end, and the container frame enclosing one or more launchers, each of the one or more launchers configured to receive a munition, the method comprising: operating a stabilizer associated with the at least one mobile munition assembly to place the container in an upright position such that an axis defined along the container frame from the first end to the second end is generally orthogonal to a surface of a launch terrain upon which the container is mounted; forming a secure network of one or more electronic devices with one another in the mission environment when the one or more electronic devices are communicatively coupled to, and in association with, one another, at least one of the one or more electronic devices associated with one or more of the at least one mobile munition assembly; transmitting a status of a situational awareness (SA) corresponding to each of the one or more electronic devices in the mission environment; enabling an input of parameters of the mission for the at least one mobile munition assembly in the mission environment, the parameters having one or more predefined rules associated therewith, the one or more predefined rules configured to be applied to the parameters based on at least the status of the situational awareness (SA); the one or more predefined rules comprising a method of control of the munition subsequent to launch and during a directionally dynamic flight path; detecting, by at least one of the one or more electronic devices not associated with the at least one mobile munition assembly, the upright position of the container; establishing an omnidirectional targetable range outwardly extending from a position of each of the at least one mobile munition assembly in the mission environment; subsequent to enabling the input of parameters, detecting the upright position, and establishing the omnidirectional targetable range, requesting an authorization or a denial of the mission for the at least one mobile munition assembly; where an authorized mission request is received, launching the munition, in a launch configuration, in the directionally dynamic flight path; and subsequent to launch the munition, monitoring a condition of the munition associated with at least one of guiding, in a flight configuration, the munition within the omnidirectional targetable range, or disabling the directionally dynamic flight path of the munition.
2. The method of claim 1, further comprising: deploying the at least one mobile munition assembly on the surface of the launch terrain in the mission environment.
3. The method of claim 1, further comprising: identifying one or more targetable assets and one or more non-targetable assets in the mission environment based at least on the parameters of the mission for the at least one mobile munition assembly and an application of the one or more predefined rules to the parameters of the mission.
4. The method of claim 3, wherein: the one or more non-targetable assets include locations corresponding to the one or more electronic devices in the mission environment.
5. The method of claim 1, wherein: the one or more predefined rules related to the parameters of the mission include at least one of information corresponding to at least to one of a location of the one or more electronic devices in the mission environment, a location of the at least one mobile munition assembly in the mission environment, an identification of one or more targetable assets in the mission environment, an identification of one or more non-targetable assets in the mission environment, an altitude of the munition when launched from the at least one mobile munition assembly, a trajectory of the munition when launched from the at least one mobile munition assembly, a flight path of the munition when launched from the at least mobile munition assembly, a type of warhead located within the munition, an impact radius of the munition, or a time constraint on the mission.
6. The method of claim 1, further comprising: receiving the authorization of the mission for the at

least one mobile munition assembly in the mission environment.

7. The method of claim 6, further comprising: selecting one or more of the at least one mobile munition assembly to launch the munition from the one or more of the at least one mobile munition assembly in the mission environment.

8. The method of claim 7 further comprising: commanding the one or more of the at least one mobile munition assembly to launch the munition from the one or more of the at least one mobile munition assembly in the mission environment.

9. The method of claim 1, further comprising: reporting whether there is a mission error detected by the one or more electronic devices in the mission environment.

10. The method of claim 9, wherein: the mission error detected by the one or more electronic devices in the mission environment includes at least one of a loss of communication, on the secure network, of the one or more electronic devices in the mission environment, an uncertainty of a location of the one or more electronic devices in the mission environment, an uncertainty of a location of the at least one mobile munition assembly in the mission environment, a latency in the secure network, an identification of one or more unauthorized devices on the secure network, an alert that the munition is not configured to be launched from one of the one or more launchers in the mobile munition assembly, an alert that at least one of the one or more launchers does not have sufficient power to enable a launch of the munition in the mission environment, an alert that a warhead located with the munition does not conform with the parameters of the mission, or an alert that at least one of the one or more launchers is not arranged in an orientation to enable a vertical launch of the munition.

11. The method of claim 1, wherein: the munition includes a warhead having a length ranging from about ten (10) inches to about twenty (20) inches and a weight between about eight (8) pounds and fifteen (15) pounds.

12. The method of claim 1, wherein: the secure network comprises a mobile ad-hoc network (MANET) or a wireless mesh network (WMN).

13. The method of claim 1, wherein the stabilizer associated with the at least one mobile munition assembly is operated from a first configuration, wherein a plurality of legs thereof are folded up adjacent to the container frame, to a second configuration, wherein the plurality of legs are pivoted away from the container frame, to place the container in the upright position.

14. The method of claim 1, further comprising: operating the munition from the launch configuration to the flight configuration by deploying at least one of a wing or a fin.
