

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399164
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Smith; Brendan James et al.

Emissions estimate model algorithms and methods

Abstract

Systems, devices, and methods including a processor having addressable memory, the processor configured to: receive a trace-gas data packet, where the trace-gas data packet comprises a trace-gas concentration data from a trace-gas sensor and a location data for the trace-gas sensor from a location sensor, where the location data for the trace-gas sensor comprises a trajectory of the trace-gas sensor in space; receive at least one Meteorological data packet from one or more weather stations, where each weather station is distal from the trace-gas sensor, where each weather station generates a corresponding Meteorological data packet, where each Meteorological data packet comprises weather data; combine the trace-gas data packet with a selected spatial and temporal Meteorological data packet; and determine a trace-gas emission rate of a trace-gas source based on the combined trace-gas data packet and the selected Meteorological data packet.

Inventors: Smith; Brendan James (Lakeway, TX), Nottrott; Anders Andelman (Santa Barbara, CA), Aubrey; Andrew David (Austin, TX), Buckingham; Stuart (Austin, TX)

Applicant: SeekOps Inc. (Austin, TX)

Family ID: 1000008784435

Assignee: SeekOps Inc. (Austin, TX)

Appl. No.: 17/125863

Filed: December 17, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210140934 A1	May. 13, 2021

Related U.S. Application Data

continuation-in-part parent-doc US 16972156 PENDING WO PCT/US2019/038011 20190619
child-doc US 17125863
us-provisional-application US 62949309 20191217
us-provisional-application US 62687147 20180619

Publication Classification

Int. Cl.: **G01N33/00** (20060101); **B64U101/35** (20230101); **G05D1/00** (20240101); **G06V20/10** (20220101); **G06V20/13** (20220101); **G06V20/17** (20220101); **G08G5/26** (20250101); **G08G5/30** (20250101); B64U101/30 (20230101)

U.S. Cl.:

CPC **G01N33/0073** (20130101); **G05D1/0022** (20130101); **G05D1/0094** (20130101); **G05D1/106** (20190501); **G06V20/10** (20220101); **G06V20/13** (20220101); **G06V20/17** (20220101); **G08G5/26** (20250101); **G08G5/30** (20250101); B64U2101/30 (20230101); B64U2101/35 (20230101)

Field of Classification Search

CPC: G01N (33/0062); G01N (33/0047); B64C (39/024); B64D (47/00); H04L (5/0044); B64U (10/13); B64U (2201/20); B64U (2101/00); B64U (2201/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3780566	12/1972	Smith et al.	N/A	N/A
4135092	12/1978	Milly	250/338.5	G01N 1/2273
4233564	12/1979	Kerbel	N/A	N/A
4507558	12/1984	Bonne	N/A	N/A
4651010	12/1986	Javan	N/A	N/A
4988833	12/1990	Lai	N/A	N/A
5047639	12/1990	Wong	N/A	N/A
5075619	12/1990	Said	N/A	N/A
5173749	12/1991	Tell et al.	N/A	N/A
5291265	12/1993	Kebabian	N/A	N/A
5317156	12/1993	Cooper et al.	N/A	N/A
5767780	12/1997	Smith et al.	N/A	N/A
5822058	12/1997	Adler-Golden et al.	N/A	N/A
6064488	12/1999	Brand et al.	N/A	N/A
6295859	12/2000	Hayden et al.	N/A	N/A
6356350	12/2001	Silver et al.	N/A	N/A
6509566	12/2002	Wamsley et al.	N/A	N/A
6549630	12/2002	Bobisuthi	N/A	N/A
7162933	12/2006	Thompson et al.	N/A	N/A
7800751	12/2009	Silver et al.	N/A	N/A

7833480	12/2009	Blazewicz et al.	N/A	N/A
8060270	12/2010	Vian et al.	N/A	N/A
8294899	12/2011	Wong	N/A	N/A
8451120	12/2012	Johnson, Jr. et al.	N/A	N/A
8730461	12/2013	Andreussi	356/72	G01N 21/3103
9183371	12/2014	Narendra et al.	N/A	N/A
9183731	12/2014	Bokhary	N/A	N/A
9235974	12/2015	Johnson, Jr. et al.	N/A	N/A
9250175	12/2015	McManus	N/A	N/A
9494511	12/2015	Wilkins	N/A	N/A
9599529	12/2016	Steele et al.	N/A	N/A
9599597	12/2016	Steele et al.	N/A	N/A
10023311	12/2017	Lai et al.	N/A	N/A
10023323	12/2017	Roberts et al.	N/A	N/A
10031040	12/2017	Smith et al.	N/A	N/A
10126200	12/2017	Steele et al.	N/A	N/A
10268198	12/2018	Mantripragada et al.	N/A	N/A
10325485	12/2018	Schuster	N/A	N/A
10365646	12/2018	Farnsworth et al.	N/A	N/A
10429546	12/2018	Ulmer	N/A	N/A
10677771	12/2019	Dittberner et al.	N/A	N/A
10753864	12/2019	Kasten et al.	N/A	N/A
10816458	12/2019	Kasten et al.	N/A	N/A
10830034	12/2019	Cooley et al.	N/A	N/A
10962437	12/2020	Nottrott et al.	N/A	N/A
11105784	12/2020	Kukreja et al.	N/A	N/A
11112308	12/2020	Kreitinger et al.	N/A	N/A
11275068	12/2021	Willett	N/A	N/A
11299268	12/2021	Christensen et al.	N/A	N/A
11519855	12/2021	Black et al.	N/A	N/A
11557212	12/2022	Hong	N/A	N/A
11614430	12/2022	Buckingham et al.	N/A	N/A
11619562	12/2022	Leen et al.	N/A	N/A
11710411	12/2022	Van Meeteren et al.	N/A	N/A
11748866	12/2022	Vargas	N/A	N/A
12015386	12/2023	Gatabi et al.	N/A	N/A
2002/0005955	12/2001	Kramer et al.	N/A	N/A
2003/0160174	12/2002	Grant et al.	N/A	N/A
2003/0189711	12/2002	Orr et al.	N/A	N/A
2003/0230716	12/2002	Russell et al.	N/A	N/A
2004/0012787	12/2003	Galle et al.	N/A	N/A
2004/0017762	12/2003	Sogawa et al.	N/A	N/A
2004/0212804	12/2003	Neff et al.	N/A	N/A
2006/0015290	12/2005	Warburton et al.	N/A	N/A
2006/0044562	12/2005	Hagene et al.	N/A	N/A
2006/0232772	12/2005	Silver	N/A	N/A
2006/0234621	12/2005	Desrochers et al.	N/A	N/A
2007/0137318	12/2006	Desrochers et al.	N/A	N/A

2008/0169934	12/2007	Lang et al.	N/A	N/A
2008/0243372	12/2007	Bodin et al.	N/A	N/A
2009/0201507	12/2008	Kluczynski et al.	N/A	N/A
2009/0263286	12/2008	Isomura et al.	N/A	N/A
2009/0326792	12/2008	McGrath	701/4	G01W 1/08
2010/0004798	12/2009	Bodin et al.	N/A	N/A
2010/0131207	12/2009	Lippert	702/49	G01S 17/95
2010/0140478	12/2009	Wilson et al.	N/A	N/A
2010/0147081	12/2009	Thomas	N/A	N/A
2011/0035149	12/2010	McAndrew et al.	N/A	N/A
2011/0074476	12/2010	Heer et al.	N/A	N/A
2011/0150035	12/2010	Hanson et al.	N/A	N/A
2011/0164251	12/2010	Richter	N/A	N/A
2011/0213554	12/2010	Archibald et al.	N/A	N/A
2011/0242659	12/2010	Eckles et al.	N/A	N/A
2011/0257944	12/2010	Du et al.	N/A	N/A
2012/0120397	12/2011	Furtaw et al.	N/A	N/A
2013/0044314	12/2012	Koulikov et al.	N/A	N/A
2013/0061692	12/2012	Muresan et al.	N/A	N/A
2013/0076900	12/2012	Mrozek et al.	N/A	N/A
2013/0208262	12/2012	Andreussi	356/72	G01M 3/38
2014/0172323	12/2013	Marino	N/A	N/A
2014/0204382	12/2013	Christensen	N/A	N/A
2014/0236390	12/2013	Mohamadi	N/A	N/A
2014/0336957	12/2013	Hanson et al.	N/A	N/A
2015/0039256	12/2014	Michalske	N/A	N/A
2015/0072633	12/2014	Massarella et al.	N/A	N/A
2015/0145954	12/2014	Pulleti et al.	N/A	N/A
2015/0226575	12/2014	Rambo	N/A	N/A
2015/0275114	12/2014	Tumiatti et al.	N/A	N/A
2015/0295543	12/2014	Brown et al.	N/A	N/A
2015/0316473	12/2014	Kester et al.	N/A	N/A
2015/0323449	12/2014	Jones et al.	N/A	N/A
2015/0336667	12/2014	Srivastava et al.	N/A	N/A
2016/0018373	12/2015	Pagé et al.	N/A	N/A
2016/0070265	12/2015	Liu et al.	N/A	N/A
2016/0104250	12/2015	Allen et al.	N/A	N/A
2016/0146696	12/2015	Steele et al.	N/A	N/A
2016/0161456	12/2015	Risk et al.	N/A	N/A
2016/0202225	12/2015	Feng et al.	N/A	N/A
2016/0214715	12/2015	Meffert	N/A	G01S 17/88
2016/0216172	12/2015	Rella et al.	N/A	N/A
2016/0307447	12/2015	Johnson et al.	N/A	N/A
2016/0357192	12/2015	McGrew et al.	N/A	N/A
2017/0003684	12/2016	Knudsen et al.	N/A	N/A
2017/0057081	12/2016	Krohne et al.	N/A	N/A
2017/0089829	12/2016	Bartholomew et al.	N/A	N/A
2017/0093122	12/2016	Bean et al.	N/A	N/A
2017/0097274	12/2016	Thorpe et al.	N/A	N/A
2017/0115218	12/2016	Huang et al.	N/A	N/A

2017/0134497	12/2016	Harter et al.	N/A	N/A
2017/0158353	12/2016	Schmick	N/A	N/A
2017/0199647	12/2016	Richman et al.	N/A	N/A
2017/0206648	12/2016	Marra et al.	N/A	N/A
2017/0235018	12/2016	Foster et al.	N/A	N/A
2017/0259920	12/2016	Lai	N/A	G05D 1/0011
2017/0290034	12/2016	Desai et al.	N/A	N/A
2017/0307519	12/2016	Black et al.	N/A	N/A
2017/0336281	12/2016	Waxman et al.	N/A	N/A
2018/0023974	12/2017	Otani et al.	N/A	N/A
2018/0024091	12/2017	Wang et al.	N/A	N/A
2018/0045561	12/2017	Leen et al.	N/A	N/A
2018/0045596	12/2017	Prasad et al.	N/A	N/A
2018/0050798	12/2017	Kapuria	N/A	N/A
2018/0059003	12/2017	Jourdainne et al.	N/A	N/A
2018/0067066	12/2017	Giedd et al.	N/A	N/A
2018/0095478	12/2017	van Cruyningen	N/A	N/A
2018/0109767	12/2017	Li et al.	N/A	N/A
2018/0122246	12/2017	Clark	N/A	N/A
2018/0127093	12/2017	Christensen et al.	N/A	N/A
2018/0188129	12/2017	Choudhury et al.	N/A	N/A
2018/0209902	12/2017	Myshak et al.	N/A	N/A
2018/0259955	12/2017	Noto	N/A	N/A
2018/0266241	12/2017	Ferguson et al.	N/A	N/A
2018/0266946	12/2017	Kotidis et al.	N/A	N/A
2018/0284088	12/2017	Verbeck, IV	N/A	N/A
2018/0292374	12/2017	Dittberner et al.	N/A	N/A
2018/0321692	12/2017	Castillo-Effen et al.	N/A	N/A
2018/0322699	12/2017	Gray et al.	N/A	N/A
2019/0011920	12/2018	Heinonen et al.	N/A	N/A
2019/0011935	12/2018	Ham et al.	N/A	N/A
2019/0025199	12/2018	Koulikov	N/A	N/A
2019/0033194	12/2018	DeFreez et al.	N/A	N/A
2019/0049364	12/2018	Rubin	N/A	N/A
2019/0066479	12/2018	Wesley et al.	N/A	N/A
2019/0077506	12/2018	Shaw et al.	N/A	N/A
2019/0086202	12/2018	Guan et al.	N/A	N/A
2019/0095687	12/2018	Shaw et al.	N/A	N/A
2019/0154874	12/2018	Shams	N/A	B64C 1/0009
2019/0178743	12/2018	McNeil	N/A	N/A
2019/0195789	12/2018	Pan et al.	N/A	N/A
2019/0204189	12/2018	Mohr, Jr. et al.	N/A	N/A
2019/0212419	12/2018	Jeong et al.	N/A	N/A
2019/0220019	12/2018	Tan et al.	N/A	N/A
2019/0228573	12/2018	Sen et al.	N/A	N/A
2019/0234868	12/2018	Tanomura et al.	N/A	N/A
2019/0331652	12/2018	Ba et al.	N/A	N/A
2020/0050189	12/2019	Gu et al.	N/A	N/A

2020/0065433	12/2019	Duff et al.	N/A	N/A
2020/0109976	12/2019	Ajay et al.	N/A	N/A
2020/0135036	12/2019	Campbell	N/A	N/A
2020/0182779	12/2019	Kasten et al.	N/A	N/A
2020/0249092	12/2019	Podmore et al.	N/A	N/A
2020/0309690	12/2019	Green et al.	N/A	N/A
2020/0373172	12/2019	Suzuki	N/A	N/A
2020/0400635	12/2019	Potyrailo et al.	N/A	N/A
2021/0017926	12/2020	Alkadi et al.	N/A	N/A
2021/0037197	12/2020	Kester et al.	N/A	N/A
2021/0055180	12/2020	Thorpe et al.	N/A	N/A
2021/0109074	12/2020	Smith	N/A	G01N 33/0062
2021/0140934	12/2020	Smith	N/A	G05D 1/0094
2021/0190745	12/2020	Buckingham et al.	N/A	N/A
2021/0190918	12/2020	Li et al.	N/A	N/A
2021/0199565	12/2020	John et al.	N/A	N/A
2021/0247369	12/2020	Nottrott	N/A	B64C 39/024
2021/0255158	12/2020	Smith	N/A	B64D 47/00
2021/0300591	12/2020	Tian	N/A	N/A
2021/0321174	12/2020	Sun et al.	N/A	N/A
2021/0364427	12/2020	Smith et al.	N/A	N/A
2021/0382475	12/2020	Smith et al.	N/A	N/A
2022/0082495	12/2021	Kreitinger et al.	N/A	N/A
2022/0113290	12/2021	Smith et al.	N/A	N/A
2022/0170810	12/2021	Miller, II et al.	N/A	N/A
2022/0341806	12/2021	Miller et al.	N/A	N/A
2022/0357231	12/2021	Nahata et al.	N/A	N/A
2023/0194487	12/2022	Buckingham et al.	N/A	N/A
2023/0213413	12/2022	Mohr, Jr. et al.	N/A	N/A
2023/0274651	12/2022	McGuire et al.	N/A	N/A
2023/0392498	12/2022	Srivastav et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3401499	12/1998	AU	N/A
101470072	12/2008	CN	N/A
104458588	12/2014	CN	N/A
205749271	12/2015	CN	N/A
106568516	12/2016	CN	N/A
106769977	12/2016	CN	N/A
107703075	12/2017	CN	N/A
109780452	12/2018	CN	N/A
211508182	12/2019	CN	N/A
112213443	12/2020	CN	N/A
29601472	12/1995	DE	N/A
69333010	12/2003	DE	N/A

102014013822	12/2015	DE	N/A
0450809	12/1990	EP	N/A
1371962	12/2010	EP	N/A
3339855	12/2017	EP	N/A
3047073	12/2016	FR	N/A
3047073	12/2018	FR	N/A
2538563	12/2015	GB	N/A
H08247939	12/1995	JP	N/A
200975823	12/2008	JP	N/A
20170062813	12/2016	KR	N/A
101770254	12/2016	KR	N/A
522226	12/2002	TW	N/A
1999054700	12/1998	WO	N/A
02066950	12/2001	WO	N/A
2008021311	12/2007	WO	N/A
2015073687	12/2014	WO	N/A
2016045791	12/2015	WO	N/A
2016162673	12/2015	WO	N/A
2017069979	12/2016	WO	N/A
2018121478	12/2017	WO	N/A
2018227153	12/2017	WO	N/A
2019246280	12/2018	WO	N/A
2020007684	12/2019	WO	N/A
2020028353	12/2019	WO	N/A
2020086499	12/2019	WO	N/A
2020206006	12/2019	WO	N/A
2020206008	12/2019	WO	N/A
2020206020	12/2019	WO	N/A
2021055902	12/2020	WO	N/A
2021158916	12/2020	WO	N/A
2022093864	12/2021	WO	N/A
2022211837	12/2021	WO	N/A

OTHER PUBLICATIONS

1 International Search Report and Written Opinion for PCT/US19/38011 mailed Sep. 9, 2019. cited by applicant

U.S. Appl. No. 62/687,147, filed Jun. 19, 2018, Brendan James Smith. cited by applicant

“Safesite Multi-Threat Detection System”, Jul. 11, 2012 (Jul. 11, 2012), pp. 1-6, XP055245980.

cited by applicant

International Search Report and Written Opinion for PCT/US19/38015, mailed Oct. 18, 2019. cited by applicant

International Search Report and Written Opinion for PCT/US19/44119, mailed Oct. 17, 2019. cited by applicant

International Search Report and Written Opinion for PCT/US20/26228 mailed Jul. 1, 2020. cited by applicant

International Search Report and Written Opinion for PCT/US20/26232 mailed Jun. 26, 2020. cited by applicant

International Search Report and Written Opinion for PCT/US20/26246 mailed Jun. 29, 2020. cited by applicant

International Search Report and Written Opinion for PCT/US20/51696, mailed Feb. 3, 2021. cited

by applicant
 International Search Report and Written Opinion for PCT/US2020/044978, mailed Oct. 26, 2020.
 cited by applicant
 International Search Report and Written Opinion for PCT/US2021/016821 mailed Apr. 26, 2021.
 cited by applicant
 International Search Report and Written Opinion for PCT/US2021/024177, mailed Jun. 23, 2021.
 cited by applicant
 International Search Report and Written Opinion for PCT/US2021/056708, mailed Jan. 27, 2022.
 cited by applicant
 International Search Report and Written Opinion for PCT/US21/42061, mailed Nov. 26, 2021. cited
 by applicant
 International Search Report and Written Opinion for PCT/US21/44532, mailed Jan. 11, 2022. cited
 by applicant
 International Search Report and Written Opinion for PCT/US21/56710, mailed Feb. 23, 2022. cited
 by applicant
 International Search Report and Written Opinion of PCT/US19/57305, mailed Jan. 2, 2020. cited
 by applicant
 International Search Report and Written Opinion of PCT/US20/54117, mailed Dec. 22, 2020. cited
 by applicant
 Joly, "Atmospheric Measurements by Ultra-Light Spectrometer (AMULSE) Dedicated to Vertical
 Profile In Situ Measurements of Carbon Dioxide (CO₂) Under Weather Balloons: Instrumental
 Development and Field Application," Sensors 2016, 16, 1609. cited by applicant
 Khan, "Low Power Greenhouse Gas Sensors for Unmanned Aerial Vehicles", Remote Sns. 2012,
 4, 1355-1368. cited by applicant
 Villa. "An Overview of Small Unmanned Aerial Vehicles for Air Quality Measurements: Present
 Applications and Future Prospectives". Sensors. Web . Jul. 12, 2016. cited by applicant
 White, "Development of an Unmanned Aerial Vehicle for the Measurement of Turbulence in the
 Atmospheric Boundary Layer", Atmosphere, v.8, issue 10, 195, pp. 1-25. cited by applicant
 Lilian Joly, The evolution of AMULSE (Atmospheric Measurements by Ultra-Light Spectrometer)
 and its interest in atmospheric applications. Results of the Atmospheric Profiles of Greenhouse
 gasEs (APOGEE) weather balloon release campaign for satellite retrieval validation, p. 1-28, Sep.
 25, 2019, Atmospheric Measurement Techniques Discussion (Joly). cited by applicant
 International Search Report and Written Opinion for PCT/US22/38951, mailed Nov. 28, 2022. cited
 by applicant
 Kelly J F et al. "A capillary absorption spectrometer for stable carbon isotope ratio (C/C) analysis
 in very small samples", Review of Scientific Instruments, American Institute of Physics, 2
 Huntington Quadrangle, Melville, NY 11747, vol. 83, No. 2, Feb. 1, 2012 (Feb. 1, 2012), pp.
 23101-23101, XP012161835, ISSN: 0034-6748, DOI: 10.1063/1.3680593. cited by applicant
 Krings et al., Atmos. Meas. Tech., 11, 721-739, Feb. 7, 2018. cited by applicant
 International Search Report and Written Opinion for PCT/US23/13893, mailed Jun. 30, 2023. cited
 by applicant
 Clilverd, mark A. et al., Energetic particle injection, acceleration, and loss during the geomagnetic
 disturbances which upset Galaxy 15, Journal of Geophysical Research, vol. 117, A12213, doi:
 10.1029/2012JA018175, 2012, pp. 1-16 (Year:2012). cited by applicant
 Kem, Christoph et al., Spatial Distribution of Halogen Oxides in the Plume of Mount Pagan
 Volcano, Mariana Islands, Geophysical Research Letters 10.1029/2018GL079245, Sep. 27, 2018,
 pp. 9588-9596 (Year:2018). cited by applicant
 Liao, J. et al. Observations of Inorganic bromine(HOBr, BrO, and Br₂) speciation at Barrow,
 Alaska in spring 2009, Journal of Geophysical Research, vol. 117, D00R16,
 doi:10.1029/2011JD016641, 2012, pp. 1-11 (Year:2012). cited by applicant

Liu, Siwen et al., Development of a UAV-Based System to Monitor Air Quality over an Oil Field, Montana Technological University, Montana tech Library Digital Commons @ Montana Tech Graduate Theses & Non-Theses, Fall 2018, pp. 1-85 (Year:2018). cited by applicant

Miyama, Toru et al., Estimating allowable carbon emission for CO₂ concentration stabilization using a GCM-based Earth system model, Geophysical Research Letters, vol. 36,L19709, doi:10.1029/2009GL039678, 2009, pp. 0094-8276 (Year:2009). cited by applicant

Oppenheimer Clive et al., Ultraviolet Sensing of Volcanic Sulfur Emissions, Elements (An International Magazine of Mineralogy, Geochemistry, and Petrology), Apr. 2010, vol. 6, pp. 87-92 (Year: 2010). cited by applicant

Parazoo, Nicholas C. et al., Interpreting seasonal changes in the carbon balance of southern Amazonia using measurements of XCO₂ and chlorophyll fluorescence from GOSAT, Geophysical Research Letters, vol. 40.2829-2833, doi: 10.1002/grl.50452, 2013 pp. 0 2829-2833 (Year:2013). cited by applicant

Queiber, Manuel et al., A new frontier in CO₂ flux measurements using a highly portable DIAL laser system, Scientific Reports, DOI: 10.1038/srep33834 1, Sep. 22, 2016, pp. 1-13(Year:2016). cited by applicant

Queiber, Manuel et al., Large-area quantification of subaerial CO₂ anomalies with portable laser remote sensing and 2d tomography, The Leading Edge Mar. 2018, pp. 306-313 (Year:2018). cited by applicant

International Search Report and Written Opinion for PCT/US23/23905 mailed Oct. 5, 2023. cited by applicant

International Search Report and Written Opinion for PCT/US2023/023933 mailed Sep. 26, 2023. cited by applicant

Development of a mobile tracer correlation method for assessment of air emissions from landfills and other area sources, Atmospheric Environment 102 (2015) 323-330. T.A. Foster-Wittig et al. 2015. cited by applicant

Measurements of Methane Emissions from Landfills Using a Time Correlation Tracer Method Based on FTIR Absorption Spectroscopy, Environ. Sci. Technol. 2001, 35, 21-25, B. Galle et al. 2001. cited by applicant

IEEE Conference Paper, “Research of the high pressure jet performance of small size nozzle,” ISBN :978-1-5090-1087-5, Publication Date : Oct. 1, 2016, Conference dates Oct. 10, 2016 thru Oct. 12, 2016.[retrieved from the Internet] on Sep. 1, 2023 at 4:14pm. cited by applicant

Tao Lei et al:“Low-power, open-path mobile sensing platform for high—resolution measurements of greenhouse gases and air pollutants”, Applied Physics B, Springer Berlin Heidelberg, Berlin/Heidelberg, vol. 119, No. 1, Mar. 10, 2015 (Mar. 10, 2015), pp. 153-164, XP035445836, ISSN: 0946-2171, DOI:10.1007/ S00340-015-6069-1 [retrieved on Mar. 10, 2015]. cited by applicant

Tarsitano C G et al: Multilaser Herriott Cell for Planetary Tunable Laser Spectrometers', Applied Optics , Optical Society of America, Washington, DC, US, vol. 46, No. 28, Oct. 1, 2007 (Oct. 1, 2007), pp. 6923-6935, XP001508502, ISSN:0003-6935, DOI: 10.1364/AO.46.006923. cited by applicant

Adame J A et al: “Application of cluster analysis to surface ozone, NO and SO₂ daily patterns in an industrial area in Central-Southern Spain measured with a DOAS system”, Science of the Total Environment, Elsevier, Amsterdam, NL, vol. 429, Apr. 11, 2012 (Apr. 11, 2012), pp. 281-291, XP028491183, ISSN: 0048-9697, DOI: 10.1016/J.SCITOTENV.2012.04.032. cited by applicant

Coombes et al, “Optimal Polygon Decomposition for UAV Survey Coverage Path Planning in Wind”, published: Jul. 2018, publisher: ‘Sensors’ (Year:2018). cited by applicant

He et al. “Static Targets' Track Path for UAVs Meeting the Revisit Interval Requirement”, published :2013, publisher : IEEE (Year:2013). cited by applicant

Uehara, K: “Dependence of harmonic signals 1-15 on sample-gas parameters in wavelength-

modulation spectroscopy for precise absorption measurements”, Applied Physics B, Springer Berlin Heidelberg, Berlin/Heidelberg, vol. 67, Jan. 2, 1998, pp. 517-523, XP 007921671, ISSN:0946-2171, DOI: 10.1007/ S003400050537. cited by applicant

Day, S., and et al. “Characterisation of regional fluxes of methane in the Surat Basin, Queensland, Phase 1: A review and analysis of literature on methane detection and flux determination.” (2013) (Year: 2013). cited by applicant

Field Trial of Methane Emission Quantification Technologies, Society of Petroleum Engineers, SPE-201537-MS, Allen et al., Oct. 2020. cited by applicant

Feng, Lingbing, Nowak, Gen, O'Neill, T.J., Welsh, A.H. “Cutoff; A spatio-temporal imputation method.” Journal of Hydrology 519 (2014) : 3591-3605 (Year:2014). cited by applicant

Cabreira et al. “Survey on Coverage Path Planning with Unmanned Aerial Vehicles”, published: Drones, published: Jan. 2019, pp. 1-38, year 2019. cited by applicant

Feitz Andrew et al: “The Ginninderra CH₄ and CO₂ release experiment: An evaluation of gas detection and quantification techniques”, International Journal of Greenhouse Gas Control, Elsevier, Amsterdam, NL, vol. 70, Mar. 15, 2018 (Mar. 15, 2018), pp. 202-224, XP085368237, ISSN: 1750-5836, DOI: 10.1016/J.IJGGC.2017.11.018. cited by applicant

Jensen Morten Bang et al: “Quantification of greenhouse gas emissions from a biological waste treatment facility”, Waste Management, Elsevier, New York, NY, US, vol. 67, May 29, 2017 (May 29, 2017), pp. 375-384, XP085157318, ISSN: 0956-053X, DOI: 10.1016/J.WASMAN.2017.05.033. cited by applicant

Mohn Joachim et al: “A dual tracer ratio method for comparative emission measurements in an experimental dairy housing”, Atmospheric Environment, Elsevier, Amsterdam, NL, vol. 179, Feb. 1, 2018 (Feb. 1, 2018), pp. 12-22, XP085370597, ISSN: 1352-2310, DOI: 10.1016/J.ATMOENV.2018.01.057. cited by applicant

Primary Examiner: Kay; Douglas

Attorney, Agent or Firm: Command IP LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 16/972,156, filed Dec. 4, 2020, which is a 35 U.S.C § 371 National Stage Entry of International Application No. PCT/US2019/038011 filed Jun. 19, 2019, which claims the priority benefit of U.S. Provisional Patent Application Ser. No. 62/687,147 filed Jun. 19, 2018, and this application claims the priority benefit of U.S. Provisional Patent Application Ser. No. 62/949,309 filed Dec. 17, 2019, all of which are incorporated herein by reference in their entirety for all purposes.

FIELD OF ENDEAVOR

(1) Embodiments relate generally to trace-gas concentration measurement, and more particularly to Unmanned Aerial System (UAS) trace-gas concentration measurement.

BACKGROUND

(2) Methane (CH₄) is an odorless and colorless naturally occurring organic molecule, which is present in the atmosphere at average ambient levels of approximately 1.85 ppm as of 2018 and is projected to continually climb. While methane is found globally in the atmosphere, a significant amount is collected or “produced” through anthropogenic processes including exploration, extraction, and distribution of petroleum in the form of natural gas. Natural gas, an odorless and colorless gas, is a primary source of energy used to produce electricity and heat. The main

component of natural gas is methane (93.9 mol % CH₄ typ.). While extraction of natural gas is a large source of methane released to atmosphere, major contributors of methane also include livestock farming (enteric fermentation), and solid waste and wastewater treatment (anaerobic digestion).

SUMMARY

(3) In one embodiment, a system disclosed herein may include: a processor having addressable memory, the processor configured to: receive an unmanned aerial vehicle (UAV) data packet, where the UAV data packet comprises trace-gas concentration data and UAV information from a UAV flight path; receive at least one Meteorological data packet, where the Meteorological data packet comprises weather data; combine the UAV data packet with a nearest Meteorological data packet; and determine a trace-gas emission rate of a trace-gas source based on the combined UAV data packet and the nearest Meteorological data packet.

(4) Additional system embodiments may include: a display in communication with the processor, where the display may be configured to show the determined trace-gas emission rate of the trace-gas source on a map. In additional system embodiments, the map may be at least one of: a satellite image, an aerial image, a two-dimensional color map, a two-dimensional contour map, and a three-dimensional topographical surface.

(5) In additional system embodiments, the processor may be further configured to: determine the UAV flight path. In additional system embodiments, the UAV flight path may be a raster grid flight path downwind of the trace-gas source. In additional system embodiments, the UAV flight path may form a flight plane substantially perpendicular to a ground surface and an average wind direction. In additional system embodiments, the flightpath may be any flight path that intersects the area downstream of the leak source and varies in horizontal distance perpendicular to the axis of the wind direction and altitude.

(6) Additional system embodiments may include: a payload of a UAV, where the payload may include one or more gas concentration sensors configured to generate the trace-gas concentration data along the UAV flight path. In additional system embodiments, the UAV information along the UAV flight path may include at least one of: a location of the UAV, a time corresponding to the location of the UAV, a barometric pressure, an altitude, a relative altitude, and an orientation of the UAV, and where the UAV information along the UAV flight path corresponds to the generated trace-gas concentration data along the UAV flight path. In additional system embodiments, the location of the UAV may be determined by at least one of: a global positioning system (GPS), an onboard avionics, and a location sensor. In additional system embodiments, the relative altitude of the UAV may be determined by at least one of: an altitude of a global positioning system (GPS), a LIDAR, a Sonar, a radar, and a barometric pressure sensor. In additional system embodiments, the orientation of the UAV may be determined by at least one of: an inertial measurement unit (IMU) and an orientation sensor.

(7) Additional system embodiments may include: one or more weather stations, where each weather station generates the Meteorological data packet. In additional system embodiments, the Meteorological Data Packet may include data from at least one of: an anemometer, one or more pressure sensors, a pnyanometer, a ground temperature sensor, an air temperature sensor, and a current atmospheric condition sensor. In additional system embodiments, at least one of: a ground control station (GCS), a cloud server, the UAV, and the weather station may include the processor. In additional system embodiments, the determined trace-gas emission rate may be stored by at least one of: a ground control station (GCS), a cloud server, and one or more gas concentration sensors.

(8) In another embodiment, a method disclosed herein may include: receiving, by a processor having addressable memory, an unmanned aerial vehicle (UAV) data packet, where the UAV data packet comprises trace-gas concentration data and UAV information from a UAV controller; receiving, by the processor, at least one Meteorological data packet, where the Meteorological data packet comprises weather data; combining, by the processor, the UAV data packet with a nearest

Meteorological data packet; and determining, by the processor a trace-gas emission rate of a trace-gas source based on the combined UAV data packet and the nearest Meteorological data packet.

(9) Additional method embodiments may include: determining, by the processor, the UAV flight path, where the UAV flight path may be a raster grid pattern flight path, where the UAV flight path may be downwind of the trace-gas source, and where the UAV flight path forms a flight plane substantially perpendicular to a ground surface and an average wind direction. In additional method embodiments, the UAV flight path may be controlled by a user via a ground control station (GCS).

(10) Additional method embodiments may include: measuring, by a payload of a UAV, the trace-gas concentration data along the UAV flight path, where the payload comprises one or more gas concentration sensors; generating, by the UAV, the UAV data packet, where the UAV data packet comprises a spatial position of the UAV at each trace-gas concentration data measurement; and generating, by a weather station of one or more weather stations, the Meteorological data packet; where the UAV data packet comprises data from at least one of: a weather sensor, an onboard avionics, a barometric pressure sensor, an orientation sensor, an inertial measurement unit (IMU), a wireless radio, a global positioning system (GPS), a time measurement device, an altitude sensor, a location sensor, a radar, a lidar, an anemometer, an a Sonar; and where the Meteorological data packet comprises data from at least one of: an anemometer, one or more pressure sensors, a pryanometer, a ground temperature sensor, an air temperature sensor, and a current atmospheric condition sensor.

(11) In another embodiments, the system disclosed herein may include: an unmanned aerial vehicle configured to generate a UAV data packet; a payload of the UAV, where the payload comprises one or more gas concentration sensors configured to generate the trace-gas concentration data along a UAV flight path; one or more sensors of the UAV, where the one or more sensors of the UAV are configured to generate UAV information; one or more weather stations, where each weather station generates a Meteorological data packet, where the Meteorological data packet comprises weather data from one or more sensors of the weather station; and a processor having addressable memory, the processor in communication with the UAV and the one or more weather stations, where the processor configured to: receive the UAV data packet, where the UAV data packet comprises trace-gas concentration data from the payload and UAV information the one or more sensors of the UAV; receive at least one Meteorological data packet; combine the UAV data packet with a nearest Meteorological data packet; determine a trace-gas emission rate of a trace-gas source based on the combined UAV data packet and the nearest Meteorological data packet; and show the determined trace-gas emission rate of the trace-gas source on a map via a display in communication with the processor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principals of the invention. Like reference numerals designate corresponding parts throughout the different views. Embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings, in which:

(2) FIG. 1A depicts an illustration of an unmanned aerial system (UAS) emissions measurement process and flight path, according to one embodiment.

(3) FIG. 1B depicts a high-level block diagram of a UAS emissions measurement system, according to one embodiment.

(4) FIG. 1C depicts a high-level flowchart of a method embodiment of determining emissions measurements via unmanned aerial vehicle (UAV) data and weather data, according to one embodiment.

(5) FIG. 2 depicts a data flow in a single sensor and unmanned aerial vehicle (UAV) configuration with a Ground Control Station (GCS) as a point of interface between the UAS and the cloud-connected Processor, Local Server Processor, and/or Database, according to one embodiment.

(6) FIG. 3 depicts a data flow in a single sensor and UAV configuration with the UAS directly interfacing with the cloud-connected Processor, Local Server Processor, and/or Database, according to one embodiment.

(7) FIG. 4 depicts a detailed data transfer from a single sensor with a single UAV, where this combination of devices comprise a UAS, according to one embodiment.

(8) FIG. 5 depicts a background gas concentration workflow, according to one embodiment.

(9) FIG. 6A depicts a graph showing raw concentration data, filtered/interpolated data, and a background concentration estimation, according to one embodiment.

(10) FIG. 6B depicts a graph showing a concentration enhancement data resolved utilizing a sliding window median filter, according to one embodiment.

(11) FIG. 7 depicts a plane projection workflow, according to one embodiment.

(12) FIG. 8 depicts formulas for an orthogonal vector projection, according to one embodiment.

(13) FIG. 9A depicts an overhead view of the flux plane flight trajectory with a derived regression line used for projection, according to one embodiment.

(14) FIG. 9B depicts a flight trajectory projected onto the (y, z) plane, according to one embodiment.

(15) FIG. 10A depicts projected values along the (y, z) plane, according to one embodiment.

(16) FIG. 10B depicts an averaged and interpolated flux plane, according to one embodiment.

(17) FIG. 11 depicts a diagram illustrating the primary surface level sublayers in the Atmospheric Boundary Layer, according to one embodiment.

(18) FIG. 12A depicts a flux plane average flight path vector, average wind vector, and derived normal wind component, according to one embodiment.

(19) FIG. 12B depicts a modeled wind profile for the total wind and the derived orthogonal wind.

(20) FIG. 13 depicts a schematic drawing of an Emissions Estimate Model, according to one embodiment.

(21) FIG. 14 depicts a 3-dimensional illustration of a UAS system Emissions measurement process, according to one embodiment.

(22) FIG. 15 shows a high-level block diagram and process of a computing system for implementing an embodiment of the system and process.

(23) FIG. 16 shows a block diagram and process of an exemplary system in which an embodiment may be implemented.

(24) FIG. 17 depicts a cloud computing environment for implementing an embodiment of the system and process disclosed herein.

(25) FIG. 18A depicts a flight path that fully circumnavigates a potential trace gas source, according to one embodiment.

(26) FIG. 18B depicts a flight path that partially circumnavigates a potential trace gas source, according to one embodiment.

(27) FIG. 19 depicts a top view of a circumnavigated flight path that can be generated by a series of flight lines that are a set distance from equipment being inspected, according to one embodiment.

(28) FIG. 20 depicts flight paths that may be created based upon equipment or equipment grouping, according to one embodiment.

(29) FIG. 21 depicts a resultant UAV trajectory based on the equipment grouping of FIG. 20, according to one embodiment.

(30) FIG. 22 depicts a resultant geo-rectified trace gas concentration data from the resultant UAV trajectory of FIG. 21, according to one embodiment.

(31) FIG. 23 depicts a flight path covering a series of fully or semi-enclosed flight paths that may be strewn together to be completed in a single flight, according to one embodiment.

(32) FIG. 24 depicts triangulation results with a flux surface projected, according to one embodiment.

(33) FIG. 25 depicts a fully enclosed triangulation with concentration, according to one embodiment.

(34) FIG. 26 depicts a system for detecting trace gasses, according to one embodiment.

DETAILED DESCRIPTION

(35) The following description is made for the purpose of illustrating the general principles of the embodiments disclosed herein and is not meant to limit the concepts disclosed herein. Further, particular features described herein can be used in combination with other described features in each of the various possible combinations and permutations. Unless otherwise specifically defined herein, all terms are to be given their broadest possible interpretation including meanings implied from the description as well as meanings understood by those skilled in the art and/or as defined in dictionaries, treatises, etc.

(36) The present system and method disclosed herein allow for determining a trace-gas emission rate of a trace-gas source based on measurements from one or more sensors mounted on an unmanned aerial vehicle (UAV), UAV data, and one or more sensors from one or more weather stations. The UAV may fly a flight path downwind of the trace-gas source which transects a point downstream of the emission source and varies in the horizontal axis perpendicular to the wind direction and altitude. The path of the flight pattern may be substantially perpendicular to a ground surface and an average wind direction to measure trace-gas emissions downwind of the trace-gas source. Data from the one or more UAV sensors, the UAV data, and the one or more sensors from the one or more weather stations may be combined, stored, processed, and/or filtered to determine the trace-gas emission rate of the trace-gas source.

(37) In additional system embodiments, the flightpath may be any flight path that intersects the area downstream of the leak source and varies in horizontal distance perpendicular to the axis of the wind direction and altitude. The flux can be calculated by flying a spiral pattern around the emission source. The spiral pattern may be neither a raster pattern nor a plane. In some embodiments, the flight path may intersect the plume at different horizontal distances perpendicular to the plume (wind) and altitude.

(38) The goal of the natural gas production and supply chain is to deliver gas from source production areas to endpoint users without undue loss. Product loss in this context amounts to flaring or venting, intentional or otherwise, of natural gas to the atmosphere. Undue product loss results in uncaptured revenue, an increased environmental footprint, and possible safety hazards for vented emissions. There are many opportunities throughout the natural gas production and supply chain for gas to be released from containment and lost, such as pneumatic component venting, maintenance blowdowns, component failures, accidental release, and the like. Natural gas production and distribution infrastructure are spatially distributed. Efficient, wide area survey methods are needed to identify, localize, and quantify natural gas releases throughout these spatially distributed systems.

(39) The disclosed unmanned aerial system (UAS) measures trace-gas concentration along the chosen UAV flight path at high frequency to detect anomalies associated with natural gas releases. Data from the UAV may be reconciled with atmospheric conditions to identify and quantify the mass flow rate of natural gas sources within an inspection area.

(40) UAS Emissions Measurement System and Method

(41) The disclosed method for emission rate quantification is based on an engineering control volume model. The UAS has a fast response, in situ trace-gas sensor payload and flies downwind of potential emission sources on transects that are nearly perpendicular to the average wind direction approximately ± 90 degrees. The trace-gas may include methane in some embodiments. The disclosed trace-gas sensor may be capable of measuring multiple hydrocarbon species typically found in natural gas and can be used to determine whether a gas leak consists of natural gas, i.e.,

methane and ethane are detected simultaneously, or only methane, thereby attributing whether the source of the leak is natural gas infrastructure, or anaerobic digestion or enteric fermentation. The disclosed sensors measure the crosswind and vertical profile of trace-gas concentration and maps out the spatial profile of trace-gas emissions from upwind sources as well as the characteristics of the background concentration variability.

(42) FIG. 1A depicts an illustration of an unmanned aerial system (UAS) emissions measurement process and flight path **100**, according to one embodiment. A representative flight path **102** of an unmanned aerial vehicle (UAV) **104** is downwind of a point source **108**. In this example, the point source **108** is a pump jack, but the point source **108** may be any equipment having a potential to emit gas. The UAV **104** measures a cross-section of an emissions plume **106** from the point source **108** on a vertical plane. In addition to concentration, emission rate estimates are determined by wind velocity along the UAV flight path **102**.

(43) To capture a downwind “control surface” for the emissions estimate, the disclosed UAV **104** flies a raster grid pattern flight path **102** along a vertical plane that is perpendicular to a ground surface **110** and the average wind direction ± 90 degrees. The position of the UAV **104** and corresponding natural gas concentration measurement are recorded, such as by a global positioning system (GPS) position. The altitude of the UAV **104** relative to the ground **110** may be further quantified using a range-finding LIDAR, Sonar, radar, GPS altitude, and/or barometric pressure sensor.

(44) FIG. 1B depicts a high-level block diagram of a UAS emissions measurement system **112**, according to one embodiment. The system **112** may include a UAV **104**. In some embodiments, the UAV **104** may be a quadcopter-style aerial vehicle capable of hovering and flying the raster pattern flight path, as shown in FIG. 1A. In other embodiments, the UAV **104** may be a winged aerial vehicle. The UAV **104** may have any number of rotors, motors **128**, wings, or the like to sustain flight and fly the determined UAV flight path. The UAV **104** may have the ability to fly in a three-dimensional flight path in the vicinity of a potential trace-gas source (**108**, FIG. 1A). The UAV **104** may fly ≤ 200 m from a 0.1 SCFH emissions point.

(45) Embodiments of the unmanned aerial vehicle **104** may include any number of sensors shown in FIG. 1B based on the desired data. Embodiments of the weather station **154** may include any number of sensors shown in FIG. 1B based on the desired data. In some embodiments, the weather station **154** may only include an anemometer **160**. In other embodiments, the weather station **154** may be integrated into the unmanned aerial vehicle **104**. For example, the anemometer **160** may be integrated on the unmanned aerial vehicle **104**. In another embodiment, the weather station **154** may be located on another aerial vehicle or unmanned aerial vehicle. For example, the system may include two or more unmanned aerial vehicles where at least one unmanned aerial vehicle is recording trace-gas gas concentrations and at least one unmanned aerial vehicle is recording meteorological data. The weather station **154** may be stationary or mobile. The weather station **154** may be in relatively close proximity to the unmanned aerial vehicle **104**. In some embodiments, the weather station **154** may record meteorological data. In some embodiments, the weather station **154** may be from a third-party source, such as a third-party sensor. In some embodiments, the weather station **154** may predict future meteorological measurements. The nearest temporal Meteorological (MET) data packet **174** may be combined with the UAV data packet or trace-gas data packet **152**. The frequency of each of the MET data packet **174** and the trace-gas data packet **152** may be different but close in some embodiments. The frequency of each of the MET data packet **174** and the trace-gas data packet **152** may be substantially the same in some embodiments.

(46) The UAV **104** may have a global positioning system **114**, an onboard avionics **117**, and/or a location sensor **118** to track a spatial position of the UAV **104** as it travels along the flight path (**102**, FIG. 1A). The UAV **104** may track its spatial position as it measures gas concentrations along the flight path such that each gas measurement of the UAV **104** corresponds to a spatial position where that gas measurement was taken. The global positioning system **114**, onboard avionics **117**,

and/or location sensor **118** may be in communication with a UAV processor **116** having addressable memory **118**. In some embodiments, the location of the UAV **104** may be determined by the onboard avionics **117**. The onboard avionics **117** may include a triangulation system, a beacon, a spatial coordinate system, or the like. The onboard avionics **117** may be used with the GPS **114** and/or location sensor **118** in some embodiments. In other embodiments, the UAV **104** may use only one of the GPS **114**, the onboard avionics **117**, and/or the location sensor **118**.

(47) The UAV **104** may include a payload **120** in communication with the UAV processor **116**. The payload **120** may include one or more gas concentration sensors. The payload **120** may be detachably attached to the UAV **104**. In other embodiments, the payload **120** may be fixedly attached to the UAV **104**. The payload **120** may be in communication with the UAV processor **116**. In one embodiment, the payload **120** may be an ultra-lightweight, low power, Part per Billion (ppb) sensitivity, mid-Infrared ($\lambda=3-8\ \mu\text{m}$), open path trace-gas concentration sensor with sampling rate $>0.1\ \text{Hz}$.

(48) The UAV processor **116** may also be in communication with an orientation sensor **128**, an inertial measurement unit (IMU) **130**, an altitude sensor **132**, a radar **134**, a LIDAR **136**, and/or a Sonar **138** for generating additional information on the spatial position of the UAV **104** during each gas measurement by the payload **120**. The orientation sensor **128** may be used to determine an orientation of the UAV **104** relative to ground. In some embodiments, the orientation sensor **128** may be a compass. The IMU **130** may be used to determine attitude, velocity and/or position of the UAV **104**. The altitude sensor **132** may be used to determine an altitude of the UAV **104**. The LIDAR **136**, Sonar **138**, and/or radar **134** may be used to determine a relative altitude of the UAV **104**.

(49) In some embodiments, the UAV processor **116** may also be in communication with an anemometer **142**, one or more weather sensors **144**, and/or a barometric pressure sensor **146**. The anemometer **142** may be used to measure the speed of the wind. The anemometer **142** may be attached to the UAV **104** at a point so as to ensure an accurate wind measurement without interfering with the propulsion from the motors **128** or sensors of the payload **120**. The weather sensor **144** may measure weather and/or atmospheric conditions. The barometric pressure sensor **146** may measure a barometric pressure. The anemometer **142**, weather sensor **144**, and/or barometric pressure sensor **146** may be used to record data at each gas measurement from the payload **120**.

(50) In some embodiments, the UAV processor **116** may also be in communication with a time measurement device **140**. The time measurement device **140** may be used to record the time for each gas measurement measured by the payload **120** of the UAV **104**. Each gas measurement, position measurement, orientation measurement, weather measurement, and/or relative altitude measurement may be 'time-stamped' so as to be combined by the processor **122** and/or the UAV processor **116**.

(51) The UAV processor **116** may also be in communication with a transceiver **148** and/or a wireless radio **150**. The wireless radio may include LTE, satellite, or the like. The transceiver **148** and/or wireless radio **150** may be used to communicate between the UAV **104** and the processor **122**, the ground control station (GCS) **126**, and/or a cloud server **124**.

(52) The processor **122**, the cloud server **124**, the ground control station (GCS) **126**, and/or the UAV processor **116** may determine a flight path for the UAV **104** having the payload **120**. In some embodiments, the flight path may be determined on a site-specific basis. In other embodiments, the flight path may be determined and/or flown via a user of the GCS **126**. In other embodiments, the flight path may be self-determined, autonomous control. The flight path is used to measure gas concentration along a crosswind transect, and vertical profile, in the vicinity of a possible gas emissions point. This flight plane of the flight path is designed to capture the atmospheric trace-gas background as well as emissions signature, i.e., elevated ambient concentration, from all potential sources at an inspection site.

(53) The UAV **104** may have the UAV processor **116** in communication with addressable memory **118**, a GPS **114**, one or more motors **128**, and a power supply **130**. The UAV **104** may communicate gathered payload **120** data to the UAV processor **116**. The power supply **130** may be a battery in some embodiments. In some embodiments, the processor **122** may be a part of the UAV **104**, the cloud server **124**, the GCS **126** used to control the UAV **104**, or the like.

(54) The UAV processor **116** may receive gas data from the one or more gas sensors of the payload **120**. The UAV processor **116** may also receive spatial position data from the GPS **114**, altitude sensor **132**, location sensor **118**, radar **134**, LIDAR **136**, Sonar **138**, orientation sensor **128**, IMU **130**, and/or onboard avionics **117**. In some embodiments, the UAV processor **116** may also receive weather data from the weather sensor **144**, the barometric pressure sensor **146**, and/or the anemometer. The UAV processor **116** may also receive the time from the time measurement device **140**. The UAV processor **116** may fuse the gas data from the payload **120** with the UAV **104** spatial position data, weather data, and/or time to form a trace-gas Data Packet **152**.

(55) The trace-gas data packet **152** may be sent to the processor **122**, ground control station **126**, and/or cloud server **124** via the transceiver **148** and/or wireless radio **150**. In some embodiments, the wireless radio **150** or cellular connection may be used for remote data transfer between the UAV **104**, the GCS **126**, the processor **122**, and/or the cloud server **124**. The wireless interface or cellular connection between the UAV **104**, the GCS **126**, the processor **122**, and/or the cloud server **124** may be used to performing advanced data analysis functions. Direct, bidirectional data transfer may occur between the UAV **104** and the GCS **126**, between the UAV **104** and the cloud server **124**, and/or between the GCS **124** and the cloud server **124**.

(56) The processor **122** may be a part of the UAV **104**, the GCS **126**, the cloud server **124**, and/or the weather station **154** in some embodiments. While multiple sensors and devices are depicted for the UAV **104**, any number of sensors and/or devices may be used based on the system **112**, desired accuracy, time limitations, weight limitations, and the like.

(57) One or more weather stations **154**, **156**, **158** may provide local weather information to the UAV **104**, payload **120**, GCS **126**, and/or cloud server **124**. The weather stations **154**, **156**, **158** may also receive information from the UAV **104**, payload **120**, GCS **126**, and/or cloud server **124**.

(58) The first weather station **154** may include one or more anemometers **160**, one or more pressure sensors **162**, one or more pyranometers **164**, one or more ground temperature sensors **166**, one or more air temperature sensors **168**, one or more atmospheric condition sensors **170**, and one or more location sensors **172**. The anemometer may be used to measure wind speed. The pressure sensor **162** may measure a pressure. The pyranometer may be used to measure solar irradiance. The ground temperature sensor **166** may be used to measure a temperature of the ground. The air temperature sensor **168** may be used to measure a temperature of the air. An atmospheric condition sensor **170** may be used to measure data relating to the atmosphere. The location sensor **172** may be used to measure the location of the weather station **154**. Each weather station **154**, **156**, **158** may include any number of sensors and/or devices based on the system **112**, desired accuracy, number of weather stations over a geographical area, and the like.

(59) In some embodiments, sensors and/or devices of the weather station **154** may be located and/or duplicated on the UAV **104**. High resolution (<0.1 m/s), high-frequency measurements (>5 Hz) of wind speed and direction may be recorded using one or more wind sensors, and one or more additional weather/micro-meteorological sensors including, air temperature, humidity, atmospheric pressure, solar irradiance, ground surface temperature—from the ground via a weather station **154**, **156**, **158** and/or from the UAV **104** as disclosed herein. For example, both the weather station **154** and the UAV **104** may include respective anemometers **160**, **142**, which may be used to generate wind speed data. The weather station data may be associated with a time the data was collected and/or generated. The weather station data may be used to generate a Meteorological (MET) data packet **174**. The Meteorological data packet **174** may be sent to the processor **122**, ground control station **126**, cloud server **124**, and/or UAV **104**. The Meteorological data packet **174** may include

measurements and/or predictions of the atmosphere, weather, temperature, wind patterns, or the like.

(60) Each trace-gas Data Packet **152** may be combined with the nearest temporal Meteorological Data Packet **174** by the processor **122** and saved on the GCS **126** and/or cloud server **124**. The data may be uploaded to the cloud server **124** in real-time, near real-time, or at a later time. The combined trace-gas data packet **152** and Meteorological data packet **174** may be used to determine a trace-gas emission rate of the trace-gas source by the processor **122**, GCS **126**, and/or cloud server **124**. The trace-gas emission rate may be determined based on a control volume model that combines concentration measurements from the UAV flight plane with measured wind speed, direction and spatial gradient to determine the mass flow rate emissions from sources in the inspection area.

(61) This determined trace-gas emission rate may be stored by the processor **122**, GCS **126**, and/or cloud server **124**. In some embodiments, the determined emission rate may be shown on a display **176**. The display **176** may show source emissions data on a map, satellite image, aerial image, two-dimensional color map, two-dimensional contour map, and/or three-dimensional topographical surface/mesh.

(62) FIG. **1C** depicts a high-level flowchart of a method **178** embodiment of determining emissions measurements via unmanned aerial vehicle (UAV) data and weather data, according to one embodiment. The method **178** may include determining, by a processor, a flight path of a UAV downwind of a trace-gas source (step **180**). The method **178** may then include generating a UAV data packet include a measured trace-gas concentration and UAV information from the determined flight path (step **182**). The method **178** may then include generating, by a weather station, a Meteorological data packet including data measured by the weather station **184**. The method **178** may then include receiving, by the processor, the UAV data packet and the Meteorological data packet (step **186**). The method may then include combining, by the processor, the received UAV data packet with a nearest temporal, i.e., in time, received Meteorological data packet (step **188**). The method **178** may then include determining, by the processor, a trace-gas emission rate of the trace-gas source based on the combined received UAV data packet and the Meteorological data packet (step **190**). The method **178** may then include sending, by the processor, the determined emission rate of the trace-gas source to a cloud server (step **192**).

(63) Data Transfer Scheme

(64) FIG. **2** depicts a data flow **200** in a single sensor and unmanned aerial vehicle (UAV) **202** configuration with a ground control station (GCS) **206** as a point of interface between the UAV **202** and the cloud-connected processor, local server processor, and/or database **208**, according to one embodiment. The general flow of data is from one or more gas concentration sensors, i.e., payload **204**, affixed to one or more UAVs **202** and wirelessly transmitted to the centralized GCS **206** and then transferred to the cloud-connected Server, Processor, Local Server Processor, and/or Database **206**.

(65) A weather station **210** may provide local weather information to the UAV **202**, payload **204**, and/or GCS **206**. The weather station **210** may also receive information from the UAV **202**, GCS **206**, and/or payload **204**. The UAV **202** vehicle state and other information may be transmitted by the UAV **202** and received by the GCS **206**. The GCS may send command and control information to the UAV **202**. The payload **204** may provide and/or receive payload data between the payload **204** and the UAV **202** and/or the GCS **206**.

(66) FIG. **3** depicts a data flow **300** in a single sensor and UAV **202** configuration with the UAV **202** directly interfacing with the cloud-connected processor, local server processor, and/or database **208**, according to one embodiment. In another embodiment, the payload(s) **204**, UAV(s) **202**, and/or weather station(s) **210** communicate directly with a cloud server processor, local server processor, and/or database **208**. In all cases, each subsystem, i.e., UAV **202**; payload **204**; GCS (see FIG. **2**); cloud server processor, local server processor, and/or database **208**; and weather station

210, may or may not have the ability to directly communicate with each other subsystem, as shown in FIGS. **1A-2**. At the GCS (see FIG. **2**), and/or cloud server processor, local server processor, and/or database **208**, the data from the payload **204** is coupled with local weather station **210** data through local private networks and/or publicly available over the Internet. The data can then be post-processed on the GCS (see FIG. **2**), on a local server, and/or on a cloud-hosted server **208**. (67) FIG. **4** depicts a detailed data transfer **400** from a single sensor with a single UAV **202**, where this combination of devices comprise a UAS, according to one embodiment. Data from the payload **204** transfers to the UAV **202** and directly to an autopilot **404** via a serial connection. In some embodiments, the data transfer from the UAV **202** to the autopilot **404** may be any connection hardware or wireless. Then, the data transfer is fused with GPS location and time, barometric pressure, altitude, relative altitude from LiDAR, Sonar, Radar, and/or UAV orientation, which forms a UAV Data Packet. The UAV Data Packet may be transferred to the GCS and/or cloud processor **402** via a 500 mW 915 MHz Frequency Hopping Spread Spectrum (FHSS) transceiver. In some embodiments, the UAV Data Packet may be transferred via any wireless radio. In parallel, a weather station **210** having at least an anemometer, and may contain one or more pressure sensors, pyranometers, i.e., for solar irradiance, ground temperature sensors, air temperature sensors, and/or any sensor necessary for quantifying current atmospheric conditions, may form a Meteorological Data Packet. The GCS and/or cloud processor **402** receives both the Meteorological Data Packet and UAV Data Packet at a frequency greater than 0.1 Hz. Each UAV Data Packet is fused with the nearest temporal Meteorological Data Packet and saved on the GCS and/or a cloud server, local server, and/or database **402** in an ASCII, binary, or any file necessary. The data may be uploaded to a cloud server in real-time, near real-time, or at a later time.

(68) Background Calculation

(69) FIG. **5** depicts a background gas concentration workflow **500**, according to one embodiment. The first step in the emissions estimate model is to calculate the control volume in-flow condition. The in-flow condition will determine total emissions for the source area that is of interested, by accounting for and subtracting any emissions from upwind sources. Typically, it is assumed that the background concentration measured on the upwind side of the source inspection area is a good representation of the local background concentration and provides an estimate of the upwind in-flow condition. The procedure for calculating the background concentration starts with selecting data for the appropriate time period (step **502**). Then, the GPS coordinates, i.e., longitude and latitude, are framed to along a path distance (step **504**). Third, a statistical filter is applied to the concentration data (step **506**).

(70) FIG. **6A** depicts a graph **600** showing raw concentration data **602**, filtered/interpolated data **604**, and a background concentration estimation **606**, according to one embodiment. FIG. **6B** depicts a graph **608** showing a concentration enhancement data resolved utilizing a sliding window median filter, according to one embodiment. In additional embodiments, a low-pass filter can be applied to the concentration series to generate a background concentration series. In additional embodiments, such as a flight path that circumnavigates the emission source, the background concentration can be calculated by calculating the mass-flow weighted average of the detected concentration upwind of the potential emission source. In embodiments where a filtering function is used, raw concentration data as a function of distance, i.e., spatial coordinate, is filtered using the prescribed filter. The filter window scale is determined based on a typical, or expected, gas plume width. For example, if the maximum plume width is expected to be on the order of 10 m, the filter scale would be set to three to five times the max plume width. The median filter also removes infrequent transients, or dropouts, in the concentration measurement caused by communication interference, or platform vibrations. The background concentration is subtracted from the total concentration to obtain the concentration enhancement. The concentration enhancement signal represents the signature of an upwind emission source where the flight path is only downwind of the emission source. In embodiments where the flight path circumnavigates the emission source,

the concentration enhancement signal represents the signature of an emission within the bounds of the flightpath. The signature calculated is used to quantify the emissions released by the local source.

(71) Spike/Emissions Detection

(72) Spike detection on the concentration enhancement signal is performed as part of the emissions calculation to determine if an emission source is present upwind of the flight path. This is a binary determination step, after performing spike detection on the concentration enhancement signal the remaining portion of the emissions algorithm only continues if an upwind emission source is present.

(73) A statistical filter is then applied to the concentration enhancement signal to identify “spikes” in the data that indicate trace-gas plumes from nearby sources. The statistical filter is determined by analysis of the Cumulative Distribution Function (CDF) for the concentration enhancement, and targets extremum data points based on a prescribed percentile threshold. In additional embodiments, the spike is detected with a quantile analysis. In additional embodiments, the spike is detected with a high-pass filter and threshold. The selected points are then analyzed for contiguity and consolidated to form spatially continuous events. Each spike event may be further analyzed according to other metrics such as spatial extent, amplitude, magnitude, variance, and waveform shape. Individual spike events may be included or excluded through a selection process based on these derived quantities.

(74) Plane Projection

(75) FIG. 7 depicts a plane projection workflow **700**, according to one embodiment. Due to variability in the flight trajectory caused by wind and GPS uncertainty, it is not generally possible to fly perfect transects along the same line at various heights. Therefore, an automatic detection of the nominal flight path, or plane, orientation may be performed using a least-squares fitting method to the data. First, data is selected for the appropriate time period (step **702**). Then, a GPS coordinate, i.e., longitude and latitude, frame is converted to a Cartesian frame, i.e., x and y (step **704**). Then, the nominal flight path is calculated, e.g., least squares (step **706**). Finally, the data is projected onto the nominal control surface coordinate, i.e., y (step **708**).

(76) FIG. 8 depicts formulas **800** for an orthogonal vector projection, according to one embodiment. The projection is accomplished utilizing a linear algebra vector projection equation. Other projected vector formulas are possible and contemplated to determine the vector projection. Gamma (γ) is the vector norm, which is the length of the vector, as shown in FIG. 8.

(77) FIG. 9A depicts a graph **900** of an overhead view of the flux plane flight trajectory with derived nominal flight plane trajectory used for projection, according to one embodiment. FIG. 9B depicts a graph **901** of a flight trajectory projected onto the (y, z) plane, according to one embodiment. The line **902** in the FIG. 9A represents the best estimate for the nominal flight plane trajectory, onto which the measurement coordinates are projected. FIG. 9B shows the vertical profile of concentration measurements as a function of the projected flight plane coordinate, i.e., gamma, and the altitude.

(78) Interpolation

(79) FIG. 10A depicts a graph **1000** of projected values along the (y, z) plane, according to one embodiment. FIG. 10B depicts a graph **1001** of an averaged and interpolated flux plane, according to one embodiment. Once the background concentration value is measured or estimated, the value is subtracted at each point along the flight path to obtain the concentration enhancement, and the measurements are averaged and interpolated on a continuous grid across the flight plane. A grid is created with a specified resolution over the range of coordinates in the projected flight plane. The concentration measurements within each grid cell are averaged, if no measurements exist for a particular grid cell then the value is left empty or replaced with null. After the grid is populated with the average measurements, a linear interpolation is applied to fill the grid with continuous concentration values. Some values on the grid have a negative concentration enhancement, this is

important to ensure that the calculation returns a zero value for the flux when no upwind emission source is present.

(80) Generation of a Control Surface

(81) As an alternative method to projecting the measurements to a plane and interpolating the point concentrations onto a grid, a control surface can be directly calculated from the measurement points in three-dimensional space. This process involves calculating a horizontal value that represents the distance along the control surface. For planar or planar-like control surfaces, the value can be calculated as the incremental distance from one extent of the plane to the other extent of the plane. For flight paths that fully circumnavigate (FIG. 18A) or partially circumnavigate a source (FIG. 18B), the value can be calculated as the distance along the flight path from any specified starting point.

(82) The circumnavigated path can be generated by a series of flight lines shown in green (FIG. 19) that are a set distance from the equipment being inspected. The paths can be generated using a handheld GPS, map, drawing, or other geo-referenced source (FIG. 26). The partially circumnavigated path shown by the path 1904 can be calculated by the average wind direction 1908 and variance 1906, or by other methods.

(83) The flight paths may be created based upon equipment or equipment grouping 2002, 2004, 2006, 2008 as shown in FIG. 20. The resultant drone trajectory 2100 given the equipment groups is shown in FIG. 21. The resultant geo-rectified trace gas concentration data from the fully enclosed flight paths 2200 are shown in FIG. 22.

(84) A series of fully or semi-enclosed flight paths can be strewn together to be completed in a single flight as shown in FIG. 23), where the lines 2308 on the map shown the flight path 2300.

(85) With the additional value of flight path distance for each measurement point, the dataset can be transformed from a three dimensional representation to a two dimensional space with one axis being the flight path distance, and the other axis being the altitude. In this two-dimensional space, a Delaunay Triangulation can be calculated to yield a two dimensional surface in the two dimensional space where each measurement is connected to others with triangles to produce a contiguous manifold surface (FIG. 24). The triangulation defined by the relationships for the connections between measurement points can then be applied to the points represented in three dimensional space to produce a three dimensional contiguous manifold surface that connects all the measurement points.

(86) In order to capture all the emissions on a site, flying a closed perimeter surface may be preferred (FIG. 25). If a flightpath completely encompasses the site, Gauss' Theorem may be applied directly to calculate the source rate within the flightpath perimeter using the concentration measurements at the perimeter. Due to operational constraints (access roads, power lines etc.), flying a fully closed flightpath may not always be possible, and so flying the perimeter with a small gap where flying is disallowed is an alternate approach (semi-Gauss).

(87) Analyzing Gauss and semi-Gauss flights to extract a source rate requires application of computational geometry algorithms. Firstly, the dataset is taken from the aircraft and converted into Cartesian coordinates. The conversion is done using the Position Easting, Position Northing coordinates from the Extended Kalman Filter (EKF) as the X and Y components, and the LiDAR altitude from the LiDAR range finder for the Z component. Using the EKF outputs for location may allow for a more accurate measurement of location over using only GPS.

(88) The dataset consists of point measurements made by the aerial vehicle in space. In order to deduce a source rate of gas emission, the individual flux values will have to be integrated over the whole dataset. Once the dataset has been converted into Cartesian space, it is necessary to triangulate the point measurements so that a continuous surface is available to perform the surface integral on (dS).

$$\iiint_{\text{sub.V}(\nabla.\text{Math.F})} dV = \text{custom character}(F.\text{Math.n}) dS$$

(89) The disclosed system and method for generating the continuous surface is disclosed herein.

Delaunay Triangulation algorithms create a two-dimensional triangulation (surface) from a two-dimensional dataset, but may not be able to create a two-dimensional triangulation (surface) from a three-dimensional dataset. Therefore, before applying a Delaunay Triangulation algorithm, the dataset may first be represented in two-dimensional space. For Gauss and semi-Gauss flightpaths, the dataset may be converted into altitude-s space, where altitude is the same dimension as in the three-dimensional dataset, and s is a new dimension measuring distance along the pass. For example, in a Gauss flightpath, the value of s monotonically increases along the pass, until the aerial vehicle reaches a determined point and then the value of s starts again from zero. This is akin to the distance along a lap. For a semi-Gauss flightpath, the value of s monotonically increases until the aerial vehicle reaches whatever obstacle it must avoid, and then makes a U-turn and backtracks along the same path (at a different altitude) while the value of s decreases. Both methods, including the identification of crossing a home point and detection of U-turn points are automatically processed.

(90) Once the dataset is represented in altitude-s space, a Delaunay Triangulation is performed. The resulting triangulation is then applied on the dataset original Cartesian X, Y, Z space to produce a fully closed or semi-closed surface, with all the original scalar values (e.g. gas concentrations) intact.

(91) In addition to the measurements made using the one or more gas concentration sensors mounted to the airframe, an anemometer is setup on-site at a suitable location to make unaffected wind measurements. As the aerial vehicle is sampling species concentrations, the anemometer is measuring instantaneous wind speed in three dimensions. These measurements are recorded at synchronized times as the species concentrations are made. An appropriate aerodynamic surface roughness length is chosen to represent the local ground conditions surrounding the measurement site. The wind speed measurements taken by the anemometer are then extrapolated from the anemometer measurement altitude to the altitude of the aerial vehicle at that specific point in time. This may be done using the log-law boundary condition model for flows near rough boundaries. The wind direction remains uncorrected, and only the magnitude of the wind speed is scaled using the log-law. The altitude corrected wind vector from the anemometer is then assumed to be the wind vector at the location the gas concentration measurement is made. While this assumption that the wind is the same at two different points may not be physically accurate, it is a way to determine wind speed and direction at the measurement point. In moderate wind speed conditions, the stability of the atmospheric boundary layer increases, resulting in less wind variance, therefore giving better correlation between the anemometer measurement and the wind at the sensor.

(92) With the surface now created, a surface normal unit vector can be calculated at each point in the dataset. By performing the dot product of the surface normal vector and the wind vector, a volumetric flux rate of airflow is calculated for every point on the surface. This represents how many m^3 of air is entering or leaving the control volume per m^2 (dS).

(93) In order to provide accurate relative gas measurements, a high pass filter is applied over the input concentration measurements. The filter removes any low frequency sensor drift, while still resolving all details from emissions. The time constant chosen for the filter is based on analysis of the sensor stability.

(94) Multiplying the above wind flux values by the volume fraction of gas ($\text{m}^3 \text{CH}_4$ or CO_2/m^3 air) gives the volumetric flux rate of gas at each point ($\text{m}^3 \text{ gas/s/m}^2$ area).

(95) Because the control surface does not completely encompass the control volume, and the measurements were not taken at the exact same time (therefore wind may vary during flight), the standard incompressible equation of continuity does not hold true.

$\nabla \cdot \mathbf{u} \neq 0$

(96) This means that the net flux cannot simply be calculated by integrating the point gas flux measurements across the entire surface. Instead, a more piecemeal approach must be taken. To

calculate the flux of gas entering the control volume, the surface is thresholded to where wind is flowing into the control volume only. With this surface, the volumetric flux rate of gas can be integrated to give the total inward volumetric flux of gas into the control volume (m.sup.3 species/s).

(97) volumetric flowrate averaging =
$$\frac{\int_A \frac{dc}{\partial A} dA}{\int_A \frac{du}{\partial A} dA}$$

(98) Once the species flux rate has been established, a total air volumetric rate must be calculated as well. The volumetric rate calculation may be done by integrating the wind velocity normal component to give a total air volumetric flux rate. By dividing the species volumetric flux rate by the air volumetric flux rate, the volumetric flowrate averaged inflowing species concentration is calculated.

(99) A similar solution could be obtained by averaging all the values of volumetric flux rate of gas at each point, but the triangulation of the real-world dataset yields varied triangles, and this difference in size should be considered when calculating the average incoming volumetric gas flux rate. This process to get the total background concentration value is volumetric flow averaging and is necessary for calculating convective quantities such as species concentrations. In this case, the integral operator is not commutative because the wind values vary on the surface, and therefore the two integrals must be performed separately, and their results divided together.

(100) The volumetric-flow-rate averaged concentration of the inflowing gas can then be subtracted from the concentration values measured where anemometry indicates gas is flowing out of the control volume. The resulting values are the enhanced concentrations with the background concentration component removed.

(101) With the enhanced concentration values, the final net flux rate can be calculated. By again multiplying the component of wind velocity normal to the control surface by the concentration enhancement, the flux rate of the enhanced species concentration per unit area is obtained (m.sup.3 species/m.sup.2/second). Integrating this across the whole of the outflowing area

(102) This disclosed approach has the benefit that it satisfies the fundamental fluid dynamics equation for flow of a species through a control volume. Continuity of the species is used to ensure that all of the concentration upstream is subtracted from the concentration downstream, even if the oncoming flow has not got a uniform concentration of gas. Because the control volume is still open at the top, and the discrete sampling process means that there are gaps in the control surface, absolute integrals of continuity of mass and continuity of species cannot be simply applied. In addition, sampling all the points non-simultaneously, and in transient wind conditions, means that flux through any point in the control surface is constantly changing.

(103) Despite fully considering the background concentration into calculations, there may still be a significant degree of error incurred from wind speed measurement. One process may utilize a ground weather station, that is set-up on site in a location with the least amount of interference from other obstacles as possible. Even in the optimal location, the anemometer is not co-located with the aerial vehicle at any time, and so the reading at the anemometer will be different from the actual wind-speed at the drone. This effect is particularly strong during light wind conditions, as a small change in the wind speed can incur a large change in the concentration values measured. In light wind conditions, the atmospheric boundary layer is also more unstable, resulting in more diffusion of the species plume, and therefore lower concentration values than with a more consistent wind.

(104) Wind Direction and Vertical Gradient

(105) FIG. 11 depicts a diagram 1100 illustrating the primary surface level sublayers in the Atmospheric Boundary Layer, according to one embodiment. An important input to the Emissions Estimate model disclosed herein is wind speed. Most of the measurements made by the disclosed UAS will be performed within the Roughness Sublayer portion of the atmospheric sublayer, i.e., the region from the surface to just above the average obstruction height or the local topography. In

this region, the standard log law vertical wind gradient model provides a reasonable approximation of the vertical wind profile. Vertical wind profile may be approximated using a log law. Other ways of determining the vertical wind profile given the wind at a certain height and projected altitude are possible and contemplated. In some embodiments, the vertical wind profile may be measured directly. The vertical wind gradient or the vertical wind model may be determined based on the meteorological data measured, recorded, and/or predicted.

(106) FIG. 12A depicts a graph **1200** of a flux plane average flight path vector **1202**, average wind vector **1204**, and derived normal wind component **1206**, according to one embodiment. FIG. 12B depicts a graph **1201** of a modeled wind profile for the total wind **1208** and the derived orthogonal wind **1210**. The Emissions Estimate algorithm determines the surface wind speed and direction utilizing measurements from the onsite 2D or 3D sonic anemometer. Due to local wind variability, it is necessary to derive the average and/or median normal wind component to the flown flight path surface. The orthogonal wind component is utilized to model the local wind profile. The derived orthogonal wind profile **1210** is utilized in the emissions calculation.

(107) Emissions Calculation

(108) FIG. 13 depicts a schematic drawing **1300** of an Emissions Estimate Model, according to one embodiment. The Emissions Estimate algorithm is based on an engineering control volume model. This means that the two key inputs to the model are the concentration profile on the outflow surface (or flight path surface), and the wind speed through the outflow. The concentration enhancement is measured by the disclosed sensor in volumetric concentration units, i.e., ppmv. To determine the source emission rate, it is necessary to convert from volumetric concentration to mass concentration, this is accomplished through the ideal gas law. The ideal gas law is used to calculate the air density based on the local air temperature and atmospheric pressure. At or below about 1% trace-gas in air, the contribution of trace-gas to the overall mixture density is negligible, i.e. the change in specific gravity of the mixture is small. For trace-gas concentrations less than 10,000 ppmv, the mass concentration of trace-gas can be obtained by multiplying the volumetric concentration measurement by the air density to yield kg.sub.CH4/m.sup.3. In the ideal gas law, the state of an amount of gas is determined by its pressure, volume, and temperature.

(109) After converting the concentration enhancement to mass units and multiplying the concentration surface by the altitude dependant wind, a 2D integration over the entire surface is performed to arrive at the mass flux through the surface (Eq. 1) in units of kg/s. The velocity (u) is at a given altitude (z). A concentration (c) is at the distance Gamma (γ) and altitude (z). The concentration (c) is a function of Gamma (γ) along the flight path and altitude (z).

$$\iint u(z)c(\gamma,z)d\gamma dz \quad \text{Eq. 1}$$

(110) FIG. 14 depicts a 3-dimensional illustration of a UAS system Emissions measurement process **1400**, according to one embodiment. The UAV **202** flies vertical, cross-wind transects downwind of potential trace-gas sources **108** and measures ambient trace-gas concentration. Elevated trace-gas concentration is the signature of an upwind source. The measurements are interpolated onto a continuous grid **1402**, multiplied by the corresponding wind vector, and spatially integrated to quantify the source emission rates.

(111) FIG. 15 is a high-level block diagram **1500** showing a computing system comprising a computer system useful for implementing an embodiment of the system and process, disclosed herein. Embodiments of the system may be implemented in different computing environments. The computer system includes one or more processors **1502**, and can further include an electronic display device **1504** (e.g., for displaying graphics, text, and other data), a main memory **1506** (e.g., random access memory (RAM)), storage device **1508**, a removable storage device **1510** (e.g., removable storage drive, a removable memory module, a magnetic tape drive, an optical disk drive, a computer readable medium having stored therein computer software and/or data), user interface device **1511** (e.g., keyboard, touch screen, keypad, pointing device), and a communication interface **1512** (e.g., modem, a network interface (such as an Ethernet card), a communications port, or a

PCMCIA slot and card). The communication interface **1512** allows software and data to be transferred between the computer system and external devices. The system further includes a communications infrastructure **1514** (e.g., a communications bus, cross-over bar, or network) to which the aforementioned devices/modules are connected as shown.

(112) Information transferred via communications interface **1514** may be in the form of signals such as electronic, electromagnetic, optical, or other signals capable of being received by communications interface **1514**, via a communication link **1516** that carries signals and may be implemented using wire or cable, fiber optics, a phone line, a cellular/mobile phone link, an radio frequency (RF) link, and/or other communication channels. Computer program instructions representing the block diagram and/or flowcharts herein may be loaded onto a computer, programmable data processing apparatus, or processing devices to cause a series of operations performed thereon to produce a computer implemented process.

(113) Embodiments have been described with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments. Each block of such illustrations/diagrams, or combinations thereof, can be implemented by computer program instructions. The computer program instructions when provided to a processor produce a machine, such that the instructions, which execute via the processor, create means for implementing the functions/operations specified in the flowchart and/or block diagram. Each block in the flowchart/block diagrams may represent a hardware and/or software module or logic, implementing embodiments. In alternative implementations, the functions noted in the blocks may occur out of the order noted in the figures, concurrently, etc.

(114) Computer programs (i.e., computer control logic) are stored in main memory and/or secondary memory. Computer programs may also be received via a communications interface **1512**. Such computer programs, when executed, enable the computer system to perform the features of the embodiments as discussed herein. In particular, the computer programs, when executed, enable the processor and/or multi-core processor to perform the features of the computer system. Such computer programs represent controllers of the computer system.

(115) FIG. **16** shows a block diagram of an example system **1600** in which an embodiment may be implemented. The system **1600** includes one or more client devices **1601** such as consumer electronics devices, connected to one or more server computing systems **1630**. A server **1630** includes a bus **1602** or other communication mechanism for communicating information, and a processor (CPU) **1604** coupled with the bus **1602** for processing information. The server **1630** also includes a main memory **1606**, such as a random access memory (RAM) or other dynamic storage device, coupled to the bus **1602** for storing information and instructions to be executed by the processor **1604**. The main memory **1606** also may be used for storing temporary variables or other intermediate information during execution or instructions to be executed by the processor **1604**. The server computer system **1630** further includes a read only memory (ROM) **1608** or other static storage device coupled to the bus **1602** for storing static information and instructions for the processor **1604**. A storage device **1610**, such as a magnetic disk or optical disk, is provided and coupled to the bus **1602** for storing information and instructions. The bus **1602** may contain, for example, thirty-two address lines for addressing video memory or main memory **1606**. The bus **1602** can also include, for example, a 32-bit data bus for transferring data between and among the components, such as the CPU **1604**, the main memory **1606**, video memory and the storage **1610**. Alternatively, multiplex data/address lines may be used instead of separate data and address lines.

(116) The server **1630** may be coupled via the bus **1602** to a display **1612** for displaying information to a computer user. An input device **1614**, including alphanumeric and other keys, is coupled to the bus **1602** for communicating information and command selections to the processor **1604**. Another type or user input device comprises cursor control **1616**, such as a mouse, a trackball, or cursor direction keys for communicating direction information and command selections to the processor **1604** and for controlling cursor movement on the display **1612**.

(117) According to one embodiment, the functions are performed by the processor **1604** executing one or more sequences of one or more instructions contained in the main memory **1606**. Such instructions may be read into the main memory **1606** from another computer-readable medium, such as the storage device **1610**. Execution of the sequences of instructions contained in the main memory **1606** causes the processor **1604** to perform the process steps described herein. One or more processors in a multi-processing arrangement may also be employed to execute the sequences of instructions contained in the main memory **1606**. In alternative embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement the embodiments. Thus, embodiments are not limited to any specific combination of hardware circuitry and software.

(118) The terms “computer program medium,” “computer usable medium,” “computer readable medium”, and “computer program product,” are used to generally refer to media such as main memory, secondary memory, removable storage drive, a hard disk installed in hard disk drive, and signals. These computer program products are means for providing software to the computer system. The computer readable medium allows the computer system to read data, instructions, messages or message packets, and other computer readable information from the computer readable medium. The computer readable medium, for example, may include non-volatile memory, such as a floppy disk, ROM, flash memory, disk drive memory, a CD-ROM, and other permanent storage. It is useful, for example, for transporting information, such as data and computer instructions, between computer systems. Furthermore, the computer readable medium may comprise computer readable information in a transitory state medium such as a network link and/or a network interface, including a wired network or a wireless network that allow a computer to read such computer readable information. Computer programs (also called computer control logic) are stored in main memory and/or secondary memory. Computer programs may also be received via a communications interface. Such computer programs, when executed, enable the computer system to perform the features of the embodiments as discussed herein. In particular, the computer programs, when executed, enable the processor multi-core processor to perform the features of the computer system. Accordingly, such computer programs represent controllers of the computer system.

(119) Generally, the term “computer-readable medium” as used herein refers to any medium that participated in providing instructions to the processor **1604** for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, optical or magnetic disks, such as the storage device **1610**. Volatile media includes dynamic memory, such as the main memory **1606**. Transmission media includes coaxial cables, copper wire and fiber optics, including the wires that comprise the bus **1602**. Transmission media can also take the form of acoustic or light waves, such as those generated during radio wave and infrared data communications.

(120) Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, an EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read.

(121) Various forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to the processor **1604** for execution. For example, the instructions may initially be carried on a magnetic disk of a remote computer. The remote computer can load the instructions into its dynamic memory and send the instructions over a telephone line using a modem. A modem local to the server **1630** can receive the data on the telephone line and use an infrared transmitter to convert the data to an infrared signal. An infrared detector coupled to the bus **1602** can receive the data carried in the infrared signal and place the data on the bus **1602**. The bus **1602** carries the data to the main memory **1606**, from which the processor **1604** retrieves

and executes the instructions. The instructions received from the main memory **1606** may optionally be stored on the storage device **1610** either before or after execution by the processor **1604**.

(122) The server **1630** also includes a communication interface **1618** coupled to the bus **1602**. The communication interface **1618** provides a two-way data communication coupling to a network link **1620** that is connected to the world wide packet data communication network now commonly referred to as the Internet **1628**. The Internet **1628** uses electrical, electromagnetic or optical signals that carry digital data streams. The signals through the various networks and the signals on the network link **1620** and through the communication interface **1618**, which carry the digital data to and from the server **1630**, are exemplary forms or carrier waves transporting the information.

(123) In another embodiment of the server **1630**, interface **1618** is connected to a network **1622** via a communication link **1620**. For example, the communication interface **1618** may be an integrated services digital network (ISDN) card or a modem to provide a data communication connection to a corresponding type of telephone line, which can comprise part of the network link **1620**. As another example, the communication interface **1618** may be a local area network (LAN) card to provide a data communication connection to a compatible LAN. Wireless links may also be implemented. In any such implementation, the communication interface **1618** sends and receives electrical electromagnetic or optical signals that carry digital data streams representing various types of information.

(124) The network link **1620** typically provides data communication through one or more networks to other data devices. For example, the network link **1620** may provide a connection through the local network **1622** to a host computer **1624** or to data equipment operated by an Internet Service Provider (ISP). The ISP in turn provides data communication services through the Internet **1628**. The local network **1622** and the Internet **1628** both use electrical, electromagnetic or optical signals that carry digital data streams. The signals through the various networks and the signals on the network link **1620** and through the communication interface **1618**, which carry the digital data to and from the server **1630**, are exemplary forms or carrier waves transporting the information.

(125) The server **1630** can send/receive messages and data, including e-mail, program code, through the network, the network link **1620** and the communication interface **1618**. Further, the communication interface **1618** can comprise a USB/Tuner and the network link **1620** may be an antenna or cable for connecting the server **1630** to a cable provider, satellite provider or other terrestrial transmission system for receiving messages, data and program code from another source.

(126) The example versions of the embodiments described herein may be implemented as logical operations in a distributed processing system such as the system **1600** including the servers **1630**. The logical operations of the embodiments may be implemented as a sequence of steps executing in the server **1630**, and as interconnected machine modules within the system **1600**. The implementation is a matter of choice and can depend on performance of the system **1600** implementing the embodiments. As such, the logical operations constituting said example versions of the embodiments are referred to for e.g., as operations, steps or modules.

(127) Similar to a server **1630** described above, a client device **1601** can include a processor, memory, storage device, display, input device and communication interface (e.g., e-mail interface) for connecting the client device to the Internet **1628**, the ISP, or LAN **1622**, for communication with the servers **1630**.

(128) The system **1600** can further include computers (e.g., personal computers, computing nodes) **1605** operating in the same manner as client devices **1601**, wherein a user can utilize one or more computers **1605** to manage data in the server **1630**.

(129) Referring now to FIG. **17**, illustrative cloud computing environment **50** is depicted. As shown, cloud computing environment **50** comprises one or more cloud computing nodes **10** with which local computing devices used by cloud consumers, such as, for example, personal digital assistant (PDA), smartphone, smart watch, set-top box, video game system, tablet, mobile

computing device, or cellular telephone **54A**, desktop computer **54B**, laptop computer **54C**, and/or unmanned aerial system **54N** may communicate. Nodes **10** may communicate with one another. They may be grouped (not shown) physically or virtually, in one or more networks, such as Private, Community, Public, or Hybrid clouds as described hereinabove, or a combination thereof. This allows cloud computing environment **50** to offer infrastructure, platforms and/or software as services for which a cloud consumer does not need to maintain resources on a local computing device. It is understood that the types of computing devices **54A-N** shown in FIG. **17** are intended to be illustrative only and that computing nodes **10** and cloud computing environment **50** can communicate with any type of computerized device over any type of network and/or network addressable connection (e.g., using a web browser).

(130) FIG. **18A** depicts a flight path **1800** that fully circumnavigates a potential trace gas source **1802**, according to one embodiment. FIG. **18B** depicts a flight path **1804** that partially circumnavigates a potential trace gas source, according to one embodiment.

(131) FIG. **19** depicts a top view **1900** of a circumnavigated flight path **1904** that can be generated by a series of flight lines that are a set distance from equipment **1902** being inspected, according to one embodiment.

(132) FIG. **20** depicts flight paths that may be created based upon equipment or equipment grouping, according to one embodiment. A location **2000** may include one or more survey groups **2002**, **2004**, **2006**, **2008**. Each survey group **2002**, **2004**, **2006**, **2008** may include at least one equipment group **2018**, **2020**, **2024**, **2026**, **2028**, **2030**, **2034**. The at least one equipment group **2018**, **2020**, **2024**, **2026**, **2028**, **2030**, **2034** may include potential trace gas sources, such as wellheads, flow lines, meter runs, manifolds, separators, tanks, or the like. The location **2000** may also include one or more obstacles **2010**, **2012**, **2014**, **2016**. The one or more obstacles **2010**, **2012**, **2014**, **2016** may include stairs, SCADA, power lines, guard rails, or the like. A UAV may want to avoid or be required to avoid the one or more obstacles **2010**, **2012**, **2014**, **2016** in the flight path.

(133) FIG. **21** depicts a resultant UAV trajectory **2100** based on the equipment grouping of FIG. **20**, according to one embodiment. A close-up view **2102** of a waypoint in the UAV trajectory **2100** is shown. The UAV may fly a flight path **2106** between waypoints **2104** in order to survey the equipment groups and detect any trace gas emissions from the potential trace gas sources.

(134) FIG. **22** depicts a resultant geo-rectified trace gas concentration data **2200** from the resultant UAV trajectory of FIG. **21**, according to one embodiment. Trace gas data may include measurements of no or almost no trace gas **2202**, elevated trace gas measurements **2204**, and high trace gas measurements **2206**.

(135) FIG. **23** depicts a flight path **2300** covering a series of fully or semi-enclosed flight paths that may be strewn together to be completed in a single flight, according to one embodiment. The flight path **2300** may cover several geographically separate locations **2302**, **2304**, **2306** that may be connected **2308** by flight paths. Each location **2302**, **2304**, **2306** may include one or more equipment groups, such as shown in FIG. **20**.

(136) FIG. **24** depicts triangulation results with a flux surface projected **2400**, according to one embodiment.

(137) FIG. **25** depicts a fully enclosed triangulation with concentration **2500**, according to one embodiment.

(138) FIG. **26** depicts a system **2600** for detecting trace gasses, according to one embodiment. The system may include one or more trace gas sensors located in one or more vehicles **2602**, **2604**, **2606**, **2610**. The one or more trace gas sensors may detect elevated trace gas concentrations from one or more potential gas sources **2620**, **2622**, such as a holding tank, pipeline, or the like. The potential gas sources **2620**, **2622** may be part of a large facility, a small facility, or any location. The potential gas sources **2620**, **2622** may be clustered and/or disposed distal from one another. The one or more trace gas sensors may be used to detect and quantify leaks of toxic gases, e.g., hydrogen disulfide, or environmentally damaging gases, e.g., methane, sulfur dioxide) in a variety

of industrial and environmental contexts. Detection and quantification of these leaks are of interest to a variety of industrial operations, such as oil and gas, chemical production, and painting. Detection and quantification of leaks is also of value to environmental regulators for assessing compliance and for mitigating environmental and safety risks. In some embodiments, the at least one trace gas sensor may be configured to detect methane. In other embodiments, the at least one trace gas sensor may be configured to detect sulfur oxide, such as SO, SO₂, SO₃, S₇O₂, S₆O₂, S₂O₂, and the like. A trace gas leak **2624** may be present in a potential gas source **2620**. The one or more trace gas sensors may be used to identify the trace gas leak **2624** and/or the source **2620** of the trace gas leak **2624** so that corrective action may be taken.

(139) The one or more vehicles **2602**, **2604**, **2606**, **2610** may include an unmanned aerial vehicle (UAV) **2602**, an aerial vehicle **2604**, a handheld device **2606**, and a ground vehicle **2610**. In some embodiments, the UAV **2602** may be a quadcopter or other device capable of hovering, making sharp turns, and the like. In other embodiments, the UAV **2602** may be a winged aerial vehicle capable of extended flight time between missions. The UAV **2602** may be autonomous or semi-autonomous in some embodiments. In other embodiments, the UAV **2602** may be manually controlled by a user. The aerial vehicle **2604** may be a manned vehicle in some embodiments. The handheld device **2606** may be any device having one or more trace gas sensors operated by a user **2608**. In one embodiment, the handheld device **2606** may have an extension for keeping the one or more trace gas sensors at a distance from the user **2608**. The ground vehicle **2610** may have wheels, tracks, and/or treads in one embodiment. In other embodiments, the ground vehicle **2610** may be a legged robot. In some embodiments, the ground vehicle **2610** may be used as a base station for one or more UAVs **2602**. In some embodiments, one or more aerial devices, such as the UAV **2602**, a balloon, or the like, may be tethered to the ground vehicle **2610**. In some embodiments, one or more trace gas sensors may be located in one or more stationary monitoring devices **2626**. The one or more stationary monitoring devices may be located proximate one or more potential gas sources **2620**, **2622**. In some embodiments, the one or more stationary monitoring devices may be relocated.

(140) The one or more vehicles **2602**, **2604**, **2606**, **2610** and/or stationary monitoring devices **2626** may transmit data including trace gas data to a ground control station (GCS) **2612**. The GCS may include a display **2614** for displaying the trace gas concentrations to a GCS user **2616**. The GCS user **2616** may be able to take corrective action if a gas leak **2624** is detected, such as by ordering a repair of the source **2620** of the trace gas leak. The GCS user **2616** may be able to control movement of the one or more vehicles **2602**, **2604**, **2606**, **2610** in order to confirm a presence of a trace gas leak in some embodiments.

(141) In some embodiments, the GCS **2612** may transmit data to a cloud server **2618**. In some embodiments, the cloud server **2618** may perform additional processing on the data. In some embodiments, the cloud server **2618** may provide third party data to the GCS **2612**, such as wind speed, temperature, pressure, weather data, or the like.

(142) It is contemplated that various combinations and/or sub-combinations of the specific features and aspects of the above embodiments may be made and still fall within the scope of the invention. Accordingly, it should be understood that various features and aspects of the disclosed embodiments may be combined with or substituted for one another in order to form varying modes of the disclosed invention. Further, it is intended that the scope of the present invention herein disclosed by way of examples should not be limited by the particular disclosed embodiments described above.

Claims

1. A system, comprising: a trace-gas concentration sensor configured to be carried by an unmanned aerial vehicle (UAV), wherein the trace-gas concentration sensor is configured to generate trace-gas

concentration data, which is included in a trace-gas data packet; a location sensor configured to generate location data comprising a trajectory of the trace-gas concentration sensor in space; one or more weather stations distal from the trace-gas concentration sensor, wherein each weather station generates a Meteorological data packet comprising weather data; a processor having addressable memory, the processor configured to: determine a control surface along a flight path of a UAV, wherein the control surface comprises a horizontal value that represents a distance along the control surface, wherein the control surface intersects an area downwind of a trace-gas source and circumnavigates the trace-gas source, wherein the control surface includes two or more first flight planes and one or more second flight planes, wherein the two or more first flight planes are substantially parallel to a ground surface, and wherein the one or more second flight planes are angled to connect two of the two or more first flight planes; receive the trace-gas data packet, wherein the trace-gas data packet comprises a trace-gas concentration data from the trace-gas concentration sensor and the location data for the trace-gas concentration sensor, wherein the location data is based on the horizontal value of the control surface along the flight path of the UAV; receive at least one Meteorological data packet from the one or more weather stations; combine the trace-gas data packet with a selected spatial and temporal Meteorological data packet; and determine a trace-gas emission rate of the trace-gas source based on the combined trace-gas data packet and the selected Meteorological data packet.

2. The system of claim 1 further comprising: a display in communication with the processor, wherein the display is configured to show the determined trace-gas emission rate of the trace-gas source on a map.

3. The system of claim 2, wherein the map is at least one of: a satellite image, an aerial image, a two-dimensional color map, a two-dimensional contour map, and a three-dimensional topographical surface.

4. The system of claim 1, wherein the processor is further configured to: determine the flight path of the UAV.

5. The system of claim 4, wherein the flight path of the UAV intersects an area downstream of the gas source and varies in horizontal distance perpendicular to an axis of a wind direction and an altitude.

6. The system of claim 1, further comprising: a payload of the trace-gas concentration sensor, wherein the payload comprises one or more in situ trace-gas concentration sensors configured to generate the trace-gas concentration data along the trajectory of the trace-gas concentration sensor in space.

7. The system of claim 6 wherein the location data comprises at least one of: a location of the trace-gas concentration sensor, a time corresponding to the location of the trace-gas concentration sensor, a barometric pressure, an altitude, a relative altitude, and an orientation of the trace-gas concentration sensor, and wherein the location data corresponds to the generated trace-gas concentration data along the trajectory of the trace-gas concentration sensor in space.

8. The system of claim 7 wherein the location of the at least one trace-gas concentration sensor is determined by at least one of: a global positioning system (GPS) and a location sensor.

9. The system of claim 7 wherein the location of the trace-gas concentration sensor further comprises a detection of at least one of: an absolute altitude of the trace-gas concentration sensor and a relative altitude of the trace-gas concentration sensor.

10. The system of claim 7 wherein the orientation of the trace-gas concentration sensor is determined by at least one of: an inertial measurement unit (IMU) and an orientation sensor.

11. The system of claim 1 wherein the trace-gas data packet comprises: a global positioning system (GPS) location of the trace-gas concentration sensor, a time, a barometric pressure, an altitude of the trace-gas concentration sensor, and an orientation of the trace-gas concentration sensor corresponding to the trace-gas concentration data.

12. The system of claim 1 wherein the Meteorological Data Packet comprises data from: an

anemometer, one or more pressure sensors, a pyranometer, a ground temperature sensor, an air temperature sensor, and a current atmospheric condition sensor.

13. The system of claim 11 wherein at least one of: a ground control station (GCS), a cloud server, the trace-gas concentration sensor, and one or more weather stations comprises the processor.

14. The system of claim 1 wherein the determined trace-gas emission rate may be stored by at least one of: a ground control station (GCS), a cloud server, and one or more gas concentration sensors.

15. A method of determining a trace-gas emission rate using a system comprising one or more trace-gas concentration sensors generating trace-gas concentration data and a location sensor generating location data of the trace-gas concentration sensor in space, two or more weather stations distal from the trace-gas concentration sensor and generating weather data, and a processor having addressable memory, the method comprising: determining a control surface along a flight path of an unmanned aerial vehicle (UAV), wherein the control surface comprises a horizontal value that represents a distance along the control surface, wherein the control surface intersects an area downwind of a trace-gas source and circumnavigates the trace-gas source, wherein the control surface includes two or more first flight planes and one or more second flight planes, wherein the two or more first flight planes are substantially parallel to a ground surface, and wherein the one or more second flight planes are angled to connect two of the two or more first flight planes; receiving, by the processor, a UAV data packet from the UAV, wherein the UAV data packet comprises the trace-gas concentration data and UAV information covering locations of a UAV flight path, wherein the UAV information comprises a global positioning system (GPS) location of the one or more trace-gas concentration sensors corresponding to the trace-gas concentration data, wherein the location data is based on the horizontal value of the control surface along the flight path of the UAV; receiving, by the processor, at least one Meteorological data packet from the two or more weather stations, wherein each weather station is distal from the UAV, wherein each weather station generates the Meteorological data packet comprising the weather data; combining, by the processor, the UAV data packet with a nearest spatial and temporal Meteorological data packet; and determining, by the processor, the trace-gas emission rate of a trace-gas source based on the combined UAV data packet and the nearest Meteorological data packet.

16. The method of claim 15 wherein the UAV flight path is controlled by a user via a ground control station (GCS).

17. The method of claim 15 further comprising: measuring, by a payload of a UAV, the trace-gas concentration data along the UAV flight path, wherein the payload comprises one or more gas concentration sensors; generating, by the UAV, the UAV data packet, wherein the UAV data packet comprises a spatial position of the UAV at each trace-gas concentration data measurement; and generating, by the two or more weather stations of one or more weather stations, the Meteorological data packet; wherein the UAV data packet comprises data from at least one of: a weather sensor, an onboard avionics, a barometric pressure sensor, an orientation sensor, an inertial measurement unit (IMU), a wireless radio, a global positioning system (GPS), a time measurement device, an altitude sensor, a location sensor, a radar, a lidar, an anemometer, and a Sonar; and wherein the Meteorological data packet comprises data from: an anemometer, one or more pressure sensors, a pyranometer, a ground temperature sensor, an air temperature sensor, and a current atmospheric condition sensor.

18. A system, comprising: one or more in-situ trace-gas concentration sensors connected to an unmanned aerial vehicle (UAV) configured to fly a UAV flight path and configured to generate the trace-gas concentration data measured along the UAV flight path, wherein the trace-gas concentration data is included in a UAV data packet; one or more location sensors of the UAV configured to generate UAV information comprising a global positioning system (GPS) location of the UAV corresponding to the trace-gas concentration data measured along the UAV flight path, wherein the UAV information is included in the UAV data packet; two or more weather stations distal from the UAV and configured to measure weather data and generate a Meteorological data

packet comprising the weather data; and a processor having addressable memory, the processor in communication with the UAV and the one or more weather stations, wherein the processor configured to: determine a control surface along a flight path of a UAV, wherein the control surface comprises a horizontal value that represents a distance along the control surface, wherein the control surface intersects an area downwind of a trace-gas source and circumnavigates the trace-gas source, wherein the control surface includes two or more first flight planes and one or more second flight planes, wherein the two or more first flight planes are substantially parallel to a ground surface, and wherein the one or more second flight planes are angled to connect two of the two or more first flight planes; receive the UAV data packet, from the UAV, comprising the trace-gas concentration data and UAV information comprising the location of the UAV, wherein the location of the UAV is based on the horizontal value of the control surface along the flight path of the UAV; receive two or more Meteorological data packets from the two or more weather stations; combine the UAV data packet with a nearest spatial and temporal Meteorological data packet; determine a trace-gas emission rate of a trace-gas source based on the combined UAV data packet and the nearest Meteorological data packet; and show the determined trace-gas emission rate of the trace-gas source on a map via a display in communication with the processor.
