

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399440
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Cheng; Chen-Pin et al.

Lithography system and methods

Abstract

A method includes: placing a mask on a mask stage; placing a pellicle assembly on a pellicle stage, the pellicle assembly including a pellicle; determining whether a defect level of the pellicle is less than a selected value by scanning the pellicle by a first optical detector; forming a protected mask assembly by mounting the pellicle assembly to the mask assembly; and performing semiconductor processing using the protected mask assembly.

Inventors: Cheng; Chen-Pin (Hsinchu, TW), Tang; Tsun-Cheng (Hsinchu, TW), Yen; Guo-Chih (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

Family ID: 1000008783005

Assignee: Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

Appl. No.: 18/328637

Filed: June 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240402623 A1	Dec. 05, 2024

Publication Classification

Int. Cl.: G03F7/00 (20060101); G03F1/64 (20120101); G03F1/84 (20120101)

U.S. Cl.:

CPC G03F7/70983 (20130101); G03F1/64 (20130101); G03F1/84 (20130101); G03F7/70591 (20130101); G03F7/7085 (20130101); G03F7/70975 (20130101);

Field of Classification Search

CPC: G03F (7/70983); G03F (7/70316); G03F (7/70591); G03F (7/70033); G03F (7/70041); G03F (7/70); G03F (7/70483-70541); G03F (7/70691); G03F (7/70716); G03F (7/70741); G03F (7/708); G03F (7/70808); G03F (7/70825); G03F (7/70833); G03F (7/70841); G03F (7/7085); G03F (7/70858); G03F (7/70866); G03F (7/70883); G03F (7/70916); G03F (7/7095); G03F (7/70958); G03F (7/70975); G03F (7/70991); G03F (1/62); G03F (1/64); G03F (1/68); G03F (1/82); G03F (1/84); G03F (1/86); G03F (7/70605-706851); G01B (11/161-164); G01B (9/02); G01B (9/02022); G01B (9/02024); G01B (9/02029); G01B (9/021-029); G01N (2021/451); G01N (2021/456); G01N (2021/458); G01N (21/45); G01N (21/453); G01N (21/455); G01N (21/456)

USPC: 430/5; 355/18; 355/30; 355/52-55; 355/66-77; 356/237.1-23

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5652657	12/1996	Yoshii	356/394	G01N 21/94
6346986	12/2001	Nguyen	430/4	G03F 1/64
6521889	12/2002	Ina	356/336	G01N 21/88
9513229	12/2015	Suzuki	N/A	G03F 7/7085
2001/0026355	12/2000	Aoki	355/53	G03F 7/70933
2007/0035715	12/2006	Choi	355/75	G03F 7/70983
2008/0252869	12/2007	Mori	355/53	G03F 9/7088
2016/0078608	12/2015	Na	382/149	G06T 7/001
2016/0139501	12/2015	Kim	430/5	G03F 1/62
2018/0364561	12/2017	Vles	N/A	G03F 7/7085
2020/0012204	12/2019	Van Der Meulen	N/A	G03F 7/70825
2020/0057383	12/2019	Shih et al.	N/A	N/A
2024/0053281	12/2023	Magana	N/A	G03F 7/70916

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112987490	12/2020	CN	N/A
100620160	12/2005	KR	G03F 7/70741
201619693	12/2015	TW	N/A
202229849	12/2021	TW	N/A

OTHER PUBLICATIONS

English translation of KR100620160, published Sep. 1, 2006. (Year: 2006). cited by examiner

Primary Examiner: Riddle; Christina A

Attorney, Agent or Firm: Seed Intellectual Property Law Group LLP

Background/Summary

BACKGROUND

(1) The semiconductor integrated circuit (IC) industry has experienced exponential growth. Technological advances in IC materials and design have produced generations of ICs where each generation has smaller and more complex circuits than the previous generation. In the course of IC evolution, functional density (i.e., the number of interconnected devices per chip area) has generally increased while geometry size (i.e., the smallest component (or line) that can be created using a fabrication process) has decreased. This scaling down process generally provides benefits by increasing production efficiency and lowering associated costs. Such scaling down has also increased the complexity of processing and manufacturing ICs.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.
- (2) FIGS. 1A and 1B are views of portions of a lithography scanner according to embodiments of the present disclosure.
- (3) FIGS. 2A-2C are views of various embodiments of a mask assembly of the lithography scanner according to various aspects of the present disclosure.
- (4) FIGS. 3A-3G are views illustrating use of a pellicle in accordance with various embodiments.
- (5) FIG. 4 is a view depicting a process for attaching a pellicle to a mask assembly in accordance with various embodiments.
- (6) FIGS. 5A-5D are views depicting a process for attaching a pellicle to a mask assembly according to various aspects of the present disclosure.
- (7) FIGS. 6A-6F are views depicting a process for in-situ scanning a pellicle and a mask according to various aspects of the present disclosure.
- (8) FIG. 7 is a flowchart of a process for performing semiconductor processing using a mask assembly having a pellicle attached thereto in accordance with various embodiments.
- (9) FIG. 8 is a flowchart of a process for scanning a mask and a pellicle prior to mounting in accordance with various embodiments.

DETAILED DESCRIPTION

(10) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(11) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or

at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(12) Terms such as “about,” “roughly,” “substantially,” and the like may be used herein for ease of description. A person having ordinary skill in the art will be able to understand and derive meanings for such terms.

(13) The present disclosure is generally related to lithography equipment for fabricating semiconductor devices, and more particularly to methods of inspecting a pellicle that is part of a mask assembly. Dimension scaling (down) is increasingly difficult in advanced technology nodes. Lithography techniques employ ever shorter exposure wavelengths, including deep ultraviolet (DUV; about 193-248 nanometers), extreme ultraviolet (EUV; about 10-100 nanometers; particularly 13.5 nanometers), and X-ray (about 0.01-10 nanometers) to ensure accurate patterning at the scaled-down dimensions. In an EUV scanner, EUV light is generated by a light source, and reflected toward a wafer by multiple mirrors and a reflective mask. Only a fraction of the EUV light reaches the wafer, such that increasing intensity of EUV light generated by the light source is a topic of much interest.

(14) In EUV lithography, patterns of a mask or reticle are reflected toward a wafer to expose and print the patterns to the wafer. Particles from an EUV scanner chamber, which is a vacuum environment due to EUV absorption, can transport freely onto a pattern-carrying surface of the reticle, forming reticle defects and leading to pattern failure in all exposure fields. Mounting a pellicle, which may be a nanometer-scale thickness thin film that is transparent to EUV wavelengths, at a selected distance from the reticle can prevent reticle defects formed by particles released from the tool. The distance is selected to be far enough away from the reticle focus plane so that no pattern failure occurs due to any particle on the outer surface of the pellicle (e.g., the surface of the pellicle facing away from the reticle), as long as the particle size and EUV transparency are small and clear, respectively.

(15) The pellicle is beneficial to prevent some particles from settling on the reticle. However, particles on an outer surface of the pellicle (e.g., a surface facing away from the reticle) may reduce EUV power, which increases cycle time. In another example, pattern failure may still occur due to particles at an inner region of the pellicle, which are referred to as “inner on-pellicle defects” (IOPDs). IOPDs can be formed in various ways. For example, the IOPD may be formed during a thin film process that forms the pellicle or during mounting to the mask assembly. The IOPDs are prone to falling onto the mask after mounting of the pellicle, such as during wafer fabrication.

(16) Even with a lot of effort on improving mounting process cleanliness (e.g., increased mask cleaning, pellicle particle inspection, mounting tool and environment cleanliness and the like), particles are present on the pellicle after mounting in about 1% of cases. For example, prior to pellicle mounting, an inspection process may be performed for pellicle qualification. After pellicle mounting, a reticle inspection tool may not be used, because the pellicle under tension is easily ruptured by fluctuation and external vibration. One effective method to identify IOPD after mounting is performing wafer exposure and checking whether pattern failure occurs. However, yield is reduced by the number of wafers sent for wafer defect inspection. The wafer defect inspection tool may also be heavily taxed by IOPD detection, and have reduced availability for other inspection tasks. Once the IOPD attaches on the pattern surface, an increased batch size results in an increased reduction in yield.

(17) In embodiments of this disclosure, a method that scans the pellicle in-situ (e.g., inside a mounter) is described. The method may be performed by scanning the pellicle using an optical imager mounted to a mask stage as the pellicle moves to a mating position. When a particle is detected on the pellicle, the pellicle may be removed from the lithography assembly for replacement or rework, which reduces tool downtime. Embodiments of the disclosure provide real-time scanning and particle gating before a final mounting operation. As such, particles not only on the mask surface but also on the pellicle inner membrane may be identified. Particles of size less

than about 2 micrometers (um) and their position(s) can be determined. When a particle(s) is detected on the pellicle, another clean pellicle may be attached. In some embodiments, a second optical imager mounted to a pellicle may similarly scan the mask surface for particles. In response to a particle(s) being detected on the mask, the mask may be cleaned. As such, fall-on particles and rework flow issues may be avoided, reducing tool downtime and improving yield.

(18) FIGS. 1A and 1B depict a lithography exposure system **10** in accordance with various embodiments. The lithography exposure system **10** is described in detail to give context for the description of processes for detecting particles that is provided with reference to FIGS. 6A-7.

(19) FIG. 1A is a schematic and diagrammatic view of a lithography exposure system **10**, in accordance with some embodiments. In some embodiments, the lithography exposure system **10** is an extreme ultraviolet (EUV) lithography system designed to expose a resist layer by EUV radiation, and may also be referred to as the EUV system **10**. The EUV system **10** may also be referred to as an EUV scanner or lithography scanner. The lithography exposure system **10** includes a light source **120**, an illuminator **140**, a mask stage **16**, a projection optics module (or projection optics box (POB)) **30** and a substrate stage **24**, in accordance with some embodiments. The elements of the lithography exposure system **10** can be added to or omitted, and the disclosure should not be limited by the embodiment.

(20) The light source **120** is configured to generate light radiation having a wavelength ranging between about 1 nm and about 100 nm in certain embodiments. In one particular example, the light source **120** generates an EUV radiation with a wavelength centered at about 13.5 nm. Accordingly, the light source **120** is also referred to as an EUV radiation source. However, it should be appreciated that the light source **120** should not be limited to emitting EUV radiation. The light source **120** can be utilized to perform any high-intensity photon emission from excited target fuel.

(21) In various embodiments, the illuminator **140** includes various refractive optic components, such as a single lens or a lens system having multiple reflectors **100**, for example lenses (zone plates) or alternatively reflective optics (for EUV lithography exposure system), such as a single mirror or a mirror system having multiple mirrors in order to direct light from the light source **120** onto the mask stage **16**, particularly to a mask **18** secured on the mask stage **16**. In embodiments in which the light source **120** generates light in the EUV wavelength range, reflective optics are employed. In some embodiments, the illuminator **140** includes at least two lenses, at least three lenses, or more.

(22) The mask stage **16** is configured to secure the mask **18**. In some embodiments, the mask stage **16** includes an electrostatic chuck (e-chuck) to secure the mask **18**. One reason an e-chuck is beneficial is that gas molecules absorb EUV radiation and the e-chuck is operable in the lithography exposure system for the EUV lithography patterning that is maintained in a vacuum environment to avoid EUV intensity loss. In the present disclosure, the terms mask, photomask, and reticle are used interchangeably. In the present embodiment, the mask **18** is a reflective mask. One exemplary structure of the mask **18** includes a substrate with a suitable material, such as a low thermal expansion material (LTEM) or fused quartz. In various examples, the LTEM includes TiO.sub.2 doped SiO.sub.2, or other suitable materials with low thermal expansion. The mask **18** includes a reflective multilayer deposited on the substrate. The mask stage **16** is operable to translate in two horizontal directions, such as an X-axis direction and a Y-axis direction, so as to expose multiple different regions of the semiconductor wafer **22** to light having a pattern generated by the mask **18**. The semiconductor wafer **22** may have a mask layer **26** thereon, which may be a photoresist layer that is sensitive to the light carrying the pattern of the mask **18**.

(23) The projection optics module (or projection optics box (POB)) **180** is configured for imaging the pattern of the mask **18** on to a semiconductor wafer **22** secured on the substrate stage **24** of the lithography exposure system **10**. In some embodiments, the POB **180** has refractive optics (such as for a UV lithography exposure system) or alternatively reflective optics (such as for an EUV lithography exposure system) in various embodiments. The light directed from the mask **18**,

carrying the image of the pattern defined on the mask, is collected by the POB **180**. The illuminator **140** and the POB **180** are collectively referred to as an optical module of the lithography exposure system **10**. In some embodiments, the POB **180** includes at least six reflective optics.

(24) In some embodiments, the semiconductor wafer **22** may be made of silicon or other semiconductor materials. Alternatively or additionally, the semiconductor wafer **22** may include other elementary semiconductor materials such as germanium (Ge). In some embodiments, the semiconductor wafer **22** is made of a compound semiconductor such as silicon carbide (SiC), gallium arsenic (GaAs), indium arsenide (InAs), or indium phosphide (InP). In some embodiments, the semiconductor wafer **22** is made of an alloy semiconductor such as silicon germanium (SiGe), silicon germanium carbide (SiGeC), gallium arsenic phosphide (GaAsP), or gallium indium phosphide (GaInP). In some other embodiments, the semiconductor wafer **22** may be a silicon-on-insulator (SOI) or a germanium-on-insulator (GOI) substrate.

(25) In addition, the semiconductor wafer **22** may have various device elements. Examples of device elements that are formed in the semiconductor wafer **22** include transistors (e.g., metal oxide semiconductor field effect transistors (MOSFET), complementary metal oxide semiconductor (CMOS) transistors, bipolar junction transistors (BJT), high voltage transistors, high-frequency transistors, p-channel and/or n-channel field-effect transistors (PFETs/NFETs), etc.), diodes, and/or other applicable elements. Various processes are performed to form the device elements, such as deposition, etching, implantation, photolithography, annealing, and/or other suitable processes. In some embodiments, the semiconductor wafer **22** is coated with a resist layer sensitive to the EUV radiation. Various components including those described above are integrated together and are operable to perform lithography processes.

(26) The lithography exposure system **10** may further include other modules or be integrated with (or be coupled with) other modules, such as a cleaning module designed to provide hydrogen gas to the light source **120**. The hydrogen gas helps reduce contamination in the light source **120**. Further description of the light source **120** is provided with reference to FIG. **1B**.

(27) In FIG. **1B**, the light source **120** is shown in a diagrammatical view, in accordance with some embodiments. In some embodiments, the light source **120** employs a dual-pulse laser produced plasma (LPP) mechanism to generate plasma **88** and further generate EUV radiation from the plasma. The light source **120** includes a droplet generator **30**, a droplet receptacle **35**, a laser generator **50**, a laser produced plasma (LPP) collector **60**, a monitoring device **70** and a controller **90**. Some or all of the above-mentioned elements of the light source **120** may be held under vacuum. It should be appreciated that the elements of the light source **120** can be added to or omitted, and should not be limited by the embodiment.

(28) The droplet generator **30** is configured to generate a plurality of droplets **82**, which may be elongated, of a target fuel **80** to a zone of excitation at which at least one laser pulse **51** from the laser generator **50** hits the droplets **82** along an x-axis, as shown in FIG. **1B**. In an embodiment, the target fuel **80** includes tin (Sn). In an embodiment, the droplets **82** may be formed with an elliptical shape. In an embodiment, the droplets **82** are generated at a rate of about 50 kilohertz (kHz) and are introduced into the zone of excitation in the light source **120** at a speed of about 70 meters per second (m/s). Other material can also be used for the target fuel **80**, for example, a tin containing liquid material such as eutectic alloy containing tin, lithium (Li), and xenon (Xe). The target fuel **80** in the droplet generator **30** may be in a liquid phase.

(29) The laser generator **50** is configured to generate at least one laser pulse to allow the conversion of the droplets **82** into plasma **88**. In some embodiments, the laser generator **50** is configured to produce a laser pulse **51** to the lighting point **52** to convert the droplets **82** to plasma **88** which generates EUV radiation **84**. The laser pulse **51** is directed through window (or lens) **55**, and irradiates droplets **82** at the lighting point **52**. The window **55** is formed in the sectional collector **60** and adopts a suitable material substantially transparent to the laser pulse **51**. The droplet receptacle **35** catches and collects unused droplets **82** and/or scattered material of the droplets **82** resulting

from the laser pulse **51** striking the droplets **82**.

(30) The plasma emits EUV radiation **84**, which is collected by the collector **60**. The collector **60** further reflects and focuses the EUV radiation **84** for the lithography processes performed through an exposure tool. In some embodiments, the collector **60** has an optical axis **61** which is parallel to the z-axis and perpendicular to the x-axis. The collector **60** may include a single section, as shown, or at least two sections that are offset from each other in the z-axis direction. The collector **60** may further include a vessel wall **65** having first and second pumps **66**, **68** attached thereto. In some embodiments, the first and second pumps **66**, **68** include scrubbers configured to remove particulates and/or gases from the collector **60**. The first and second pumps **66**, **68** may be collectively referred to as “the pumps **66**, **68**” herein.

(31) In an embodiment, the laser generator **50** is a carbon dioxide (CO₂) laser source. In some embodiments, the laser generator **50** is used to generate the laser pulse **51** with single wavelength. The laser pulse **51** is transmitted through an optic assembly for focusing and determining incident angle of the laser pulse **51**. In some embodiments, the laser pulse **51** has a spot size of about 200-300 μm, such as 225 μm. The laser pulse **51** is generated to have certain driving power to meet wafer production targets, such as a throughput of 125 wafers per hour (WPH). For example, the laser pulse **51** is equipped with about 23 KW driving power. In various embodiments, the driving power of the laser pulse **51** is at least 20 KW, such as 27 kW.

(32) The monitoring device **70** is configured to monitor one or more conditions in the light source **70** so as to produce data for controlling configurable parameters of the light source **120**. In some embodiments, the monitoring device **70** includes a metrology tool **71** and an analyzer **73**. In cases where the metrology tool **71** is configured to monitor condition of the droplets **82** supplied by the droplet generator **30**, the metrology tool may include an image sensor, such as a charge coupled device (CCD), complementary metal oxide semiconductor sensor (CMOS) sensor or the like. The metrology tool **71** produces a monitoring image including image or video of the droplets **82** and transmits the monitoring image to the analyzer **73**. In cases where the metrology tool **71** is configured to detect energy or intensity of the EUV light **84** produced by the droplet **82** in the light source **12**, the metrology tool **71** may include a number of energy sensors. The energy sensors may be any suitable sensors that are able to observe and measure energy of electromagnetic radiation in the ultraviolet region.

(33) The analyzer **73** is configured to analyze signals produced by the metrology tool **71** and outputs a detection signal to the controller **90** according to an analyzing result. For example, the analyzer **73** includes an image analyzer. The analyzer **73** receives the data associated with the images transmitted from the metrology tool **71** and performs an image analysis process on the images of the droplets **82** in the excitation zone. Afterwards, the analyzer **73** sends data related to the analysis to the controller **90**. The analysis may include a flow path error or a position error.

(34) In some embodiments, two or more metrology tools **71** are used to monitor different conditions of the light source **120**. One is configured to monitor condition of the droplets **82** supplied by the droplet generator **30**, and the other is configured to detect energy or intensity of the EUV light **84** produced by the droplet **82** in the light source **120**. In some embodiments, the metrology tool **71** is a final focus module (FFM) and positioned in the laser source **50** to detect light reflected from the droplet **82**.

(35) The controller **90** is configured to control one or more elements of the light source **120**. In some embodiments, the controller **90** is configured to drive the droplet generator **30** to generate the droplets **82**. In addition, the controller **90** is configured to drive the laser generator **50** to fire the laser pulse **51**. The generation of the laser pulse **51** may be controlled to be associated with the generation of droplets **82** by the controller **90** so as to make the laser pulse **51** hit each target **82** in sequence.

(36) In some embodiments, the droplet generator **30** includes a reservoir **31** and a nozzle assembly **32**. The reservoir **31** is configured for holding the target material **80**. In some embodiments, one gas

line **41** is connected to the reservoir **31** for introducing pumping gas, such as argon, from a gas source **40** into the reservoir **31**. By controlling the gas flow in the gas line **41**, the pressure in the reservoir **31** can be manipulated. For example, when gas is continuously supplied into the reservoir **31** via the gas line **41**, the pressure in the reservoir **31** increases. As a result, the target material **80** in the reservoir **31** can be forced out of the reservoir **31** in the form of droplets **82**.

(37) FIGS. **2A-2C** are views of various embodiments of a mask assembly **200** of a lithography scanner according to various aspects of the present disclosure. FIG. **2A** is a side view of a mask assembly **200**. FIG. **2B** is a top view of a mask pattern **230** of the mask assembly **200**. FIG. **2C** is a diagram illustrating exposure errors in regions **225** of a semiconductor wafer **220**. FIGS. **2A-2C** are described in detail to provide context for the processes for detecting particles that are described with reference to FIGS. **6A-7**.

(38) In FIG. **2A**, the mask assembly **200** includes a mask stage **216** and a mask **218** attached thereto. The mask stage **216** and the mask **218** may be the mask stage **16** and the mask **18**, respectively, of FIGS. **1A** and **1B**. The mask **218** includes mask patterns **230** that may be located in a layer of the mask **218** facing reflectors of the illuminator **140** and the POB **30** on either side of the mask assembly **200**.

(39) Particles **250** may be present in the lithography scanner. The particles **250** may include different types of particles generated by different sources in the lithography scanner. For example, the particles **250** may include tin particles generated by the light source **120** during formation of the plasma **88**. The particles **250** may include SiC particles generated by movement of the mask assembly **200** in the X- and Y-axis directions. The particles **250** may include carbon particles generated by a pod or carrier used for transporting the mask **218** in and out of the lithography scanner. Other particles **250** having different material composition may be generated by other sources internal or external to the lithography scanner. One or more of the particles **250** may settle on the surface of the mask **218** on one or more mask pattern regions of the mask patterns **230**. The particles **250** that settle on the reticle surface form reticle defects that can lead to pattern failure in all exposure fields (e.g., regions **225** of FIG. **2C**) of a wafer.

(40) FIG. **2B** shows a view of the mask patterns **230** with a particle **250** thereon. The mask patterns **230** are exposed to the internal environment of the lithography scanner. While the mask assembly **200** is in the lithography scanner, the particle **250** may fall on the mask **218**. The particle **250** may form a short circuit or bridge or merger between one or more pattern regions of the mask patterns **230**. When the pattern of the mask **218** is transferred to a semiconductor wafer, an electrical defect, such as a short circuit or bridge or merger, may occur between features of the semiconductor wafer. For example, neighboring semiconductor fins or neighboring conductive traces may merge unintentionally, which may result in failure of an integrated circuit die formed in the semiconductor wafer.

(41) FIG. **2C** shows a diagrammatic view of a semiconductor wafer **220**, which may be the semiconductor wafer **22** of FIGS. **1A** and **1B**. The view of FIG. **2C** may be a diagram of an image generated by a metrology tool that analyzes the semiconductor wafer **220**. During exposure, in which light carrying the pattern of the mask patterns **230** is incident on the semiconductor wafer **220**, the particle **250** alters the pattern, which is transferred repeatedly onto some or all of the regions **225** of the semiconductor wafer **220**. As such, quality of the semiconductor wafer **220** is reduced, reducing productivity of the lithography scanner.

(42) FIGS. **3A-3G** are diagrammatic views showing a pellicle **370** and frame **360** installed on the mask assembly **200** to prevent the particles **250** from attaching to the mask **218**. In FIGS. **3A** and **3B**, the pellicle **370** is shown suspended by the frame **360** over the mask patterns **230**. The pellicle **370** may be a nanoscale thickness thin film that has high transparency (e.g., >90%) to EUV wavelengths (e.g., 13.5 nm). For example, the pellicle **370** may have thickness in the Z-axis direction in a range of about 1 nm to about 10 nm.

(43) The frame **360** has height **D1**, which may be in a range of about 1 millimeter to about 3

millimeters, or more. The height **D1** is about the same as a separation distance between the pellicle **370** and the mask patterns **230** in the Z-axis direction. The frame **360** may have rectangular (e.g., square) shape in the XY-plane, as shown in FIG. 3B. The frame **360** may be adjacent to the mask patterns **230** on four sides, as shown. The frame **360** may be offset horizontally in the X-axis and Y-axis directions from the mask patterns **230**. For example, the frame **360** may be offset from the mask patterns by a second distance **D2** in the Y-axis direction and by a third distance **D3** in the X-axis direction. The distances **D1**, **D2**, **D3** may be the same as each other. In some embodiments, one or more of the distances **D1-D3** is different from others of the distances **D1-D3**. For example, the distance **D1** may be in the range of about 1-3 millimeters as described above, and the second and third distances **D2**, **D3** may be in a range of about 0.5 millimeters to about 10 millimeters.

Mounting the pellicle **370** on the frame **360** can prevent mask defects formed by particles released by the lithography scanner. Generally, the distance **D1** is sufficiently large such that any particle **250** less than a selected size (e.g., diameter less than about 500 nm) that settles on the outside surface of the pellicle **370** is far enough from a focal plane of incident light that the particle **250** does not cause a pattern defect failure.

(44) FIG. 3C illustrates presence of particles **370S**, **370L** on the pellicle **370**. The particles **370S**, **370L** may include small particles **370S** and large particles **370L**. The small particles **370S** may have diameter **D4** that is less than a particle detection resolution of an inspection tool, and the large particles **370L** may have a diameter **D5** that is greater than the particle detection resolution. The particles **370S**, **370L** may be the same as the particles **250** described above with reference to FIGS. 2A-2C. Prior to mounting the pellicle **370** onto the mask assembly **200**, an inspection process may be performed by the inspection tool for pellicle qualification. The qualification process may have a particle detection range or resolution outside of which, particles may not be identified. For example, the particle detection resolution may be about 300 nm. The diameter **D4** of the small particles **370S** may be less than 300 nm, such as less than 200 nm, less than 100 nm, less than 50 nm, or the like. The diameter **D5** of the large particles **370L** may be greater than 300 nm. As such, the large particles **370L** on the inside and outside surfaces of the pellicle **370** may be identified by the inspection tool, and the small particles **370S** may not be identified by the inspection tool, and may remain on the pellicle **370** when mounted.

(45) After mounting the pellicle **370**, further inspection by the inspection tool may damage the pellicle **370**, due to the pellicle **370** being under tension, making it easily ruptured by fluctuation and external vibration. As such, the small particles **370S** may remain on the inside and outside surfaces of the pellicle **370** after the pellicle **370** is mounted to the mask assembly **200**.

(46) FIG. 3D illustrates the mask assembly **200** with the pellicle **370** mounted thereto after a period of operation. Generally, the pellicle **370** may be operated for a selected number of wafers before being replaced. For example, the pellicle **370** may be said to have a “lifetime” of about 10,000 wafers, about 15,000 wafers, or the like. In another example, the pellicle **370** may have a lifetime measured in number of moves or translations. Exposure of all regions of a single wafer may include tens, hundreds or thousands of moves. During manufacture of integrated circuit dies on the semiconductor wafer **220**, the mask assembly **200** may translate back and forth along the XY plane, and particles **350T**, **350P** may attach to the outside surface of the pellicle **370**, as shown in FIG. 3D. The particles **350T**, **350P** may include tool particles **350T** and pod particles **350P**, among other particle types described above with reference to FIGS. 2A-2G. Over time, as the particles **350T**, **350P** accumulate on the pellicle **370**, and due to repeated acceleration along the XY plane of the pellicle **370**, the pellicle **370** may deform or rupture and be replaced.

(47) One or more inner particles or “IOPD” **350I** may be on an inner surface of the pellicle **370** that faces the reticle **218**. As described above with reference to FIG. 3C, the inner particles **350I** may be small particles **350S** that are present on the pellicle **370** prior to and following mounting. For example, the IOPD **350I** may be formed during a thin film process that forms the pellicle **370** or may be induced during mounting of the pellicle **370** to the reticle **218**. In another example, the

inner particles **350I** may be due to bond breaking of pellicle elements after EUV exposure. In yet another example, the inner particles **350I** may be tool particles **350T** or pod particles **350P** that enter the space between the frame **360**, the pellicle **370** and the reticle **218**, which is described in greater detail with reference to FIGS. **3E** and **3F**.

(48) FIGS. **3E** and **3F** illustrate a side view of the frame **360** (FIG. **3E**) and formation of inner pellicle defects due to openings or holes **362** in the frame **360** (FIG. **3F**). Because the pellicle **370** is operated in a vacuum or near-vacuum environment, the holes **362** are present in the frame **360** that are beneficial to balance pressure between the space underneath the pellicle **370** and an internal environment of the lithography scanner in which the mask assembly **200** is disposed. Without the holes **362**, the pellicle **370** would be prone to rupture in the vacuum or near-vacuum environment due to air pressure in the space underneath the pellicle **370** between the pellicle **370** and the mask patterns **230** following mounting of the pellicle **370** to the mask **218**.

(49) As shown in FIG. **3F**, due to the holes **362** in the frame **360**, a particle **350** may enter the space between the pellicle **370** and the mask patterns **230** through the holes **362**. The particle **350** may settle on the inside surface of the pellicle **370**, then may fall and settle on the mask patterns **230**. The particle **350** illustrated in FIG. **3F** may be referred to as an “inner pellicle defect.” The inner pellicle defect is difficult to detect, and may lead to significant reduction of yield.

(50) FIG. **3G** is a diagram that illustrates loss of output power of light incident on the semiconductor wafer **220** relative to number of moves of the mask assembly **200** during processing of wafers. For example, output power of the light source **120** may be about 250 Watts, and after **20,000** moves of the mask assembly **200**, due to accumulation of particles on the pellicle **370**, effective output power may be reduced by about 5% to about 238 Watts. As shown in FIG. **3G**, decay of the pellicle **370** may vary significantly from pellicle to pellicle, batch to batch, lot to lot, or the like, which may increase difficulty in estimating output power and controlling for (e.g., compensating for) the reduction in output power relative to number of moves. For example, if decay of the output power over the lifetime of the pellicle **370** were well known, exposure time could be increased based on the decay relative to the number of moves.

(51) FIG. **4** depicts a method of attaching a pellicle to a mask assembly in accordance with various embodiments. The method of FIG. **4** is described to provide context for the processes described with reference to FIGS. **6A-7**.

(52) In operation **410**, a mask assembly having a pellicle assembly thereon is formed. Operation **410** includes operations **411** and **412**. The mask assembly in operation **410** may be an embodiment of the mask assembly **200**, may be similar or the same as the mask assembly **200**, and is described using the same reference numerals as used above. In operation **411**, mask **218** having mask pattern **230** thereon and a pellicle assembly including frame **360** and pellicle **370** are provided. Pellicle **370** may have one or more particles **350** thereon. For example, as depicted in operation **411**, a particle **350** is on an inner surface of pellicle **370**. In operation **412** the pellicle assembly is mounted or mated to the mask assembly, as shown.

(53) After forming the mask assembly with the pellicle assembly thereon in operation **410**, the mask assembly with the pellicle assembly thereon is inspected in operation **420**. An optical inspection device is used in operation **420** to detect presence of particle(s) **350** on inner and/or outer surfaces of the pellicle **370**. When number and size of particle(s) on the pellicle **370** does not exceed a selected threshold value, the process proceeds from operation **420** to operation **450**, in which the mask assembly with the pellicle assembly thereon is sent on for use in a lithography system, such as the lithography system **10** described with reference to FIGS. **1A** and **1B**. When number and size of particle(s) on the pellicle **370** exceeds the selected threshold value, the process proceeds from operation **420** to operation **430**, in which particle removal is attempted.

(54) Operation **430** follows operation **420** when particle(s) having size and/or number greater than a selected threshold value are detected on pellicle **370**. In operation **430**, removal of the particle(s) from the pellicle **370** is attempted. If removal of the particle(s) is successful, the mask assembly

having the pellicle assembly thereon passes, and may be sent on for use in a lithography system, such as the lithography system **10**, in operation **450**. When removal of the particle(s) is unsuccessful or insufficiently successful, the process proceeds from operation **430** to operation **440**, in which the mask assembly having the pellicle assembly thereon enters a rework flow.

(55) Operation **440** follows operation **430** when removal of particle(s) from the pellicle **370** fails. In the rework flow, the pellicle frame and the pellicle may be demounted from the mask assembly, and a second cleaning operation may be performed on the pellicle. In some embodiments, the pellicle is replaced with a new pellicle by removing the pellicle and attaching the new pellicle to the frame.

(56) Following operation **440**, the process proceeds to operation **412**, in which the pellicle assembly is mounted to the mask assembly as described previously.

(57) The process depicted in FIG. **4** is beneficial to sent out the mask assembly with the pellicle assembly attached thereto with few or no particles thereon. A detailed process **701** that is illustrated in FIG. **7** includes one or more optical sensors installed in the mounter to expedite detection of particles on the pellicle, the mask, or both. In the detailed process **701**, particles may be detected prior to mounting the pellicle assembly to the mask assembly, which may be beneficial to reducing or eliminating rework in the rework flow of operation **440**. FIGS. **6A-6F** illustrate operations of the process **701**. The following description of FIGS. **5A-5D** provides context for the structural elements and process operations in which the process **701** may be performed.

(58) FIG. **5A** depicts operations **511A**, **511B** for forming mask pattern **230** on mask **218** (operation **511A**) and storing the mask **218** in a standard mechanical interface (SMIF) pod **514** (operation **511B**) in accordance with various embodiments. A number of operations may be performed in operation **511A** when making a mask for EUV lithography, such as the mask **218**. Forming the EUV mask may initially include providing a blank substrate **518** made of fused silica or another suitable material. The substrate **518** may be polished to be very flat and clean, which is beneficial for achieving accuracy and resolution in the final mask. An absorber or metal layer **230** may be deposited as a thin layer of metal (e.g., molybdenum) on the substrate **518**. The metal layer **230** absorbs EUV light and forms a pattern that may be transferred to a wafer during semiconductor processing. After the absorber layer **230** is deposited, a layer of photoresist (not depicted) is coated onto the surface thereof. The photoresist layer is then exposed to a pattern of light, which causes the photoresist to become either more or less soluble in certain areas. The photoresist is developed, which removes the soluble regions, leaving a patterned layer of photoresist on top of the absorber layer. The patterned photoresist layer may be used as a mask for etching the absorber layer. Exposed areas of the absorber layer are selectively removed using, for example, a plasma etcher **513**, which leaves behind the desired pattern. The patterned metal layer **230** is also referred to as the “mask pattern” **230**. The substrate **518** and the mask pattern **230** may be referred to collectively as the mask **218**.

(59) In operation **511B**, following formation of the mask pattern **230** in operation **511A**, the mask **218** is positioned in the SMIF pod **514**, as shown. Prior to positioning the mask **218** in the SMIF pod **514**, the mask may be cleaned by a cleaner or cleaning apparatus (not depicted).

(60) FIG. **5B** illustrates an operation **511C** and an operation **511D**. Operation **511C** follows operation **511B**. Following positioning the mask **218** in the SMIF pod **514** in operation **511B**, the SMIF pod **514** is transferred to a mounter or mounting apparatus **530**, and the mask **218** is transferred from the SMIF pod **514** to a mask stage **522**. The mask stage **522** is an embodiment of mask stage **16** and mask stage **216** and may be similar in many respects thereto. The mask **218** is mounted to the mask stage **522** in operation **511C**, for example, by a robot **520**, which may be or include a robot arm **520**. The robot **520** may remove the mask **218** from the SMIF pod **514** and may position the mask **218** on the mask stage **522**, after which the robot **520** may release the mask **218**. The mask stage **522** may be positioned at a top portion **538** of the mounting apparatus **530** and the pellicle stage **532** may be positioned at a bottom portion **536** of the mounting apparatus **530**.

(61) Operation **511D** follows operation **511C**. After the mask **218** is positioned on the mask stage **522**, the mask stage **522** may move in the mounter **530** to a mask mount or mask mate position (see FIG. 5C) as depicted by an arrow in FIG. 5B. The mount position may be aligned with a pellicle mount or pellicle mate position of pellicle stage **532**.

(62) FIG. 5C depicts operations **511E** and **511F**. Operation **511E** follows operation **511D**. Following moving the mask stage **522** to the mask mount position in operation **511D**, pellicle assembly **542** including a pellicle mounted on a frame as described previously is transferred from a pellicle box **540** to the pellicle stage **532**. Operation **511E** may be performed by robot **520**. For example, the robot **520** may grip the pellicle box **540**, open a cover of the pellicle box **540**, remove the pellicle assembly **542** from the pellicle box **540** and place the pellicle assembly **542** on the pellicle stage **532**.

(63) Operation **511F** follows operation **511E**. Following transferring the pellicle assembly **542** from the pellicle box **540** to the pellicle stage **542** in operation **511E**, the pellicle stage **542** may move under the mask stage to a pellicle mount or pellicle mate position (see FIG. 5D) in operation **511F**, as depicted by an arrow in FIG. 5C.

(64) FIG. 5D depicts operation **511G**, which follows operation **511F**. In operation **511G**, the pellicle stage **532** rises slowly until the pellicle assembly **542** is mounted to the mask **218**.

(65) In the process described with reference to FIGS. 5A-5D, each of the operations **511A-511G** may induce particles on the mask **218** or inside the pellicle membrane. FIGS. 6A-6F and FIG. 7 depict a process **701** that detects particle(s) on the pellicle assembly **542** or the mask **218** prior to mounting the pellicle assembly **542** to the mask **218** (e.g., prior to operation **511G** of FIG. 5D). One or more in-situ surface scans detect particle(s) and verify mask quality prior to mounting the pellicle assembly **542** to the mask **218**, for example, by detecting whether a defect level (e.g., number of defects) of the pellicle assembly **542** and/or the mask **218** is less than a selected value. The process **701** may prevent presence of fall-on particles inside the pellicle assembly **542** or on a surface of the mask **218** after mounting of the pellicle assembly **542** to the mask **218**.

(66) FIG. 7 is a flowchart of a process or method **701** for forming a device in accordance with various embodiments. In some embodiments, the process **701** for forming the device includes a number of operations (**700**, **710**, **720**, **722**, **724**, **730**, **740**, **750**, **760**, **762**, **764**, **770**, **772**, **774** and **780**). The process **701** for forming the device will be further described according to one or more embodiments. It should be noted that the operations of the process **701** may be rearranged or otherwise modified within the scope of the various aspects. It should further be noted that additional processes may be provided before, during, and after the process **701**, and that some other processes may be only briefly described herein. In some embodiments, the process **701** is performed by the mounting system **500** described with reference to FIGS. 6A-6F. The embodiments are described with reference to the structural elements and processes described in FIGS. 6A-6F and FIGS. 5A-5D, but the process **701** may be performed by a mounting system having one or more structural elements that are different from those of the mounting system **500**. It should be understood that operation **780** of performing semiconductor processing using the mask assembly may be performed by the lithography exposure system **10** described with reference to FIGS. 1A and 1B. Process **701** may be performed by one or more processors executing computer instructions. In some embodiments, process **701** is performed by specifically designed hardware. In some embodiments, process **701** is performed by a combination of hardware and software.

(67) The method **701** begins at operation **700** and proceeds to operation **710** in which a mask is attached to a mask stage. The mask may be attached to the mask stage in a manner similar to that described for operation **511C** of FIG. 5B. In FIG. 6A, the mask **218** is shown already attached to the mask stage **522**.

(68) Operation **720** follows operation **710**. After the mask is attached to the mask stage in operation **710**, the mask stage is moved toward a mask mounting position in operation **720**, as indicated by an arrow in FIG. 6A and as is indicated by an arrow in FIG. 6B. The mask mounting position may be

similar to that described with reference to operation 511D of FIG. 5B.

(69) Operation 722 follows operation 720. In operation 722, it is determined whether the mask stage has reached the mask mounting position. When the mask stage has not yet reached the mask mounting position, the method 701 proceeds from operation 722 to operation 724, in which the mask is scanned by a first optical detector (e.g., a first interferometer).

(70) A first optical detector 600 is depicted in FIGS. 6A and 6B. In some embodiments, the first optical detector 600 is an interferometer. For example, the first optical detector 600 may be a Spectral Domain Optical Coherence Tomography (SD-OCT) imaging apparatus. An embodiment of the SD-OCT imaging apparatus 600 is depicted in FIG. 6E and described in greater detail later with reference thereto.

(71) The first optical detector 600 may be mounted to a side of the pellicle stage 532, as shown in FIG. 6A. The side may be a side that is distal the pellicle mounting position, as shown in FIG. 6A. In some embodiments, the side is a side that is proximal the pellicle mounting position. The first optical detector 600 may face upward toward the mask stage 522, as depicted in FIGS. 6A and 6B. As such, light for scanning the mask pattern 230 that exits the first optical detector 600 may be incident on the mask pattern 230 as the mask stage 522 passes over the first optical detector 600 on the way to the mask mounting position.

(72) In some embodiments, the light is elongated along an axis. For example, the mask stage 522 may move in a first direction toward the mask mounting position, as indicated by the arrow in FIG. 6B. The light may be elongated along a second direction perpendicular the first direction. Width of the light along the second direction may be substantially the same as width of the mask patterns 230 along the second direction.

(73) In some embodiments, the light has width in the second direction that is much less than the width of the mask patterns 230 along the second direction. As such, the light exiting the first optical detector 600 may scan back and forth along the second direction to cover substantially the entire width of the mask patterns 230 as the mask stage 522 moves toward the mask mounting position.

(74) The first optical detector 600 captures one or more images at different depths. It should be understood that “depth” refers to a third direction that is perpendicular to the first and second directions described herein. The different depths when scanning the mask 218 may refer to depths that are at or above the surface of the mask 218 at which the mask patterns 230 are positioned. Namely, the first optical detector 600 may not need to capture images under the mask patterns 230, as particles are generally not present behind the mask patterns 230, but instead are present on top of the mask patterns 230, on the surface facing the first optical detector 600.

(75) The images may be combined to determine whether the mask 218 passes or fails inspection. For example, the mask 218 may pass inspection when no particle is detected on the mask 218 or when a number and/or size of particles (or “defect level”) on the mask 218 does not exceed (e.g., is less than) a mask particle threshold value (or “selected value”). In some embodiments, the mask particle threshold value is zero, corresponding to no particles being detected on the mask 218. It should be understood that particles below a selected size may not be detected by combining the images captured by the first optical detector 600. As such, the mask 218 may not be free of particles, but may be free of particles over the selected size. For example, the selected size may be having major diameter greater than 200 nm, greater than 300 nm or greater than another suitable dimension.

(76) Operations 720, 722 and 724 may be repeated until the mask stage 522 reaches the mask mounting position. In some embodiments, operation 724 may be performed only while the mask 218 is directly over the first optical detector 600 and may not be performed after the mask 218 has been completely scanned and the mask stage 522 is still moving toward the mask mounting position. When it is determined that the mask stage 522 has reached the mask mounting position, the process 701 moves from operation 722 to operation 730.

(77) Operations 720, 722 and 724 are described as embodiments in which the first optical detector

600 scans the mask **218** as the mask stage **522** moves toward the mask mounting position, which is depicted in FIG. **6A**. Namely, the first optical detector **600** is stationary while capturing images of the mask **218** as the mask stage **522** moves toward the mask mounting position. And, the pellicle assembly **542** is not present on the pellicle stage **532** while the images are captured by the first optical detector **600**.

(78) In some other embodiments, a first optical detector **600A** may be positioned on a side of the pellicle stage **532** that is proximal the pellicle mounting position, namely the opposite side of that shown in FIG. **6A**. In such embodiments, the first optical detector **600A** may be in motion while capturing images of the mask **218** on the mask stage **522** that is stationary at the mask mounting position. Namely, the first optical detector **600A** may scan the mask **218** while the pellicle stage **532** moves toward the pellicle mounting position. And, the pellicle assembly **542** is present on the pellicle stage **532** while the images are captured by the first optical detector **600A**.

(79) In some further embodiments, first optical detectors **600**, **600A** are positioned on both sides (distal and proximal) of the pellicle stage **532**. In such embodiments, the first optical detector **600** on the distal side may scan the mask **218** while the mask stage **522** moves toward the mask mounting position and the first optical detector **600A** on the proximal side may scan the mask **218** while the pellicle stage **532** moves toward the pellicle mounting position. Results of the two scans by the first optical detectors **600**, **600A** on either side of the pellicle stage **532** may be compared or merged to determine count, size and location of particle(s) on the mask **218**.

(80) Operation **730** follows operation **722** when the mask stage **522** has reached the mask mounting position. In operation **730**, it is determined whether the mask **218** passes inspection. When the mask **218** fails as determined based on the images captured by the first optical detector **600**, the process **701** proceeds from operation **730** to operation **740**. When the mask **218** passes as determined based on the images captured by the first optical detector **600**, the process **701** proceeds from operation **730** to operation **750**.

(81) Operation **740** follows operation **730** in response to determining that the mask **218** does not pass inspection. In operation **740**, the mask **218** is cleaned. Cleaning the mask **218** may include backing the mask stage **522** away from the mask mounting position to a position accessible by the robot **520**, removing the mask **218** from the mask stage **522**, placing the mask **218** in the SMIF pod **514**, transporting the mask **218** to a cleaning apparatus (not depicted), transferring the mask **218** from the SMIF pod **514** to the cleaning apparatus and cleaning the mask **218** to remove particle(s) therefrom. After the mask **218** has been cleaned, the mask **218** is reattached to the mask stage **522** by returning to operation **710** from operation **740**.

(82) Operation **750** follows operation **730** in response to determining that the mask **218** does pass inspection. In operation **750**, a pellicle assembly including a pellicle is attached to a pellicle stage. For example, the pellicle assembly **542** is attached to the pellicle stage **532** in FIG. **6C**. Operation **750** may be similar in many respects to operation **511E** of FIG. **5C**.

(83) Operation **760** follows operation **750**. After the pellicle assembly **542** is attached to the pellicle stage **532** in operation **750**, the pellicle stage **532** moves toward the pellicle mounting position, as indicated by arrows in FIGS. **6C** and **6D**.

(84) Operation **762** follows operation **760**. In operation **762**, a determination is made whether the pellicle stage has reached the pellicle mounting position. In response to the pellicle stage not having reached the pellicle mounting position, the process **701** proceeds from operation **762** to operation **764**. In response to the pellicle stage having reached the pellicle mounting position, the process **701** proceeds from operation **762** to operation **770**.

(85) Operation **764** follows operation **762**. In operation **764**, in response to determining that the pellicle stage has not reached the pellicle mounting position, or simply while the pellicle stage is moving toward the pellicle mounting position, the pellicle of the pellicle assembly **542** is scanned by a second optical detector **602**. The second optical detector **602** may be similar in many respects to the first optical detector **600** and/or the first optical detector **600A**. The scanning by the second

optical detector **602** may be similar in many respects to that described with reference to operation **724**, with a difference being that the scanning may be at depths that are on both sides of the pellicle. Namely, the pellicle may have particles on the side facing toward the mask **218** and on the side facing away from the mask **218**, as described with reference to FIG. **3D**. As such, the images may be captured by the second optical detector **602** at depths above the pellicle and below the pellicle.

(86) The second optical detector **602** may be mounted to a side of the mask stage **522**, as shown in FIG. **6C**. The side may be a side that is distal the mask mounting position, as shown in FIG. **6C**. The first optical detector **600** may face downward toward the pellicle stage **532**, as depicted in FIGS. **6C** and **6D**. As such, light for scanning the pellicle that exits the second optical detector **602** may be incident on the pellicle as the pellicle stage **532** passes under the second optical detector **602** on the way to the pellicle mounting position. Because the mask **218** is typically positioned in the mounting apparatus **530** prior to the pellicle assembly **542**, another second optical detector **602** is generally not mounted to the proximal side of the mask stage **522**, as the pellicle is not present while the mask stage **522** moves to the mask mounting position.

(87) The images may be combined to determine whether the pellicle passes or fails inspection. For example, the pellicle may pass inspection when no particle is detected on the pellicle or when a number and/or size of particles (or “defect level”) on the pellicle does not exceed a pellicle particle threshold value (or “selected value”). In some embodiments, the pellicle particle threshold value is zero, corresponding to no particles being detected on the pellicle. It should be understood that particles below a selected size may not be detected by combining the images captured by the second optical detector **602**. As such, the pellicle may not be free of particles, but may be free of particles over the selected size. For example, the selected size may be having major diameter greater than 200 nm, greater than 300 nm or greater than another suitable dimension. In some embodiments, the pellicle may pass inspection when no particle is detected on the inner side of the pellicle that faces toward the mask **218**. Namely, the pellicle may pass even if one or more particles is detected on the outer side of the pellicle that faces away from the mask **218**.

(88) Operation **770** follows operation **762** when the pellicle stage **532** has reached the pellicle mounting position. In operation **770**, it is determined whether the pellicle passes inspection. When the pellicle fails as determined based on the images captured by the second optical detector **602**, the process **701** proceeds from operation **770** to operation **772**. When the pellicle passes as determined based on the images captured by the second optical detector **602**, the process **701** proceeds from operation **770** to operation **774**.

(89) Operation **772** follows operation **770** in response to the pellicle failing inspection. In operation **772**, the pellicle is replaced or reworked. For example, the pellicle may be cleaned by backing the pellicle assembly away from the pellicle mounting position, transferring the pellicle assembly to the pellicle box, transporting the pellicle assembly or the pellicle to a cleaning apparatus, cleaning the pellicle, and optionally remounting the pellicle to the frame. In some cases, the pellicle is replaced with a new pellicle. For example, the cleaning of the pellicle may fail to remove a sufficient number of particles from the pellicle. In another example, the pellicle may be damaged prior to or during cleaning. As such, the new pellicle may be mounted to the frame instead of the pellicle that had the particles thereon. After replacing or successfully reworking the pellicle, the pellicle assembly is reattached to the pellicle stage in operation **750**.

(90) Operation **774** follows operation **770** in response to the pellicle passing inspection. In operation **774**, the pellicle assembly is mounted to the mask assembly. Mounting the pellicle assembly to the mask assembly may include a number of operations. A layer of adhesive may be applied to edges of the mask assembly where the pellicle assembly will be attached. The adhesive may be a UV-cured adhesive that is beneficial to forming tight bond between the mask assembly and pellicle assembly surfaces. Pressure may be applied to the edges of the pellicle assembly that is beneficial for the pellicle assembly to adhere tightly to the mask assembly. The pressure may be

applied using a vacuum chuck (e.g., the pellicle stage **532**) that holds the pellicle assembly in place while the pressure is applied. After the pellicle assembly is attached to the mask assembly, the adhesive may be cured using a UV light source, causing the adhesive to harden and bond tightly to the mask assembly and pellicle assembly surfaces.

(91) Operation **780** follows operation **774**. After mounting the pellicle assembly to the mask assembly, the mask assembly having the pellicle assembly mounted thereto (or simply “protected mask assembly”) is used to perform one or more semiconductor processes. For example, the protected mask assembly may be installed in a lithography system (e.g., the lithography system **10**), light may be reflected as patterned light from the mask **218**, and the patterned light may be directed to a photoresist layer on a semiconductor wafer. The photoresist layer is exposed to a pattern of the patterned light, which causes the photoresist to become either more or less soluble in certain areas. The photoresist is developed, which removes the soluble regions, leaving a patterned layer of photoresist on top of the underlying layer. The patterned photoresist layer may be used as a mask for etching the underlying layer. Exposed areas of the underlying layer are selectively removed using, for example, a plasma etcher, atomic layer etcher, or other suitable etcher, which leaves behind the desired pattern.

(92) The process **701** may be modified in a variety of ways to form different embodiments. For example, operation **724** may be optional. Namely, the process **701** may only scan the pellicle. In another example, operation **764** may be optional. Namely, the process **701** may only scan the mask.

(93) FIG. **6E** depicts an embodiment of the first optical detector **600**. The first optical detector **600** depicted in FIG. **6E** may also be an embodiment of the first optical detector **600A**, the second optical detector **602** or both.

(94) The first optical detector **600** may include an optical module **610** positioned in a housing **612**. The first optical detector **600** may include at least one motor that is operable to step the optical module **610** in the third axis direction, which may be a Z-axis direction or depth direction.

(95) The optical module **610** includes light source **620**. The light source **620** may be or include one or more superluminescent diodes (SLDs) that emit near-infrared light.

(96) The optical module **610** includes a splitter or interferometer **630**. The interferometer **630** splits the light into two beams, one that goes directly to the surface being imaged (e.g., the mask **218** or the pellicle), and the other that reflects off a reference mirror **640**. By measuring the difference in time it takes for the two beams to reach a detection sensor **650**, the optical module **610** can determine the depth of each point on the surface.

(97) The optical module **610** includes one or more mirrors **670** that direct the light to and from the light source **620**, the splitter **630** and the reference mirror **640**.

(98) The optical module **610** includes lenses **680** along optical paths between the light source **620**, the splitter **630**, the reference mirror **640** and the detection sensor **650**. The optical module **610** further includes an object lens **690** that is positioned between the splitter **630** and the surface being imaged.

(99) In FIG. **6E**, the optical module **610** may generate one or more images **652**. Each of the images **652** may be captured at a different depth. With different Z-axis depths, a three-dimensional (3D) Z-axis interference wave map **654** may be generated, and particle(s) may be found using a gating rule or algorithm.

(100) FIG. **6F** depicts partial interference wave maps **656**, **658** that are generated by comparing or merging the images **652** of FIG. **6E**. The wave map **658** is a visual graph of the wave map **656**, which is a numerical representation of depths at each respective region of the surface that was imaged. The partial interference wave maps **656**, **658** depicted in FIG. **6F** may correspond to a region having a particle thereon.

(101) During stage movement, the optical module **610** may scan a variety of ranges of the pellicle membrane with various Z steps, and may thereby identify particles, including particle sizes, particle positions and whether each particle is on the inner or outer surface of the pellicle membrane.

(102) FIG. 8 is a flowchart of a process **801** for scanning a mask and a pellicle prior to mounting in accordance with various embodiments. The process **801** may be utilized when the two first optical detectors **600**, **600A** and the second optical detector **602** are present.

(103) In operation **810**, a mask is attached to a mask stage, which may be similar in many respects to operation **710** of FIG. 7.

(104) Operation **820** follows operation **810**. In operation **820**, a first mask scan is performed. During the first mask scan, the pellicle stage is in the pellicle mounting position, and the first optical detector **600** scans the mask **218** as the mask stage **522** moves toward the mask mounting position. Operation **820** is similar in many respects to operation **724** of FIG. 7.

(105) Operation **830** follows operation **820**. Following the first mask scan being performed, a pellicle assembly is attached or mounted to a pellicle stage in operation **820**, which is similar in many respects to operation **750** of FIG. 7.

(106) Operation **840** follows operation **830**. Following the first mask scan and attaching the pellicle assembly to the pellicle stage, a second mask scan and a pellicle scan are performed in operation **840**. The second mask scan and the pellicle scan may be performed simultaneously as the pellicle stage moves toward the pellicle mounting position. For example, the first optical detector **600A** may scan the mask **218** while the second optical detector **602** scans the pellicle.

(107) Operation **850** follows operation **840**. In operation **850**, presence of particles is detected on the mask and the pellicle, which may be similar in many respects to operations **730** and **770** of FIG. 7, respectively. In the process **801**, the detection of particles on the pellicle does not have to follow after or be dependent on the detection of particles on the mask. Instead, the detection of particles on the pellicle may be performed simultaneously with the detection of particles on the mask or may be performed prior to the detection of particles on the mask.

(108) Embodiments may provide advantages. The methods **701**, **801** of the embodiments detect particles **350** before the pellicle assembly is mounted to the mask assembly, which reduces rework and improves utilization.

(109) In accordance with at least one embodiment, a method includes: placing a mask on a mask stage; placing a pellicle assembly on a pellicle stage, the pellicle assembly including a pellicle; determining whether a defect level of the pellicle is less than a selected value by scanning the pellicle by a first optical detector; forming a protected mask assembly by mounting the pellicle assembly to the mask assembly; and performing semiconductor processing using the protected mask assembly.

(110) In accordance with at least one embodiment, an apparatus includes: a top portion; a mask stage positioned on the top portion; a bottom portion; a pellicle stage positioned on the bottom portion; and a second optical detector mounted to the mask stage, the second optical detector facing the pellicle stage.

(111) In accordance with at least one embodiment, a method includes: placing a mask assembly on a mask stage in a mounting apparatus; placing a pellicle assembly on a pellicle stage in the mounting apparatus; generating a second plurality of images by scanning the pellicle assembly by a second interferometer positioned in the mounting apparatus; determining whether a number of particles on a pellicle of the pellicle assembly exceeds a threshold value; and in response to the number of particles not exceeding the threshold value: forming a protected mask assembly by mounting the pellicle assembly to the mask assembly; and performing semiconductor processing on a semiconductor wafer by using the protected mask assembly.

(112) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that

they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A method, comprising: placing a mask on a mask stage; placing a pellicle assembly on a pellicle stage, the pellicle assembly including a pellicle; determining whether a defect level of the pellicle is less than a selected value by scanning the pellicle by a first optical detector; scanning the mask by a second optical detector mounted on the pellicle stage; forming a protected mask assembly by mounting the pellicle assembly to the mask assembly; and performing semiconductor processing using the protected mask assembly.
2. The method of claim 1, wherein the scanning the pellicle includes scanning the pellicle by the first optical detector that is mounted on the mask stage.
3. The method of claim 1, wherein the scanning of the pellicle by the first optical detector comprises: capturing a plurality of images at different axial positions of the pellicle; combining, by one or more processors, the plurality of images to generate a three-dimensional interference wave map of the pellicle; and determining, by the one or more processors, from the wave map, particle size and position for at least one particle detected from the wave map.
4. The method of claim 1, further comprising capturing a plurality of images by the second optical detector at the same depth.
5. The method of claim 1, wherein the scanning the pellicle includes scanning the pellicle by the first optical detector while the pellicle assembly moves toward a pellicle mounting position.
6. The method of claim 5, wherein the first optical detector is stationary along at least two axes while the pellicle assembly moves toward the pellicle mounting position.
7. The method of claim 1, further comprising capturing a plurality of images by the first optical detector, at least one of the first plurality of images being captured at a different depth than another of the first plurality of images.
8. An apparatus, comprising: a top portion; a mask stage positioned on the top portion; a bottom portion; a pellicle stage positioned on the bottom portion; a first optical detector mounted to the pellicle stage, the first optical detector facing the mask stage; and a second optical detector mounted to the mask stage, the second optical detector facing the pellicle stage.
9. The apparatus of claim 8, wherein the second optical detector comprises an imaging objective sized to illuminate at least a full width of the pellicle while the pellicle stage is in motion.
10. The apparatus of claim 8, further comprising a third optical detector mounted to the pellicle stage, the third optical detector being on an opposite side of the pellicle stage from the first optical detector.
11. The apparatus of claim 8, further comprising a superluminescent diode (SLD) that, in operation, directs light toward a surface of a pellicle mounted to the pellicle stage.
12. The apparatus of claim 11, wherein, in operation, the second optical detector scans the pellicle during movement of the pellicle stage toward a pellicle mounting position along a first direction and the light has width along a second direction perpendicular to the first direction, the width being at least as large as width of the pellicle.
13. The apparatus of claim 8, wherein, in operation, the second optical detector generates a second plurality of images by generating at least one first image at a first depth above a surface of the pellicle and generating at least one second image at a second depth below the surface of the pellicle.
14. The apparatus of claim 13, wherein, in operation, an optical module of the second optical detector is stepped in a direction of the first and second depths during the generating a second plurality of images.
15. A method, comprising: placing a mask assembly on a mask stage in a mounting apparatus;

placing a pellicle assembly on a pellicle stage in the mounting apparatus; generating a second plurality of images by scanning the pellicle assembly by a second interferometer attached to a side of the mask stage and positioned in the mounting apparatus; determining whether a number of particles on a pellicle of the pellicle assembly exceeds a threshold value; and in response to the number of particles not exceeding the threshold value: forming a protected mask assembly by mounting the pellicle assembly to the mask assembly; and performing semiconductor processing on a semiconductor wafer by using the protected mask assembly.

16. The method of claim 15, further comprising generating a first plurality of images by scanning a mask of the mask assembly by a first interferometer positioned in the mounting apparatus.

17. The method of claim 15, wherein generating the second plurality of images comprises: capturing at least one first image at a depth above a surface of the pellicle; capturing at least one second image at a depth below the surface of the pellicle; and stepping an optical module of the second interferometer in a direction perpendicular to the pellicle surface between the first and second depths.

18. The method of claim 15, wherein the side is a side distal a mask mounting position.

19. The method of claim 15, further comprising generating a three-dimensional interference wave map by combining the second plurality of images.

20. The method of claim 19, further comprising determining size and position of at least one particle based on the interference wave map.
