

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399502
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ready-Campbell; Noah Austen et al.

Obstacle map for autonomous pile driving system

Abstract

An autonomous off-road vehicle (AOV) accesses a pile plan map indicating a plurality of locations within a geographic area at which piles are to be installed. The AOV generates an obstacle map indicating locations of obstacles within the geographic area. The AOV autonomously navigates to a first location of the plurality of locations using the pile plan map. In response to driving a pile into the ground at the first location, the AOV modifies the obstacle map to include a representation of the pile at the first location. The AOV autonomously navigates to a second location of the plurality of locations using the pile plan map. In response to driving a pile into ground at the second location, the AOV modifies the obstacle map that includes the representation of the pile at the first location to further include a representation of the pile at the second location.

Inventors: Ready-Campbell; Noah Austen (San Francisco, CA), Liang; Andrew Xiao (San Francisco, CA), Kikani; Gaurav Jitendra (San Francisco, CA)

Applicant: Built Robotics Inc. (San Francisco, CA)

Family ID: 1000008784418

Assignee: Built Robotics Inc. (San Francisco, CA)

Appl. No.: 18/483652

Filed: October 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240210947 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 18085881 20221221 US 11822342 child-doc US 18483652

Publication Classification

Int. Cl.: G05D1/00 (20240101)

U.S. Cl.:

CPC G05D1/0274 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3061121	12/1961	Sutton	N/A	N/A
5548397	12/1995	Kool et al.	N/A	N/A
5610818	12/1996	Ackroyd et al.	N/A	N/A
6543551	12/2002	Sparks et al.	N/A	N/A
7516563	12/2008	Koch	N/A	N/A
9756771	12/2016	Redden	N/A	N/A
10907318	12/2020	Flanigan et al.	N/A	N/A
11301790	12/2021	Damia-Levy	N/A	N/A
11378964	12/2021	Wei	N/A	N/A
11788247	12/2022	Ready-Campbell et al.	N/A	N/A
11822342	12/2022	Ready-Campbell et al.	N/A	N/A
2012/0136525	12/2011	Everett et al.	N/A	N/A
2013/0060461	12/2012	Wong et al.	N/A	N/A
2014/0074342	12/2013	Wong et al.	N/A	N/A
2014/0215953	12/2013	Sawaki	N/A	N/A
2014/0365084	12/2013	Chan et al.	N/A	N/A
2015/0233076	12/2014	Montgomery et al.	N/A	N/A
2016/0108598	12/2015	Waxse	N/A	N/A
2016/0371400	12/2015	Challita et al.	N/A	N/A
2020/0032489	12/2019	Yamazaki et al.	N/A	N/A
2020/0047337	12/2019	Williams et al.	N/A	N/A
2020/0217034	12/2019	Karkheck et al.	N/A	N/A
2020/0350850	12/2019	Di Stefano et al.	N/A	N/A
2020/0394813	12/2019	Theverapperuma et al.	N/A	N/A
2021/0072760	12/2020	Ready-Campbell et al.	N/A	N/A
2021/0325875	12/2020	Schlacks et al.	N/A	N/A
2022/0121353	12/2021	Cesic et al.	N/A	N/A
2022/0163974	12/2021	Davis	N/A	N/A
2022/0244741	12/2021	Da Silva et al.	N/A	N/A

2022/0275662	12/2021	Tassinari	N/A	E02D 7/02
2022/0379481	12/2021	Brett	N/A	N/A
2023/0098524	12/2022	Tiwari et al.	N/A	N/A
2023/0119845	12/2022	O'Brien et al.	N/A	N/A
2024/0025714	12/2023	Brulo et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019340235	12/2019	AU	N/A
113981867	12/2021	CN	N/A
113981969	12/2021	CN	N/A
1223094	12/2018	ES	N/A
2787948	12/2019	ES	N/A
H01-209300	12/1988	JP	N/A
H05-025826	12/1992	JP	N/A
H05-202522	12/1992	JP	N/A
2021-028764	12/2020	JP	N/A
WO 2000/024666	12/1999	WO	N/A
WO 2019/027311	12/2018	WO	N/A
WO 2023/060318	12/2022	WO	N/A

OTHER PUBLICATIONS

Groundwork, STX GPS System, [https://web.archive.org/web/20220415000000*/https://67Sa72ad-9537-472c-802a-](https://web.archive.org/web/20220415000000*/https://67Sa72ad-9537-472c-802a-c568d990efeb.usrfiles.com/ugd/678a72_0503eed7474b4c17b70fda5ac3273039.pdf)

[c568d990efeb.usrfiles.com/ugd/678a72_0503eed7474b4c17b70fda5ac3273039.pdf](https://www.groundworkexperts.com/product-page/gps-system-for-solar-pile-installation),
<https://www.groundworkexperts.com/product-page/gps-system-for-solar-pile-installation> (Year: 2022), 4 pages. cited by applicant

Hannigan, P.J., et al., “Design and Construction of Driven Pile Foundations,” *Geotechnical Engineering Circular* No. 12, vol. 1, (Jul. 2016). Retrieved May 1, 2023, from <https://www.fhwa.dot.gov/engineering/geotech/pubs/gec12/index.cfm> (Year: 2016), 563 pages. cited by applicant

M. A. Mortenson Company, “Mortenson & Orteco Announce New Robotic Technology for Solar Energy Construction,” Sep. 19, 2022, 3 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <<https://www.mortenson.com/newsroom/apds-solar-construction-technology>>. cited by applicant

Orteco, “6001-800J-1000J—on excavator: Piledriver mounted on excavator,” undated, 6 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <<https://www.orteco.com/en/scheda.php?id=201>>. cited by applicant

Orteco, “Piledriver HD 800 crawler mounted: Piledriver crawler mounted,” undated, 6 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <<https://www.orteco.com/en/scheda.php?id=199>>. cited by applicant

Plotkin, K. Kym Plotkin's Post on Solar X Blade Pile installation mast system, 2021, 11 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <https://www.linkedin.com/posts/kym-plotkin-72567099_sxbp-install-mast-showcase-activity-6864779122137292800-n81r?utm_source=share&utm_medium=member_desktop>. cited by applicant

Scully, J. “Mortenson deploys robotic pile distribution system to speed up solar project construction,” PV Tech, Sep. 21, 2022, 4 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved

from the Internet URL: <<https://www.pv-tech.org/mortenson-deploys-robotic-pile-distribution-system-to-speed-up-solar-project-construction/>>. cited by applicant

Stonex STX Suite—guidance solution “full automatic release”, https://www.youtube.com/watch?v=hzbkH-IE_xY, accessed May 23, 2023, Publication Jan. 28, 2019 (Year: 2019), 1 page. cited by applicant

Stonex STX Suite, STX-Drill presentation at Intergeo Digital 2020, Nov. 3, 2020, <https://www.youtube.com/watch?v=rY7L9Sr4Gqs>, (Year: 2020), 4 pages. cited by applicant

United States Final Office Action, U.S. Appl. No. 18/085,888, Jul. 21, 2023, 14 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,888, May 19, 2023, 15 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,893, Jun. 7, 2023, 9 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,901, Jun. 8, 2023, 8 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/180,626, Aug. 22, 2023, 17 pages. cited by applicant

Universal Field Robots, “Creators of Autonomous Robots with Extraordinary Capabilities,” undated, 5 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <<https://universalfieldrobots.com.au>>. cited by applicant

Universal Field Robots, “The UFR Product Portfolio is Expanding,” undated, 5 pages, [Online] [Retrieved on Dec. 20, 2022] Retrieved from the Internet URL: <<https://universalfieldrobots.com.au/our-products/>>. cited by applicant

Built Robotics, “Solar Piling,” date unknown, 16 pages, [Online] [Retrieved on Jul. 1, 2024] Retrieved from the Internet <URL: <https://www.builtrobotics.com/solutions/solar-piling>>. cited by applicant

International Search Report and Written Opinion, Patent Cooperation Treaty Application No. PCT/US2023/078487, mailing date Apr. 5, 2024, 18 pages. cited by applicant

United States Final Office Action, U.S. Appl. No. 18/085,881, Jun. 1, 2023, 16 pages. cited by applicant

United States Final Office Action, U.S. Appl. No. 18/085,901, Nov. 24, 2023, 14 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,881, Apr. 20, 2023, 14 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,888, Dec. 8, 2023, 16 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/085,901, Mar. 28, 2024, 18 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/180,630, Jan. 25, 2024, 9 pages. cited by applicant

United States Non-Final Office Action, U.S. Appl. No. 18/180,630, Nov. 9, 2023, 10 pages. cited by applicant

Universal Field Robots, “Autonomous Piling: Two Robots Working Together,” youtube.com, Nov. 29, 2019, URL: <https://www.youtube.com/watch?v=X0PYY_8LNzc>, 3 pages. cited by applicant

Vestil Manufacturing, Spring Scissor Tables (Year: 2019), 1 page. cited by applicant

United States Office Action, U.S. Appl. No. 18/085,888, Jun. 20, 2024, 14 pages. cited by applicant

United States Office Action, U.S. Appl. No. 18/085,888, Oct. 28, 2024, 13 pages. cited by applicant

United States Office Action, U.S. Appl. No. 18/180,630, May 31, 2024, 12 pages. cited by applicant

United States Office Action, U.S. Appl. No. 18/180,626, Aug. 2, 2024, 17 pages. cited by applicant

Primary Examiner: Rink; Ryan

Attorney, Agent or Firm: Fenwick & West LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 18/085,881, filed Dec. 21, 2022, now U.S. Pat. No. 11,822,342, which is incorporated by reference in its entirety.

TECHNICAL FIELD

(1) This disclosure relates to driving piles into the ground, and, more specifically, to various autonomous operations related to autonomous pile driving.

BACKGROUND

(2) Heavy equipment vehicles such as backhoes, loaders, and excavators may be used to perform a variety of earthwork operations (e.g., pile driving, drilling, excavating, digging, jackhammering, demolishing, and the like). Currently, operation of these vehicles is very expensive as each vehicle requires a manual operator on the vehicle during the entire earthwork operation. Another complication stems from an insufficient labor force skilled enough to meet the demand for operating these vehicles. Because these vehicles must be operated manually, the operations can only be performed during the day, extending the duration of projects, and further increasing overall costs. Also, dependence of current vehicles on manual operators increases the risk of human error during operations and reduces the quality of work done at the site.

SUMMARY

(3) In one embodiment, a method includes a plurality of steps performed by an autonomous off-road vehicle (AOV). The steps include a step of accessing a pile plan map indicating a plurality of locations within a geographic area at which piles are to be installed. The steps further include a step of generating an obstacle map indicating locations of obstacles within the geographic area. The steps further include a step of autonomously navigating by the AOV to a first location of the plurality of locations using the pile plan map. And the steps further include, in response to driving a pile into the ground at the first location, a step of modifying the obstacle map to include a representation of the pile at the first location.

(4) In another embodiment, a method includes a plurality of steps performed by an autonomous off-road vehicle. The steps include a step of accessing a pile plan map indicating a plurality of locations in a geographic area at which piles are to be installed. The steps further include a step of selecting a first location and a second location from the plurality of locations using the pile plan map. The steps further include a step of autonomously navigating the AOV to the first location. The steps further include a step of autonomously loading a first pile onto a driving tool of the AOV. The steps further include a step of autonomously driving the first pile into the ground at the first location using the driving tool. The steps further include a step of autonomously navigating the AOV to the second location. The steps further include a step of autonomously loading a second pile onto the driving tool. And the steps further include a step of autonomously driving the second pile into the ground at the second location using the driving tool.

(5) In another embodiment, a method includes a plurality of steps. The steps include a step of

accessing a pile plan map indicating a plurality of locations in a geographic area at which piles are to be installed. The steps further include a step of identifying a first set of locations from the plurality of locations and a first set of piles to be driven into the ground at the first set of locations using the pile plan map. The steps further include a step of identifying an order for driving the first set of piles into the ground and a pile type for each of the first set of piles. And the steps further include a step of generating basket assembly instructions for assembling the first set of piles into a basket based on the identified order and the identified pile types.

(6) In yet another embodiment, a method includes a plurality of steps performed by an autonomous off-road vehicle (AOV). The steps include a step of autonomously performing a pile driving operation by driving a pile into the ground at a location identified by a pile plan map. The steps further include a step of detecting one or more attributes of the pile using one or more sensors during or after the pile driving operation. The steps further include a step of determining whether the one or more attributes of the pile exceed respective tolerance thresholds. And the steps further include a step of performing a quality control action in response to determining that the one or more attributes of the pile exceed the respective tolerance thresholds.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The disclosed embodiments have other advantages and features which will be more readily apparent from the detailed description, the appended claims, and the accompanying figures (or drawings). A brief introduction of the figures is below.

(2) FIG. 1 illustrates an autonomous off-road vehicle (AOV) system environment, according to some embodiments.

(3) FIG. 2A shows a perspective view of one exemplary design of the AOV of FIG. 1, in accordance with some embodiments.

(4) FIG. 2B shows a perspective view of another exemplary design of the AOV of FIG. 1, in accordance with some embodiments.

(5) FIG. 3A is a block diagram of the AOV of FIG. 1, in accordance with some embodiments.

(6) FIG. 3B is a block diagram of the control system of the AOV of FIG. 3A, in accordance with some embodiments.

(7) FIG. 4 illustrates an exemplary pile plan map, in accordance with some embodiments.

(8) FIG. 5 is a block diagram of the basket assembly module of the control system of FIG. 3B, in accordance with some embodiments.

(9) FIG. 6A depicts a basket loading operation performed by the AOV having the exemplary design shown in FIG. 2A, in accordance with some embodiments.

(10) FIG. 6B depicts an autonomous pile loading operation performed by the AOV having the exemplary design shown in FIG. 2A, in accordance with some embodiments.

(11) FIG. 6C depicts an autonomous pile driving operation performed by the AOV having the exemplary design shown in FIG. 2A, in accordance with some embodiments.

(12) FIG. 7 is a block diagram of the quality control module of the control system of FIG. 3B, in accordance with some embodiments.

(13) FIG. 8 depicts a quality control operation performed by the AOV having the exemplary design shown in FIG. 2A, in accordance with some embodiments.

(14) FIG. 9 is a block diagram of the obstacle mapping module of the control system of FIG. 3B, in accordance with some embodiments.

(15) FIG. 10 illustrates an exemplary obstacle map generated and modified by the obstacle mapping module of FIG. 9, in accordance with some embodiments.

(16) FIG. 11 is a flow chart illustrating a process for generating basket assembly instructions, in

accordance with some embodiments.

(17) FIG. 12 is a flow chart illustrating a process of autonomously driving a plurality of piles into the ground, in accordance with some embodiments.

(18) FIG. 13 is a flow chart illustrating a process of performing an autonomous quality control operation for autonomously driven piles, in accordance with some embodiments.

(19) FIG. 14 is a flow chart illustrating a process of performing an autonomous obstacle map creation operation based on autonomously driven piles, in accordance with some embodiments.

(20) FIG. 15 is a block diagram illustrating components of an example machine for reading and executing instructions from a machine-readable medium, in accordance with one or more example embodiments.

DETAILED DESCRIPTION

(21) The Figures (FIGS.) and the following description relate to preferred embodiments by way of illustration only. It should be noted that from the following discussion, alternative embodiments of the structures and methods disclosed herein will be readily recognized as viable alternatives that may be employed without departing from the principles of what is claimed.

(22) Reference will now be made in detail to several embodiments, examples of which are illustrated in the accompanying figures. It is noted that wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict embodiments of the disclosed system (or method) for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles described herein.

Configuration Overview

(23) This disclosure pertains to autonomous off-road vehicles (AOVs) for performing various autonomous operations related to pile driving. As used herein, “AOV” refers to any vehicle, apparatus, multi-unit system, or robot, that moves and/or operates autonomously. The AOVs are configured to operate on paved surfaces as well as in off-road environments (e.g., on surfaces other than paved roadway). The AOVs may include any tracked vehicle, construction vehicle, robot, tractor, excavator, bulldozer, transport vehicle, delivery vehicle, distribution vehicle, and the like. Example off-road environments include solar farms, dirt roads, fields, agricultural sites, rocky or gravel terrain, construction sites, forest or wooded sites, hill or mountain trails or sites, underground sites, indoor sites, rooftops, and the like. As used herein, “autonomous” refers to the ability of the off-road vehicle to operate without constant human supervision, for instance enabling the off-road vehicle to move, navigate, perform a function, and/or make a decision without explicitly receiving instructions from a human operator.

(24) Pile driving operations involve driving piles into the ground to build structures supported on top of the piles. Piles (e.g., stakes, rebars, piers, poles, posts, beams, etc.) may be of different types based on features like length, dimensions, shape or design, bolt hole pattern, material, weight, thickness or steel gauge, and the like. Non-limiting examples of different pile designs or shapes include ground screws, helical piles, c-channel piles, sheet piles, wide flange beam piles, H-beam piles, I-beam piles. Non-limiting examples of different pile materials include metal, wood, concrete, precast concrete, reinforced concrete, synthetic material, and the like. Each pile type (having a specific configuration or set of characteristics) may have a corresponding color code or other identification code. As used herein, “ground” may refer to any earth or non-earth substrate where piles are to be installed. For example, a large collection (e.g., hundreds, thousands, tens of thousands, etc.) of photovoltaic (PV) solar panels may be installed in a geographic area to create a solar farm by driving a large number of piles into the ground, mounting individual solar panels on top of the driven piles, and electrically interconnecting the solar panels to generate large amounts of electricity from solar power. Techniques disclosed herein look to automate the pile driving process by operating AOVs (e.g., an AOV or a fleet of multiple AOVs operating simultaneously

and communicating with a central server) that are configured to perform a plurality of autonomous operations related to pile driving (e.g., path planning operation, navigation operation, pile basket assembly operation, pile basket loading operation, pile basket distribution operation, pile distribution operation, pile loading operation, pile driving operation, obstacle map creation operation, quality control operation, pile removal operation, and the like).

(25) The systems and methods disclosed herein look to automate the process of driving a plurality of piles at respective locations into the ground using one or more AOVs based on a pile plan map. As used herein, the “pile plan map” (e.g., see FIG. 4) may be a digital representation indicating a plurality of locations in a geographic area (e.g., a lot, plot, tract, parcel of land, indoor site, elevated site, etc.) in which piles are intended to be driven and located. The pile plan map may specify locations (e.g., geolocations, geographic (x,y) or GPS coordinates) in the geographic area where the respective piles are to be driven, and the type (e.g., thickness, length, weight, shape or design, material, bolt hole pattern, etc.) of the pile to be driven at the location. For each location, the pile plan map may also specify other pile parameters (e.g., length, reveal height, orientation, tilt, tolerance range or threshold, number of piles, type of each pile or any other type of object that is to be located at or driven into the ground in addition to the pile at the location, etc.) for driving of the pile at the location. The pile parameters in the pile plan map may thus define the intended state of the pile at the location after the installation of the pile at the location is complete. It should be noted that reference herein to the movement, manipulation, driving, adjustment, or any other manipulation of a pile can apply equally to ground screws, beams, stakes, or any other object that can be inserted into the ground.

(26) Based on the pile plan map, the systems and methods enable the performance of the different autonomous operations. For example, based on the pile plan map, the systems and methods may perform a path planning operation for a given AOV. In the path planning operation, the systems and methods may select a set of locations, where piles are to be installed by the AOV, from among a plurality of locations indicated in the pile plan map. The set of locations may be selected to optimize predetermined criteria. For example, the set of locations may be selected to minimize navigation or driving time and/or cost, minimize greenhouse gas emissions, maximize efficiency, reduce downtime (e.g., non-pile-driving time). The set of locations may also be selected based on pile availability, based on an obstacle map, or to ensure accessibility of each location specified by the pile plan map for subsequent pile driving by the same or other AOVs.

(27) Based on the selected set of locations, the systems and methods may perform a basket assembly operation. For example, the systems and methods may generate instructions for assembling a set of piles in a specific order based on the order in which the piles are to be driven into the ground at the selected set of locations. In some embodiments, based on the specific order for the set of piles in the generated instructions, a pile basket assembly robot (e.g., AOV) may assemble and load the set of piles that may have different pile types in the specified order into a pile set holder (e.g., basket, cartridge, housing, etc.).

(28) As a result, during the subsequent pile driving operation at each location specified by the path plan, a pile type of the pile that is accessible to a pile driving AOV from the basket of piles (e.g., the top pile in a stack of piles in the basket) will match the pile type of the pile that is to be driven into the ground at that location per the pile plan map. That is, the “correct” pile is always accessible to the AOV when it arrives at the target location. Thus, based on the generated instructions, piles of different types may be loaded in the designated order into the basket autonomously (e.g., by the pile basket assembly robot or AOV). In other embodiments, based on the generated basket assembly instructions, piles of different types may be loaded in the designated order into the basket manually (e.g., by a third-party vendor that receives the instructions and assembles the piles of the different types in the specified order into the respective baskets and delivers the assembled baskets ready for use during autonomous pile driving). As a result of the basket assembly operation, conventional manual steps of material distribution to access the correct pile at the target location or

prior material distribution need not be performed, thereby eliminating significant amounts of manual labor, and reducing error during construction. As used herein, a “basket” of piles or “pile basket” refers to anything (e.g., cartridge, cassette, housing, container, bin, silo, etc.) in which a set of piles of different types can be carried or moved.

(29) In some embodiments, instead of performing the basket assembly operation, the piles of the different types may be assembled in respective baskets and loaded onto a carriage so that a pile of each type remains always accessible to the loading and/or driving tool of the AOV. In such embodiments, based on the type of pile that is to be driving into the ground at each location, the pile loading tool may be actuated at each location to corresponding baskets having one or more piles of respective types for driving into the ground. For example, at a first location where a first type of pile is to be installed, the pile loading tool may be autonomously actuated to load a pile of the first type from a location (e.g., a first basket) storing the first type of piles. And at a second location where a second type of pile is to be installed, the pile loading tool may be autonomously actuated to load a pile of the second type from a location (e.g., a second basket the same or separate from the first basket) storing the second type of piles.

(30) The systems and methods may further be configured to perform autonomous pile driving for each location of the pile plan map. Autonomous pile driving may include an autonomous navigation operation, an autonomous pile loading operation, and an autonomous pile driving operation (performed by a same/single AOV, or by a multi-vehicle system). In the autonomous navigation operation, an AOV (which may be the same as or different from the AOV that carries the basket of the ordered set of piles) may navigate autonomously (based on a path plan determined by the path planning operation) to a first location where a first one of the set of piles in the loaded basket is to be driven.

(31) In the autonomous pile loading operation, the pile driving AOV may autonomously load the first one of the set of piles from the basket (e.g., the first or top pile in the stack of piles in the basket) onto a driving tool of the AOV to drive the pile into the ground. In the autonomous pile driving operation, the AOV may autonomously drive the pile loaded onto the driving tool of the AOV into the ground. In performing the autonomous pile driving operation at the location, the AOV may utilize the pile parameters for the location included in the pile plan map and, in some embodiments, control actuation parameters of the driving tool of the AOV based on the pile parameters to achieve the intended state (e.g., pile height, plumbness, orientation, location, etc.) of the pile at the location after the autonomous pile driving operation. The AOV may then similarly perform repeated autonomous pile driving operations for subsequent locations per the path plan. A fleet of AOVs may simultaneously and continuously perform the autonomous pile driving operations at respective sets of locations from among the plurality of locations of the same pile plan map to complete large-scale pile driving projects quickly and accurately, and with high efficiency and reduced costs.

(32) During or after the pile driving operation, the pile driving AOV (or a separate quality control AOV) may perform a quality control operation to ensure that the driving of the pile at each location complies with the corresponding pile parameters dictated by the pile plan map. For example, the AOV may operate one or more sensors at a predetermined frequency during the pile driving operation to obtain sensor data and determine whether one or more attributes of the pile (being) installed at the location are within corresponding tolerance thresholds. The one or more attributes of the pile that may be monitored based on the sensor data may include the (actual) horizontal location of the pile driven into the ground, the vertical location of the top of the pile (e.g., to detect an over-driven pile, or an under-driven pile; also referred to as reveal height), pile refusal condition, plumbness or verticality of the pile relative to ground, orientation of the pile (e.g., 3D orientation of the bolt holes of the pile), rotation or yaw of the pile relative to the ground, deformation (e.g., bend, dents, etc.) of the pile, damage (e.g., crack or other manufacturing defect) to the pile, and the like.

(33) The quality control operation may determine performance of one or more quality control actions based on quality control condition data (e.g., pile attribute data) generated based on the determination regarding one or more of the pile attributes being outside corresponding tolerance thresholds. For example, the quality control action may be to flag the location in association with the corresponding quality control condition data in a quality control map for subsequent manual inspection. Another example of the action may be to stop the pile driving operation prior to its completion. As yet another example, the action may be to modify actuation parameters of the pile driving tool to perform corrective action during the pile driving operation to attempt to bring an offending attribute back within the corresponding tolerance threshold (e.g., change the angle of impact of the driving tool on top of the pile being driven into the ground to bring the plumbness of the pile closer to a desired plumbness as dictated by the pile parameters in the pile plan map).

(34) Based on the pile driving operation, the systems and methods according to the present disclosure may also generate an obstacle map indicating locations of obstacles within the geographic area. As used herein, the “obstacle map” may be a digital representation indicating obstacles or objects within the geographic area. For each obstacle tagged in the map, the obstacle map may include attributes of the obstacle such as identity, type or category of the object, physical characteristics of the object, 3D location of the object, depth of the object, and the like. The obstacle map may thus convey non-navigable regions for the AOV within the geographic area and may include as-built obstacles like piles that have been installed by the AOV at locations prescribed by the pile plan map. The as-built obstacles may be added to the obstacle map based on the pile driving operation performed by the AOV. That is, in response to the pile driving operation of driving the pile at a first location, the obstacle map may be modified to include a representation of the pile at the first location. Subsequent pile driving operations at subsequent locations may result in similar modifications to the obstacle map to include representations of the piles at the subsequent locations. The representations of the piles at the respective locations may include obstacle attributes such as horizontal location of the pile, vertical location of the top of the pile, 3D discretized pile volume data, and the like. The obstacle map may also include data regarding other types of static (e.g., inverters, torque tubes, trenches, dirt piles, electric poles, etc.) or dynamic (e.g., other AOVs or vehicles, pedestrians, etc.) obstacles (e.g., non-pile obstacles). The non-pile obstacles may be added to the obstacle map perceptually based on sensor data captured by the AOV.

(35) Techniques disclosed herein may also look to synchronize the obstacle map based on operations being performed by multiple AOVs and use the synchronized and continuously updated, dynamic obstacle map to avoid obstacles while performing the different operations by the multiple AOVs like the path planning operation, the navigation operation, the pile loading operation, AOV tool actuation operation, the pile driving operation, and the like.

Example Autonomous Off-Road Vehicle System Environment

(36) FIG. 1 illustrates an autonomous off-road vehicle system environment **100**, according to some embodiments. The environment **100** of FIG. 1 includes one or more autonomous off-road vehicles **110** (“AOV” or simply “vehicle” hereinafter), a central server **130**, and a client device **140**, each communicatively coupled via a network **160**. It should be noted that in other embodiments, the environment **100** may include different, fewer, or additional components than those illustrated in FIG. 1. For instance, the client device **140** and the central server **130** may be the same device.

(37) Each AOV **110** of FIG. 1 may be a vehicle (e.g., item of heavy equipment, vehicle, apparatus, system, robot, and the like) that is configured to move and/or operate autonomously and that is configured to communicate with the central server **130**. Examples of AOVs **110** within the scope of this description include, but are not limited to pile loaders, pile drivers, pile driving rigs, pile distribution vehicles, pile basket assembly robots, loaders such as backhoe loaders, track loaders, wheel loaders, skid steer loaders, scrapers, graders, bulldozers, compactors, excavators, mini-excavators, trenchers, skip loaders, tracked vehicles, construction vehicles, tractors, transport

vehicles, delivery vehicles, distribution vehicles, and the like. Collectively, AOVs **110** may correspond to an AOV fleet that includes one or more of each of different types of AOVs **110** that respectively have different functionality. Example embodiments and functional components of the AOV **110** are described in greater detail below in at least FIGS. 3A-3B.

(38) The central server **130** is a computing system located remotely from the AOV **110**. In some embodiments, the central server is a web server or other computer configured to receive data from and/or send data to one or more AOVs **110** within the environment **100**. In some embodiments, the central server **130** receives information from the AOV **110** (e.g., obstacle data, quality control condition data, sensor data, etc.) indicating a location of the AOV **110**, a result of a function or operation being performed by the AOV **110**, a state of one or more vehicles, information describing the surroundings of the AOV **110**, and the like. In some embodiments, the central server **130** may receive a real-time feed of data from the AOV **110**, such as a real-time video feed of the environment surrounding the AOV. In some embodiments, the central server **130** can provide information to the AOV **110**, such as an instruction to perform an operation or function (e.g., pile driving operation on a set of locations), a navigation instruction (such as a route), synced obstacle data, and the like. In some embodiments, the central server **130** can enable a remote operator to assume manual control of the AOV **110** and provide manual navigation or operation instructions to the AOV. In some embodiments, some of the functionality of the AOV **110** described below in connection with, e.g., FIGS. 3A-3B may be subsumed by the central server **130**. For example, sensor data from the AOV **110** may be transmitted to the central server **130**, and the central server **130** may subsume the functionality corresponding to one or more of the obstacle map creation operation, the quality control operation, and the like.

(39) The central server **130** may include an interface engine **135** configured to generate one or more interfaces for viewing by a user (such as a user of the central server **130** or a user of the client device **140**). The user can be a remote operator of the AOV **110**, can be an individual associated with the environment **100** (such as a supervisor, a consultant, etc.), can be an individual associated with the AOV **110** (such as an operator, a repairman, an on-site coordinator, or the like), or can be any other suitable individual. The interface engine **135** can be used by a user to provide one or more instructions to an AOV **110**, such as autonomous navigation instructions, operation or function instructions, remote piloting instructions, and the like. The interface engine **135** can generate a user interface displaying information associated with the AOV **110**, other vehicles, or the environment **100**. For instance, the user interface can include a map illustrating a location and/or movement of each of the AOVs **110** within the geographic area, a path plan generated for each AOV **110**, a respective set of locations where piles will be driven by each AOV **110**, a current status of the AOV **110**, a remaining number and type of piles available to each AOV **110**, any notifications or other data received from each AOV **110**, and the like. The user interface can display notifications generated by and/or received from the AOV **110**, for instance, within a notification feed, as pop-up windows, using icons within the map interface, and the like. By communicatively coupling to multiple AOVs **110**, the central server **130** beneficially enables one user to track, monitor, and/or control multiple AOVs simultaneously.

(40) The client device **140** is a computing device, such as a computer, a laptop, a mobile phone, a tablet computer, or any other suitable device configured to receive information from or provide information to the central server **130**. The client device **140** includes a display configured to receive information from the interface engine **135**, that may include information representative of one or more of the AOVs **110** or the environment **100**. The client device **140** can also generate notifications (e.g., based on notifications generated by an AOV **110**) for display to a user. The client device **140** can include input mechanisms (such as a keypad, a touch-screen monitor, and the like), enabling a user of the client device to provide instructions to a selected one of the AOVs **110** (via the central server **130**). It should be noted that although the client device **140** is described herein as coupled to an AOV **110** via the central server **130**, in practice, the client device **140** may

communicatively couple directly to the AOV (enabling a user to receive information from or provide instructions to the AOV **110** without going through the central server **130**).

(41) As noted above, the systems or components of FIG. **1** are configured to communicate via a network **160**, which may include any combination of local area and/or wide area networks, using both wired and/or wireless communication systems. In one embodiment, the network **160** uses standard communications technologies and/or protocols. For example, the network **160** includes communication links using technologies such as Ethernet, 802.11, worldwide interoperability for microwave access (WiMAX), 3G, 4G, code division multiple access (CDMA), digital subscriber line (DSL), etc. Examples of networking protocols used for communicating via the network **160** include multiprotocol label switching (MPLS), transmission control protocol/Internet protocol (TCP/IP), hypertext transport protocol (HTTP), simple mail transfer protocol (SMTP), and file transfer protocol (FTP). Data exchanged over the network **160** may be represented using any suitable format, such as hypertext markup language (HTML) or extensible markup language (XML). In some embodiments, all or some of the communication links of the network **160** may be encrypted using any suitable technique or techniques.

Example Autonomous Off-Road Vehicle Designs

(42) FIGS. **2A-2B** show perspective views of exemplary designs of the AOV **110** of FIG. **1**, in accordance with some embodiments. More specifically, FIG. **2A** illustrates an exemplary design of a pile driving AOV **200A**, and FIG. **2B** illustrates another exemplary design of a pile driving AOV **200B**. Both pile driving AOVs **200A-B** shown in FIGS. **2A-2B** are capable of performing at least the autonomous pile loading operation and the autonomous pile driving operation. The exemplary designs of the pile driving AOVs **200A-B** shown in FIGS. **2A-2B** are for ease of illustration and explanation only and not intended to be limiting. Any suitable design for the AOV **110** is encompassed within the scope of this disclosure so long as the design can perform one or more of the functions or operations described herein.

(43) The pile driving AOV **200A** of FIG. **2A** illustrates an excavator-based design for an autonomous pile driving apparatus. As shown in FIG. **2A**, the pile driving AOV **200A** may include a chassis **205A** including a base frame **206A** upon which all other components are physically mounted. A carriage **207A** mounted to the base frame **206A** may include supporting members **208A** on which one or more baskets **210** (e.g., pile set holders, cartridges, and the like) may be removably loaded. The embodiment shown in FIG. **2A** shows the carriage **207A** as being supported by wheels (not labeled in FIG. **2A**). In other embodiments, the carriage **207A** may be mounted to the AOV **200A** without any wheels. Each basket **210** is adapted to hold a plurality of piles **215** that are driven by the pile driving AOV **200A** into the ground using a driving tool **220A**. More specifically, during the autonomous pile loading operation, the pile driving AOV **200A** may actuate (e.g., using hydraulics, pneumatics, electric motors, etc.) articulated arm **225A** of the driving tool **220A** to adjust position and orientation of the driving tool **220A** to load a pile **215** from a basket **210** onto the driving tool **220A**, and lift and position the pile **215** loaded onto the driving tool **220A** at a predetermined location above the ground where the pile is to be driven. After driving the pile **215** at the location, the pile driving AOV **200A** may autonomously navigate to a next location dictated by a pile plan map and repeat the autonomous pile loading operation and the autonomous pile driving operation for a next pile **215** from the (same or different) basket **210**.

(44) The pile driving AOV **200A** may also include a drive system **230A** to impart mobility to the AOV **220A** through a worksite. Although not specifically labeled in FIG. **2A**, the pile driving AOV **200A** may also include a power source that powers the drive system **230A**, as well as components mounted on the AOV **200A** such as the articulated arm **225A**, and the driving tool **220A**. The power source can be a rechargeable power source (e.g., a set of rechargeable batteries), an energy harvesting power source (e.g., a solar system), a fuel consuming power source (e.g., a set of fuel cells or an internal combustion system), or any other suitable power source. In many pile driving AOVs, the power source powers the drive system **230A** and the driving tool **220A** commonly

through a single hydraulic system, however other means of actuation may also be used. A common property of hydraulic systems used within pile driving AOVs is that the hydraulic capacity of the vehicle is shared between the drive system **230A** and the driving tool **220A**. In some embodiments, the instructions and control logic for the pile driving AOV **200A** to operate autonomously and semi-autonomously includes instructions relating to determinations about how and under what circumstances to allocate the hydraulic capacity of the hydraulic system.

(45) The pile driving AOV **200A** may also include a sensor assembly **250A**. For example, the sensor assembly **250A** can include cameras (e.g., camera array) that capture image data, a location sensor (e.g., GPS receiver, Bluetooth sensor), a LIDAR system, a RADAR system, depth sensors, proximity detectors, or any other component. The sensor assembly **250A** may thus be configured to detect one or more of image data, location data (e.g., geolocation data) indicating a location of the AOV **200A** (or a location where a pile is being driven into the ground by the driving tool **220A**) on a map corresponding to the geographic area, a presence of objects or things within a proximity of the AOV **200A**, dimensions of any detected objects or things, and the like. Although not shown in FIG. 2A, the sensors of the sensor assembly **250A** can be mounted on an external surface or appendage of the AOV **200A**, can be located within the AOV **200A**, can be coupled to an object or surface external to the AOV **200A**, or can be mounted to a different vehicle. In some configurations, the AOV **220A** may additionally include a communication apparatus, which functions to communicate (e.g., send and/or receive) data between the AOV **200A** and a set of remote devices (e.g., central server **130** of FIG. 1). The communication apparatus can be a Wi-Fi communication system, a cellular communication system, a short-range communication system (e.g., Bluetooth, NFC, etc.), or any other suitable communication system.

(46) The pile driving AOV **200B** of FIG. 2B illustrates a custom-built design for an autonomous pile driving apparatus. As shown in FIG. 2B, the pile driving AOV **200B** may include a chassis **205B** including a base frame upon which all other components are physically mounted. Instead of including a carriage for loading baskets of piles **215**, the system of the pile driving AOV **200B** may utilize a separate pile distribution AOV (not shown) that carries the piles (or baskets of piles) **215**. The pile driving AOV **200B** may load a pile **215** from the separate pile distribution AOV by operating a pile loading mechanism **225B-1** and drive the pile **215** into the ground by operating a pile driving mechanism **225B-2**. For example, during pile driving the separate pile distribution AOV may be parked adjacent the pile driving AOV **200B**. The pile driving AOV **200B** may perform the autonomous pile loading operation by actuating (e.g., using hydraulics, pneumatics, electric motors, etc.) the pile loading mechanism **225B-1** to adjust position and orientation of a loading tool to load a pile **215** from the separate pile distribution AOV onto the pile driving mechanism **225B-2**. The pile driving AOV **200B** may then perform the autonomous pile driving operation by actuating (e.g., using hydraulics, pneumatics, electric motors, etc.) the pile driving mechanism **225B-2** to adjust position and orientation of a driving tool **220B** of the pile driving mechanism **225B-2** to drive the loaded pile **215** into the ground at a predetermined location where the pile is to be driven. After driving the pile **215** at the location, the pile driving AOV **200B** may autonomously navigate to a next location dictated by the pile plan map and repeat the autonomous pile loading operation and the autonomous pile driving operation for a next pile **215** from the separate pile distribution AOV. Similar to the pile driving AOV **200A**, the pile driving AOV **200B** may also include a drive system, a power source, a sensor assembly, a communication apparatus, and the like. These components are not shown in FIG. 2B, and their detailed description is omitted here for simplicity.

Example Pile Driving AOV Configuration

(47) FIG. 3A is a block diagram of the AOV **110** of FIG. 1, in accordance with some embodiments. As shown in FIG. 3A, the AOV **110** includes a sensor array **310**, a component array **320**, and a control system **330**, each communicatively coupled via a network **350**. It should be noted that in other embodiments, the AOV **110** may include different, fewer, or additional components than

those illustrated in FIG. 3.

(48) The sensor array **310** includes a combination of one or more of: measurement sensors **312**, spatial sensors **314**, imaging sensors **316**, and position sensors **318**. The sensor array **310** is configured to collect data related to the AOV **110** and environmental data surrounding the AOV **110**. The control system **330** is configured to receive the data from the AOV **110** and carry out instructions based on the received data to perform various autonomous operations (e.g., path planning operation, navigation operation, pile basket assembly operation, pile basket loading operation, pile basket distribution operation, pile distribution operation, pile loading operation, pile driving operation, obstacle map creation operation, quality control operation, pile removal operation, etc.). Each sensor is either removably mounted to the AOV **110** without impeding the operation of the AOV **110** or is an integrated component that is a native part of the AOV **110** as made available by its manufacturer. Each sensor transmits the data in real-time or as soon as a network connection is achieved, automatically without input from the AOV **110** or a human operator. Data recorded by the sensor array **310** is used by the control system **330** and/or the central server **130** of FIG. 1 to perform the various autonomous operations.

(49) Measurement sensors **312** generally measure properties of the ambient environment, or properties of the AOV **110** itself. These properties may include tool position/orientation, relative articulation of the various joints of the arm supporting the tool, vehicle speed, ambient temperature, hydraulic pressure (either relative to capacity or absolute) including how much hydraulic capacity is being used by the drive system and the driving tool separately. A variety of possible measurement sensors **312** may be used, including hydraulic pressure sensors, linear encoders, radial encoders, inertial measurement unit sensors, incline sensors, accelerometers, strain gauges, gyroscopes, and string encoders.

(50) The spatial sensors **314** output a three-dimensional map in the form of a three-dimensional point cloud representing distances, for example between one meter and fifty meters between the spatial sensors **314** and the ground surface or any objects within the field of view of the spatial sensor **314**, in some cases per rotation of the spatial sensor **314**. In one embodiment, spatial sensors **314** include a set of light emitters (e.g., Infrared (IR)) configured to project structured light into a field near the AOV **110**, a set of detectors (e.g., IR cameras), and a processor configured to transform data received by the infrared detectors into a point cloud representation of the three-dimensional volume captured by the detectors as measured by structured light reflected by the environment. In one embodiment, the spatial sensor **314** is a LIDAR sensor having a scan cycle that sweeps through an angular range capturing some or all of the volume of space surrounding the AOV **110**. Other types of spatial sensors **314** may be used, including time-of-flight sensors, ultrasonic sensors, and radar sensors.

(51) Imaging sensors **316** capture still or moving-video representations of the ground surface, objects, and environment surrounding the AOV **110**. Example imaging sensors **316** include, but are not limited to, stereo RGB cameras, structure from motion cameras, and monocular RGB cameras. In one embodiment, each camera can output a video feed containing a sequence of digital photographic images at a rate of 20 Hz. In one embodiment, multiple imaging sensors **316** are mounted such that each imaging sensor captures some portion of the entire 360-degree angular range around the vehicle. For example, front, rear, left lateral, and right lateral imaging sensors may be mounted to capture the entire angular range around the AOV **110**.

(52) The position sensors **318** provide a position of the AOV **110**. This may be a localized position within a geographic area, or a global position with respect to latitude/longitude, or some other external reference system. In one embodiment, a position sensor is a global positioning system interfacing with a static local ground-based GPS node mounted to the AOV **110** to output a position of the AOV **110**.

(53) There are a number of different ways for the sensor array **310** generally and the individual sensors specifically to be constructed and/or mounted to the AOV **110**. This will also depend in part

on the design or construction of the AOV **110**. The number, location, type or mounting position of the sensors for the AOV **110** is not intended to be limiting, so long as the sensors can operate to enable the autonomous operations described.

(54) Generally, individual sensors as well as the sensor array **310** itself range in complexity from simplistic measurement devices that output analog or electrical systems electrically coupled to a network bus or other communicative network, to more complicated devices which include their own onboard computer processors, memory, and the communications adapters. Regardless of construction, the sensors and/or sensor array together function to record, store, and report information to the control system **330**. Any given sensor may record, or the sensor array may append to recorded data time stamps for when data was recorded.

(55) The sensor array **310** may include its own network adapter (not shown) that communicates with the control system **330** either through either a wired or wireless connection. For wireless connections, the network adapter may be a Bluetooth Low Energy (BTLE) wireless transmitter, infrared, or **802.11** based connection. For wired connection, a wide variety of communications standards and related architecture may be used, including Ethernet, a Controller Area Network (CAN) Bus, or similar. In the case of a BTLE connection, after the sensor array **310** and the control system **330** have been paired with each other using a BLTE passkey, the sensor array **310** automatically synchronizes and communicates sensor data to the control system **330**. If the sensor array **310** has not been paired with the control system **330** prior to operation, the information is stored locally until such a pairing occurs. Upon pairing, the sensor array **310** communicates any stored data to the control system **330**.

(56) The component array **320** includes one or more components **322**. The components **322** are elements of the AOV **110** that can perform different actions. Non-limiting examples of the components **322** include the articulated arm **225A**, the pile loading mechanism **225B-1**, the pile driving mechanism **225B-2**, the driving tools **220**, the drive system **230A**, as shown in FIGS. **2A-2B**. Other examples of components **322** may include components for performing one or more of the various autonomous operations (e.g., path planning operation, navigation operation, pile basket assembly operation, pile basket loading operation, pile basket distribution operation, pile distribution operation, pile loading operation, pile driving operation, obstacle map creation operation, quality control operation, pile removal operation). As illustrated in FIG. **3**, each component has one or more input controllers **324** and one or more component sensors **326**, but a component may include only sensors or only input controllers. An input controller controls the function of the component. For example, an input controller may receive machine commands via the network and actuate the component in response. A component sensor **326** generates measurements within the system environment. The measurements may be of the component, the AOV **110**, or the environment surrounding the AOV **110**. For example, a component sensor **326** may measure a configuration or state of the component **322** (e.g., a setting, parameter, power load, etc.), or measure an area surrounding the AOV (e.g., moisture, temperature, etc.).

(57) The control system **330** receives information from the sensor array **310** and the component array **320**, and performs operations based on an input pile plan map. For example, the control system **330** controls one or more of the components **322** based on the pile plan map to autonomously assemble an ordered set of piles that may include piles of different types into a basket of piles and load the basket of piles onto a vehicle for distribution and/or driving into the ground. As another example, the control system **330** controls one or more of the components **322** based on the pile plan map to autonomously perform the pile loading operation and the pile driving operation at a first location, and autonomously navigate to a next location based on the pile plan map to autonomously perform the pile loading operation and the pile driving operation at the next location, and so on. As another example, the control system **330** controls one or more of the components **322** based on an obstacle map to autonomously navigate to a desired location or perform AOV tool path planning (e.g., movement of articulated arm to load a pile into the driving

tool) based on the pile plan map and while avoiding obstacles. Operation and functionality of the control system **330** is described in greater detail in FIG. **3B**.

(58) The network **350** connects nodes of the AOV **110** to allow microcontrollers and devices to communicate with each other. In some embodiments, the components are connected within the network as a Controller Area Network (CAN). In this case, within the network each element has an input and output connection, and the network **350** can translate information between the various elements. For example, the network **350** receives input information from the sensor array **310** and the component array **320**, processes the information, and transmits the information to the control system **330**. The control system **330** generates instructions to execute different steps of the different autonomous operations based on the information and transmits the instructions to carry out the steps of the autonomous operations to the appropriate component(s) **322** of the component array **320**. In other embodiments, the components may be connected in other types of network environments and include other networks, or a combination of network environments with several networks. For example, the components may be connected in a network such as the Internet, a LAN, a MAN, a WAN, a mobile wired or wireless network, a private network, a virtual private network, a direct communication line, and the like.

(59) FIG. **3B** is a block diagram of the control system **330** of FIG. **3A**, in accordance with some embodiments. Referring to FIG. **3B**, the control system **330** includes a datastore **332**, an interface module **342**, a path planning module **350**, a basket assembly module **355**, a navigation module **360**, a pile loading module **365**, a tracking module **367**, a pile driving module **370**, a quality control module **380**, and an obstacle mapping module **390**. The datastore **332** may store different types of data utilized, generated, or received by the control system **330** for performing the different autonomous operations related to pile driving. For example, the datastore **332** may store pile plan data **334**, pile type data **335**, obstacle data **336**, sensor data **337**, and quality control condition data **340**. The pile loading module **365** may include a verification routine **366**. In different embodiments, the control system **330** may include fewer or additional components. The control system **330** may also include different components. Additionally, some of the data or functionality described in connection with the control system **330** may be subsumed by other components, such as the central server **130** of FIG. **1**.

(60) The interface module **342** is an interface for a user and/or a third-party software platform to interact with the control system **330**. The interface module **342** may be a web application that is run by a web browser on a user device or a software as a service platform that is accessible by a user device through a network (e.g., network **160** of FIG. **1**). In some embodiments, the interface module **342** may use application program interfaces (APIs) to communicate with user devices or third-party platform servers, which may include mechanisms such as webhooks.

Example Pile Plan Map

(61) The control system **330** may be configured to perform the various autonomous operations related to pile driving based on the pile plan data **334** stored in the datastore **332**. The pile plan data **334** may include data corresponding to the pile plan map. FIG. **4** illustrates an exemplary pile plan map **400**, in accordance with some embodiments. The pile plan map **400** may include map data corresponding to a geographic area **410** where autonomous pile driving operations are to be performed by one or more of the AOVs **110**. For example, the pile plan map **400** may be developed by a user (e.g., site engineer) using a software application for the geographic area **410** where a solar farm project is being developed and installed. The user may develop the pile plan map **400** based on, e.g., environmental conditions, ground conditions, customer requirements, budget, target installed solar power generation capacity, etc. As shown in FIG. **4**, the pile plan map **400** may specify a plurality of locations **420** in the geographic area **410** in which the piles are intended to be driven and located.

(62) For each location **420**, the pile plan data **334** of the pile plan map **400** may include data of one or more pile parameters. For example, the pile parameter data may specify the exact or

approximate geolocation (e.g., GPS location, latitude and longitude data) in the geographic area where the corresponding pile (or piles) is to be installed. As another example, the data may specify the type of pile to be installed at that location.

(63) As yet another example, the pile parameter data may specify an install pattern detailing the number and/or type of piles to be installed at a given location. For example, in hard ground conditions (e.g., rock surface) the install pattern may specify parameters of a pre-drilling step that is to be performed at the given location. The pre-drilling step may be performed by a separate specialized drilling AOV or may be performed manually. In embodiments where the pre-drilling is performed autonomously, the pile parameter data may specify the actuation parameters for the drilling AOV to perform the pre-drilling at the given location (e.g., location, depth/dimensions of hole to be drilled). In addition, the pile parameter data may specify the intended state of the pile at the given location after the installation. For example, the intended state may specify the orientation, the plumbness or verticality, the height of the pile, reveal height of the pile, and the like. As yet another example, the pile parameter data may specify one or more tolerance thresholds for one or more of the pile parameters. For example, the pile parameter data may specify a given target height of the pile and the corresponding tolerance threshold may specify a range within which the actual installed height of the pile should fall after the pile driving operation is complete (e.g., tolerance threshold of ± 0.2 inches of the minimum reveal height). As another example, the pile parameter data may specify a target verticality (e.g., 90 degrees) of the pile relative to a horizontal plane and the corresponding tolerance threshold may specify a range within which the actual plumbness of the pile should fall after the pile driving operation is complete (e.g., $\pm 10\%$ of the target plumbness).

(64) In FIG. 4, the different shapes (e.g., circle, square, triangle plus circle) may convey the different pile parameters for each location. For example, the pile parameter data for location **420A** of the pile plan map **400** of FIG. 4 may convey that both a pre-drilling step is to be performed and a pile of a first type (e.g., H-pile Type 1 having a particular length) is to be driven into the ground at the location **420A** (having, e.g., a first reveal height and a first plumbness). As another example, the pile parameter data for location **420B** may convey that a second type of pile (e.g., I-pile having a particular bolt hole pattern) is to be driven into the ground at that location **420B** (having, e.g., a second reveal height and a second plumbness). And as yet another example, the pile parameter data for location **420C** may convey that a third type of pile is to be driven into the ground at location **420C** (having, e.g., a third reveal height and a third plumbness).

Example Path Planning

(65) The pile plan data **334** corresponding to the pile plan map **400** may be accessed by the control system **330** to perform various operations. For example, based on the pile plan data **334**, the path planning module **350** of FIG. 3B may perform a path planning operation of setting a path plan for one or more AOVs to drive a plurality of piles at respective locations **420** and consistent with the corresponding pile parameter data. The path planning operation may entail determining and setting one or more path plans for one or more AOVs **110** to cover the entire area defined by, e.g., the geographic area **410** of FIG. 4, to drive piles at each respective locations **420** while optimizing for various factors (e.g., cost, efficiency, time, etc.). Based on the set path plan, a given AOV **110** may traverse the entire geographic area **410** or a portion thereof to perform various operations related to pile driving (e.g., autonomous pile loading operation, autonomous pile driving operation, quality control operation, obstacle map creation operation). For example, the path plan may be executed by one or more AOVs **110** by autonomously navigating over one or more linear columns and stopping at each location **420** in each column to autonomously drive piles, so as to cover the entire geographic area **410** while minimizing at least one of a total drive time, a total number of turns, and the like.

Example Basket Assembly Operations

(66) One of the autonomous operations that may be performed by the control system **330** by accessing the pile plan data **334** corresponding to the pile plan map **400** may be a basket assembly

operation. For example, the basket assembly module **355** may take the pile plan data **334** as input and generate instructions prescribing a breakdown of basket quantity and composition for each basket. Configuration and functionality of the basket assembly module **355** is described below in connection with FIG. 5.

(67) As shown in FIG. 5, the basket assembly module **355** may include a location set identification module **505**, a weight estimation module **506**, an order setting module **510**, an instruction generation module **520**, a basket assembly unit **522**, and a verification unit **525**. In different embodiments, the basket assembly module **355** of FIG. 5 may include fewer or additional components. The basket assembly module **355** may also include different components.

(68) The location set identification module **505** may take the pile plan data **334** as input and identify, on a per-basket-basis, a set of locations (e.g., locations A-F of column **11** of FIG. 4) from among the plurality of locations (e.g., all locations **420** in FIG. 4 within geographic area **410**) of the pile plan map, and further identify the pile parameter data corresponding to the piles (e.g., pile type data) to be respectively driven into the ground at each of the identified set of locations.

(69) For example, the location set identification module **505** may access the path plan for the AOV **110** generated by the path planning module **350** and/or the pile plan data **334** and determine a number of baskets of piles required to complete the pile driving operations per the pile driving order dictated by the path plan for the AOV **110**. The number of baskets may be determined based on, e.g., information regarding a maximum number of piles that can be held in each basket. Further, for each of the prescribed number of baskets, the location set identification module **505** may identify the set of locations whose piles will be loaded or stored in that basket. In determining for each basket, the set of locations whose piles will be loaded in the basket, the location set identification module **505** may utilize weight estimates generated by the weight estimation module **506**. For a given basket, based on the corresponding set of locations determined by the location set identification module **505**, the number of piles to be loaded into the basket may be less than a maximum number of piles that the basket can hold, e.g., based on the total basket weight, or based on the remaining number of pile driving locations.

(70) For each prescribed basket, the weight estimation module **506** may be configured to estimate a total weight of the basket based on the set of locations and corresponding pile parameters included in the pile plan data **334**. For example, the datastore **332** of FIG. 3B may include pile type data **335** that includes information regarding each type of pile. For example, the information may include dimensions of the type of pile, weight of the type of pile, and the like. Based on the pile type data **335** and based on the identified set of locations for the basket, the weight estimation module **506** may estimate the weight of the basket. Further, based on the estimated weight, the location set identification module **505** may determine whether any modifications should be made to the identified set of locations corresponding to the basket. For example, the location set identification module **505** may determine whether the estimated weight is higher than a threshold and/or determine whether a weight distribution between the piles (that may have different weights and/or dimensions) that are to be loaded within the same basket in a particular order is within a threshold tolerance. Based on the determination, the location set identification module **505** may modify/adjust the set of locations associated with the basket. For example, the location set identification module **505** may reduce the number of locations associated with the basket to reduce the total weight of the basket and/or to adjust the weight distribution of the piles assigned to the same basket.

(71) Further, based on the estimated total weights of each of the prescribed number of baskets, the location set identification module **505** may also perform similar determination regarding whether a weight distribution between multiple baskets (which may all be loaded onto a same pile distribution vehicle or pile driving AOV) is within a threshold tolerance. Based on this determination, the location set identification module **505** may also similarly modify the set of locations (and corresponding assembled piles) associated with one or more of the prescribed

baskets.

(72) After the set of locations for a given basket has been identified by the location set identification module **505**, the order setting module **510** may identify the pile driving order of the piles corresponding to the set of locations per the pile plan data **334**. For example, in case of the set of locations being the locations A-F of column **11** of FIG. **4**, the order setting module **510** may identify the type of pile to be driven at each of the locations A-F, and further determine the order in which (e.g., based on the path plan) the pile driving operation is to be performed for the set of locations (e.g., A, then B, then C, . . . , then F).

(73) The instruction generation module **520** may generate basket assembly (e.g., kitting) instructions for each prescribed basket based on the pile type and pile order identified by the order setting module **510**. The basket assembly instructions may be for assembling or kitting a set of piles into a basket based on the pile type and the pile order identified by the order setting module **510**. Continuing with the above example of locations A-F of column **11** of FIG. **4**, since the piles are to be driven in the order of A, B, C, . . . , F, the basket assembly instructions generated by the instruction generation module **520** may dictate basket assembly in, e.g., a reverse order (i.e., F, E, . . . A) such that the piles of the corresponding pile types become accessible during pile driving operations in the order of A, B, C, . . . , F. For example, if the basket stores the piles as a stack of piles, the assembly is performed such that the top pile in the stack is of a pile type that is to be driven at location A, the second from the top pile in the stack is of a pile type that is to be driven at location B, and so on.

(74) The basket assembly unit **522** may be configured to assemble an ordered set of piles into a basket based on the basket assembly instructions generated by the instruction generation module **520**. For example, the basket assembly unit **522** may be configured to transmit the basket assembly instructions to a third-party vendor for manual assembly of baskets of piles based on the corresponding pile driving order and pile types specified by the corresponding basket assembly instructions for each basket. The third-party vendor may receive the instructions and assemble the piles of the different types in the specified order into the prescribed baskets and deliver the assembled baskets ready for use for autonomous pile driving per the pile plan map.

(75) As another example, the basket assembly unit **522** may control an autonomous basket assembly robot or AOV that is adapted to accept the basket assembly instructions as input and autonomously navigate or operate in a pile storage area where piles of different types are stored in respective silos, bins, or sections and assemble an ordered set of piles having respective pile types into the baskets based on the basket assembly instructions. The pile basket assembly operation may thus be performed fully autonomously based on an input pile plan map.

(76) The verification unit **525** may be configured to perform a verification operation of verifying that an access order of the set of piles in the assembled basket assembled under control of the basket assembly unit **522** matches the order for driving the set of piles into the ground as identified by the order setting module **510**. In some embodiments, the verification unit **525** may utilize one or more sensors (e.g., of sensor array **310** of the AOV **110**) to obtain sensor data (e.g., image data) of the basket of piles assembled under control of the basket assembly unit **522**, to perform the verification operation. In other embodiments, the verification unit **525** may operate in a semi-autonomous mode where the unit takes human input in order to complete the verification process.

(77) For example, piles may be color-coded based on pile type, and by obtaining image data of the color-coded piles assembled as an ordered set of piles in the basket, the verification unit **525** may apply known image processing techniques to determine the access order of piles of different pile types in the assembled basket and determine whether or not a comparison of the access order determined by the verification unit **525** and the pile driving order identified by the order setting module **510** reveals a match. The verification unit **525** may perform predetermined actions based on the comparison. For example, in response to detecting a mismatch between the access order and the pile driving order, the verification unit **525** may flag the basket for re-assembly, notify an

operator for manual intervention, and the like.

Example Autonomous Operations Related to Pile Driving

(78) Returning to FIG. 3B, other autonomous operations that may be performed by the control system **330** based on the pile plan data **334** may include operations related to pile driving such as the navigation operation, the pile basket loading operation, the pile distribution operation, the pile loading operation, and the pile driving operation.

(79) In some embodiments, the navigation module **360** may take the path plan generated by the path planning module **350** as input and perform the autonomous navigation operation. The autonomous navigation operation may entail the AOV **110** (e.g., pile driving AOV, pile loading AOV, pile distribution AOV, etc.) autonomously navigating within the geographic area from one location to another. For instance, the navigation module **360** can, in response to identifying a task or function to be performed by the AOV **110** (e.g., drive a pile into the ground), identify a location associated with the identified task or function (e.g., based on the pile plan data **334**), and can select a route from a current location of the AOV **110** to the identified location, and autonomously navigate along the selected route in the geographic area.

(80) For example, based on the order in which the piles are to be driven into the ground by a given AOV **110** (as dictated by the path plan), the navigation module **360** may select a first location that corresponds to a next location based on the path plan and controls one or more components of the AOV **110** (e.g., components **322**) to autonomously navigate the AOV **110** from its current location to the first location. After completion of pile driving operations at the first location, the navigation module **360** may select a second location that corresponds to a next location based on the path plan and controls one or more components of the AOV **110** (e.g., components **322**) to autonomously navigate the AOV **110** from its current location to the second location, and so on. The route selection by the autonomous navigation module **360** may be so that obstacles detected (e.g., in real-time) by the AOV **110** using sensor data from sensors (e.g., of the sensor array **310**) and/or based on the obstacle data **336** including an obstacle map generated (and updated in real-time) by the obstacle mapping module **380**, are avoided.

(81) The pile loading module **365** may be configured to control one or more components (e.g., components **322**) of an AOV **110** to autonomously load a pile onto a driving tool of an AOV **110**. In some embodiments, the AOV **110** that loads the pile onto the driving tool and the AOV **110** that actuates the driving tool to drive the pile into the ground may be the same. In other embodiments, the AOV **110** that loads the pile onto the driving tool and the AOV **110** that actuates the driving tool to drive the pile into the ground may be separate autonomous AOVs **110**.

(82) In some embodiments, as explained previously in connection with the basket assembly operation, piles having pile types corresponding to the driving order per the path plan may be assembled as an ordered set into a basket of piles. Further, the AOV **110** may be loaded with multiple baskets of the ordered sets of piles. In this case, the pile loading module **365** may be configured to automatically identify one of the baskets of piles as corresponding to the current location and further automatically identify a position of one of the piles (e.g., the pile on the top of the stack of piles in the identified basket) in the identified basket as the pile having the correct pile type for the current location. The pile loading module **365** may then autonomously actuate one or more components of the AOV **110** to pick up the identified pile from the identified basket and load the pile onto a driving tool of the AOV.

(83) Continuing with the above example, at the first location that corresponds to the next location based on the path plan, the pile loading module **365** autonomously actuates one or more components of the AOV to load the identified pile from the identified basket of piles (e.g., top pile in the identified basket storing the ordered set of piles). After completion of pile driving operations at the first location and autonomous navigation of the AOV to the second location, the pile loading module **365** may autonomously actuate one or more components of the AOV to load a next identified pile from the identified basket of piles that corresponds to the second location, and so on.

(84) In some embodiments, the pile loading module **365** may also include a verification routine **366** to confirm accuracy of the pile being picked up and loaded onto the driving tool for driving. For example, piles may be color-coded or may be associated with a unique code (e.g., scannable QR code, RFID tag, bar-code, etc.) based on pile type, and by obtaining image data or other sensor data of the pile before or after it is picked up for loading and applying known techniques (and based on the pile type data **335** and the pile plan data **334**), the verification routine **366** may verify whether the picked-up pile has a pile type that matches that pile type for the current pile driving location. The verification routine **366** may perform predetermined actions based on the verification. For example, in case of a mismatch, the pile loading module **365** may stop the pile loading operation and notify an operator.

(85) In some embodiments, instead of performing the basket assembly operation, piles of different types may be arranged in respective baskets or otherwise arranged on a pile distribution AOV (or on a carriage of a pile driving AOV) such that a pile of each type remains always accessible to the components actuatable by the pile loading module **365** for pick up and loading. In this case, the pile loading module **365** may be configured to take as input the pile plan data **334**, determine the pile type for the current location, and autonomously actuate one or more components of the AOV to pick up and load a pile onto the driving tool from one of the respective baskets, bins, or regions based on the pile type for the current location. At the next location where the AOV is autonomously navigated to, the pile loading module **365** may again repeat the operations to determine the pile type for the next location based on the pile plan data **334** and autonomously actuate one or more components of the AOV to pick up and load the pile of the determined pile type for a corresponding one of the baskets or regions.

(86) The control system **330** may further include a tracking module **367** to track for each pile type, a number of remaining piles of the type on the carriage of the pile driving AOV or other vehicle acting as the pile distribution AOV. Based on the tracking data from the tracking module **367**, the navigation module **360** may control to modify the autonomous navigation operation. For example, when selecting, based on the path plan, the next location for autonomous navigation, pile loading, and pile driving, the navigation module **360** may utilize the pile tracking data from the tracking module **367** to determine whether a pile of the type needed for driving at the next location is available to the AOV **110**. If the pile of the type is available, the navigation module **360** may actuate the one or more components to navigate to the next location as described previously. If, on the other hand, the pile of the type is determined not to be available, the navigation module **360** may skip the next location per the path plan and select a subsequent location per the path plan and repeat the determination process to determine whether a pile of the type needed for driving at the subsequent location is available. The navigation module **360** may repeat the process until the remaining piles available to the AOV are all driven into the ground at appropriate locations, while skipping locations for which appropriate piles are not available currently to the AOV. And in this case, the navigation module **360** may also update one or more of the pile plan data **334** or the path plan to track the skipped locations where pile driving remains outstanding.

(87) In some embodiments, piles of the correct pile type may be pre-distributed at the respective locations by a pile distribution AOV conducting a pile distribution operation. For example, a pile (of the correct type) may be pre-placed on the ground at or proximal to a location where the pile is to be driven, and the pile loading module **365** may autonomously actuate one or more components to pick up the pile from the ground at the location and load the pile onto the driving tool of the AOV for driving.

(88) The pile driving module **370** may be configured to control one or more components of an AOV **110** (e.g., components **322**) to autonomously drive the pile loaded by the pile loading module **365** into the ground at the location selected by the navigation module **360**. Continuing with the above example, at the first location that corresponds to the next location based on the path plan, the pile driving module **370** autonomously actuates one or more components of the AOV to drive the

loaded pile into the ground at the first location selected by the navigation module **360**. After completion of pile driving operation at the first location and autonomous navigation of the AOV to the second location, the pile driving module **370** may autonomously actuate one or more components of the AOV to drive the next pile loaded by the pile loading module **365** into the ground at the second location selected by the navigation module **360**, and so on. During the pile driving operation, the pile driving module **370** may continuously monitor the (co-occurring) sensor data **337** from one or more sensors (e.g., sensors of sensor array **310**, component sensors **326**, and the like) to determine when the pile driving operation is completed. For example, the pile parameters may dictate a predetermined reveal height (e.g., how high the pile protrudes from the surface of the ground) for the pile, and the pile driving module **370**, while driving the pile into the ground, may monitor the time-series sensor data to continuously measure the reveal height, and stop the pile driving operation when the reveal height reaches the intended reveal height per the pile parameters. The basket loading operation, autonomous navigation operation, the pile loading operation, and the pile driving operation are depicted and described in further detail below in connection with FIGS. **6A-6C**.

(89) FIG. **6A** depicts a basket loading operation for the pile driving AOV **200A** of FIG. **2A**, in accordance with some embodiments. In FIG. **6A**, AOV **610** may be a basket loading AOV that is adapted to load assembled baskets **210** onto the pile driving AOV **200A**. As explained previously, the basket **210** may house an ordered set of piles based on the path plan or the driving order of piles into the ground at respective locations of the pile plan map. In other embodiments, the basket **210** may house piles of a same type or a subset of types, and multiple baskets **210** of respective pile types or pile type subsets may be mounted to the carriage **207A** such a pile of each type remains always accessible to the driving tool of the pile driving AOV **200A**. Once the basket of piles has been assembled, the basket **210** may be loaded onto the carriage **207A** of the pile driving AOV **200A**. In some embodiments, the pile driving AOV **200A** may be configured to autonomously navigate to a known reload point (e.g., a predetermined location or zone) where the basket loading operation may be performed autonomously. For example, the basket loading AOV **610** may be configured to operate in the predetermined reload zone and when the pile driving AOV **200A** navigates to the reload zone, the basket loading AOV **610** may perform autonomous basket loading operation of loading one or more assembled basket of piles **210** onto the carriage **207A** of the AOV **200A** by placing the basket **210** onto the carriage **207A** as shown in FIG. **6A**. In the embodiment shown in FIG. **6A**, the carriage **207A** is adapted to be mounted with a plurality of baskets **210** on both sides of the main body of the pile driving AOV **200A**.

(90) FIG. **6B** depicts an autonomous pile loading operation for the pile driving AOV **200A** of FIG. **2A**, in accordance with some embodiments. In FIG. **6B**, two baskets **610A-B** of piles are shown as being loaded onto the carriage **207A** of the pile driving AOV **200A**. FIG. **6B** depicts a state where the AOV **200A** has been autonomously navigated by the navigation module **360** to a selected first location (based on the pile plan and the path plan) for pile driving. Further,

(91) FIG. **6B** depicts a state where the pile **615A** has a type (e.g., attributes like length, bolt hole pattern, design or shape, etc.) that accords with the pile parameters for the first location per the pile plan data **334**. Further, based on data associated with the basket assembly operation and the basket loading operation, the pile loading module **365** “knows” where each pile for each driving location is positioned in the basket **610A**, and “knows” where the basket **610A** is positioned on the carriage **207A**. Thus, based on data associated with the basket assembly operation and the basket loading operation, the pile loading module **365** can determine the exact position of the pile **615A** in the basket **610A** and on the carriage **207A**. Based on the known (and/or verified by routine **366**) position of the pile **615A**, the pile loading module **365** may actuate one or more components of the articulated arm **225A** and the drive tool **220A** of the AOV **200A** to pick up the pile **615A** from the basket **610A** and load the pile **615A** onto the drive tool **220A** of the AOV **200A** during the pile loading operation. The pile loading module **365** may further actuate the one or more components to

position the pile **615A** at or above the first location for pile driving.

(92) After completion of the pile driving at the first location and after autonomous navigation of the AOV **200A** by the navigation module **360** to a next or second location (based on the pile plan and the path plan), the pile loading module **365** may repeat the above-described pile loading operation. For example, based on data associated with the basket assembly operation and the basket loading operation, the pile loading module **365** can determine the exact position of a pile **615B** (that has a type that accords with the pile parameters for the second location per the pile plan data **334**) in the basket **610A** (or another location on or off the carriage **207A**). Based on the known position of the pile **615B**, the pile loading module **365** may actuate one or more components of the articulated arm **225A** and the drive tool **220A** of the AOV **200A** to pick up the pile **615B** from the basket **610A** and load the pile **615B** onto the drive tool **220A** of the AOV **200A** during the pile loading operation. The pile loading module **365** may further actuate the one or more components to position the pile **615B** at or above the second location for pile driving.

(93) FIG. **6C** depicts an autonomous pile driving operation for the pile driving AOV **200A** of FIG. **2A**, in accordance with some embodiments. Continuing with the above example of loading the piles **615A** and **615B** at respective first and second locations, FIG. **6C** depicts a state where the first pile **615A** has already been driven (to its intended state) into the ground by the driving tool **220A** at the first location **650A**, and the pile driving module **370** is now actuating one or more components of the articulated arm **225A** and the driving tool **220A** to drive the pile **615B** into the ground at the second location **650B** selected by the navigation module **360**. It should be noted that the autonomous navigation operation by the navigation module **360** to autonomously navigate from the first location **650A** to the second location **650B** may simply involve (depending on distance between locations **650A** and **650B**) actuating one or more components of the articulated arm **225A** or to rotate the main body of the AOV **220A** without moving or driving the AOV **200A** by actuating components of the drive system **230A**.

(94) During the pile driving operation, the pile driving module **370** may take as input the pile parameters included in the pile plan data **334** for the location (e.g., location **650B**) to inform the pile driving operation for the pile **615B** at the location **650B**. For example, the driving tool **220A** may use, e.g., hydraulic, electric, or other action to raise a weight and then drop it on the upper end **616B** of the pile **615B** to drive the pile into the ground. Non-limiting examples of the driving tool **220A** may include a hydraulic hammer, a hydraulic press-in, a vibratory pile driver, and the like. Based on the one or more pile parameters, the pile driving module **370** may control (e.g., adjust or modify) the actuation parameters for one or more components of the driving tool **220A** to achieve the intended state for the pile **615B** after it has been driven into the ground. For example, the one or more parameters may specify the orientation of the pile **615B** to be a predetermined orientation so that a bolt pattern on the pile **615B** aligns with a component (e.g., solar panel) to be installed subsequently on top of the pile **615B**. As another example, the one or more parameters may specify the height of the top **616B** of the pile **615B** as measured from a reference point (e.g., sea level) to be a predetermined height after the pile **615B** has been driven into the ground. As yet another example, the one or more parameters may specify the plumbness of the pile **615B** to be a predetermined plumbness after install. Thus, during the pile driving operation, the pile driving module **370** may actuate one or more components of the AOV **200A** such that the driven pile **615B** has attributes that match the input specified parameters of the predetermined orientation, height, plumbness, etc., as dictated by the pile plan data **334**.

(95) In some embodiments, the pile driving module **370** may monitor sensor data from one or more sensors (e.g., sensors of sensor array **310**, component sensors **326**, and the like) at a predetermined frequency (e.g., periodically or aperiodically) to inform or adjust the actuation parameters of the components of the AOV **200A** during the operation to ensure the attributes (e.g., height, plumbness, orientation) of the pile **615B** during the driving operation maintain an intended state or progress toward the intended state per the pile plan or otherwise stay within respective tolerance thresholds

of the intended state.

Example Autonomous Quality Control Operation

(96) Returning to FIG. 3B, another autonomous operation that may be performed by the control system **330** based on the pile plan data **334** may include the quality control operation. For example, the quality control module **380** may take the pile plan data **334** as input and monitor the pile driving operation performed by the pile driving module **370** and monitor the corresponding (co-occurring) sensor data from one or more sensors (e.g., sensors of sensor array **310**, component sensors **326**, and the like) to perform the quality control operation. By performing the quality control operation, the quality control module **380** may ensure for each driven pile at each location that the attributes (e.g., (x,y,z) location, orientation, etc.) of the driven pile (based on the sensor data) accord with the pile parameters for the location (based on the pile plan map). Configuration and functionality of the quality control module **380** is described below in connection with FIGS. 7 and 8.

(97) As shown in FIG. 7, the quality control module **380** may include an attribute detection module **705**, a thresholding unit **709**, an action module **710**, a notification module **715**, a parameter adjustment module **720**, and a pile removal module **725**. The attribute detection module **705** may include a location detection module **706** and an orientation detection module **708**. In different embodiments, the quality control module **380** of FIG. 7 may include fewer or additional components. The quality control module **380** may also include different components.

(98) The attribute detection module **705** may be configured to detect one or more attributes (e.g., location, orientation, etc.) of the pile using one or more sensors during or after the pile driving operation. The one or more attributes of the pile may correspond to a (current, actual, or final) state of the pile during or after the pile driving operation. In some embodiments, the sensor data based on which the one or more attributes are detected may be time-series data received by the attribute detection module **705** at a predetermined frequency (e.g., periodic or aperiodic) before, during, and/or after the pile driving operation.

(99) The location detection module **706** may detect the (actual) location of the driven pile using the sensor data **337** during or after the pile driving operation. For example, the location detection module **706** may detect the (actual) horizontal and/or vertical location of the pile driven into the ground. The detected location may convey the xy location (e.g., geolocation, GPS location, latitude and longitude data, etc.) corresponding to the base of the pile where the pile makes contact with the ground; the xy and/or xyz location of the top of the pile in a point cloud model; the height (altitude) of the top of the pile relative to a reference point; a reveal height of the pile (e.g., how high the pile protrudes from the surface of the ground); the xy and/or xyz location of a feature (e.g., bolt hole, clamp, etc.) on the pile; and the like.

(100) The orientation detection module **708** may detect the (actual) orientation (e.g., plumbness, verticality, angle, positioning, bearing, etc.) of the driven pile using the sensor data **337** during or after the pile driving operation. For example, the orientation detection module **708** may detect the real-time plumbness or verticality of the pile being driven into the ground. As another example, the orientation detection module **708** may detect the real-time 3D orientation or bearing of the pile (or of one or more features on the pile) being driven into the ground.

(101) Other attributes that may be detected by the attribute detection module **705** based on the sensor data **337** may include pile refusal (e.g., pile not budging or driving further into the ground when threshold amount of force is applied to the top of the pile for a threshold time period or a requisite rate of driving movement is not achieved after a predetermined amount of time driving the pile with predetermined actuation parameters), a deformation (e.g., bend, etc.) of the pile, damage (e.g., crack or other manufacturing defect) to the pile, and the like.

(102) The thresholding unit **709** may utilize the pile parameter data corresponding to the current pile driving location and included in the pile plan data **334** to determine for one or more of the attributes detected by the attribute detection module **705**, whether the value of the attribute is

within a corresponding tolerance range. For example, for each of one or more pile parameters, the pile plan data **334** may include a tolerance threshold, and the thresholding unit **709** may access this information to determine for each of one or more measured attributes, whether the actual measured value of the attribute of the pile is within the permissible range. The thresholding unit **709** may also be configured to predict based on the time-series sensor data whether a given attribute of the pile is trending toward exceeding the corresponding tolerance threshold.

(103) This determination (or prediction) by the thresholding unit **709** may be performed at a predetermined frequency. For example, the determination may be performed at the same frequency as the frequency at which new sensor data becomes available and/or the attribute value detection is performed by the attribute detection module **705**. As another example, the determination by the thresholding unit **709** may be performed at one or more predetermined inspection points that may be predefined in a pile driving operation timeline (e.g., any point during or after the pile driving operation). As yet another example, the determination may be performed based on a trigger condition. The trigger condition may be sensor-based (e.g., based on sensor data) or based on user input (e.g., user operating on a user interface element to trigger the determination). The determination or prediction frequency may be different for the different detected attributes. For example, for the location attribute, the thresholding unit **709** may at the start of the pile driving operation determine whether the xy location of the bottom of the pile driven into the ground (as determined based on the sensor data **337**) accords with the xy location as dictated by the pile parameters of the pile plan data **334**, by being within the prescribed permissible tolerance range. As another example, for the orientation attribute, the thresholding unit **709** may (periodically or aperiodically during the pile driving operation) predict whether the plumbness or verticality of the pile being driven into the ground (as determined based on the sensor data **337**) is trending toward exceeding the prescribed permissible tolerance range with respect to the intended plumbness as dictated by the pile parameters of the pile plan data **334**.

(104) The thresholding unit **709** outputs a result of the determination or prediction as quality control condition data. For example, if the thresholding unit **709** determines that the plumbness or verticality of the pile being driven into the ground (as determined based on the sensor data **337**) is outside the permissible tolerance range of the target plumbness, the thresholding unit **709** outputs this determination as quality control condition data. As another example, if the thresholding unit **709** predicts that the plumbness or verticality of the pile being driven into the ground (as determined based on the sensor data **337**) is trending toward going outside the permissible tolerance range of the target plumbness, the thresholding unit **709** outputs this prediction as quality control condition data. As another example, if the thresholding unit **709** detects pile refusal based on the signal from the attribute detection module **705** and further detects that the pile refusal has exceeded corresponding tolerance threshold, the thresholding unit **709** may output the under-drive of the pile (e.g., height more than target height) as the quality control condition data. As another example, if the thresholding unit **709** detects pile over-drive based on the signal from the attribute detection module **705** and further detects that the pile height has fallen below the corresponding tolerance threshold for the target height, the thresholding unit **709** may output the over-drive of the pile (e.g., height less than target height) as the quality control condition data.

(105) The action module **710** performs a quality control action in response to the thresholding unit **709** determining or predicting that the one or more attributes of the pile exceed (or are predicted to exceed) the respective tolerance thresholds. The action module **710** may perform the quality control action based on the quality control condition data corresponding to the determined or predicted offending attribute. For example, the action module **710** may operate notification module **715** to transmit a notification to an external device (e.g., central server **130** of FIG. 1) reporting the offending (or predicted to offend) attribute. The notification may include the corresponding quality control condition data from the thresholding unit **709**. The notification may serve to inform a user to, e.g., switch over to performing the pile driving operation manually, or to otherwise intervene

during the autonomous pile driving operation.

(106) As another example, the action module **710** may operate the parameter adjustment module **720** to adjust or modify the actuation parameters of the driving tool of the pile driving AOV to perform corrective action during the pile driving operation to attempt to keep an attribute that is predicted to exceed the tolerance range to be within the tolerance range (or to attempt to bring an offending attribute back within the corresponding tolerance threshold). For example, in case the plumbness is predicted to exceed the tolerance threshold for the target plumbness by the time the driving operation is completed, the parameter adjustment module **720** may adjust the actuation parameters of the driving tool associated with the angle of impact of the driving tool on top of the pile to attempt to bring the plumbness of the pile closer to a desired plumbness and within the threshold tolerance.

(107) Another example of the action may be to stop the pile driving operation prior to completion based on the determination or the prediction by the thresholding unit **709**. The action module **710** may further annotate a quality control log with the quality control condition data associated with the location where the pile driving operation was stopped based on the determination or the prediction by the thresholding unit **709**. As another example, the action module **710** may flag the location with the quality control issue in association with the corresponding quality control condition data in a quality control review map for subsequent manual inspection. As another example, based on a measured attribute significantly exceeding (or predicted to significantly exceed) a corresponding tolerance threshold, the action module **710** may be configured to control the pile removal module **725** to autonomously remove the pile from the ground (e.g., actuate a clamping tool to grab the pile and wiggle it out of the ground), so that the autonomous pile driving operation at the location may be restarted with a new pile. In some embodiments, instead of removing the pile, the quality control review map may be updated to mark the location where the pile driving operation was stopped based on the determination or the prediction by the thresholding unit **709**.

(108) The quality control operation is depicted and described in further detail below in connection with FIG. **8**. FIG. **8** depicts the quality control operation for the pile driving AOV **200A** of FIG. **2A**, in accordance with some embodiments. FIG. **8** depicts an illustrative state where the first pile **815A** has already been driven into the ground by the driving tool **220A** at the first location **850A** without quality control issues, and the pile driving module **370** is now performing the pile driving operation for the second pile **815B** at the second location **850B** by actuating one or more components of the articulated arm **225A** and the driving tool **220A** to drive the second pile **815B** into the ground at the second location **850B**.

(109) In this case, for example, the pile parameters for both the locations **850A** and **850B** may indicate the same target pile height H , and as shown in FIG. **8**, the driving tool **220A** of the AOV **200A** may drive the pile **815A** into to ground to match the target height H at the location **850A**. However, as shown in FIG. **8**, while the driving tool **220A** of the AOV **200A** is driving the pile **815B** into the ground at the location **850B** to achieve the target height H , the pile **815B** may be driven to refusal prior to reaching the target height H and start bending (at **860**). The pile attributes of refusal and bending may be detected by the attribute detection module **705** based on the co-occurring time-series sensor data **337**. And the thresholding unit **709** may further detect that the pile refusal and/or pile bending has exceeded corresponding tolerance thresholds, and output corresponding quality control condition data (e.g., data indicating the pile height is more than the target height and exceeds the corresponding height tolerance threshold, image or other sensor data indicating pile is bent). Based on the quality control condition data, the action module **710** may perform one or more actions. For example, for the location **850B**, the action module **710** may control to stop the actuation of the drive tool **220A** of the AOV **200A** to immediately stop the pile driving operation for the location **850B** prior to its completion and notify an operator or flag the location (and corresponding data) in a map or a log for further manual inspection. As another

example, the action module **710** may control the pile removal module **725** to control actuation of the drive tool **220A** of the AOV **200A** to grab the bent/deformed pile **815B** and wiggle the bent pile **815B** to remove it from the location **850B** autonomously, so that a new pile can be installed at or near the location **850B**.

Example Obstacle Map Creation Operation

(110) Returning to FIG. **3B**, another operation that may be performed by the control system **330** may include the obstacle map creation operation. For example, based on the autonomous navigation operation, the autonomous pile driving operation and/or the autonomous quality control operation, the obstacle mapping module **390** may generate an obstacle map indicating locations of obstacles within the geographic area. By performing the obstacle map creation operation, the obstacle mapping module **390** may ensure efficient autonomous navigation and path planning for each AOV in the geographic area. Features of the obstacle mapping module **390** are described below in connection with FIG. **9**. An example obstacle map generated by the obstacle mapping module **390** is depicted and described below in connection with FIG. **10**. In some embodiments, the obstacle map may simply be a log of geolocation data corresponding to the obstacles.

(111) As shown in FIG. **9**, the obstacle mapping module **390** may include a pile obstacle mapping module **910**, a non-pile obstacle mapping module **920**, and a syncing module **930**. In different embodiments, the obstacle mapping module **390** of FIG. **9** may include fewer or additional components. The obstacle mapping module **390** may also include different components.

(112) The pile obstacle mapping module **910** may be configured to generate obstacle data **336** of an obstacle map (see FIG. **10**) indicating locations of obstacles within the geographic area. The obstacle data **336** may be generated for each location of the pile plan map where the pile driving operation has been completed. An obstacle may be any object or thing that defines a volume of space within the geographic area that is not navigable by an AOV or by a component (e.g., mechanical arm or driving tool) of the AOV. For example, in response to the autonomous navigation operation of the AOV to a first location based on the path plan, and in response to performance of the pile driving operation at the first location (and optionally, passing the quality control check), the pile obstacle mapping module **910** may generate the obstacle data **336** of the obstacle map (or update/modify the obstacle data **336** of the obstacle map) to include a representation of the pile at the first location. Subsequent pile driving operations at subsequent locations may result in similar modifications to the obstacle data **336** of the obstacle map to include representations of the piles at the subsequent locations.

(113) The representations of the piles at the respective locations may include pile obstacle information including one or more of pile height information (e.g., pile reveal height, pile height relative to a reference point, etc.), pile location information (e.g., horizontal location of the bottom and/or top of the pile, horizontal or vertical location of the top of the pile, etc.), pile volume information (e.g., depth information, point cloud model data, etc.), and discretized pile information (e.g., 3D discretized pile volume data). For example, the pile obstacle information may correspond to the (final state of the) pile attributes detected by the attribute detection module **705** of the quality control module **380**.

(114) The obstacle data **336** may be generated or the obstacle map may be modified in real-time. Thus, continuing with the above example, after modifying the obstacle map to include the obstacle data **336** for the first location, in response to the autonomous navigation operation of the AOV to a second location based on the path plan, and in response to performance of the pile driving operation at the second location (and optionally, passing the quality control check), the pile obstacle mapping module **910** may generate the obstacle data **336** of the obstacle map (or update/modify the obstacle data **336** of the obstacle map that has already been modified previously to include the obstacle data **336** of the first location) to include a representation of the pile at the second location.

(115) The non-pile obstacle mapping module **920** may also be configured to generate the obstacle

data **336** of an obstacle map (see FIG. **10**) indicating locations of (non-pile) obstacles within the geographic area. The obstacle data **336** generated by the non-pile obstacle mapping module **920** perceptually based on sensor data captured by an AOV. The obstacle data **336** data **336** generated by the non-pile obstacle mapping module **920** may correspond to non-pile obstacles including static obstacles (e.g., trenches, dirt piles, electric poles, etc.) or dynamic obstacles (e.g., AOVs or other vehicles, humans, etc.) within the geographic area that are perceived by the non-pile obstacle mapping module **920** based on the time-series sensor data **337**. Techniques known to those skilled in the art (e.g., computer vision, image segmentation, machine learning based techniques, etc.) may be employed to detect the static or dynamic obstacles in the geographic area.

(116) The non-pile obstacles detected by the non-pile obstacle mapping module **920** may be autonomously perceived when the AOV is performing other manual or autonomous operations (e.g., navigation operation, pile loading operation, pile driving operation, basket loading operation, pile distribution operation, quality control operation, etc.). Representations of the non-pile obstacles detected by the non-pile obstacle mapping module **920** include obstacle information similar to the pile obstacle information described above in connection with the pile obstacle mapping module **910**. for example, the obstacle data **337** corresponding to the non-pile obstacle information may include obstacle height information, obstacle location information (e.g., horizontal or vertical location of the obstacle etc.), obstacle volume information (e.g., depth information, point cloud model data, etc.), and discretized obstacle information (e.g., 3D discretized pile volume data).

(117) The syncing module **930** may be configured to synchronize and update in real-time, the obstacle data **337** of the obstacle map across multiple AOVs based on (pile and non-pile) obstacle mapping operations simultaneously being performed by multiple AOVs. The synced obstacle data **337** may then be broadcast to all AOVs operating in the geographic area so that performance of operations by the multiple AOVs like the path planning operation, the navigation operation, the pile loading operation, the pile driving operation, and the like, accounts for all of the obstacles within the geographic area. In some embodiments, the syncing module **930** may be configured to transmit a local state of the obstacle data **337** to a central server (e.g., server **130** of FIG. **1**) periodically or based on other criteria (e.g., every time an update is made to the local state of the map, user operation, etc.). The server may be configured to maintain a master state of the obstacle data **337** based on respective local state updates received from one or more AOVs operating in the geographic area. The server may further be configured to broadcast the master state of the obstacle map to the respective one or more AOVs to update the local state at each AOV. Based on the received broadcast of the master state, the syncing module **930** may update the local state of the obstacle map, thereby syncing the obstacle data **337** of the obstacle map with the server. The autonomous operation by the AOV may then be performed based on the updated local state of the obstacle map of the AOV.

(118) Thus, for example, the autonomous navigation operation by a first AOV may be based on an update to an obstacle map that is updated to include a (pile or non-pile) obstacle by a second AOV. The first AOV may thus be navigated (or a component of the first AOV operated to perform, e.g., an arm actuation operation, a pile loading operation, a pile driving operation, etc.) to avoid not only obstacles added to the map by the first AOV, but also obstacles added to the obstacle map by the second AOV.

(119) FIG. **10** depicts an example obstacle map **1000** generated by the obstacle mapping module **390**, in accordance with some embodiments. In some embodiments, the obstacle map **1000** may correspond to the pile plan map (e.g., see FIG. **4**). The obstacle map **1000** may represent an “as-built” or real-time state of the pile driving operation being carried out autonomously in the geographic area **1010** by one or more AOVs. FIG. **10** depicts an illustrative state where the pile driving operation for all of the locations **1020** in column **11** (e.g., six locations **1020** as shown and marked as solid shapes) in the geographic area **1010** has already been completed, and the obstacle

data **337** corresponding to the locations **1020** in column **11** has already been generated and recorded in the obstacle map **1000**. The illustrative state of FIG. **10** further depicts that in column **12**, the obstacle data **337** corresponding to the first nine locations **1020** (marked as solid shapes) has already been generated and recorded in the obstacle map **1000**. The obstacle map **1000** may also show (and corresponding obstacle data **337** include) locations **1040** corresponding to columns **12-20** where the pile driving operation has still not been performed. Such locations **1040** are shown with broken lines in FIG. **10**.

(120) For each location **1020**, the obstacle data **337** may include the pile obstacle information as explained above. Although not specifically shown in FIG. **10**, the obstacle data **337** for each location **1020** may also convey, e.g., depth information, point cloud model data, 3D discretized pile volume data, and the like. Using the pile obstacle information corresponding to the pile obstacles at each location **1020**, the one or more AOVs (e.g., AOVs **1030A**, **1030B**, and **1030C** in FIG. **10**) in the geographic area **1010** may be operated so as to avoid the obstacles while performing the variety of autonomous operations according to the present disclosure (e.g., navigation operation, component actuation operation, path planning operation, pile loading operation, pile driving operation, etc.).

(121) FIG. **10** depicts the state where the obstacle data **336** for the location **1020A** has already been generated by the AOV **1030A** and the obstacle map **1000** modified for the location **1020A**. FIG. **10** further depicts the state where the AOV **1030A** is now going to perform the autonomous operations including the pile driving operation for the location **1040A**. After the performance of the pile driving operation at the location **1040A** (and optionally, passing the quality control check), the pile obstacle mapping module **910** may similarly generate the obstacle data **336** (i.e., the pile obstacle information) for the location **1040A**, update the map based on the generated data **337**, and move on to the next location.

(122) The pile obstacle mapping operation described above may also simultaneously be performed by other AOVs **1030B** and **1030C**, and the obstacle data **336** generated by the other AOVs **1030B** and **1030C** may also be added to the same obstacle map **1000** in real-time. The updated obstacle map **1000** may then be made accessible to all of the AOVs **1030** so that the autonomous operations performed by each AOV **1030** may be based on the obstacle map **1000** that has been updated to include all obstacles.

(123) FIG. **10** also depicts static non-pile obstacles (e.g., trenches, dirt piles, construction equipment, etc.) **1050** that may be perceived by one or more of the AOVs **1030** while performing other operations (e.g., navigation operation) using the sensor data **337**, and the obstacle data **337** corresponding to the obstacles **1050** generated and added into the obstacle map **1000**. Each AOV **1030** may also detect dynamic non-pile obstacles like the other AOVs **1030**, other vehicles, humans, etc., based on the sensor data, and add the obstacle data **337** corresponding to the dynamic obstacles **1030** into the obstacle map **1000**. One or more of the non-pile obstacles **1050** of FIG. **10** may also correspond to an obstacle that is manually added to the obstacle map **1000** by a user. For example, an “as-built” file with geolocation data (e.g., GPS coordinates) of known obstacles may be uploaded by a user to the system and the obstacle map **1000** may be updated to include the obstacles identified in the uploaded file.

(124) Thus, more generally, for each obstacle (e.g., **1020**, **1030**, **1050**) tagged in the map **1000**, the obstacle map **1000** may include obstacle attribute information such as identity, type or category of the object, physical characteristics of the object, 3D location of the object, depth of the object, point cloud model of the object, discretized model of the object, and the like. The obstacle map **1000** may thus convey 3D non-navigable regions to inform AOV or AOV tool path planning within the geographic area **1010** (e.g., minimum height a tool of the AOV needs to be to avoid hitting the pile that has been driven into the ground and that has a certain reveal height). The obstacles may include as-built obstacles like piles that have been installed by the AOV at locations prescribed by the pile plan map, or non-pile static or dynamic obstacles perceived or detected based on sensor

data.

Example Methods

(125) FIG. **11** is a flow chart **1100** illustrating a process for generating basket assembly instructions, in accordance with some embodiments. It should be noted that the process illustrated herein can include fewer, different, or additional steps in other embodiments. Process **1100** may be performed by a control system (e.g., control system **330** of FIG. **3B**). The control system **330** may access **1110** a pile plan map (e.g., FIG. **4**) indicating a plurality of locations within a geographic area at which piles are to be installed. The control system **330** may generate **1120** an obstacle map (e.g., FIG. **10**) indicating locations of obstacles within the geographic area. The control system **330** may autonomously navigate **1130** the AOV to a first location of the plurality of locations using the pile plan map. The control system **330** may, in response to driving a pile into the ground at the first location, modify **1140** the obstacle map (e.g., location **1020A** in FIG. **10**) to include a representation of the pile at the first location.

(126) FIG. **12** is a flow chart **1200** illustrating a process of autonomously driving a plurality of piles into the ground, in accordance with some embodiments. It should be noted that the process illustrated herein can include fewer, different, or additional steps in other embodiments. Process **1200** may be performed by a control system (e.g., control system **330** of FIG. **3B**). The control system **330** may access **1210** a pile plan map (e.g., FIG. **4**) indicating a plurality of locations in a geographic area at which piles are to be installed. The control system **330** may select **1220** a first location and a second location (e.g., locations **650A** and **650B** in FIG. **6C**) from the plurality of locations using the pile plan map. The control system **330** may autonomously navigate **1230** the AOV to the first location (e.g., location **650A** FIG. **6C**). The control system **330** may autonomously load **1240** a first pile (e.g., pile **615A** in FIG. **6B**) onto a driving tool of the AOV. The control system **330** may autonomously drive **1250** the first pile into the ground at the first location (e.g., pile **615A** at location **650A** in FIG. **6C**). The control system **330** may autonomously navigate **1260** the AOV to the second location (e.g., location **650B** in FIG. **6C**). The control system **330** may autonomously load **1270** a second pile (e.g., pile **615B** in FIG. **6B**) onto the driving tool. The control system **330** may autonomously drive **1280** the second pile into the ground at the second location using the driving tool (e.g., pile **615B** at location **650B** in FIG. **6C**).

(127) FIG. **13** is a flow chart **1300** illustrating a process of performing an autonomous quality control operation for autonomously driven piles, in accordance with some embodiments. It should be noted that the process illustrated herein can include fewer, different, or additional steps in other embodiments. Process **1300** may be performed by a control system (e.g., control system **330** of FIG. **3B**). The control system **330** may access **1310** a pile plan map (e.g., FIG. **4**) indicating a plurality of locations in a geographic area at which piles are to be installed. The control system **330** may identify **1320** a first set of locations from the plurality of locations and a first set of piles to be driven into the ground at the first set of locations using the pile plan map. The control system **330** may identify **1330** an order for driving the first set of piles into the ground and a pile type for each of the first set of piles. The control system **330** may generate **1340** basket assembly instructions for assembling the first set of piles into a basket based on the identified order and the identified pile types.

(128) FIG. **14** is a flow chart **1400** illustrating a process of performing an autonomous obstacle map creation operation based on autonomously driven piles, in accordance with some embodiments. It should be noted that the process illustrated herein can include fewer, different, or additional steps in other embodiments. Process **1400** may be performed by a control system (e.g., control system **330** of FIG. **3B**). The control system **330** may autonomously perform **1410** a pile driving operation (e.g., FIG. **6C**) by driving a pile into the ground at a location identified by a pile plan map (e.g., FIG. **4**). The control system **330** may detect **1420** one or more attributes of the pile using one or more sensors during or after the pile driving operation. The control system **330** may determine **1430** whether the one or more attributes of the pile exceed respective tolerance thresholds (e.g.,

bent pile in FIG. 8). The control system **330** may perform **1440** a quality control action in response to determining that the one or more attributes of the pile exceed the respective tolerance thresholds.

Example Computer System

(129) FIG. **15** is a block diagram illustrating components of an example machine for reading and executing instructions from a machine-readable medium, in accordance with one or more example embodiments.

(130) FIG. **15** is a block diagram illustrating components of an example machine for reading and executing instructions from a machine-readable medium, in accordance with one or more example embodiments. Specifically, FIG. **15** shows a diagrammatic representation of one or more of the central server **130** of FIG. **1**, the client device **140** of FIG. **1**, the control system **330** of FIGS. **3A-3B**, the basket assembly module **355** of FIG. **5**, the quality control module **380** of FIG. **7**, the obstacle mapping module **390** of FIG. **7**, and machines for performing the processes **1100-1400** of FIGS. **11-14**, in the example form of a computer system **1500**.

(131) The computer system **1500** can be used to execute instructions **1524** (e.g., program code or software) for causing the machine to perform any one or more of the methodologies (or processes) or modules described herein. In alternative embodiments, the machine operates as a standalone device or a connected (e.g., networked) device that connects to other machines. In a networked deployment, the machine may operate in the capacity of a server machine or a client machine in a client-server network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

(132) The machine may be a server computer, a client computer, a personal computer (PC), a tablet PC, a set-top box (STB), a smartphone, an internet of things (IoT) appliance, a network router, switch or bridge, or any machine capable of executing instructions **1524** (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute instructions **1524** to perform any one or more of the methodologies discussed herein.

(133) The example computer system **1500** includes one or more processing units (generally processor **1502**). The processor **1502** is, for example, a central processing unit (CPU), a graphics processing unit (GPU), a digital signal processor (DSP), a control system, a state machine, one or more application specific integrated circuits (ASICs), one or more radio-frequency integrated circuits (RFICs), or any combination of these. The computer system **1500** also includes a main memory **1504**. The computer system may include a storage unit **1516**. The processor **1502**, memory **1504**, and the storage unit **1516** communicate via a bus **1508**.

(134) In addition, the computer system **1500** can include a static memory **1506**, a graphics display **1510** (e.g., to drive a plasma display panel (PDP), a liquid crystal display (LCD), or a projector). The computer system **1500** may also include an alphanumeric input device **1512** (e.g., a keyboard), a cursor control device **1517** (e.g., a mouse, a trackball, a joystick, a motion sensor, or other pointing instrument), a signal generation device **1518** (e.g., a speaker), and a network interface device **1520**, which also are configured to communicate via the bus **1508**.

(135) The storage unit **1516** includes a machine-readable medium **1522** on which is stored instructions **1524** (e.g., software) embodying any one or more of the methodologies or functions described herein. For example, the instructions **1524** may include the functionalities of modules of one or more of the central server **130** of FIG. **1**, the client device **140** of FIG. **1**, the control system **330** of FIGS. **3A-3B**, the basket assembly module **355** of FIG. **5**, the quality control module **380** of FIG. **7**, the obstacle mapping module **390** of FIG. **7**, and the machines for performing the processes **1100-1400** of FIGS. **11-14**. The instructions **1524** may also reside, completely or at least partially, within the main memory **1504** or within the processor **1502** (e.g., within a processor's cache memory) during execution thereof by the computer system **1500**, the main memory **1504** and the processor **1502** also constituting machine-readable media. The instructions **1524** may be

transmitted or received over a network 1526 via the network interface device 1520.

Additional Configuration Considerations

(136) The foregoing description of the embodiments has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the patent rights to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

(137) Some portions of this description describe the embodiments in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like.

(138) Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

(139) Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices. In one embodiment, a software module is implemented with a computer program product comprising a computer-readable medium containing computer program code, which can be executed by a computer processor for performing any or all of the steps, operations, or processes described.

(140) Embodiments may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a non-transitory, tangible computer readable storage medium, or any type of media suitable for storing electronic instructions, which may be coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

(141) Embodiments may also relate to a product that is produced by a computing process described herein. Such a product may comprise information resulting from a computing process, where the information is stored on a non-transitory, tangible computer readable storage medium and may include any embodiment of a computer program product or other data combination described herein.

(142) Finally, the language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the patent rights. It is therefore intended that the scope of the patent rights be limited not by this detailed description, but rather by any claims that issue on an application based hereon.

Accordingly, the disclosure of the embodiments is intended to be illustrative, but not limiting, of the scope of the patent rights, which is set forth in the following claims.

Claims

1. A method comprising: accessing a pile plan map indicating a plurality of locations within a geographic area at which piles are to be installed; autonomously navigating by a first autonomous off-road vehicle (“AOV”) of a plurality of AOVs to a location of the plurality of locations using the pile plan map; in response to the first AOV autonomously driving a pile into the ground at the location, modifying an obstacle map indicating locations of obstacles within the geographic area to include a representation of the pile at the location; sharing the modified obstacle map with the plurality of AOVs; and autonomously modifying a planned movement of a portion of a second AOV of the plurality of AOVs based on contents of the modified obstacle map by stopping a next

pile driving operation in response to determining that the next pile driving operation cannot be completed and notifying an operator that the next pile driving operation was stopped.

2. The method of claim 1, wherein the portion of the second AOV is at least one of an articulated arm, a component of a pile loading mechanism, a component of a pile driving mechanism, a driving tool, and a component of a drive system, of the second AOV.

3. The method of claim 1, wherein the location is a first location, and wherein the method further comprises: autonomously navigating by the first AOV to a second location of the plurality of locations using the pile plan map; and in response to autonomously driving a pile into ground at the second location, modifying the obstacle map that includes the representation of the pile at the first location to further include a representation of the pile at the second location.

4. The method of claim 3, wherein each of the representation of the pile at the first location and the representation of the pile at the second location in the obstacle map includes one or more of pile height information, pile location information, pile volume information, and discretized pile information.

5. The method of claim 3, further comprising: autonomously navigating the first AOV to the second location while avoiding obstacles based on the modified obstacle map; and autonomously actuating a component of the first AOV while avoiding obstacles based on the modified obstacle map.

6. The method of claim 1, further comprising: detecting a non-pile obstacle at a given location; and modifying the obstacle map that includes the representation of the pile at the location to further include a representation of the non-pile obstacle at the given location.

7. The method of claim 6, further comprising autonomously navigating the first AOV to a next pile driving location while avoiding obstacles based on the obstacle map modified to include the representation of the non-pile obstacle at the given location.

8. The method of claim 6, further comprising autonomously actuating a component of the first AOV while avoiding obstacles based on the obstacle map modified to include the representation of the non-pile obstacle at the given location.

9. The method of claim 6, further comprising detecting sensor data with one or more sensors mounted to the first AOV, wherein the non-pile obstacle is detected at the given location based on the sensor data.

10. The method of claim 1, further comprising: receiving obstacle information; updating the obstacle map based on the received obstacle information; and autonomously navigating the first AOV to a next pile driving location while avoiding obstacles based on the updated obstacle map.

11. An autonomous off-road vehicle (AOV), comprising: a hardware processor; and a non-transitory computer-readable storage medium storing executable instructions that, when executed by the hardware processor, cause the hardware processor to perform steps comprising: accessing a pile plan map indicating a plurality of locations within a geographic area at which piles are to be installed; autonomously navigating the AOV to a location of the plurality of locations using the pile plan map; in response to the AOV autonomously driving a pile into the ground at the location, modifying an obstacle map indicating locations of obstacles within the geographic area to include a representation of the pile at the location; and sharing the modified obstacle map with a second AOV, the second AOV configured to autonomously modify a planned movement of a portion of the second AOV based on contents of the modified obstacle map by stopping a next pile driving operation in response to determining that the next pile driving operation cannot be completed and notifying an operator that the next pile driving operation was stopped.

12. The AOV of claim 11, wherein the portion of the second AOV is at least one of an articulated arm, a component of a pile loading mechanism, a component of a pile driving mechanism, a driving tool, and a component of a drive system component, of the second AOV.

13. The AOV of claim 11, wherein the location is a first location, and wherein the instructions further cause the hardware processor to perform steps comprising: autonomously navigating the AOV to a second location of the plurality of locations using the pile plan map; and in response to

autonomously driving a pile into ground at the second location, modifying the obstacle map that includes the representation of the pile at the first location to further include a representation of the pile at the second location.

14. The AOV of claim 13, wherein each of the representation of the pile at the first location and the representation of the pile at the second location includes one or more of pile height information, pile location information, pile volume information, and discretized pile information.

15. The AOV of claim 13, wherein the instructions further cause the hardware processor to perform steps comprising: autonomously navigating the AOV to the second location while avoiding obstacles based on the modified obstacle map; and autonomously actuating a component of the AOV while avoiding obstacles based on the modified obstacle map.

16. The AOV of claim 11, wherein the instructions further cause the hardware processor to perform steps comprising: detecting sensor data with one or more sensors mounted to the AOV; detecting a non-pile obstacle at a given location based on the sensor data; and modifying the obstacle map that includes the representation of the pile at the location to further include a representation of the non-pile obstacle at the given location.

17. The AOV of claim 16, wherein the instructions further cause the hardware processor to perform a step comprising autonomously navigating the AOV to a next pile driving location while avoiding obstacles based on the obstacle map modified to include the representation of the non-pile obstacle at the given location.

18. The AOV of claim 16, wherein the instructions further cause the hardware processor to perform a step comprising autonomously actuating a component of the AOV while avoiding obstacles based on the obstacle map modified to include the representation of the non-pile obstacle at the given location.

19. The AOV of claim 11, wherein the instructions further cause the hardware processor to perform steps comprising: receiving obstacle information; updating the obstacle map based on the received obstacle information; and autonomously navigating the AOV to a next pile driving location while avoiding obstacles based on the updated obstacle map.

20. A central server comprising: a hardware processor; and a non-transitory computer-readable storage medium storing executable instructions that, when executed by the hardware processor, cause the hardware processor to perform steps comprising: in response to autonomously driving a pile into the ground at a first location of a plurality of locations using a pile plan map by a first autonomous off-road vehicle (“AOV”) of a plurality of AOVs, modifying an obstacle map indicating locations of obstacles within a geographic area to include a representation of the pile at the first location, the pile plan map indicating the plurality of locations within the geographic area at which piles are to be installed; in response to autonomously driving a pile into the ground at a second location of the plurality of locations using the pile plan map by a second AOV, modifying the obstacle map that includes the representation of the pile at the first location to further include a representation of the pile at the second location; and transmitting to the first AOV and to the second AOV, the modified obstacle map that includes the representation of the pile at the first location and the representation of the pile at the second location, wherein each of the first AOV and the second AOV autonomously modifies a planned movement of a portion of the first AOV and the second AOV based on contents of the modified obstacle map by stopping a next pile driving operation in response to determining that the next pile driving operation cannot be completed and notifying an operator that the next pile driving operation was stopped.
