

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401767
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tamagawa; Shuichi

Display system

Abstract

A display system includes: one or more moving body cameras that capture one or more images in front of a moving body; one or more intersection cameras; a display device including one or more screens that display, as one or more images for remote operation of the moving body, one or more moving-body camera images; and one or more processors. The one or more processors are configured to: execute a determination process of determining whether or not a moving object is included in an intersection camera image by analyzing the intersection camera image; and execute a highlighting process of applying a highlighting to the one or more moving-body camera images when the moving object is included in the intersection camera image. The highlighting indicates whether the moving object is present in a left or right direction with respect to a traveling direction of the moving body.

Inventors:	Tamagawa; Shuichi (Kitanagoya, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	1000008783101
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	18/524680
Filed:	November 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240251060 A1	Jul. 25, 2024

Foreign Application Priority Data

JP	2023-009489	Jan. 25, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: H04N7/18 (20060101); G05D1/00 (20240101); G06V20/54 (20220101); G08G1/04 (20060101); H04N23/90 (20230101)

U.S. Cl.:

CPC H04N7/181 (20130101); G05D1/0038 (20130101); G06V20/54 (20220101); G08G1/04 (20130101); H04N23/90 (20230101);

Field of Classification Search

CPC: H04N (7/181); H04N (23/90); H04N (7/18); G05D (1/0038); G06V (20/54); G08G (1/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8179241	12/2011	Sakai	340/436	G08G 1/164
9487139	12/2015	Ishida	N/A	B60W 30/08
10552690	12/2019	Schubert	N/A	G06T 11/00
11215982	12/2021	Urano et al.	N/A	N/A
11325618	12/2021	Umeda	N/A	N/A
2007/0139523	12/2006	Nishida	348/E7.086	G06V 20/58
2009/0140881	12/2008	Sakai	340/901	G08G 1/164
2018/0181118	12/2017	Yoneda et al.	N/A	N/A
2019/0137999	12/2018	Taguchi et al.	N/A	N/A
2020/0063397	12/2019	Hatake	N/A	E02F 9/2004
2020/0209888	12/2019	Sakai et al.	N/A	N/A
2020/0326702	12/2019	Iwamoto et al.	N/A	N/A
2021/0041894	12/2020	Urano et al.	N/A	N/A
2021/0055741	12/2020	Kawanai et al.	N/A	N/A
2021/0058173	12/2020	Otaki et al.	N/A	N/A
2021/0072743	12/2020	Otaki et al.	N/A	N/A
2021/0080943	12/2020	Iwamoto et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021-189683	12/2020	JP	N/A
7029910	12/2021	JP	N/A

Primary Examiner: Topgyal; Gelek W
Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATION

(1) The present disclosure claims priority under 35 U.S.C. § 119 to Japanese Patent Application No. 2023-009489, filed on Jan. 25, 2023, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a display system that displays an image for remote operation of a moving body.

BACKGROUND

(3) JP 2021-189683 A discloses a remote assistance control device that remotely assists traveling of an automated driving vehicle. The control device receives, from the automated driving vehicle, vehicle information including at least position information indicating a traveling position and a surrounding image of the traveling position. Also, the control device reads accident pattern data related to the vehicle information from an accident pattern database in which a plurality of past accident cases and traffic conditions are associated with each other and stored, and superimposes attention calling information on the surrounding image to generate auxiliary information for the driving assistance. The generated auxiliary information for the driving assistance is provided to the automated driving vehicle.

(4) Moreover, JP 7029910 B2 discloses a remote operation system for an operator to remotely operate a vehicle. This system includes a display device that displays the vehicle and an obstacle around the vehicle. The display device displays the obstacle sensed by the vehicle by enclosing the obstacle in a solid-line square frame.

SUMMARY

(5) In order to supplement safety confirmation at an intersection by a remote operator who performs remote operation (remote driving, remote assistance, or remote monitoring) of a moving body, such as an automobile, it is conceivable to display, on a screen of a display device of a remote operator terminal, an image of an intersection camera installed at the intersection. However, the installation direction and the angle of view of the intersection camera vary depending on the intersection. Therefore, even if the image of the intersection camera is displayed on the display device, it is difficult for the remote operator to instantaneously grasp the traveling direction of the moving body in the image, and it may take time to confirm safety.

(6) The present disclosure has been made in view of the problem described above, and an object thereof is to provide a display system that can facilitate safety confirmation by a remote operator at an intersection while using image information of an intersection camera.

(7) A display system according to the present disclosure includes one or more moving body cameras, one or more intersection cameras, a display device, and one or more processors. The one or more moving body cameras are configured to capture one or more images in front of a moving body. The one or more intersection cameras are installed at an intersection through which the moving body passes, and are configured to image a traffic situation in an area of the intersection. The display device includes one or more screens configured to display, as one or more images for remote operation of the moving body, one or more moving-body camera images of the one or more moving body cameras. The one or more processors are configured to: execute a determination process of determining whether or not a moving object is included in an intersection camera image of the one or more intersection cameras by analyzing the intersection camera image; and execute a highlighting process of applying a highlighting to the one or more moving-body camera images when the moving object is included in the intersection camera image. The highlighting indicates whether the moving object is present in a left or right direction with respect to a traveling direction of the moving body.

(8) According to the present disclosure, safety confirmation by the remote operator at an intersection can be facilitated while using the image information of an intersection camera.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram schematically illustrating a configuration example of a remote operation system to which a display system according to an embodiment is applied;
- (2) FIG. 2A is a diagram illustrating an example of an intersection;
- (3) FIG. 2B is a diagram illustrating an example of an intersection camera image;
- (4) FIG. 3A is a diagram illustrating a highlighting example A1 according to an embodiment;
- (5) FIG. 3B is a diagram illustrating a highlighting example A2 according to an embodiment;
- (6) FIG. 3C is a diagram illustrating a highlighting example B according to an embodiment;
- (7) FIG. 4A is one of flowcharts illustrating an example of a flow of processing related to image display according to an embodiment, which is executed by the cooperation of a remote operator terminal side and an infrastructure side;
- (8) FIG. 4B is the other of the flowcharts illustrating the example of the flow of processing related to the image display according to the embodiment, which is executed by the cooperation of the remote operator terminal side and the infrastructure side;
- (9) FIG. 5 is a flowchart illustrating another example of the flow of processing related to image display according to an embodiment, which is executed by a remote operator terminal side;
- (10) FIG. 6A is a diagram illustrating an example of the intersection camera image displayed as reference information; and
- (11) FIG. 6B is a diagram illustrating another example of the intersection camera image displayed as reference information.

DETAILED DESCRIPTION

1. Configuration of Remote Operation System

- (12) FIG. 1 is a diagram schematically illustrating a configuration example of a remote operation system **1** to which a display system according to an embodiment is applied. The remote operation system **1** includes a vehicle **10**, a remote operator terminal **20**, a camera device **30**, and a management server **40**.
- (13) 1-1. Vehicle
- (14) The vehicle **10** is an example of a “moving body” that is a target of “remote operation” according to the present disclosure, and more specifically, is, for example, an automobile. The vehicle **10** includes a global navigation satellite system (GNSS) receiver **11**, one or more in-vehicle cameras (one or more moving body cameras) **12**, a travel device **13**, a communication device **14**, an antenna **15**, and a control device **16**.
- (15) The GNSS receiver **11** is used to acquire a position and an orientation of the vehicle **10**. The one or more in-vehicle cameras **12** recognize (detect) a situation around the vehicle **10**. The one or more in-vehicle cameras **12** are configured to capture images in front of the vehicle **10**. As an example, the one or more in-vehicle cameras **12** include three cameras respectively configured to image the front center, the left front, and the right front of the vehicle **10**.
- (16) The travel device **13** includes a drive device, a brake device, and a steering device. The drive device includes, for example, at least one of an electric motor and an internal combustion engine for driving the vehicle **10**. The brake device includes a brake actuator for braking the vehicle **10**. The steering device includes, for example, an electric motor configured to steer wheels.
- (17) The communication device **14** communicates with the outside of the vehicle **10**. Specifically, the communication device **14** communicates with, for example, the remote operator terminal **20** via the antenna **15**.
- (18) The control device **16** is a computer configured to control the vehicle **10**. The control device **16** includes one or more processors and one or more memory devices. The one or more processors execute various processes related to control of the vehicle **10**. The one or more memory devices

store various types of information necessary for the processes executed by the one or more processors.

(19) During the remote operation of the vehicle **10**, the control device **16** communicates with the remote operator terminal **20** via the communication device **14**. The control device **16** transmits vehicle information VCL to the remote operator terminal **20**. The vehicle information VCL is information necessary for the remote operation by the remote operator, and includes surrounding situation information of the vehicle **10**. The surrounding situation information includes images captured by the in-vehicle cameras **12**. The surrounding situation information may include moving object information related to a moving object around the vehicle **10**.

(20) Further, the control device **16** receives remote operation information from the remote operator terminal **20**. The remote operation information is related to the remote operation by the remote operator. For example, the remote operation information includes the amount of operation by the remote operator. The control device **16** performs vehicle traveling control by controlling the travel device **13** in accordance with the received remote operation information.

(21) 1-2. Remote Operator Terminal

(22) The remote operator terminal **20** is a terminal device used when the remote operator remotely operates the vehicle **10**. The “remote operation” according to the present disclosure is a concept including “remote driving” in which a remote operator drives a moving body from a remote place, “remote assistance” in which a remote operator assists the driving of a moving body from a remote place, and “remote monitoring” in which a remote operator monitors the driving of a moving body from a remote place. In addition, when the remote operation is performed as the remote driving, the remote operator terminal **20** corresponds to a remote cockpit.

(23) The remote operator terminal **20** includes a communication device **21**, an antenna **22**, a display device **23**, a speaker **24**, an operating device **25**, and a control device **26**.

(24) The communication device **21** performs communication (wireless communication) with the vehicle **10** via the antenna **22**. Further, the communication device **21** communicates with the management server **40**.

(25) The display device **23** presents various kinds of information to the remote operator by displaying the various kinds of information. The various kinds of information include, as images for the remote operation of the vehicle **10**, images in front of the vehicle **10** (vehicle front images) captured by the plurality of in-vehicle cameras **12**. In addition, the “vehicle front image” corresponds to an example of the “one or more moving-body camera images” according to the present disclosure.

(26) FIG. 1 shows an example of a screen configuration of the display device **23** viewed from the remote operator. That is, the right side of the drawing sheet corresponds to the right side of the screen when viewed from the remote operator, and the left side of the drawing sheet corresponds to the left side of the screen when viewed from the remote operator. In this example, the display device **23** includes three monitors **231**, **232**, and **233**. The monitors **231**, **232**, and **233** display the vehicle front images. More specifically, as an example, one or more vehicle front images include a front center image displayed by the monitor **231**, a left front image displayed by the monitor **232**, and a right front image displayed by the monitor **233**. As shown in FIG. 1, the monitor **232** is arranged on the left side of the monitor **231**, and the monitor **233** is arranged on the right side of the monitor **231**.

(27) Additionally, in the example illustrated in FIG. 1, the display device **23** includes one monitor (monitor **231**, **232**, or **233**) for one image. However, instead of the example illustrated in FIG. 1, the “display device” according to the present disclosure may include one monitor configured to display a plurality of vehicle front images.

(28) The speaker **24** presents sound information to the remote operator by outputting the sound information. The sound information includes, for example, a sound detected by an in-vehicle microphone.

(29) The operating device **25** receives an input from the remote operator. For example, the operating device **25** includes one or more remote operation members operated by the remote operator when remotely operating the vehicle **10**. The one or more remote operation members include an accelerator pedal, a brake pedal, and a steering wheel. In addition, the operating device **25** includes switches for other various operations related to the remote operation.

(30) The control device **26** controls the remote operator terminal **20**. The control device **26** includes one or more processors **27** (hereinafter, simply referred to as “processor **27**”) and one or more memory devices **28** (hereinafter, simply referred to as “memory device **28**”). The processor **27** executes various processes related to the remote operation including display control of images of the display device **23**. The memory device **28** stores various types of information necessary for the processes executed by the processor **27**.

(31) The control device **26** communicates with the vehicle **10** via the communication device **21**. The control device **26** receives the vehicle information VCL transmitted from the vehicle **10**. The control device **26** presents the vehicle information VCL to the remote operator via the display device **23** and the speaker **24**. For example, the control device **26** displays the images captured by the in-vehicle camera **12** on the display device **23**. Further, the control device **26** outputs the sound detected by the in-vehicle microphone from the speaker **24**. The remote operator can recognize the state of the vehicle **10** and the surrounding situation based on the vehicle information VCL.

(32) The remote operator operates the remote operation members of the operating device **25**. The operating amounts of the remote operation members are detected by sensors provided in the remote operation members. The control device **26** generates the remote operation information reflecting the operating amounts of the remote operation members by the remote operator. Then, the control device **26** transmits the remote operation information to the vehicle **10** via the communication device **21**.

(33) 1-3. Intersection Camera

(34) An intersection camera **31** (hereinafter, also simply referred to as “camera **31**”) is installed at each intersection through which the vehicle **10** passes, and capture an image of an intersection area that is the inside of the intersection and the vicinity thereof. The camera **31** is configured as, for example, the camera device **30** including the camera **31**, a communication device **32**, and a control device **33**. In an example shown in FIGS. **2A** and **2B** described below, one camera **31** is installed for one intersection.

(35) An image of an intersection area (intersection camera image) captured by each camera **31** is transmitted to the management server **40** via the communication device **32**. The management server **40** is configured to be able to communicate with each camera device **30**, and manages the intersection camera image transmitted from each camera device **30**. The management server **40** is also configured to be able to communicate with the remote operator terminal **20**.

(36) The control device **33** includes one or more processors **34** (hereinafter, simply referred to as “processor **34**”) and one or more memory devices **35** (hereinafter, simply referred to as “memory device **35**”). The processor **34** executes various processes related to the intersection camera image. The memory device **35** stores various types of information necessary for the processes executed by the processor **34**.

(37) Additionally, communication between the management server **40** and each camera device **30** may be either wired communication or wireless communication. This also applies to communication between the management server **40** and the remote operator terminal **20**.

Furthermore, when the remote operator terminal **20** communicates with each camera device **30**, unlike the example illustrated in FIG. **1**, the remote operator terminal **20** may directly communicate with each camera device **30** without going through the management server **40**.

2. Control of Image Display on Display Device

(38) According to the present embodiment, in order to facilitate safety confirmation by the remote operator at an intersection while using the image information of the intersection camera **31**, the

following “determination process PR1” and “highlighting process PR2” are executed.

(39) In the determination process PR1, the intersection camera image installed at an intersection through which the vehicle **10** is planned to pass is analyzed in real time to determine whether or not a moving object is included in the intersection camera image. The highlighting process PR2 is executed when it is determined that the moving object is included in the intersection camera image. Then, in the highlighting process PR2, based on the result of the analysis described above, a highlighting indicating whether the moving object is present in the left or right direction with respect to a traveling direction Dv of the vehicle **10** is applied to the moving-body camera image. The “moving object” is, for example, another vehicle (such as an automobile), a pedestrian, or a bicycle.

(40) 2-1. Highlighting Example A

(41) In the highlighting examples A, the “highlighting” described above is a caution mark indicating whether the moving object is present in the left or right direction with respect to the traveling direction Dv of the vehicle **10**, and is added to the front center image (moving-body camera image) displayed on the screen (front center screen) of the monitor **231**.

(42) The highlighting examples A and a highlighting example B described below are described using an intersection CR1 shown in FIG. 2A as an example. In FIG. 2A, a first road R1 on which the vehicle **10** travel is connected to a second road R2 at the intersection CR1. More specifically, FIG. 2A illustrates a traffic situation in an area of the intersection CR1 when the vehicle **10** traveling on the first road R1 along the traveling direction Dv of the vehicle **10** is approaching the intersection CR1. As an example, the camera **31** captures an area of the second road R2 located on the right side of the intersection CR1 with respect to the traveling direction Dv together with the area in the intersection CR1. Another vehicle **2** traveling on the second road R2 is present in the imaging area of this camera **31**. In addition, in FIG. 2A, a crosswalk CW1 and stop lines SL1 and SL2 that are provided on the second road R2 are shown.

(43) FIG. 2B shows an intersection camera image captured by the camera **31** shown in FIG. 2A. An intersection camera image indicates a traffic situation in an area of an intersection into which the vehicle **10** enters. The intersection camera image illustrated in FIG. 2B includes another vehicle **2** which is an example of the moving object. According to the determination process PR1 of the present embodiment, it is determined that the another vehicle **2** is included in the intersection camera image by analyzing the intersection camera image of the camera **31**. Further, according to the analysis of the intersection camera image by the determination process PR1, when the another vehicle **2** is included in the intersection camera image, the direction in which the another vehicle **2** is present is determined among the left and right directions with respect to the traveling direction Dv of the vehicle **10**. In the example of the intersection camera image illustrated in FIG. 2B, the another vehicle **2** is determined to be present on the right side with respect to the traveling direction Dv.

(44) FIG. 3A is a diagram illustrating a highlighting example A1 which is one of the highlighting examples A. FIG. 3A shows a vehicle front image of each of the monitors **231** to **233** when the vehicle **10** approaches the intersection CR1 shown in FIG. 2A. In the highlighting example A1, a caution mark **50** is added, by the highlighting process PR2 of the present embodiment, to the front center image displayed on the monitor **231**. As shown in FIG. 3A, the caution mark **50** indicates whether another vehicle **2** is present in the left or right direction with respect to the traveling direction Dv of the vehicle **10**, and is arranged on the right side of the front center image when viewed from the remote operator. As described above, according to the highlighting example A, the information of the moving object (e.g., another vehicle **2**) included in the intersection camera image is displayed, for calling attention, on the front center image in which the moving object is not displayed. In addition, a reference numeral **6** denotes a building beside the roads R1 and R2.

(45) More specifically, the caution mark **50** is, for example, a mark (still image) expressed to indicate a state in which the another vehicle **2** that is present near the vehicle **10** is detected. This

kind of caution mark **50** is suitably used in a situation in which the type of the moving object can be identified as a result of the analysis by the determination process **PR1**. In addition, in an example in which the moving object, such as another vehicle **2**, is present in the left direction with respect to the traveling direction **Dv**, a caution mark obtained by flipping the caution mark **50** horizontally is arranged on the left side of the front center image displayed on the monitor **231**. (46) FIG. **3B** is a diagram illustrating a highlighting example **A2** which is another example of the highlighting examples **A**. This highlighting example **A2** is different from the highlighting example **A1** in the caution mark as the highlighting. That is, in the highlighting example **A2**, animation display is used as a caution mark **52**. The caution mark **52** is, for example, an arrow indicating a direction in which the another vehicle **2** is present as illustrated in FIG. **3B**. The arrow is displayed by animation so as to flow toward the direction in which the another vehicle **2** is present. In addition, in an example in which the moving object, such as the another vehicle **2** is present in the left direction with respect to the traveling direction **Dv**, a caution mark obtained by flipping the caution mark **52** horizontally is arranged on the left side of the front center image displayed on the monitor **231**.

(47) Additionally, the highlighting examples **A** (**A1** and **A2**) are applied here to the display device **23** having three screens of the front center screen, the left front screen, and the right front screen. However, application of the highlighting examples **A** is not limited to the display device **23** having the three screens and can be applied to a display device having at least a front center screen.

(48) 2-2. Highlighting Example B

(49) FIG. **3C** is a diagram showing a highlighting example **B**. In the highlighting example **B**, a highlighting is applied, by the highlighting process **PR2** of the present embodiment, to the left front screen or the right front screen corresponding to the direction in which the moving object is present among the left and right directions with respect to the traveling direction **Dv** of the vehicle **10**. To be specific, in an example of the intersection camera image illustrated in FIG. **2B**, the highlighting is applied to the right front screen of the monitor **233** corresponding to the right direction in which the another vehicle **2** is present. The highlighting is performed by, for example, surrounding the right front screen with a red frame **54** as shown in FIG. **3C**.

(50) Additionally, in an example in which a moving object, such as the another vehicle **2**, is present in the left direction with respect to the traveling direction **Dv**, the left front screen is surrounded by a red frame, contrary to the highlighting example **B** illustrated in FIG. **3C**. Moreover, the highlighting in the highlighting example **B** may be performed using a frame of any color other than red as long as the color attracts attention of the remote operator. Alternatively, the highlighting may be performed by, for example, flashing or blinking the left front screen or the right front screen, which is the screen on the side where the moving object is present, a designated number of times.

(51) Furthermore, according to the highlighting example **B**, unlike the highlighting examples **A**, a highlighting is not added to the front center screen which is the main screen of the remote operation. For this reason, it is possible to perform the highlighting while preventing interference of the highlighting with the vehicle front image.

(52) 2-3. Examples of Processing Related to Image Display

(53) In the remote operation system **1** illustrated in FIG. **1**, the configuration including the in-vehicle cameras **12**, the intersection camera **31**, the display device **23**, and the processors **27** and **34** corresponds to an example of the “display system” according to the present disclosure. In the display system configured as described above, the determination process **PR1** and the highlighting process **PR2** described above may be executed by the cooperation of the processor **27** of the remote operator terminal **20** (remote operator terminal side) and the processor **34** of the camera device **30** (infrastructure side) (see FIGS. **4A** and **4B**). Alternatively, the determination process **PR1** and the highlighting process **PR2** may be executed by the processor **27** (remote operator terminal-side) (see FIG. **5**).

(54) 2-3-1. Execution Example A by Cooperation of Remote Operator Terminal Side and

Infrastructure Side

(55) FIGS. 4A and 4B are flowcharts illustrating an example of a flow of processing related to the image display according to the embodiment, which is executed by the cooperation of the remote operator terminal side and the infrastructure side. The processing of the flowchart on the remote operator terminal side is started when the remote operation of the vehicle **10** is started, and is ended when the remote operation is ended. The processing of the flowchart on the infrastructure side is always executed for each camera **31** during the operation of the camera **31** at each intersection.

(56) In step **S100** in FIG. 4A, the processor **27** determines whether or not the vehicle **10** has approached an intersection where the intersection camera **31** is installed, based on, for example, the vehicle position information transmitted from the vehicle **10**. As a result, when this determination result is Yes, the processing proceeds to step **S102**.

(57) In step **S102**, the processor **27** executes a process of determining the orientation of the vehicle **10** (subject vehicle) with respect to the position of the camera **31** installed at the intersection that the vehicle **10** has approached. To be specific, for example, the processor **27** acquires information on an imaging direction D_c of the camera **31** from the camera device **30** including the camera **31**. Also, the processor **27** calculates, for example, the traveling direction D_v based on the vehicle position information. Then, based on the information of the imaging direction D_c and the traveling direction D_v , the processor **27** determines the orientation of the vehicle **10** with respect to the installation position of the camera **31** and acquires the orientation as the information of the orientation of the subject vehicle.

(58) Next, in step **S104**, the processor **27** controls the communication device **21** to transmit to the camera **31** the information on the orientation of the vehicle **10** (subject vehicle) acquired in step **S102** together with the position information of the subject vehicle. Then, in step **S106**, the processor **27** determines whether or not the moving object information of the intersection has been received from the camera **31**. This moving object information is information transmitted to the remote operator terminal **20** by the processing of step **S210** in FIG. 4B.

(59) In FIG. 4B, in step **S200**, the processor **34** acquires an intersection camera image from the camera **31**. Then, in step **S202**, the processor **34** analyzes the acquired intersection camera image. This kind of real-time analysis is executed using, for example, the following manner in order to detect a moving object in the intersection camera image.

(60) That is, the analysis is executed by, for example, moving object detection. According to the moving object detection, a moving object can be detected from a difference between temporally consecutive intersection camera images. In addition, the analysis may be executed by image processing using machine learning. By using the machine learning, it is possible to identify and classify moving objects, such as an automobile, a pedestrian, and a bicycle. As a result, for example, like the caution mark **50** described above, the caution mark can be switched in accordance with the type of the moving object.

(61) To be more specific, the analysis of the intersection camera image in step **S202** may be executed, for example, while adjusting the size and the moving speed of a moving object as a detection target and the detection area of the moving object as follows. That is, a moving object smaller than a designated size may be excluded from the detection target. As a result, erroneous detection of a moving object can be reduced. In addition, a moving object having a moving speed lower than a designated value may be excluded from the detection target. This also makes it possible to reduce erroneous detection of a moving object.

(62) Further, the adjustment of the detection area of the moving object may be executed as follows, for example. That is, in order to reduce erroneous detection and reduce the calculation load, the area in the intersection camera image used to detect a moving object may be changed (adjusted) for each camera **31** in accordance with at least one of the angle of view and the installation environment of the camera **31**. Specifically, in an example of the camera **31** having an angle of view such that the vehicle **10** (subject vehicle) is captured in the intersection camera image, the

detection area may be adjusted such that the subject vehicle and the road on which the subject vehicle travels are excluded. Moreover, the detection area may be designated for each camera **31** in order to avoid erroneous detection caused by the presence of an object, such as a tree, that shakes due to wind, and erroneous detection caused by flickering of a fluorescent light. Furthermore, the detection area may be determined based on the information of the traveling direction D_v of the vehicle **10**. For example, regarding the intersection camera image of the camera **31** having a wide angle of view, an area unnecessary for the analysis, such as an area behind the vehicle **10**, may be excluded from the detection target.

(63) Next, in step **S204**, the processor **34** (control device **33**) internally holds the moving object information acquired based on the result of the analysis in step **S202**. That is, the moving object information is stored in the memory device **35**.

(64) Next, in step **S206**, the processor **34** determines whether or not the information on the position and orientation of the subject vehicle has been transmitted from the remote operator terminal **20**. As a result, when there is no transmission of the information on the position and the orientation of the subject vehicle, the processor **34** repeatedly executes the processing of step **S200** and the subsequent steps. On the other hand, when there is transmission of the information, the processing proceeds to step **S208**.

(65) In step **S208**, the processor **34** executes a process of determining, from the information on the position and the orientation of the subject vehicle received from the remote operator terminal **20**, the presence or absence of a moving object as a detection target in the highlighting according to the present embodiment. To be specific, the processor **34** first determines whether or not a moving object is included in the moving object information held internally in step **S204**. As a result, when a moving object is included in the moving object information, the processor **34** determines whether or not the moving object is a detection target, based on, for example, the moving direction of the moving object. More specifically, whether the moving object is approaching or moving away from the vehicle **10** may be determined based on the information on the position and the orientation of the subject vehicle transmitted from the remote operator terminal **20**. Then, when it is determined that the moving object is approaching the vehicle **10**, the processor **34** may set the moving object as a detection target, and when it is determined that the moving object is moving away from the vehicle **10**, the processor **34** may exclude the moving object from the detection target. As a result, it is possible to appropriately select the moving object that should be highlighted for attracting attention of the remote operator.

(66) Next, in step **S210**, the processor **34** controls the communication device **32** to transmit the moving object information determined by the processing of step **S208** to the remote operator terminal **20**. To be specific, the processor **34** transmits the moving object information determined in response to receiving of the information on the position and the orientation of the subject vehicle from the remote operator terminal **20** (**S206**; Yes). The moving object information transmitted in this way includes, for example, a flag indicating the presence or absence of a moving object, and the position and the moving direction of the moving object. In addition, when the type of the moving object (for example, another vehicle, a pedestrian, or a bicycle) can be identified by using the machine learning described above, the moving object information which is transmitted may include the type of the moving object.

(67) In FIG. **4A**, when the determination result in step **S106** is Yes, that is, when the moving object information transmitted by the processing of step **S210** is received, the processing proceeds to step **S108**. In step **S108**, the processor **27** determines whether or not a moving object is included in the intersection camera image, based on the received moving object information. As a result, when this determination result is Yes, the processing proceeds to step **S110**, and when the determination result is No, the processing proceeds to step **S116**.

(68) In step **S110**, the processor **27** determines whether or not the moving object is present in the left direction with respect to the traveling direction D_v of the vehicle **10** (in other words, with

respect to the course of the subject vehicle), based on the received moving object information. As a result, when this determination result is Yes, that is, when the moving object is present in the left direction, the processing proceeds to step **S112**. In step **S112**, the processor **27** displays a caution mark (in other words, a caution alert) so as to be arranged on the left side of the front center image displayed on the monitor **231**. For example, the caution mark is obtained by horizontally flipping the caution mark **50** or **52**. Thereafter, the processing proceeds to step **S116**.

(69) On the other hand, when the determination result in step **S110** is No, that is, when the moving object is present in the right direction, the processing proceeds to step **S114**. In step **S114**, the processor **27** displays a caution mark so as to be arranged on the right side of the front center image displayed on the monitor **231**. The caution mark is, for example, the caution mark **50** or **52**. Thereafter, the processing proceeds to step **S116**.

(70) Additionally, although the highlighting examples A are applied to the processing of steps **S112** and **S114** described above, the highlighting example B may be applied.

(71) In step **S116**, the processor **27** determines whether or not the vehicle **10** has passed through the intersection determined in step **S100**, based on, for example, the vehicle position information. As a result, the processor **27** repeatedly executes the processing of step **S106** and the subsequent steps while the vehicle **10** has not yet passed through the intersection described above. On the other hand, after the vehicle **10** has passed through the intersection, the processor **27** proceeds to step **S118** and erases the caution mark displayed by the processing of step **S112** or **S114**.

(72) 2-3-2. Execution Example B by Remote Operator Terminal Side

(73) FIG. 5 is a flowchart illustrating an example of a flow of processing related to the image display according to the embodiment, which is executed by the remote operator terminal side. Hereinafter, differences between the processing of the flowchart illustrated in FIG. 4A and the processing of this flowchart will be described.

(74) In FIG. 5, after step **S102**, the processing proceeds to step **S300**. In step **S300**, the processor **27** of the remote operator terminal **20** executes a process of acquiring an intersection camera image from the camera **31** installed at an intersection determined in step **S100**.

(75) Next, in step **S302**, the processor **27** executes a process of analyzing the intersection camera image acquired in step **S300**. The processing of this step **S302** is the same as the processing executed in steps **S202** and **S208** in FIG. 4B. That is, the processor **27** analyzes the intersection camera image received from the camera device **30**, and detects the presence or absence of a moving object on the planned course of the subject vehicle using the information on the position and orientation of the subject vehicle. After step **S302**, the processing proceeds to step **S108**.

(76) Additionally, in FIG. 5, when the determination result in step **S116** is No, the processor **27** repeatedly executes the processing of step **S300** and the subsequent steps.

(77) Moreover, the execution example A by the cooperation of the remote operator terminal side and the infrastructure side has the following advantage effect over the execution example B by the remote operator terminal side. That is, according to the execution example A, only the moving object information (see step **S210**), such as the flag indicating the presence or absence of a moving object, is transmitted from the infrastructure side to the remote operator terminal side, and, as a result, there is no need to transmit the intersection camera image to the remote operator terminal **20**. Therefore, according to the execution example A, it is possible to reduce the communication amount as compared with the execution example B. In addition, since it is not necessary to transmit the intersection camera image, the influence of communication delay can also be reduced.

(78) Additionally, in the flowcharts shown in FIGS. 4A and 4B, the processes of steps **S202**, **S208**, and **S108** correspond to an example of the “determination process PR1” according to the present disclosure, and the processes of steps **S110** to **S114** correspond to an example of the “highlighting process PR2” according to the present disclosure. On the other hand, in the flowchart shown in FIG. 5, the processes of steps **S302** and **S108** correspond to an example of the “determination process PR1” according to the present disclosure, and the processes of steps **S110** to **S114**

correspond to an example of the “highlighting process PR2” according to the present disclosure. (79) As described above, according to the present embodiment, the determination process PR1 is executed to determine whether or not a moving object is included in an intersection camera image by analyzing the intersection camera image. As a result, when the moving object is included in the intersection camera image, the highlighting process PR2 is executed to apply, to the vehicle front image, a highlighting indicating whether the moving object is present in the left or right direction with respect to the traveling direction Dv of the vehicle **10**. That is, the moving object information based on the analysis result of the intersection camera image is displayed as a highlighting on the vehicle front image. Therefore, without displaying the intersection camera image itself on the display device **23**, it is possible to make the remote operator recognize that there is a moving object which may be an obstacle to the traveling of the vehicle **10** in the right or left direction of an intersection in front of the vehicle **10**, based on the moving object information from the intersection camera image. As described above, according to the present embodiment, it is possible to facilitate the safety confirmation by the remote operator at an intersection while using the image information of the intersection camera **31**.

(80) Furthermore, in the remote operator terminal **20**, the intersection camera image itself acquired by the intersection camera **31** is not displayed. By narrowing down the display targets on the display device **23** in this way, the remote operator only needs to confirm the main screens of the remote operation, that is, the front center screen, the left front screen, and the right front screen that display the vehicle front images. That is, excessive provision of information to the remote operator can be reduced. Thus, in an example of the remote driving, the remote operator can more easily concentrate on the remote driving of the vehicle **10**. Further, since the attention is called by the highlighting according to the present embodiment, the number of confirmation points of the remote operator is reduced. This leads to less fatigue for the remote operator.

3. Examples of Displaying Intersection Camera Image for Reference

(81) In the embodiment described above, the intersection camera image itself is not displayed on the display device **23**. However, the intersection camera image may be displayed on the display device **23** as reference information. For example, the intersection camera image may be displayed on a monitor arranged above the monitors **231-233** shown in FIG. **1**. In addition, display/non-display of this kind of intersection camera image may be selectable by the remote operator.

(82) FIGS. **6A** and **6B** are diagrams illustrating examples of the intersection camera image displayed as reference information. In an intersection camera image shown in FIG. **6A**, another vehicle **3** approaching an intersection CR2 is detected as a moving object. Further, in an intersection camera image shown in FIG. **6B**, a pedestrian **4** crossing a crosswalk CW2 and another vehicle **5** traveling on a road away from the intersection CR2 are detected as moving objects. In order to display one or more moving objects detected as described above in an easy-to-understand manner, quadrilateral frames **60**, **62**, and **64** respectively surrounding the another vehicle **3**, the pedestrian **4**, and the another vehicle **5** may be additionally displayed on the corresponding intersection camera image. Furthermore, where the type of each moving object can be determined using the machine learning described above, a mark indicating the type of moving object, such as a pedestrian mark **66** in the example of the pedestrian **4**, may be added.

Claims

1. A display system, comprising: three moving body cameras respectively configured to image a front center, a left front, and a right front of a moving body; one or more intersection cameras installed at an intersection through which the moving body passes, and configured to image a traffic situation in an area of the intersection, and included in one or more camera devices; a display device including a front center screen, a left front screen, and a right front screen respectively configured to display, as images for remote operation of the moving body, moving-body camera

images of the front center, the left front, and the right front of the moving body captured by the three moving body cameras; one or more first processors included in a remote operator terminal; and one or more second processors included in the one or more camera devices, wherein the one or more first processors and the one or more second processors are configured to cooperate to execute a determination process, the determination process includes: the one or more second processors analyze an intersection camera image of the one or more intersection cameras; the one or more second processors determine a moving object information including a flag indicating a presence or absence of a moving object in the intersection camera image, and a position and moving direction of the moving object, based on a result of the analysis of the intersection camera image and information on a position and orientation of the moving body from the remote operator terminal; the one or more second processors transmit the determined moving object information to the remote operator terminal; and the one or more first processors determine whether or not the moving object is included in the intersection camera image based on the determined moving object information from the one or more second processors, the one or more first processors are configured to execute a highlighting process of applying a highlighting to the moving-body camera images when the moving object is included in the intersection camera image, the highlighting indicating whether the moving object is present in a left or right direction with respect to a traveling direction of the moving body, and in the highlighting process, the one or more first processors apply the highlighting to the left front screen or the right front screen corresponding to a direction in which the moving object is present among the left and right directions with respect to the traveling direction.

2. The display system according to claim 1, wherein in the determination process, the one or more second processors set the moving object as a detection target when the moving object is approaching the moving body, and exclude the moving object from the detection target when the moving object is moving away from the moving body.

3. The display system according to claim 1, wherein in the determination process, the one or more second processors change, in accordance with at least one of an angle of view and an installation environment of the one or more intersection cameras, an area in an intersection camera image that is a target of the determination as to whether or not the moving object is included in the intersection camera image.
