

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402275
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Wattier; Joshua D et al.

Universal ruggedized computer system enclosure

Abstract

In one embodiment, an enclosure device for a printed circuit board (PCB) comprises: an enclosure wall structure including therein a heater exchanger, a pipe to direct a cooling liquid through the heat exchanger, and a ducting to direct a gas through the heat exchanger to be cooled by the cooling liquid; and a PCB space adjacent to a portion of the enclosure wall structure for receiving the PCB. The ducting includes a downstream duct disposed downstream of the heat exchanger and extending through the portion of the enclosure wall structure adjacent to the PCB space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the PCB space.

Inventors: Wattier; Joshua D (Champaign, IL), Bidner; Nathaniel J (Champaign, IL)

Applicant: United States of America as Represented by The Secretary of the Army
(Alexandria, VA)

Family ID: 1000008783097

Assignee: UNITED STATES OF AMERICA AS REPRESENTED BY THE SECRETARY
OF THE ARMY (Alexandria, VA)

Appl. No.: 17/957230

Filed: September 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240114653 A1	Apr. 04, 2024

Publication Classification

Int. Cl.: H05K7/20 (20060101); G06F1/18 (20060101); G06F1/20 (20060101)

U.S. Cl.:

CPC **H05K7/20272** (20130101); **G06F1/181** (20130101); **G06F1/182** (20130101);
G06F1/183 (20130101); **G06F1/20** (20130101); **H05K7/20154** (20130101);
H05K7/2039 (20130101); G06F2200/1633 (20130101); G06F2200/201 (20130101);
H05K7/20181 (20130101)

Field of Classification Search

CPC: H05K (7/20272); H05K (7/20154); H05K (7/2039); H05K (7/20181); G06F (1/181);
G06F (1/182); G06F (1/183); G06F (1/20); G06F (2200/1633); G06F (2200/201)

USPC: 361/679.47

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3970292	12/1975	Dachicourt	188/315	B60G 15/12
4646202	12/1986	Hook	361/689	H05K 11/02
4659070	12/1986	Buma	267/64.25	B60G 15/14
5285347	12/1993	Fox	257/714	G06F 1/20
5297005	12/1993	Gourdine	361/695	H05K 7/20154
5718628	12/1997	Nakazato	236/49.5	H05K 7/20745
5808866	12/1997	Porter	174/544	H05K 7/1424
6094351	12/1999	Kikinis	361/728	H05K 7/1438
6115252	12/1999	Ohta	361/689	G06F 1/203
6164369	12/1999	Stoller	165/104.34	H05K 7/20572
6333847	12/2000	Katsui	361/679.55	G06F 1/203
6374627	12/2001	Schumacher	62/263	G06F 1/20
6412292	12/2001	Spinazzola	62/89	G06F 1/206
6438984	12/2001	Novotny	257/E23.098	H05K 7/20172
6494050	12/2001	Spinazzola	62/89	H05K 7/20745
6574104	12/2002	Patel	62/263	H05K 7/20745
6854284	12/2004	Bash	236/49.3	H05K 7/20836
6967842	12/2004	Aoki	165/80.4	H05K 7/20772
7012807	12/2005	Chu	165/80.4	G06F 1/20
7170745	12/2006	Bash	361/695	G06F 1/206
7203063	12/2006	Bash	174/15.1	H05K 7/20772
7212403	12/2006	Rockenfell	361/679.52	G06F 1/20
7405930	12/2007	Hongo	361/679.48	G06F 1/203
7466548	12/2007	Ishikawa	174/15.1	H01L 23/4006
7471509	12/2007	Oliver	361/728	G11B 25/043
7471513	12/2007	Hayashi	361/695	G06F 1/20
7641028	12/2009	Fox	188/278	F16F 9/0236
7675748	12/2009	Matsushima	361/699	G11B 33/1426
7813121	12/2009	Bisson	361/679.53	H05K 7/20736
7878889	12/2010	Day	454/184	H05K 7/20745
7898805	12/2010	MacDonald	361/679.48	G06F 1/203
8184436	12/2011	Campbell	361/701	H05K 7/203
8248793	12/2011	Bash	361/679.48	H05K 7/20781

8713956	12/2013	Couto	165/80.2	G06F 1/1632
8902581	12/2013	Goto	257/722	G06F 1/203
8959941	12/2014	Campbell	361/679.52	H05K 7/20781
10416736	12/2018	Dupont	N/A	H05K 7/20936
11687133	12/2022	Kulkarni	361/679.46	H05K 7/20145
2003/0042004	12/2002	Novotny	257/E23.098	H05K 7/20172
2003/0067745	12/2002	Patel	361/690	H05K 7/20745
2004/0250992	12/2003	Aoki	165/80.4	H05K 7/20727
2005/0217828	12/2004	Tomioka	165/104.31	G06F 1/203
2005/0243518	12/2004	Hata	257/E23.098	G06F 1/203
2006/0162901	12/2005	Aizono	257/E23.098	H01L 23/473
2007/0091567	12/2006	Hayashi	361/695	G06F 1/20
2008/0101017	12/2007	Hata	361/690	G06F 1/20
2008/0239638	12/2007	Chinuki	361/679.07	F16M 11/42
2013/0271905	12/2012	Sullivan	361/679.02	G06F 1/1607

Primary Examiner: Vortman; Anatoly

Background/Summary

BACKGROUND

Field of the Invention

(1) The present invention relates to enclosures for computers and, more specifically, universal ruggedized enclosures for portable computers including, for example, ATX (Advanced Technology extended) systems.

Description of the Related Art

(2) This section introduces aspects that may help facilitate a better understanding of the invention. Accordingly, the statements of this section are to be read in this light and are not to be understood as admissions about what is prior art or what is not prior art.

(3) Enclosures have been used for receiving and supporting motherboards including, for example, ATX and NLX (New Low-profile extended) motherboards. One example is disclosed in U.S. Pat. No. 6,094,351 for UNIVERSAL ENCLOSURE FOR DIFFERENT TYPE MOTHER BOARDS, which is incorporated herein by reference in its entirety.

SUMMARY

(4) The present invention was developed to improve the performance and functionality of an enclosure for housing a PCB (Printed Circuit Board) of a computer. An onboard computer needs to meet requirements for both performance and ruggedization in a variety of applications including, for instance, unmanned ground vehicle robotics. A main problem is that the highest performance computers which can handle heavy software development are meant to sit idle in a desktop environment. COTS ruggedized computers do not meet hardware compute performance requirements for heavy software development, especially with constantly evolving technology in both the hardware and software space. In addition, such rugged computers are often very cost ineffective, do not include the newest hardware available, and are effectively a black box which cannot be upgraded or modified to meet changing hardware requirements.

(5) Research and development have led to a novel universal ruggedized system enclosure that can be used to integrate a high performance non-ruggedized computer and expansion accessories in a rugged environment. One unique problem is that computer components can be outdated within a year or two of being released. A ruggedized computer built with specific components may become

“old technology” by the time it is actually out for production in the field. While there are COTS ruggedized computers, they cannot be fitted with new motherboards or PCIe (Peripheral Component Interconnect Express) expansion cards. Although one may be able to swap the CPU or GPU, such PCU or GPU may have higher requirements for cooling in situations where one cannot actually utilize them in the existing infrastructure.

(6) There are known ways to better ruggedize a desktop style computer such as a sealed pelican case but there are many disadvantages. One obvious disadvantage is that the form factor is quite large compared to a purpose-built ruggedized computer. In addition, they are often sealed from the environment such that while one can water cool some components of the computer, the motherboard still relies on ambient air movement for cooling. In such a case, the air circulating will become increasingly warmer. There are some existing solutions which utilize an air conditioning unit or peltier device for cooling the air inside the case. One drawback here is that the A/C unit requires a lot of space and power and is expensive, the peltier devices used in some cases require a lot of power because they are trying to cool an unnecessarily large space, and the air will not be conditioned to remove moisture which can kill a motherboard in extreme scenarios. With both of these existing solutions, passive water cooling is still needed on several components of the computer. The other drawback of this pelican case is that there is usually very limited shock dampening, so in the case where it is mounted onboard a ground platform which may experience very uneven terrain the components inside of the computer will eventually loosen or break resulting in failure as they were not assembled to see this kind of shock and vibration. Another drawback in integrating a desktop computer on a ground platform is that a large inverter is required to power the computer which already has a built in power supply. The inverter takes valuable space and power delivery is inefficient as it is likely converted from DC to AC back to DC and additional noise is added to the system. In sum, COTS ruggedized computers often do not have enough compute power, are expensive, are not modular to expansion or updates, and often utilize custom motherboards which lead to difficulty in software development. Existing methods to ruggedize existing desktop style computers is space inefficient, power inefficient, and are not known to be able to withstand severely rugged or harsh environments and operation.

(7) Embodiments of the present invention provide a universal ruggedized PCB system enclosure as a solution to ruggedizing a common COTS desktop computer in a compact, easily integrated format. It is composed of a number of components including but not limited to integrated water cooling, a heat exchanger for cooling the ambient circulating air, a positive pressure system which filters particulates and removes moisture from outside air while also providing ingress protection via a constant pressure inside the system, a unique mounting method for PCIe expansion cards for reduced form factor, and protection from shock and vibration. In addition, the enclosure is supported by an adjustable air suspension for extreme shock and vibration protection which can be adjusted based on the contents of the enclosure and the environment of operation.

(8) The system enclosure has one or more of the following features: a universal system enclosure that allows one to take a COTS motherboard and immediately ruggedize, an adjustable suspension for adaptation to differing environments and varying payloads, an inner core that allows for customization of accessories, a unique mounting method for expansion hardware that allows for reduced form factor and enhanced structural integrity, hollow chambers built in the wall for storage of cooling fluid so as to provide insulation and EMI shielding, coolant filled chambers that greatly reduce the form factor by eliminating the need for an external reservoir, integration of a positive pressure and environmental control system, and directed ambient air circulation system with integrated water cooled heat exchanger for heat removal.

(9) The system enclosure may be a universal ruggedized ATX system enclosure. It is a self-contained compact computer enclosure that is universal to housing any ATX style motherboard. The system is sealed from the environment while still providing the necessary features to properly cool and protect the computer and peripherals needed.

(10) An aspect of the present invention is directed to an enclosure device for a printed circuit board (PCB). The enclosure device comprises: an enclosure wall structure including therein a heater exchanger, a pipe to direct a cooling liquid through the heat exchanger, and a ducting to direct a gas through the heat exchanger to be cooled by the cooling liquid; and a PCB space adjacent to a portion of the enclosure wall structure for receiving the PCB. The ducting includes a downstream duct disposed downstream of the heat exchanger and extending through the portion of the enclosure wall structure adjacent to the PCB space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the PCB space.

(11) In some embodiments, a shelf is disposed inside the enclosure device and includes a graphics processing unit (GPU) shelf space for receiving a GPU, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the GPU shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the GPU shelf space. The shelf may include an expansion card shelf space for receiving one or more expansion cards, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the expansion card shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the expansion card shelf space. The shelf may include a power supply shelf space for receiving a power supply, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the power supply shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the power supply shelf space.

(12) In specific embodiments, a positive pressure system is disposed inside the enclosure device to produce a positive pressure inside the enclosure device. The positive pressure system may comprise: a peltier device including a cold side heat sink and a hot side heat sink; a compressor to pull air from inside the enclosure device, compress the air, and push the compressed air across the cold side heat sink; at least one fan to direct air to cool the hot side heat sink; an air filter; and a valve which is openable to allow the compressor to pull air from outside the enclosure through the valve and the air filter.

(13) In some embodiments, at least three (e.g., four) air cylinders are connected to at least three (e.g., four) corresponding exterior locations of the enclosure device. The at least three air cylinders are adjustable to provide independent air suspension to the enclosure device at the at least three corresponding exterior locations.

(14) In accordance with another aspect, an enclosure device for a printed circuit board (PCB) comprises: an enclosure wall structure including therein a heater exchanger, a pipe to direct a cooling liquid through the heat exchanger, and a ducting to direct a gas through the heat exchanger to be cooled by the cooling liquid, the ducting including a downstream duct disposed downstream of the heat exchanger and extending through portions of the enclosure wall structure to direct the cooled gas to the portions of the enclosure wall structure; and a shelf disposed inside the enclosure device and including a plurality of shelf spaces to receive electronic components and position the electronic components adjacent to the portions of the enclosure wall structure to be cooled by the cooled gas flowing through the portions of the enclosure wall structure.

(15) In accordance with another aspect, an enclosure device for a printed circuit board (PCB) comprises: an enclosure wall structure including therein a ducting to direct a cooled gas through portions of the enclosure wall structure; a PCB space adjacent to a portion of the portions of the enclosure wall structure through which the cooled gas is directed by the ducting for receiving the PCB; and a positive pressure system disposed inside the enclosure device to produce a positive pressure inside the enclosure device.

(16) In some embodiment, a shelf is disposed inside the enclosure device and includes a plurality of shelf spaces for receiving electronic components and positioning the electronic components adjacent to the portions of the enclosure wall structure through which the cooled gas is directed by the ducting. The shelf may include one or more of: a graphics processing unit (GPU) shelf space

for receiving a GPU; an expansion card shelf space for receiving one or more expansion cards; or a power supply shelf space for receiving a power supply.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments of the invention will become more fully apparent from the following detailed description, the appended claims, and the accompanying drawings in which like reference numerals identify similar or identical elements.
- (2) FIG. 1 is a perspective view of an enclosure **100** for a computer system including a printed circuit board (PCB) according to an embodiment of the present invention.
- (3) FIG. 2 is a sectional view of an interior of the enclosure of FIG. 1 showing internal ducting and plumbing which is at least partially built into the enclosure wall structure and the upper panel and the lower panel according to an embodiment.
- (4) FIG. 3 is a sectional view of the interior of the enclosure of FIG. 1 showing internal ducting and plumbing without the upper panel and the lower panel according to another embodiment.
- (5) FIG. 4 is a perspective view of the enclosure of FIG. 1 illustrating the enclosure wall structure in which at least a portion of the internal ducting and plumbing is built according to an embodiment.
- (6) FIG. 5 is a perspective view of the internal ducting and plumbing which is at least partially built in the enclosure wall structure of FIG. 4.
- (7) FIG. 6 is an interior sectional view of the internal ducting and plumbing of FIG. 5.
- (8) FIG. 7 is an interior sectional view of an interior of the enclosure of FIG. 1 illustrating components of a positive pressure system including a pump and a peltier device according to an embodiment.
- (9) FIG. 8 is another sectional view of the interior of the enclosure of FIG. 1 illustrating the peltier device and the cooling fan thereof the positive pressure system of FIG. 7.
- (10) FIG. 9 illustrates the positive pressure system of FIG. 7 including (A) a left side view showing a cooling fan, (B) a right side view showing the pump, and (C) a perspective view showing an air filter and the cooling fan thereof.
- (11) FIG. 10 is a side sectional view of the positive pressure system of FIG. 7 illustrating a heat sink and an air filter thereof.
- (12) FIG. 11 is a perspective view of a shelf system for housing computer system components such as GPU or other expansion cars PCIe, power supply, and the like according to an embodiment.
- (13) FIG. 12 is an elevational view of the shelf system of FIG. 11.
- (14) FIG. 13 shows the shelf system of FIG. 11 as installed inside the enclosure.

DETAILED DESCRIPTION

- (15) Detailed illustrative embodiments of the present invention are disclosed herein. However, specific structural and functional details disclosed herein are merely representative for purposes of describing example embodiments of the present invention. The present invention may be embodied in many alternate forms and should not be construed as limited to only the embodiments set forth herein. Further, the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of example embodiments of the invention.
- (16) As used herein, the singular forms “a,” “an,” and “the,” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It further will be understood that the terms “comprises,” “comprising,” “includes,” and/or “including,” specify the presence of stated features, steps, or components, but do not preclude the presence or addition of one or more other features, steps, or components. It also should be noted that in some alternative implementations, the functions/acts noted may occur out of the order noted in the figures. For example, two figures

shown in succession may in fact be executed substantially concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

(17) Embodiments of the present invention provide a universal ruggedized PCB system enclosure as a solution to ruggedizing a common COTS desktop computer in a compact, easily integrated format. It is composed of a number of components including but not limited to integrated water cooling, a heat exchanger for cooling the ambient circulating air, a positive pressure system which filters particulates and removes moisture from outside air while also providing ingress protection via a constant pressure inside the system, a unique mounting method for PCIE expansion cards for reduced form factor, and protection from shock and vibration. In addition, the enclosure is supported by an adjustable air suspension for extreme shock and vibration protection which can be adjusted based on the contents of the enclosure and the environment of operation.

(18) A specific embodiment of the system enclosure is a universal ruggedized ATX system enclosure. It is a self-contained compact computer enclosure that is universal to housing any ATX style motherboard. The system is sealed from the environment while still providing the necessary features to properly cool and protect the computer and peripherals needed.

(19) FIG. 1 is a perspective view of an enclosure **100** for a computer system including a printed circuit board (PCB) according to an embodiment of the present invention. The enclosure **100** has an enclosure wall structure **102** (e.g., front, back, top, and bottom walls) and side panels **104** (right and left) that form a nearly completely sealed system to provide ingress protection of the computer or electronic components inside from objects, water, dust, and accidental contact. The enclosure **100** includes a liquid or water inlet **106** and a liquid or water outlet **108** for flowing a liquid such as water in and out of the enclosure **100** for cooling.

(20) Modular cable glands **110** protruding through the side wall of the enclosure wall structure **102** allow quick cable entry into the computer system inside the enclosure **100** while still providing ingress protection.

(21) An integrated IP rated power bulkhead connector **112** protruding through the side panel **104** is able to accept DC power from a vehicle or other source. This power is sent to the ATX power supply or the like and other components in the system requiring power, including but not limited to, for example, an environmental control unit and various fans.

(22) An adjustable air ride suspension setup provides an air cushion for the computer system. The suspension setup may include a plurality of air cylinders. The embodiment shown in FIG. 1 has four air cylinders **130** connected between four corners of the enclosure and a portable case or the like. In other embodiments, three or more (at least three) air cylinders may be used. The enclosure **100** may include an upper panel **132** and a bottom panel **134**. The air cylinders **130** are connected to four corners of the upper panel **132** in the embodiment shown. The air cylinders **130** are each adjustable independently and easily. The air cylinder pressure can be adjusted on each corner or simultaneously to provide the proper support depending on the mass of the system and the terrain in which operation is to be performed. For example, if multiple GPUs (Graphs Processing Units) were added to the computer, then the system pressure could be boosted to support the additional mass. If the system were going to experience harsh bumps, the pressure could be boosted to better absorb the sudden shock. If only mild on-road conditions were to be experienced, then the pressure could be reduced to better allow suspension travel during small vibrations.

(23) FIG. 2 is a sectional view of an interior of the enclosure of FIG. 1 showing internal ducting and plumbing which is at least partially built into the enclosure wall structure **102** and the upper panel **132** and the lower panel **134** according to an embodiment.

(24) FIG. 3 is a sectional view of the interior of the enclosure of FIG. 1 showing internal ducting and plumbing without the upper panel **132** and the lower panel **134** according to another embodiment.

(25) FIG. 4 is a perspective view of the enclosure **100** of FIG. 1 illustrating the enclosure wall structure **102** in which at least a portion of the internal ducting and plumbing is built according to

an embodiment.

(26) FIG. 5 is a perspective view of the internal ducting and plumbing **500** which is at least partially built in the enclosure wall structure **102** of FIG. 4.

(27) FIG. 6 is an interior sectional view of the internal ducting and plumbing of FIG. 5.

(28) The system lends itself to easy integration and optimization of computer fluid cooling loops and direct air cooling. This is done with the features to be mentioned. Referring to FIGS. 2-6, a fluid reservoir built into the enclosure wall structure **102** of the enclosure **100** also provides additional thermal protection and EMI shielding.

(29) An air-to-water heat exchanger **200** is used to cool the ambient air inside the enclosure **100**. Air flows via one or more air ducts **230** through the heat exchanger **200** to be cooled by a liquid or water that flows through the heat exchanger **200** via liquid piping such as an inflowing pipe **226** with an inlet **236** and an outflowing pipe **228** with an outlet **238**. Additional fluid manifolds may be built into the enclosure wall structure **102** with spill-free quick-disconnect ports (similar to inlet port **236** and outlet port **238**) that provide easy hookup points for additional components or accessories to be fluid cooled.

(30) Air ducting throughout the enclosure wall structure **102** of the enclosure **100** directs air across and underneath the motherboard. The air duct **230** includes an upstream duct portion **231** upstream of the heat exchanger **200** and a downstream duct portion **232** downstream of the heat-exchanger **200**. As best seen in FIGS. 5 and 6, the air duct **230** extends (from the upstream duct portion **231**) along the bottom enclosure wall underneath the motherboard in the motherboard space or CPU space **234** and along the front enclosure wall, the top enclosure wall, and the back enclosure wall. There may be additional outlets directing air from the top down onto the GPU, power supply and any other additional expansion cards or peripherals. One or more fans supply the air movement to the ducting throughout the sealed system. An example is a fan **510** shown in FIGS. 5 and 6.

(31) The system lends itself to easy integration and optimization in rugged environments onboard off-road and on-road vehicles. This is done with the features described above.

(32) FIG. 7 is an interior sectional view of an interior of the enclosure of FIG. 1 illustrating components of a positive pressure system **700** including a pump **702** and a peltier device **704** according to an embodiment.

(33) FIG. 8 is another sectional view of the interior of the enclosure of FIG. 1 illustrating the peltier device and the cooling fan thereof the positive pressure system of FIG. 7.

(34) FIG. 9 illustrates the positive pressure system of FIG. 7 including (A) a left side view showing a cooling fan, (B) a right side view showing the pump, and (C) a perspective view showing an air filter and the cooling fan thereof.

(35) FIG. 10 is a side sectional view of the positive pressure system of FIG. 7 illustrating a heat sink and an air filter thereof.

(36) Referring to FIGS. 7-10, the positive pressure system **700** works in the enclosure **100** for the purpose of conditioning the air therein. The positive pressure system **700** can reduce humidity and thus temperature. It can also prevent introducing particulates into the system even while the enclosure is not 100% sealed from the outside environment. In the embodiment shown, the positive pressure system or subsystem **700** includes a small pump or compressor **702**, a peltier device **704**, one or more cooling fans **706**, an air filter **708**, a valve **710**, and heat sinks **712**, **714**. The pump or compressor **702** pulls air from inside the enclosure **100** and subsequently pushes compressed air across the cold side of a peltier device **704**. The peltier device **704** contains a heat sink **712**, **714** on both the hot side and the cold side. The peltier device **704** removes moisture from the air passing over the cold side heat sink **712**. The moisture is then drained outside the system **700**. The hot side heat sink **714** expels heat outside the enclosure **100**. The hot heat sinks **714** are additionally cooled with fans to improve the efficiency of the dehumidifying process. In addition, there are one or more valves **710** (see FIG. 10) which when opened allows the compressor **702** to pull filtered clean air from outside the enclosure **100**. This would be advantageous when the ambient air inside the

enclosure **100** becomes hotter than the ambient air outside. Lastly, the compressor **702** can produce a low pressure inside of the system while it is sealed. This is done to provide a positive pressure inside of the system which effectively prevents or reduces the ingress of dust, moisture, or other contaminants into the system. The system can be set to trip the peltier device **704** on and off when a specific humidity level is attained.

(37) FIGS. **7-10** show another cooling feature that may also be set up to expel hot ambient air from inside the system when needed. This may be done with a built-in valve **710** that when opened will provide a passage for the fans (e.g., **706**) to force the air out of the system. When this is done, clean outside air is also pulled through the filter **708** into the system.

(38) FIG. **11** is a perspective view of a shelf system **1100** for housing computer system components such as GPU or other expansion cards PCIe, power supply, and the like according to an embodiment.

(39) FIG. **12** is an elevational view of the shelf system **1100** of FIG. **11**.

(40) FIG. **13** shows the shelf system **1100** of FIG. **11** as installed inside the enclosure **100**.

(41) The shelf **1100** may be made of metal such as aluminum to provide a secure mounting location for a variety of computer or electronic components. One example is a full size GPU or other expansion cards that would otherwise be plugged in directly to a motherboard PCIe slot. In rough terrain these cards may otherwise break off or loosen themselves from the PCIe slots. The GPU may be placed in shelf space **1110**. A DC-DC ATX power supply **1122** may be placed in shelf space **1120**. PCIe expansion cards may be placed in shelves **1130**.

(42) In specific embodiments, the air ducting provides air ducts adjacent the shelf system **1100** to cool the GPU, other expansion cards, power supply, and the like. As shown in FIGS. **2-6** and described above, the air duct **230** extends along the bottom enclosure wall of the enclosure wall structure **102** underneath the motherboard space **234** for receiving the motherboard and along the front enclosure wall, the top enclosure wall, and the back enclosure wall. As best seen in FIG. **13**, the GPU shelf space **1110** is disposed adjacent the top enclosure wall and upper portion of the back enclosure wall of the enclosure wall structure **102**. The power supply shelf space **1120** is disposed adjacent the top enclosure wall and the front enclosure wall. The expansion card shelf is disposed adjacent the lower portion of the back enclosure wall. These electronic components may be disposed very close to the enclosure walls or in contact with the portions of the enclosure walls to be cooled by the cooling gas or air flowing through the portions of the enclosure walls.

(43) The DC-DC ATX power supply mounting location may be on the power supply shelf space **1120**. The power supply shelf space **1120** may also act as a large heat sink for the power supply and be placed under directed airflow (e.g., using a fan). This power supply eliminates the need for a large inverter onboard to power a standard AC-DC ATX power supply.

(44) The system is more compact than a standard rack-mount computer case. This is advantageous for integrating into a smaller system or platform. As configured, the enclosure **100** requires about 10 to 35 percent less space than standard rackmount chassis capable of housing an ATX motherboard with a full size dedicated GPU and associated components.

(45) Embodiments of the invention can be manifest in the form of methods and apparatuses for practicing those methods.

(46) Unless explicitly stated otherwise, each numerical value and range should be interpreted as being approximate as if the word “about” or “approximately” preceded the value or range.

(47) Unless otherwise indicated, all numbers expressing quantities of ingredients, properties such as molecular weight, percent, ratio, reaction conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term “about,” whether or not the term “about” is present. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and claims are approximations that may vary depending upon the desired properties sought to be obtained by the present disclosure. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant

digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the disclosure are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements.

(48) It will be further understood that various changes in the details, materials, and arrangements of the parts which have been described and illustrated in order to explain embodiments of this invention may be made by those skilled in the art without departing from embodiments of the invention encompassed by the following claims.

(49) In this specification including any claims, the term “each” may be used to refer to one or more specified characteristics of a plurality of previously recited elements or steps. When used with the open-ended term “comprising,” the recitation of the term “each” does not exclude additional, unrecited elements or steps. Thus, it will be understood that an apparatus may have additional, unrecited elements and a method may have additional, unrecited steps, where the additional, unrecited elements or steps do not have the one or more specified characteristics.

(50) It should be understood that the steps of the exemplary methods set forth herein are not necessarily required to be performed in the order described, and the order of the steps of such methods should be understood to be merely exemplary. Likewise, additional steps may be included in such methods, and certain steps may be omitted or combined, in methods consistent with various embodiments of the invention.

(51) Although the elements in the following method claims, if any, are recited in a particular sequence with corresponding labeling, unless the claim recitations otherwise imply a particular sequence for implementing some or all of those elements, those elements are not necessarily intended to be limited to being implemented in that particular sequence.

(52) All documents mentioned herein are hereby incorporated by reference in their entirety or alternatively to provide the disclosure for which they were specifically relied upon.

(53) Reference herein to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments necessarily mutually exclusive of other embodiments. The same applies to the term “implementation.”

(54) The embodiments covered by the claims in this application are limited to embodiments that (1) are enabled by this specification and (2) correspond to statutory subject matter. Non-enabled embodiments and embodiments that correspond to non-statutory subject matter are explicitly disclaimed even if they fall within the scope of the claims.

Claims

1. An enclosure device for a printed circuit board (PCB), the enclosure device comprising: an enclosure wall structure including therein a heat exchanger, a pipe to direct a cooling liquid through the heat exchanger, and a ducting to direct a gas through the heat exchanger to be cooled by the cooling liquid; and a PCB space adjacent to a portion of the enclosure wall structure for receiving the PCB; the ducting including a downstream duct disposed downstream of the heat exchanger and extending through the portion of the enclosure wall structure adjacent to the PCB space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the PCB space, a shelf disposed inside the enclosure device and including a graphics processing unit (GPU) shelf space for receiving a GPU, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the GPU shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the GPU shelf space, wherein the positive pressure system

- comprises: a peltier device including a cold side heat sink and a hot side heat sink; a compressor to pull air from inside the enclosure device, compress the air, and push the compressed air across the cold side heat sink; at least one fan to direct air to cool the hot side heat sink; an air filter; and a valve which is openable to allow the compressor to pull air from outside the enclosure through the valve and the air filter.
2. The enclosure device of claim 1, further comprising: at least three air cylinders connected to at least three corresponding exterior locations of the enclosure device, the at least three air cylinders being adjustable to provide independent air suspension to the enclosure device at the at least three corresponding exterior locations.
 3. The enclosure device of claim 1, wherein a shelf disposed inside the enclosure device includes an expansion card shelf space for receiving one or more expansion cards, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the expansion card shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the expansion card shelf space.
 4. The enclosure device of claim 1, wherein a shelf disposed inside the enclosure device includes a power supply shelf space for receiving a power supply, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the power supply shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the power supply shelf space.
 5. The enclosure device of claim 1, further comprising: a positive pressure system disposed inside the enclosure device to produce a positive pressure inside the enclosure device.
 6. An enclosure device for a printed circuit board (PCB), the enclosure device comprising: an enclosure wall structure including therein a heat exchanger, a pipe to direct a cooling liquid through the heat exchanger, and a ducting to direct a gas through the heat exchanger to be cooled by the cooling liquid, the ducting including a downstream duct disposed downstream of the heat exchanger and extending through portions of the enclosure wall structure to direct the cooled gas to the portions of the enclosure wall structure; and a shelf disposed inside the enclosure device and including a plurality of shelf spaces to receive electronic components and position the electronic components adjacent to the portions of the enclosure wall structure to be cooled by the cooled gas flowing through the portions of the enclosure wall structure, a positive pressure system disposed inside the enclosure device to produce a positive pressure inside the enclosure device, wherein the positive pressure system comprises: a peltier device including a cold side heat sink and a hot side heat sink; a compressor to pull air from inside the enclosure device, compress the air, and push the compressed air across the cold side heat sink; at least one fan to direct air to cool the hot side heat sink; an air filter; and a valve which is openable to allow the compressor to pull air from outside the enclosure through the valve and the air filter.
 7. The enclosure device of claim 6, further comprising: at least three air cylinders connected to at least three corresponding exterior locations of the enclosure device, the at least three air cylinders being adjustable to provide independent air suspension to the enclosure device at the at least three corresponding exterior locations.
 8. The enclosure device of claim 6, wherein the shelf disposed inside the enclosure device includes a graphics processing unit (GPU) shelf space for receiving a GPU, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the GPU shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the GPU shelf space; and wherein the downstream duct extends through a bottom enclosure wall portion of the enclosure wall structure to provide a PCB space above the bottom enclosure wall portion for receiving the PCB.
 9. The enclosure device of claim 6, wherein the shelf disposed inside the enclosure device includes an expansion card shelf space for receiving one or more expansion cards, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the expansion

card shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the expansion card shelf space.

10. The enclosure device of claim 6, wherein the shelf disposed inside the enclosure device includes a power supply shelf space for receiving a power supply, the downstream duct of the ducting extending through a portion of the enclosure wall structure adjacent to the power supply shelf space to direct the cooled gas to the portion of the enclosure wall structure adjacent to the power supply shelf space.

11. An enclosure device for a printed circuit board (PCB), the enclosure device comprising: an enclosure wall structure including therein a ducting to direct a cooled gas through portions of the enclosure wall structure: a PCB space adjacent to a portion of the enclosure wall structure through which the cooled gas is directed by the ducting for receiving the PCB; and a positive pressure system disposed inside the enclosure device to produce a positive pressure inside the enclosure device wherein the positive pressure system comprises: a peltier device including a cold side heat sink and a hot side heat sink; a compressor to pull air from inside the enclosure device, compress the air, and push the compressed air across the cold side heat sink; at least one fan to direct air to cool the hot side heat sink; an air filter; and a valve which is openable to allow the compressor to pull air from outside the enclosure through the valve and the air filter.

12. The enclosure device of claim 11, further comprising: a shelf disposed inside the enclosure device and including a plurality of shelf spaces for receiving electronic components and positioning the electronic components adjacent to the portions of the enclosure wall structure through which the cooled gas is directed by the ducting.

13. The enclosure device of claim 12, wherein the shelf includes one or more of: a graphics processing unit (GPU) shelf space for receiving a GPU; an expansion card shelf space for receiving one or more expansion cards; or a power supply shelf space for receiving a power supply.

14. The enclosure device of claim 11, wherein the enclosure wall structure further includes therein a heat exchanger and a pipe to direct a cooling liquid through the heat exchanger; and wherein the ducting is configured to direct a gas through the heat exchanger to be cooled by the cooling liquid, the ducting including a downstream duct disposed downstream of the heat exchanger and extending through portions of the enclosure wall structure to direct the cooled gas to the portions of the enclosure wall structure.

15. The enclosure device of claim 11, further comprising: at least three air cylinders connected to at least three corresponding exterior locations of the enclosure device, the at least three air cylinders being adjustable to provide independent air suspension to the enclosure device at the at least three corresponding exterior locations.
