

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408725
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Birnbaum; Bernardo

Insole

Abstract

A shoe insole comprising a cut out that follows the projection of the metatarsal area, said insole made out of a rigid material, and with a first predetermined thickness so that a user's weight is transmitted to the user's toes and calcaneal anterior area while minimizing the weight applied to the metatarsal area.

Inventors:	Birnbaum; Bernardo (Miami, FL)
Applicant:	Birnbaum; Bernardo (Miami, FL)
Family ID:	96950302
Appl. No.:	17/723173
Filed:	April 18, 2022

Publication Classification

Int. Cl.: A43B7/145 (20220101); A43B3/00 (20220101); A43B7/149 (20220101)

U.S. Cl.:

CPC A43B3/0036 (20130101); A43B7/145 (20130101); A43B7/149 (20130101);

Field of Classification Search

CPC: A43B (3/0057); A43B (13/10); A43B (13/183); A43B (17/00); A43B (17/003); A43B (17/14); A43B (3/0036)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2129588	12/1937	Nickerson	36/76R	A43B 23/22
2909854	12/1958	Edelstein	36/43	A43B 7/1425
3999558	12/1975	Barnwell	36/145	A43B 7/142
5204173	12/1992	Canary	162/146	D21H 13/14
5438768	12/1994	Bauerfeind	36/43	A43B 7/1445
5768803	12/1997	Levy	36/43	A43B 17/02
6026599	12/1999	Blackwell	36/43	A43B 7/14
6038790	12/1999	Pyle	36/28	A43B 7/144
6199303	12/2000	Luthi	36/31	A43B 7/1425
7980006	12/2010	Aveni	36/114	A43B 21/36
2007/0033834	12/2006	Cheskin	36/28	A43B 7/223
2013/0081306	12/2012	Park	36/43	A43B 17/14
2015/0289584	12/2014	Nurse	36/89	A43B 3/0031
2017/0105482	12/2016	Smaniotto	N/A	A43B 17/006
2018/0000196	12/2017	Lovell	N/A	A43B 7/148
2018/0027922	12/2017	Orand	N/A	A43B 13/141
2018/0168281	12/2017	Case	N/A	A43B 13/185
2021/0112920	12/2020	Dinshaw	N/A	B33Y 80/00
2021/0298412	12/2020	Takahashi et al.	N/A	N/A
2022/0273070	12/2021	Head	N/A	A43B 13/125

Primary Examiner: Bravo; Jocelyn

Attorney, Agent or Firm: Sanchelima & Associates, P.A.

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to insoles and, more particularly, to an insole that shifts the weight of a user away from the metatarsal area and towards the front of the insole to coincide with the user's toes.

2. Description of the Related Art

(2) Several designs for insoles have been designed in the past. None of them, however, are designed to shift the user's weight toward his or her toes from the metatarsal area. Some conditions, like the Morton neuroma, involves the inflammation of the metatarsal area. Applying pressure (the user's weight) in that area results in pain and further aggravation of the condition. The present invention resolves this problem.

(3) Applicant believes that a related reference corresponds to U.S. Pub. No. US2021/0298412A1 issued for Shoe Insole published on Sep. 30, 2021. However, as it is disclosed in paragraphs 0066 and 0067, the reference teaches away from the invention by trying to avoid the application of the user's weight in his or her toes.

(4) Other documents describing the closest subject matter provide for a number of more or less complicated features that fail to solve the problem in an efficient and economical way. None of these patents suggest the novel features of the present invention.

SUMMARY OF THE INVENTION

(5) It is one of the objects of the present invention to provide an insole that diverts the user's weight

towards his or her toes relieving the metatarsal area from pressure.

(6) It is yet another object of this invention to provide such an insole that is inexpensive to implement and maintain while retaining its effectiveness.

(7) Further objects of the invention will be brought out in the following part of the specification, wherein detailed description is for the purpose of fully disclosing the invention without placing limitations thereon.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) With the above and other related objects in view, the invention consists in the details of construction and combination of parts as will be more fully understood from the following description, when read in conjunction with the accompanying drawings in which:

(2) FIG. 1 represents a top view of the insole subject of the present application.

DETAILED DESCRIPTION OF THE EMBODIMENTS OF THE INVENTION

(3) Referring now to the drawings, where the present invention is generally referred to with numeral **10**. The forefoot section **40** of insole **10** includes the projected areas of the phalanx bones and metatarsal bones two through five. A bay or cutout **20** in forefoot section **40** coincides with the user's metatarsal and phalanx projected areas except the distal phalanx bones projected end area **50**. End area **50** has a peninsular shape for cooperatively supporting the underside of a user's toes' distal phalanx bones receiving most of his/her weight.

(4) The thickness of insole **10** extends at a constant thickness continuously from hindfoot section **60** to midfoot section **70** and lastly forefoot section **40**. Insole **10** is made out of rigid material. Optionally, a soft cushion **80** can mounted to insole **10** to cover cutout **20** provided that no significant weight is applied to the metatarsal area.

(5) It should be understood there are modifications and variations of the invention that are too numerous to be listed but that all fit within the scope of the invention. Also, singular words should be read as plural and vice versa and masculine as feminine and vice versa, where appropriate, and alternative embodiments do not necessarily imply that the two are mutually exclusive.

(6) The foregoing description conveys the best understanding of the objectives and advantages of the present invention. Different embodiments may be made of the inventive concept of this invention. It is to be understood that all matter disclosed herein is to be interpreted merely as illustrative, and not in a limiting sense.

Claims

1. A shoe insole configured to be worn by a wearer, the insole comprising: a forefoot section; a midfoot section; and a hindfoot section; wherein said insole is made of a rigid material and includes a first predetermined thickness; wherein said forefoot section comprises a bay that extends directly from a lateral edge of the forefoot section towards a medial portion of the forefoot section and extends through the entire thickness of the insole, removing a portion of said insole that is configured to underlie the wearer's second through fifth proximal phalanges and a forward portion of the wearer's second through fifth metatarsal bones; wherein said forefoot section further comprises a toe end portion directly adjacent to the bay, the toe end portion having a peninsular shape that is configured to underlie the wearer's first through fifth distal phalanges, wherein the toe end portion includes a plurality of rounded portions configured to respectively correspond to each of the wearer's first through fifth distal phalanges; wherein, when the insole is used, the user's

weight is transmitted to the user's distal phalanges and the user's anterior calcaneal area, while minimizing the weight applied to the user's metatarsal area.
