

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408769
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Kelsch; Christopher A. et al.

Anti-theft bracket with a compression gap

Abstract

An anti-theft device for securing an article of merchandise against unauthorized removal from a display counter. The anti-theft device includes two mating bracket members. Each bracket member includes a lip configured to engage a lateral side of the article of merchandise. The bracket members are configured to be independently placed onto the opposite lateral sides of the article of merchandise and then coupled together. The collective length of the bracket members is less than the distance between the lateral sides of the article of merchandise, thus creating a gap between the bracket members when the article of merchandise is initially received therein. A fastener connecting the bracket members together is operated to reduce the width of the gap, thereby causing the bracket members to exert compressive forces onto the lateral sides of the article of merchandise.

Inventors: Kelsch; Christopher A. (Palm Harbor, FL), Zhu; Wade (Land O' Lakes, FL), Eckert; Lee (Sarasota, FL)

Applicant: Kelsch; Christopher A. (Palm Harbor, FL); Vanguard Products Group, Inc. (Oldsmar, FL)

Family ID: 96950330

Assignee: Vanguard Products Group, Inc. (Oldsmar, FL)

Appl. No.: 18/446891

Filed: August 09, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17707512 20220329 US 12258792 child-doc US 18446891
us-provisional-application US 63167420 20210329

Publication Classification

Int. Cl.: E05B73/00 (20060101); A47F7/024 (20060101)

U.S. Cl.:

CPC A47F7/0246 (20130101); E05B73/0082 (20130101);

Field of Classification Search

CPC: E05B (73/0005); E05B (73/0017); E05B (73/0023); E05B (73/0082); A47F (7/0246)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8711553	12/2013	Trinh	361/679.02	E05B 73/0082
11015626	12/2020	Leyden	N/A	E05B 73/0082
11122917	12/2020	Chapuis	N/A	F16M 11/041
11178983	12/2020	Kelsch	N/A	A47F 7/024
11236528	12/2021	Berglund	N/A	E05B 73/0082
11553790	12/2022	Gulick	N/A	F16M 13/022
11680428	12/2022	Chapuis	248/551	F16M 11/22
11739568	12/2022	Penny	248/551	G06F 1/166
12049981	12/2023	Horvath	N/A	F16M 11/08
2023/0313568	12/2022	Gulick, Jr.	248/551	F16B 2/10

Primary Examiner: Fulton; Kristina R

Assistant Examiner: Horowitz; Noah

Attorney, Agent or Firm: Hill Ward Henderson, P.A.

Background/Summary

PRIORITY CLAIM (1) This non-provisional patent application is a continuation-in-part of and claims priority to U.S. Non-Provisional patent application Ser. No. 17/707,512 filed on Mar. 29, 2022, which claims priority to U.S. Provisional Patent Application No. 63/167,420 filed on Mar. 29, 2021, which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) This invention relates to merchandise anti-theft devices. More specifically, it relates to a non-obtrusive anti-theft device for securing merchandise against theft, while leaving at least one lateral side of the merchandise unobstructed.

2. Brief Description of the Related Art

(2) Retailers often prefer to present their merchandise to consumers in a way that allows the consumers to touch, inspect, and otherwise interact with the products at a display counter. Many merchandise items, especially portable electronic devices, are relatively expensive and, therefore, are under a serious threat of theft. Retailers often face a dilemma pertaining to how to interactively display their merchandise to attract customers and increase sales, while, at the same time,

safeguarding the merchandise against theft.

(3) Currently available anti-theft solutions generally involve obtrusive and aesthetically unattractive devices such as bulky brackets, steel cables, locks, and casings. Although these security measures may effectively protect against theft, they have a negative effect on the consumer shopping experience by discouraging interaction with products and may ruin the overall ambiance of a retail store. Furthermore, anti-theft devices for electronic merchandise, such as smartphones and tablets, must not interfere with the functional features of the merchandise.

(4) Traditional anti-theft brackets retain merchandise by at least partially capturing all four lateral sides thereof, thereby immobilizing the merchandise within the bracket. This type of anti-theft device, however, is not suitable to secure foldable, rollable, or expandable electronic gadgets. Because traditional anti-theft devices capture all lateral sides of the electronic gadget, such traditional anti-theft device would interfere with the hinge or other type of expandable mechanism of the merchandise. Thus, what is needed is a non-obtrusive anti-theft bracket configured to immobilize merchandise while leaving at least one of its lateral edges unobstructed.

SUMMARY OF THE INVENTION

(5) The unresolved need stated above is now met by a novel and non-obvious invention disclosed and claimed herein. In an embodiment, the invention pertains to an anti-theft device for securing an article of merchandise—for example, an electronic gadget such as a smartphone or a tablet. The anti-theft device is especially adapted for securing of foldable, rollable, or expandable electronic gadgets, although the applications of the anti-theft device are not limited to these types of articles of merchandise.

(6) In an embodiment, the anti-theft device comprises a two-part bracket assembly having a first bracket member and a second bracket member. The first bracket member has a first lip configured to receive a lateral side of the article of merchandise. When the lip of the first bracket member receives a lateral side of the article of merchandise, the first bracket member contacts both a back surface and a front surface of the article of merchandise.

(7) The second bracket member has a second lip. The second lip is configured to receive a second lateral side of the article of merchandise therein such that the second bracket member contacts both the back surface and the front surface of the article of merchandise. The first lip of the first bracket member and the second lip of the second bracket member may be configured to engage opposite lateral sides of the article of merchandise.

(8) To secure the article of merchandise, the first bracket member is coupled to the article of merchandise by receiving the first lateral side thereof into the first lip and receiving the protruding feature of the article of merchandise into the first aperture. The second bracket member is coupled to the article of merchandise by receiving the second lateral side of the article of merchandise into the second lip. Each bracket member has a length defined as a normal distance between an inner surface of the lip of the bracket member and the opposite edge of that bracket member. The sum of the lengths of the first and the second bracket members is less than a distance between the lateral sides of the article of merchandise received within the first and the second bracket members. In this manner, a gap is present between the first bracket member and the second bracket member when the first lip is in receipt of the first lateral side of the article of merchandise and the second lip is in receipt of the second lateral side thereof.

(9) Next, the first and the second bracket members are configured to be coupled together using a fastener, collectively forming a bracket assembly. Operation of the fastener reduces the width of the gap between the first and the second bracket members, thereby causing the first lip and the second lip to exert compressive forces onto the lateral sides of the article of merchandise received therein. The fastener retains the first and the second bracket members in the coupled configuration. To release the article of merchandise from the bracket assembly, the fastener must be operated to restore the gap between the bracket members to its original width.

(10) The first bracket member may further have an aperture configured to receive a protruding

feature (for example, a camera lens module) of the article of merchandise. Engagement between the outer contour of the protruding feature and the inner contour of the aperture restricts the article of merchandise against relative movement with respect to the first bracket member in a plane parallel to a front and back surfaces of the article of merchandise. To achieve a precise alignment and fit between the protruding feature of the article of merchandise and the aperture of the bracket assembly, the bracket assembly may be custom-made to correspond to the exact dimensions and shape of the specific article of merchandise being secured.

(11) In an embodiment, the article of merchandise has four lateral sides—top, bottom, left, and right—and when the bracket assembly is coupled to the article of merchandise, at least one of four lateral sides is unobstructed by the bracket assembly. The unobstructed lateral side may have a hinge, or another type of mechanical connector, configured to enable the article of merchandise to transition between a closed configuration and an open or expanded configuration.

(12) The first bracket member and/or the second bracket member may comprise an additional aperture configured to receive a cable coupled to the article of merchandise. The engagement between the cable connector and the additional aperture may be utilized to further immobilize the article of merchandise relative the bracket assembly.

(13) Furthermore, the first bracket member may include a first mounting block part and the second bracket member may include a complementary second mounting block part. When the first and the second bracket members are coupled together, the first and the second mounting block parts collectively form a mounting block, which may be used to couple the bracket assembly to a pedestal. The mounting block may be centered relative to the bracket assembly to enable centered display of the article of merchandise in a closed or folded configuration. Alternatively, the mounting block may be offset relative to the bracket assembly, enabling centered display of the article of merchandise in an open/expanded configuration.

Description

DESCRIPTION OF THE DRAWINGS

(1) For a fuller understanding of the invention, reference should be made to the following detailed description, taken in connection with the accompanying drawings, in which:

(2) FIG. 1A is a perspective front view of a first embodiment of the anti-theft device securing an article of merchandise.

(3) FIG. 1B is a perspective back view of the first embodiment of the anti-theft device securing the article of merchandise.

(4) FIG. 2A is a perspective front view of the first embodiment of the bracket assembly in an uncoupled configuration.

(5) FIG. 2B is a perspective front view of the first embodiment of the bracket assembly in a coupled configuration.

(6) FIG. 3 is perspective back view of the first embodiment of the bracket assembly in a coupled configuration.

(7) FIG. 4A is a perspective front view of a second embodiment of the anti-theft device securing an article of merchandise.

(8) FIG. 4B is a perspective back view of the second embodiment the anti-theft device securing the article of merchandise.

(9) FIG. 5A is a perspective front view of the second embodiment of the bracket assembly in an uncoupled configuration.

(10) FIG. 5B is a perspective front view of the second embodiment to of the bracket assembly in a coupled configuration.

(11) FIG. 6A is a perspective front view depicting an uncoupled configuration of a bracket

assembly with an offset mounting platform.

(12) FIG. 6B is a perspective front view depicting an article of merchandise in a closed configuration mounted to a pedestal via the offset mounting block.

(13) FIG. 6C is a perspective front view depicting the article of merchandise in an unfolded configuration centrally positioned relative to the pedestal.

(14) FIG. 7A is a side view depicting an embodiment of the bracket assembly in which the distance between the opposite lateral sides of the article of merchandise exceeds the collective length of the two bracket members, resulting in a gap therebetween when initially deployed over the article of merchandise.

(15) FIG. 7B is a side view depicting the article of merchandise being received into the bracket assembly with a fastener connecting the first and the second bracket members.

(16) FIG. 7C is a side view depicting the fastener being used to reduce the width of the gap between the first and the second bracket members, thereby causing the first and the second bracket members to apply compressive forces onto the lateral sides of the article of merchandise.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(17) In the following detailed description of the preferred embodiment, reference is made to the accompanying drawings, which form a part hereof, and within which specific embodiments are shown by way of illustration by which the invention may be practiced. It is to be understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the invention.

(18) FIGS. 1-3 depict an embodiment of an anti-theft device having a two-part, non-obtrusive bracket assembly **12** configured to secure an article of merchandise **14**—for example, a smartphone or a tablet. FIGS. 1A and 1B depict article of merchandise **14** having four lateral sides: top, bottom, left, and right. In the embodiment depicted in FIGS. 1A and 1B, bracket assembly **12** engages front and rear surfaces of article of merchandise **14** and, also, engages top, bottom, and left lateral sides of article of merchandise **14**, while the right lateral side remains unobstructed.

(19) In this embodiment, bracket assembly **12** comprises a first bracket member **16** and a second bracket member **18**. First bracket member **16** has a lip **20**. FIG. 1A depicts that lip **20** is configured to receive the top and left lateral sides of article of merchandise **14**. When these lateral sides are positioned within lip **20**, the edge of lip **20** engages the front surface of article of merchandise **14**. FIG. 1A further depicts that lip **20** may have cutouts **21** configured to accommodate features of article of merchandise **14**, such as a power button, volume rocker, a camera lens, a light emitting diode (LED), etc.

(20) FIG. 1B depicts that first bracket member **16** has an aperture **22** configured to receive a protruding feature **24** of article of merchandise **14**, for example a camera lens module. As explained in more detail below, when protruding feature **24** resides within aperture **22** of first bracket member **16**, engagement between protruding feature **24** and aperture **22** immobilizes first bracket member **16** and article of merchandise **14** against movement relative to one another in the x-y plane (plane parallel to the front and back surfaces of article of merchandise **14**).

(21) FIG. 1A further depicts second bracket member **18** having a lip **26** configured to receive the portion of the left lateral side of article of merchandise **14** that is not secured by first bracket member **16**. Lip **26** also receives the bottom lateral side of article of merchandise **14**. In this embodiment, second bracket member **18** is configured to attach to article of merchandise **14** by capturing a power connector inserted into a power port thereof. This functionality is achieved due to second bracket member **18** having a recess **30** configured to receive the power connector. Furthermore, recess **30** may have a neck **32**, which is sufficient to permit passage of a power cable but not the power connector. In this manner, the power connector is immobilized within recess **30** and cannot be disconnected from article of merchandise **14** when second bracket member **18** is attached thereto.

(22) By immobilizing the power connector, bracket assembly **12** provides an additional securement

point between article of merchandise **14** and bracket assembly **12**. Attempts to remove article of merchandise from **14** from bracket assembly **12** while the power connector is positioned within recess **30** and plugged into article of merchandise **14** will result in extensive damage to article of merchandise **14**, significantly diminishing its value. In other words, the power port retention feature is used both for physical securement and, also, as a means of theft deterrent through benefit denial. (23) As depicted in FIGS. **1A** and **1B**, when first bracket member **16** and second bracket member **18** are positioned onto article of merchandise **14**, first bracket member **16** and second bracket member **18** are configured to be coupled together, forming bracket assembly **12**. FIGS. **1A** and **1B** depict that bracket assembly **12** engages the rear and front surfaces of article of merchandise **14**, thereby immobilizing article of merchandise **14** relative to bracket assembly **12** in the z-axis (the axis normal to the front surface of article of merchandise **14**). Bracket assembly **12** also partially captures the top and the bottom lateral sides of article of merchandise **14**, thereby immobilizing article of merchandise **14** against relative movement in a direction of the y-axis.

(24) With respect to the relative movement in a direction of the x-axis, lip **20** and lip **26** of first and second bracket members **16** and **18** capture the left edge of article of merchandise **14**, thereby immobilizing article of merchandise **14** against relative movement in the left direction of the x-axis. Finally, engagement between protruding feature **24** of article of merchandise **14** and aperture **22** of first bracket member **16** restrains relative movement of article of merchandise **14** relative to bracket assembly **12** in the x-y plane (including the right direction along the x-axis), without obstructing the right edge of article of merchandise **14**. In the embodiment depicted in FIG. **1B**, aperture **22** receives a protruding camera lens module positioned on the rear surface of article of merchandise **14**. The precise engagement between the outer contour of protruding feature **24** and the inner contour of aperture **22** ensures that bracket assembly **12** cannot be removed from article of merchandise **14** through application of a force in the x-y plane. In addition, engagement between power connector and recess **30** further secures bracket assembly **12** to article of merchandise **14** in the direction of the x-axis.

(25) FIGS. **1A** and **1B** depict that first bracket member **16** and second bracket member **18** have complementary features that interface together forming a mounting block **28**. Mounting block **28** may be used to anchor bracket assembly **12** to a designated pedestal positioned within the retail store. In this manner, bracket assembly **12** securely attaches article of merchandise **14** to a display counter. As explained above, article of merchandise **14** cannot be removed from bracket assembly **12** without decoupling first bracket member **16** and second bracket member **18** from one another. When bracket assembly **12** is attached to a pedestal, the fasteners coupling first bracket member **16** and second member **18** may be concealed and/or may require a specialized tool, thereby providing an additional layer of security.

(26) FIG. **2A** depicts first bracket member **16** and second member **18** in a decoupled configuration. Because bracket assembly **12** comprises two separate bracket members, each bracket member can be placed onto the merchandise independently, enabling aperture to be positioned over protruding feature **24** and lip **20** to receive the top lateral of article of merchandise **14**, while lip **26** receives the bottom lateral side. After first bracket member **16** and second bracket member **18** are independently positioned onto article of merchandise **14**, their mating surfaces abut one another, enabling them to be coupled together, as depicted in FIG. **2B**. In an embodiment, first bracket member **16** and/or second member **18** may have threaded holes **38** configured to receive fasteners **40** therein, thereby securely coupling first and second bracket members **16** and **18** together, thereby forming bracket assembly **12**.

(27) FIG. **3** depicts a perspective rear view of bracket assembly **12**. This view shows a slot **34** and an opening **36** disposed within second bracket member **18**. Opening **36** is structured to be sufficiently large to permit passage of the power connector therethrough, while slot **34** permits the power connector to enter recess **30**, wherein the power connector is secured within recess **30** by neck **32**. In a decoupled configuration, second bracket member **18** can be attached to article of

merchandise **14** by aligning second bracket member **18** with article of merchandise **14** in the direction of x-axis and then sliding article of merchandise **14** downward relative to second bracket member **18**, such that the power connector enters the corresponding power port of article of merchandise **14**. At this point, second bracket member **18** is immobilized relative to article of merchandise **14** against relative movement. Neck **32** of recess **30** ensures that the power connector cannot be unplugged from article of merchandise **14** while second member **18** remain coupled thereto.

(28) After bracket members **16** and **18** are positioned to capture their respective features, bracket members **16** and **18** are coupled together using fasteners, adhesive, or any other coupling means known in the art. After brackets members **16** and **18** are coupled together, article of merchandise **14** is immobilized against movement in all directions relative to bracket assembly **12**. In this manner, article of merchandise **14** cannot be removed from bracket assembly **12** until first and second bracket members **16** and **18** are separated from one another.

(29) FIGS. **4-6** depict another embodiment of the anti-theft bracket. FIGS. **4A** and **4B** depict that, in this embodiment, bracket assembly **42** is configured to secure a foldable article of merchandise **44**—for example, a foldable smartphone. To allow article of merchandise **44** to close and open, bracket assembly **42** must not obstruct, or otherwise interfere with, a hinge **45** positioned at the left lateral side of article of merchandise **44**. For this reason, bracket assembly **42** captures only the right, the top, and the bottom lateral sides of article of merchandise **44**, leaving the left lateral side unobstructed.

(30) Analogously to the explanation provided for the embodiment depicted in FIGS. **1-3**, to effectively secure article of merchandise **44**, bracket assembly **42** must immobilize article of merchandise **44** against all relative movement in relation thereto. To that end, bracket assembly **42** comprises a first bracket member **46** having a lip **50** configured to receive the top lateral side of article of merchandise **44**. Lip **50** has an edge configured to engage the front surface of article of merchandise **44** when first bracket member **46** is positioned thereon. Thus, because first bracket member **46** simultaneously engages the front and the rear surfaces of article of merchandise **44**, first bracket member **46** immobilizes article of merchandise **44** against relative movement in the direction of the z-axis. First bracket member **46** further comprises an aperture **52** configured to receive a protruding feature **54** of article of merchandise **44**. Engagement between aperture **52** and protruding feature **54** immobilizes article of merchandise **44** against relative movement in the x-y plane relative to first bracket member **46**.

(31) Bracket assembly **42** further comprises second bracket member **48**. Second bracket member **48** has a lip **56** configured to receive the bottom and right lateral sides of article of merchandise **44**. In this manner, second bracket member **48** immobilizes article of merchandise **44** against relative movement in the downward direction along the y-axis and the right direction along the x-axis.

(32) FIG. **5A** depicts a decoupled configuration of bracket assembly **42**. To secure article of merchandise **44**, first bracket member **46** and second bracket member **48** must be positioned onto article of merchandise **44** independently. First bracket member **46** is positioned such that lip **50** receives the top lateral side of article of merchandise **44** and aperture **52** receives protruding feature **54**. Second bracket member **48** is positioned such that lip **56** receives the bottom lateral side and right lateral side of article of merchandise **44**. At this point, mating edges of first bracket member **46** and second bracket member **48** contact one another and can be coupled together, using one or more fasteners, adhesive, electromagnets, or any other coupling means known in the art. To that end, first bracket member **46** and/or second bracket member **48** may include threaded holes **58** configured to receive fasteners **60**.

(33) After first bracket member **46** and second bracket member **48** are coupled together, article of merchandise **44** is immobilized within bracket assembly **42**. Edges of lip **50** and lip **56** engage front surface of article of merchandise **44**, thereby immobilizing article of merchandise against movement relative to bracket assembly **42** in the direction of z-axis. Likewise, because lip **50** and

lip 56 engage top and bottom lateral edges of article of merchandise 44, article of merchandise 44 is immobilized against relative movement in the direction of y-axis. Finally, bracket assembly 42 immobilizes article of merchandise 44 against relative movement in the x-y plane by capturing protruding feature 54 of article of merchandise 44 into aperture 52. In this manner, bracket assembly 42 is configured to secure article of merchandise 44 without interfering with the functionality of hinge 45.

(34) FIG. 4B further depicts that bracket assembly 42 may include a mounting block 62. After article of merchandise 44 is secured within bracket assembly 42, mounting block 48 can be coupled to a pedestal for display in a retail environment. Because bracket assembly 42 is designed to capture protruding feature 56 (or a cavity/port) of article of merchandise 44, bracket assembly 42 does not need to capture all lateral sides of article of merchandise 44. In this manner, bracket assembly 42 enables attractive and non-obtrusive presentation of article of merchandise 44, without interfering with its functionality. Furthermore, because bracket assembly 42 leaves at least one lateral side of article of merchandise 44 unobstructed, bracket assembly 42 does not interfere with the folding, rolling, or sliding functionality of the merchandise.

(35) FIG. 4B depicts that mounting block 62 is centered relative to bracket assembly 42. This configuration enables article of merchandise 44 to be displayed in a centered configuration relative to the pedestal when article of merchandise 44 is in a closed configuration. FIGS. 6A-6C depict a variant of bracket assembly 42, in which mounting block 62 is offset relative bracket assembly 42. This embodiment is configured to mount article of merchandise 44 relative to pedestal 64 in a position that centers article of merchandise 44 relative to pedestal 64 when article of merchandise 44 is in its unfolded configuration, as depicted in FIG. 6C. In this manner, store personnel may select a variant of bracket assembly 42 based on the display preferences and needs of a specific retail store.

(36) Compression Gap

(37) FIGS. 1A and 1B depict a gap at the interface between the bracket members 16 and 18. This gap is referred to herein as a compression gap 19 and is illustrated in more detail in FIGS. 7A and 7B. In an embodiment of the bracket assembly, the compression gap 19 is formed due to the length of the article of merchandise 14 exceeding the distance between the inner surfaces of the lip 20 and the lip 26 when the first and the second bracket members 16 and 18 are brought into an abutting contact with one another. In other words, the distance between the opposite lateral sides of the article of merchandise 14 received within the lip 20 and the lip 26 exceeds the sum of the distance $d_{sub.1}$, which is a normal distance from the inner surface of lip 20 to the opposite edge of the first bracket member 16, and the distance $d_{sub.2}$, which is a normal distance from the inner surface of the lip 26 to the opposite edge of the second bracket member 18. FIG. 7A depicts that the length of the article of merchandise 14 exceed the sum of the distances $d_{sub.1}$ and $d_{sub.2}$ by a distance $d_{sub.3}$, which is the width of the compression gap 19.

(38) FIGS. 7B and 7C depict a fastener 40 connecting the first bracket member 16 and the second bracket member 18. As the fastener 40 is threaded into the bracket members 16 and 18, the width of the compression gap 19 is reduced or eliminated, thereby decreasing the distance between inner surfaces of the lip 20 and the lip 26. As a result, the lip 20 and the lip 26 apply compressive forces 17a and 17b onto the opposite lateral sides of the article of merchandise 14. The compressive forces 17a and 17b cause the frame of the article of merchandise 14 to undergo an elastic deformation, thereby tightly securing the article of merchandise 14 within the bracket assembly 12 without damaging the article of merchandise 14. This tight securement prevents movement of the article of merchandise 14 within the bracket assembly 12.

(39) In addition, because the plane in which the fasteners 40 are positioned is offset relative to the plane in which the overhang 20a of the lip 20 and the overhang 26a of lip 26 reside, tightening of the fasteners 40 results in moments 19a and 19b being exerted onto the overhangs 20a and 26a, thereby causing the overhangs 20a and 26a to come into a tight contact with the front surface of the

article of merchandise **14**. In this manner, as the fasteners **40** are tightened, a secure fit of the article of merchandise **14** within the bracket assembly **12** is achieved. Furthermore, the compression gap **19** enables the bracket assembly **12** to account for deviations in the dimensions of the article of merchandise **14** due to manufacturing tolerances. In an embodiment, the fastener **40** has a low thread pitch count, so that as the fastener **40** is threaded in, the compressive forces **17a** and **17b** are increased gradually, thus helping prevent excessive compressive forces that could damage the article of merchandise **14**.

(40) Although the compression gap **19** is discussed with respect to the embodiment of the bracket assembly **12** depicted in FIGS. **1-3**, the compression gap **19** is not limited to this embodiment and can be implemented with the embodiments depicted in FIGS. **4-6**, as well as other dual-component security brackets.

(41) The advantages set forth above, and those made apparent from the foregoing description, are efficiently attained. Since certain changes may be made in the above construction without departing from the scope of the invention, it is intended that all matters contained in the foregoing description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. An anti-theft device for securing an article of merchandise, comprising: a first bracket member having a first lip configured to at least partially receive a first lateral side of the article of merchandise such that the first bracket member contacts both a back surface and a front surface of the article of merchandise, wherein a normal distance from an inner surface of the first lip to an opposite edge of the first bracket member defines a first length; a second bracket member having a second lip configured to receive a second lateral side of the article of merchandise therein such that the second bracket member contacts both the back surface and the front surface of the article of merchandise, the second lateral side of the article of merchandise being opposite to the first lateral side of the article of merchandise, wherein a normal distance between an inner surface of the second lip to an opposite edge of the second bracket defines a second length; wherein a distance between the first and the second lateral sides of the article of merchandise exceeds a sum of the first length and the second length such that a gap having a width is present between the first bracket member and the second bracket member when the first lip is in receipt of the first lateral side and the second lip is in receipt of the second lateral side, and a threaded fastener having a longitudinal axis wherein the threaded fastener extends between the first bracket member and the second bracket member thereby bridging the gap therebetween and coupling the first and the second bracket members to one another, wherein rotation of the threaded fastener about the longitudinal axis thereof in a first direction is configured to reduce the width of the gap between the first and the second bracket members, thereby causing the first lip and the second lip to exert compressive forces onto the first and the second lateral sides of the article of merchandise, wherein the first and the second bracket members collectively form a bracket assembly, and wherein to release the article of merchandise from the bracket assembly, the threaded fastener must be rotated about the longitudinal axis thereof in a second direction to restore the width of the gap.

2. The anti-theft device of claim 1, wherein the article of merchandise has at least four lateral sides, and wherein the bracket assembly is configured to leave at least one of the four lateral sides unobstructed when the article of merchandise is secured within the bracket assembly.

3. The anti-theft device of claim 2, wherein the at least one of the four lateral sides unobstructed by the bracket assembly has an opening mechanism that enables the article of merchandise to transition between a closed configuration and an open configuration.

4. The anti-theft device of claim 1, wherein the first bracket member comprises an aperture configured to receive a protruding feature of the article of merchandise thereby restricting relative

movement of the article of merchandise relative to the bracket assembly.

5. The anti-theft device of claim 4, wherein the protruding feature of the article of merchandise is a camera lens module.

6. The anti-theft device of claim 1, wherein the first bracket member or the second bracket member comprises an opening configured to receive a cable connector for supplying electrical power to the article of merchandise.

7. The anti-theft device of claim 1, wherein the first bracket member comprises a first mounting block component and the second bracket member comprises a second mounting block component, wherein when the first and the second bracket members are coupled together, the first and the second mounting block components collectively form a mounting block, and wherein the mounting block is configured to be coupled to a pedestal.

8. The anti-theft device of claim 7, wherein the first mounting block component or the second mounting block component comprises a screw-threaded opening configured to receive the threaded fastener.

9. The anti-theft device of claim 7, wherein the mounting block is disposed off-center relative to the bracket assembly, such that the article of merchandise in an open configuration is centered relative to the pedestal.

10. A method of securing an article of merchandise within an anti-theft device, comprising: placing a first lip of a first bracket member onto a first lateral side of the article of merchandise such that the first bracket member contacts both a back surface and a front surface of the article of merchandise, wherein a normal distance from an inner surface of the first lip to an opposite edge of the first bracket member defines a first length; placing a second lip of a second bracket member onto a second lateral side of the article of merchandise such that the second bracket member contacts both the back surface and the front surface of the article of merchandise, the second lateral side of the article of merchandise being opposite to the first lateral side of the article of merchandise, wherein a normal distance between an inner surface of the second lip to an opposite edge of the second bracket defines a second length, and wherein a sum of the first length and the second length is less than a distance between the first and the second lateral sides of the article of merchandise such that a gap having a width is present between the first bracket member and the second bracket member when the first lip is in receipt of the first lateral side and the second lip is in receipt of the second lateral side, and rotating, in a first direction, a threaded fastener extending between the first and the second bracket members and bridging the gap therebetween, wherein rotation of the threaded fastener in the first direction reduces the width of the gap between the first and the second bracket members, thereby causing the first lip and the second lip to exert compressive forces onto the first and the second lateral sides of the article of merchandise, thereby securing the article of merchandise within a bracket assembly collectively formed by the first and the second bracket members, and wherein to release the article of merchandise from the bracket assembly, the threaded fastener must be rotated in a second direction to restore the width of the gap.

11. The method of claim 10, wherein the article of merchandise has at least four lateral sides, and wherein, when the bracket assembly is coupled to the article of merchandise, at least one of four lateral sides is unobstructed by the bracket assembly.

12. The method of claim 11, further comprising the step of transitioning the article of merchandise between a closed configuration and an open configuration, by operating an opening mechanism of the article of merchandise disposed at the unobstructed lateral side thereof.

13. The method of claim 10, further comprising the step of positioning a protruding feature of the article of merchandise into an aperture within the first bracket member, wherein engagement between the aperture and the protruding feature restricts relative movement between the bracket assembly and the article of merchandise.

14. The method of claim 13, wherein the protruding feature of the article of merchandise is a

camera lens module.

15. The method of claim 10, further comprising the step of passing a cable connector through an opening within the first bracket member or the second bracket member and coupling the cable connector to the article of merchandise.

16. The method of claim 10, further comprising the step of coupling the bracket assembly to a pedestal, wherein the first bracket member comprises a first mounting block component and the second bracket member comprises a second mounting block component, wherein the first and the second mounting block components collectively form a mounting block when the first and the second bracket members are coupled together.

17. The method of claim 16, wherein the threaded fastener is operatively received into a screw-threaded opening disposed within the first mounting block component or the second mounting block component.

18. The method of claim 16, wherein the mounting block is disposed off-center relative to the bracket assembly, such that the article of merchandise in an open configuration is centered relative to the pedestal.
