

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409057
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Danforth; Michael

Knee brace spring lock and release hinge

Abstract

A knee brace spring lock and release hinge including a first section and second section. The first section has an arched support housing with a J-curved recess. The second section includes a base with base platform, an arched support surrounding a rotational wheel, a wheel pad abutting a portion of the wheel, and at least one spring extending from the base platform to the wheel pad. The second section is structured to rotate within the J-curved recess when the at least one spring is extended. The second section is structured to be locked into place when the at least one spring is compressed.

Inventors:	Danforth; Michael (Ft. Pierce, FL)
Applicant:	Danforth; Michael (Ft. Pierce, FL)
Family ID:	96950355
Appl. No.:	19/204487
Filed:	May 10, 2025

Publication Classification

Int. Cl.: A61F5/01 (20060101)

U.S. Cl.:

CPC **A61F5/0123** (20130101); A61F2005/0162 (20130101); A61F2005/0165 (20130101);
A61F2005/0179 (20130101)

Field of Classification Search

CPC: A61F (5/0123); A61F (5/0125); A61F (2005/0158); A61F (2005/0162); A61F
(2005/0165); A61F (2005/0179); B25J (9/0006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5547464	12/1995	Luttrell	N/A	N/A
5749840	12/1997	Mitchell	N/A	N/A
5899869	12/1998	Barrack, Jr.	602/16	A61F 5/0125
6635024	12/2002	Hatton	602/26	A61F 5/0125
7553289	12/2008	Cadichon	N/A	N/A
10682249	12/2019	Kazerooni	N/A	N/A
11369494	12/2021	Kazerooni	N/A	N/A
2009/0299244	12/2008	Chiang	N/A	N/A
2014/0005584	12/2013	Pretz	N/A	N/A
2015/0150708	12/2014	Paez	602/16	A61F 5/0123
2017/0281390	12/2016	Abdul-Hafiz	N/A	A61F 5/0125
2020/0383814	12/2019	Vogel	N/A	A61F 5/0125
2023/0172741	12/2022	Johnson	N/A	N/A

Primary Examiner: Bredefeld; Rachael E

Assistant Examiner: Brown; Seth R.

Attorney, Agent or Firm: Bullock Law

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to knee brace hinges. In particular, the present invention relates to a lock and release rotational knee brace hinge.

BACKGROUND

(2) The current state of the art only provides for a knee brace hinge that rotates, but does not lock in place when walking. Some provide a locking mechanism that requires a user to manually lock the hinge in place by hand. This becomes cumbersome for a user to use and does not simulate a true walking motion.

(3) There exists a need in the art for an improved knee brace hinge that simulates a walking motion by locking into place when a user steps down. Likewise, it should unlock and rotate when a user releases weight from that leg. Therefore, there exists a need in the art for a knee brace spring lock and release hinge as claimed and described herein.

SUMMARY OF THE INVENTION

(4) Embodiments of the present invention are related to a knee brace spring lock and release hinge including a first section and second section. The first section has an arched support housing with a J-curved recess. The second section includes a base with base platform, an arched support surrounding a rotational wheel, a wheel pad abutting a portion of the wheel, and at least one spring extending from the base platform to the wheel pad. The second section is structured to rotate within the J-curved recess when the at least one spring is extended. The second section is structured to be

locked into place when the at least one spring is compressed.

(5) In this embodiment, the first section and the second section may each include a brace support recess structured to receive a longitudinal brace support. The hinge may be structured to rotate between a vertically locked first position and at least a 90-degree angle second position and the arched support may include a first leg and a second leg. The hinge may be prevented from rotating when the second leg abuts a wall created by the J-curved recess when the at least one spring is compressed. Furthermore, a curved portion of the arched support may be structured to allow the second section to rotate within the J-curved recess when the at least one spring is extended. Additionally, the wheel may rotate along an axle and the axle may double as a fastener that connects the first section to the second section.

(6) Another embodiment may include a knee brace spring lock and release hinge with a first section and second section. The first section may have an arched support housing with a recess formed by two generally perpendicular walls connected by a curved wall. The second section may include a base, an arched support surrounding a rotational wheel, a wheel pad connected to a portion of the rotational wheel, and a plurality of springs extending from the base to the wheel pad. The second section may be structured to rotate within the recess when the plurality of springs is extended. Also, the second section may be structured to be locked in place when the plurality of springs is compressed.

(7) In this embodiment, the arched support may be structured to reduce rotational space within the recess when the plurality of springs is compressed, thereby preventing the second section from rotating. The hinge may be structured to be attached to a knee brace whereby the brace hinge is structured to lock when a user steps down with their weight on a leg with the brace and is structured to rotate when a user releases their body weight from that leg.

(8) Furthermore, the wheel pad may include two spring pad holes structured to receive two springs therein. Likewise, the base may include a base platform with two spring base holes configured to receive two springs therein. The base may be angled on one side and straight on another side, and the wheel pad may be curved on a first side and flat on an opposing side. The plurality of springs may push the wheel pad distally from the base when extended and abut the wheel pad to the base when compressed. Additionally, an arched support curve atop the arched support may be flush with the rotational wheel when the plurality of springs is extended. It may be distal to the rotational wheel creating space therebetween when the plurality of springs is compressed.

(9) Furthermore, a portion of the arched support curve atop the arched support may be pushed into the curved wall and a leg of the arched support may align with one of the perpendicular walls when the plurality of springs is compressed creating a second section wedge within the recess preventing rotation of the second section.

(10) Another embodiment of the invention may include a knee brace spring lock and release hinge with a first section and a second section. The first section may include an arched support housing with a J-curved recess. The second section may include a base with base platform, an arched support surrounding a rotational wheel, a wheel pad connected to a portion of the rotational wheel, and at least one spring extending from the base platform to the wheel pad. It may have an axle permeated through a medial wheel sheath whereby the axle is a threaded fastener structured to secure the first section to the second section. The second section may be structured to rotate within the J-curved recess when the at least one spring is extended and it may be structured to be locked in place when the spring is compressed.

(11) The hinge itself may be structured to be attached to a knee brace. It may be structured to lock when a user steps down with their body weight on a leg with the brace and may be structured to rotate when a user releases their body weight from that leg. Both the first section and the second section may include a brace support recess structured to receive a longitudinal brace support.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is an environmental side view of the knee brace spring lock and release hinge in a bent orientation according to an embodiment of the invention.
- (2) FIG. 1B is an environmental side view of the knee brace spring lock and release hinge illustrated in FIG. 1A in a straight unlocked orientation.
- (3) FIG. 1C is an environmental side view of the knee brace spring lock and release hinge illustrated in FIG. 1A in a straight locked orientation.
- (4) FIG. 2A is a side perspective view of the knee brace spring lock and release hinge illustrated in FIG. 1A.
- (5) FIG. 2B is a side perspective view of the knee brace spring lock and release hinge illustrated in FIG. 1B.
- (6) FIG. 2C is a side perspective view of the knee brace spring lock and release hinge illustrated in FIG. 1C.
- (7) FIG. 3 is an overhead side perspective view of the knee brace spring lock and release hinge in FIG. 1A.
- (8) FIG. 4 is an internal side view of the knee brace spring lock and release hinge illustrated in FIG. 1A with cover plate removed.
- (9) FIG. 5 is a side perspective view of the knee brace spring lock and release hinge illustrated in FIG. 1A.
- (10) FIG. 6 is a side perspective view of the knee brace spring lock and release hinge illustrated in FIG. 1C.
- (11) FIG. 7A is an exploded view of componentry of the knee brace spring lock and release hinge.
- (12) FIG. 7B is an exploded view of componentry of the knee brace spring lock and release hinge.
- (13) FIG. 7C is an exploded view of componentry of the knee brace spring lock and release hinge.
- (14) FIG. 7D is a top perspective view of a component of the knee brace spring lock and release hinge.
- (15) FIG. 7E is a bottom perspective view of a component of the knee brace spring lock and release hinge.

DETAILED DESCRIPTION OF THE INVENTION

- (16) The present invention will now be described in detail with reference to the accompanying drawings. The embodiment descriptions are illustrative and not intended to be limiting in any way. Other embodiments of the invention will readily suggest themselves to persons with ordinary skill in the art after having the benefit of this disclosure. Accordingly, the following embodiments are set forth without any loss of generality and without imposing limitation upon the claimed invention.
- (17) Directional terms such as “above” “below” “upper” “lower” and other like terms are used for the convenience of the reader in reference to the drawings. Additionally, the description may contain terminology to convey position, orientation, and direction without departing from the principles of the present invention. Such positional language should be taken in context of the represented drawings.
- (18) Quantitative terms such as “generally” “substantially” “mostly” and other like terms are used to mean that the referred object, characteristic, or quality constitutes a majority of the referenced subject. Likewise, use of the terms such as first and second do not necessarily designate a limitation of quantity. Such terms may be used as a method of describing the presence of at least one of the referenced elements or may provide a means of differentiating orientation. The meaning of any term within this description is dependent upon the context within which it is used, and the meaning may be expressly modified.
- (19) Referring now to FIGS. 1A, 1B, and 1C, a knee brace spring lock and release hinge **100**,

hereinafter hinge **100**, will be described more fully. FIG. 1A illustrates the hinge **100** in a bent orientation **103** thereby bending the entire knee brace when a user has swung their leg backward **106** when walking. FIG. 1B illustrates the hinge **100** in a straight, but open and unlocked orientation **104**. This may occur when a user has swung their leg forward, but has not yet stepped down with their weight on that leg **107**. FIG. 1C illustrates the hinge **100** in a straight, closed and locked orientation **105**. This may occur when a user has swung their leg forward and has applied weight to take a step forward **108**.

(20) The hinge **100** may include a first section **101** and a second section **102**. The first section **101** and the second section may be attached to a knee brace via longitudinal support brace **115**.

Respective longitudinal support braces **115** may attach to the hinge **100** at an upper portion of the first section **101** and a lower portion of the second section **102**.

(21) As shown, when a user has swung their leg backwards **106**, the first section **101** and second section **102** are separated allowing the hinge **100** to rotate freely backwards. However, a vertical spring motion **120** allows the hinge **100** to compress when a user has swung their leg forward and has taken a step using their weight on that leg.

(22) FIGS. 2A, 2B, and 2C take a closer look at the operational features of the hinge **100**. FIG. 2A illustrates the hinge **100** in a bent orientation **103**. As shown, the first section **101** may include a first section exoskeleton **215** that encloses internal componentry.

(23) One such internal component of the second section **102** may be a wheel pad **406**. The wheel pad **406** may receive at least one spring **201**. In this embodiment the wheel pad **406** receives a pair of springs **201**. The springs **201** may be connected to the second section base **425** at an opposing end. The second section base **425** may include a base platform **450** with a flat ledge structured to act as a rotational stopper when meeting the first section exoskeleton **215** in a straight closed and locked orientation **105**. The second section base **425** includes one angled side and an opposing straight side.

(24) FIG. 2B shows the hinge **100** in a straight, open and unlocked orientation **104** whereby a user has rotated their leg forward but not stepped downward. Here, there may be a gap **205** between the first section **101** and the second section **102** because the springs are extended and separating the two.

(25) FIG. 2C illustrates the hinge **100** in a straight, closed, and locked orientation **105** whereby a user has rotated their leg forward and stepped, applying their body weight downward. Therefore, there is no gap **206** between the first section **101** and the second section **102** because the springs **201** have been contracted. Hence, the first section **101** is abutting the second section **102** and the hinge **100** is unable to rotate further forward because of the locking features in this position.

(26) Also shown in these figures is a brace support aperture **204** used to secure a longitudinal support brace **115** to the second section **102**. A similar brace support aperture **204** is used to secure a longitudinal support brace **115** to the first section **101**.

(27) FIG. 3 is a rear view of an embodiment of the hinge **100** illustrating a brace support recess **301** capable of fitting therein a longitudinal support brace **115**. Both the first section **101** and the second section include a brace support recess **301** therein whereby a respective longitudinal support brace **115** may be fitted thereto. As shown, the springs **201** may still be extended when the hinge **100** is in a bent orientation **103**.

(28) FIG. 4 illustrates more internal componentry of the hinge **100** as a first section cover plate **401** has been removed. The first section cover plate **401** may include a threaded cover aperture **409** allowing it to be removably attached to the hinge **100** via the axle **408**. The axle **408** may pass through both the first section **101** and the second section **102** securing one to the other and allowing rotation of the hinge **100** along its axis. The axle **408** itself may be threaded because it may serve the dual purpose of securing the first section cover plate **401** to the hinge **100** while also providing a rotational axis for the hinge **100**. Therefore, the axle **408** may pass through an axle sheath **415**, which may be a surrounding tube through a middle portion of the hinge **100** reducing friction that

may occur from threading of the axle **408** and facilitating smooth rotation of the hinge **100**.

(29) As shown, the second section **102** may fit into the arched support housing **402** of the first section. The arched support housing **402** may include a j-curved notch or recess forming a j-curved wall **405**. In some embodiments, this j-curved recess may be formed by two generally perpendicular walls connected by a curved wall. The recess may allow an arched support **403** from the second section **102** to fit and operate therein.

(30) The second section **102** may include a second section base **425** with a second section base platform **450**. The arched support **403** may be a rigid arch extending from one end of the base platform **450** proximate another. Therefore, the arched support **403** may include a first leg **411** and a second leg **412** on either side of an arch support curve **410**. Within the arched support **403** may be a rotational wheel **407** including a medial aperture encapsulating the axle sheath **415** with axle **408** therein. In its straight, unlocked, orientation **104** the rotational wheel **407** may be abutted on the underside by the wheel pad **406**. The wheel pad **406** may be curved on one end to geometrically conform to the curve of the wheel pad **406** to which it abuts. An opposing end of the wheel pad **406** may be flat so as to accommodate the springs **201** therein. As such, the springs **201** keep the curved portion of the wheel pad **406** flush with the rotational wheel **407** at all times since they push away from the base platform **450** at one end and toward the wheel pad **406** and rotational wheel **407** at the other. Likewise, the arch support curve **410** atop the arched support **403** may be flushed with the rotational wheel **407** when the springs **201** are extended, since they push the base platform **450** away from the rotational wheel **407** and the arch **410** of the arched support gets caught thereon. Furthermore, the arched support curve **410** atop the arched support **403** may be distal to the rotational wheel **407** creating space therebetween when the springs **201** are compressed. This pushes the arch support **403** into the housing walls **405** and forms a second section wedge preventing rotation of the second section **102**.

(31) FIG. 5 illustrates the internal componentry of the hinge **100** when it is in the bent orientation **103**. As shown, when there is not downward pressure applied to the springs **201** and they are extended, the arched support curve **410** is biased away from the housing wall **405**. Therefore, there exists space **501A** for the arched support **403** to rotate **501** within the arched support housing **405**. The rounded nature of the arched support curve **410** also facilitates rotation **501** since it is able to roll off of the housing wall **405**. The second section **102** as a whole is able to rotate to at least a 90-degree orientation within the J-curve of the support housing **405** when the springs **201** are extended.

(32) FIG. 6 shows the internal componentry of the hinge **100** when in its vertical, closed, and locked orientation **105**. As shown, there is downward pressure being applied to the hinge **100** as when a user has stepped with that leg. Therefore, the springs **201** are compressed and the wheel pad **406** is pressed against the base platform **450**. This in turn, pushes the arched support **403** into the arched support housing walls **405** leaving little to no gap **501b** between the two and thereby preventing the second section **102** from being able to rotate. Furthermore, in this position, the second leg **412** may abut the J-curved wall **405** further preventing rotation. Hence, the range of motion of the hinge **100** may be from a vertically locked position when the springs **201** are compressed, to at least a 90-degree angled second position when the springs **201** are extended. In other words, a portion of the arched support curve **410** atop the arched support **403** may be pushed into the housing curve **404** and a leg **412** of the arched support **403** may align with one of the perpendicular walls **405** when the plurality of springs **201** are compressed. This is what creates the second section **102** wedge within the housing recess **402** preventing rotation **602** of the second section **102**.

(33) FIGS. 7A through 7E illustrate the componentry of the hinge **100** in more focused detail. FIG. 7A shows an exploded view of the internal componentry including the rotational wheel **407** and axle sheath **415**. The wheel pad **406** and springs **201** are shown as well as a better view of the second section base **425** with spring base holes **701** illustrating how the springs **201** may fit therein

to secure in place on the second section base platform **450**. Also shown is how the arched support **410** connects to the second section base platform **450**. Additionally, a different view of the first section **101** with its arched support housing **402** and housing aperture **701** are shown.

(34) FIG. 7B illustrates an exploded view of the internal componentry from a different angle that shows the wheel pad **406** with spring pad holes **702** located on the flat portion thereof. The spring pad holes **702** may be designed to fit the springs **201** therein so that they may secure in place between there and the second section base platform **450**. Also shown in this view is the axle **408**, which may also serve as the apparatus fastener. Meaning, the axle **408** may be a bolt that extends through both the first section **101** and the second section **102** securing the two together, while also providing a rotational axis. FIG. 7C also shows the internal componentry from a different perspective.

(35) FIG. 7D shows the spring base holes **701** surrounded by the arched support **410** on the base platform **450**. FIG. 7E gives a detailed view of the wheel pad **406** with its wheel pad curve **750** and spring pad holes **702**. Again, the spring pad holes **702** are opposing the spring base holes **701** with the springs **201** fitted between the two to provide tensioned connectivity between the base platform **450**, wheel pad **406**, rotational wheel **407**, arched support **403** and arched support housing **402** depending on orientation of the hinge **100** and applied force of the user.

Claims

1. A knee brace spring lock and release hinge comprising: a first section comprising an arched support housing with a J-curved recess; a second section comprising a base with a base platform, an arched support surrounding a rotational wheel, a wheel pad abutting a portion of the rotational wheel, and at least one spring extending from the base platform to the wheel pad; wherein the second section is configured to rotate within the J-curved recess when the at least one spring is extended; and wherein the second section is configured to be locked into place when the at least one spring is compressed.
2. The knee brace spring lock and release hinge of claim 1 wherein the first section and the second section each include a brace support recess configured to receive a longitudinal brace support.
3. The knee brace spring lock and release hinge of claim 1 wherein the hinge is configured to rotate between a vertically locked first position and at least a 90-degree angle second position.
4. The knee brace spring lock and release hinge of claim 1 wherein the arched support includes a first leg and a second leg.
5. The knee brace spring lock and release hinge of claim 4 wherein the hinge is prevented from rotating when the second leg abuts a wall created by the J-curved recess when the at least one spring is compressed.
6. The knee brace spring lock and release hinge of claim 1 wherein a curved portion of the arched support is configured to allow the second section to rotate within the J-curved recess when the at least one spring is extended.
7. The knee brace spring lock and release hinge of claim 1 wherein the wheel rotates along an axle; and wherein the axle is a fastener that connects the first section to the second section.
8. A knee brace spring lock and release hinge comprising: a first section comprising an arched support housing with a recess formed by two generally perpendicular walls connected by a curved wall; a second section comprising a base, an arched support surrounding a rotational wheel, a wheel pad connected to a portion of the rotational wheel, and a plurality of springs extending from the base to the wheel pad; wherein the second section is configured to rotate within the recess when the plurality of springs are extended; wherein the second section is configured to be locked in place when the plurality of springs are compressed.
9. The knee brace spring lock and release hinge of claim 8 wherein the arched support is configured to reduce rotational space within the recess when the plurality of springs are compressed thereby

preventing the second section from rotating.

10. The knee brace spring lock and release hinge of claim 8 wherein the hinge is configured to be attached to a knee brace; and wherein the brace hinge is configured to lock when the user steps down with their weight on a leg with the brace and is configured to rotate when a user releases their body weight from that leg.

11. The knee brace spring lock and release hinge of claim 8 wherein the wheel pad comprises two spring pad holes configured to receive two springs of the plurality of springs therein.

12. The knee brace spring lock and release hinge of claim 8 wherein the base includes a base platform with two spring base holes configured to receive two springs of the plurality of springs therein.

13. The knee brace spring lock and release hinge of claim 8 wherein the base is angled on one side and straight on another side.

14. The knee brace spring lock and release hinge of claim 8 wherein the wheel pad is curved on a first side and flat on an opposing side.

15. The knee brace spring lock and release hinge of claim 8 wherein the plurality of springs push the wheel pad distally from the base when extended and abut the wheel pad to the base when compressed.

16. The knee brace spring lock and release hinge of claim 8 wherein an arched support curve atop the arched support is flush with the rotational wheel when the plurality of springs are extended.

17. The knee brace spring lock and release hinge of claim 8 wherein an arched support curve atop the arched support is distal to the rotational wheel creating space therebetween when the plurality of springs are compressed.

18. The knee brace spring lock and release hinge of claim 8 wherein a portion of an arched support curve atop the arched support is pushed into the curved wall and a leg of the arched support aligns with one of the perpendicular walls when the plurality of springs are compressed creating a second section wedge within the recess preventing rotation of the second section.

19. A knee brace spring lock and release hinge comprising: a first section comprising an arched support housing with a J-curved recess; a second section comprising a base with a base platform, an arched support surrounding a rotational wheel, a wheel pad connected to a portion of the rotational wheel, and at least one spring extending from the base platform to the wheel pad; an axle permeated through a medial wheel sheath; wherein the axle is a threaded fastener configured to secure the first section to the second section; wherein the second section is configured to rotate within the J-curved recess when the at least one spring is extended; wherein the second section is configured to be locked in place when the at least one spring is compressed; wherein the hinge is configured to be attached to a knee brace; and wherein the brace hinge is configured to lock when a user steps down with their body weight on a leg with the brace and is configured to rotate when the user releases their body weight from that leg.

20. The knee brace spring lock and release hinge of claim 17 wherein the first section and the second section each include a brace support recess configured to receive a longitudinal brace support.
