

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409277
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Wu; Haiming et al.

Medicament delivery device

Abstract

There is provided a medicament delivery device comprising: a main body arranged to receive a medicament cartridge; a needle for delivery of medicament from the medicament cartridge; a needle cover moveable between an initial position, in which the needle cover covers the needle, and an activated position for dispensing medicament from the medicament delivery device, wherein in the activated position the needle protrudes from a distal end of the needle cover; an outer frame, moveable relative to the main body between an extended position in which the outer frame extends past a distal end of the needle, and a retracted position in which the outer frame is moved towards the main body; an attachment element comprising an adhesive region for attaching the medicament delivery device to a surface when the needle cover is in the activated position, the attachment element comprising a protective barrier covering the adhesive region.

Inventors: Wu; Haiming (Melbourn, GB), Hee-Hanson; Alexander (Melbourn, GB), Vespa; William (Boston, MA), Delmy; Cedric (Boston, MA), Frankel; Seth (Boston, MA)

Applicant: Genzyme Corporation (Cambridge, MA)

Family ID: 96950305

Assignee: Genzyme Corporation (Cambridge, MA)

Appl. No.: 18/819570

Filed: August 29, 2024

Publication Classification

Int. Cl.: A61M5/32 (20060101)

U.S. Cl.:

CPC A61M5/3204 (20130101);

Field of Classification Search

CPC: A61M (5/3204); A61M (5/422); A61M (2005/1585)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0010423	12/2001	Gross	604/170.03	A61M 5/14248
2019/0030240	12/2018	Cabiri	N/A	A61M 5/14248
2021/0196892	12/2020	Dasbach	N/A	A61M 5/50
2022/0273925	12/2021	Zeira	N/A	A61M 5/14248

OTHER PUBLICATIONS

Needle-based injection systems for medical use requirements and test methods, Part 1: Needle injection systems, ISO 11608 1:2014(E), Third Edition, Switzerland, ISO, Dec. 15, 2014, pp. 1-13. cited by applicant

Primary Examiner: Bredefeld; Rachael E

Assistant Examiner: Diop; Fatimata Sahra

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a medicament delivery device and to a method of operating a medicament delivery device.

BACKGROUND

(2) Medicament delivery devices are used to deliver a range of medicaments. In some devices, the device must be held in a holding position at an injection site to ensure that the correct dose of medicament is dispensed from the device, before removing the device from the injection site. It may be difficult to hold the device in the holding position whilst the medicament is dispensed. This may result in pain, discomfort, a wet injection site, early device removal and/or partial delivery of the medicament. Administering an injection is a process which presents several risks and challenges, both mental and physical. The present disclosure provides an improved medicament delivery device.

SUMMARY

(3) A first aspect of this disclosure provides a medicament delivery device comprising: a main body arranged to receive a medicament cartridge; a needle for delivery of medicament from the medicament cartridge; a needle cover moveable between an initial position, in which the needle cover covers the needle, and an activated position for dispensing medicament from the medicament delivery device, wherein in the activated position the needle protrudes from a distal end of the needle cover; an outer frame, moveable relative to the main body between an extended position in which the outer frame extends past a distal end of the needle, and a retracted position in which the outer frame is moved towards the main body; an attachment element comprising an adhesive region

for attaching the medicament delivery device to a surface when the needle cover is in the activated position, the attachment element comprising a protective barrier covering the adhesive region; wherein the protective barrier is coupled to the outer frame and is removed from the attachment element to expose the adhesive region as the outer frame is moved towards the retracted position.

(4) The protective barrier may be removed from the attachment element, and the needle cover may be moved from the initial to the activated position, with a single action of providing a force on the medicament delivery device in a distal direction.

(5) A first end of the protective barrier may be coupled to the outer frame, and a second end of the protective barrier may be releasably attached to the attachment element.

(6) The protective barrier may comprise a folded portion releasably secured to the attachment element.

(7) The folded portion may comprise a double layer of the protective barrier covering at least a portion of the attachment element.

(8) A whole of the adhesive region may be covered by a double layer of the protective barrier.

(9) A second end of the protective barrier may be releasably secured to the attachment element, and the second end may be folded towards the attachment element to form the folded portion.

(10) The protective barrier may comprise a single component that extends to cover the adhesive region.

(11) The protective barrier may comprise at least two components that extend to cover a part of the adhesive region.

(12) The protective barrier may comprise two components that each extend to cover half of the adhesive region.

(13) The second end may be releasably attached to a central part of the adhesive region.

(14) The outer frame may be external to the main body in both the extended position and the retracted position.

(15) The outer frame may be pushed inside the main body as it moves towards the retracted position.

(16) The main body may comprise a frame cavity for receiving the outer frame in the retracted position.

(17) The outer frame may extend around the main body in the extended, and/or the retracted position.

(18) The outer frame may extend around the needle cover in the extended, and/or the retracted position.

(19) The outer frame may comprise a flange on its distal most end for contacting the surface for the delivery of medicament.

(20) Movement of the outer frame relative to the needle cover may remove the protective barrier from the attachment element.

(21) The outer frame may be configured such that the protective barrier may be removed and the adhesive region may be adhered to the surface, before the needle cover is in the activated position.

(22) The attachment element may be coupled to the needle cover.

(23) The attachment element may move axially in a distal direction as the needle cover is moved towards the activated position.

(24) An adhesive force from the attachment element may be greater than a spring force of the needle cover.

(25) When the needle cover is in the initial position, the attachment element may be positioned set back in a proximal direction from a distal most end of the medicament delivery device.

(26) The adhesive region of the attachment element may cover between 40% and 100% of a contact face of the needle cover or the outer frame.

(27) The adhesive region of the attachment element may cover between 50% and 100% of the contact face of the needle cover or the outer frame.

- (28) The adhesive region of the attachment element may cover between 50% and 90% of the contact face of the needle cover or the outer frame.
- (29) The adhesive region of the attachment element may cover between 60% and 90% of the contact face of the needle cover or the outer frame.
- (30) The adhesive region may comprise one or more of an adhesive, glue or sticky tape.
- (31) The adhesive region of the attachment element may be one or more of a single patch, a plurality of patches, dots, lines or patterns of adhesive.
- (32) The attachment element may move independently of the needle cover.
- (33) The main body may comprise an attachment element support coupled to the attachment element.
- (34) The attachment element support may be fixed with respect to the rest of the main body and the attachment element may be pushed towards the surface as the main body is pushed towards the surface.
- (35) The needle may be configured to penetrate the attachment element during delivery of medicament from the medicament cartridge.
- (36) The needle may be configured to deliver medicament from the medicament cartridge without contacting the attachment element.
- (37) The outer frame may be adjacent to the needle cover.
- (38) The outer frame may be pivotable relative to the main body to move between the extended position and the retracted position.
- (39) The outer frame may comprise a pivot towards an end opposite to the needle.
- (40) The outer frame may comprise a removal arm, wherein a first end of the removal arm may be pivotally coupled to the main body, and a second end of the removal arm may be moveable relative to an internal face of a contact surface of the outer frame.
- (41) As the outer frame moves from the extended to the retracted position, the second end of the removal arm may be pushed along the internal face of the outer frame to pull the protective barrier away from the attachment element.
- (42) The first end of the removal arm may be a proximal end, and the second end of the removal arm may be a distal end.
- (43) The distal end may extend away from the main body in a distal direction towards the contact surface of the outer frame, when the outer frame is in the extended position.
- (44) The protective barrier may be pulled through an aperture in the contact surface of the outer frame.
- (45) The contact surface of the outer frame may comprise a needle hole for the needle to extend through for the delivery of medicament.
- (46) The aperture may be independent of the needle hole. For example, they are separate holes.
- (47) Alternatively, the holes may be joined.
- (48) The attachment element may comprise at least two adhesive regions, each disposed on opposite sides of the aperture.
- (49) The aperture may be in the form of a slit. The aperture may extend over the majority of a width of the contact surface.
- (50) The outer frame may extend further out from the main body at a front end than at the rear end, wherein the front end may be disposed closer to the needle than the rear end.
- (51) At the second end the removal arm may comprise a fastener to attach the removal arm to the protective barrier.
- (52) The fastener may be attached to an intermediate point of the protective barrier, between a first end and a second end of the protective barrier.
- (53) The fastener may be attached near to a mid point of the protective barrier.
- (54) The protective barrier may be removably attached to the first adhesive region, extend through the aperture in the outer frame to attach to the fastener, extend back out through the aperture and

may be removably attached to the second adhesive region.

(55) The protective barrier may comprise at least two components, each having a first end attached to the fastener, and a second end removably attached to the attachment element.

(56) The removal arm may move towards a position parallel to the internal face of the outer frame, as the outer frame may move towards the retracted position.

(57) As a distance between the aperture and a second end of the removal arm increases, the removal arm may pull the protective barrier away from the attachment element.

(58) The outer frame may comprise a releasable mechanism to automatically retract the protective barrier from the attachment element, wherein the releasable mechanism may be activated as the outer frame is moved towards the main body.

(59) The releasable mechanism may comprise at least one releasable component, and a first end of the protective barrier may be attached to the at least one releasable component, and a second end of the protective barrier may be releasably attached to the attachment element.

(60) The releasable component may comprise a biased roller, and a first end of the protective barrier may be wound around the at least one biased roller, and a second end of the protective barrier may be releasably attached to the attachment element.

(61) The releasable mechanism may comprise a set of releasable components.

(62) The releasable mechanism may comprise two releasable components.

(63) The protective barrier may comprise a number of components, equal to the number of releasable components.

(64) The releasable mechanism may be released by a button, a lever, a latch or a catch.

(65) The outer frame may comprise at least one tension member to hold the protective barrier in tension as it is removed from the attachment element.

(66) The outer frame may comprise two sets of tension members, a set of distal tension members and a set of proximal tension members, wherein the protective barrier may extend around each of the distal and proximal tension members to hold the protective barrier in tension as it is removed from the attachment element.

(67) The tension members may be rollers and may rotate as the protective barrier is removed from the attachment element.

(68) The tension members may be stationary as the protective barrier is removed from the attachment element.

(69) The protective barrier may drag or pull the surface in a direction away from the injection site as the protective barrier is removed from the attachment element.

(70) Pulling the surface away from the injection site may cause a taut surface for the delivery of medicament.

(71) The protective barrier may comprise two components and the surface may be pulled in opposing directions by each part of the protective barrier as the protective barrier is removed from the attachment element.

(72) The adhesive regions may hold the surface taut until the device is removed from the surface.

(73) There may be two tension members. There may be more than four tension members.

(74) The tension member may be a static frame around which the protective barrier may be wound.

(75) The device may be an axial form injection device.

(76) The device may be a flat form injection device.

(77) The device may comprise a container of medicament.

(78) A second aspect of this disclosure provides a method of operating a medicament delivery device comprising: moving an outer frame relative to a main body of the medicament delivery device from an extended position, in which the outer frame extends past a distal end of a needle, to a retracted position, in which the outer frame is moved towards the main body; exposing an adhesive region of an attachment element by removing a protective barrier covering the adhesive region, wherein the protective barrier is coupled to an outer frame of the medicament delivery

device and is removed as the outer frame is moved towards the retracted position; adhering the exposed adhesive region of the attachment element to a surface for the preparation of delivery of a medicament.

(79) The method of operating a medicament delivery device may further comprise, moving a needle cover from an initial position, in which the needle cover may cover the needle, to an activated position for dispensing medicament from the medicament delivery device, wherein in the activated position the needle may protrude from a distal end of the needle cover.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments will now be described, by way of example only, with reference to the accompanying drawings, in which:

(2) FIG. 1 shows a schematic cross section of a medicament delivery device;

(3) FIG. 2 shows a schematic example of a medicament delivery device in the form of a flat form injection device;

(4) FIG. 3A shows a schematic example of the medicament delivery device of FIG. 2 when an outer frame is in an extended position and a protective barrier covers an adhesive region;

(5) FIG. 3B shows a schematic example of the medicament delivery device of FIG. 2 when an outer frame contacts an injection site;

(6) FIG. 3C shows a schematic example of the medicament delivery device of FIG. 2 when an outer frame is moved towards a retracted position; and

(7) FIG. 3D shows a schematic example of the medicament delivery device of FIG. 2 when the medicament delivery device is adhered to an injection site;

(8) FIG. 4A shows a schematic cross section of the medicament delivery device of FIG. 2 when an outer frame is in an extended position;

(9) FIG. 4B shows a schematic cross section of the medicament delivery device of FIG. 2 when an outer frame is between an extended position and a retracted position;

(10) FIG. 4C shows a schematic cross section of the medicament delivery device of FIG. 2 when an outer frame is in a retracted position;

(11) FIG. 5 shows a schematic cross section of a medicament delivery device having an outer frame positioned externally to a main body;

(12) FIG. 6A shows a schematic cross section of a medicament delivery device with an attachment element support when an outer frame is in an extended position;

(13) FIG. 6B shows a schematic cross section of the medicament delivery device of FIG. 6A when the outer frame is in a retracted position;

(14) FIG. 7A shows a schematic cross section of a medicament delivery device with a pivoting outer frame in an extended position;

(15) FIG. 7B shows a schematic cross section of the medicament delivery device of FIG. 7A with the outer frame in a retracted position;

(16) FIG. 8A shows a schematic cross section of a medicament delivery device with an outer frame comprising a releasable mechanism;

(17) FIG. 8B shows a schematic cross section of the medicament delivery device of FIG. 8A as the outer frame moves towards a retracted position;

(18) FIG. 9A shows a schematic example of a medicament delivery device with an outer frame comprising two sets of tension members;

(19) FIG. 9B shows a schematic cross section of the medicament delivery device of FIG. 9A when an outer frame is in a retracted position;

(20) FIG. 10 shows a flow chart of an example of a method of operating a medicament delivery

device.

DETAILED DESCRIPTION

(21) A drug delivery device (also referred to as an injection device), as described herein, may be configured to inject a medicament into a subject such as a human or animal. For example, delivery could be sub-cutaneous, intra-muscular, or intravenous. Such a device could be operated by a user, who may or may not be the subject. In examples where the user is not the subject, the user may be a care-giver such as a nurse or physician. The device can include various types of safety syringe, pen-injector, or auto-injector. The device can include a cartridge-based system that requires piercing a sealed ampule before use. Volumes of medicament delivered with these various devices can range from about 0.5 ml to about 2 ml. Yet another device can include a large volume device (“LVD”) or patch pump, configured to adhere to a subject's skin for a period of time (e.g., about 5, 15, 30, 60, or 120 minutes) to deliver a “large” volume of medicament (typically about 2 ml to about 10 ml).

(22) In combination with a specific medicament, the presently described devices may also be customized in order to operate within required specifications. For example, the device may be customized to inject a medicament within a certain time period (e.g., about 3 to about 20 seconds for auto-injectors, and about 10 minutes to about 60 minutes for an LVD). Other specifications can include a low or minimal level of discomfort, or to certain conditions related to human factors, shelf-life, expiry, biocompatibility, environmental considerations, etc. Such variations can arise due to various factors, such as, for example, a drug ranging in viscosity from about 3 cP to about 50 cP. Consequently, a drug delivery device will often include a hollow needle ranging from about 25 to about 31 Gauge in size. Common sizes are 27 and 29 Gauge.

(23) The delivery devices described herein can also include one or more automated functions. For example, one or more of needle insertion, medicament injection, and needle retraction can be automated. Energy for one or more automation steps can be provided by one or more energy sources. Energy sources can include, for example, mechanical, pneumatic, chemical, or electrical energy. For example, mechanical energy sources can include springs, levers, elastomers, or other mechanical mechanisms to store or release energy. One or more energy sources can be combined into a single device. Devices can further include gears, valves, or other mechanisms to convert energy into movement of one or more components of a device. The one or more automated functions of an auto-injector may each be activated via an activation mechanism. Such an activation mechanism can include one or more of a button, a lever, a needle sleeve, or other activation component. Activation of an automated function may be a one-step or multi-step process. That is, a user may need to activate one or more activation components in order to cause the automated function. For example, in a one-step process, a user may depress a needle sleeve against their body in order to cause injection of a medicament. Other devices may require a multi-step activation of an automated function. For example, a user may be required to depress a button and retract a needle shield in order to cause injection.

(24) In addition, activation of one automated function may activate one or more subsequent automated functions, thereby forming an activation sequence. For example, activation of a first automated function may activate at least two of needle insertion, medicament injection, and needle retraction. Some devices may also require a specific sequence of steps to cause the one or more automated functions to occur. Other devices may operate with a sequence of independent steps.

(25) Some delivery devices can include one or more functions of a safety syringe, pen-injector, or auto-injector. For example, a delivery device could include a mechanical energy source configured to automatically inject a medicament (as typically found in an auto-injector) and a dose setting mechanism (as typically found in a pen-injector).

(26) Auto-injectors require user actions to commence medicament delivery. One of these actions may involve a user placing a needle cover (also referred to as a needle shroud or needle sleeve) against an injection site of a subject and applying an axial force to the device to cause the needle

cover to retract into the housing of the device. As the needle cover retracts into the housing, the needle of the device extends beyond the needle cover and penetrates the injection site of the subject (e.g. the subject's skin). Medicament delivery may be automatically initiated in response to the retraction of the needle cover or in response to some other action by the user, for example the user pressing a button on the device. Once medicament delivery has been initiated, a medicament delivery mechanism will cause medicament contained within the device to be injected into the subject via the needle. The user should hold the device steady with respect to the injection site during the course of medicament delivery to ensure the needle remains steady within the subject. This is to minimise pain and/or discomfort for the subject, and to prevent a wet injection site, early device removal and/or partial medicament delivery.

(27) After the device is removed from injection site, many autoinjectors cover the needle with the needle cover/needle shroud, which is extended out of the device by a control spring. During activation of the device and while holding the device steady during medicament delivery, the user must counteract the biasing force applied by the control spring to the needle cover. However, some users such as those with impaired dexterity may find it difficult to hold the device steady for a relatively long period of time during medicament delivery. It may be beneficial to provide a device which is easier to handle during medicament delivery.

(28) Injection devices described herein use an attachment element to temporarily adhere the device to a user's skin during medicament delivery. As such, the user of the device may no longer need to counteract the biasing force of the control spring to hold the device steady against the injection site. The device may therefore be easier to handle during medicament delivery, for example by users with impaired dexterity.

(29) Some medicament delivery devices are directly temporarily adhered to the skin, removing the need for the user to apply the hold force. However, any adhesive area will be covered, and the cover must be manually removed by a user before application of the medicament delivery device to the injection site for adhesion. Medicament delivery is then a two handed operation starting with removal of the protective film. The protective film may also be difficult to manually remove for some people, for example by users with impaired dexterity.

(30) FIG. 1 shows a schematic example of a cross section of an injection device **100** according to one or more aspects of the present disclosure. The injection device **100** is configured to inject a medicament into a subject. The injection device **100** comprises an outer casing **102** (also referred to as a housing or injection device body) that encloses a reservoir **104**, a plunger **106** and a rotatable collar **108**. The reservoir **104** typically contains the medicament to be injected, and may, for example, be in the form of a syringe. The injection device **100** can also include a cap assembly **110** that can be detachably mounted to the outer casing **102**. Typically a user must remove cap **110** from the outer casing **102** before device **100** can be operated.

(31) As shown, casing **102** is substantially cylindrical and has a substantially constant diameter along the longitudinal axis of the device **100**. The injection device **100** has a distal region **126** and a proximal region **128**. The term “distal” refers to a location that is relatively closer to a site of injection, and the term “proximal” refers to a location that is relatively further away from the injection site.

(32) The outer casing **102** is closed at a proximal end by a rear casing **114**. A needle **116** and a retractable needle cover **118** (also referred to as a “needle sleeve” or “needle cover”) extend from a distal end of the outer casing **102**. The retractable needle cover **118** is biased axially in the distal direction of the injection device **100**, for example using a control spring **120**. The needle cover **118** is coupled to the outer casing **102** to permit axial movement of needle cover **118** relative to the outer casing **102**. For example, the cover **118** can move in a longitudinal direction parallel to longitudinal axis **112**. Specifically, movement of cover **118** in a proximal direction relative to the casing **102** can cause a needle **116** to extend from distal region of the casing **102**, and outside a distal end of the cover **118**.

(33) The plunger **106** is biased towards the distal end of the injection device **100** by a biasing means, for example comprising a drive spring **122**. The plunger **106** is retained in an initial position by a combination of the rear casing **114** and the collar **108**, preventing the biasing means from displacing the plunger **106** in the distal direction. Activation of the injection device **100** causes the collar **108** to rotate, which releases the plunger **106**. Once released, the biasing means causes the plunger **106** to move in the distal direction (i.e., towards the needle **116** end of the injection device **100**). The plunger **106** contacts a stopper **113** in the reservoir **104**, displacing the stopper **113** in the distal direction and causing medicament stored in the reservoir **104** to be expelled from the injection device **100** via the needle **116**.

(34) Activation of the injection device **100** can occur via several mechanisms. For example, the needle **116** may be fixedly located relative to the casing **102** and initially be located within an extended needle cover **118**. Proximal movement of the needle cover **118** by placing a distal end of the cover **118** against an injection site of the subject and moving the casing **102** in a distal direction will uncover the distal end of the needle **116**. Such relative movement allows the distal end of the needle **116** to extend into the injection site. Such insertion is termed “manual” insertion as the needle **116** is manually inserted via the user's manual movement of the casing **102** relative to cover **118**. Retraction of the cover **118** into the casing **102** causes the collar **108** to rotate, releasing the plunger **106**.

(35) Another form of activation is “automated”, whereby the needle **116** moves relative to casing **102**. Such insertion can be triggered by movement of the cover **118** and/or by another form of activation, such as, for example, user actuation of a button (not shown) of the injection device **100**.

(36) Typically, the user presses the needle cover **118** against an injection site to push the needle cover **118** at least partially into the device casing **102**. The exposed needle **116** is pushed into the injection site of the subject. In a holding position, medicament is automatically dispensed from the needle **116** via an automated mechanism. A user must typically hold the needle cover **118** in the holding position for a predetermined period of time, to ensure that the correct dose of medicament is dispensed from the device **100**, before removing the device **100** from the injection site.

(37) The spring biasing force from the control spring **120** against which the user must apply a force to move the needle cover **118** is one component of an “activation force” of the device **100**. The activation force refers to the force or force profile that the user must exert on the device **100** to move the needle cover **118** from the extended position shown in FIG. 1 to a retracted position within the casing **102** for medicament delivery. If this force or force profile is not well balanced, it can lead to difficulty in activating the device **100** for some users, or increase the pain or anxiety associated with using the device **100**.

(38) Following injection, the needle **116** can be retracted within the cover **118**. Retraction can occur when the cover **118** moves distally under the biasing of the control spring **120** as a user removes the device **100** from the injection site of the subject. Once a distal end of the cover **118** has moved past a distal end of the needle **116** such that the needle **116** is covered, the cover **118** may be locked in its extended position to prevent any (substantial) proximal movement of the cover **118** relative to the casing **102** (i.e., preventing any movement of the cover **118** that would uncover the needle **116**). The cover **118** may be locked by a needle cover non-return element (not shown), such as a catch.

(39) FIG. 2 shows an example of a medicament delivery device **200** in the form of a flat form injection device (hereinafter referred to as the injection device **200**). In contrast FIG. 1 shows an axial form injection device. Injection device **200** is similar to the device shown in FIG. 1 (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 100.

(40) A flat form injection device can also be described as a large volume device as described above with reference to FIG. 1.

(41) The injection device **200** has a main body **202** which is arranged to receive a medicament cartridge or container of medicament **204**. The main body **202** also contains a needle carrier **215**

carrying a needle **216** for the delivery of medicament to a user. The needle carrier **215** is movable with respect to the main body **202**.

(42) The injection device **200** has a needle cover **218**, that is moveable between an initial position (as shown in FIG. 4A) and an activated position (as shown in FIG. 4C). In the initial position the needle cover **218** covers the needle **216**. The needle cover **218** extends past the distal most end of the needle **216** to protect a user from needle sticks. In the activated position the needle **216** protrudes from a distal end of the needle cover **218**. The activated position is for delivery of medicament from the injection device **200**.

(43) The needle cover **218** has a contact face **219** for contacting an injection site **224**, for example a user's skin. The needle cover **218** also has needle cover side walls **217** which extend into the main body **202**.

(44) An attachment element **221** is provided on the contact face **219** of the needle cover **218**. The attachment element **221** is for attaching the injection device **200** to a surface, such as a user's skin or alternative injection site **224**, during delivery of medicament to the user. As the injection device **200** is directly adhered to a user's skin, the user does not need to apply a holding force for the duration of the injection. Therefore, the burden on the user to hold the needle cover **218** in a holding position for a predetermined period of time, to ensure that the correct dose of medicament is dispensed from the device **200**, is reduced.

(45) The attachment element **221** has an adhesive region **223** for releasable attachment to a surface, for example a user's skin or alternative injection site **224**. The adhesive region **223** may comprise an adhesive, glue, sticky tape or any alternative known method of releasably attaching two elements. The adhesive region **223** covers between 40% and 100% of the contact face **219** of the needle cover **218**. However, the precise area of coverage required by the adhesive region **223** is determined relative to the dimensions of the contact face **219**, the holding force required to hold the medicament delivery device **200** during an injection, and the strength and type of adhesive used to form the releasable attachment to the surface.

(46) The attachment element **221** is set back from a distal most end of the injection device **200**, when the needle cover **218** is in the initial position. As the needle cover **218** moves towards the activated position, the attachment element **221** is moved towards the injection site **224**.

(47) The attachment element **221** has a protective barrier **225** covering the adhesive region **223**. The protective barrier **225** is for protecting the adhesive region **223** from losing its adhesive properties, for example by being contaminated with dirt or debris, until the injection device **200** is ready to be attached to the injection site. The protective barrier **225** is typically a thin layer of material which can easily be removed from the adhesive region **223**. Typically the protective barrier **225** is not adhesive itself, and is releasably attached to the adhesive region **223** of the attachment element **221** due to the adhesive properties of the adhesive region **223**. The protective barrier **225** may be made of a thin film of polymeric material. Optionally the thickness of the protective barrier **225** is between 0.05 mm and 0.2 mm.

(48) The injection device **200** comprises an outer frame **227**. The outer frame **227** is moveable relative to the main body **202** between an extended position (as shown in FIG. 3A and FIG. 4A) in which the outer frame **227** extends past a distal end of the needle cover **218**, and a retracted position (as shown in FIG. 3B and FIG. 4C) in which the outer frame **227** is received at least partially in the main body **202**. In the retracted position the outer frame **227** does not extend past a distal most end of the needle cover **218**. As illustrated in the embodiment shown in FIG. 2 the outer frame **227** is arranged to move axially in a proximal direction towards the main body **202** from the extended position to the retracted position as a user presses the injection device **200** against a surface.

(49) FIG. 3A shows the injection device **200** when the outer frame **227** is in the extended position and the protective barrier **225** covers the adhesive region **223**. When the outer frame **227** is in the extended position and the needle cover **218** is in the initial position, the outer frame **227** surrounds

the needle cover **218**. FIG. 3B shows the injection device **200**, when the outer frame **227** is in the retracted position, the protective barrier **225** has been removed to expose the adhesive region **223**, and the attachment element **221** is adhered to a user's skin for medicament delivery. When the outer frame **227** is in the retracted position and the needle cover **218** is in the activated position abutting an injection site **224**, the outer frame **227** surrounds the needle cover **218**.

(50) FIG. 4A to FIG. 4C shows the protective barrier **225** coupled to the outer frame **227**. Movement of the outer frame **227** in a proximal direction relative to the attachment element **221** removes the protective barrier **225** to expose the adhesive region **223**. The protective barrier **225** is fixed at a first end **230** to an internal wall **231** of the outer frame **227**. The protective barrier **225** is folded on itself to form a double layer of the protective barrier **225** at a second end **232**. The second end **232**, is releasably attached to the attachment element **221**.

(51) The portion of the protective barrier **225** between the second end **232** and the fold **234** can be referred to as a folded portion **233**. The protective barrier **225** is folded on itself in a proximal direction, such that the folded portion **233** is located between the attachment element **221** and the rest of the protective barrier **225**.

(52) The outer frame **227** is arranged to contact the injection site **224** before the main body **202** or the needle cover **218**. The outer frame **227** comprises a flange **257** on its distal most end for contacting the injection site **224** for the delivery of medicament.

(53) As the user presses the outer frame **227** against the injection site the outer frame **227** is pushed at least partially into the main body **202**. The main body **202** has a frame cavity **229** to receive the outer frame **227** within the main body **202**. The frame cavity **229** extends continuously around an inside edge of the main body **202**, and in the retracted position, the majority of the outer frame **227** is received within the frame cavity **229**.

(54) The outer frame **227** is moveable relative to the attachment element **221**. As the outer frame **227** is pushed into the main body **202**, the outer frame **227** moves the first end **230** of the protective barrier **225** in a proximal direction relative to the attachment element **221**. The second end **232** of the protective barrier **225** remains substantially in the same position. This causes tension in the protective barrier **225**. As the first end **230** moves further in a proximal direction, the protective barrier **225** begins to peel away from the attachment element **221**. Further movement of the outer frame **227**, and the first end **230**, causes the protective barrier **225** to be removed at least partially from the attachment element **221**. The adhesive region **223** is exposed as the protective barrier **225** is removed.

(55) As the user continues to push the injection device **200** on to the injection site **224**, the outer frame **227** moves towards its retracted position and the exposed adhesive region **223** contacts the injection site **224**. As the adhesive region **223** is pressed onto the injection site **224**, the injection device **200** is adhered to the user's skin. The pushing action described in this specification, can also be described as the user applying an axial force in a distal direction on the injection device **200**.

(56) Once the adhesive region **223** is adhered to the injection site, continued pushing of the injection device **200** causes the needle cover **218** to be pushed at least partially into the main body **202**. In other words, the needle cover **218** is caused to move from the initial position to the activated position. As the needle cover **218** is pushed further into the main body **202**, the needle **216** is inserted into the injection site **224**, the plunger **206** is released and medicament delivery begins. Further details of the movement of the needle cover **218** and instigation of medicament delivery is described above with reference to FIG. 1 and is not repeated here for brevity.

(57) Once the attachment element **221** has adhered the injection device **200** to the injection site, a user may let go of the injection device **200** until medicament delivery has been completed and in some embodiments, the needle **216** is retracted safely into the injection device **200**.

(58) A user can remove the protective barrier **225**, adhere the injection device **200** to the injection site and instigate medicament delivery of the injection device, all within a single action. Typically, with a single movement in an axial distal direction. A user is also able to remove the protective

barrier **225**, adhere the injection device **200** to the injection site and instigate medicament delivery of the injection device with one hand. As the injection device **200** is adhered to the injection site **224**, a user does not need to apply a holding force, i.e. hold the needle cover **218** in the holding position (further details of the holding position are described with reference to FIG. **1**).

(59) The adhesive force of the adhesive region **223** is stronger than the needle cover **218** spring force. If the adhesive force from the adhesive region **223** was not greater than the needle cover **218** spring force then the needle cover **218** spring force will push the injection device **200** off of the injection site **242** during medicament delivery.

(60) FIG. **5** shows an example of a medicament delivery device **300** (hereinafter referred to as the injection device **300**). Injection device **300** is similar to the device shown in FIG. **2** (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 100. One difference of this example is that injection device **300** comprises the outer frame **327** external to the main body **302**.

(61) FIG. **6** shows an example of a medicament delivery device **400** (hereinafter referred to as the injection device **400**). Injection device **400** is similar to the device shown in FIG. **2** (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 200. One difference of this example is that the attachment element **421** is not located on the contact face **419** of the needle cover **418**, but on an attachment element support **440**. A further difference is that the outer frame **427** is adjacent to the needle cover **418** and not surrounding the needle cover **418**.

(62) The attachment element support **440** is coupled to the main body **402** of the injection device **400**. The attachment element **421** is coupled to the support **440** and is able to move independently of the needle cover **418**. The attachment element support **440** is fixed with respect to the rest of the main body **402** and the attachment element **421** is pushed towards the injection site **424** as the main body **402** is pushed towards the injection site **424**.

(63) The injection device **400** is pushed towards the injection site **424** by a user. The outer frame **427** contacts the injection site **424** before the needle cover **418**, and before the main body **402**. The outer frame **427** is moveable relative to the main body **402** between an extended position (as shown in FIG. **6A**) in which the outer frame **427** extends past a distal end of the needle cover **418**, and a retracted position (as shown in FIG. **6B**) in which the outer frame **427** is received at least partially in the main body **402**. In the retracted position the outer frame **427** does not extend past a distal most end of the needle cover **418**.

(64) Relative motion between the outer frame **427** and the attachment element **421** removes the protective barrier **425** (as described in more detail with reference to FIG. **2**). In the retracted position, the protective barrier **425** has been removed from the attachment element **440** to expose the adhesive region **423**.

(65) For an injection device with manual needle insertion, as the user continues to push the device on to the injection site **424** the needle cover **418** contacts the injection site **424**. The user must overcome the needle cover spring force (as described in more detail with reference to FIG. **1**) to push the adhesive region **423** against the injection site **424**. The user continues to push the injection device **400** on to the injection site adhering the adhesive region **423** close to the injection site **424**, and inserting the needle **416** into the injection site **424**. Once the needle **416** is fully inserted the user can remove their force. As the adhesive force is stronger than the needle cover spring force medicament delivery occurs whilst the injection device **400** remains adhered to the injection site **424**.

(66) When the delivery of medicament is complete, the user then removes the injection device **400** from the injection site **424**. The needle cover **418** extends out of the main body **402** under the force of the needle cover spring so that the needle **416** is not exposed.

(67) FIG. **7A** and FIG. **7B** show an example of a medicament delivery device **500** (hereinafter referred to as the injection device **500**). Injection device **500** is similar to the device shown in FIG.

2 (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 300. One difference of this example is that the attachment element **521** is not located on the contact face **519** of the needle cover **518**, but on a part of the outer frame **527**. A further difference is that outer frame **527** pivots relative to the main body **502** to move between the extended and retracted position.

(68) FIG. 7A shows the injection device **500** with the outer frame **527** in the extended position, and FIG. 7B shows the injection device **500** with the outer frame in the retracted position.

(69) The injection device **500** comprises a front end **552** and a rear end **553**. The front end **552** is closer to the needle **516** than the rear end **553**. The pivotable connection **554** (referred to as a pivot from here on for brevity) between the main body **502** and the outer frame **527** is typically located towards the rear end **553**. The outer frame **527** extends further out from the main body **502** at the front end **552** than at the rear end **553**. This causes the outer frame **527** visible in the extended position to be wedge shaped in cross section.

(70) The outer frame **527** has a housing **541** comprising a contact surface **542** and a surrounding wall **545** extending from the contact surface **542**. The surrounding wall **545** extends at least partially into the main body **502**. The surrounding wall **545** is larger at the end opposite to the pivot **554**. The contact surface **542** is configured to be pushed against an injection site **524** to begin actuation of the injection device **500**. The contact surface **542** comprises an aperture **544** and a needle hole **546**.

(71) Needle hole **546** is configured to be aligned with the needle **516** when the outer frame **527** is in the retracted position, such that the needle **516** can extend through the needle hole **546** for the delivery of medicament. The needle hole **546** is of a similar size to the needle such that the risk of debris and dirt entering the injection device **500** through the needle hole **546** is reduced. However, enough clearance is provided around the needle **516** such that it can easily extend and retract through the needle hole **546**.

(72) Coupled to the contact surface **542** is an attachment element **521** covered by a protective barrier **525**. Some details of the attachment element **521** and protective barrier **525** have been described with reference to FIG. 2 and will not be repeated here for brevity. As shown in FIGS. 7A and 7B the attachment element **521** comprises two adhesive regions **523a**, **523b**. A first adhesive region **523a** is disposed on one side of the aperture **544**, and a second adhesive region **523b** is disposed on the other side of the aperture **544**. Although two adhesive regions **523a**, **523b** are shown in the figures, it can be appreciated that there could be more than two, or that the adhesive region could extend around the aperture **544** to form a single continuous adhesive region covering both sides of the aperture **544**. The aperture **544** is of a similar width to the protective barrier **525** such that protective barrier can enter and exit the aperture without being hindered or caught by the edges of the aperture **544**. Typically the aperture **544** is in the form of a slit. Typically, the aperture **544** extends over the majority of a width of the contact surface **542**.

(73) The outer frame **527** further comprises a removal arm **543**. A proximal end **547** of the removal arm **543** is pivotally coupled to the main body **502**. The removal arm **543** has a distal end **548** which extends away from the main body **502** in a distal direction towards the contact surface **542** of the outer frame **527**, when the outer frame **527** is in the extended position.

(74) At its distal end **548** the removal arm **543** comprises a fastener **550** to attach the removal arm **543** to the protective barrier **525**. The protective barrier **525** can be attached to the fastener **550** in many known ways, for example by clamping, tying, using an adhesive, the protective barrier **525** could comprise holes and the fastener **550** could comprise pins through the holes to keep the protective barrier **525** in place. The fastener **550** is attached to an intermediate point **551** of the protective barrier **525** between its first end **530** and its second end **532**. Typically, the fastener **550** is attached near to a mid point of the protective barrier **525**. The protective barrier **525** covers the first adhesive region **523a**, extends through the aperture **544** in the outer frame **527** to attach to the fastener **550**. The protective barrier **525** then extends back out through the aperture **544** and covers

the second adhesive region **523b**.

(75) Typically the protective barrier **525** is a single continuous component. However, it can be envisaged that the protective barrier **525** is more than one component attached together, either attached at the fastener **550** or to each other. For example, in the embodiment shown in FIG. 7A the protective barrier **525** may comprise two parts, a first part covering the first adhesive region **523a** and a second part covering the second adhesive region **523b**. The two parts may both extend through the aperture **544** to each be attached to the fastener **550**.

(76) As described with reference to FIG. 2 the protective barrier **525** may be folded at its first end to form a double layer of protective barrier **525** where it is removably attached to the attachment element. It is folded in a proximal direction to form a double layer. Differently to the embodiment described in FIG. 2, the protective barrier **525** may also be folded at its second end to form a double layer of protective barrier **525** where it is removably attached to the attachment element **521**. In some embodiments the protective barrier **525** is also folded to form a double layer at the intermediate point **551**, with both layers being coupled to the fastener **550**.

(77) The injection device **500** is pushed towards the injection site **524** by a user. The outer frame **527** contacts the injection site **524** before the needle cover **518**, and before the main body **502**. Continued force on the injection device **500** by the user causes the outer frame **527** to move from the extended to the retracted position. As the outer frame **527** moves towards the retracted position, the main body **502** applies a force in a distal direction to the removal arm **543**. The distal end **548** of the removal arm **543** is moveable relative to an internal face **549** of the contact surface **542**. Pushing on the removal arm **543** causes the pivot **554** to be moved in a distal direction. The removal arm **543** extends between the main body **502** and the outer frame **527**. Therefore, as the distance between the main body **502** and the internal face **549** of the outer frame **527** is decreased, the removal arm **543** begins to rotate about the pivot **554**, and the distal end **548** of the removal arm **543** is pushed along the internal face **549**. As the removal arm **543** is pushed along the internal face **549**, and the distance between the main body **502** and the internal face **549** decreases, the removal arm **543** moves towards a position parallel to the internal face **549**.

(78) The distance between the aperture **544** and the second end **548** is therefore increased as the outer frame **527** is moved towards the retracted position. The increasing distance between the aperture **544** and the second end **548** causes the removal arm **543** to pull the protective barrier **525** in through the aperture **544** and away from the attachment element **521**. Removing the protective barrier **525** from the attachment element **521** exposes the adhesive regions **523a**, **523b**.

(79) The user continues to push the injection device **500** on to the injection site **524** adhering the adhesive region **523a**, **523b** close to the injection site **524**, and inserting the needle **516**. Once the needle **516** is fully inserted into the injection site, the user can remove their force. Medicament delivery occurs whilst the injection device **500** remains adhered to the injection site **524**. When the delivery of medicament is complete, the user removes the injection device **500** from the injection site **524** by peeling the adhesive region **523a**, **523b** from the injection site **524**.

(80) FIG. 8A and FIG. 8B show an example of a medicament delivery device **600** (hereinafter referred to as the injection device **600**). Injection device **600** is similar to the device shown in FIG. 2 (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 400. One difference of this example is that the outer frame **627** comprises a releasable mechanism **655** to retract the protective barrier **625**.

(81) FIG. 8A shows the injection device **600** with the outer frame **627** in the extended position, and FIG. 8B shows the injection device **600** as it moves towards the retracted position and the protective barrier **625** is removed.

(82) The releasable mechanism **655** comprises at least one releasable component, and a first end **630** of the protective barrier **625** is attached to the at least one releasable component **655**, and a second end **632** of the protective barrier **625** is releasably attached to the attachment element **621**.

(83) The releasable mechanism **655** shown in FIGS. 8A and 8B is a set of releasable components,

and the releasable component is a roller. In particular a set of sprung rollers (hereinafter referred to as biased rollers). The releasable components **655** are installed towards a proximal end of the outer frame **627**.

(84) The protective barrier **625** is fixed at a first end **630** by being wound around the biased rollers **655**. The protective barrier **625** is folded on itself to form a double layer of the protective barrier **625** at a second end **232**. As described in more detail with respect to FIG. 2, the second end **632**, is releasably attached to the attachment element **621**.

(85) The protective barrier **625** comprises a number of components or parts equal to the number of releasable components **655**. As shown in FIG. 8A the protective barrier **625** comprises two parts and therefore two releasable components **655**.

(86) As the outer frame **627** is pushed against the injection site **624**, the outer frame **627** moves in an axial proximal direction and releases the releasable rollers **655**. The rollers **655** can be released by any known means for example a button, lever, catch or latch. Once released, the releasable rollers **655** begin to wind the protective barrier **625** around themselves, pulling the protective barrier **625** in a proximal direction. This causes tension in the protective barrier **625**, which causes the protective barrier **225** to begin to peel away from the attachment element **221**. Continued winding of the releasable rollers **655** causes the protective barrier **625** to be removed at least partially from the attachment element **621**. The adhesive region **623** is exposed as the protective barrier **625** is removed.

(87) As the user continues to push the injection device **600** on to the injection site **624**, the outer frame **627** moves towards the retracted position and the exposed adhesive region **623** contacts the injection site **624**. As the adhesive region **623** is pressed onto the injection site **624**, the injection device **600** is adhered to the user's skin.

(88) Once the adhesive region **623** is adhered to the injection site **624**, a continued force on the injection device **600** in a distal direction actuates the delivery of medicament to the injection site **624**. Further details of the movement of the needle cover **618** and instigation of medicament delivery is described above with reference to FIG. 1 and FIG. 2 and is not repeated here for brevity.

(89) Once the attachment element **621** has adhered the injection device **600** to the injection site, a user may let go of the injection device **600** until medicament delivery has been completed.

(90) FIG. 9A and FIG. 9B show an example of a medicament delivery device **700** (hereinafter referred to as the injection device **700**). Injection device **700** is similar to the device shown in FIG. 2 (and therefore the description will not be repeated here for brevity) and similar features have been given the same reference numeral but increased by 500. One difference of this example is that the outer frame **727** comprises at least one tension member **756** to hold the protective barrier **725** in tension as it is removed from the attachment element **721**.

(91) The tension members **756** are two sets of rollers, a set of distal tension rollers **756a**, **756b** and a set of proximal tension rollers **756c**, **756d**. The protective barrier **725** is fixed at its first end **730** to the main body **702**. The protective barrier **725** extends round the proximal tension roller **756c**, **756d**, then round the distal tension roller **756a**, **756b**. The protective barrier **725** is then coupled at its second end **732** to the attachment element **721** to cover the adhesive region **723**. The protective barrier **725** is folded near to its second end **732** as described in more detail with reference to FIG. 4A to FIG. 4C. The outer frame **727** is coupled to the main body **702**, and is moveable relative to the needle cover **718** and the main body **702**.

(92) As the outer frame **727** moves towards the retracted position (i.e. towards the main body **702**), the protective barrier **725** is removed from the attachment element **721** to expose the adhesive region **723**.

(93) In some embodiments a taut surface at the injection site **724** may be beneficial. For example, users of the injection device **700** can have loose skin or the injection site **724** may not be a flat surface. In such cases, stretching the skin at the injection site **724** may facilitate better control of the injection site **724** relative to the device **700** in terms of stiffness, position and deformation. This

may in turn increase the chances of an accurate needle insertion depth.

(94) As the protective barrier **725** is removed from the attachment element **721**, it drags across the user's skin in a direction away from the injection site **724**. As the injection device **700** is pressed against the injection surface, the initial motion of the outer frame **727** relative to the main body **702** pulls the protective barrier **725** round the tension members, **756a**, **756c** and/or **756b**, **756d** to remove the protective barrier **725** from the attachment element **721**. When the outer frame **727** contacts the user's skin, the attachment element **721** is held between the outer frame and the user's skin. In this position, any force on the injection device **700** in a distal direction will create a frictional force between the attachment element **721**, or more specifically the adhesive region **723**, and the user's skin. The frictional force can be increased or decreased by varying the axial force on the injection device **700**, or changing the surface texture, for example by choice of material or by providing a textured or grippable surface. The frictional force between the protective barrier **725** and the skin causes the skin to be pulled in a direction away from the injection site **724**, tightening the skin at the injection site **724**. As the protective barrier **725** comprises two components in some embodiments, for example as shown in FIG. **9A** and FIG. **9B**, the skin is pulled in opposing directions as the protective barrier **725** is removed, facilitating a taut, flatter surface prior to the needle **716** being inserted.

(95) Once the needle **716** has entered the injection site **724**, the protective barrier **725** has dragged the skin away from the injection site **724** and the adhesive region **723** is adhered to the user's skin in the taut position. The skin is therefore held in the taut position for the duration of medicament delivery. Once medicament delivery is complete, and the injection device **700** is removed from the injection site **724**, the skin returns to its original state.

(96) In some embodiments the protective barrier **725** may be a continuous sheet that is releasably attached to the attachment element **721** at its first end **730** and at its second end **732**. The protective barrier **725** extends from the attachment element **721**, around the first distal tension roller **756a**, around the first proximal tension roller **756c**, around the second proximal tension roller **756d**, around the second distal tension roller **756b**, and back to the attachment element **721**. The protective barrier **725** is folded on itself to form a double layer of the protective barrier **725** at both the first end **730** and the second end **732**. In such embodiments, the needle **716** may penetrate the protective barrier **725** as it pierces the injection site **724**.

(97) It can be envisaged that the tension members **756** may not be rollers, but may be stationary members such as static bearings, such that the tension members **756** are stationary (and do not rotate as the rollers do) as the protective barrier **725** is removed from the attachment element **721**. It can also be envisaged that there may be only two tension members **756**, or more than four tension members **756**. In some embodiments the tension members **756** may be replaced with a static frame around which the protective barrier **725** is wound.

(98) FIG. **10** shows a flow chart of an example of a method of operating a medicament delivery device. Steps of the method illustrated in FIG. **10** may be applicable to any of the examples shown in FIG. **1** to FIG. **9**.

(99) In one step **801** the outer frame **227**, **327**, **427**, **527**, **627**, **727** is moved relative to a main body **102**, **202**, **302**, **402**, **502**, **602**, **702** of the medicament delivery device **100**, **200**, **300**, **400**, **500**, **600**, **700** from an extended position, in which the outer frame **227**, **327**, **427**, **527**, **627**, **727** extends past a distal end of a needle cover **118**, **218**, **318**, **418**, **518**, **618**, **718**, to a retracted position, in which the outer frame **227**, **327**, **427**, **527**, **627**, **727** is moved towards the main body **102**, **202**, **302**, **402**, **502**, **602**, **702**.

(100) In another step **802** the adhesive region **223**, **323**, **423**, **523a**, **523b**, **623**, **723** of an attachment element **221**, **321**, **421**, **521**, **621**, **721** is exposed by removing a protective barrier **225**, **325**, **425**, **525**, **625**, **725** covering the adhesive region **223**, **323**, **423**, **523a**, **523b**, **623**, **723**, wherein the protective barrier **225**, **325**, **425**, **525**, **625**, **725** is coupled to an outer frame **227**, **327**, **427**, **527**, **627**, **727** of the medicament delivery device **100**, **200**, **300**, **400**, **500**, **600**, **700** and is removed as

the outer frame 227, 327, 427, 527, 627, 727 is moved towards the retracted position.

(101) In another step 803 the exposed adhesive region 223, 323, 423, 523a, 523b, 623, 723 of the attachment element 221, 321, 421, 521, 621, 721 is adhered to an injection surface 224, 324, 424, 524, 624, 724 for the delivery of medicament.

(102) In another optional step 804 the needle cover 118, 218, 318, 418, 518, 618, 718 is moved from an initial position, in which a needle cover 118, 218, 318, 418, 518, 618, 718 covers a needle 116, 216, 316, 416, 516, 716, to an activated position for dispensing medicament from the medicament delivery device 100, 200, 300, 400, 500, 600, 700, wherein in the activated position the needle 116, 216, 316, 416, 516, 716, protrudes from a distal end of the needle cover 118, 218, 318, 418, 518, 618, 718.

(103) In the above-described embodiments the adhesive region 223 of the attachment element 221 covers between 40% and 100% of the contact face 219. However, in alternative embodiments intended within the scope of the present disclosure, the adhesive region 223 of the attachment element 221 covers between 50% and 100% of the contact face 219. It can also be envisaged that the adhesive region 223 covers between 50% and 90% of the contact face 219, or between 60% and 90% of the contact face 219. The precise area of coverage required by the adhesive region 223 is determined relative to the dimensions of the contact face 219 and or outer frame 227, the holding force required to hold the medicament delivery device, 100, 200, 300, 400, 500, and the strength and type of adhesive used to form the releasable attachment to the surface.

(104) In the above-described embodiments the adhesive region 223, 323, 423, 523a, 523b, 623, 723 of the attachment element 221, 321, 421, 521, 621, 721 is described as single element 223, 323, 423, 623, or two elements 523a, 523b. However, in alternative embodiments intended within the scope of the present disclosure, the adhesive region of the attachment element can be a single continuous patch (where two or more have been described), a number of patches, dots, lines or patterns of adhesive, or any combination of the above.

(105) In the above-described embodiments the protective barrier 225, 325, 425, 525, 625, 725 is described as being a single element or two elements. However, in alternative embodiments intended within the scope of the present disclosure, any of the above described embodiments may comprise a protective barrier 225, 325, 425, 525, 625, 725 with one or more components. In embodiments where more than one component is described, it is intended within the scope of the present disclosure that the protective barrier 225, 325, 425, 525, 625, 725 may comprise a single component that extends to cover the or all adhesive regions 223, 323, 423, 523a, 523b, 623, 723.

(106) In the above-described embodiments the protective barrier 225, 325, 425, 525, 625, 725 is not adhesive itself, and is releasably attached to the adhesive region 223, 323, 423, 523a, 523b, 623, 723 of the attachment element 221, 321, 421, 521, 621, 721 due to the adhesive properties of the adhesive region 223. However, in alternative embodiments intended within the scope of the present disclosure, the protective barrier 225 may be adhesive, for example in embodiments in which the protective barrier is attached to a part of the attachment element not covered by the adhesive region 223, or attached to a further part of the injection device 200.

(107) In the above-described embodiments the protective barrier 225, 325, 425, 525, 625, 725 is folded on itself to form a double layer of the protective barrier 225, 325, 425, 525, 625, 725 at a second end 232, 332, 432, 532, 632, 732. This provides improved peeling of the protective barrier 225, 325, 425, 525, 625, 725 from the attachment element 221, 321, 421, 521, 621, 721. However, in alternative embodiments intended within the scope of the present disclosure, the protective barrier 225, 325, 425, 525, 625, 725 may not be folded at the second end 232, 332, 432, 532, 632, 732.

(108) In some embodiments the needle 116, 216, 316, 416, 516, 616, 716 is configured to penetrate the attachment element 221, 321, 421, 521, 621, 721 and/or the adhesive region 223, 323, 423, 523a, 523b, 623, 723 during delivery of medicament from the medicament cartridge 104, 204, 304, 404, 504, 604, 704. In other embodiments the needle 116, 216, 316, 416, 516, 616, 716 is

configured to deliver medicament from the medicament cartridge **104, 204, 304, 404, 504, 604, 704** without contacting the attachment element **221, 321, 421, 521, 621, 721** and/or the adhesive region **223, 323, 423, 523, 623, 723**.

(109) In some of the above-described embodiments the outer frame **227, 327, 427, 627, 727** comprises a flange **257, 357, 657**. However, it is intended within the scope of the present disclosure that all of the injection devices **100, 200, 300, 400, 500, 600, 700** may or may not comprise a flange **257, 357, 657**, for contacting the injection site **124, 224, 324, 424, 524, 624, 724**.

(110) In some of the above-described embodiments the attachment element **221, 321, 421, 521, 621, 721** is described as being set back in a proximal direction from a distal most end of the injection device **100, 200, 300, 400, 500, 600, 700**. However, it is intended within the scope of the present disclosure that all of the injection devices **100, 200, 300, 400, 500, 600, 700** may comprise the attachment element **221, 321, 421, 521, 621, 721** set back in a proximal direction from a distal most end of the injection device **100, 200, 300, 400, 600, 700**. For example with reference to the embodiment shown in FIGS. 7A and 7B, the outer frame **527** may comprise a rim which extends past the contact surface **542**.

(111) In some embodiments the needle **116, 216, 316, 416, 516, 616, 716** is configured to penetrate the attachment element **221, 321, 421, 521, 621, 721** and/or the adhesive region **223, 323, 423, 523a, 523b, 623, 723** during delivery of medicament from the medicament cartridge **104, 204, 304, 504, 604, 704**. This is where the attachment element or adhesive region extends across a path of the needle **116, 216, 316, 416, 516, 616, 716**. However it can be envisaged that the attachment element **221, 321, 421, 521, 621, 721** or adhesive regions **223, 323, 423, 523a, 523b, 623, 723** have a portion that is absent where the needle protrudes, or the attachment element **221, 321, 421, 521, 621, 721** or adhesive regions **223, 323, 423, 523a, 523b, 623, 723** are located surrounding or next to the path of the needle **116, 216, 316, 416, 516, 616, 716**. The path of the needle is the path the needle **116, 216, 316, 416, 516, 616, 716** takes as it moves from its initial position retracted within the injection device **100, 200, 300, 400, 500, 600, 700**, to an extended/activated position for the delivery of medicament, where it extends from a distal most end of the injection device **100, 200, 300, 400, 500, 600, 700**.

(112) In some embodiments the medicament delivery device **100, 200, 300, 400, 500, 600, 700** is an auto-injector. In some embodiments the medicament delivery device comprises manual needle insertion, in others the medicament delivery device comprises automatic needle insertion.

(113) In some embodiments automatic needle insertion is triggered by movement of the needle cover **118, 218, 318, 418, 518, 618, 718** towards the main body **102, 202, 302, 303, 402, 502, 602, 702**, in other embodiments the medicament delivery device **100, 200, 300, 400, 500, 600, 700** comprises a button or alternative activation means to activate automatic needle insertion.

(114) Although pulling the user's skin taut is described with reference to FIGS. 9A and 9B. It can be envisaged that this is applicable to any embodiment in which the protective barrier **225, 325, 425, 525, 625, 725** is against a user's skin during removal.

(115) The term “protective barrier” as used throughout, may also mean a protective barrier with more than one component, for example, two parts, the description being applicable to both, or all, parts.

(116) The terms “drug” or “medicament” are used synonymously herein and describe a pharmaceutical formulation containing one or more active pharmaceutical ingredients or pharmaceutically acceptable salts or solvates thereof, and optionally a pharmaceutically acceptable carrier. An active pharmaceutical ingredient (“API”), in the broadest terms, is a chemical structure that has a biological effect on humans or animals. In pharmacology, a drug or medicament is used in the treatment, cure, prevention, or diagnosis of disease or used to otherwise enhance physical or mental well-being. A drug or medicament may be used for a limited duration, or on a regular basis for chronic disorders.

(117) As described below, a drug or medicament can include at least one API, or combinations

thereof, in various types of formulations, for the treatment of one or more diseases. Examples of API may include small molecules having a molecular weight of 500 Da or less; polypeptides, peptides and proteins (e.g., hormones, growth factors, antibodies, antibody fragments, and enzymes); carbohydrates and polysaccharides; and nucleic acids, double or single stranded DNA (including naked and cDNA), RNA, antisense nucleic acids such as antisense DNA and RNA, small interfering RNA (siRNA), ribozymes, genes, and oligonucleotides. Nucleic acids may be incorporated into molecular delivery systems such as vectors, plasmids, or liposomes. Mixtures of one or more drugs are also contemplated.

(118) The drug or medicament may be contained in a primary package or “drug container” adapted for use with a drug delivery device. The drug container may be, e.g., a cartridge, syringe, reservoir, or other solid or flexible vessel configured to provide a suitable chamber for storage (e.g., short- or long-term storage) of one or more drugs. For example, in some instances, the chamber may be designed to store a drug for at least one day (e.g., 1 to at least 30 days). In some instances, the chamber may be designed to store a drug for about 1 month to about 2 years. Storage may occur at room temperature (e.g., about 20° C.), or refrigerated temperatures (e.g., from about -4° C. to about 4° C.). In some instances, the drug container may be or may include a dual-chamber cartridge configured to store two or more components of the pharmaceutical formulation to-be-administered (e.g., an API and a diluent, or two different drugs) separately, one in each chamber. In such instances, the two chambers of the dual-chamber cartridge may be configured to allow mixing between the two or more components prior to and/or during dispensing into the human or animal body. For example, the two chambers may be configured such that they are in fluid communication with each other (e.g., by way of a conduit between the two chambers) and allow mixing of the two components when desired by a user prior to dispensing. Alternatively or in addition, the two chambers may be configured to allow mixing as the components are being dispensed into the human or animal body.

(119) The drugs or medicaments contained in the drug delivery devices as described herein can be used for the treatment and/or prophylaxis of many different types of medical disorders. Examples of disorders include, e.g., diabetes mellitus or complications associated with diabetes mellitus such as diabetic retinopathy, thromboembolism disorders such as deep vein or pulmonary thromboembolism. Further examples of disorders are acute coronary syndrome (ACS), angina, myocardial infarction, cancer, macular degeneration, inflammation, hay fever, atherosclerosis and/or rheumatoid arthritis. Examples of APIs and drugs are those as described in handbooks such as Rote Liste 2014, for example, without limitation, main groups 12 (anti-diabetic drugs) or 86 (oncology drugs), and Merck Index, 15th edition.

(120) Examples of APIs for the treatment and/or prophylaxis of type 1 or type 2 diabetes mellitus or complications associated with type 1 or type 2 diabetes mellitus include an insulin, e.g., human insulin, or a human insulin analogue or derivative, a glucagon-like peptide (GLP-1), GLP-1 analogues or GLP-1 receptor agonists, or an analogue or derivative thereof, a dipeptidyl peptidase-4 (DPP4) inhibitor, or a pharmaceutically acceptable salt or solvate thereof, or any mixture thereof. As used herein, the terms “analogue” and “derivative” refers to a polypeptide which has a molecular structure which formally can be derived from the structure of a naturally occurring peptide, for example that of human insulin, by deleting and/or exchanging at least one amino acid residue occurring in the naturally occurring peptide and/or by adding at least one amino acid residue. The added and/or exchanged amino acid residue can either be codable amino acid residues or other naturally occurring residues or purely synthetic amino acid residues. Insulin analogues are also referred to as “insulin receptor ligands”. In particular, the term “derivative” refers to a polypeptide which has a molecular structure which formally can be derived from the structure of a naturally occurring peptide, for example that of human insulin, in which one or more organic substituent (e.g., a fatty acid) is bound to one or more of the amino acids. Optionally, one or more amino acids occurring in the naturally occurring peptide may have been deleted and/or replaced by

other amino acids, including non-codeable amino acids, or amino acids, including non-codeable, have been added to the naturally occurring peptide.

(121) Examples of insulin analogues are Gly(A21), Arg(B31), Arg(B32) human insulin (insulin glargine); Lys(B3), Glu(B29) human insulin (insulin glulisine); Lys(B28), Pro(B29) human insulin (insulin lispro); Asp(B28) human insulin (insulin aspart); human insulin, wherein proline in position B28 is replaced by Asp, Lys, Leu, Val or Ala and wherein in position B29 Lys may be replaced by Pro; Ala(B26) human insulin; Des(B28-B30) human insulin; Des(B27) human insulin and Des(B30) human insulin.

(122) Examples of insulin derivatives are, for example, B29-N-myristoyl-des(B30) human insulin, Lys(B29) (N-tetradecanoyl)-des(B30) human insulin (insulin detemir, Levemir®); B29-N-palmitoyl-des(B30) human insulin; B29-N-myristoyl human insulin; B29-N-palmitoyl human insulin; B28-N-myristoyl LysB28ProB29 human insulin; B28-N-palmitoyl-LysB28ProB29 human insulin; B30-N-myristoyl-ThrB29LysB30 human insulin; B30-N-palmitoyl-ThrB29LysB30 human insulin; B29-N—(N-palmitoyl-gamma-glutamyl)-des(B30) human insulin, B29-N-omega-carboxypentadecanoyl-gamma-L-glutamyl-des(B30) human insulin (insulin degludec, Tresiba®); B29-N—(N-lithocholyl-gamma-glutamyl)-des(B30) human insulin; B29-N-(ω-carboxyheptadecanoyl)-des(B30) human insulin and B29-N-(ω-carboxyheptadecanoyl) human insulin.

(123) Examples of GLP-1, GLP-1 analogues and GLP-1 receptor agonists are, for example, Lixisenatide (Lyxumia®), Exenatide (Exendin-4, Byetta®, Bydureon®, a 39 amino acid peptide which is produced by the salivary glands of the Gila monster), Liraglutide (Victoza®), Semaglutide, Taspoglutide, Albiglutide (Syncria®), Dulaglutide (Trulicity®), rExendin-4, CJC-1134-PC, PB-1023, TTP-054, Langlenatide/HM-11260C (Efpeglenatide), HM-15211, CM-3, GLP-1 Eligen, ORMD-0901, NN-9423, NN-9709, NN-9924, NN-9926, NN-9927, Nodexen, Viador-GLP-1, CVX-096, ZYOG-1, ZYD-1, GSK-2374697, DA-3091, MAR-701, MAR709, ZP-2929, ZP-3022, ZP-DI-70, TT-401 (Pegapamodtide), BHM-034, MOD-6030, CAM-2036, DA-15864, ARI-2651, ARI-2255, Tirzepatide (LY3298176), Bamadutide (SAR425899), Exenatide-XTEN and Glucagon-Xten.

(124) An example of an oligonucleotide is, for example: mipomersen sodium (Kynamro®), a cholesterol-reducing antisense therapeutic for the treatment of familial hypercholesterolemia or RG012 for the treatment of Alport syndrome.

(125) Examples of DPP4 inhibitors are Linagliptin, Vildagliptin, Sitagliptin, Denagliptin, Saxagliptin, Berberine.

(126) Examples of hormones include hypophysis hormones or hypothalamus hormones or regulatory active peptides and their antagonists, such as Gonadotropine (Follitropin, Lutropin, Choriogonadotropin, Menotropin), Somatropine (Somatropin), Desmopressin, Terlipressin, Gonadorelin, Triptorelin, Leuprorelin, Buserelin, Nafarelin, and Goserelin.

(127) Examples of polysaccharides include a glucosaminoglycane, a hyaluronic acid, a heparin, a low molecular weight heparin or an ultra-low molecular weight heparin or a derivative thereof, or a sulphated polysaccharide, e.g. a poly-sulphated form of the above-mentioned polysaccharides, and/or a pharmaceutically acceptable salt thereof. An example of a pharmaceutically acceptable salt of a poly-sulphated low molecular weight heparin is enoxaparin sodium. An example of a hyaluronic acid derivative is Hylan G-F 20 (Synvisc®), a sodium hyaluronate.

(128) The term “antibody”, as used herein, refers to an immunoglobulin molecule or an antigen-binding portion thereof. Examples of antigen-binding portions of immunoglobulin molecules include F(ab) and F(ab')₂ fragments, which retain the ability to bind antigen. The antibody can be polyclonal, monoclonal, recombinant, chimeric, de-immunized or humanized, fully human, non-human, (e.g., murine), or single chain antibody. In some embodiments, the antibody has effector function and can fix complement. In some embodiments, the antibody has reduced or no ability to bind an Fc receptor. For example, the antibody can be an isotype or subtype, an antibody fragment

or mutant, which does not support binding to an Fc receptor, e.g., it has a mutagenized or deleted Fc receptor binding region. The term antibody also includes an antigen-binding molecule based on tetravalent bispecific tandem immunoglobulins (TBTI) and/or a dual variable region antibody-like binding protein having cross-over binding region orientation (CODV).

(129) The terms “fragment” or “antibody fragment” refer to a polypeptide derived from an antibody polypeptide molecule (e.g., an antibody heavy and/or light chain polypeptide) that does not comprise a full-length antibody polypeptide, but that still comprises at least a portion of a full-length antibody polypeptide that is capable of binding to an antigen. Antibody fragments can comprise a cleaved portion of a full length antibody polypeptide, although the term is not limited to such cleaved fragments. Antibody fragments that are useful in the present disclosure include, for example, Fab fragments, F(ab')₂ fragments, scFv (single-chain Fv) fragments, linear antibodies, monospecific or multispecific antibody fragments such as bispecific, trispecific, tetraspecific and multispecific antibodies (e.g., diabodies, triabodies, tetrabodies), monovalent or multivalent antibody fragments such as bivalent, trivalent, tetravalent and multivalent antibodies, minibodies, chelating recombinant antibodies, tribodies or bibodies, intrabodies, nanobodies, small modular immunopharmaceuticals (SMIP), binding-domain immunoglobulin fusion proteins, camelized antibodies, and VHH containing antibodies. Additional examples of antigen-binding antibody fragments are known in the art.

(130) The terms “Complementarity-determining region” or “CDR” refer to short polypeptide sequences within the variable region of both heavy and light chain polypeptides that are primarily responsible for mediating specific antigen recognition. The term “framework region” refers to amino acid sequences within the variable region of both heavy and light chain polypeptides that are not CDR sequences, and are primarily responsible for maintaining correct positioning of the CDR sequences to permit antigen binding. Although the framework regions themselves typically do not directly participate in antigen binding, as is known in the art, certain residues within the framework regions of certain antibodies can directly participate in antigen binding or can affect the ability of one or more amino acids in CDRs to interact with antigen.

(131) Examples of antibodies are anti PCSK-9 mAb (e.g., Alirocumab), anti IL-6 mAb (e.g., Sarilumab), and anti IL-4 mAb (e.g., Dupilumab).

(132) Pharmaceutically acceptable salts of any API described herein are also contemplated for use in a drug or medicament in a drug delivery device. Pharmaceutically acceptable salts are for example acid addition salts and basic salts.

(133) Those of skill in the art will understand that modifications (additions and/or removals) of various components of the APIs, formulations, apparatuses, methods, systems and embodiments described herein may be made without departing from the full scope and spirit of the present disclosure, which encompass such modifications and any and all equivalents thereof.

(134) An example drug delivery device may involve a needle-based injection system as described in Table 1 of section 5.2 of ISO 11608-1:2014(E). As described in ISO 11608-1:2014(E), needle-based injection systems may be broadly distinguished into multi-dose container systems and single-dose (with partial or full evacuation) container systems. The container may be a replaceable container or an integrated non-replaceable container.

(135) As further described in ISO 11608-1:2014(E), a multi-dose container system may involve a needle-based injection device with a replaceable container. In such a system, each container holds multiple doses, the size of which may be fixed or variable (pre-set by the user). Another multi-dose container system may involve a needle-based injection device with an integrated non-replaceable container. In such a system, each container holds multiple doses, the size of which may be fixed or variable (pre-set by the user).

(136) As further described in ISO 11608-1:2014(E), a single-dose container system may involve a needle-based injection device with a replaceable container. In one example for such a system, each container holds a single dose, whereby the entire deliverable volume is expelled (full evacuation).

In a further example, each container holds a single dose, whereby a portion of the deliverable volume is expelled (partial evacuation). As also described in ISO 11608-1:2014(E), a single-dose container system may involve a needle-based injection device with an integrated non-replaceable container. In one example for such a system, each container holds a single dose, whereby the entire deliverable volume is expelled (full evacuation). In a further example, each container holds a single dose, whereby a portion of the deliverable volume is expelled (partial evacuation).

(137) Those of skill in the art will understand that modifications (additions and/or removals) of various components of the embodiments described herein may be made without departing from the full scope and spirit of the present disclosure, which encompass such modifications and any and all equivalents thereof.

LIST OF REFERENCE NUMBERS

(138) **100**—injection device **102**—outer casing/housing/main body **104**—reservoir **106**—plunger **108**—collar **110**—cap **112**—longitudinal axis **113**—stopper **114**—rear casing **116**—needle **118**—needle shroud/sleeve/cover **120**—control spring **122**—drive spring **124**—injection site **126**—distal end **128**—proximal end **200**—injection device **202**—main body **206**—plunger **215**—needle carrier **216**—needle **217**—needle cover side walls **218**—needle cover **219**—needle cover contact face **221**—attachment element **223**—adhesive region **224**—injection site **225**—protective barrier **226**—distal end **227**—outer frame **228**—proximal end **229**—frame cavity **230**—barrier first end **231**—outer frame internal wall **232**—barrier second end **233**—folded portion **234**—fold **257**—flange **300**—injection device **302**—main body **315**—needle carrier **316**—needle **317**—needle cover side walls **318**—needle cover **319**—needle cover contact face **321**—attachment element **323**—adhesive region **324**—injection site **325**—protective barrier **326**—distal end **327**—outer frame **328**—proximal end **330**—barrier first end **331**—outer frame internal wall **332**—barrier second end **333**—folded portion **334**—fold **357**—flange **400**—injection device **402**—main body **415**—needle carrier **416**—needle **417**—needle cover side walls **418**—needle cover **419**—needle cover contact face **421**—attachment element **423**—adhesive region **424**—injection site **425**—protective barrier **426**—distal end **427**—outer frame **428**—proximal end **430**—barrier first end **431**—outer frame internal wall **432**—barrier second end **434**—fold **440**—attachment element support **500**—injection device **502**—main body **504**—reservoir/container of medicament **506**—plunger **515**—needle carrier **516**—needle **517**—needle cover side walls **518**—needle cover **519**—needle cover contact face **521**—attachment element **523a**—first adhesive region **523b**—second adhesive region **524**—injection site **525**—protective barrier **526**—distal end **527**—outer frame **528**—proximal end **529**—frame cavity **530**—barrier first end **531**—outer frame internal wall **532**—barrier second end **533**—folded portion **534**—fold **541**—outer frame housing **542**—contact surface **543**—removal arm **544**—aperture **545**—outer frame surrounding wall **546**—needle hole **547**—proximal end removal arm **548**—distal end removal arm **549**—internal face **550**—fastener **551**—intermediate point **552**—front end device **553**—rear end device **554**—pivotal connection **600**—injection device **602**—main body **616**—needle **617**—needle cover side walls **618**—needle cover **619**—needle cover contact face **621**—attachment element **623**—adhesive region **624**—injection site **625**—protective barrier **626**—distal end **627**—outer frame **628**—proximal end **630**—barrier first end **632**—barrier second end **633**—folded portion **634**—fold **655**—rollers/releasable mechanism **657**—flange **700**—injection device **702**—main body **717**—needle cover side walls **718**—needle cover **719**—needle cover contact face **721**—attachment element **723**—adhesive region **724**—injection site **725**—protective barrier **726**—distal end **727**—outer frame **728**—proximal end **730**—barrier first end **732**—barrier second end **734**—fold **756a**—first distal tension member/roller **756b**—second distal tension member/roller **756c**—first proximal tension member/roller **756d**—second proximal tension member/roller **801**—one step of a method of operating a medicament delivery device **802**—one step of a method of operating a medicament delivery device **803**—one step of a method of operating a medicament delivery device **804**—one step of a method of operating a medicament delivery device

Claims

1. A medicament delivery device comprising: a main body arranged to receive a medicament cartridge; a needle for delivery of medicament from the medicament cartridge; a needle cover moveable between an initial position, in which the needle cover covers the needle, and an activated position for dispensing medicament from the medicament delivery device, wherein in the activated position the needle protrudes from a distal end of the needle cover; an outer frame, moveable relative to the main body between an extended position in which the outer frame extends past a distal end of the needle, and a retracted position in which the outer frame is moved towards the main body; and an attachment element comprising an adhesive region for attaching the medicament delivery device to a surface when the needle cover is in the activated position, the attachment element comprising a protective barrier covering the adhesive region, wherein the protective barrier is coupled to the outer frame and is removed from the attachment element to expose the adhesive region as the outer frame is moved towards the retracted position, and wherein the protective barrier is configured to pull the surface in a direction away from an injection site as the protective barrier is removed from the attachment element.
2. The medicament delivery device according to claim 1, wherein the protective barrier is removed from the attachment element, and the needle cover is moved from the initial position to the activated position, with a single action of providing a force on the medicament delivery device in a distal direction.
3. The medicament delivery device according to claim 1, wherein the protective barrier comprises a folded portion releasably secured to the attachment element.
4. The medicament delivery device according to claim 3, wherein the folded portion comprises a double layer of the protective barrier covering at least a portion of the attachment element.
5. The medicament delivery device according to claim 3, wherein a second end of the protective barrier is releasably secured to the attachment element, and the second end is folded towards the attachment element to form the folded portion.
6. The medicament delivery device according to claim 1, wherein the outer frame is external to the main body in both the extended position and the retracted position.
7. The medicament delivery device according to claim 1, wherein an adhesive force from the attachment element is greater than a spring force of the needle cover.
8. The medicament delivery device according to claim 1, wherein when the needle cover is in the initial position, the attachment element is positioned set back in a proximal direction from a distal most end of the medicament delivery device.
9. The medicament delivery device according to claim 1, wherein the outer frame is pivotable relative to the main body to move between the extended position and the retracted position.
10. The medicament delivery device according to claim 9, wherein the outer frame comprises a removal arm, wherein a first end of the removal arm is pivotally coupled to the main body, and a second end of the removal arm is moveable relative to an internal face of a contact surface of the outer frame.
11. The medicament delivery device according to claim 10, wherein as the outer frame moves from the extended position to the retracted position, the second end of the removal arm is pushed along the internal face of the outer frame to pull the protective barrier away from the attachment element.
12. The medicament delivery device according to claim 9, wherein the protective barrier is configured to be pulled through an aperture in a contact surface of the outer frame.
13. The medicament delivery device according to claim 1, wherein the outer frame comprises a releasable mechanism to automatically retract the protective barrier from the attachment element, wherein the releasable mechanism is activated as the outer frame is moved towards the main body.
14. The medicament delivery device according to claim 13, wherein the releasable mechanism

comprises at least one biased roller, and a first end of the protective barrier is wound around the at least one biased roller, and a second end of the protective barrier is releasably attached to the attachment element.

15. The medicament delivery device according to claim 1, wherein the outer frame comprises at least one tension member to hold the protective barrier in tension as it is removed from the attachment element.

16. The medicament delivery device according to claim 1, wherein the protective barrier comprises two components and the surface is pulled in opposing directions by each part of the protective barrier as the protective barrier is removed from the attachment element.

17. The medicament delivery device according to claim 1, wherein the adhesive region holds the surface taut until the medicament delivery device is removed from the surface.

18. The medicament delivery device according to claim 1, comprising a container of medicament.

19. A method of operating a medicament delivery device, the method comprising: moving an outer frame relative to a main body of the medicament delivery device from an extended position, in which the outer frame extends past a distal end of a needle, to a retracted position, in which the outer frame is moved towards the main body; exposing an adhesive region of an attachment element by removing a protective barrier covering the adhesive region, wherein the protective barrier is coupled to the outer frame of the medicament delivery device and is removed as the outer frame is moved towards the retracted position; and adhering the exposed adhesive region of the attachment element to a surface for preparation of delivery of a medicament, wherein the protective barrier is configured to pull the surface in a direction away from an injection site as the protective barrier is removed from the attachment element.
