

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409713
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Schmeichel; Shayde Daniel et al.

Roll tarp system

Abstract

An arm assembly for a roll tarp system includes a first arm which defines a first arm axis; a first arm extension attached to the first arm, the first arm extension defines a first arm extension axis, the first arm extension axis defines an angle with respect to the first arm extension axis between 10 to 95 degrees, the first arm extension comprises a first pivot aperture; a second arm which defines a second arm axis; a second arm extension attached to the second arm, the second arm extension defines a second arm extension axis, the second arm extension axis defines an angle with respect to the second arm extension axis between 10 to 95 degrees, the second arm extension comprises a second pivot aperture; a pivot through the first pivot aperture and the second pivot aperture; and a torsion spring mounted about the pivot to extend into the first arm and the second arm to bias the first arm and the second arm away from one another.

Inventors: Schmeichel; Shayde Daniel (Jamestown, ND), Schmeichel; Hunter Max (Valley City, ND)

Applicant: Schmeichel; Shayde Daniel (Jamestown, ND); Schmeichel; Hunter Max (Valley City, ND)

Family ID: 96950367

Appl. No.: 19/046162

Filed: February 05, 2025

Publication Classification

Int. Cl.: B60J7/08 (20060101)

U.S. Cl.:

CPC B60J7/085 (20130101);

Field of Classification Search

CPC: B60J (7/085); B60J (7/061); B60J (7/062); B60J (7/064); B60J (7/065); B60J (7/068); B60J (7/10); B60J (7/102); B60J (7/104); B60J (7/12); B60J (11/02); B60P (7/02); B60P (7/04)

USPC: 296/98; 296/100.01; 296/100.1; 296/100.11-; 296/100.08

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4659134	12/1986	Johnson	242/379.2	B60J 7/085
4834445	12/1988	Odegaard	160/245	B60J 7/085
5944374	12/1998	Searfoss	296/98	B60J 7/085
6237985	12/2000	O'Brian	160/23.1	B60J 7/085
7726720	12/2009	Searfoss	296/100.01	B60J 7/085
8177284	12/2011	Royer	296/100.16	B60J 5/067
9283832	12/2015	Knight	N/A	B60P 7/04
10696145	12/2019	Hunter	N/A	B61D 39/00
11833956	12/2022	Reeder	N/A	B60P 7/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2023031682	12/2022	KR	N/A

Primary Examiner: Weisberg; Amy R

Assistant Examiner: Condo; Veronica M

Attorney, Agent or Firm: Fargo Patent & Business Law

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION[S]

(1) None

BACKGROUND

(2) The present disclosure relates to roll tarps for trailers and vehicles, and more specifically to an arm system therefor.

(3) Roll tarp systems protect cargo within a container from the elements. A roll tarp may include an elongated roller for rolling and unrolling the tarp attached to one longitudinal side of a container, and an actuator attached to the arm and the elongated roller for rolling and unrolling the tarp between a closed and open position. Although effective, the roll tarp may catch or be blocked by heaping loads that are piled above the sides of the container.

(4) This background section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present disclosure, which are described and/or claimed below. This discussion is believed to assist the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

SUMMARY

(5) An arm assembly for a roll tarp system according to one disclosed non-limiting embodiment of the present disclosure includes a first arm which defines a first arm axis; a first arm extension attached to the first arm, the first arm extension defines a first arm extension axis, the first arm extension axis defines an angle with respect to the first arm extension axis between 10 to 95 degrees, the first arm extension comprises a first pivot aperture; a second arm which defines a second arm axis; a second arm extension attached to the second arm, the second arm extension defines a second arm extension axis, the second arm extension axis defines an angle with respect to the second arm extension axis between 10 to 95 degrees, the second arm extension comprises a second pivot aperture; a pivot through the first pivot aperture and the second pivot aperture; and a torsion spring mounted about the pivot to extend into the first arm and the second arm to bias the first arm and the second arm away from one another.

(6) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the angle with respect to the first arm extension axis is between 10 to 30 degrees and wherein the angle with respect to the second arm extension axis is between 10 to 30 degrees.

(7) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the first arm extension fits at least partially within the second arm extension.

(8) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the first arm extension and the second arm extension each comprise two ears.

(9) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the first pivot aperture and the second pivot aperture are coaxial and within an intersection of the first arm axis and the second arm axis.

(10) A further embodiment of any of the foregoing embodiments of the present disclosure includes a first cuboid bushing mounted to a first leg of the torsion spring to fit within the first arm.

(11) A further embodiment of any of the foregoing embodiments of the present disclosure includes a second cuboid bushing mounted to a second leg of the torsion spring to fit within the second arm.

(12) A further embodiment of any of the foregoing embodiments of the present disclosure includes a tubular bushing mounted within a coil of the torsion spring to receive the pivot therethrough, the tubular bushing, the first cuboid bushing and the second cuboid bushing formed of a non-metallic material.

(13) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the torsion spring at least partially counterbalances a weight of the second arm and a roll tarp attached thereto.

(14) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the first arm comprises a mount assembly for pivotable attachment to a container about a container pivot along a longitudinal axis of the container.

(15) A further embodiment of any of the foregoing embodiments of the present disclosure includes that a first arm length between the pivot and the container pivot is at least one-half a width of the container.

(16) A further embodiment of any of the foregoing embodiments of the present disclosure includes an aft arm plate removably fastened to the second arm to receive a roll tarp axle tube therethrough.

(17) A further embodiment of any of the foregoing embodiments of the present disclosure includes a first and a second collar assembly attachable to the roll tarp axle tube to sandwich the aft arm plate therebetween.

(18) A further embodiment of any of the foregoing embodiments of the present disclosure includes that the first and the second collar assembly comprise a split bushing and a clamp.

(19) A further embodiment of any of the foregoing embodiments of the present disclosure includes a split bushing assembly fastened to the aft arm plate about a tarp tube aperture, the split bushing assembly comprises a first portion and a second portion each with a multiple of fastener apertures to receive fasteners adjacent to a semi-circular tarp tube aperture.

(20) A further embodiment of any of the foregoing embodiments of the present disclosure includes

a guide plate bracket attached to the second arm to receive a roll tarp axle tube therethrough, the guide plate bracket arranged to mount a motor drive to drive a roll tarp axle tube, the motor drive mounted adjacent to a distal end of the roll tarp axle tube.

(21) A further embodiment of any of the foregoing embodiments of the present disclosure includes a first guide plate bushing and a second guide plate bushing attachable to the guide plate bracket transverse thereto, the first guide plate bushing and the second guide plate bushing form a split tarp tube aperture that receives the roll tarp axle tube therethrough.

(22) A further embodiment of any of the foregoing embodiments of the present disclosure includes a first fastener that attaches the guide plate bracket to the first guide plate bushing and the second guide plate bushing, and a second fastener that attaches the guide plate bracket to the first guide plate bushing and the second guide plate bushing, the first fastener parallel to the second fastener and transverse to the roll tarp axle tube.

(23) A further embodiment of any of the foregoing embodiments of the present disclosure includes a collar assembly attachable to the roll tarp axle tube to retain the guide plate bracket, wherein the collar assembly comprises a split bushing and a clamp that surrounds the split bushing.

(24) The foregoing features and elements may be combined in various combinations without exclusivity, unless expressly indicated otherwise. These features and elements as well as the operation thereof will become more apparent in light of the following description and the accompanying drawings. It should be appreciated that however the following description and drawings are intended to be exemplary in nature and non-limiting.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Various features will become apparent to those skilled in the art from the following detailed description of the disclosed non-limiting embodiment. The drawings that accompany the detailed description can be briefly described as follows:

(2) FIG. 1 is a schematic perspective view of a roll tarp system for a container according to one disclosed non-limiting embodiment.

(3) FIG. 2 is an exploded view of the roll tarp system.

(4) FIG. 3 is an exploded view of an arm assembly of the roll tarp system.

(5) FIG. 4 is a perspective view of a torsion spring for the arm assembly of the roll tarp system.

(6) FIG. 5 is an expanded side view of an aft arm plate for an aft arm assembly of the roll tarp system.

(7) FIG. 6 is a perspective view of the aft arm assembly to rotationally support the roller assembly.

(8) FIG. 7 is a perspective view of a split bushing assembly for the aft arm plate.

(9) FIG. 8 is a perspective view of a forward aft arm assembly.

(10) FIG. 9 is an expanded end view of a guide plate bushing assembly for a guide plate bracket of the forward arm assembly.

(11) FIG. 10 is a perspective view of the guide plate bushing assembly for the guide plate bracket of the forward arm assembly to support the roll tarp assembly.

(12) FIG. 11 is a perspective end view of the roll tarp system in an unrolled position.

(13) FIG. 12 is a perspective end view of the roll tarp system in an intermediate position.

(14) FIG. 13 is a perspective end view of the roll tarp system in a rolled position.

DETAILED DESCRIPTION

(15) FIG. 1 schematically illustrates a roll tarp system **20** that may be used to tarp a container C such as trailer, truck, etc. The container C may oftentimes be filled with a heaping load (e.g. grain, gravel, etc.) that extends above an upper edge E of the container C which the roll tarp system **20** effectively covers. The roll tarp system **20** pivots about a longitudinal axis A along the container C

to roll or unroll a tarp about an axis R to cover or uncover the container C.

(16) The roll tarp system **20** generally includes an aft arm assembly **30**, a forward arm assembly **40**, a roller assembly **50** between the arms, and a motor drive M. The aft arm assembly **30** and the forward arm assembly **40** are pivotally mounted to a container C such as trailers, truck boxes, etc., about a longitudinal axis A. The roller assembly **50** extends along a roller axis R to laterally cover or uncover an opening of the container C with a tarp **52** rolled or unrolled from the roller assembly **50** over the heaping load in the container C. The tarp **52** may be attached to the container C along one longitudinal side via various fastener structures.

(17) With reference also to FIG. 2, the aft arm assembly **30** will be described in detail as the aft arm assembly **30** is generally equivalent to the forward arm assembly **40** which supports the motor drive M to power the roller assembly **50**. The aft arm assembly **30** includes an aft first arm **60** which defines an aft first arm axis A1 and an aft first arm extension **62** that defines an aft first arm extension axis A2, and an aft second arm **70** which defines an aft second arm axis A3 and an aft second arm extension **72** that defines an aft second arm extension axis A4.

(18) With reference also to FIG. 3, the aft arm assembly **30** includes an aperture **32** in a container mount **34** attached to the first arm **60**. The container mount **34** is attached to a mount CM on the container C about the longitudinal axis A via a container pivot **36** such as a pin, fastener, bolt, etc., though the aperture **32**. The container mount **34** may be formed as ears **38** welded to the aft first arm **60** along the first arm axis A1.

(19) The first arm axis A1 defines an angle a1 with respect to the first arm extension axis A2 between, for example, 10 to 95 degrees. The first arm extension **62** defines a first pivot aperture **64**.

(20) The second arm axis A3 defines an angle a2 with respect to the second arm extension axis A3 between, for example, 10 to 95 degrees and more specifically between 10 to 30 degrees. The second arm extension **72** defines a second pivot aperture **74**.

(21) In one embodiment, the aft first arm **60** and the aft second arm **70** may be rectilinear in cross-section and manufactured of a tubular steel material. The first arm extension **62** may be formed as ears **66** that fits at least partially within the second arm extension **72** which may be formed as ears **76**. The ears **66**, **76** may be formed as plates that are welded to the respective arms.

(22) A pivot **80** such as a pin, fastener, bolt, etc., is secured through the first pivot aperture **64** and the second pivot aperture **74** to support a torsion spring **90** about a pivot axis P1. The torsion spring **90** is mounted about the pivot **80** to extend into the aft first arm **60** and the aft second arm **70** to bias the aft first arm **60** and the aft second arm **70** away from one another to counterbalance a weight of the aft second arm **70** and the roll tarp assembly **50** attached thereto.

(23) With reference also to FIG. 4, in one embodiment, the torsion spring **90** generally includes a coil **92** with a first leg **94** and a second leg **96** which extends therefrom. The first leg **94** and the second leg **96** are offset with respect to the coil **92** such that the first leg **94** and the second leg **96** are centered with respect thereto. The first leg **94** forms an angle «S with respect to the second leg **94** about the pivot axis P1. In one embodiment, the first leg **94** forms an obtuse angle aS with respect to the second leg **96** of between, for example, 90 to 130 degrees and more specifically about 100 degrees.

(24) A first cuboid bushing **100** is mounted to the first leg **94** of the torsion spring **90** to fit within the aft first arm **60** and a second cuboid bushing **102** is mounted to the second leg **96** of the torsion spring **90** to fit within the aft second arm **70**. The bushings **100**, **102** may be retained upon the respective legs via clamps **106**, stops, etc.

(25) A tubular bushing **104** is mounted within the coil **92** of the torsion spring **90** to receive the pivot **80** therethrough. The bushings **100**, **102**, **104** may be manufactured of a non-metallic material to facilitate locating and centering of the torsion spring **90** between the arms **60**, **70** about the about the pivot axis P1. The bias force applied by the torsion spring **90** facilitates the extension of the arms **60**, **70** which, in effect, facilitates the “floating” of the roller assembly **50** over the heaping load.

(26) With reference also to FIG. 5, an aft arm plate **110** is removably fastened to the aft second arm **70** opposite the second arm extension **72** via a multiple of fasteners **112** such as bolts. The aft arm plate **110** includes a tarp tube aperture **114** that receives a roll tarp axle tube **52** of the roller assembly **50** therethrough (FIG. 6). The tarp tube aperture **114** may be offset from the second arm axis **A3** and on an opposite side with respect to the second pivot aperture **74** in the second arm extension **72**.

(27) With reference also to FIG. 6, a split bushing assembly **120** may be fastened to the aft arm plate **110** about the tarp tube aperture **114** via a multiple of fasteners **122** such as bolts. The split bushing assembly **120** includes a first portion **124A** and a second portion **124B** each with two fastener apertures **126A**, **126B** to receive the fasteners **122** parallel to a semi-circular tarp tube aperture **114A**, **114B** which collectively form the tarp tube aperture **114** about the roller axis **R** (FIG. 7). The split bushing assembly **120** may be manufactured of a non-metallic material to facilitate rotational support of the roll tarp axle tube **52**. By being a separable assembly, the split bushing assembly **120** facilitates replacement of the roll tarp assembly **50**.

(28) A first collar assembly **130A** and a second collar assembly **130B** is mounted to the roll tarp axle tube **52** to sandwich the aft arm plate **110** and the split bushing assembly **120** therebetween to facilitate replacement of the roll tarp assembly **50**. The first collar assembly **130A** and the second collar assembly **130B** each include a split cylindrical bushing **132** and a clamp **134**. The clamp **134** encircles and compresses the split cylindrical bushing **132** to sandwich the aft arm plate **110** and rotationally retain the roll tarp axle tube **52** within the tarp tube aperture **114**.

(29) With reference also to FIG. 8, the forward arm assembly **40** is generally equivalent to the aft arm assembly **30** but supports the motor drive **M** to power the roller assembly **50**. In other words, the geometry, torsion spring, interface, etc., of the forward arm assembly **40** is generally equivalent to the aft arm assembly **30** and need not be again described in detail.

(30) A guide plate bracket **140** is attached to a forward second arm **70A** opposite a forward second arm extension **72A**. The guide plate bracket **140** may be generally “L” shaped with a first guide plate bracket portion **142** welded to the forward second arm **70A** and a second guide plate bracket portion **144** transverse thereto. The first guide plate bracket portion **142** includes drive apertures **146** to mount the motor drive **M** thereto to power the roller assembly **50**. The motor drive **M** is mounted adjacent to a distal end **54** (FIG. 10) of the roll tarp axle tube **52** to engage therewith along a motor axis of rotation **Mr** which is coaxial with the roller axis **R**.

(31) A drive shaft **Ms** of the motor drive **M** may engage the distal end **54** of the roll tarp axle tube **52** via a transverse fastener **Mf**. The motor drive **M** may be manually and/or automatically controlled via a control unit mounted to the container **C** and in communication with the motor drive **M**.

(32) With reference also to FIG. 8-10, a split guide plate bushing assembly **150** may be fastened to the second guide plate bracket portion **144** via a multiple of fasteners **152** such as bolts so as to be parallel to the first guide plate bracket portion **142**. The split guide plate bushing assembly **150** includes a first portion **154A** and a second portion **154B** each with two fastener apertures **156A**, **156B** to receive the fasteners **152** adjacent to, and within a common plane of a split tarp tube aperture **158** along the roller axis **R**. That is, the split tarp tube aperture **158** is split as semi-circular apertures **158A**, **158B** within each of the first portion **154A** and the second portion **154B**, respectively. The split guide plate bushing assembly **150** may be manufactured of a non-metallic material to facilitate rotational support of the roll tarp axle tube **52**. By being a separable assembly, the split guide plate bushing assembly **150** further facilitates replacement of the roll tarp assembly **50**.

(33) A third collar assembly **130C** is mounted to the roll tarp axle tube **52** to abut the split guide plate bushing assembly **150** to facilitate replacement of the roll tarp assembly **50**. The collar assembly **130C** includes a split cylindrical bushing **132C** and a clamp **134C**. The clamp **134C** encircles and compresses the split cylindrical bushing **132C** to rotationally retain the roll tarp axle

tube **52** within the split tarp tube aperture **158**. The third collar assembly **130C** is located between the first guide plate bracket portion **142** and the split guide plate bushing assembly **150**.

(34) The roll tarp system **20** readily facilitates the “floating” of the roller assembly **50** over the heaping loads that are piled above the sides of the container (FIGS. **11-13**) and facilitates disassembly of the roller assembly **50** from the aft arm assembly **30** and the forward arm assembly **40** for replacement of the tarp.

(35) Although the different non-limiting embodiments have specific illustrated components, the embodiments of this invention are not limited to those particular combinations. It is possible to use some of the components or features from any of the non-limiting embodiments in combination with features or components from any of the other non-limiting embodiments.

(36) The foregoing description is exemplary rather than defined by the limitations within. Various non-limiting embodiments are disclosed herein, however, one of ordinary skill in the art would recognize that various modifications and variations in light of the above teachings will fall within the scope of the appended claims. It is therefore to be appreciated that within the scope of the appended claims, the disclosure may be practiced other than as specifically described. For that reason the appended claims should be studied to determine true scope and content.

Claims

1. An arm assembly for a roll tarp system, comprising: a first arm which defines a first arm axis; a first arm extension attached to the first arm, the first arm extension defines a first arm extension axis, the first arm extension axis defines a first angle with respect to the first arm axis between 10 to 95 degrees, the first arm extension comprises a first pivot aperture; a second arm which defines a second arm axis; a second arm extension attached to the second arm, the second arm extension defines a second arm extension axis, the second arm extension axis defines second angle with respect to the second arm axis between 10 to 95 degrees, the second arm extension comprises a second pivot aperture; a pivot through the first pivot aperture and the second pivot aperture; and a torsion spring mounted about the pivot to extend into the first arm and the second arm to bias the first arm and the second arm away from one another.
2. The arm assembly as recited in claim 1, wherein the first angle is between 10 to 30 degrees and wherein the second angle is between 10 to 30 degrees.
3. The arm assembly as recited in claim 1, wherein the first arm extension fits at least partially within the second arm extension.
4. The arm assembly as recited in claim 3, wherein the first arm extension and the second arm extension each comprise two ears.
5. The arm assembly as recited in claim 1, wherein the first pivot aperture and the second pivot aperture are coaxial and within an intersection of the first arm axis extension and the second arm axis extension.
6. The arm assembly as recited in claim 1, further comprising a first cuboid bushing mounted to a first leg of the torsion spring to fit within the first arm.
7. The arm assembly as recited in claim 6, further comprising a second cuboid bushing mounted to a second leg of the torsion spring to fit within the second arm.
8. The arm assembly as recited in claim 7, further comprising a tubular bushing mounted within a coil of the torsion spring to receive the pivot therethrough, the tubular bushing, the first cuboid bushing and the second cuboid bushing formed of a non-metallic material.
9. The arm assembly as recited in claim 1, wherein the torsion spring at least partially counterbalances a weight of the second arm and a roll tarp attached thereto.
10. The arm assembly as recited in claim 1, wherein the first arm comprises a mount assembly for pivotable attachment to a container about a container pivot along a longitudinal axis of the container.

11. The arm assembly as recited in claim 10, wherein a first arm length between the pivot and the container pivot is at least one-half a width of the container.
 12. The arm assembly as recited in claim 1, further comprising an aft arm plate removably fastened to the second arm to receive a roll tarp axle tube therethrough.
 13. The arm assembly as recited in claim 12, further comprising a first and a second collar assembly attachable to the roll tarp axle tube to sandwich the aft arm plate therebetween.
 14. The arm assembly as recited in claim 13, wherein the first and the second collar assembly comprise a split bushing and a clamp.
 15. The arm assembly as recited in claim 14, further comprising a split bushing assembly fastened to the aft arm plate about a tarp tube aperture, the split bushing assembly comprises a first portion and a second portion each with a multiple of fastener apertures to receive fasteners adjacent to a semi-circular tarp tube aperture.
 16. The arm assembly as recited in claim 1, further comprising a guide plate bracket attached to the second arm to receive a roll tarp axle tube therethrough, the guide plate bracket arranged to mount a motor drive to drive a roll tarp axle tube, the motor drive mounted adjacent to a distal end of the roll tarp axle tube.
 17. The arm assembly as recited in claim 16, further comprising a first guide plate bushing and a second guide plate bushing attachable to the guide plate bracket transverse thereto, the first guide plate bushing and the second guide plate bushing forms a split tarp tube aperture that receives the roll tarp axle tube therethrough.
 18. The arm assembly as recited in claim 17, further comprising a first fastener that attaches the guide plate bracket to the first guide plate bushing and the second guide plate bushing, and a second fastener that attaches the guide plate bracket to the first guide plate bushing and the second guide plate bushing, the first fastener parallel to the second fastener and transverse to the roll tarp axle tube.
 19. The arm assembly as recited in claim 18, further comprising a collar assembly attachable to the roll tarp axle tube to retain the guide plate bracket, wherein the collar assembly comprises a split bushing and a clamp that surrounds the split bushing.
-