

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409877
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Kuang; Junjie

Folding stroller

Abstract

A folding stroller includes a framework and wheels mounted at a bottom of the framework. The framework has a folded state and an unfolded state. The frame includes front and rear bracket assemblies, a lower bracket assembly, and a support frame assembly. Front and rear connecting rod units are respectively arranged at lower ends of the front and rear bracket assemblies. The lower bracket assembly includes first and second lower bracket units. First ends of the first and second lower bracket units are respectively rotatably connected to a lower end of the front bracket assembly and a lower end of the rear bracket assembly. Second ends of the first and second lower bracket units are rotatably connected. The support frame assembly includes first and second support frame units and first and second rotating rod units.

Inventors: Kuang; Junjie (Linwu County, CN)

Applicant: Kuang; Junjie (Linwu County, CN)

Family ID: 96950360

Assignee: ZHONGSHAN KANGDI BABY PRODUCTS CO., LTD. (Zhongshan, CN)

Appl. No.: 19/010214

Filed: January 06, 2025

Related U.S. Application Data

continuation-in-part parent-doc US 18808117 20240819 PENDING child-doc US 19010214

Publication Classification

Int. Cl.: B62B7/08 (20060101); B62B9/14 (20060101); B62B9/20 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: B62B (7/08); B62B (9/142); B62B (9/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4706986	12/1986	Kassai	108/177	B62B 7/08
4746140	12/1987	Kassai	108/177	B62B 7/08
8388015	12/2012	Chen	280/642	B62B 3/02
10414422	12/2018	Choi	N/A	B62B 9/082
10583852	12/2019	Fitzwater	N/A	B62B 7/008
10668939	12/2019	Yabuuchi	N/A	B62B 5/04
10988153	12/2020	Horowitz	N/A	B62B 7/008
11465665	12/2021	Sturgeon	N/A	B62B 7/062
11608098	12/2022	Horowitz	N/A	B62B 3/004
2010/0156069	12/2009	Chen	280/639	B62B 9/142
2023/0117703	12/2022	Sturgeon	280/651	B62B 3/025

Primary Examiner: Evans; Bryan A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation-in-Part of the U.S. application Ser. No. 18/808,117 filed on Aug. 19, 2024, and entitled “FOLDING STROLLER” now pending, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of baby products, and in particular, to a folding stroller.

BACKGROUND OF THE INVENTION

(2) With the development of the society and the improvement of the living standard, outdoor recreations have become a popular way for sports and leisure. More and more parents or legal guardians prefer to accompany babies and young children to play outdoors at their leisure time. As a children's product suitable for outdoor use, a stroller not only allows a baby to sit and lie in, making it convenient to take the baby to play around, but also allows for placement of some outdoor products, so that the stroller is used as a convenient and labor-saving tool for transportation.

(3) In the prior art, there are many rods in a stroller, so that a folding component is complex, and a folding operation is cumbersome. Moreover, it is also easy to pinch the fingers of a user during folding of the stroller. Meanwhile, this type of folding stroller product still has a large volume after being folded, making it inconvenient to carry. Furthermore, the stroller is not stable in a folded state and easily deforms. In addition, an accommodating space formed in the existing folding stroller product is approximately rectangular. When a baby sits or lies in the accommodating space, the legs need to bend or curl up. The comfort level is low.

(4) For this purpose, the present disclosure provides a folding stroller, which can effectively solve the above problems. The folding stroller has a simple structure, and a folded product has a small volume and is stable. In addition, a leg accommodating space is provided, making it convenient to place the feet of a baby. The comfort level is high.

SUMMARY OF THE INVENTION

(5) The present disclosure provides a folding stroller. The folding stroller has a simple structure, and a folded product has a small volume and is stable. In addition, a leg accommodating space is provided, making it convenient to place the feet of a baby. The comfort level is high.

(6) The technical solution adopted by the present invention to solve the technical problem is as follows.

(7) A folding stroller includes a framework and wheels mounted at a bottom of the framework. The framework has a folded state and an unfolded state. The framework includes a front bracket assembly, a rear bracket assembly, a lower bracket assembly and a support frame assembly.

(8) The rear bracket assembly is arranged in a manner of being opposite to the front bracket assembly.

(9) The lower bracket assembly includes a first lower bracket unit and a second lower bracket unit; a first end of the first lower bracket unit is rotationally connected to a lower end of the front bracket assembly; a first end of the second lower bracket unit is rotationally connected to a lower end of the rear bracket assembly; a second end of the first lower bracket unit is rotationally connected to a second end of the second lower bracket unit.

(10) The support frame assembly is connected to the lower bracket assembly; the support frame assembly includes several support rod and frame units; the support rod and frame units are rotationally connected to at least one adjacent support rod and frame unit; when the framework is in the unfolded state, a downwards sunken foot accommodating space is formed among at least some of the support rod and frame units, the first lower bracket unit, and the second lower bracket unit.

(11) As an improvement of the present invention, the support rod and frame units include a first support frame unit, a second support frame unit, a first rotating rod unit, and a second rotating rod unit; a first end of the first support frame unit is rotationally connected to a lower end of the front connecting rod unit; a first end of the second support frame unit is rotationally connected to a lower end of the rear connecting rod unit; a second end of the first support frame unit is rotationally connected to the second end of the second support frame unit; two ends of the first rotating rod unit are respectively rotationally connected to the first lower bracket unit and the first support frame unit; and two ends of the second rotating rod unit are respectively rotationally connected to the second lower bracket unit and the second support frame unit.

(12) As an improvement of the present invention, the downwards sunken foot accommodating space is formed among the first rotating rod unit, the second rotating rod unit, a portion of the first lower bracket unit, a portion of the second lower bracket unit, a portion of the first support frame unit, and a portion of the second support frame unit.

(13) As an improvement of the present invention, the support rod and frame units include two third support frame units; first ends of the two third support frame units are respectively rotationally connected to the first lower bracket unit and the second lower bracket unit; second ends of the two third support frame units are rotationally connected; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit, a portion of the second lower bracket unit, and the two third support frame units.

(14) As an improvement of the present invention, the support rod and frame units include two fourth support frame units and a middle connecting rod unit; first ends of the two fourth support frame units are respectively rotationally connected to the first lower bracket unit and the second lower bracket unit; second ends of the two fourth support frame units are respectively rotationally connected to the middle connecting rod unit; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit, a portion of the second lower

bracket unit, the middle connecting rod unit, and the two fourth support frame units.

(15) As an improvement of the present invention, the first lower bracket unit includes a first limiting member arranged at the second end; the second end of the second lower bracket unit is rotatably connected to the first limiting member; and when the framework is in the unfolded state, the first limiting member resists against the second lower bracket unit.

(16) As an improvement of the present invention, a first locking member is arranged in the second end of the second lower bracket unit; a locking end of the first locking member is threaded out of a side wall of the second end of the second lower bracket unit; the first limiting member is provided with a first locking hole; and when the framework is in the unfolded state, the locking end of the first locking member is inserted into the first locking hole.

(17) As an improvement of the present invention, the first limiting member is provided with an unlocking button; a press end of the unlocking button is arranged towards the first locking hole; and under the driving of an external force, the press end of the unlocking button is moved towards the first locking hole to drive the locking end of the first locking member to be detached from the first locking hole.

(18) As an improvement of the present invention, a second limiting member is arranged at a second end of the second support frame unit; and when the framework is in the unfolded state, the second limiting member resists against the first support frame unit.

(19) As an improvement of the present invention, the framework further includes a fixing member; a first end of the fixing member is connected to the rear bracket assembly; a second end of the fixing member is detachably connected to the front bracket assembly; when the framework is in the folded state, the second end of the fixing member is connected to the front bracket assembly; and when the framework is in the unfolded state, the second end of the fixing member is detached from the front bracket assembly.

(20) As an improvement of the present invention, the framework further includes a push rod assembly and a lock fastener; the push rod assembly is rotatably connected to the rear bracket assembly; the lock fastener is connected to the push rod assembly and the rear bracket assembly; and the lock fastener is configured to allow or hinder relative rotation between the push rod assembly and the rear bracket assembly.

(21) As an improvement of the present invention, the wheels include movable casters and fixed casters; the movable casters are connected to a bottom of the front bracket assembly; and the fixed casters are connected to a bottom of the rear bracket assembly. The framework further includes a second locking assembly. The second locking assembly is moved between a locked position and an unlocked position. Several second locking holes are provided on inner sides of the fixed casters along edges of rotating shafts. When the second locking assembly is moved to the locked position, a locking rod of the second locking assembly is inserted into the second locking holes. When the second locking assembly is moved to the unlocked position, the locking rod of the second locking assembly is detached from the second locking holes.

(22) As an improvement of the present invention, the second locking assembly further includes a driving pedal and a driving rod; the driving pedal is connected to the driving rod; a driving slope is arranged at an end portion of the driving rod; the driving pedal and the driving rod rotate around a rotating shaft of the driving rod under the action of an external force; and a first end of the locking rod resists against the driving slope and slides along a surface of the driving slope to allow the locking rod to extend and retract and to be inserted or detached from the second locking holes.

(23) As an improvement of the present invention, the second locking assembly further includes a reset spring; one end of the reset spring is connected to a connecting portion at the bottom of the framework, and the other end of the reset spring is connected to the locking rod; and an elastic force of the reset spring enables the locking rod to have a tendency to move away from the second locking holes.

(24) As an improvement of the present invention, the folding stroller further includes a cover body,

a first connector is arranged at an upper end of each of the front bracket assembly and the rear bracket assembly; an upper end of the cover body is connected to the first connectors; and a lower end of the cover body is connected to a lower end of the front bracket assembly and a lower end of the rear bracket assembly or the lower bracket assembly.

(25) As an improvement of the present invention, a connecting strap is arranged at the upper end of the cover body; through holes are provided on the first connectors; and a free end of the connecting strap passes through the through holes and are connected to a surface of the cover body.

(26) As an improvement of the present invention, the folding stroller further includes a sunshade assembly, the sunshade assembly includes a second connector; and the second connector is detachably connected to the first connectors to connect or detach the sunshade assembly to or from the framework.

(27) As an improvement of the present invention, one of the first connector and the second connector is provided with an insertion block, and the other one of the first connector and the second connector is provided with an insertion slot; and the insertion block is inserted into the insertion slot.

(28) As an improvement of the present invention, the framework further includes an eccentric locking piece; the sunshade assembly is provided with a mounting column and a sunshade body connected to the mounting column; the first connector is provided with an insertion hole and an opening communicated to the insertion hole; the mounting column is inserted into the insertion hole; the eccentric locking piece is connected to the first connector and is rotated between a locking position and an unlocking position; and when the eccentric locking piece is rotated to the locking position, an eccentric portion of the eccentric locking piece passes through the opening and resists against a surface of the mounting column.

(29) As an improvement of the present invention, the framework further includes an upper bracket assembly; the upper bracket assembly includes a first upper bracket unit, a second upper bracket unit, and two connecting bracket units; a first end of the first upper bracket unit and a first end of the second upper bracket unit are respectively rotationally connected to the two connecting bracket units; the two connecting bracket units are connected to the mounting column; and a second end of the first upper bracket unit is rotationally connected to a second end of the second upper bracket unit.

(30) Beneficial effects: By the arrangement of the above structure, during use, the front bracket assembly and the rear bracket assembly are respectively pulled in a front direction and a rear direction and separated from each other until the first lower bracket unit and the second lower bracket unit are flushed with each other and in the same plane, and the support frame assembly is in a stretched state. In this case, the framework is in an unfolded state, making it convenient for a user to sit and lie down. The support frame assembly can provide an additional support force to hinder relative rotation of the first lower bracket unit and the second lower bracket unit, so that the structure of the product is stable. Moreover, the downwards sunken foot accommodating space is formed among some of the support rod and frame units, the first lower bracket unit, and the second lower bracket unit. A baby can sit in the stroller and place the feet in the downwards sunken foot accommodating space, so that the baby feels more comfortable when sitting in this product, and a user experience is enhanced. For storage, a middle portion of the lower bracket assembly and a middle portion of the support frame assembly are moved upwards. The first lower bracket unit and the second lower bracket unit rotate relative to each other. The first lower bracket unit rotates relative to the front bracket assembly; the second lower bracket unit rotates relative to the front bracket assembly; and the support frame assembly rotates relative to the lower bracket assembly, the front bracket assembly, and the rear bracket assembly. The support frame assembly collapses itself, and the front bracket assembly and the rear bracket assembly approach each other. The overall volume of the product is small, which is convenient for storage and transportation.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) In order to explain the technical solutions of the embodiments of the present disclosure more clearly, the following will briefly introduce the accompanying drawings used in the embodiments. The drawings in the following description are only some embodiments of the present disclosure. Those of ordinary skill in the art can obtain other drawings based on these drawings without creative work.
- (2) The present disclosure is further described below in detail in combination with the accompanying drawings and embodiments.
- (3) FIG. 1 is a schematic structural diagram of a push state according to Embodiment I of the present disclosure;
- (4) FIG. 2 is a schematic structural diagram of a pull state according to Embodiment I of the present disclosure;
- (5) FIG. 3 is a schematic structural diagram of an unfolded state of a framework in an angle according to Embodiment I of the present disclosure;
- (6) FIG. 4 is a schematic structural diagram of an unfolded state of a framework in another angle according to Embodiment I of the present disclosure;
- (7) FIG. 5 is a side view of an unfolded state of a framework according to Embodiment I of the present disclosure;
- (8) FIG. 6 is a schematic structural diagram of a semi-folded state of a framework according to Embodiment I of the present disclosure;
- (9) FIG. 7 is a schematic structural diagram of a folded state of a framework according to Embodiment I of the present disclosure;
- (10) FIG. 8 is an enlarged view of circle A in FIG. 1;
- (11) FIG. 9 is an enlarged view of circle B in FIG. 6;
- (12) FIG. 10 is a sectional view of a second locking assembly at an unlocked position according to Embodiment I of the present disclosure;
- (13) FIG. 11 is a sectional view of a second locking assembly at a locked position according to Embodiment I of the present disclosure;
- (14) FIG. 12 is a partially structural exploded diagram of a second locking assembly in an angle according to Embodiment I of the present disclosure;
- (15) FIG. 13 is a partially structural exploded diagram of a second locking assembly in another angle according to Embodiment I of the present disclosure;
- (16) FIG. 14 is a schematic structural diagram of a framework in an unfolded state according to Embodiment II of the present disclosure;
- (17) FIG. 15 is a schematic structural diagram of switching of the framework between an unfolded state and a folded state according to Embodiment II of the present disclosure;
- (18) FIG. 16 is a schematic structural diagram of the framework in a folded state according to Embodiment II of the present disclosure;
- (19) FIG. 17 is a partially structural exploded diagram of the framework in an unfolded state according to Embodiment II of the present disclosure;
- (20) FIG. 18 is an enlarged view of block A in FIG. 17;
- (21) FIG. 19 is a cross-sectional view of the framework in an unfolded state according to Embodiment II of the present disclosure;
- (22) FIG. 20 is an enlarged view of circle C in FIG. 19;
- (23) FIG. 21 is a side view of Embodiment II of the present disclosure;
- (24) FIG. 22 is a side view of Embodiment III of the present disclosure; and
- (25) FIG. 23 is a side view of Embodiment IV of the present disclosure.

Embodiment I

(26) Referring to FIG. 1 to FIG. 13, a folding stroller includes a framework **100** and wheels **200** mounted at a bottom of the framework **100**. The framework **100** has a folded state and an unfolded state. The framework **100** includes: a front bracket assembly **110**; a rear bracket assembly **120**, wherein the rear bracket assembly **120** is arranged in a manner of being opposite to the front bracket assembly **110**; a lower bracket assembly **130**, wherein the lower bracket assembly **130** includes a first lower bracket unit **131** and a second lower bracket unit **132**; a first end of the first lower bracket unit **131** is rotationally connected to a lower end of the front bracket assembly **110**; a first end of the second lower bracket unit **132** is rotationally connected to a lower end of the rear bracket assembly **120**; a second end of the first lower bracket unit **131** is rotationally connected to a second end of the second lower bracket unit **132**; and a support frame assembly **140**, wherein the support frame assembly **140** is connected to the lower bracket assembly **130**; the support frame assembly **140** includes several support rod and frame units; the support rod and frame units are rotationally connected to at least one adjacent support rod and frame unit; when the framework **100** is in the unfolded state, a downwards sunken foot accommodating space is formed among at least some of the support rod and frame units, the first lower bracket unit **131**, and the second lower bracket unit **132**.

(27) By the arrangement of the above structure, during use, the front bracket assembly **110** and the rear bracket assembly **120** are respectively pulled in a front direction and a rear direction and separated from each other until the first lower bracket unit **131** and the second lower bracket unit **132** are flushed with each other and in the same plane, and the support frame assembly **140** is in a stretched state. In this case, the framework **100** is in an unfolded state, making it convenient for a user to sit and lie down. The support frame assembly **140** can provide an additional support force to hinder relative rotation of the first lower bracket unit **131** and the second lower bracket unit **132**, so that the structure of the product is stable. Moreover, the downwards sunken foot accommodating space is formed among some of the support rod and frame units, the first lower bracket unit **131**, and the second lower bracket unit **132**. A baby can sit in the stroller and place the feet in the downwards sunken foot accommodating space, so that the baby feels more comfortable when sitting in this product, and a user experience is enhanced. For storage, a middle portion of the lower bracket assembly **130** and a middle portion of the support frame assembly **140** are moved upwards. The first lower bracket unit **131** and the second lower bracket unit **132** rotate relative to each other. The first lower bracket unit **131** rotates relative to the front bracket assembly **110**; the second lower bracket unit **132** rotates relative to the front bracket assembly **110**; and the support frame assembly **140** rotates relative to the lower bracket assembly **130**, the front bracket assembly **110**, and the rear bracket assembly **120**. The support frame assembly **140** collapses itself, and the front bracket assembly **110** and the rear bracket assembly **120** approach each other. The overall volume of the product is small, which is convenient for storage and transportation.

(28) In this embodiment, the support rod and frame units include a first support frame unit **141**, a second support frame unit **142**, a first rotating rod unit **143**, and a second rotating rod unit **144**. A front connecting rod unit **111** is arranged at a lower end of the front bracket assembly **110**, and a rear connecting rod unit **121** is arranged at a lower end of the rear bracket assembly **120**.

(29) a first end of the first support frame unit **141** is rotatably connected to a lower end of the front connecting rod unit **111**; a first end of the second support frame unit **142** is rotatably connected to a lower end of the rear connecting rod unit **121**; a second end of the first support frame unit **141** is rotatably connected to the second end of the second support frame unit **142**; two ends of the first rotating rod unit **143** are respectively rotatably connected to the first lower support frame unit **131** and the first support frame unit **141**; and two ends of the second rotating rod unit **144** are respectively rotatably connected to the second lower support frame unit **132** and the second support frame unit **142**.

(30) By the arrangement of the above structure, during use, the front bracket assembly **110** and the rear bracket assembly **120** are respectively pulled in a front direction and a back direction and are separated from each other until the first lower bracket unit **131** and the second lower bracket unit **132** are flush and in the same plane, and the first support frame unit **141** and the second support frame unit **142** are flush and in the same plane. At this point, when the framework **100** is in the unfolded state, it is convenient for a user to sit and lie down. The support frame assembly **140** can provide an additional supporting force to hinder relative rotation of the first lower bracket unit **131** and the second lower bracket unit **132** and stabilize the structure of the product. To store the product, a middle part of the lower bracket assembly **130** and a middle part of the support frame assembly **140** are moved upwards; the first lower bracket unit **131** and the second lower bracket unit **132** rotate relative to each other; the first lower bracket unit **131** rotates relative to the front bracket assembly **110**; the second lower bracket unit **132** rotates relative to the rear bracket assembly **120**; the first support frame unit **141** and the second support frame unit **142** rotate relative to each other; the first support frame unit **141** rotates relative to the front connecting rod unit **111**; the second support frame unit **142** rotates relative to the rear connecting rod unit **121**; and the front bracket assembly **110** and the rear bracket assembly **120** are close to each other. The overall volume of the product is small, which is convenient for storage and transportation.

(31) In this embodiment, a downwards sunken foot accommodating space is formed among the first rotating rod unit **143**, the second rotating rod unit **144**, a portion of the first lower bracket unit **131**, a portion of the second lower bracket unit **132**, a portion of the first support frame unit **141**, and a portion of the second support frame unit **142**. By the arrangement of the above structure, during use, a baby can sit in the stroller, and the feet can be placed in the downwards sunken foot accommodating space, so that the infant feels more comfortable when sitting in the product, and a user experience is enhanced.

(32) In this embodiment, the first lower bracket unit **131** includes a first limiting member **133** arranged at the second end; the second end of the second lower bracket unit **132** is rotatably connected to the first limiting member **133**; and when the framework **100** is in the unfolded state, the first limiting member **133** resists against the second lower bracket unit **132**. By the arrangement of the above structure, during use, when the framework **100** is in the unfolded state, the first lower bracket unit **131** and the second lower bracket unit **132** are flush and in the same plane. At this time, the first limiting member **133** resists against the second lower bracket unit **132**, which can hinder the continuously downwards relative rotation between the first lower bracket unit **131** and the second lower bracket unit **132** to limit their relative positions, so that the product is stabilized and fixed in the unfolded state, and it is convenient for use. Furthermore, the product has a stable structure and is safe to use.

(33) In this embodiment, a first locking member **134** is arranged in the second end of the second lower bracket unit **132**; a locking end of the first locking member **134** is threaded out of a side wall of the second end of the second lower bracket unit **132**; the first limiting member **133** is provided with a first locking hole **135**; and when the framework **100** is in the unfolded state, the locking end of the first locking member **134** is inserted into the first locking hole **135**. By the arrangement of the above structure, when the framework **100** is in the unfolded state, the first lower bracket unit **131** and the second lower bracket unit **132** are flush and in the same plane. The locking end of the first locking member **134** is inserted into the first locking hole **135**, which can lock the first lower bracket unit **131** and the second lower bracket unit **132**, hinder the relative rotation between the first lower bracket unit **131** and the second lower bracket unit **132**, and improve the stability and safety of the product.

(34) In this embodiment, the first limiting member **133** is provided with an unlocking button **136**; a press end of the unlocking button **136** is arranged towards the first locking hole **135**; and under the driving of an external force, the press end of the unlocking button **136** is moved towards the first locking hole **135** to drive the locking end of the first locking member **134** to be detached from the

first locking hole **135**. By the arrangement of the above structure, to fold the product, the press end of the unlocking button **136** is pressed to resist against the locking end of the first locking member **134**, thereby driving the locking end of the first locking member **134** to be detached from the first locking hole **135** to relieve the locked state. Meanwhile, the middle part of the lower bracket assembly **130** is moved upwards to fold the product. The operation is convenient.

(35) In this embodiment, a second limiting member **145** is arranged at a second end of the second support frame unit **142**; and when the framework **100** is in the unfolded state, the second limiting member **145** resists against the first support frame unit **141**. By the arrangement of the above structure, during use, when the framework **100** is in the unfolded state, the first support frame unit **141** and the second support frame unit **142** are flush and in the same plane. At this time, the second limiting member **145** resists against the first support frame unit **141**, which can hinder the continuously downwards relative rotation between the first support frame unit **141** and the second support frame unit **142** to limit their relative positions, so that the product is stabilized and fixed in the unfolded state, and it is convenient for use. Furthermore, the product has a stable structure and is safe to use.

(36) In this embodiment, the framework **100** further includes a fixing member **150**; a first end of the fixing member **150** is connected to the rear bracket assembly **120**; a second end of the fixing member **150** is detachably connected to the front bracket assembly **110**; when the framework **100** is in the folded state, the second end of the fixing member **150** is connected to the front bracket assembly **110**; and when the framework **100** is in the unfolded state, the second end of the fixing member **150** is detached from the front bracket assembly **110**. By the arrangement of the above structure, during use, the framework **100** is adjusted to the folded state. At this time, a distance between the front bracket assembly **110** and the rear bracket assembly **120** is shortened; the second end of the fixing member **150** is connected to the front bracket assembly **110**, which can hinder the front bracket assembly **110** to move away from the rear bracket assembly **120**, thereby hindering the framework **100** from being switched to the unfolded state, improving the stability of storage and transportation of the product, and facilitating a user to store and transport the product; and detaching the second end of the fixing member **150** from the front bracket assembly **110** can allow the framework **100** to be switched to the unfolded state.

(37) In this embodiment, the framework **100** further includes a push rod assembly **161** and a lock fastener **162**; the push rod assembly **161** is rotatably connected to the rear bracket assembly **120**; the lock fastener **162** is connected to the push rod assembly **161** and the rear bracket assembly **120**; and the lock fastener **162** is configured to allow or hinder relative rotation between the push rod assembly **161** and the rear bracket assembly **120**. By the arrangement of the above structure, during use, the push rod assembly **161** is rotated to enable a gripping end of the push rod assembly **161** to be away from the rear bracket assembly **120**; the lock fastener **162** is moved to fix the push rod assembly **161**, which can facilitate a user to grip the gripping end of the push rod assembly **161** and push and pull the product. Furthermore, the user can rotate the push rod assembly **161** according to a need to adjust an angle between the push rod assembly **161** and the rear bracket assembly **120**, thereby adjusting a height of the gripping end of the push rod assembly **161** to improve the comfort level of the product. Different users can have appropriate gripping heights, making it more convenient to use. When the push rod assembly **161** is rotated to fit the rear bracket assembly **120**, the push rod assembly **161** can be effectively stored, so that a length of the product is reduced, and transportation and storage of the product are facilitated.

(38) In this embodiment, the wheels **200** include movable casters **210** and fixed casters **220**; the movable casters **210** are connected to a bottom of the front bracket assembly **110**; and the fixed casters **220** are connected to a bottom of the rear bracket assembly **120**. By the arrangement of the above structure, during use, the movable casters **210** and the fixed casters **220** can cooperate to facilitate a user to push the framework **100**, so that it is more convenient to move the product. Moreover, the movable casters **210** can rotate around a vertical axis to allow the movable casters

210 to change a direction, thereby facilitating the users to change a movement direction of the stroller and simplifying the operation.

(39) In this embodiment, the framework **100** further includes a second locking assembly **170**; the second locking assembly **170** is moved between a locked position and an unlocked position; several second locking holes **221** are provided on inner sides of the fixed casters **220** along edges of rotating shafts; when the second locking assembly **170** is moved to the locked position, a locking rod **171** of the second locking assembly **170** is inserted into the second locking holes **221**; and when the second locking assembly **170** is moved to the unlocked position, the locking rod **171** of the second locking assembly **170** is detached from the second locking holes **221**. By the arrangement of the above structure, when the second locking assembly **170** is moved to the locked position, the locking rod **171** is inserted into the second locking holes **221**. The locking rod **171** hinders the rotation of the fixed casters **220**, thereby hindering the movement of the stroller, so that the stroller can stably stop in place and be safer to use. When the second locking assembly **170** is moved to the unlocked position, the locking rod **171** is separated from the locking holes **221**. At this time, the fixed casters **220** can rotate freely, making it convenient for a user to push, pull, and move the stroller. It is convenient and labor-saving to move the product.

(40) In this embodiment, the second locking assembly **170** further includes a driving pedal **172** and a driving rod **173**; the driving pedal **172** is connected to the driving rod **173**; a driving slope **174** is arranged at an end portion of the driving rod **173**; the driving pedal **172** and the driving rod **173** rotate around a rotating shaft of the driving rod **173** under the action of an external force; and a first end of the locking rod **171** resists against the driving slope **174** and slides along a surface of the driving slope **174** to allow the locking rod **171** to extend and retract and to be inserted or detached from the second locking holes **221**. By the arrangement of the above structure, during use, the driving pedal **172** is stepped on to drive the driving rod **173** and the driving slope **174** to rotate. The driving slope **174** drives the locking rod **171** to translate in an axial direction to be then inserted into the second locking holes **221** to hinder the rotation of the fixed casters **220**, so that the stroller can be stably stopped in place and safer to use.

(41) In this embodiment, the second locking assembly **170** further includes a reset spring **175**; one end of the reset spring **175** is connected to a connecting portion at the bottom of the framework **100**, and the other end of the reset spring **175** is connected to the locking rod **171**; and an elastic force of the reset spring **175** enables the locking rod **171** to have a tendency to move away from the second locking holes **221**. By the arrangement of the above structure, during use, when the second locking assembly **170** is moved to the unlocked position, the locking rod **171** is detached from the second locking holes **221** under the action of the elastic force of the reset spring **175**, so that the fixed casters **220** are allowed to rotate freely, facilitating a user to move the stroller and making the product convenient to use.

(42) In this embodiment, friction lines **176** are arranged on an upper surface of the driving pedal **172**. By the arrangement of the above structure, the friction lines **176** can increase a friction coefficient of the upper surface of the driving pedal **172**. When a user steps on the driving pedal **172**, a friction force between the sole of the foot of the user and the upper surface of the driving pedal **172** is increased, so that it is easier for the user to step on the driving pedal **172**. The operation is simple.

(43) In this embodiment, the folding stroller further includes a cover body **300**; a first connector **101** is arranged at an upper end of each of the front bracket assembly **110** and the rear bracket assembly **120**; an upper end of the cover body **300** is connected to the first connectors **101**; and a lower end of the cover body **300** is connected to a lower end of the front bracket assembly **110** and a lower end of the rear bracket assembly **120** or the lower bracket assembly **130**. By the arrangement of the above structure, during use, the upper end of the cover body **300** is connected to the first connector **101**, and the lower end of the cover body **300** is connected to the lower end of the front bracket assembly **110** and the lower end of the rear bracket assembly **120** or the lower

bracket assembly **130**. The cover body **300** can be stably connected to the framework **100**, and an inner wall of the cover body **300** forms an accommodating space, which facilitates a user to sit and lie down in the accommodating space and improves the comfort and safety of the product.

(44) In this embodiment, a connecting strap **310** is arranged at the upper end of the cover body **300**; through holes **102** are provided on the first connectors **101**; and a free end of the connecting strap **310** passes through the through holes **102** and are connected to a surface of the cover body **300**. By the arrangement of the above structure, during use, the free end of the connecting strap **310** passes through the through hole **102** and is connected to the surface of the cover body **300** to achieve the connection between the cover body **300** and the first connectors **101**. The product has a stable structure and is conveniently connected. Preferably, the free end of the connecting strap **310** is connected to the surface of the cover body **300** through a hook and loop fastener or a button. The connection is convenient and stable.

(45) In this embodiment, the folding stroller further includes a sunshade assembly **400**; the sunshade assembly **400** includes a second connector **410**, several sunshade brackets **420**, and a sunshade body **430**; and the second connector **410** is detachably connected to the first connectors **101** to connect or detach the sunshade assembly **400** to or from the framework **100**. By the arrangement of the above structure, during use, the second connector **410** is connected to or detached from the first connectors **101** to mount or remove the sunshade assembly **400**, making it easier for a user to select whether to use the sunshade assembly **400** and making it more convenient for a user to use the product. Moreover, the sunshade brackets **420** can stably support the sunshade body **430**, to shield the user from the sunlight and provide a better user experience.

(46) In this embodiment, one of the first connector **101** and the second connector **410** is provided with an insertion block **103**, and the other one of the first connector **101** and the second connector **410** is provided with an insertion slot; and the insertion block **103** is inserted into the insertion slot. By the arrangement of the above structure, during use, the insertion block **103** is inserted into the insertion slot, making it convenient for a user to connect the first connector **101** to the second connector **410**, so that the mounting is convenient.

(47) In this embodiment, the second connector **410** is provided with a first rotating portion **411** and a second rotating portion **412**; the first rotating portion **411** is rotatably connected to the second rotating portion **412**; one of the sunshade brackets **420** is connected to the first rotating portion **411**, and another sunshade bracket **420** is connected to the second rotating portion **412**. By the arrangement of the above structure, during use, rotating the second rotating portion **412** can make the various sunshade brackets **420** approach or separated from each other to unfold or fold the sunshade body **430**, so that a user can conveniently adjust a shading area of the sunshade body **430**, and a better user experience is achieved.

(48) In this embodiment, the framework **100** further includes a traction assembly **180**; the traction assembly **180** is rotatably connected to the front bracket assembly **110**; and the traction assembly **180** is configured to allow a user to pull product. By the arrangement of the above structure, during use, a user can move the product by pulling the traction assembly **180**. The user can select to push or pull the product. More usage options are provided for the user.

(49) In this embodiment, the traction assembly **180** includes a traction rod **181**, a connecting rod **182**, and a connecting shell **183**; the traction rod **181** is slidably connected to the connecting shell **183**; one end of the connecting rod **182** is rotatably connected to a lower part of the front bracket assembly **110**, and the other end of the connecting rod **182** is connected to the connecting shell **183**; the traction rod **181** is provides with several third locking positions; the connecting shell is provided with a third locking member; and the locking member is connected to any one of the third locking positions. By the arrangement of the above structure, when the traction assembly **180** is used, the third locking member is connected to any third locking position, which can adjust a length of extension of the traction rod **181**, making it convenient for a user to grip and pull the product. When the traction assembly **180** is stored, the third locking member can be connected to

the topmost third locking position to shorten the length of extension of the traction rod **181** and facilitate the storage of the product.

Embodiment II

(50) Referring to FIG. **14** to FIG. **21**, this embodiment discloses a folding stroller, a main structure of which is basically the same as that of Embodiment I.

(51) A main difference between this embodiment and Embodiment I is that in this embodiment, a connection mode for a sunshade assembly **400** and the framework **100**. The framework **100** further includes eccentric locking pieces **500**. The sunshade assembly **400** is provided with mounting columns **440** and a sunshade body **430** connected to the mounting columns **440**; first connectors **101** are provided with insertion holes **104** and openings **105** communicated to the insertion holes **104**; the mounting columns **440** are inserted into the insertion holes **104**; eccentric locking pieces **500** are connected to the first connectors **101** and are rotated between a locking position and an unlocking position; and when the eccentric locking pieces **500** are rotated to the locking position, eccentric portions **510** of the eccentric locking pieces **500** pass through the openings **105** and resist against surfaces of the mounting columns **440**. By the arrangement of the above structure, during use, lower end portions of the mounting columns **440** are inserted along the insertion holes **104**. The eccentric locking pieces **500** are rotated to the locking position, so that the eccentric portions **510** of the eccentric locking pieces **500** pass through the openings **105**, and the eccentric portions **510** resist against the lower end portions of the mounting columns **440**, to fix the mounting columns **440**, thus effectively fixing the sunshade body **430**. The structure of the product is more stable. To remove the sunshade assembly **400**, only the eccentric locking pieces **500** need to be rotated to the unlocking position. The eccentric portions **510** are removed from the lower end portions of the mounting columns **440**, making it convenient for a user to pull out the mounting columns **440** from the insertion holes **104**. It is more convenient to mount and remove the sunshade assembly **400**, and the user can choose whether to mount or remove the sunshade assembly **400** according to a need. Preferably, each eccentric locking piece **500** has a rotating grip **520**. A user can turn the rotating grip **520** to make the eccentric locking piece **500** rotate between the locking position and the unlocking position. By using the rotating grip **520**, the user can adjust the position of the eccentric locking piece **500** more easily, so that the user experience is better.

(52) In this embodiment, the framework **100** further includes an upper bracket assembly **190**; the upper bracket assembly **190** includes a first upper bracket unit **191**, a second upper bracket unit **192**, and two connecting bracket units **193**; a first end of the first upper bracket unit **191** and a first end of the second upper bracket unit **192** are respectively rotationally connected to the two connecting bracket units **193**; the two connecting bracket units **193** are connected to the mounting columns **440**; and a second end of the first upper bracket unit **191** is rotationally connected to a second end of the second upper bracket unit **192**. By the arrangement of the above structure, during use, the two connecting bracket units **193** are respectively connected to the mounting columns **440** on front and rear sides, and then two ends of the upper bracket assembly **190** are fixed, so that the upper bracket assembly **190** can support the front bracket assembly **110** and the rear bracket assembly **120**, which further improves the structural stability of the product. Moreover, when the framework **100** transitions from the unfolded state to the folded state, the first end of the first upper bracket unit **191** and the first end of the second upper bracket unit **192** both rotate relative to the connecting bracket units **193**, and the second end of the first upper bracket unit **191** rotates relative to the second end of the second upper bracket unit **192**, so that the framework **100** transitions to the folded state more smoothly, and the product is more convenient to use. Preferably, each connecting bracket unit **193** is provided with a first mounting hole **193a**. The mounting columns **440** pass through the first mounting holes **193a** and are inserted into the insertion holes **104**, to achieve fixed connection to the connecting bracket unit **193**, so that the connection is convenient and stable. Meanwhile, the connection bracket units **193** may also be directly connected to the front bracket assembly **110** and/or the rear bracket assembly **120**, without using the mounting columns **440**.

Preferably, the upper bracket assembly **190** further comprises a middle limiting member **194**. The second end of the first upper bracket unit **191** and the second end of the second upper bracket unit **192** are rotationally connected through the middle limiting member **194**. Furthermore, an edge of the middle limiting member **194** resists against an upper surface of the first upper bracket unit **191** and an upper surface of the second upper bracket unit **192**, to limit a direction and angle of rotation between the first upper bracket unit **191** and the second upper bracket unit **192**.

(53) In this embodiment, the sunshade assembly **400** further includes third connectors **450** and rotating brackets **460**. The third connectors **450** are provided with second mounting holes **451**, and the mounting columns **440** pass through the second mounting holes **451** in sequence and are inserted into the insertion holes **104** through the first mounting holes **193a**, to connect the third connectors **450** to the mounting columns **440**. The rotating bracket **460** is rotationally connected to the third connectors **450**, and the sunshade body **430** is connected to the mounting columns **440** and the rotating brackets **460**. When a user rotates the rotating brackets **460**, the sunshade body **430** can be controlled to be opened or closed.

Embodiment III

(54) Referring to FIG. 22, this embodiment discloses a folding stroller, a main structure of which is basically the same as that of Embodiment II.

(55) A main difference between this embodiment and Embodiment I is that in this embodiment, the support rod and frame units include two third support frame units **146**; first ends of the two third support frame units **146** are respectively rotationally connected to the first lower bracket unit **131** and the second lower bracket unit **132**; second ends of the two third support frame units **146** are rotationally connected; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit **131**, a portion of the second lower bracket unit **132**, and the two third support frame units **146**. By the arrangement of the above structure, when the framework **100** is in the unfolded state, extension directions of the first lower bracket unit **131** and the second lower bracket unit **132** are the same, forming a whole. The foot accommodating space with a triangular cross section is formed among two third support frame units **146**, the first lower bracket unit **131**, and the second lower bracket unit **132**. The foot accommodating space has a more stable structure, which can facilitate a passenger sitting and lying in the stroller to place the feet and have a more comfortable passenger experience. Moreover, the two third support frame units **146** can effectively provide a support force to the first lower bracket unit **131** and the second lower bracket unit **132**, making the structure of the framework **100** more stable.

Embodiment IV

(56) Referring to FIG. 23, this embodiment discloses a folding stroller, a main structure of which is basically the same as that of Embodiment II.

(57) A main difference between this embodiment and Embodiment I is that in this embodiment, the support rod and frame units include two fourth support frame units **147** and a middle connecting rod unit **148**; first ends of the two fourth support frame units **147** are respectively rotationally connected to the first lower bracket unit **131** and the second lower bracket unit **132**; second ends of the two fourth support frame units **147** are respectively rotationally connected to the middle connecting rod unit **148**; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit **131**, a portion of the second lower bracket unit **132**, the middle connecting rod unit **148**, and the two fourth support frame units **147**. By the arrangement of the above structure, when the framework **100** is in the unfolded state, extension directions of the first lower bracket unit **131** and the second lower bracket unit **132** are the same, forming a whole. A foot accommodating space with a trapezoidal cross section is formed among the first lower bracket unit **131**, the second lower bracket unit **132**, the middle connecting rod unit **148**, and the two fourth support frame units **147**. The foot accommodating space can accommodate the feet of a passenger, making the passenger sitting in the stroller feel more comfortable and have a better user experience. Moreover, the cooperation between the two fourth support frame units **147** and the middle

connecting rod unit **148** can improve the structural stability of connection between the first lower bracket unit **131** and the second lower bracket unit **132**, thereby prolonging the service life of the product.

(58) One or more implementation modes are provided above in combination with specific contents, and it is not deemed that the specific implementation of the present disclosure is limited to these specifications. Any technical deductions or replacements approximate or similar to the method and structure of the present disclosure or made under the concept of the present disclosure shall fall within the scope of protection of the present disclosure.

Claims

1. A folding stroller, comprising a framework and wheels mounted at a bottom of the framework, wherein the framework has a folded state and an unfolded state; the framework comprises: a front bracket assembly; a rear bracket assembly, wherein the rear bracket assembly is arranged in a manner of being opposite to the front bracket assembly; a lower bracket assembly, wherein the lower bracket assembly comprises a first lower bracket unit and a second lower bracket unit; a first end of the first lower bracket unit is rotationally connected to a lower end of the front bracket assembly; a first end of the second lower bracket unit is rotationally connected to a lower end of the rear bracket assembly; a second end of the first lower bracket unit is rotationally connected to a second end of the second lower bracket unit; and a support frame assembly, wherein the support frame assembly is connected to the lower bracket assembly; the support frame assembly comprises several support rod and frame units; the support rod and frame units are rotationally connected to at least one adjacent support rod and frame unit; when the framework is in the unfolded state, a downwards sunken foot accommodating space is formed among at least some of the support rod and frame units, the first lower bracket unit, and the second lower bracket unit; wherein the first lower bracket unit comprises a first limiting member arranged at the second end of the second first lower bracket unit; the second end of the second lower bracket unit is rotatably connected to the first limiting member; and when the framework is in the unfolded state, the first limiting member resists against the second lower bracket unit; wherein a first locking member is arranged in the second end of the second lower bracket unit; a locking end of the first locking member is threaded out of a side wall of the second end of the second lower bracket unit; the first limiting member is provided with a first locking hole; and when the framework is in the unfolded state, the locking end of the first locking member is inserted into the first locking hole.

2. The folding stroller according to claim 1, wherein the support rod and frame units comprise a first support frame unit, a second support frame unit, a first rotating rod unit, and a second rotating rod unit; a front connecting rod unit is arranged at the lower end of the front bracket assembly; a rear connecting rod unit is arranged at the lower end of the rear bracket assembly; a first end of the first support frame unit is rotationally connected to a lower end of the front connecting rod unit; a first end of the second support frame unit is rotationally connected to a lower end of the rear connecting rod unit; a second end of the first support frame unit is rotationally connected to the second end of the second support frame unit; two ends of the first rotating rod unit are respectively rotationally connected to the first lower bracket unit and the first support frame unit; and two ends of the second rotating rod unit are respectively rotationally connected to the second lower bracket unit and the second support frame unit.

3. The folding stroller according to claim 2, wherein the downwards sunken foot accommodating space is formed among the first rotating rod unit, the second rotating rod unit, a portion of the first lower bracket unit, a portion of the second lower bracket unit, a portion of the first support frame unit, and a portion of the second support frame unit.

4. The folding stroller according to claim 1, wherein the support rod and frame units comprise two third support frame units; first ends of the two third support frame units are respectively

rotationally connected to the first lower bracket unit and the second lower bracket unit; second ends of the two third support frame units are rotationally connected; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit, a portion of the second lower bracket unit, and the two third support frame units.

5. The folding stroller according to claim 1, wherein the support rod and frame units comprise two fourth support frame units and a middle connecting rod unit; first ends of the two fourth support frame units are respectively rotationally connected to the first lower bracket unit and the second lower bracket unit; second ends of the two fourth support frame units are respectively rotationally connected to the middle connecting rod unit; and the downwards sunken foot accommodating space is formed among a portion of the first lower bracket unit, a portion of the second lower bracket unit, the middle connecting rod unit, and the two fourth support frame units.

6. The folding stroller according to claim 1, wherein the first limiting member is provided with an unlocking button; a press end of the unlocking button is arranged towards the first locking hole; and under the driving of an external force, the press end of the unlocking button is moved towards the first locking hole to drive the locking end of the first locking member to be detached from the first locking hole.

7. The folding stroller according to claim 2, wherein a second limiting member is arranged at a second end of the second support frame unit; and when the framework is in the unfolded state, the second limiting member resists against the first support frame unit.

8. The folding stroller according to claim 1, wherein the framework further comprises a fixing member; a first end of the fixing member is connected to the rear bracket assembly; a second end of the fixing member is detachably connected to the front bracket assembly; when the framework is in the folded state, the second end of the fixing member is connected to the front bracket assembly; and when the framework is in the unfolded state, the second end of the fixing member is detached from the front bracket assembly.

9. The folding stroller according to claim 1, wherein the framework further comprises a push rod assembly and a lock fastener; the push rod assembly is rotatably connected to the rear bracket assembly; the lock fastener is connected to the push rod assembly and the rear bracket assembly; and the lock fastener is configured to allow or hinder relative rotation between the push rod assembly and the rear bracket assembly.

10. The folding stroller according to claim 1, wherein the wheels comprise movable casters and fixed casters; the movable casters are connected to a bottom of the front bracket assembly; and the fixed casters are connected to a bottom of the rear bracket assembly; wherein the framework further comprises a second locking assembly; the second locking assembly is moved between a locked position and an unlocked position; several second locking holes are provided on inner sides of the fixed casters along edges of rotating shafts; when the second locking assembly is moved to the locked position, a locking rod of the second locking assembly is inserted into the second locking holes; and when the second locking assembly is moved to the unlocked position, the locking rod of the second locking assembly is detached from the second locking holes.

11. The folding stroller according to claim 1, further comprising a cover body, wherein a first connector is arranged at an upper end of each of the front bracket assembly and the rear bracket assembly; an upper end of the cover body is connected to the first connectors; and a lower end of the cover body is connected to a lower end of the front bracket assembly and a lower end of the rear bracket assembly or the lower bracket assembly.

12. The folding stroller according to claim 11, further comprising a sunshade assembly, wherein the sunshade assembly comprises a second connector; and the second connector is detachably connected to the first connectors to connect or detach the sunshade assembly to or from the framework.

13. The folding stroller according to claim 12, wherein one of the first connector and the second connector is provided with an insertion block, and the other one of the first connector and the

second connector is provided with an insertion slot; and the insertion block is inserted into the insertion slot.

14. The folding stroller according to claim 12, wherein the framework further comprises an eccentric locking piece; the sunshade assembly is provided with a mounting column and a sunshade body connected to the mounting column; the first connector is provided with an insertion hole and an opening communicated to the insertion hole; the mounting column is inserted into the insertion hole; the eccentric locking piece is connected to the first connector and is rotated between a locking position and an unlocking position; and when the eccentric locking piece is rotated to the locking position, an eccentric portion of the eccentric locking piece passes through the opening and resists against a surface of the mounting column.

15. The folding stroller according to claim 14, wherein the framework further comprises an upper bracket assembly; the upper bracket assembly comprises a first upper bracket unit, a second upper bracket unit, and two connecting bracket units; a first end of the first upper bracket unit and a first end of the second upper bracket unit are respectively rotationally connected to the two connecting bracket units; the two connecting bracket units are connected to the mounting column; and a second end of the first upper bracket unit is rotationally connected to a second end of the second upper bracket unit.

16. A folding stroller, comprising a framework and wheels mounted at a bottom of the framework, wherein the framework has a folded state and an unfolded state; the framework comprises: a front bracket assembly; a rear bracket assembly, wherein the rear bracket assembly is arranged in a manner of being opposite to the front bracket assembly; a lower bracket assembly, wherein the lower bracket assembly comprises a first lower bracket unit and a second lower bracket unit; a first end of the first lower bracket unit is rotationally connected to a lower end of the front bracket assembly; a first end of the second lower bracket unit is rotationally connected to a lower end of the rear bracket assembly; a second end of the first lower bracket unit is rotationally connected to a second end of the second lower bracket unit; and a support frame assembly, wherein the support frame assembly is connected to the lower bracket assembly; the support frame assembly comprises several support rod and frame units; the support rod and frame units are rotationally connected to at least one adjacent support rod and frame unit; when the framework is in the unfolded state, a downwards sunken foot accommodating space is formed among at least some of the support rod and frame units, the first lower bracket unit, and the second lower bracket unit; wherein the wheels comprise movable casters and fixed casters; the movable casters are connected to a bottom of the front bracket assembly; and the fixed casters are connected to a bottom of the rear bracket assembly; wherein the framework further comprises a second locking assembly; the second locking assembly is moved between a locked position and an unlocked position; several second locking holes are provided on inner sides of the fixed casters along edges of rotating shafts; when the second locking assembly is moved to the locked position, a locking rod of the second locking assembly is inserted into the second locking holes; and when the second locking assembly is moved to the unlocked position, the locking rod of the second locking assembly is detached from the second locking holes; wherein the second locking assembly further comprises a driving pedal and a driving rod; the driving pedal is connected to the driving rod; a driving slope is arranged at an end portion of the driving rod; the driving pedal and the driving rod rotate around a rotating shaft of the driving rod under the action of an external force; and a first end of the locking rod resists against the driving slope and slides along a surface of the driving slope to allow the locking rod to extend and retract and to be inserted or detached from the second locking holes.

17. The folding stroller according to claim 16, wherein the second locking assembly further comprises a reset spring; one end of the reset spring is connected to a connecting portion at the bottom of the framework, and the other end of the reset spring is connected to the locking rod; and an elastic force of the reset spring enables the locking rod to have a tendency to move away from the second locking holes.

18. A folding stroller, comprising a framework and wheels mounted at a bottom of the framework, wherein the framework has a folded state and an unfolded state; the framework comprises: a front bracket assembly; a rear bracket assembly, wherein the rear bracket assembly is arranged in a manner of being opposite to the front bracket assembly; a lower bracket assembly, wherein the lower bracket assembly comprises a first lower bracket unit and a second lower bracket unit; a first end of the first lower bracket unit is rotationally connected to a lower end of the front bracket assembly; a first end of the second lower bracket unit is rotationally connected to a lower end of the rear bracket assembly; a second end of the first lower bracket unit is rotationally connected to a second end of the second lower bracket unit; a support frame assembly, wherein the support frame assembly is connected to the lower bracket assembly; the support frame assembly comprises several support rod and frame units; the support rod and frame units are rotationally connected to at least one adjacent support rod and frame unit; when the framework is in the unfolded state, a downwards sunken foot accommodating space is formed among at least some of the support rod and frame units, the first lower bracket unit, and the second lower bracket unit; and a cover body, wherein a first connector is arranged at an upper end of each of the front bracket assembly and the rear bracket assembly; an upper end of the cover body is connected to the first connectors; and a lower end of the cover body is connected to a lower end of the front bracket assembly and a lower end of the rear bracket assembly or the lower bracket assembly; wherein a connecting strap is arranged at the upper end of the cover body; through holes are provided on the first connectors; and a free end of the connecting strap passes through the through holes and are connected to a surface of the cover body.
