

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411008
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Roth; Alex

Wall art hanging tool

Abstract

A wall art hanging tool including a central assembly, a telescopic assembly and a leveling assembly. The central assembly includes a central rod. The telescopic assembly includes a telescopic rod. The telescopic rod is perpendicularly attached to the telescopic rod. The leveling assembly includes eyelets and leveling members attached to the telescopic rod. The leveling members are used to level the telescopic rod. Nails can be introduced into the eyelets to be equidistantly fixed to a wall surface.

Inventors:	Roth; Alex (Deerfield Beach, FL)
Applicant:	Roth; Alex (Deerfield Beach, FL)
Family ID:	96950425
Appl. No.:	18/200995
Filed:	May 23, 2023

Publication Classification

Int. Cl.: G01C9/28 (20060101); G01C9/34 (20060101)

U.S. Cl.:

CPC G01C9/28 (20130101); G01C9/34 (20130101);

Field of Classification Search

CPC: G01B (3/08); G01B (5/24); G01B (5/25)

USPC: 33/418; 33/419; 33/452; 33/465; 33/468; 33/469; 33/470; 33/613; 33/645; 33/809

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3808690	12/1973	Balder	33/809	G01B 3/08
4152838	12/1978	Cook	D10/69	G01C 9/28
4165567	12/1978	Olsson	33/608	G01B 5/207
4241510	12/1979	Radecki	33/474	G01B 3/02
4392184	12/1982	Hearold	362/120	G01C 9/32
4648185	12/1986	Brandimarte	33/669	B25H 7/04
5357683	12/1993	Trevino	33/528	B25H 7/00
5867917	12/1998	Karon	33/666	A47G 1/205
6029362	12/1999	Miodragovic	33/483	B25H 7/00
6032378	12/1999	Null	33/645	A47G 1/205
6049991	12/1999	Gruenberg	33/485	A47G 1/205
6473983	12/2001	Gier	33/613	A47G 1/205
6550156	12/2002	Scoville	33/645	F16L 55/18
6684518	12/2003	Voorhees	248/495	A47G 1/205
6739065	12/2003	Hofmeister	33/666	A47G 1/205
6785977	12/2003	Crichton	33/613	G01C 9/00
6944962	12/2004	Tessel	33/414	B44D 3/38
6971184	12/2004	Prevost	33/666	A47G 1/205
7155840	12/2006	Carbonaro	33/666	A47G 1/205
7316078	12/2007	Hagman	33/666	A47G 1/205
7814675	12/2009	Venderley	33/645	A47G 1/205
8672286	12/2013	Darre	33/666	A47G 1/164
8739423	12/2013	Cortum	33/613	G01C 9/28
8875408	12/2013	Steffensen	33/809	G01C 15/06
9032637	12/2014	Propp	33/669	B25H 7/04
9067314	12/2014	Frazer	N/A	B25H 7/04
9549624	12/2016	Parrillo	N/A	G01C 9/34
9709393	12/2016	Oppenheim	N/A	G01C 15/02
9885198	12/2017	Risley	N/A	E04H 17/26
10149559	12/2017	Marks	N/A	A47G 1/205
10328667	12/2018	Yanashima	N/A	N/A
10683670	12/2019	Rush	N/A	E04F 21/18
10690471	12/2019	DuFaux	N/A	G01B 3/08
11231275	12/2021	Bunting	N/A	G01B 3/004
11255651	12/2021	Medina	N/A	N/A
11547223	12/2022	Hassett	N/A	A47G 1/17
11781850	12/2022	Marshall	33/301	G01B 5/14
12185851	12/2024	Cox	N/A	A47G 1/205
2002/0078583	12/2001	Richardson	33/613	A47G 1/205
2002/0189119	12/2001	High	33/613	B25H 7/04
2003/0029986	12/2002	Zuller	248/476	A47G 1/164
2003/0033722	12/2002	Lanham	33/374	G01C 9/26
2004/0049936	12/2003	Newman	33/613	G01C 9/28
2004/0211074	12/2003	Tessel	33/414	B44D 3/38
2016/0097625	12/2015	Dykes	33/760	G01C 9/34

Background/Summary

II. BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to a wall art hanging tool and, more particularly, to a wall art hanging tool that can be used to install evenly disposed nails at a predetermined height.

2. Description of the Related Art

(2) Several designs for hanging tools have been designed in the past. None of them, however, include telescopic horizontal arms which are extended to place grommets attached thereto at equidistantly distances therebetween.

(3) Applicant believes that a related reference corresponds to U.S. Pat. No. 10,328,667 issued for a picture hanging device with a sliding level mechanism and a pair of wall punch assemblies which are used to drive finish nails into the wall surface. Applicant believes that another related reference corresponds to U.S. Pat. No. 11,255,651 issued for a leveling device that is used to hang picture frames which utilizes a slide ruler assembly with a bubble level and a plurality of pins which are used to mark the mounting locations. None of these references, however, teach of a wall art hanging tool that is comprised of a T-shaped leveling tool with integrated spirit levels and a pair of telescopically adjustable grommets which slide horizontally outwards to mark the locations of the mounting hardware when installing a painting or photograph on a wall surface.

(4) Other documents describing the closest subject matter provide for a number of more or less complicated features that fail to solve the problem in an efficient and economical way. None of these patents suggest the novel features of the present invention.

III. SUMMARY OF THE INVENTION

(5) It is one of the objects of the present invention to provide a wall art hanging tool that includes a handle located on a central member of the present invention to ease holding the tool.

(6) It is another object of this invention to provide a wall art hanging tool that includes a rubber portion located on a rear side of the central member to prevent sliding of the present invention when being in abutting contact with a wall surface.

(7) It is still another object of the present invention to provide a wall art hanging tool that includes bubble levels to allow leveling the present invention.

(8) It is yet another object of this invention to provide such a device that is inexpensive to implement and maintain while retaining its effectiveness.

(9) Further objects of the invention will be brought out in the following part of the specification, wherein detailed description is for the purpose of fully disclosing the invention without placing limitations thereon.

Description

IV. BRIEF DESCRIPTION OF THE DRAWINGS

(1) With the above and other related objects in view, the invention consists in the details of construction and combination of parts as will be more fully understood from the following description, when read in conjunction with the accompanying drawings in which:

(2) FIG. 1 represents an isometric operational view of the present invention 10.

(3) FIG. 2 shows an isometric view of the present invention **10** in an expanded configuration **10**. The present invention **10** includes a central assembly **20**, a telescopic assembly **40** and a leveling assembly **60**.

(4) FIG. 3 illustrates an isometric view of the present invention **10** in a retracted configuration.

(5) FIG. 4 is a representation of a front view of the present invention **10** in an expanded configuration.

V. DETAILED DESCRIPTION OF THE EMBODIMENTS OF THE INVENTION

(6) Referring now to the drawings, where the present invention is generally referred to with numeral **10**, it can be observed that it basically includes a central assembly **20**, a telescopic assembly **40** and a leveling assembly **60**. It should be understood there are modifications and variations of the invention that are too numerous to be listed but that all fit within the scope of the invention. Also, singular words should be read as plural and vice versa and masculine as feminine and vice versa, where appropriate, and alternative embodiments do not necessarily imply that the two are mutually exclusive.

(7) The central assembly **20** may include a central member **22**, a rubber portion **26**, marks **27** and a handle **24**. The central member **22** may substantially have a rectangular shape. It also may be suitable for the central member **22** to have a cylindrical shape, a triangular shape, or any other suitable shape. The central member **22** may preferably be made of aluminum. It also may be suitable for the central member **22** to be made of polyurethane, polyvinyl chloride, steel, or any other resistant material. The central member **22** may have the handle **24** in a front portion thereof.

(8) The handle **24** may preferably be made of polyvinyl chloride, polyurethane, or any other resistant material. The handle **24** may substantially have a curved shape. It also may be suitable for the handle **24** to have a rectangular shape, a triangular shape, or any other suitable shape. The handle **24** may have an opening. The handle **24** may be used to handle the present invention **10**.

(9) Referring now to FIG. 2 it can be observed that the rubber portion **26** may be located on a rear side of the central member **22**. The rubber portion **26** may be made of rubber plastic. The rubber portion **26** may be attached to the rear side of the central member **22** and conform to the shape of the central member **22**. The marks **27** may be equidistantly disposed on a length of the central member **22** in such a way that the central member **22** may be used as a ruler.

(10) The telescopic assembly **40** may include a central tube **41**, a left tube **44**, a pivoting element **43** and a right tube **42**. The central tube **41**, the left tube **44** and the right tube **42** may substantially have a rectangular shape. It also may be suitable for the central tube **41**, the left tube **44** and the right tube **42** to have a cylindrical shape, a triangular shape, or any other suitable shape. The central tube **41** may be hollow. the central tube **41** may be adapted to receive the right tube **42** and the left tube **44**. It may be suitable for the central tube **41**, the left tube **44** and the right tube **42** to have marks **27** used to measure size. The left tube **44** and the right tube **42** may be selectively inserted into the central tube **41** providing a retracted configuration illustrated in FIG. 3.

(11) The telescopic assembly **40** may be rotatably attached to the central assembly **20** by means of the pivoting element **43**. The pivoting element **43** may be used to selectively rotate the telescopic assembly **40** with respect to the central assembly **20**, as best illustrated in FIG. 3. The pivoting element **43** may be located at a central portion of the central tube **41**. The pivoting element **43** may be adapted to fix the telescopic assembly **40** in a perpendicular and steady position with respect to the central assembly **20**. The telescopic assembly **40** may be rotated parallel to the central member **22** and have the right tube **42** and the left tube **44** inserted into the central tube **41** so that the present invention **10** may be carried as a unique tube piece.

(12) The leveling assembly **60** may include insertion members **64** and leveling members **62**. The insertion members **64** may have a circular shape. In a preferred embodiment the insertion members **64** may be silicone grommets having a cross opening in a central portion thereof. It also may be suitable for the insertion members **64** to have a rectangular shape, a triangular shape, or any other suitable shape. In a preferred embodiment the insertion members **64** may be made of silicone. It

also may be suitable for the insertion members **64** to be made of polyvinyl chloride, or any other suitable material. The insertion members **64** may be equidistantly attached to a top end of the left tube **44**, the central tube **41**, and the right tube **42**. The insertion members **64** may have an “x” opening to permit fasteners such as nail, screws, drywall anchors to be inserted therethrough and fixed to a wall.

(13) The leveling members **62** may substantially have a cylindrical shape. It also may be suitable for the leveling members **62** to have a rectangular shape, an ovoid shape, or any other suitable shape. In a preferred embodiment the leveling members **62** may be tubular spirit levels. It also may be suitable for the leveling members **62** to be bull's eye spirit levels, an inclinometer, or any other suitable leveling tool known in the prior art. In a preferred embodiment the leveling members **62** may include a first leveling member and a second leveling member. The first leveling member may be located on a first distal end of the left tube **44**. The second leveling member may be located on a second distal end of the right tube **42** opposite to the first leveling member. In a preferred embodiment the leveling members **62** are inserted or integrally formed on the right tube **42** and the left tube **42**.

(14) In a preferred embodiment illustrated in FIG. **1**, the present invention **10** may be placed in an expanded configuration having the telescopic assembly **40** perpendicular to the central assembly **40**. In a preferred embodiment the telescopic assembly **40** may be used to measure distance between frame hangers, then fasteners may be introduced through the openings of the insertion member **64** to place the fasteners equidistantly disposed at a predetermined distance. Then, the present invention **10** may be used to place evenly and equidistantly apart nails, providing an evenly an straight disposition thereof.

(15) The foregoing description conveys the best understanding of the objectives and advantages of the present invention. Different embodiments may be made of the inventive concept of this invention. It is to be understood that all matter disclosed herein is to be interpreted merely as illustrative, and not in a limiting sense.

Claims

1. A wall art hanging tool, comprising: a central assembly, wherein said central assembly includes a central member; a telescopic assembly, wherein said telescopic assembly includes a telescopic member, wherein said telescopic member is perpendicularly connected to said central member; and a leveling assembly, wherein said leveling assembly includes insertion members and leveling members attached thereto, wherein said insertion members are equidistantly disposed on said telescopic member, wherein nails are configured to be introduced into said insertion members to be equidistantly fixed to a wall surface.
2. The wall art hanging tool set forth in claim 1, wherein said insertion members are silicone grommets having an x-shaped opening on a central portion thereof.
3. The wall art hanging tool set forth in claim 1, wherein said leveling members are tubular spirit levels.
4. The wall art hanging tool set forth in claim 1, wherein said telescopic member includes a central tube, a right tube and a left tube, wherein said left tube and said right are capable of being selectively introduced into said central tube.
5. The wall art hanging tool set forth in claim 1, wherein said telescopic member includes a pivoting element, wherein said pivoting element is configured to rotatably connect said telescopic assembly with said central member.
6. The wall art hanging tool set forth in claim 1, wherein said central member includes a handle in a front wall thereof.
7. The wall art hanging tool set forth in claim 1, wherein said central member includes a rubber portion on a rear wall thereof.

8. The wall art hanging tool set forth in claim 1, wherein said central member, said left tube and said right have a rectangular shape and are made of aluminum.

9. A wall art hanging tool, comprising: a central assembly, wherein said central assembly includes a central member; a telescopic assembly, wherein said telescopic assembly includes a telescopic member, wherein said telescopic member includes a central tube, a right tube and a left tube, wherein said central tube is hollow, said central tube is configured to receive said left tube and said right tube therein defining an expanded configuration and a retracted configuration, wherein said left tube and said right tube are inserted into said central tube in said retracted configuration, wherein said central tube is perpendicularly attached to said central member in said expanded configuration, wherein said telescopic member includes a pivoting element, wherein said pivoting element is configured to rotatably attach said central tube to said central member; and a leveling assembly, wherein said leveling assembly includes insertion members and leveling members attached thereto, wherein said insertion members are equidistantly disposed on said telescopic member, wherein nails are configured to be introduced into said insertion members to be equidistantly fixed to a wall surface.

10. A wall art hanging tool, consisting of: a central assembly, wherein said central assembly includes a central member a handle and a rubber portion, wherein said central member has a rectangular elongated shape, said central member is made of aluminum, wherein said handle is in a front wall of said central member, wherein said rubber portion is located at a rear said of said central member, said central member having a top end; a telescopic assembly, wherein said telescopic assembly includes a telescopic member, wherein said telescopic member includes a central tube, a right tube and a left tube, wherein said central tube is hollow, said central tube is configured to receive said left tube and said right tube therein defining an expanded configuration and a retracted configuration, wherein said left tube and said right tube are inserted into said central tube in said retracted configuration, wherein said central tube is perpendicular to said top end of said central member in said expanded configuration, wherein said telescopic member includes a pivoting element, wherein said pivoting element is configured to rotatably attach said central tube to said central member; and a leveling assembly, wherein said leveling assembly includes insertion members and leveling members attached thereto, wherein said insertion members are equidistantly and colinearly disposed on said telescopic member, wherein nails are configured to be introduced into said insertion members to be equidistantly fixed to a wall surface, wherein said leveling members include a first leveling member and a second leveling member, wherein said first leveling member is attached to a first distal end of said left tube, said second leveling member is attached opposite to said first distal end to a second distal end of said right tube, said leveling members are tubular spirit levels.
