

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411481
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Suzuki; Daichi et al.

Control system, control method, and method of producing solid

Abstract

A control device capable of efficiently heating an object by a heating device is disclosed. The control system includes a receipt signal obtainer configured to obtain a receipt signal indicating that a transfer device has received an object, a device selector configured to select an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal obtainer has obtained the receipt signal, a movement instructor configured to instruct the transfer device to move to a position of the selected heating device, a standby signal obtainer configured to obtain a standby signal indicating that the transfer device stands by in the position of the selected heating device, and a loading instructor configured to instruct, in a case where the standby signal obtainer has obtained the standby signal, the selected heating device to open a door and instruct the transfer device to load the object into the selected heating device.

Inventors: Suzuki; Daichi (Yokohama, JP), Iwama; Tatsuhiro (Yokohama, JP), Ichiishi; Kenji (Yokohama, JP)

Applicant: K.K. SUN METALON (Yokohama, JP)

Family ID: 96950445

Assignee: K.K. Sun Metalon (Yokohama, JP)

Appl. No.: 19/089770

Filed: March 25, 2025

Foreign Application Priority Data

JP	2024-224192	Dec. 19, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: G05B19/418 (20060101)

U.S. Cl.:
CPC G05B19/4189 (20130101); G05B2219/45244 (20130101); G05B2219/49051 (20130101)

Field of Classification Search

CPC: G05B (19/4189); G05B (2219/45244); G05B (2219/49051)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6928892	12/2004	Storbeck	73/865.8	G01N 15/06
2023/0217558	12/2022	Kou	N/A	N/A
2024/0165700	12/2023	Nishioka et al.	N/A	N/A
2024/0165706	12/2023	Nishioka et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
7270800	12/2022	JP	N/A
7450312	12/2023	JP	N/A
7450313	12/2023	JP	N/A

OTHER PUBLICATIONS

L'Orange, Christian, et al. “A high-throughput, robotic system for analysis of aerosol sampling filters.” Aerosol and air quality research 21.11 (2021): 210037. (Year: 2021). cited by examiner

Primary Examiner: Ortiz Rodriguez; Carlos R
Attorney, Agent or Firm: Knobbe, Martens, Olson & Bear, LLP

Background/Summary

BACKGROUND

- Field
(1) The present disclosure relates to a control system, a control method, and a method of producing a solid.
- Related Art
(2) In a product production process, a product or a raw material of the product may be heated (for example, see Japanese Patent No. 7450313, Japanese Patent No. 7450312, and Japanese Patent No. 7270800).
(3) According several aspects, a control device is disclosed capable of efficiently heating an object by a heating device.

SUMMARY

- (4) A control system according to an embodiment of the present disclosure is a control system configured to control a transfer device and a plurality of heating devices, the control system including a receipt signal obtainer configured to obtain a receipt signal indicating that the transfer device has received an object, a device selector configured to select an available heating device as a

selected heating device from among the plurality of heating devices in a case where the receipt signal obtainer has received the receipt signal, a movement instructor configured to instruct the transfer device to move to a position of the selected heating device, a standby signal obtainer configured to obtain a standby signal indicating that the transfer device stands by in the position of the selected heating device, a loading instructor configured to instruct, in a case where the standby signal obtainer has obtained the standby signal, the selected heating device to open a door and instruct the transfer device to load the object into the selected heating device, a loading signal obtainer configured to obtain a loading signal indicating that the transfer device has loaded the object into the selected heating device, a heating instructor configured to instruct, in a case where the loading signal obtainer has obtained the loading signal, the selected heating device to close the door and heat the object, a heating completion signal obtainer configured to obtain a heating completion signal indicating that heating of the object has been completed in the selected heating device, and an unloading instructor configured to instruct, in a case where the heating completion signal obtainer has obtained the heating completion signal, the selected heating device to open the door and instruct the transfer device to unload the object from the selected heating device.

(5) In the control system, each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal may be issued.

(6) In the control system, the aerosol may be smoke or vapor.

(7) In the control system, the object may contain oil or water.

(8) In the control system, the object may further contain a metal or a metal compound.

(9) In the control system, each of the plurality of heating devices may include an irradiation device configured to emit electromagnetic waves therein.

(10) In the control system, the transfer device may receive the object from the processing device.

(11) In the control system, the processing device may be a molding machine.

(12) In the control system, the molding machine may be a briquette machine.

(13) The control system may further include a processing completion signal obtainer configured to obtain a processing completion signal indicating that processing on the object has been completed in the processing device, and a reception instructor configured to instruct the transfer device to receive the object from the processing device in a case where the processing completion signal obtainer has obtained the processing completion signal.

(14) In the control system, in a case where the processing completion signal obtainer has obtained the processing completion signal, the movement instructor may instruct the transfer device to move to a position of the processing device.

(15) In the control system, in a case where the loading signal obtainer has obtained the loading signal, the movement instructor may instruct the transfer device to move to the position of the processing device.

(16) In the control system, in a case where the heating completion signal obtainer has obtained the heating completion signal, the movement instructor may instruct the transfer device to move to the position of the selected heating device.

(17) The control system may further include a container status checker configured to obtain a container status signal indicating that a container has a space to accommodate the object, and in a case where the container status checker has obtained the container status signal, the movement instructor may instruct the transfer device to move the object unloaded from the selected heating device into the container.

(18) In the control system, the heating instructor may transmit a heating condition based on a composition of the object to the selected heating device.

(19) A method of controlling a transfer device and a plurality of heating devices according to an embodiment of the present invention includes obtaining a receipt signal indicating that the transfer

device has received an object, selecting an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal has been obtained, instructing the transfer device to move to a position of the selected heating device, obtaining a standby signal indicating that the transfer device stands by in the position of the selected heating device, instructing, in a case where the standby signal has been obtained, the selected heating device to open a door and instructing the transfer device to load the object into the selected heating device, obtaining a loading signal indicating that the transfer device has loaded the object into the selected heating device, instructing, in a case where the loading signal has been obtained, the selected heating device to close the door and heat the object, obtaining a heating completion signal indicating that heating of the object has been completed in the selected heating device, and instructing, in a case where the heating completion signal has been obtained, the selected heating device to open the door and instructing the transfer device to unload the object from the selected heating device.

(20) In the control method, after the loading signal has been obtained, until unloading of the object is instructed, the obtaining the receipt signal, the selecting the available heating device as the selected heating device, the instructing the movement, the obtaining the standby signal, and the instructing the loading may be repeated.

(21) In the control method, each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal may be issued.

(22) In the control method, the aerosol may be smoke or vapor.

(23) In the control method, the object may contain oil or water.

(24) In the control method, the object may further contain a metal or a metal compound.

(25) In the control method, each of the plurality of heating devices may include an irradiation device configured to emit electromagnetic waves therein.

(26) In the control method, the transfer device may receive the object from the processing device.

(27) In the control method, the processing device may be a molding machine.

(28) In the control method, the molding machine may be a briquette machine.

(29) The control method may further include obtaining a processing completion signal indicating that processing on the object has been completed in the processing device, and instructing the transfer device to receive the object from the processing device in a case where the processing completion signal has been obtained.

(30) In the control method, in a case where the processing completion signal has been obtained, the transfer device may be instructed to move to a position of the processing device.

(31) In the control method, in a case where the loading signal has been obtained, the transfer device may be instructed to move to the position of the processing device.

(32) In the control method, in a case where the heating completion signal has been obtained, the transfer device may be instructed to move to the position of the selected heating device.

(33) The control method may further include obtaining a container status signal indicating that a container has a space to accommodate the object, in which in a case where the container status signal has been obtained, the transfer device may be instructed to move the object unloaded from the selected heating device into the container.

(34) In the control method, a heating condition based on a composition of the object may be transmitted to the selected heating device.

(35) A method of producing a solid according to an embodiment of the present disclosure includes: receiving, by a transfer device, an object; transmitting, to a control system, a receipt signal indicating that the transfer device has received the object; obtaining, by the control system, the receipt signal and selecting an available heating device as a selected heating device from among a plurality of heating devices; instructing, by the control system, the transfer device to move to a

position of the selected heating device; transmitting, to the control system, a standby signal indicating that the transfer device stands by in the position of the selected heating device; instructing, by the control system, the selected heating device to open a door and instructing the transfer device to load the object into the selected heating device; transmitting, to the control system, a loading signal indicating that the transfer device has loaded the object into the selected heating device; instructing, by the control system, the selected heating device to close the door and heat the object; heating, by the selected heating device, the object to solidify; transmitting, by the selected heating device, a heating completion signal indicating that the heating of the object has been completed to the control system; and instructing, by the control system, the selected heating device to open the door and instructing the transfer device to unload the object from the selected heating device.

(36) In the method of producing the solid, in the heating, by the selected heating device, the object to solidify, an impurity contained in the object may be reduced.

(37) In the method of producing the solid, the impurity may be oil or water.

(38) In the method of producing the solid, in the heating, by the selected heating device, the object to solidify, an oxide film contained in the object may be reduced.

(39) In the method of producing the solid, after the loading signal has been transmitted to the control system, until unloading of the object is instructed, the transmitting the receipt signal to the control system, the selecting the available heating device as the selected heating device, the instructing the movement, the transmitting the standby signal to the control system, and the instructing the loading may be repeated.

(40) In the method of producing the solid, each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal may be issued.

(41) In the method of producing the solid, the aerosol may be smoke or vapor.

(42) In the method of producing the solid, the object may further contain a metal or a metal compound.

(43) In the method of producing the solid, each of the plurality of heating devices may include an irradiation device configured to emit electromagnetic waves therein.

(44) In the method of producing the solid, the transfer device may receive the object from the processing device.

(45) In the method of producing the solid, the processing device may be a molding machine.

(46) In the method of producing the solid, the molding machine may be a briquette machine.

(47) The method of producing the solid may further include obtaining a processing completion signal indicating that processing on the object has been completed in the processing device, and instructing the transfer device to receive the object from the processing device in a case where the processing completion signal has been obtained.

(48) In the method of producing the solid, in a case where the processing completion signal has been obtained, the transfer device may be instructed to move to a position of the processing device.

(49) In the method of producing the solid, in a case where the loading signal has been obtained, the transfer device may be instructed to move to the position of the processing device.

(50) In the method of producing the solid, in a case where the heating completion signal has been obtained, the transfer device may be instructed to move to the position of the selected heating device.

(51) The method of producing the solid may further include obtaining a container status signal indicating that a container has a space to accommodate the object, in which in a case where the container status signal has been obtained, the transfer device may be instructed to move the object unloaded from the selected heating device into the container.

(52) In the method of producing the solid, a heating condition based on a composition of the object

may be transmitted to the selected heating device.

(53) A program according to an embodiment of the present invention is a program for causing a computer to execute a method of controlling a transfer device and a plurality of heating devices, the method including obtaining a receipt signal indicating that the transfer device has received an object, selecting an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal has been obtained, instructing the transfer device to move to a position of the selected heating device, obtaining a standby signal indicating that the transfer device stands by in the position of the selected heating device, instructing, in a case where the standby signal has been obtained, the selected heating device to open a door and instructing the transfer device to load the object into the selected heating device, obtaining a loading signal indicating that the transfer device has loaded the object into the selected heating device, instructing, in a case where the loading signal has been obtained, the selected heating device to close the door and heat the object, obtaining a heating completion signal indicating that heating of the object has been completed in the selected heating device, and instructing, in a case where the heating completion signal has been obtained, the selected heating device to open the door and instructing the transfer device to unload the object from the selected heating device.

(54) In the method that the program causes the computer to execute, after the loading signal has been obtained, until unloading of the object is instructed, the obtaining the receipt signal, the selecting the available heating device as the selected heating device, the instructing the movement, the obtaining the standby signal, and the instructing the loading may be repeated.

(55) In the method that the program causes the computer to execute, each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal may be issued.

(56) In the method that the program causes the computer to execute, the aerosol may be smoke or vapor.

(57) In the method that the program causes the computer to execute, the object may contain oil or water.

(58) In the method that the program causes the computer to execute, the object may further contain a metal or a metal compound.

(59) In the method that the program causes the computer to execute, each of the plurality of heating devices may include an irradiation device configured to emit electromagnetic waves therein.

(60) In the method that the program causes the computer to execute, the transfer device may receive the object from the processing device.

(61) In the method that the program causes the computer to execute, the processing device may be a molding machine.

(62) In the method that the program causes the computer to execute, the molding machine may be a briquette machine.

(63) The method that the program causes the computer to execute may further include obtaining a processing completion signal indicating that processing on the object has been completed in the processing device, and instructing the transfer device to receive the object from the processing device in a case where the processing completion signal has been obtained.

(64) In the method that the program causes the computer to execute, in a case where the processing completion signal has been obtained, the transfer device may be instructed to move to a position of the processing device.

(65) In the method that the program causes the computer to execute, in a case where the loading signal has been obtained, the transfer device may be instructed to move to the position of the processing device.

(66) In the method that the program causes the computer to execute, in a case where the heating completion signal has been obtained, the transfer device may be instructed to move to the position

of the selected heating device.

(67) The method that the program causes the computer to execute may further include obtaining a container status signal indicating that a container has a space to accommodate the object, in which in a case where the container status signal has been obtained, the transfer device may be instructed to move the object unloaded from the selected heating device into the container.

(68) In the method that the program causes the computer to execute, a heating condition based on a composition of the object may be transmitted to the selected heating device.

(69) A computer readable recording medium according to an embodiment of the present invention is a recording medium having recorded thereon a program for causing a computer to execute a method of controlling a transfer device and a plurality of heating devices, the method including obtaining a receipt signal indicating that the transfer device has received an object, selecting an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal has been obtained, instructing the transfer device to move to a position of the selected heating device, obtaining a standby signal indicating that the transfer device stands by in the position of the selected heating device, instructing, in a case where the standby signal has been obtained, the selected heating device to open a door and instructing the transfer device to load the object into the selected heating device, obtaining a loading signal indicating that the transfer device has loaded the object into the selected heating device, instructing, in a case where the loading signal has been obtained, the selected heating device to close the door and heat the object, obtaining a heating completion signal indicating that heating of the object has been completed in the selected heating device, and instructing, in a case where the heating completion signal has been obtained, the selected heating device to open the door and instructing the transfer device to unload the object from the selected heating device.

(70) In the method which the program recorded on the recording medium causes the computer to execute, after the loading signal has been obtained, until unloading of the object is instructed, the obtaining the receipt signal, the selecting the available heating device as the selected heating device, the instructing the movement, the obtaining the standby signal, and the instructing the loading may be repeated.

(71) In the method which the program recorded on the recording medium causes the computer to execute, each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal may be issued.

(72) In the method which the program recorded on the recording medium causes the computer to execute, the aerosol may be smoke or vapor.

(73) In the method which the program recorded on the recording medium causes the computer to execute, the object may contain oil or water.

(74) In the method which the program recorded on the recording medium causes the computer to execute, the object may further contain a metal or a metal compound.

(75) In the method which the program recorded on the recording medium causes the computer to execute, each of the plurality of heating devices may include an irradiation device configured to emit electromagnetic waves therein.

(76) In the method which the program recorded on the recording medium causes the computer to execute, the transfer device may receive the object from the processing device.

(77) In the method which the program recorded on the recording medium causes the computer to execute, the processing device may be a molding machine.

(78) In the method which the program recorded on the recording medium causes the computer to execute, the molding machine may be a briquette machine.

(79) The method which the program recorded on the recording medium causes the computer to execute may further include obtaining a processing completion signal indicating that processing on

the object has been completed in the processing device, and instructing the transfer device to receive the object from the processing device in a case where the processing completion signal has been obtained.

(80) In the method which the program recorded on the recording medium causes the computer to execute, in a case where the processing completion signal has been obtained, the transfer device may be instructed to move to a position of the processing device.

(81) In the method which the program recorded on the recording medium causes the computer to execute, in a case where the loading signal has been obtained, the transfer device may be instructed to move to the position of the processing device.

(82) In the method which the program recorded on the recording medium causes the computer to execute, in a case where the heating completion signal has been obtained, the transfer device may be instructed to move to the position of the selected heating device.

(83) The method which the program recorded on the recording medium causes the computer to execute may further include obtaining a container status signal indicating that a container has a space to accommodate the object, in which in a case where the container status signal has been obtained, the transfer device may be instructed to move the object unloaded from the selected heating device into the container.

(84) In the method which the program recorded on the recording medium causes the computer to execute, a heating condition based on a composition of the object may be transmitted to the selected heating device.

(85) A recording medium according to an embodiment of the present invention is a recording medium having recorded thereon a program for controlling a transfer device and a plurality of heating devices and for causing a computer to execute a method including obtaining a receipt signal indicating that the transfer device has received an object, selecting an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal has been obtained, instructing the transfer device to move to a position of the selected heating device, obtaining a standby signal indicating that the transfer device stands by in the position of the selected heating device, instructing, in a case where the standby signal has been obtained, the selected heating device to open a door and instructing the transfer device to load the object into the selected heating device, obtaining a loading signal indicating that the transfer device has loaded the object into the selected heating device, instructing, in a case where the loading signal has been obtained, the selected heating device to close the door and heat the object, obtaining a heating completion signal indicating that heating of the object has been completed in the selected heating device, and instructing, in a case where the heating completion signal has been obtained, the selected heating device to open the door and instructing the transfer device to unload the object from the selected heating device.

Advantageous Effect

(86) According to several aspects of the present disclosure, it is possible to provide the control device capable of efficiently heating the object by the heating device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a control system according to an embodiment;
- (2) FIG. 2 is a schematic diagram of the control system according to the embodiment;
- (3) FIG. 3 is a schematic diagram of the control system according to the embodiment;
- (4) FIG. 4 is a schematic diagram of the control system according to the embodiment;
- (5) FIG. 5 is a schematic diagram of the control system according to the embodiment;
- (6) FIG. 6 is a schematic diagram of the control system according to the embodiment;

- (7) FIG. 7 is a schematic side view of an inside of a heating device according to the embodiment;
- (8) FIG. 8 is a schematic top view of the inside of the heating device according to the embodiment as viewed from an A-A direction in FIG. 7;
- (9) FIG. 9 is a schematic side view of the inside of the heating device according to the embodiment;
- (10) FIG. 10 is a flowchart of a method according to the embodiment;
- (11) FIG. 11 is a flowchart of the method according to the embodiment; and
- (12) FIG. 12 is a schematic diagram of a data collection system according to the embodiment.

DETAILED DESCRIPTION

(13) Hereinafter, an embodiment of the present invention will be described with reference to the drawings. It is noted however that the drawings are schematic drawings. Therefore, specific dimensions and the like are to be determined in the light of the following description. In addition, parts with mutually different dimensional relationships and ratios are of course included between the mutual drawings too.

(14) As illustrated in FIG. 1, a control system **100** according to the embodiment which is configured to control a transfer device **10** and a plurality of heating devices **20A**, **20B**, **20C**, . . . (**20x**) includes a receipt signal obtainer **101** configured to obtain a receipt signal indicating that the transfer device **10** has received an object **30**, a device selector **102** configured to select an available heating device as a selected heating device from among the plurality of heating devices **20A**, **20B**, **20C** . . . in a case where the receipt signal obtainer **101** has obtained the receipt signal, and a movement instructor **103** configured to instruct the transfer device **10** to move to a position of the selected heating device.

(15) The control system **100** according to the embodiment also includes a standby signal obtainer **104** configured to obtain a standby signal indicating that the transfer device **10** stands by in the position of the selected heating device as illustrated in FIG. 2, a loading instructor **105** configured to instruct, in a case where the standby signal obtainer **104** has obtained the standby signal, the selected heating device to open the door **21A** and instruct the transfer device **10** to load the object **30** into the selected heating device, and a loading signal obtainer **106** configured to obtain a loading signal indicating that the transfer device **10** has loaded the object **30** in the selected heating device as illustrated in FIG. 3 and FIG. 4. In a case where the loading signal obtainer **106** has obtained the loading signal, the movement instructor **103** may instruct the transfer device **10** to move to a position of a processing device **40** configured to process the object **30**.

(16) In addition, the control system **100** according to the embodiment includes a heating instructor **107** configured to instruct, in a case where the loading signal obtainer **106** has obtained the loading signal, the selected heating device to close the door **21A** and heat the object **30** as illustrated in FIG. 5, a heating completion signal obtainer **108** configured to obtain a heating completion signal indicating that heating of the object **30** has been completed in the selected heating device, and an unloading instructor **109** configured to instruct, in a case where the heating completion signal obtainer **108** has obtained the heating completion signal, the selected heating device to open the door **21A** and instruct the transfer device **10** to unload the object **30** from the selected heating device. The heating instructor **107** may transmit a heating condition based on a composition of the object **30** to the selected heating device. In a case where the heating completion signal obtainer **108** has obtained the heating completion signal, the movement instructor **103** may instruct the transfer device **10** to move to the position of the selected heating device.

(17) In addition, the control system **100** according to the embodiment may include a processing completion signal obtainer **110** configured to obtain a processing completion signal indicating that processing of the object **30** in the processing device **40** has been completed, and a reception instructor **111** configured to instruct, in a case where the processing completion signal obtainer **110** has obtained the processing completion signal, the transfer device **10** to receive the object **30** from the processing device **40**. In a case where the processing completion signal obtainer **110** has

obtained the processing completion signal, the movement instructor **103** may instruct the transfer device **10** to move to the position of the processing device **40**.

(18) In addition, the control system **100** according to the embodiment may further include a container status checker **112** configured to obtain a container status signal indicating that a container **60** designed to store the object **30** after being heated has a space to accommodate the object **30**. In a case where the container status checker **112** has obtained the container status signal, as illustrated in FIG. **6**, the movement instructor **103** may instruct the transfer device **10** to move the object **30** unloaded from the selected heating device into the container **60**.

(19) The control system **100** is, for example, a computer and includes a processor such as a CPU (central processing unit) or FPGA (field-programmable gate array) and a volatile and/or nonvolatile storage device such as a ROM (read only memory), a RAM (random access memory), and a hard disk. It is noted however that the storage device may be outside the computer or may be situated in a location away from the computer.

(20) The receipt signal obtainer **101**, the device selector **102**, the movement instructor **103**, the standby signal obtainer **104**, the loading instructor **105**, the loading signal obtainer **106**, the heating instructor **107**, the heating completion signal obtainer **108**, the unloading instructor **109**, the processing completion signal obtainer **110**, the reception instructor **111**, and the container status checker **112** are realized when a program stored in the storage device is executed by the processor in the computer.

(21) Alternatively, the device selector **102**, the movement instructor **103**, the standby signal obtainer **104**, the loading instructor **105**, the loading signal obtainer **106**, the heating instructor **107**, the heating completion signal obtainer **108**, the unloading instructor **109**, the processing completion signal obtainer **110**, the reception instructor **111**, and the container status checker **112** may be realized by a hardware such as, for example, a PLC (programmable logic controller).

(22) The control system **100**, and the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . and the container **60** are electrically connected to one another via a wired or wireless configuration and can mutually transmit and receive electric signals. The control system **100**, and the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , and the container **60** may be arranged in separate locations. Alternatively, the control system **100**, and the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , and the container **60** may be arranged in adjacent locations. The control system **100** may be arranged inside any one of the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , and the container **60**.

(23) The object **30** is not particularly limited and may be, for example, an industrial material, an industrial product, a food material, and food. The object **30** is also referred to as a work. A shape of the object **30** is not particularly limited and is, for example, disk-shaped, cylindrical, and prismatic. A hardness of the object **30** is not particularly limited and may be hard or may be brittle as long as the object **30** can be transferred by the transfer device **10**. A material of the object **30** is not particularly limited and may be a metal, a non-metallic inorganic matter, and an organic matter. The object **30** may be a metal briquette obtained by compressing a metal material. The material of the object **30** may contain a metal element or a metal compound such as an alloy. Examples of the metal include iron (Fe), nickel (Ni), copper (Cu), gold (Au), silver (Ag), aluminum (Al), and cobalt (Co).

(24) A sintering temperature of iron (Fe) is, for example, 1200° C. A melting point of iron (Fe) is 1538° C. A sintering temperature of nickel (Ni) is, for example, 1200° C. A melting point of nickel (Ni) is 1495° C. A sintering temperature of copper (Cu) is, for example, 800° C. A melting point of copper (Cu) is 1085° C. A sintering temperature of gold (Au) is, for example, 800° C. A melting point of gold (Au) is 1064° C. A sintering temperature of silver (Ag) is, for example, 750° C. A melting point of silver (Ag) is 962° C. A sintering temperature of aluminum (Al) is, for example, 500° C. A melting point of aluminum (Al) is 660° C. A sintering temperature of cobalt (Co) is, for example, 1100° C. A melting point of cobalt (Co) is 1455° C.

(25) The material of the object **30** may contain one type of a metal or may contain a plurality of types of metals. Examples of the metal compound include an alloy consisting of a plurality of metallic elements, an alloy consisting of a metallic element and a non-metallic element, a metal oxide, a metal hydroxide, a metal chloride, a metal carbide, a metal boride, and a metal sulfide but are not particularly limited. A metal powder may contain, as alloy components, for example, silicon (Si), manganese (Mn), chromium (Cr), nickel (Ni), carbon (C), boron (B), copper (Cu), aluminum (Al), titanium (Ti), niobium (Nb), vanadium (V), zinc (Zn), sulfur (S), and the like.

(26) The object **30** may contain an impurity. In a case where the object **30** is a metal briquette, the object **30** may contain an impurity such as oil, a lubricant, an organic compound, an aqueous solution, and water. The impurity may be volatile. An oxide such as an oxide film may be formed in the object **30**.

(27) The transfer device **10** may be, for example, a transfer robot. The transfer device **10** can, for example, move in any direction on a floor. Alternatively, the transfer device **10** can move along a rail and a guide. The rail and the guide may be set on the floor or may be suspended from a ceiling. The transfer device **10** includes a grip device **11** configured to grip the object **30**, for example. The grip device **11** is also referred to as a robot hand or an end effector. The transfer device **10** includes, for example, a movement device **12** which is connected to the grip device **11** and configured to move the grip device **11**. The movement device **12** can move in a three-dimensional direction and can move the grip device **11** to any location. The movement device **12** may include a robot arm and a manipulator. The movement device **12** may include a vertical robot arm, a SCARA robot arm, a parallel link robot arm, and a Cartesian robot arm.

(28) The transfer device **10** receives the object **30**, for example, from the processing device **40** which processes the object **30**. Examples of the processing device **40** include a briquette machine. The briquette machine may be a molding machine, a compression machine, and a solidification machine. The processing device **40** processes the material to produce the object **30**. The processing device **40** applies a pressure to the material, for example, to produce the object **30**, which is a molded product. A shape and a size of the material are not limited. The material is, for example, a metal material. The metal material is, for example, a metal piece. The metal piece may be, for example, a metal cut piece, a metal fragment, a metal chip, a metal machining dust, or a metal powder. The pressure to be applied to the material by the processing device **40** is not limited but is, for example, greater than or equal to 1 MPa, greater than or equal to 100 MPa, or greater than or equal to 200 MPa and is less than or equal to 2000 MPa, less than or equal to 1900 MPa, or less than or equal to 1800 MPa. Examples of the pressure application method include uniaxial molding, cold isostatic pressing (CIP) molding, hot isostatic pressing (HIP) molding, roller pressurization, and the like.

(29) Means for heating the object **30** by each of the heating devices **20A**, **20B**, **20C** . . . is not particularly limited. The heating devices **20A**, **20B**, **20C** . . . irradiate the object **30**, for example, with electromagnetic waves to heat the object **30**. The heated object **30** sinters or melts to solidify, for example. In a case where the object **30** contains a volatile impurity, when the object **30** is heated, the impurity is vaporized. According to this, the impurity is reduced in the object **30**. Alternatively, the impurity is removed from the object **30**. In a case where the object **30** contains an oxide such as an oxide film, when the object **30** is heated, the oxide is vaporized. Alternatively, reduction of the oxide occurs. According to this, the oxide is reduced in the object **30**. Alternatively, the oxide is removed from the object **30**.

(30) The electromagnetic waves are, for example, millimeter waves and microwaves. The millimeter waves are electromagnetic waves, for example, with a frequency from 30 GHz to 300 GHz. The microwaves are electromagnetic waves, for example, with a frequency from 300 MHz to 30 GHz. Each of the heating devices **20A**, **20B**, **20C** . . . may include a pressurizer configured to apply a pressure to the object **30**. The pressurizer may apply a pressure to the object **30** at least any of moments before the object **30** is irradiated with electromagnetic waves, while the object **30** is

irradiated with electromagnetic waves, and after the object **30** is irradiated with electromagnetic waves.

(31) The heating devices **20A**, **20B**, **20C** . . . respectively include chambers and doors **21A**, **21B**, **21C** . . . provided in the chambers. When the object **30** is put into the chamber, the heating devices **20A**, **20B**, **20C** . . . open the doors **21A**, **21B**, **21C** . . . , respectively. When the object **30** is heated in the chamber, the heating devices **20A**, **20B**, **20C** . . . close the doors **21A**, **21B**, **21C** . . . , respectively. When the object **30** is taken out from the chamber, the heating devices **20A**, **20B**, **20C** . . . open the doors **21A**, **21B**, **21C** . . . , respectively.

(32) For example, the heating devices **20A**, **20B**, **20C** . . . have a same configuration. Hereinafter, the configuration of the heating device **20A** will be described. The heating device **20A** includes, for example, as illustrated in FIG. 7 and FIG. 8, a chamber **22A**, an electromagnetic wave irradiation device **50A** configured to emit electromagnetic waves within the chamber **22A**, and a stage **23A** which is provided in the chamber **22A** and designed to place the object **30** thereon. A window **61A** for allowing electromagnetic waves emitted from the electromagnetic wave irradiation device **50A** to pass through is provided in the chamber **22A**. The heating device **20A** may include a drive device **24A** configured to rotate the stage **23A**. By rotating the stage **23A**, it is possible to evenly irradiate the object **30** with electromagnetic waves. A promotor **25A** configured to promote heating of the object **30** may be arranged on the stage **23A**, and the object **30** may be arranged on the stage **23A** via the promotor **25A**.

(33) The heating device **20A** may include a promotor **26A** in contact with a top surface of the object **30** as illustrated in FIG. 9. The promotor **26A** is configured to be movable up and down inside the chamber **22A**. The promotor **26A** is connected to a shaft **27A**, for example. When the stage **23A** rotates, the promotor **26A** passively rotates via a friction force between a top surface of the stage **23A** and a bottom surface of the promotor **25A**, a friction force between a top surface of the promotor **25A** and a bottom surface of the object **30**, and a friction force between the top surface of the object **30** and a bottom surface of the promotor **26A**.

(34) The promotors **25A** and **26A** may contain a thermal insulation material with a higher transmittance of electromagnetic waves than that of the object **30** and a lower absorption degree of electromagnetic wave than that of the object **30**. The thermal insulation material has a higher melting point than a melting point of the object **30**. Since the thermal insulation material has a low absorption degree of electromagnetic waves, even when irradiated with electromagnetic waves, the thermal insulation material has a low degree of heat generation and exhibits a heat insulation effect. In addition, since the thermal insulation material has the higher melting point than that of the object **30**, even when irradiated with electromagnetic waves, the thermal insulation material has a stable shape. For this reason, even while the object **30** irradiated with electromagnetic waves sinters or melts, shapes of the promotors **25A** and **26A** containing the thermal insulation material may be stable.

(35) The thermal insulation material may contain a metal oxide or may contain a metalloid oxide. Examples of the metal and metalloid oxides include aluminum oxide (Al.sub.2O.sub.3), silicon oxide (SiO.sub.2), magnesium oxide (MgO), zirconium oxide (ZrO.sub.2), and titanium oxide (TiO.sub.2) but are not particularly limited. For example, a melting point of aluminum oxide (Al.sub.2O.sub.3) is 2072°C . A melting point of silicon oxide (SiO.sub.2) is 1710°C . A melting point of magnesium oxide (MgO) is 2852°C . The thermal insulation material may be a compound of these.

(36) The promotors **25A** and **26A** may contain an absorbing material that absorbs electromagnetic waves in a temperature range at least partially below a temperature range in which the object **30** absorbs electromagnetic waves. The absorbing material has a higher melting point than the melting point of the object **30**. At least part of the temperature range in which the absorbing material absorbs electromagnetic waves is lower than the temperature range in which the object **30** absorbs electromagnetic waves. In a case where the object **30** contains a metal, the temperature range in

which the object **30** absorbs electromagnetic waves is, for example, greater than or equal to 300° C. and less than or equal to 1200° C., greater than or equal to 450° C. and less than or equal to 1100° C., or greater than or equal to 600° C. and less than or equal to 800° C. The temperature range in which the absorbing material absorbs electromagnetic waves is, for example, greater than or equal to 100° C. and less than or equal to 1000° C., greater than or equal to 250° C. and less than or equal to 900° C., or greater than or equal to 400° C. and less than or equal to 600° C.

(37) At least part of the temperature range in which the absorbing material absorbs electromagnetic waves is preferably overlapped with the temperature range in which the object **30** absorbs electromagnetic waves. Since the absorbing material absorbs electromagnetic waves in the temperature range at least partially below the temperature range in which the object **30** absorbs electromagnetic waves, the absorbing material generates heat faster than the object **30**. For this reason, until the object **30** reaches the temperature range for absorbing electromagnetic waves, the absorbing material can heat the object **30**. Therefore, when the promoters **25A** and **26A** contain the absorbing material, a temperature of the object **30** can reach the temperature range for absorbing electromagnetic waves faster, and a heating time period of the object **30** can be shortened. In addition, since the absorbing material absorbs electromagnetic waves in the temperature range at least partially below the temperature range in which the object **30** absorbs electromagnetic waves, it is possible to avoid heating the promoters **25A** and **26A** more than necessary. For this reason, while the object **30** irradiated with electromagnetic waves sinters or melts too, the shapes of the promoters **25A** and **26A** containing the absorbing material may be stable.

(38) The absorbing material contains, for example, a carbon material. Examples of the carbon material include carbon black, an amorphous carbon, graphite, silicon carbide, carbon resin, and a metal carbide but are not particularly limited. The absorbing material may contain a metal nitride, a metal oxide, a metal boride, and the like that absorb electromagnetic waves in a temperature range at least partially below the temperature range in which the object **30** subjected to sintering or melt solidification absorbs electromagnetic waves. The absorbing material may be a compound of these. Preferably, the absorbing material does not contain a volatile component. Since the absorbing material does not contain a volatile component, it is possible to avoid a situation where electromagnetic waves are absorbed into the volatile component.

(39) The promoters **25A** and **26A** may contain a reducing material which reduces the object **30**. The reducing material has a higher melting point than the melting point of the object **30**. Examples of the reducing material include carbon and silicon carbide. A carbon material used as the absorbing material may function as the reducing material.

(40) The promoters **25A** and **26A** may consist of a thermal insulation material alone, may consist of an absorbing material alone, may consist of a reducing material alone, or may contain a combination of these. In addition, each of the thermal insulation material, the absorbing material, and the reducing material may have overlapping properties and functions. For example, the carbon material may function as the absorbing material and may function as the reducing material.

(41) The heating device **20A** includes, for example, an aerosol sensor **51A** configured to detect an aerosol in the chamber **22A**. The aerosol is, for example, smoke or vapor. The smoke may be oil smoke. The vapor may be water vapor. The aerosol is generated, for example, when the object **30** is heated, and a volatile substance contained in the object **30** evaporates. The aerosol sensor **51A** measures the aerosol, for example, by irradiating the inside of the chamber **22A** with light and measuring an amount of transmitted light. Alternatively, the aerosol sensor **51A** measures the aerosol by irradiating the inside of the chamber **22A** with light and measuring light scattering. In a case where an aerosol of a predetermined concentration is detected by the aerosol sensor **51A** and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, it can be regarded that evaporation of the volatile substance contained in the object **30** has been completed and sintering and solidification of the object **30** has been completed. The predetermined amount of aerosol may be set based on an amount of volatile

substance that the object **30** is allowed to contain. The predetermined amount of aerosol may be a predetermined concentration of aerosol.

(42) The heating device **20A** includes, for example, a fire sensor **52A** configured to detect a fire, a flame, and a spark in the chamber **22A**. The fire, the flame, and the spark break out, for example, when the object **30** is abnormally heated. The heating device **20A** includes, for example, temperature sensors **53A**, **54A**, and **55A** configured to detect a temperature in the chamber **22A**. The temperature sensors **53A**, **54A**, and **55A** may be radiation thermometers. In a case where the temperature sensors **53A**, **54A**, and **55A** detect that the object **30** has reached a predetermined temperature or detect that the object **30** has reached a predetermined temperature and a predetermined period of time has elapsed, it can be regarded that sintering and solidification of the object **30** have been completed.

(43) The heating device **20A** may include an atmosphere control device **56** configured to control an atmosphere in the chamber **22A**. The atmosphere control device **56** may set, for example, an inert gas atmosphere in the chamber **22A**. Examples of an inert gas include argon (Ar) and helium (He). The atmosphere control device **56** may set, for example, a neutral gas atmosphere in the chamber **22A**. Examples of a neutral gas include nitrogen (N.sub.2), dry hydrogen (H.sub.2), and ammonia (NH.sub.3). The atmosphere control device **56** may set, for example, a reducing gas atmosphere in the chamber **22A**. Examples of a reducing gas include hydrogen (H.sub.2), carbon monoxide (CO), and hydrocarbon gases (such as CH.sub.4, C.sub.3H.sub.8, and C.sub.4H.sub.10). By setting the atmosphere in the chamber **22A** to be a reducing atmosphere, it is possible to realize reduction of an oxide that may be contained in the object **30**.

(44) Next, a method of controlling the transfer device **10** and the plurality of heating devices **20A**, **20B**, **20C** . . . , an operation method of the transfer device **10** and the plurality of heating devices **20A**, **20B**, **20C** . . . , and a method of producing a solid according to the embodiment will be described with reference to flowcharts of FIG. **10** and FIG. **11**.

(45) In step **S101**, the processing device **40** transmits, to the control system **100**, a processing completion signal indicating that processing of the object **30** has been completed. The processing completion signal obtainer **110** of the control system **100** receives the processing completion signal. In step **S102**, the reception instructor **111** of the control system **100** transmits, to the transfer device **10**, a reception instruction signal for instructing the transfer device **10** to receive the object **30** from the processing device **40**. The transfer device **10** receives the reception instruction signal. It is noted that in a case where the transfer device **10** is not situated in a position of the processing device **40**, the movement instructor **103** of the control system **100** instructs the transfer device **10** to move to the position of the processing device **40**. The position of the processing device **40** includes a position in the vicinity of the processing device **40** and is, for example, in front of the processing device **40**. In step **S103**, the transfer device **10** receives the object **30** from the processing device **40**. The transfer device **10** transmits, to the control system **100**, a receipt signal indicating that the object **30** has been received. The receipt signal obtainer **101** of the control system **100** receives the receipt signal.

(46) In step **S104**, the device selector **102** of the control system **100** transmits, to each of the plurality of heating devices **20A**, **20B**, **20C** . . . , a status check signal for checking whether its status is running or available. Each of the plurality of heating devices **20A**, **20B**, **20C** . . . receives the status check signal. Each of the plurality of heating devices **20A**, **20B**, **20C** . . . transmits, to the device selector **102** of the control system **100**, a status notification signal for notifying that its status is running or available. The device selector **102** of the control system **100** receives the status notification signal.

(47) In step **S105**, the device selector **102** of the control system **100** selects, from among the plurality of heating devices **20A**, **20B**, **20C** . . . , an available heating device as a selected heating device. In a case where there are a plurality of available heating devices, the device selector **102** of the control system **100** may select an available heating device to which a movement distance of the

transfer device **10** becomes the shortest as the selected heating device. Herein, an example will be described where the device selector **102** of the control system **100** selects the heating device **20A** as the selected heating device.

(48) In step **S106**, the movement instructor **103** of the control system **100** transmits, to the transfer device **10**, a movement instruction signal for instructing the transfer device **10** to move to a position of the selected heating device. The transfer device **10** receives the movement instruction signal. The transfer device **10** moves to the position of the heating device **20A** serving as the selected heating device. The position of the heating device **20A** includes a position in the vicinity of the heating device **20A** and is, for example, in front of the heating device **20A**. The transfer device **10** transmits, to the control system **100**, a standby signal indicating that transfer device **10** stands by in the position of the selected heating device. The standby signal obtainer **104** of the control system **100** receives the standby signal. In step **S107**, the loading instructor **105** of the control system **100** transmits, to the selected heating device, a door open instruction signal for instructing the selected heating device to open the door **21A**. The selected heating device receives the door open instruction signal and opens the door **21A**.

(49) In step **S108**, the loading instructor **105** of the control system **100** transmits, to the transfer device **10**, a loading instruction signal for instructing the transfer device **10** to load the object **30** into the selected heating device the door **21A** of which has been opened. The transfer device **10** receives the loading instruction signal and loads the object **30** into the selected heating device. The transfer device **10** transmits, to the control system **100**, a loading signal indicating that the object **30** has been loaded into the selected heating device. The loading signal obtainer **106** of the control system **100** receives the loading signal.

(50) While the processing device **40** processes a plurality of objects **30**, a loop from steps **S101** to **S108** may be repeated, and the plurality of objects **30** may be sequentially loaded into available heating devices. The loop from steps **S101** to **S108** may be implemented in parallel with step **S109** to step **S113** which will be described below. Therefore, after step **S108** is implemented, the flow may proceed to step **S109** in parallel with the repetition of the loop from steps **S101** to **S108**.

(51) In step **S109**, the heating instructor **107** of the control system **100** transmits, to the selected heating device, a heating instruction signal for instructing the selected heating device to close the door **21A** and heat the object **30**. The selected heating device receives the heating instruction signal. The heating instructor **107** may transmit a heating condition based on a composition of the object **30** to the selected heating device. The heating condition is set, for example, based on the material of the object **30**. The heating condition is set, for example, based on a melting point and a sintering temperature of the material of the object **30**. The heating condition is set, for example, based on an amount of impurity contained in the object **30**. The heating condition may include an atmosphere condition in the chamber of the selected heating device. The selected heating device closes the door **21A**. In step **S110**, the selected heating device heats the object **30** therein. In a case where the heating condition has been received, the selected heating device heats the object **30** according to the heating condition. In a case where the heating condition includes an atmosphere condition, the atmosphere control device **56** of the selected heating device controls an atmosphere in the chamber of the selected heating device according to the atmosphere condition.

(52) In step **S111**, in a case where the fire sensor **52A** of the selected heating device has not detected a fire, a flame, or a spark caused by abnormal heating of the object **30**, the flow proceeds to step **S112**. In step **S111**, in a case where the fire sensor **52A** of the selected heating device has detected a fire, a flame, or a spark caused by abnormal heating of the object **30**, in step **S201**, it is determined whether or not the number of times to have detected the fire, the flame, or the spark is greater than or equal to a predetermined number of times. In a case where the number of times to have detected the fire, the flame, or the spark is greater than or equal to the predetermined number of times, the selected heating device stops the heating of the object **30**. In a case where the number of times to have detected the fire, the flame, or the spark is not greater than or equal to the

predetermined number of times, in step **S202**, the selected heating device pauses the heating of the object **30**. Thereafter, the flow returns to step **S110**.

(53) In step **S112**, in a case where an impurity adheres to the object **30** or the object **30** contains an impurity, the impurity evaporates from the object **30** due to heating to generate an aerosol. In a case where the aerosol sensor **51A** of the selected heating device detects an aerosol, and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the flow proceeds to step **S113**. In a case where the aerosol sensor **51A** of the selected heating device has not detected an aerosol even once or keeps detecting the aerosol, the flow returns to step **S110**, and the selected heating device continues the heating of the object **30**. In step **S113**, the selected heating device stops the heating and solidification of the object **30**. The selected heating device transmits, to the control system **100**, a heating completion signal indicating that the heating of the object **30** has been completed. The heating completion signal obtainer **108** of the control system **100** receives the heating completion signal.

(54) In step **S114**, the unloading instructor **109** of the control system **100** transmits the door open instruction signal to the selected heating device to instruct the selected heating device to open the door **21A**. The selected heating device receives the door open instruction signal and opens the door **21A**. In step **S115**, the unloading instructor **109** of the control system **100** transmits, to the transfer device **10**, an unloading instruction signal to instruct the transfer device **10** to unload the object **30** from the selected heating device. The transfer device **10** receives the unloading instruction signal and unloads the object **30** from the selected heating device the door **21A** of which has been opened. It is noted that in a case where the transfer device **10** is not situated in the position of the selected heating device, the movement instructor **103** of the control system **100** instructs the transfer device **10** to move to the position of the selected heating device. In addition, in a case where the transfer device **10** implements the loop from steps **S101** to **S108**, after the loop from steps **S101** to **S108** has been implemented once, the transfer device **10** may pause the loop from steps **S101** to **S108** to implement step **S115**.

(55) In step **S116**, the unloading instructor **109** of the control system **100** transmits, to the selected heating device, a door close instruction signal for instructing the selected heating device to close the door **21A**. The selected heating device receives the door close instruction signal and closes the door **21A**. In step **S117**, the container status checker **112** of the control system **100** transmits, to the container **60**, a container status check signal for checking whether there is a space for accommodating the object **30**. The container **60** receives the container status check signal. In a case where there is a space for accommodating the object **30**, the container **60** transmits, to the control system **100**, a container status notification signal indicating that there is a space for accommodating the object **30**. The container status checker **112** of the control system **100** receives the container status notification signal.

(56) In step **S118**, the movement instructor **103** of the control system **100** instructs the transfer device **10** to move the object **30** unloaded from the selected heating device into the container **60**. The transfer device **10** moves to a position of the container **60**. The position of the container **60** includes a position in the vicinity of the container **60** and is, for example, in front of the container **60**. The transfer device **10** puts the object **30** into the container **60**.

(57) A data collection system **200** according to the embodiment illustrated in FIG. **12** includes a pre-heating object data collector **201** configured to collect data of the object **30** before being heated by the heating devices **20A**, **20B**, **20C** The data of the object **30** before being heated is, for example, a weight, a shape, a temperature, a strength, an ingredient of a raw material, a particle size of the raw material, an ingredient mixed in the raw material, a source of the raw material, and a date of receipt of the raw material of the object **30** before being heated.

(58) The weight of the object **30** before being heated is measured, for example, by a mass meter provided in the processing device **40**, the transfer device **10**, or the heating devices **20A**, **20B**, **20C** . . . or provided in the vicinity of these devices and is transmitted to the pre-heating object data

collector **201**. Examples of the mass meter include a load cell.

(59) The shape of the object **30** before being heated is measured by a shape measurement machine provided in the processing device **40**, the transfer device **10**, or the heating devices **20A**, **20B**, **20C** . . . or provided in the vicinity of these devices and is transmitted to the pre-heating object data collector **201**. Examples of the shape include a height, a width, and a surface roughness. Examples of the shape measurement machine include a laser sensor and a camera.

(60) The temperature of the object **30** before being heated is measured by a thermometer provided in the processing device **40**, the transfer device **10**, or the heating devices **20A**, **20B**, **20C** . . . or provided in the vicinity of these devices and is transmitted to the pre-heating object data collector **201**. Examples of the thermometer include a radiation thermometer and a thermocouple.

(61) The strength of the object **30** before being heated is measured by a strength measurement machine provided in the processing device **40**, the transfer device **10**, or the heating devices **20A**, **20B**, **20C** . . . or provided in the vicinity of these devices and is transmitted to the pre-heating object data collector **201**. Examples of the strength measurement machine include a torque sensor. For example, in a mechanism in which the object **30** is gripped, in a case where a ball screw is driven by a motor to clamp the object **30** between parts for gripping the object **30**, a rotational torque of the motor may be detected.

(62) The data collection system **200** according to the embodiment includes a heating data collector **202** configured to collect heating data in the heating devices **20A**, **20B**, **20C** The heating data is, for example, an arrangement of the object **30** in the heating devices **20A**, **20B**, **20C** . . . , a change over time of a temperature of the object **30**, a change over time of a temperature of the door, a heating time period, a strength of electromagnetic waves, a change over time of an atmospheric gas component, a change over time of an atmospheric gas concentration, a change over time of an exhaust gas component, a change over time of an exhaust gas concentration, a change over time of a temperature of an exhaust gas, a change over time of an aerosol concentration, the presence or absence of fire, and a firing time period.

(63) The arrangement of the object **30** in the heating devices **20A**, **20B**, **20C** . . . is measured, for example, by a position sensor provided in the heating devices **20A**, **20B**, **20C** . . . and is transmitted to the heating data collector **202**. Examples of the position sensor include a laser sensor.

(64) The change over time of the temperature of the object **30** in the heating devices **20A**, **20B**, **20C** . . . , the change over time of the temperature of the door, and the change over time of the temperature of the exhaust gas are measured, for example, by a thermometer provided in the heating devices **20A**, **20B**, **20C** . . . and are transmitted to the heating data collector **202**. Examples of the thermometer include a radiation thermometer and a thermocouple.

(65) The heating time period in the heating devices **20A**, **20B**, **20C** . . . is measured, for example, by an electromagnetic wave irradiation device provided in the heating devices **20A**, **20B**, **20C** . . . and is transmitted to the heating data collector **202**. The strength of electromagnetic waves in the heating devices **20A**, **20B**, **20C** . . . is measured, for example, by an electromagnetic wave detector provided in the heating devices **20A**, **20B**, **20C** . . . and is transmitted to the heating data collector **202**.

(66) The change over time of the atmospheric gas component, the change over time of the atmospheric gas concentration, the change over time of the exhaust gas component, and the change over time of the exhaust gas concentration in the heating devices **20A**, **20B**, **20C** . . . are measured, for example, by a gas sensor provided in the heating devices **20A**, **20B**, **20C** . . . and are transmitted to the heating data collector **202**.

(67) The change over time of the aerosol concentration in the heating devices **20A**, **20B**, **20C** . . . is measured, for example, by an aerosol sensor provided in the heating devices **20A**, **20B**, **20C** . . . and is transmitted to the heating data collector **202**.

(68) The presence or absence of fire and the firing time period in the heating devices **20A**, **20B**, **20C** . . . are measured, for example, by a fire sensor provided in the heating devices **20A**, **20B**, **20C**

... and are transmitted to the heating data collector **202**.

(69) The data collection system **200** according to the embodiment includes a post-heating object data collector **203** configured to collect data of the object **30** after being heated by the heating devices **20A**, **20B**, **20C** The data of the object **30** after being heated is, for example, a weight, a shape, a temperature, a strength, and a processing lot number of the object **30** after being heated. A processing lot is, for example, a set of a plurality of objects **30** heated during a certain period of time. Alternatively, the processing lot may be a set of a certain number of objects **30**.

(70) The weight of the object **30** after being heated is measured, for example, by a mass meter provided in the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , or the container **60** or provided in the vicinity of these devices and is transmitted to the post-heating object data collector **203**. Examples of the mass meter include a load cell.

(71) The shape of the object **30** after being heated is measured by a shape measurement machine provided in the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , or the container **60** or provided in the vicinity of these devices and is transmitted to the post-heating object data collector **203**. Examples of the shape include a height, a width, and a surface roughness. Examples of the shape measurement machine include a laser sensor and a camera.

(72) The temperature of the object **30** after being heated is measured by a thermometer provided in the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , or the container **60** or provided in the vicinity of these devices and is transmitted to the post-heating object data collector **203**. Examples of the thermometer include a radiation thermometer and a thermocouple.

(73) The strength of the object **30** after being heated is measured by a strength measurement machine provided in the transfer device **10**, the heating devices **20A**, **20B**, **20C** . . . , or the container **60** or provided in the vicinity of these devices and is transmitted to the post-heating object data collector **203**. Examples of the strength measurement machine include a torque sensor.

(74) The data collection system **200** according to the embodiment includes an associator **204** configured to associate an identifier of the object **30** heated by the heating devices **20A**, **20B**, **20C** . . . with data collected by at least any of the pre-heating object data collector **201**, the heating data collector **202**, and the post-heating object data collector **203**. By associating the identifier of the object **30** with these pieces of data, a quality of the object **30** can be guaranteed, or in a case where a defect occurs in the object **30**, it is possible to use the data to find out a cause of the defect.

(75) As above, the present invention has been described by way of the embodiment, but the description and drawings forming part of this disclosure is not to be understood as limiting the present invention. For example, in step **S112** in the method of controlling the transfer device **10** and the plurality of heating devices **20A**, **20B**, **20C** . . . according to the embodiment, the operation method of the transfer device **10** and the plurality of heating devices **20A**, **20B**, **20C** . . . , and the method of producing the solid which have been described with reference to the flowcharts in FIG. **10** and FIG. **11**, instead of detection of the aerosol, or in addition to detection of the aerosol, in a case where the temperature sensors **53A**, **54A**, and **55A** detect the temperature of the object **30** and the object **30** has reached a predetermined temperature or a case where it is detected that the object **30** has reached a predetermined temperature and a predetermined period of time has elapsed, the flow may proceed to step **S113**, and in a case where the object **30** has not reached the predetermined temperature, the flow may return to step **S110**. From this disclosure, various alternative embodiments, embodiments, and operational techniques are to become apparent to those skilled in the art. It is to be understood that the present invention encompasses various embodiments and the like that are not described herein.

REFERENCE LIST

(76) **10** . . . transfer device, **11** . . . grip device, **12** . . . movement device, **20A**, **20B**, **20C** . . . heating device, **21A**, **21B**, **21C** . . . door, **22A** . . . chamber, **23A** . . . stage, **24A** . . . drive device, **25A**, **26A** . . . promotor, **27A** . . . shaft, **30** . . . object, **40** . . . processing device, **50A** . . . electromagnetic wave irradiation device, **51A** . . . aerosol sensor, **52A** . . . fire sensor, **53A**, **54A**, **55A** . . . temperature

sensor, **60** . . . container, **61A** . . . window, **100** . . . control system, **101** . . . receipt signal obtainer, **102** . . . device selector, **103** . . . movement instructor, **104** . . . standby signal obtainer, **105** . . . loading instructor, **106** . . . loading signal obtainer, **107** . . . heating instructor, **108** . . . heating completion signal obtainer, **109** . . . unloading instructor, **110** . . . processing completion signal obtainer, **111** . . . reception instructor, **112** . . . container status checker, **200** . . . data collection system, **201** . . . pre-heating object data collector, **202** . . . heating data collector, **203** . . . post-heating object data collector, **204** . . . associator

Claims

1. A control system configured to control a transfer device and a plurality of heating devices, the control system comprising: a receipt signal obtainer configured to obtain a receipt signal indicating that the transfer device has received an object; a device selector configured to select an available heating device as a selected heating device from among the plurality of heating devices in a case where the receipt signal obtainer has received the receipt signal; a movement instructor configured to instruct the transfer device to move to a position of the selected heating device; a standby signal obtainer configured to obtain a standby signal indicating that the transfer device stands by in the position of the selected heating device; a loading instructor configured to instruct, in a case where the standby signal obtainer has obtained the standby signal, the selected heating device to open a door and instruct the transfer device to load the object into the selected heating device; a loading signal obtainer configured to obtain a loading signal indicating that the transfer device has loaded the object into the selected heating device; a heating instructor configured to instruct, in a case where the loading signal obtainer has obtained the loading signal, the selected heating device to close the door and heat the object; a heating completion signal obtainer configured to obtain a heating completion signal indicating that heating of the object has been completed in the selected heating device; and an unloading instructor configured to instruct, in a case where the heating completion signal obtainer has obtained the heating completion signal, the selected heating device to open the door and instruct the transfer device to unload the object from the selected heating device, wherein each of the plurality of heating devices includes an aerosol sensor, and in a case where the aerosol sensor detects an aerosol and thereafter, the aerosol has no longer been detected or the aerosol has become less than or equal to a predetermined amount, the heating completion signal is issued, wherein the aerosol is smoke or vapor, wherein the object contains oil or water, wherein the object further contains a metal or a metal compound, and wherein each of the plurality of heating devices includes an irradiation device configured to emit electromagnetic waves therein.
2. The control system according to claim 1, wherein the transfer device receives the object from a processing device.
3. The control system according to claim 2, wherein the processing device is a molding machine.
4. The control system according to claim 3, wherein the molding machine is a briquette machine.
5. The control system according to claim 2, further comprising: a processing completion signal obtainer configured to obtain a processing completion signal indicating that processing of the object in the processing device has been completed; and a reception instructor configured to instruct, in a case where the processing completion signal obtainer has obtained the processing completion signal, the transfer device to receive the object from the processing device.
6. The control system according to claim 5, wherein in a case where the processing completion signal obtainer has obtained the processing completion signal, the movement instructor instructs the transfer device to move to a position of the processing device.
7. The control system according to claim 2, wherein in a case where the loading signal obtainer has obtained the loading signal, the movement instructor instructs the transfer device to move to a position of the processing device.
8. The control system according to claim 1, wherein in a case where the heating completion signal

obtainer has obtained the heating completion signal, the movement instructor instructs the transfer device to move to the position of the selected heating device.

9. The control system according to claim 1, further comprising: a container status checker configured to obtain a container status signal indicating that a container has a space to accommodate the object, wherein in a case where the container status checker has obtained the container status signal, the movement instructor instructs the transfer device to move the object unloaded from the selected heating device into the container.

10. The control system according to claim 1, wherein the heating instructor transmits a heating condition based on a composition of the object to the selected heating device.
