

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12411885
B1
September 09, 2025
Park; Juliana et al.

Optimizing storage of images at an electronic device by monitoring available storage and providing for multiple image-management modes, and systems and methods of use thereof

Abstract

A method for optimizing storage of images at a wearable device includes obtaining information about an amount of storage remaining at the wearable device. Upon determining the amount of storage at the wearable device is less than a first of multiple storage-depletion thresholds, the method provides the user an indication that a first image-management mode is available. In the first image-management mode, the method deletes images that are not of a predetermined image type. Then, upon a determination that the amount of storage at the wearable device is less than or equal to a second of multiple storage-depletion thresholds, the method automatically causes the wearable device to operate in a second image-management mode. While in the second image-management mode, the method blocks a user from storing additional images until the method determines that the amount of storage remaining at the wearable device is above the second storage-depletion threshold.

Inventors: Park; Juliana (Emerald Hills, CA), Shen; Mengnan (Redwood City, CA), Shrestha; Sarjan (Hayward, CA), Xu; Liang (Mountain View, CA), Carney; Matthew Adam (Lincoln, CA), Aghdaee; Hamid (Berkeley, CA), Kundu; Sanjiban (Malden, MA)

Applicant: Meta Platforms Technologies, LLC (Menlo Park, CA)

Family ID: 96950432

Assignee: Meta Platforms Technologies, LLC (Menlo Park, CA)

Appl. No.: 18/190855

Filed: March 27, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06F16/51** (20190101); **G06F3/01** (20060101); **G06F3/04842** (20220101); **G06F11/14** (20060101); **G06T11/00** (20060101)

U.S. Cl.:

CPC **G06F16/51** (20190101); **G06F3/011** (20130101); **G06F3/04842** (20130101); **G06F11/1458** (20130101); **G06T11/00** (20130101); G06F2201/84 (20130101)

Field of Classification Search

CPC: G06F (16/51); G06F (3/011); G06F (3/04842); G06F (11/1458); G06F (2201/84); G06T (11/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7933936	12/2010	Aggarwal	707/812	G06F 16/128
9747057	12/2016	Ramani	N/A	G06F 3/067
10545653	12/2019	Dye	N/A	H04N 21/2385
2014/0226909	12/2013	Montalvo	382/224	G11B 27/105
2016/0283366	12/2015	Nguyen Tien	N/A	G06F 12/0246
2017/0046340	12/2016	Bhide	N/A	G06F 16/583
2017/0357465	12/2016	Dzeryn	N/A	G06F 3/0647
2018/0196587	12/2017	Bialynicka-Birula	N/A	G06V 20/41
2018/0364557	12/2017	Park	N/A	H04N 23/651
2021/0142438	12/2020	Appu	N/A	G06F 9/3818
2022/0309700	12/2021	Ito	N/A	H04N 23/45

OTHER PUBLICATIONS

Android Enthusiasts (<https://android.stackexchange.com/questions/84254/i-cannot-take-pictures-because-my-phone-says-your-internal-storage-is-running-o>; Oct. 7, 2014.) (Year: 2014). cited by examiner

Primary Examiner: Chen; Yu

Attorney, Agent or Firm: Morgan, Lewis & Bockius LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Prov. App. No. 63/356,465, filed on Jun. 28, 2022, and entitled “Optimizing Storage of Images at an Electronic Device by Monitoring Available Storage and Providing for Multiple

Image-Management Modes, and Systems and Methods of Use Thereof,” which is incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates generally to memory management for electronic devices, including but not limited to, optimizing storage of images captured or otherwise received by wearable devices (e.g., wearable devices such as smartwatches) by monitoring whether an amount of storage at a respective wearable device has been depleted beyond storage-depletion thresholds, which correspond to respective amounts of available storage at the wearable device, and then suggesting and then mandating (as different storage-depletion thresholds are satisfied) that the wearable device operate in specific image-management modes.

BACKGROUND

(2) Many electronic devices are designed for a particular subset of general computing functionality and/or use cases. Smaller, specialized computing devices, especially devices intended to be worn by users (e.g., which can be referred to as wearable devices), are generally more resource-constrained than standalone computers or laptops, because there is not as much space to house computing components, such as processors and memory, without causing the device to be overly obtrusive or cumbersome to wear for daily activities, thereby limiting the user's enjoyment of the electronic device's capabilities, including portability.

(3) As one example, images captured and/or received by an electronic device can require a large amount of memory (as compared to other stored data such as textual messages and other data that occupies a lesser amount of storage), since such images generally comprise a multitude of individual pixels with information about the pixels and the overall image (e.g., coded data related to the color and/or additional features of each pixel), as well as additional information about the images including image properties, such as available file formats, file descriptions, etc. As such, there is a need for electronic devices, including wearable devices, that can proactively manage memory issues, particularly for smaller, wearable devices that may have constrained resources and especially for certain types of stored data, such as data about digital images.

SUMMARY

(4) To avoid one or more of the drawbacks or challenges discussed above, the electronic devices (e.g., wearable devices) disclosed herein provide users with efficient and intuitive functionality for proactively managing storage (e.g., proactive in the sense that memory issues are identified and surfaced to the user before those issues become more pronounced and then action is taken to avoid negative impacts to functioning of the device before those issues would occur) to avoid running out of memory, and/or causing the electronic devices to operate less effectively as a result of having too little free memory. More specifically, the electronic devices, including wearable devices, provide users with indications that they are crossing various depletion thresholds associated with amounts of available storage. In addition to the indications, the electronic devices can also provide selectable options to users for managing storage to free up or otherwise make available more storage at the respective electronic devices or others. Further, the electronic devices can also perform automatic functions, without intervention from respective users, which cause the devices to free up more space by automatically deleting images that are not of a pre-determined image type (e.g., images that have not been selected as favorites, or otherwise delineated as a predetermined protected image type by the user). These techniques allow for electronic devices, including wearable devices, to be designed such that they are functional, practical, and convenient for day-to-day use, while also allowing users to capture images without worrying that they will unknowingly use too much of the available storage, resulting in at least one of the deleterious consequences described above. While the primary example described herein relates to implementing these techniques at a wearable device (e.g., a smart watch), other wearable and non-wearable devices with cameras can also benefit from these techniques, such as head-wearable devices (smart glasses

or VR goggles), smart anklets with cameras, smart ring devices (finger or toe rings), and other wearable devices that can include a camera but have more limited storage and computing resources.

(5) In certain embodiments, the storage-management techniques described herein can be performed by a single electronic device (e.g., a wearable device), or can be performed by the single electronic device in conjunction with other electronic devices (e.g., smart phones, head-wearable devices, portable computing units, etc.) in communication with respective wearable devices. As such, users are able to receive and respond to indications related to storage depletion, including available image storage, at their wearable devices while interacting with other respective electronic devices that have more screen space (or currently-utilized screen space if the user is viewing a display through a head-wearable device and is determined, e.g., via gaze tracking or positioning of the wearable device, to not currently be viewing the display of the wearable device), computing power, and/or storage management applications. In other words, systems employing the techniques discussed herein can include multiple devices operating in tandem to manage resources associated with a group of multiple devices (which can each be associated with, and even worn at one time by one user), and can likewise provide user interfaces (e.g., user interfaces with user-interface elements and selectable affordances (e.g., buttons)) at multiple electronic devices, for the user to control image-management modes at one or more of the multiple electronic devices.

(6) To further some of the ends briefly summarized above, in accordance with some embodiments, a method is performed at a wearable device. The wearable device has one or more processors and memory storing instructions for execution by the one or more processors. The method includes determining a first amount of storage at the wearable device. The method also includes, in accordance with a first determination that the first amount of storage is less than or equal to a first storage-depletion threshold, providing an indication, at the wearable device, that a first image-management mode is available, wherein when the wearable device is operating in the first image-management mode, the wearable device is caused to delete one or more images that are not of a predetermined protected image type. The method also includes, in accordance with a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first storage-depletion threshold, automatically, and without a request from a user of the wearable device, operating the wearable device in a second image-management mode, wherein when the wearable device is operating in the second image-management mode, the wearable device is configured to block the user from storing any additional images at the wearable device until a repletion determination is made that a respective amount of storage remaining at the wearable device is greater than or equal to the second storage-depletion threshold. Other embodiments include corresponding wearable devices, capsules of wearable devices, and computing systems that include wearable devices and other connected devices, each configured to perform one or more of the operations described herein. One example of this is shown in FIGS. 1A-1K, in which a computing system includes a wearable device and a smart phone device, and the computing system is caused to present indications that a first image-management mode is available at the wearable device as the amount of available storage at the wearable device becomes less than each of a plurality of storage-depletion thresholds and also causes the wearable device to prevent storage of new images when the amount of available storage at the wearable device is less than a critical storage-depletion threshold.

(7) Note that the various embodiments described above can be combined with one or more of the other embodiments described herein. The features and advantages described in the specification are not necessarily all-inclusive and, in particular, many additional features and advantages will be apparent to one of ordinary skill in the art in view of the drawings, the specification, and the claims. Moreover, it should be noted that the language used in the specification has been selected

for readability and instructional purposes and may not necessarily have been selected to delineate or circumscribe the inventive subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) So that the present disclosure can be understood in greater detail, a more particular description may be had by reference to the features of various embodiments, some of which are illustrated in the appended drawings. The appended drawings, however, merely illustrate pertinent features of the present disclosure and are therefore not to be considered limiting, for the description may admit to other effective features as the person of skill in this art will appreciate upon reading this disclosure.

(2) FIGS. 1A-1K depict user interactions with a wearable device that are performed in conjunction with a method for storage management at the wearable device as storage is being depleted, and then made available, at the wearable device, in accordance with some embodiments.

(3) FIGS. 2A-2B depict a flow diagram of a method for storage management is at the wearable device as storage is being depleted and/or made available at the wearable device, in accordance with some embodiments.

(4) FIG. 3 is a block diagram illustrating a computing system (e.g., a wearable device with capsule, cradle, and band components that are shown at the bottom of FIG. 3) in accordance with some embodiments.

(5) FIGS. 4A-4B illustrate an example of additional views of the wearable device of FIG. 3, in accordance with some embodiments.

(6) FIG. 5 is a detailed flow diagram illustrating a method for storage management performed by a computing system with at least one electronic device, in accordance with some embodiments.

(7) In accordance with common practice, the various features illustrated in the drawings are not drawn to scale. Accordingly, the dimensions of the various features may be arbitrarily expanded or reduced for clarity. In addition, some of the drawings may not depict all of the components of a given system, method, or device. Finally, like reference numerals are used to denote like features throughout the specification and figures.

DETAILED DESCRIPTION

(8) Having thus briefly described the drawings, what follows next is a detailed description of each of the figures/drawings.

(9) For ease of reference, attention will first be directed to an example sequence of events performed at a computing system that includes a wearable device and a smart phone. Example components and their detailed specifications will be referred to throughout the description of the example sequence, and the structures and functionality of the example electronic devices will be described in more detail in later parts of the specification and/or will otherwise be made apparent by the methods, systems, and devices described herein.

(10) Example Sequences and Methods of Operation

(11) FIGS. 1A-1K illustrate an example of a sequence of events performed in conjunction with computing system **100**, which includes an example of the wearable device **102**. While the example sequence of events is occurring, processors executing instructions stored in memory **105** (e.g., memory **1400** in FIG. 3) cause operations to be performed at the wearable device **102**, including techniques for optimizing storage at the wearable device **102**.

(12) In some embodiments, the wearable device **102** includes a removable capsule device (e.g., the watch body **104**, which can be referred to as a display capsule, which can be removably coupled with a cradle portion (e.g., the cradle portion **1002C** in FIG. 3) to a wearable structure that can include the cradle portion and a watch band **106**, thereby forming a wearable device) and the watch

band **106**, that is used for attaching the watch body **104** to a wrist of a user **101**. In some embodiments, the wearable device **102** includes one or more components (e.g., hardware, software, and firmware components) described below with reference to FIG. 3, such as a display **1212** that presents interactable user interfaces, one or more image sensors (e.g., an imaging sensor **1104**, an EMG sensor **1108**, etc.), and one or more cameras (e.g., the front camera **108A**, and the rear camera **108B**). In some embodiments, one or more components can be disposed within the capsule device (e.g., the watch body **104** and/or the watch band **106**). As discussed in more detail with respect to FIG. 4, the components of the wearable device can all be coupled with (or entirely or partially contained within) the watch body **104**, the watch band **106** (which can be coupled with a cradle portion **1002C**, as was mentioned above), or they can be integrated via a split architecture that includes some components on the watch body **104**, some on the cradle portion **1002C**, and some components on the watch band **106**.

(13) Turning now to the example scenario shown in FIG. 1A, the user **101** is wearing the wearable device **102**. There is a home-screen user interface **112** displayed at the display **110** of the wearable device **102**. The home-screen user interface **112** can be used to access various applications (e.g., one or more of the applications **1430** in FIG. 3). The wearable device **102**, as depicted in the example of FIG. 1A, is being viewed from the wrist of the user **101** and is attached to wrist of the user **101** by the watch band **106**.

(14) Additionally, FIG. 1A illustrates a visual depiction of a portion of the memory **105** of the wearable device **102**. Specifically, the memory **105** contains an amount of available storage **120** at the wearable device **102**. The amount of available storage **120** may be an allocated portion (e.g., allocated to storage of a particular type of data, such as digital images) of the total amount of available storage (e.g., the available image storage **1418** in FIG. 4A) at the wearable device **102**. The visual depiction of the memory **105** further shows the amount of used storage **122** with respect to the amount of available storage **120** at the wearable device **102**. It also includes symbolic threshold lines indicating thresholds within the amount of available storage **120** used up by used storage **122** (e.g., depleted from the available storage **120**) with respect to a plurality of depletion thresholds (the first storage-depletion threshold **124**, the second storage-depletion threshold **126**, the third storage-depletion threshold **128**, and the critical storage-depletion threshold **130**). As will be discussed in detail below, when a determination (e.g., an initial determination upon startup of the wearable device or one made based on a time-based (e.g., every 10 seconds to 1 minute) or event-based (e.g., each time a new image is added to the available storage) determination cycle) is made that a remaining amount of available storage **120** at the wearable device **102** that is not used storage **122** is below the first storage-depletion threshold **124**, the wearable device **102** operates in a default image-management mode. That is, if used storage **122** crosses (e.g., is greater than) any of the schematically shown storage-depletion thresholds (e.g., the first storage-depletion threshold **124**) shown in the upper right corner of FIG. 1A, then that would result in some form of action to alert the user to take some action and alter a current image-management mode and/or to force the device to switch to a different image-management mode, in accordance with some embodiments. In some embodiments, there is no auto-deletion performed at the wearable device **102** by default when the wearable device **102** is in the default image-management mode. In some embodiments, the user **101** can configure settings of the wearable device **102** to cause auto-deletion to be performed to certain images while the wearable device **102** is operating in the default image-management mode. In some embodiments, auto-deletion can only occur at the wearable device **102** when the wearable device **102** is in a charging state. In some embodiments, certain images are subject to auto-deletion regardless of the image-management mode that the wearable device **102** is operating in. For example, the wearable device may have a trash logical directory (e.g., in a filesystem structure of the wearable device) where the user **101** can specify that media files, including images, are trash, and images in the trash directory can be subject to auto-deletion even when the wearable device **102** is not operating in an image-management mode.

(15) In some embodiments, images are not backed up at the wearable device **102**, or another electronic device (e.g., the smart phone **103**), while the wearable device **102** operates in the default image-management mode. In some embodiments, images are backed up at another electronic device (e.g., the smart phone **103**). In some embodiments, the wearable device **102** backs up all images captured at the wearable device **102** to another electronic device (e.g., the smart phone **103**) when the wearable device **102** is being charged (e.g., in a charging state), regardless of determinations concerning the available storage **120** and/or the image-management mode that the wearable device **102** is operating in. In some embodiments, images stored at the wearable device **102** are down-sampled after they are backed up to another electronic device (e.g., the smart phone **103**). In some embodiments, the images stored at the wearable device **102** are down-sampled on a regular schedule (e.g., at night). In some embodiments, the time when the images stored at the wearable device **102** are down-sampled depends on the usage data associated with the wearable device **102** (e.g., down-sampling can occur on a schedule that is determined based on how often a user uses the wearable device at various points in time, such that lighter usage time periods can be selected as the time periods when down-sampling should occur).

(16) In some embodiments, the determination about the amount of available storage **120** remaining (e.g., an amount of available storage other than the used storage **122**) is made by the wearable device **102**. In some embodiments, the determination is made, at least in part, by another electronic device (e.g., the smart phone **103**).

(17) Turning now to FIG. **1B**, the user **101** is capturing a new image **125** (e.g., a selfie that includes the user **101** taking a picture of their own face) using one of the cameras (e.g., front camera **108A**) of the wearable device **102**. The new image **125** of the user **101** is displayed at the display **110** of the wearable device **102** in conjunction with the user **101** confirming that the new image **125** should be captured with the front camera **108A**. Confirmation of the capture of the new image **125** can be received based on the user **101** performing a tap gesture **123** on a peripheral button **116** disposed on the watch body **104** of the wearable device **102**. In some embodiments, when the user **101** captures the new image **125**, the used storage **122** changes as a result of adding the new image **125** to the used storage **122**, thereby also reducing the remaining amount of available storage **120**. In some embodiments, such a deletion event can trigger a new determination as to an amount of remaining available storage to see if any of the storage-depletion thresholds have been crossed or satisfied. In some embodiments, if the wearable device **102** is operating in an image-management mode besides the default image-management mode, the new image **125** is saved to another electronic device, such as the smart phone **103**. In some embodiments, when the user **101** captures the new image **125**, the user **101** can also provide another user input to specify that the new image **125** has a predetermined protected image type, which can prevent the new image **125** from being deleted if the wearable device **102** is operating in one of the image-management modes besides the default image-management mode, and/or if the user **101** actively performs operations that cause auto-deletion to be performed. After the tap gesture **123**, the display **110** can optionally then display respective selectable affordances (a “cancel” affordance **126**, and a “confirm” affordance **128**) for allowing the user **101** to confirm that the capture of the new image **125** should proceed.

(18) Turning now to FIG. **1C**, the wearable device **102** is shown during a state in which it has determined that the remaining amount of available storage **120** is less than the first storage-depletion threshold **124** (e.g., based on the increased amount of used storage **122** caused by the user **101** capturing images like the new image **125** in FIG. **1B**). In some embodiments, the first storage-depletion threshold **124** corresponds to the amount of available storage **120** at the wearable device **102** being less than or equal to 515 megabytes (this first storage-depletion threshold can also be defined on a percentage basis, e.g., as a value that is 10% of the allocated storage for images). In some embodiments, the first storage-depletion threshold **124** is based, at least in part, on the average size of an image captured by the user **101** (e.g., five, ten, or fifteen megabytes). In accordance with determining that the remaining amount of available storage **120** is below the first

storage-depletion threshold **124**, the wearable device **102** is caused to provide an indication that a first image-management mode is available. Specifically, in FIG. **1C**, a storage-alert user interface **131** displayed at the display of the wearable device **102**, includes a plurality of affordances (also referred to as user interface elements), including an affordance **134** indicating that the user **101** can turn on auto-delete to ensure space for images is made available at the wearable device **102** (e.g., causing the wearable device **102** to operate in the first image-management mode). The storage-alert user interface **131** also includes an affordance **132** providing an explanation to the user **101** as to why the user interface is being displayed, e.g., in the depicted example of FIG. **1C**, the affordance **132** indicates that the wearable device **102** has a low amount of available storage **120** (e.g., a textual element that states: “Low Storage”). The storage-alert user interface **131** also includes the affordance **134** described above, indicating that the first image-management mode is available (e.g., a textual element that states: “Turn on auto delete to ensure space for photos”). The storage-alert user interface **131** also includes a selectable affordance **136**, which, when selected, displays additional information about the first image-management mode and/or other image-management techniques. The storage-alert user interface **131** also includes a selectable affordance **138** that, when selected, can cause the display **110** of the wearable device **102** to display additional information about image-management options at the wearable device **102**.

(19) In some embodiments, the determination that the available storage **120** is less than the first storage-depletion threshold **124** is performed at (and/or the results of the determination are communicated to) another electronic device (e.g., the smart phone **103**). In some embodiments, when the determination is made that the available storage **120** is less than the first storage-depletion threshold **124**, an additional indication is displayed at another electronic device (e.g., the smart phone **103**) that is in communication with the wearable device **102**. In some embodiments, the additional indication (e.g., a storage-alert user interface **133**, denoted by a dashed box on the display of the smart phone **103**) displayed at the smart phone **103** includes additional information (e.g., an affordance **135**) notifying the user **101** that the first image-management mode is available at the wearable device **102**. As shown in FIG. **1C**, the affordance **135** can include information that is not included in the indication (e.g., the storage-alert user interface **131**) displayed at the wearable device **102**. The storage-alert user interface **133** also includes a selectable affordance **137** for enabling the first image-management mode at the wearable device **102**. And the smart phone **103** also includes another user interface element **139** that includes representations of a portion of images associated with a gallery of images stored at the wearable device **102**. In some embodiments, the other user interface element **139** includes representations of images captured at more than one electronic device (e.g., the wearable device **102** and the smart phone **103**).

(20) Turning now to FIG. **1D**, the user **101** is capturing another image **140** with one of the cameras (e.g., the rear camera **108B**) of the wearable device **102**. The image **140** is displayed at the display **110** of the watch body **104** of the wearable device **102**. In some embodiments, as shown in FIG. **1D**, the watch body **104** of the wearable device **102** can be removed from the watch band **106** of the wearable device **102** (e.g., by detaching the watch body **104** from a magnetic and/or pin-based attached to a cradle portion **1002C** (FIG. **3**, bottom)). The user **101** captures the image **140** by performing a touch gesture **144** directed to an affordance **142** displayed on the display **110** of the wearable device **102**. In some embodiments, when the user **101** captures the image **140**, the used storage **122** changes as a result of the adding the image **140** to the available storage **120**.

(21) Turning now to FIG. **1E**, the wearable device **102** is shown during a state in which it has made a determination that the remaining available storage **120** is less than the second storage-depletion threshold **126**, between the first storage-depletion threshold **124** and the critical storage-depletion threshold **130**, and providing a new indication (e.g., a user-interface element **146**), displayed at the display **110** of the wearable device **102**, that the first image-management mode is available. In some embodiments, the second storage-depletion threshold **126** corresponds to an amount of available storage at the wearable device **102** of less than or equal to 250 megabytes. In some

embodiments, the second storage-depletion threshold **126** corresponds to any amount of available storage at the wearable device that is between 100 megabytes and 250 megabytes. The user-interface element **146** includes an affordance **150** that includes information about the first image-management mode. As shown in FIG. **1E**, the affordance **150** can display different information than is displayed in the storage-alert user interface **131** in FIG. **1C**. The user-interface element **146** includes a selectable affordance **152** for enabling the first image-management mode (e.g., a textual element that states: “Turn on auto delete”). The user-interface element **146** includes another selectable affordance **154**, that, when selected, displays additional information about the first image-management mode and/or other image-management techniques.

(22) In some embodiments, the determination that the available storage **120** is less than the second storage-depletion threshold **126** is performed at another electronic device (e.g., the smart phone **103**). In some embodiments, when the determination is made that the available storage **120** is less than the second storage-depletion threshold **126**, an additional indication is displayed at another electronic device (e.g., the smart phone **103**) that is in communication with the wearable device **102**. In some embodiments, the additional indication (e.g., a user-interface element **141**, denoted by a dashed box on the display of the smart phone **103**) displayed at the smart phone **103** includes additional information notifying the user **101** that the first image-management mode is available at the wearable device **102**. As shown in FIG. **1E**, the user-interface element **141** can include information that is not included in the indication (e.g., the user-interface element **146**) displayed at the wearable device **102**. In some embodiments, the additional information displayed at the smart phone **103** can include one or more affordances identical to those displayed in the storage-alert user interface **133** shown in FIG. **1C**. In some embodiments, the additional information displayed in the user-interface element **141** includes distinct affordances from those displayed in the storage-alert user interface **133**. The affordance **135** can also include selectable affordances (e.g., a selectable affordance **143**, and a selectable affordance **145**) that can cause operations to be performed at the wearable device **102** and/or the smart phone **103**. For example, the selectable affordance **143** which includes a textual indication that states “Manage backup settings” can be used to identify which images that are captured at the wearable device **102** should be “backed-up” (e.g., replicated, and/or otherwise made available for restoration) to the smart phone **103**. In some embodiments, the user-interface element **141** can also include a similar selectable affordance to the one displayed in FIG. **1C** for enabling the first image-management mode at the wearable device. In some embodiments, the smart phone **103** also includes another user-interface element that includes a gallery of images stored at the wearable device **102** (e.g., the same or a similar user interface element **139** that was displayed at the smart phone **103** in FIG. **1C**).

(23) Turning now to FIG. **1F**, the user **101** is capturing another image **157** with one of the cameras (e.g., the rear camera **108B**) of the wearable device **102**. The image **157** is displayed at the display **110** of the watch body **104** of the wearable device **102**. In some embodiments, as shown in FIG. **1F**, the watch body **104** of the wearable device **102** can be removed from the watch band **106** of the wearable device **102**. The user **101** captures the image **157** by performing a touch gesture **158** at an affordance **156** displayed on the display **110** of the wearable device **102**. In some embodiments, when the user **101** captures the image **157**, the used storage **122** changes as a result of adding the image **157** to the available storage **120**.

(24) Turning now to FIG. **1G**, the wearable device **102** is shown during a state in which the wearable device has determined that the remaining available storage **120** is less than the third storage-depletion threshold **128**, corresponding to an amount of storage between the second storage-depletion threshold **126** and the critical storage-depletion threshold **130**, and providing a new indication (e.g., user-interface element **160**), displayed at the display **110** of the wearable device **102**, that the first image-management mode is available. In some embodiments, the third storage-depletion threshold **128** corresponds to an amount of available storage at the wearable device **102** of less than or equal to 75 megabytes. The user-interface element **160** includes an

affordance **162** that includes information about the first image-management mode. As shown in FIG. **1G**, the affordance **164** can display different information than the affordance **150** that is shown in FIG. **1E** and corresponding to the determination that the remaining available storage **120** is less than the second storage-depletion threshold **126**. The affordance **164** can also be different than the storage-alert user interface **131** that is shown in FIG. **1C**, corresponding to the determination that the remaining available storage **120** is less than the first storage-depletion threshold **124**. The user-interface element **160** includes another affordance **166** for managing settings at the wearable device **102**. In some embodiments, when the determination is made that the available storage **120** is less than the third storage-depletion threshold **128**, an additional indication is displayed at another electronic device (e.g., the smart phone **103**) that is in communication with the wearable device **102**. As illustrated by the combination of FIGS. **1E** and **1F**, in some embodiments, the smart phone **103** can display the same user-interface elements and/or selectable affordances for respective determinations that the available storage **120** is less than two or more distinct storage-depletion thresholds, even though the wearable device displays distinct user-interface elements for each of the respective distinct storage-depletion thresholds (e.g., the second storage-depletion threshold **126** and the third storage-depletion threshold **128**).

(25) Turning now to FIG. **1H**, the user **101** attempts to save an image **176** at the wearable device **102**. As shown in FIG. **1H**, in addition to new images being captured by cameras of the wearable device **102** (e.g., the front camera **108A** or the rear camera **108B**), and/or another connected device, images can also be received from other users of different electronic devices. In FIG. **1H**, the wearable device **102** is displaying a user-interface element **170** that includes content of an electronic message sent by another user of a different electronic device. The content of the electronic message includes the image **176**, and a selectable affordance **172** for saving the image **176** at the wearable device **400**. The user **101** is performing a tap gesture **174** directed to the selectable affordance **172** to attempt to save the image **176** at the wearable device **102**. In some embodiments, the user **101** can turn on auto-deletion at the wearable device **102** while the wearable device **102** device is operating in the critical image-management mode.

(26) In some embodiments, the determination that the available storage **120** is less than the critical storage-depletion threshold **130** is performed at another electronic device (e.g., the smart phone **103**). In some embodiments, when the determination is made that the available storage **120** is less than the critical storage-depletion threshold **130**, an additional indication is displayed at another electronic device (e.g., the smart phone **103**) that is in communication with the wearable device **102**. In some embodiments, the additional indication (e.g., a user-interface element **171**, denoted by a dashed box on the display of the smart phone **103**) displayed at the smart phone **103** includes additional information notifying the user **101** that the critical image-management mode has been activated at the wearable device **102**. As shown in FIG. **1H**, the user-interface element **171** can be displayed even though there is no corresponding indication at the wearable device **102** that the critical image-management mode has been activated at the wearable device **102**. In some embodiments, the additional information displayed at the smart phone **103** can include one or more affordances identical to those displayed in the storage-alert user interface **133** shown in FIG. **1C** (e.g., the selectable affordance **137** indicating that the user **101** can turn on auto-deletion at the wearable device **102**. In some embodiments, the additional information displayed in the user-interface element **175** includes distinct affordances from those displayed in the storage-alert user interface **133**, or any of the other user-interface elements and/or affordances displayed at the smart phone **103** in FIGS. **1C**, **1E**, and/or **1G**. The user-interface element **171** can include one or more indications, indicating, for example, how the critical image-management mode effects the functionality of the wearable device **102** and/or how much additional storage would be repleted (e.g., “freed up”) based on turning on auto-deletion at the wearable device **102** (e.g., the affordance **173** states: “Your wearable device is unable to capture additional images. Auto-deletion would remove 512 MB of storage.”).

(27) Additionally, in FIGS. 1H-1I, the wearable device **102** is shown during a state in which it has determined that the available storage **120** is less than the critical storage-depletion threshold **130**. In some embodiments, the critical storage-depletion threshold **130** corresponds to an amount of available storage at the wearable device **102** of less than or equal to 50 megabytes. In accordance with the determination that the available storage **120** is less than the critical storage-depletion threshold, the wearable device **102** automatically, and without a request from the user **101**, operates the wearable device **102** in a second image-management mode. In some embodiments, while the wearable device is operating in the second image-management mode (e.g., the critical image-management mode), the wearable device **102** is configured to block the user **101** from storing any additional images at the wearable device **102** until a determination is made that a respective amount of storage (e.g., available storage **120**) remaining at the wearable device **102** is above the critical storage-depletion threshold **130**. In some embodiments, the second image-management mode is not the critical image-management mode (e.g., an intermediary image-management mode). While the wearable device **102** is operating in the second image-management mode that is not the critical image-management mode, the wearable device can be configured to require additional user inputs to store additional images and/or other media items at the wearable device **102**. For example, when the user **101** attempts to save the image **176** in FIG. 1H, the wearable device **102** can present an additional user interface and or selectable affordance requesting the user **101**'s permission to override the second image-management mode in order to store the image **176** at the wearable device **102**, after the user **101** selects the selectable affordance **172** to save the image **176** at the wearable device **102** (e.g., with the tap gesture **174**).

(28) Turning now to FIG. 1I, the wearable device **102** is displaying a user-interface element **184** in response to the user **101** performing the tap gesture **174** directed to the selectable affordance **172** in FIG. 1H. In some embodiments, as shown in FIG. 1I, while the wearable device **102** is operating in the second image-management mode, when the wearable device **102** receives a request to add a new image at the wearable device **102** (e.g., the tap gesture **174** to save the image **176**), the wearable device **102** blocks the user **101** from being able to add the new image to the available storage **120**. For example, as shown in FIG. 1I, the user-interface element **184** indicates to the user **101** that they cannot save the image **176** to storage at the wearable device **102**, since the wearable device **102** is operating in the second image-management mode. The image **176** can be received within a conversation thread of a message application (e.g., the message content included in the user-interface element **170**), or the request to add the new image to storage can be made in conjunction with capturing a new image at the wearable device **102**, or another electronic device, such as a head-wearable device configured to capture images.

(29) Turning now to FIG. 1J, the wearable device **102** is shown during a state in which it has made determination that the available storage **120** is not less than the critical storage-depletion threshold **130** or any others of the plurality of storage-depletion thresholds (the first storage-depletion threshold **124**, the second storage-depletion threshold **126**, and/or the third storage-depletion threshold **128**; one or more of which can be stored in the storage-depletion thresholds **1420** in the data **1410** of the memory **1400**). As shown with reference to FIG. 1I, the second image-management mode is enabled at the wearable device **102** in accordance with the determination that the available storage **120** at the wearable device **102** is less than the critical storage-depletion threshold **130**. When the second image-management mode is enabled, images that are not of a predetermined image type are automatically deleted from the wearable device **102**. In some embodiments, in conjunction with the deletion operation, a storage-alert user interface **190** is displayed at the display **110** of the wearable device **102** to notify the user **101** that there is a greater amount of storage (e.g., the available storage **120**) has increased at the wearable device **102**. In some embodiments, the auto-deletion process is iterative, and images located in the trash directory of the wearable device **102** are deleted before other images are subject to auto-deletion (e.g., images that have not been favorited by the user **101**).

(30) Turning now to FIG. 1K, the wearable device **102** is shown during a state in which it has made determination that the available storage **120** is not less than the first storage-depletion threshold **124** or any other storage-depletion thresholds of the plurality of storage-depletion thresholds. In accordance with the determination, the display **110** of the wearable device **102** displays a user-interface element **192** that indicates to the user that the wearable device **102** is no longer operating in the second image-management mode. The user-interface element **192** includes an affordance **196** that includes information indicating that the wearable device **102** is no longer operating in the second image-management mode. The user-interface element **192** also includes a selectable affordance **194** that the user **101** can select with performance of a user input, including a touch gesture at the display **110** of the wearable device **102**. Upon selecting the selectable affordance **194**, the additional information can be displayed at the display **110** of the wearable device **102** about the second image-management mode and/or the first image-management mode.

(31) In some embodiments, the determination that the available storage **120** is not less than the first storage-depletion threshold **124**, is performed at another electronic device (e.g., the smart phone **103**). In some embodiments, when the determination is made that the available storage **120** is less than the first storage-depletion threshold **124**, an additional indication is displayed at another electronic device (e.g., the smart phone **103**) that is in communication with the wearable device **102**. In some embodiments, the additional indication can include an indication that images from the wearable device **102** that have been deleted as a result of turning on auto-deletion at the wearable device **102** have been backed up to the smart phone **103**. For example, the smart phone **103** can include a user-interface element **185** that includes an information affordance **189** stating: “The deleted images have temporarily been backed up at this device.” In some embodiments, the smart phone **103** includes a selectable affordance **191** that the user **101** can select to delete the images that were deleted from the wearable device **102** as part of the auto-deletion operation performed at the wearable device **102**. In some embodiments, the smart phone **103** can also display a gallery **193** that includes images that were deleted from the wearable device **102** as part of the auto-deletion operation, and the user **101** can select one or more of the deleted images to restore to the wearable device **102**.

(32) FIGS. 2A-2B depict a flow diagram of a method **200** for storage management, performed at an electronic device (e.g., the wearable device **102** shown in FIG. 1A-1K) as storage is depleted and/or made available at the electronic device, in accordance with some embodiments. Specifically, FIG. 2A depicts a method **200** for storage management, performed at the electronic device (e.g., any of the electronic devices **1002A-1002C** illustrated in FIG. 3, individually or in combination) as storage is being depleted (e.g., an image storage **1418** of the data **1410** in memory **1400** in FIG. 3) at the electronic device, in accordance with some embodiments, and FIG. 2B depicts a method **250** for storage management, performed at the electronic device as depleted storage is being made available, in accordance with some embodiments.

(33) Turning now to FIG. 2A, in some embodiments, performance of the method **200** includes obtaining (**202**) an amount of available image storage at the electronic device (e.g., a wearable device, a head-wearable device, and/or a removable capsule or other component that forms a part of a wearable device system, etc.). In some embodiments, the method **200** uses computing resources of another electronic device (e.g., the processors and/or memory of the smart phone **103** in FIGS. 1A-1K) to obtain information about the first amount of storage at the electronic device. In some embodiments, the first amount of storage corresponds to an amount of available image storage (e.g., available image storage **260** in FIG. 2B; the remaining available storage **120** less the used storage **122** in FIGS. 1A, 1C, and 1E-1H) that is less than a total amount of storage available in memory (e.g., memory **1400** in FIG. 3) of the electronic device.

(34) Performance of the method **200** includes determining (**204**) whether the amount of storage at the electronic device is less than one or more of a plurality of storage-depletion thresholds, including at least two of a low-severity storage-depletion threshold (e.g., the first storage-depletion

threshold **124**; FIGS. **1A-1K**), a middle-severity storage-depletion threshold (e.g., the second storage-depletion threshold **126**; FIGS. **1A-1K**), and a critical storage-depletion threshold (e.g., critical storage-depletion threshold **130**; FIGS. **1A-1K**). In some embodiments, there can be additional storage-depletion thresholds between the first storage-depletion threshold and the critical storage-depletion threshold (e.g., the third storage-depletion threshold **128**; FIGS. **1A-1K**). In some embodiments, performance of the method **200** only causes comparing the amount of available image storage to a non-critical storage-depletion threshold (e.g., a first storage-depletion threshold that can be the low-severity storage-depletion threshold and/or the middle-severity storage-depletion threshold) and a critical storage-depletion threshold (e.g., a second storage-depletion threshold). In some embodiments, the critical storage-depletion threshold can correspond to an amount of available image storage that is equal to zero (e.g., the entirety of the memory **1400**, or a specific portion allocated to storage of a type of data such as camera data (which can include various types of images and videos), shown in FIG. **3** is used storage). That is, the critical storage-depletion threshold can be satisfied after a situation in which there is no available image storage, in accordance with some embodiments.

(35) In some embodiments, performance of the method **200** includes operating (**206**) the electronic device in a default image-management mode in accordance with determining that the amount of available storage at the electronic device is not less than any of the plurality of storage-depletion thresholds (e.g., “No” at operation **204**, which can correspond to used storage **122** like that shown in FIG. **1A**). In some embodiments, the auto-deletion does not occur at the electronic device while the electronic device is in the default image-management mode.

(36) In some embodiments, in accordance with performance of the method **200** resulting in a determination that the amount of available image storage at the electronic device is less than or equal to a low-severity storage-depletion threshold (**204**, Yes-Low), the electronic device is caused to present (**208**) a second time-limited indication to the user about a suggested image-management mode (e.g., affordance **132** in FIG. **1C**). In some embodiments, the electronic device is caused to suggest the first image-management mode if the first image-management mode is not already activated at the electronic device, and the electronic device is caused to suggest the second image-management mode if the first image-management mode is already activated at the electronic device.

(37) In some embodiments, in accordance with performance of the method **200** resulting in a determination that the amount of available image storage at the electronic device is less than or equal to a middle-severity storage-depletion threshold (**204**, Yes-Middle), the electronic device is caused to present (**210**) a first time-limited indication to the user about a suggested image-management mode. In some embodiments, the electronic device is caused to present information about a plurality of image-management modes, including a first image-management mode and the critical image-management mode.

(38) In some embodiments, in accordance the determination that the amount of available image storage at the electronic device is less than or equal to the critical storage-depletion threshold, performance of the method **200** causes the electronic device to present (**212**) a persistent indication to the user about suggested image-management modes (e.g., at the electronic device itself, or at another companion device). If the determination is made that the amount of available image storage is less than or equal to the critical storage-depletion threshold, the method **200** causes the electronic device to further prevent **214** the user from storing additional captured or received images at the electronic device.

(39) In some embodiments, in accordance with the performance of the method **200** resulting in the determination that the amount of available storage is less than or equal to the low-severity storage storage-depletion threshold or the mid-severity storage-depletion threshold (e.g., “Yes-Low” or “Yes-Mid” at **204**), the electronic device, after or in conjunction with presenting the appropriate indication, also determines (**216**) whether the user has enabled a first image-management mode at

the electronic device.

(40) If the user has enabled the first image-management mode at the electronic device (e.g., “Yes” at **216**), the electronic device proceeds to auto-delete (**218**) images that are not of a predetermined image type from the electronic device while the first image-management mode remains enabled. If the user has not enabled the first image-management mode at the electronic device (e.g., “No” at **216**), then the method **200** returns to **202** and again obtains an available amount of image storage from the electronic device and then proceeds to the subsequent operations of the method **200**.

(41) Turning now to FIG. 2B, when performance of the method **250** begins, the electronic device is operating in the critical image-management mode (e.g., the second image-management mode). In some embodiments, the critical image-management mode is activated after available image storage is less than or equal to a critical storage-depletion threshold (e.g., after determination **204**, Yes-Critical in FIG. 2A).

(42) While the electronic device is operating in the critical image-management mode, the electronic device is forced to prevent (**254**) the user from storing additional captured or received images at the electronic device (e.g., the electronic device is forcibly moved to operate in the second image-management mode and the user is not given a choice since remaining storage level is critically low). In some embodiments, the electronic device is configured to block the user from storing any additional images at the electronic device until a determination is made that a respective amount of storage remaining at the electronic device is above a respective storage-depletion threshold (determination block **260**, FIG. 2B). In some embodiments, the electronic device is configured to block the user from storing any additional images until a determination is made that the electronic device is above a storage-repletion threshold that is greater than or equal to the second storage-depletion threshold.

(43) In some embodiments, in addition to preventing the user from storing any additional images, the method **250** also causes the electronic device to auto-delete (**256**) images that are not of a predetermined image type.

(44) In some embodiments, after auto-deleting one or more images that are not of the predetermined image type, performance of the method **250** causes the electronic device to obtain (**258**) an amount of available image storage for the electronic device.

(45) In some embodiments, after obtaining the amount of available image storage at the electronic device, performance of the method **250** causes the electronic device to determine (**260**) whether the amount of available image storage is greater than one or more storage-depletion thresholds (e.g., a low-severity storage-depletion threshold, a middle-severity storage-depletion threshold, and/or a critical storage-depletion threshold).

(46) In some embodiments, in accordance with performance of the method **250** resulting in a determination that the amount of available image storage at the electronic device is not greater than the critical storage-depletion threshold (or the low- or middle-severity storage-depletion thresholds), performance of the method **250** causes the electronic device to present (**262**) a persistent indication to the user about the electronic device remaining in the critical image-management mode (e.g., at the electronic device itself, or at another companion device). If the determination is made that the amount of available image storage is not greater than the critical storage-depletion threshold, the method **250** causes the electronic device to return to **254** of the method **250** and causes the electronic device to prevent the user from storing additional captured or received images at the electronic device.

(47) In some embodiments, in accordance with performance of the method **250** resulting in a determination that the amount of available image storage at the electronic device is greater than the critical-severity storage-depletion threshold, but still not greater than the low-severity storage-depletion threshold or the middle-severity storage-depletion threshold, performance of the method **250** causes the electronic device to present (**264**) a first time-limited indication to the user about image-management modes. In some embodiments, performance of the method **250** causes the

electronic device to present information about a plurality of image-management modes, including a first image-management mode (e.g., a non-critical image-management mode) and the critical image-management mode. For example, the electronic device can present an indication that the critical image-management mode has been disabled since the amount of available storage is greater than the critical-severity storage-depletion threshold and can also present an indication suggesting the user to enable the first image-management mode if they have not already enabled the first image-management mode.

(48) In some embodiments, in accordance with performance of the method **250** resulting in a determination that the amount of available image storage at the electronic device is greater than the middle-severity storage-depletion threshold, but still not greater than the low-severity storage-depletion threshold, performance of the method **250** causes the electronic device to present (**266**) a second time-limited indication to the user about a suggested image-management mode. For example, the electronic device can present an indication that the critical image-management mode is disabled since the amount of available storage is greater than the critical-severity storage-depletion threshold and can also present an indication suggesting the user to enable the first image-management mode if they have not already enabled the first image-management mode. In some embodiments, the electronic device does not present the second time-limited indication that the first image-management mode is available while the user is using one or more applications that cause presentation of the first time-limited indication corresponding to the middle-severity storage-depletion threshold.

(49) In some embodiments, in accordance with performance of the method **250** resulting in a determination that the amount of available image storage at the electronic device is greater than both the low-severity storage-depletion threshold or the mid-severity storage-depletion threshold, performance of the method **250** further includes determining (**268**) if the user has activated the first image-management mode. In accordance with a determination that the first image-management mode has been enabled at the electronic device (e.g., “Yes” at **268**), the method **250** causes the electronic device to return to **256** of the method **250**, and further causes the electronic device to auto-delete images that are not of the predetermined image type.

(50) In some embodiments, after determining that the amount of available image storage at the electronic device is less than the critical-severity storage-depletion threshold, the middle-severity storage-depletion threshold, and the low-severity storage-depletion threshold, the electronic device proceeds to operate in the default image-management mode.

(51) Example System-Level Block Diagrams

(52) FIG. 3 is a block diagram of a computing system **1000**, according to at least one embodiment of the present disclosure. The computing system **1000** includes an electronic device **1002**, which can be, for example, a wearable device. The wearable device **102** described in detail above with respect to FIGS. 1A-1K is an example of the electronic device **1002**, so the electronic device **1002** will be understood to include the components shown and described below for the computing system **1000**. In some embodiments, all, or a substantial portion of the components of the computing system **1000** are included in a single integrated circuit. In some embodiments, the computing system **1000** can have a split architecture (e.g., a split mechanical architecture, a split electrical architecture) between a watch body (e.g., a watch body **404** in FIG. 4A) and a watch band (e.g., a watch band **406** in FIG. 4A). The electronic device **1002** can include a processor (e.g., a central processing unit **1004**), a controller **1010**, a peripherals interface **1014** that includes one or more sensors **1100** and various peripheral devices, a power source (e.g., a power system **1300**), and memory (e.g., a memory **1400**) that includes an operating system (e.g., an operating system **1402**), data (e.g., data **1410**), and one or more applications (e.g., applications **1430**).

(53) In some embodiments, the computing system **1000** includes the power system **1300** which includes a charger input **1302**, a power-management integrated circuit (PMIC) **1304**, and a battery **1306**.

(54) In some embodiments, a watch body and a watch band can each be electronic devices **1002** that each have respective batteries, **1306**, and can share power with each other. The watch body and the watch band can receive a charge using a variety of techniques. In some embodiments, the watch body and the watch band can use a wired charging assembly (e.g., power cords) to receive the charge. Alternatively, or in addition, the watch body and/or the watch band can be configured for wireless charging. For example, a portable charging device can be designed to mate with a portion of watch body and/or watch band and wirelessly deliver usable power to a battery of watch body and/or watch band.

(55) The watch body and the watch band can have independent power systems **1300** to enable each to operate independently. The watch body and watch band can also share power (e.g., one can charge the other) via respective PMICs **1304** that can share power over power and ground conductors and/or over wireless charging antennas.

(56) In some embodiments, the peripherals interface **1014** can include one or more sensors **1100**. The sensors **1100** can include a coupling sensor **1102** for detecting when the electronic device **1002** is coupled with another electronic device **1002** (e.g., a watch body can detect when it is coupled to a watch band, and vice versa). The sensors **1100** can include imaging sensors **1104** for collecting imaging data. In some embodiments, the imaging sensors **1104** can be separate from the cameras **1218**. In some embodiments the sensors include an SpO2 sensor **1106**. In some embodiments, the sensors **1100** include an EMG sensor **1108** for detecting, for example muscular movements by a user of the electronic device **1002**. In some embodiments, the sensors **1100** include a capacitive sensor **1110** for detecting changes in potential of a portion of a user's body. In some embodiments, the sensors **1100** include a heart rate sensor **1112**. In some embodiments, the sensors **1100** include an inertial measurement unit (IMU) sensor **1114** for detecting, for example, changes in acceleration of the user's hand.

(57) In some embodiments, the peripherals interface **1014** includes a near-field communication (NFC) component **1202**, a global positioning system (GPS) component **1204**, a long-term evolution (LTE) component **1206**, and or a Wi-Fi or Bluetooth communication component **1208**.

(58) In some embodiments, the peripherals interface includes one or more buttons (e.g., the buttons **414**, **416**, and **418** in FIGS. 4A-4B), which, when selected by a user, cause operation to be performed at the electronic device **1002**.

(59) The electronic device **1002** can include at least one display **1212**, for displaying visual affordances to the user, including user-interface elements and/or three-dimensional virtual objects. The display can also include a touch screen for inputting user inputs, such as touch gestures, swipe gestures, and the like.

(60) The electronic device **1002** can include at least one speaker **1214** and at least one microphone **1216** for providing audio signals to the user and receiving audio input from the user. The user can provide user inputs through the microphone **1216** and can also receive audio output from the speaker **1214** as part of a haptic event provided by the haptic controller **1012**.

(61) The electronic device **1002** can include at least one camera **1218**, including a front camera **1220** and a rear camera **1222**. As described herein, the image-management module **1438** can communicate with the front camera **1220** or the rear camera **1222** based on the current image-management mode that is active at the electronic device **1002**. In some embodiments, the electronic device **1002** can be a head-wearable device, and one of the cameras **1218** can be integrated with a lens assembly of the head-wearable device.

(62) One or more of the electronic devices **1002** can include one or more haptic controllers **1012** and associated componentry for providing haptic events at one or more of the electronic devices **1002** (e.g., a vibrating sensation or audio output in response to an event at the electronic device **1002**). The haptic controllers **1012** can communicate with one or more electroacoustic devices, including a speaker of the one or more speakers **1214** and/or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid,

electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). The haptic controller **1012** can provide haptic events to that are capable of being sensed by a user of the electronic devices **1002**. In some embodiments, the one or more haptic controllers **1012** can receive input signals from an application of the applications **1430**, including from the image-management module **1438**. For example, the image-management module **1438** can provide a signal to the haptic controller **1012** instructing the haptic controller **1012** to provide a haptic event to the user in accordance with a determination that the available image storage **1418** at the electronic device **1002** is less than or equal to one or more storage-depletion thresholds, and/or is greater than or equal to one or more storage repletion thresholds.

(63) Memory **1400** optionally includes high-speed random-access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to the memory **1400** by other components of the electronic device **1002**, such as the one or more processors of the central processing unit **1004**, and the peripherals interface **1014** is optionally controlled by a memory controller of the controllers **1010**.

(64) In some embodiments, software components stored in the memory **1400** can include one or more operating systems **1402** (e.g., a Linux-based operating system, an Android operating system, etc.). The memory **1400** can also include data **1410**, including structured data (e.g., SQL databases, MongoDB databases, GraphQL data, JSON data, etc.). The data **1410** can include profile data **1412**, sensor data **1414**, media file data **1416**, and/or available image storage **1418**. Operating systems **1402** can include various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.), and can facilitate communication between various hardware and software components. In some embodiments, the methods described herein for managing storage at an electronic device **1002** are based on an amount of available image storage **1418** remaining. In some embodiments, the amount of available image storage **1418** is based on how much of the memory **1400** is allocated for use by one or more operating systems **1402** of the electronic device **1002**. For the purposes of this application, the available image storage refers to camera data generally, which can include various types of images, including sequences of images (e.g., videos), as well as other types of data that can be collected by certain embodiments of the cameras **1218**. In some embodiments, the data **1410** in the memory **1400** includes a data file or other means of logical storage, which includes data values which correspond to storage-depletion thresholds **1420**, including storage-depletion thresholds related to the available image storage **1418**.

(65) In some embodiments, software components stored in the memory **1400** include one or more applications **1430** configured to be perform operations at the electronic devices **1002**. In some embodiments, the one or more applications **1430** include one or more communication interface modules **1432**, one or more graphics modules **1434**, one or more camera application modules **1436**, and/or one or more image-management modules **1438**. In some embodiments, a plurality of applications **1430** can work in conjunction with one another to perform various tasks at one or more of the electronic devices **1002**. For example, the image-management module **1438** can determine an amount of storage available at the electronic device **1002**, and based on the detected amount of storage, can communicate with another electronic device **1002** within the computing system **1000** to sync or “back-up” images between the electronic device **1002** and the other electronic device (e.g., the user-interface element **185** in FIG. 1J indicates that the smart phone **103** has backed-up the deleted images from the wearable device **102**), and/or determine which images are deletion-candidates based on settings or other configuration information.

(66) As illustrated by the lower portion of FIG. 3, various individual components of a wearable device (e.g., the wearable device **102** in FIGS. 1A-1K) can be examples of the electronic device **1002**. For example, some or all of the components shown in the electronic device **1002** can be

housed or otherwise disposed in a combined watch device **1002A**, or within individual components of the capsule device watch body **1002B** (e.g., the watch body **404**; FIG. **4A**), the cradle portion **1002C** (e.g., the coupling mechanism **412**; FIG. **4A**), and/or a watch band (e.g., the watch band **406**; FIG. **4A**).

(67) The electronic devices **1002** are only some examples of the electronic devices **1002** within the computing system **1000**, and other electronic devices **1002**, including electronic devices that are part of the computing system **1000**, can have more or fewer components than shown optionally combines two or more components, or optionally have a different configuration or arrangement of the components. The various components shown in FIG. **3** are implemented in hardware, software, firmware, or a combination thereof, including one or more signal processing and/or application-specific integrated circuits.

(68) Having thus described example block diagrams, attention will now be directed to examples of the wearable devices that can be used in conjunction with the techniques described herein.

(69) Example Wearable Devices (e.g., Wrist-Wearable Devices Such as Smart Watches, and Companion Devices Such as Smart Phones)

(70) FIGS. **4A** and **4B** illustrate an example wearable device **400**, in accordance with some embodiments. The wearable device **400** is an instance of the electronic device **1002** described above in reference to FIGS. **3**, such that the wearable device **400** should be understood to have the features of the electronic device **1002**, and vice versa.

(71) FIG. **4A** illustrates a perspective view of the wearable device **400** that includes a watch body **404** coupled with a watch band **406**. The watch body **404** and the watch band **406** can have a substantially rectangular or circular shape and can be configured to allow a user to wear the wearable device **400** on a body part (e.g., a wrist). The watch body **404** can have a display **410**, that can have a substantially rectangular or circular shape that can correspond to the shape of the watch body **404**. The display **410** can be touch sensitive, and or can use an imaging sensor (e.g., the front camera **408A**) to detect a gesture above the display **410**. The wearable device **400** can also include a coupling mechanism **412** (e.g., a cradle) for detachably coupling capsule or watch body **402** (via a coupling surface **422** of the watch body **404**) to watch band **406**.

(72) The watch band **406** can be configured to be worn by a user such that an inner surface of the watch band **406** is in contact with the user's skin. When worn by a user, a sensor **426** of the wearable device **400** is in contact with the user's skin. The sensor **426** can be a biosensor that senses a user's heart rate, saturated oxygen level, temperature, sweat level, muscle intentions, or a combination thereof. The watch band **406** can include multiple sensors (e.g., sensors **426** and **428**) that can be distributed on an inside and/or an outside surface of the watch band **406**. Additionally, or alternatively, the watch body **404** can include the same or different sensors than the watch band **406** (or the watch band **406** can include no sensors at all in some embodiments). For example, multiple sensors can be distributed on an inside and/or an outside surface of the watch body **404**. The sensors can include any combination of one or more of the sensors including the examples of sensors described with respect to FIG. **3**. Watch band **406** can transmit data acquired by one or more sensors to the watch body **404** using a wired communication method (e.g., a UART, a USB transceiver, etc.) and/or a wireless communication method (e.g., near-field communication, Bluetooth, etc.). Watch band **406** can be configured to operate (e.g., to collect sensor data) independent of whether the watch body **404** is coupled to or decoupled from the watch band **406**.

(73) In some examples, the watch band **406** can include a neuromuscular-signal sensor **428** (e.g., an electromyography (EMG) sensor, a mechanomyogram (MMG) sensor, a sonomyography (SMG) sensor, etc.). The neuromuscular-signal sensor **428** can sense a user's intention to perform certain motor actions (the sensor **428** can be another example of a sensor used as the biometric sensor in conjunctions with the positional-state determinations described herein). The sensed muscle intention can be used to control certain user interfaces displayed on the display **410** of the wearable device **400** and/or can be transmitted to another device responsible for displaying an artificial-

reality environment (e.g., a head-mounted display) to perform an action in an associated artificial-reality environment, such as to control the motion of a virtual device displayed to the user.

(74) Signals from the neuromuscular-signal sensor **428** can be used to provide a user with an enhanced interaction with a physical object and/or a virtual object in an artificial-reality application generated by an artificial-reality system (e.g., user interface objects presented on the display **410**, or another computing device (e.g., a head-mounted display)). Signals from neuromuscular-signal sensor **428** can be obtained (e.g., sensed and recorded) by one or more neuromuscular-signal sensors **428** of watch band **406**. Although FIG. **4A** shows one neuromuscular-signal sensor **428**, watch band **406** can include a plurality of neuromuscular-signal sensors **428** arranged circumferentially on an inside surface of watch band **406** such that the plurality of neuromuscular-signal sensors **428** contact the skin of the user. The watch band **406** can include a plurality of neuromuscular-signal sensors **428** arranged circumferentially on an inside surface of watch band **406**. Neuromuscular-signal sensor **428** can sense and record neuromuscular signals from the user as the user performs muscular activations (e.g., movements, gestures, etc.). The muscular activations performed by the user can include static gestures, such as placing the user's hand palm down on a table; dynamic gestures, such as grasping a physical or virtual object; and covert gestures that are imperceptible to another person, such as slightly tensing a joint by co-contracting opposing muscles or using sub-muscular activations. The muscular activations performed by the user can include symbolic gestures (e.g., gestures mapped to other gestures, interactions, or commands, for example, based on a gesture vocabulary that specifies the mapping of gestures to commands).

(75) The watch band **406** and/or the watch body **404** can include a haptic device **430** (e.g., a vibratory haptic actuator) that is configured to provide haptic feedback (e.g., a cutaneous and/or kinesthetic sensation, etc.) to the user's skin. The sensors **426** and **428** and/or the haptic device **430** can be configured to operate in conjunction with multiple applications including, without limitation, health monitoring, social media, game playing, and artificial reality.

(76) The wearable device **400** can include a coupling mechanism (also referred to as a cradle) for detachably coupling the watch body **404** to the watch band **406**. A user can detach the watch body **404** from the watch band **406** to reduce the encumbrance of the wearable device **400** to the user. The wearable device **400** can include a coupling mechanism **412** to couple with a coupling surface of the watch body **404** (e.g., a cradle, a tracker band, a support base, a clasp, etc.). A user can perform any type of motion to couple the watch body **404** to the watch band **406** and to decouple the watch body **404** from the watch band **406**. For example, a user can twist, slide, turn, push, pull, or rotate the watch body **404** relative to the watch band **406** and to detach the watch body **404** from the watch band **406**.

(77) As shown in the example of FIG. **4A**, the coupling mechanism **412** can include a type of frame or shell that allows the watch body **404** to be retained within watch band coupling mechanism **412**. The watch body **404** can be detachably coupled to the watch band **406** through a friction fit, magnetic coupling, a rotation-based connector, a shear-pin coupler, a retention spring, one or more magnets, a clip, a pin shaft, a hook and loop fastener, or a combination thereof. In some examples, watch body **404** can be decoupled from watch band **406** by actuation of release mechanism **420**. The release mechanism **420** can include, without limitation, a button, a knob, a plunger, a handle, a lever, a fastener, a clasp, a dial, a latch, or a combination thereof.

(78) The wearable device **400** can include a single release mechanism **420** or multiple release mechanisms **420** (e.g., two release mechanisms **420** positioned on opposing sides of the wearable device **400** such as spring-loaded buttons). As shown in FIG. **4A**, the release mechanism **420** can be positioned on the watch body **404** and/or the coupling mechanism **412**. Although FIG. **4A** shows release mechanism **420** positioned at a corner of watch body **404** and at a corner of the coupling mechanism **412**, the release mechanism **420** can be positioned anywhere on the watch body **404**, the watch band **406**, and/or the coupling mechanism **412** that is convenient for a user of wearable device **400** to actuate. A user of the wearable device **400** can actuate the release mechanism **420** by

pushing, turning, lifting, depressing, shifting, or performing other actions on the release mechanism **420**. Actuation of the release mechanism **420** can release (e.g., decouple) the watch body **404** from the coupling mechanism **412** and the watch band **406**, allowing the user to use the watch body **404** independently from watch band **406**. For example, decoupling the watch body **404** from the watch band **406** can allow the user to capture images using rear camera **408B**.

(79) FIG. **4B** is a top view of the wearable device **400**. The wearable device **400** in FIGS. **4A-4B** can include a coupling mechanism **412** (another example of a cradle for the capsule portion of the device, the watch body **404**). The watch body **404** can be detachably coupled to the coupling mechanism **412**. The watch body **404** can be detachably coupled to the coupling mechanism **412** through a friction fit, magnetic coupling, a rotation-based connector, a shear-pin coupler, a retention spring, one or more magnets, a clip, a pin shaft, a hook and loop fastener, or a combination thereof.

(80) In some examples, watch body **404** can be decoupled from the coupling mechanism **412** by actuation of a release mechanism. The release mechanism can include, without limitation, a button, a knob, a plunger, a handle, a lever, a fastener, a clasp, a dial, a latch, or a combination thereof. In some examples, the wristband system functions can be executed independently in watch body **404**, independently in the coupling mechanism **412**, and/or in communication between watch body **404** and the coupling mechanism **412**. The coupling mechanism **412** can be configured to operate independently (e.g., execute functions independently) from watch body **404**. Additionally, or alternatively, the watch body **404** can be configured to operate independently (e.g., execute functions independently) from the coupling mechanism **412**. As described above with reference to the block diagram of FIG. **3**, the coupling mechanism **412** and/or the watch body **404** can each include the independent resources required to independently execute functions. For example, the coupling mechanism **412** and/or the watch body **404** can each include a power source (e.g., a battery), a memory, data storage, a processor (e.g., a CPU), communications, a light source, and/or input/output devices. As shown in FIGS. **4A-4B**, the coupling mechanism **412** can be configured to receive a coupling surface proximate to the bottom side of the watch body **404** (e.g., a side opposite to a front side of the watch body **404** where the display **410** is located), such that a user can push the watch body **404** downward into the coupling mechanism **412** to attach the watch body **404** to the coupling mechanism **412**. In some embodiments, the coupling mechanism **412** can be configured to receive a top side of the watch body **404** (e.g., a side proximate to the front side of the watch body **404** where the display **410** is located) is pushed upward into the cradle, as opposed to being pushed downward into the coupling mechanism **412**. In some embodiments, the coupling mechanism **412** is an integrated component of the watch band **406** such that the watch band **406** and the coupling mechanism **412** are a single unitary structure.

(81) In this example, the coupling mechanism **412** can include all the electronic components of watch band **406**. In additional examples, one or more electronic components can be housed in the coupling mechanism **412** and one or more other electronic components can be housed in portions of watch band **406** away from the coupling mechanism **412**.

(82) Having thus described example block diagrams of an example computing system **300**, and example wearable device **400** attention will now be directed to a detailed flow diagram illustrating example embodiments, and a detailed listing of example embodiments.

(83) Detailed Flow Diagram

(84) FIG. **5** is a detailed flow diagram illustrating a method **500** for storage management performed at a wearable device (e.g., the wearable device **400** in FIGS. **4A-4B**), in accordance with some embodiments.

(85) The method **500** includes, in accordance with (502) a first determination that a first amount of storage is less than or equal to a first storage-depletion threshold, providing an indication, at the wearable device, that a first image-management mode is available, wherein, when the wearable device is operating in the first image-management mode, the wearable device is caused to delete

one or more images that are not of a predetermined image type. For example, the wearable device **102** displays the storage-alert user interface **131** in accordance with a determination that the remaining amount of available storage **120** at the wearable device **102** is less than the first storage-depletion threshold **124**.

(86) In some embodiments, if the amount of storage is not less than the first storage-depletion threshold, the wearable device operates in a default image-management mode, the default image-management mode configured to be used at the wearable device when greater amount of storage than the first storage-depletion threshold is available at the wearable device. In some embodiments, new images captured at the wearable device are stored locally and are not backed up to another device while the wearable device is operating in the default image-management mode that is distinct from the first and second image-management modes.

(87) In some embodiments, the predetermined protected image type corresponds to one or more images that have been selected as a favorite image by the user of the wearable device. For example, when the user **101** captures the new images **125** and **140** at the wearable device **102** in FIGS. **1B** and **1D**, the user **101** can provide a user input indicating that the user **101** is selecting the image as favorite image.

(88) In some embodiments, the indication is provided in response to the user opening a first image-related application of a plurality of image-related applications available on the wearable device, and the method **500** further includes, while a current amount of storage at the wearable device remains less than the first storage-depletion threshold, in response to the user opening a second image-related application of the plurality of image-related applications available on the wearable device, displaying the indication, at the wearable device, that the first image-management mode is available such that the indication overlays a portion of content associated with the second image-related application.

(89) In some embodiments, while a current amount storage at the wearable device remains less than a first repletion threshold that is greater than or equal to the first depletion threshold, the method **500** causes display of a secondary indication at a second electronic device, which is in communication with the wearable device, where the secondary indication includes information notifying the user that the first image-management mode is available for the wearable device (e.g., the storage-alert user interface **133** displayed at the smart phone **103** in FIG. **1C**).

(90) In some embodiments, the secondary indication includes additional information that is not included in the indication displayed at the wearable device (e.g., the affordance **135** displayed at the smart phone **103** includes different information than is displayed in the corresponding affordance **134** of the wearable device **102**).

(91) In some embodiments, the method **500** further includes, in accordance with (**504**) an intermediate determination that an intermediate amount of storage at the wearable device is less than or equal to an intermediate storage-depletion threshold, the intermediate storage-depletion threshold between the first storage-depletion threshold and the second storage-depletion threshold, providing a new indication, at the wearable device, distinct from the indication provided in accordance with the first determination, that the first image-management mode is available. For example, the user-interface element **146** displays different information (e.g., the affordance **148**), which corresponds to the available storage **120** being less than the second storage-depletion threshold **126**, than the information displayed in the affordance **132** in the storage-alert user interface **131**, which indicates that the available storage **120** at the wearable device **102** is less than the first storage-depletion threshold **124**.

(92) In some embodiments, the method **500** further includes, while (**506**) the wearable device is operating in the first image-management mode, deleting one or more deletion-candidate images from the wearable device that are not of the predetermined protected image type until enough deletion-candidate images have been deleted such that a post-deletion amount of storage remaining at the wearable device is greater than the first storage-depletion threshold. For example, as shown

by the storage-alert user interface **190** in FIG. **1J**, when the wearable device **102** is caused to auto-delete images, the available storage **120** is greater than the first storage-depletion threshold **124**. The user **101** could have optionally caused the same auto-deletion operation to be performed by providing a user input to select the selectable affordance **152** in FIG. **1E**.

(93) In some embodiments, while the wearable device is in the first image-management mode, at least one of the one or more deletion-candidate images that are not of a predetermined protected image type, are backed up to another device before deleting the one or more deletion-candidate images. For example, as indicated by the user-interface element **185** in FIG. **1J**, the smart phone **103** backs up the images that were deleted through auto-deletion at the wearable device **102**.

(94) The method **500** further includes, in accordance with **(508)** a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first depletion threshold, automatically, and without a request from a user of the wearable device, operate the wearable device in a second image-management mode (e.g., the affordance **182** in FIG. **1I** indicates that the wearable device **102** is operating in a critical image-management mode).

(95) The method **500** further includes, when **(510)** the wearable device is operating in the second image-management mode, blocking the user from storing any additional images at the wearable device until a repletion determination is made that a respective amount of storage remaining at the wearable device is greater than or equal to the second storage-depletion threshold (e.g., the image **176** is blocked from being saved at the wearable device **102** in FIG. **1I**).

(96) In some embodiments, while the wearable device is operating in the second image-management mode, the wearable is caused to display, on the display of the wearable device, a critical indication that the wearable device has been forced to operate in the second image-management mode (e.g., the user-interface element **184** in FIG. **1I**). In some embodiments, the critical indication is displayed system-wide on the wearable device for at least a predefined period of time.

(97) In some embodiments, while the updated amount of storage at the wearable device remains less than the second storage-depletion threshold, the method **500** causes another electronic device in communication with the wearable device to present, an additional critical indication, where the additional critical indication indicates that the wearable device has been forced to operate in the second image-management mode (e.g., the smart phone **103** in FIG. **1I**).

(98) In some embodiments, the additional critical indication is displayed with an image-deletion option that, when selected, causes the wearable device to delete enough images that are not of the predetermined protected image type until a post-image-deletion amount of storage at the wearable device is greater than the second storage-depletion threshold. For example, FIG. **1J** shows the wearable device **102** displaying a storage-alert user interface **190** indicating to the user **101** that auto-deletion settings removed 512 megabytes from the available storage **120** of the wearable device **102**.

(99) In some embodiments, at least one of the first determination that the first amount of storage is less than or equal to the first storage-depletion threshold, and the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold, are performed at another electronic device (e.g., the smart phone **103** in FIGS. **1A-1K**). In some embodiments, the other electronic device is a portable computing unit configured to perform computations in conjunction with operation of the wearable device.

(100) In some embodiments, while the method **500** is operating the wearable device in the second image-management mode, the method **500** includes receiving, at the wearable device, a storage request to add a new image to a storage location at the wearable device, and, in response to receiving the request, blocking the user from being able to add the new image to the storage location at the wearable device. In some embodiments, the new image was received within a

conversation thread of a messaging application, or the request to add the new image to storage is made in conjunction with capturing an image using a camera of the wearable device. For example, FIG. 1H, the user **101** receives a message at their wearable device and attempts to save the image **176** that was received in the message. In response, as shown in FIG. 1I, the wearable device **102** displays a user-interface element **184** indicating that the user **101** cannot save the image **176** at the wearable device **102**.

(101) In some embodiments, while the wearable device is operating in the second image-management mode, based on determining that a post-deletion amount of storage at the wearable device is greater than a repletion threshold greater than or equal to the second depletion threshold, the method **500** ceases to operate the wearable device using the second image-management mode. For example, in FIG. 1K, the wearable device **102** makes a determination (e.g., a repletion determination) that the available storage is not less than the first storage-depletion threshold **124** or any other storage-depletion thresholds, and the wearable device **102** displays a user-interface element **192** that indicates to the user **101** that the wearable device **102** is no longer operating in the second image-management mode.

Example Embodiments

(102) A few example embodiments of the methods and systems described herein will now be briefly described.

(103) (A1) In accordance with some embodiments, a method of optimizing storage of images at a wearable device is disclosed. The method includes, determining a first amount of storage at the wearable device. The method further includes, in accordance with a first determination that the first amount of storage is less than or equal to a first storage-depletion threshold, providing an indication, at the wearable device, that a first image-management mode is available, where, when the wearable device is operating in the first image-management mode, the wearable device is caused to delete one or more images that are not of a predetermined image type. The method further includes, in accordance with a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first storage-depletion threshold, automatically, and without a request from a user of the wearable device, operating the wearable device in a second image-management mode, where, when the wearable device is operating in the second image-management mode, the wearable device is configured to block the user from storing any additional images at the wearable device until a determination is made that a respective amount of storage remaining at the wearable device is above the second storage-depletion threshold.

(104) (A2) In some embodiments of A1, the method further includes, before the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold, in accordance with an intermediate determination an intermediate amount of storage at the wearable device is less than or equal to a respective additional storage-depletion threshold, the respective additional storage-depletion threshold between the first storage-depletion threshold and the second storage-depletion threshold, providing a new indication at the wearable device that the first image-management mode is available.

(105) (A3) In some embodiments of A1-A2, the method further includes, while the wearable device is operating in the first image-management mode, deleting one or more deletion-candidate images from the wearable device that are not of the predetermined image type until enough deletion-candidate images have been deleted such that a new amount of storage remaining at the wearable device is greater than the first storage-depletion threshold.

(106) (A4) In some embodiments of A3, the method further includes, while the wearable device is in the first image-management mode, backing up at least one of the one or more deletion-candidate images that are not of a predetermined protected image type to another device before deleting the one or more deletion-candidate images.

(107) (A5) In some embodiments of A1-A4, new images captured at the wearable device are stored locally and are not backed up to another device while the wearable device is operating in a default image-management mode that is distinct from the first and second image-management modes, the default image-management mode configured to be used at the wearable device when more storage greater than the first storage-depletion threshold is available at the wearable device.

(108) (A6) In some embodiments of A1-A5, the predetermined image type is a type of image that has been selected as a favorite image by the user of the wearable device.

(109) (A7) In some embodiments of A1-A6, the method further includes, while storage at the wearable device remains less than the first storage-depletion threshold, causing display of an additional indication at another electronic device, which is in communication with the wearable device, where the additional indication on the display of the other electronic device includes information notifying the user that the first image-management mode is available for the wearable device.

(110) (A8) In some embodiments of A7, the additional indication caused to be displayed at the other electronic device includes additional information that is not included in the indication displayed at the wearable device.

(111) (A9) In some embodiments of A1-A8, at least one of (i) the first determination that the first amount of storage is less than or equal to the first storage-depletion threshold, and (ii) the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold, are performed at another electronic device that provides information to the wearable device.

(112) (A10) In some embodiments of A1-A9, the indication is provided in response to the user opening a first image-related application of a plurality of image-related applications available on the wearable device, and the method further includes, while a current amount of storage at the wearable device remains less than the first storage-depletion threshold, in response to the user opening a second image-related application of the plurality of image-related applications available on the wearable device, displaying the indication, at the wearable device, that the first image-management mode is available such that the indication overlays a portion of content associated with the second image-related application.

(113) (A11) In some embodiments of A1-A10, the method further includes, while the wearable device is operating in the second image-management mode, displaying, on a display of the wearable device, an additional indication that the wearable device has been forced to operate in the second image-management mode.

(114) (A12) In some embodiments of A11, the critical indication is displayed system-wide on the wearable device for at least a predefined period of time.

(115) (A13) In some embodiments of A11-A12, the method further includes, while the updated amount of storage at the wearable device remains less than the second storage-depletion threshold, causing another electronic device in communication with the wearable device to present, an additional critical indication, where the additional critical indication indicates that the wearable device has been forced to operate in the second image-management mode.

(116) (A14) In some embodiments of A11-A13, the additional indication is displayed with an image-deletion option that, when selected, causes the wearable device to delete enough images that are not of the predetermined image type until a post-image-deletion amount of storage at the wearable device is greater than the second storage-depletion threshold.

(117) (A15) In some embodiments of A1-A14, the method further includes, while operating the wearable device in the second image-management mode, receiving, at the wearable device, a request to add a new image to storage at the wearable device, and in response to receiving the request, blocking the user from being able to add the new image to storage at the wearable device.

(118) (A16) In some embodiments of A15, the new image was received within a conversation thread of a messaging application, or the request to add the new image to storage is made in

conjunction with capturing an image using a camera of the wearable device.

(119) (A17) In some embodiments of A1-A16, the method further includes, while the wearable device is operating in the second image-management mode, based on determining that a new amount of storage at the wearable device is greater than the second storage-depletion threshold, ceasing to operate the wearable device using the second image-management mode.

(120) (B1) In some embodiments, a wearable device is provided that is configured to perform or cause performance of the method of any of A1-A17.

(121) (C1) In some embodiments, a capsule device housing the display of the wearable device recited in any of A1-A17 is provided. The capsule device is configured to couple with a band to form a wearable device, and the capsule device includes one or more processors configured to perform or cause performance of the methods of any of A1-A17.

(122) (D1) In some embodiments, a non-transitory computer-readable storage medium is provided that includes instructions that, when executed by a wearable device, causes the wearable device to perform or cause performance of the method of any of A1-A17.

(123) (E1) In some embodiments, an electronic device, other than a wearable device, is provided that is configured to perform or cause performance of the method of any of A1-A17.

(124) (F1) In some embodiments, a non-transitory, computer-readable storage medium is provided that includes instructions that, when executed by an electronic device other than a wearable device, causes the electronic device to perform or cause performance of the method of any of A1-A17.

(125) (G1) In some embodiments, a system is provided that includes a wearable device and a connected electronic device, where either or both of the wearable device and the other electronic device are configured to perform or cause performance of the method of A1-A17.

(126) It will be understood that, although the terms “first,” “second,” etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another.

(127) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the claims. As used in the description of the embodiments and the appended claims, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(128) As used herein, the term “if” can be construed to mean “when” or “upon” or “in response to determining” or “in accordance with a determination” or “in response to detecting,” that a stated condition precedent is true, depending on the context. Similarly, the phrase “if it is determined [that a stated condition precedent is true]” or “if [a stated condition precedent is true]” or “when [a stated condition precedent is true]” can be construed to mean “upon determining” or “in response to determining” or “in accordance with a determination” or “upon detecting” or “in response to detecting” that the stated condition precedent is true, depending on the context.

(129) The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the claims to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain principles of operation and practical applications, to thereby enable others skilled in the art.

Claims

1. A method of optimizing storage of images at a wearable device, the method comprising: in accordance with a first determination that a first amount of storage is less than or equal to a first storage-depletion threshold: providing an indication, at the wearable device, that a first image-management mode is available, wherein, when the wearable device is operating in the first image-management mode, the wearable device is caused to delete one or more images that are not of a predetermined protected image type; while a current amount of storage at the wearable device remains less than a first repletion threshold that is greater than or equal to the first depletion threshold: causing display of a secondary indication at a second electronic device, which is in communication with the wearable device, wherein the secondary indication includes information indicating that the first image-management mode is available for the wearable device; and in accordance with a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first storage-depletion threshold: automatically, and without a request from a user of the wearable device, operating the wearable device in a second image-management mode, wherein when the wearable device is operating in the second image-management mode: blocking the user from storing any additional images at the wearable device until a repletion determination is made that a respective amount of storage remaining at the wearable device is greater than or equal to the second storage-depletion threshold.
2. The method of claim 1, further comprising: before the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold: in accordance with an intermediate determination that an intermediate amount of storage at the wearable device is less than or equal to an intermediate storage-depletion threshold, the intermediate storage-depletion threshold between the first storage-depletion threshold and the second storage-depletion threshold: providing a new indication, at the wearable device, distinct from the indication provided in accordance with the first determination, that the first image-management mode is available.
3. The method of claim 1, further comprising: while the wearable device is operating in the first image-management mode: deleting one or more deletion-candidate images from the wearable device that are not of the predetermined protected image type until enough deletion-candidate images have been deleted such that a post-deletion amount of storage remaining at the wearable device is greater than the first storage-depletion threshold.
4. The method of claim 3, further comprising: while the wearable device is in the first image-management mode: backing up at least one of the one or more deletion-candidate images that are not of the predetermined protected image type to another electronic device before deleting the one or more deletion-candidate images.
5. The method of claim 1, wherein new images captured at the wearable device are stored locally and are not backed up to another electronic device while the wearable device is operating in a default image-management mode that is distinct from the first and second image-management modes.
6. The method of claim 1, wherein the secondary indication includes additional information that is not included in the indication displayed at the wearable device.
7. The method of claim 1, wherein the indication is provided in response to the user opening a first image-related application of a plurality of image-related applications available on the wearable device, and further comprising: while a current amount of storage at the wearable device remains less than the first storage-depletion threshold: in response to the user opening a second image-related application of the plurality of image-related applications available on the wearable device, displaying the indication, at the wearable device, that the first image-management mode is available such that the indication overlays a portion of content associated with the second image-related application.

8. The method of claim 1, further comprising: while the wearable device is operating in the second image-management mode, displaying, on the display of the wearable device, a critical indication that the wearable device has been forced to operate in the second image-management mode.
9. The method of claim 1, further comprising: while operating the wearable device in the second image-management mode: receiving, at the wearable device, a storage request to add a new image to a storage location at the wearable device; and in response to receiving the request, blocking the user from being able to add the new image to the storage location at the wearable device.
10. A wearable device comprising: a display; one or more processors; and memory comprising instructions that, when executed by the wearable device, cause performance of operations for: in accordance with a first determination that a first amount of storage is less than or equal to a first storage-depletion threshold: providing an indication, at the wearable device, that a first image-management mode is available, wherein, when the wearable device is operating in the first image-management mode, the wearable device is caused to delete one or more images that are not of a predetermined protected image type; while a current amount of storage at the wearable device remains less than a first repletion threshold that is greater than or equal to the first depletion threshold: causing display of a secondary indication at a second electronic device, which is in communication with the wearable device, wherein the secondary indication includes an information indicating that the first image-management mode is available for the wearable device; and in accordance with a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first storage-depletion threshold: automatically, and without a request from a user of the wearable device, operating the wearable device in a second image-management mode, wherein when the wearable device is operating in the second image-management mode: blocking the user from storing any additional images at the wearable device until a repletion determination is made that a respective amount of storage remaining at the wearable device is greater than or equal to the second storage-depletion threshold.
11. The wearable device of claim 10, wherein the operations further include: before the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold: in accordance with an intermediate determination that an intermediate amount of storage at the wearable device is less than or equal to an intermediate storage-depletion threshold, the intermediate storage-depletion threshold between the first storage-depletion threshold and the second storage-depletion threshold: providing a new indication, at the wearable device, distinct from the indication provided in accordance with the first determination, that the first image-management mode is available.
12. The wearable device of claim 10, wherein the operations further include: while the wearable device is operating in the first image-management mode: deleting one or more deletion-candidate images from the wearable device that are not of the predetermined protected image type until enough deletion-candidate images have been deleted such that a post-deletion amount of storage remaining at the wearable device is greater than the first storage-depletion threshold.
13. The wearable device of claim 12, wherein the operations further include: while the wearable device is in the first image-management mode: backing up at least one of the one or more deletion-candidate images that are not of the predetermined protected image type to another electronic device before deleting the one or more deletion-candidate images.
14. The wearable device of claim 10, wherein new images captured at the wearable device are configured to be stored locally and are not configured to be backed up to another electronic device while the wearable device is configured to operate in a default image-management mode that is distinct from the first and second image-management modes.
15. The wearable device of claim 10, wherein the secondary indication includes additional information that is not included in the indication displayed at the wearable device.
16. A non-transitory, computer-readable storage medium including instructions that, when executed

by a wearable device, cause the wearable device to perform or cause performance of operations for: in accordance with a first determination that a first amount of storage is less than or equal to a first storage-depletion threshold: providing an indication, at the wearable device, that a first image-management mode is available, wherein, when the wearable device is operating in the first image-management mode, the wearable device is caused to delete one or more images that are not of a predetermined protected image type; while a current amount of storage at the wearable device remains less than a first repletion threshold that is greater than or equal to the first depletion threshold: causing display of a secondary indication at a second electronic device, which is in communication with the wearable device, wherein the secondary indication includes information indicating that the first image-management mode is available for the wearable device; and in accordance with a second determination that an updated amount of storage at the wearable device is less than or equal to a second storage-depletion threshold, the second storage-depletion threshold associated with a smaller amount of storage than the first storage-depletion threshold:

automatically, and without a request from a user of the wearable device, operating the wearable device in a second image-management mode, wherein when the wearable device is operating in the second image-management mode: blocking the user from storing any additional images at the wearable device until a repletion determination is made that a respective amount of storage remaining at the wearable device is greater than or equal to the second storage-depletion threshold.

17. The non-transitory, computer-readable storage medium of claim 16, wherein the operations further include: before the second determination that the updated amount of storage at the wearable device is less than or equal to the second storage-depletion threshold: in accordance with an intermediate determination that an intermediate amount of storage at the wearable device is less than or equal to an intermediate storage-depletion threshold, the intermediate storage-depletion threshold between the first storage-depletion threshold and the second storage-depletion threshold: providing a new indication, at the wearable device, distinct from the indication provided in accordance with the first determination, that the first image-management mode is available.

18. The non-transitory, computer-readable storage medium of claim 16, wherein the operations further include: while the wearable device is operating in the first image-management mode: deleting one or more deletion-candidate images from the wearable device that are not of the predetermined protected image type until enough deletion-candidate images have been deleted such that a post-deletion amount of storage remaining at the wearable device is greater than the first storage-depletion threshold.

19. The non-transitory, computer-readable storage medium of claim 18, wherein the operations further include: while the wearable device is in the first image-management mode: backing up at least one of the one or more deletion-candidate images that are not of the predetermined protected image type to another electronic device before deleting the one or more deletion-candidate images.

20. The non-transitory, computer-readable storage medium of claim 16, wherein new images captured at the wearable device are configured to be stored locally and are not configured to be backed up to another electronic device while the wearable device is configured to operate in a default image-management mode that is distinct from the first and second image-management modes.
