

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384227
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Matsumoto; Subaru

Vehicle air conditioning system

Abstract

A vehicle air conditioning system, having a simple structure and preferable reliability, and capable of suppressing increases in energy consumption and cost, is provided. The vehicle air conditioning system includes: an air conditioning unit, configured to adjust a temperature in a vehicle compartment and including a blower and a temperature control module; and a dehumidification device, configured to adjust a humidity in the vehicle compartment, disposed between the blower and an evaporator of the temperature control module, and enabling a part of air conditioning air flowing in from the blower to flow into the dehumidification device.

Inventors:	Matsumoto; Subaru (Saitama, JP)
Applicant:	Honda Motor Co., Ltd. (Tokyo, JP)
Family ID:	90627838
Assignee:	Honda Motor Co., Ltd. (Tokyo, JP)
Appl. No.:	18/350772
Filed:	July 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240123798 A1	Apr. 18, 2024

Foreign Application Priority Data

CN	202211259416.6	Oct. 14, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: B60H3/02 (20060101); B60H1/00 (20060101)

U.S. Cl.:

CPC **B60H3/024** (20130101); **B60H1/00464** (20130101); **B60H1/00828** (20130101);

Field of Classification Search

CPC: B60H (3/024); B60H (1/00464); B60H (1/00828); B60H (1/00007); B60H (1/00507);
 B60H (2001/00092)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2014/0338883	12/2013	Watanabe	165/59	B60H 3/024
2018/0105021	12/2017	Tsunoda	N/A	B60H 1/00921

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4567478	12/2009	JP	N/A
2016064695	12/2015	JP	N/A
2016135653	12/2015	JP	N/A
20110011100	12/2010	KR	B60H 1/3207
WO-2014002377	12/2013	WO	B60H 1/00392
WO-2014024332	12/2013	WO	B01D 53/0407

Primary Examiner: Duke; Emmanuel E

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of China application serial no. 202211259416.6, filed on Oct. 14, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to a vehicle air conditioning system.

Description of Related Art

(3) The dehumidification device may absorb air in a vehicle for dehumidification to control the humidity in the vehicle. However, in the case where an independent dehumidification device is disposed, the number of required components in the vehicle is increased, and the configuration of the three types of air duct systems of air intake, dehumidified air, and humidified exhaust of the dehumidification device also affects the element layout of other systems in the vehicle. Therefore, it is necessary to integrate the dehumidification device and other systems into an integrated system

component for installation.

(4) On the other hand, the vehicle air conditioning system is an essential device for a vehicle with a closed vehicle compartment structure and may be used to adjust the ambient temperature in the vehicle compartment, such as providing cool or warm vehicle compartment temperature. When the dehumidification device is disposed in the vehicle air conditioning system, if air from an air inlet (including an external air inlet and an internal air inlet) of the vehicle air conditioning system passes through the dehumidification device, the external air may contain water droplets, causing a risk of deterioration of the membrane elements of the dehumidification device, so it is necessary to adopt countermeasures that are water repellent.

SUMMARY

(5) The disclosure provides a vehicle air conditioning system, which includes: an air conditioning unit, configured to adjust a temperature in a vehicle compartment and including a blower and a temperature control module; and a dehumidification device, configured to adjust a humidity in the vehicle compartment, disposed between the blower and an evaporator of the temperature control module, and enabling a part of air conditioning air flowing in from the blower to flow into the dehumidification device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a block diagram of a vehicle air conditioning system according to an embodiment of the disclosure.
- (2) FIG. 1B is a schematic view of an air flow situation of the vehicle air conditioning system of FIG. 1A in a cooling mode.
- (3) FIG. 1C is a schematic view of an air flow situation of the vehicle air conditioning system of FIG. 1A in a warming mode.
- (4) FIG. 2 is a schematic structural view of the vehicle air conditioning system of FIG. 1A.
- (5) FIG. 3A is a schematic structural view of a dehumidification device of the vehicle air conditioning system of FIG. 2.
- (6) FIG. 3B is a schematic side view of the dehumidification device of FIG. 3A.
- (7) FIG. 3C is an exploded view of the dehumidification device of FIG. 3A.
- (8) FIG. 4A to FIG. 4C are schematic cross-sectional views of the dehumidification device of FIG. 3A in different operating modes.
- (9) FIG. 5A and FIG. 5B are schematic views comparing channel cross-sectional areas of different air flows of the vehicle air conditioning system of FIG. 2.
- (10) FIG. 6 is a schematic view of relative positions of the dehumidification device and a blower of the vehicle air conditioning system of FIG. 2.
- (11) FIG. 7A and FIG. 7B are schematic views of the dehumidification device of FIG. 3A when a moisture-absorbing surface is disposed in different directions.
- (12) FIG. 8A is a schematic structural view of another vehicle air conditioning system of FIG. 1A.
- (13) FIG. 8B and FIG. 8C are schematic cross-sectional views of the dehumidification device of FIG. 3A in a warming mode.
- (14) FIG. 9A to FIG. 9E are schematic cross-sectional views of different vehicle air conditioning systems of FIG. 1A.
- (15) FIG. 10A is a block diagram of a vehicle air conditioning system according to another embodiment of the disclosure.
- (16) FIG. 10B is a schematic view of an air flow situation of the vehicle air conditioning system of FIG. 10A in a cooling mode.
- (17) FIG. 10C is a schematic view of an air flow situation of the vehicle air conditioning system of

FIG. 10A in a warming mode.

(18) FIG. 11A is a schematic structural view of a dehumidification device of the vehicle air conditioning system of FIG. 10A.

(19) FIG. 11B is an exploded view of the dehumidification device of FIG. 11A.

(20) FIG. 12A to FIG. 12C are schematic cross-sectional views of the dehumidification device of FIG. 11A when the vehicle air conditioning system of FIG. 10A is in different operating modes.

(21) FIG. 13 is a block diagram of a vehicle air conditioning system according to yet another embodiment of the disclosure.

(22) FIG. 14A to FIG. 14C are schematic cross-sectional views of the dehumidification device of FIG. 11A when the vehicle air conditioning system of FIG. 13 is in different operating modes.

DESCRIPTION OF THE EMBODIMENTS

(23) The disclosure provides a vehicle air conditioning system, which has a simple structure and preferable reliability, and can suppress increases in energy consumption and cost.

(24) The disclosure provides a vehicle air conditioning system, which includes: an air conditioning unit, configured to adjust a temperature in a vehicle compartment and including a blower and a temperature control module; and a dehumidification device, configured to adjust a humidity in the vehicle compartment, disposed between the blower and an evaporator of the temperature control module, and enabling a part of air conditioning air flowing in from the blower to flow into the dehumidification device.

(25) In an embodiment of the disclosure, the air conditioning unit further includes a main flow channel and a branch flow channel, the main flow channel is communicated with an air intake end portion and an air supply end portion of the air conditioning unit and is used for the air conditioning air flowing in from the blower to flow to the temperature control module, and the branch flow channel diverges from the main flow channel, is communicated with the main flow channel and the dehumidification device, and is used for the part of the air conditioning air flowing in from the blower to flow into the dehumidification device.

(26) In an embodiment of the disclosure, an air volume of the part of the air conditioning air flowing from the branch flow path into the dehumidification device is less than or equal to an air volume of another part of air conditioning air that does not flow into the dehumidification device in the main flow path.

(27) In an embodiment of the disclosure, the dehumidification device includes: an air volume adjusting mechanism, used to form one of an air inflow channel and an air discharge channel, wherein the air inflow channel is communicated with the branch flow channel; an air path switching mechanism, used to form other one of the air inflow channel and the air discharge channel; a dehumidification element, disposed on a flow path of the part of the air conditioning air flowing in from the blower between the air volume adjusting mechanism and the air path switching mechanism.

(28) In an embodiment of the disclosure, the dehumidification device is disposed on a connection channel connecting the blower of the air conditioning unit and the temperature control module.

(29) In an embodiment of the disclosure, the air volume adjusting mechanism is used to form the air inflow channel, the air path switching mechanism is used to form the air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle.

(30) In an embodiment of the disclosure, the connection channel is formed as a part of the main flow channel, the branch flow channel is communicated with the connection channel, the air volume adjusting mechanism includes a damper structure configured to adjust a degree of opening, the degree of opening of the damper structure is used to form and adjust a size of an adjustable

cross-sectional area of an inflow pathway of the branch flow channel, and the adjustable cross-sectional area of the inflow pathway of the branch flow channel is less than or equal to half of a cross-sectional area of the connection channel.

(31) In an embodiment of the disclosure, the dehumidification device installed in the connection channel is installed on a side of a housing peripheral wall opposite to an air supply port of the blower for connecting the main flow channel in a centrifugal direction.

(32) In an embodiment of the disclosure, the dehumidification element has a moisture-absorbing surface, and the moisture-absorbing surface is disposed parallel to a gravitational direction and perpendicular to a front side direction of a vehicle.

(33) In an embodiment of the disclosure, the dehumidification element has a moisture-absorbing surface, the moisture-absorbing surface is disposed to be inclined relative to a gravitational direction and a front side direction of a vehicle, and the moisture-absorbing surface faces diagonally below a vehicle front side.

(34) In an embodiment of the disclosure, the air volume adjusting mechanism and the air path switching mechanism both include a damper structure configured to adjust a degree of opening, and the dehumidification device further includes: an actuator; and a connection mechanism, wherein the actuator connects the air volume adjusting mechanism and the air path switching mechanism through connection mechanism to control the degrees of opening of the damper structures of the air volume adjusting mechanism and the air path switching mechanism.

(35) In an embodiment of the disclosure, the degrees of opening of the damper structures of the air volume adjusting mechanism and the air path switching mechanism are linked through the connection mechanism.

(36) In an embodiment of the disclosure, the vehicle air conditioning system further includes a partition. The partition is disposed in the main flow channel and is used to divert the part of the air conditioning air in the main flow channel to the branch flow channel.

(37) In an embodiment of the disclosure, the partition faces an air inlet of the dehumidification device, and the partition extends from an end of the air inlet of the dehumidification device to other end of the air inlet of the dehumidification device.

(38) In an embodiment of the disclosure, the partition faces an air inlet and an exhaust port of the dehumidification device, and the partition extends from an end of the air inlet of the dehumidification device to an end of the exhaust port of the dehumidification device away from the air inlet.

(39) In an embodiment of the disclosure, the partition faces an air inlet and an exhaust port of the dehumidification device, and the partition extends from an upstream side of an air supply port of the blower for connecting the main flow channel to an end of the exhaust port of the dehumidification device away from the air inlet.

(40) In an embodiment of the disclosure, the vehicle air conditioning system further includes a windproof plate. The windproof plate is disposed in the main flow channel and is connected to the partition, and is used to separate the air inflow channel and the air discharge channel.

(41) In an embodiment of the disclosure, the vehicle air conditioning system further includes a main flow air volume distribution mechanism. The main flow air volume distribution mechanism is disposed in the main flow channel and is used to control an air volume of air conditioning air in the main flow channel.

(42) In an embodiment of the disclosure, the main flow air volume distribution mechanism is located on a connection portion of an air supply port of the blower for connecting the main flow channel and the connection channel, and extends toward an upstream side of the air supply port of the blower.

(43) In an embodiment of the disclosure, the main flow air volume distribution mechanism is located on a flow path of dehumidified dried air conditioning air flowing from an exhaust port of the dehumidification device to the temperature control module, and the dehumidified air

conditioning air merges with another part of air conditioning air that does not flow into the dehumidification device in the main flow channel after passing through the main flow air volume distribution mechanism.

(44) In an embodiment of the disclosure, the dehumidification device is disposed in front of the evaporator and is configured in the temperature control module.

(45) In an embodiment of the disclosure, the air conditioning unit has a drain port for discharging condensed water generated in the evaporator to an outside of a vehicle, and heated humidified air in the dehumidification device is discharged out of the vehicle through the drain port and shares a same path with a discharge of the condensed water generated in the evaporator.

(46) In an embodiment of the disclosure, the air volume adjusting mechanism is used to form the air inflow channel, the air path switching mechanism is used to form the air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle.

(47) In an embodiment of the disclosure, the air path switching mechanism is used to open and close a communication port of the branch flow path, so that a part of air conditioning air flowing in from the blower flows into an air inlet of the dehumidification device to switch between the air volume adjusting mechanism and the air path switching mechanism, wherein when the dehumidification device executes dehumidification, the air path switching mechanism is used to form the air inflow channel, and the air volume adjusting mechanism is used to form the air discharge channel, and when the dehumidification device executes regeneration, the air volume adjusting mechanism is used to form the air inflow channel, and the air path switching mechanism is used to form the air discharge channel.

(48) In an embodiment of the disclosure, there are multiple dehumidification devices, which include a first dehumidification device and a second dehumidification device, wherein when dehumidification is performed through a dehumidification element of one of the first dehumidification device and the second dehumidification device, other one of the first dehumidification device and the second dehumidification device heats the dehumidification element of the other one to regenerate the other one of the first dehumidification device and the second dehumidification device.

(49) In an embodiment of the disclosure, the dehumidification device alternately switches a cycle time of dehumidification or regeneration of the first dehumidification device and the second dehumidification device in batches based on information of a temperature and humidity sensor disposed on the air inflow channel or the air discharge channel of at least any one of the first dehumidification device and the second dehumidification device.

(50) In an embodiment of the disclosure, the first dehumidification device and the second dehumidification device alternately switch to execute a dehumidification or regeneration process at a predetermined time interval.

(51) In an embodiment of the disclosure, the air volume adjusting mechanism of any one of the first dehumidification device and the second dehumidification device is used to form the air inflow channel, includes a damper structure configured to adjust a degree of opening, and is used to adjust an air volume of the part of the air conditioning air flowing into the air inflow channel of the any one, the air path switching mechanism is used to form the air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle. When dehumidification is performed through the first dehumidification device, the degree

of opening of the damper structure of the first dehumidification device is greater than the degree of opening of the damper structure of the second dehumidification device, the air path switching mechanism of the first dehumidification device switches the air discharge channel of the first dehumidification device to the return air path of the first dehumidification device, and the air path switching mechanism of the second dehumidification device switches the air discharge channel of the second dehumidification device to the discharge air path of the second dehumidification device. When dehumidification is performed through the second dehumidification device, the degree of opening of the damper structure of the second dehumidification device is greater than the degree of opening of the damper structure of the first dehumidification device, the air path switching mechanism of the second dehumidification device switches the air discharge channel of the second dehumidification device to the return air path of the second dehumidification device, and the air path switching mechanism of the first dehumidification device switches the air discharge channel of the first dehumidification device to the discharge air path of the first dehumidification device.

(52) In an embodiment of the disclosure, the air volume adjusting mechanism of any one of the first dehumidification device and the second dehumidification device includes a damper structure configured to adjust a degree of opening, and the air path switching mechanism is used to open and close a communication port of the branch flow channel, so that a part of air conditioning air flowing in from the blower flows into an air inlet of the dehumidification device to switch between the air volume adjusting mechanism and the air path switching mechanism of the any one, wherein when the first dehumidification device executes dehumidification, the air path switching mechanism of the first dehumidification device is used to form the air inflow channel of the first dehumidification device, the air volume adjusting mechanism of the first dehumidification device is used to form the air discharge channel of the first dehumidification device, the air volume adjusting mechanism of the second dehumidification device is used to form the air inflow channel of the second dehumidification device, the air path switching mechanism of the second dehumidification device is used to form the air discharge channel of the second dehumidification device, and the degree of opening of the damper structure of the first dehumidification device is greater than the degree of opening of the damper structure of the second dehumidification device, and when the second dehumidification device executes dehumidification, the air path switching mechanism of the second dehumidification device is used to form the air inflow channel of the second dehumidification device, the air volume adjusting mechanism of the second dehumidification device is used to form the air discharge channel of the second dehumidification device, the air volume adjusting mechanism of the first dehumidification device is used to form the air inflow channel of the first dehumidification device, the air path switching mechanism of the first dehumidification device is used to form the air discharge channel of the first dehumidification device, and the degree of opening of the damper structure of the second dehumidification device is greater than the degree of opening of the damper structure of the first dehumidification device.

(53) In an embodiment of the disclosure, the dehumidification device has a built-in heater configured to directly heat through energization.

(54) Based on the above, in the vehicle air conditioning system according to an embodiment of the disclosure, the dehumidification device may be integrated in the vehicle air conditioning system as the humidity adjustment unit through sharing the structures of the blower and the housing with the vehicle air conditioning system, and through sharing the configuration of the air flow channel of the vehicle air conditioning system, increases in ventilation resistance can be suppressed and increases in power consumption of the blower can be suppressed. At the same time, through simplifying necessary components of the vehicle air conditioning system, even lower power consumption can be ensured while suppressing increases in cost. Also, through disposing the dehumidification device on the side of the housing peripheral wall opposite to the air supply port of the blower for connecting the main flow channel in the centrifugal direction and configuring the moisture-absorbing surface of the dehumidification element of the dehumidification device to be

parallel to the gravitational direction or facing diagonally below the vehicle front side and inclined relative to the gravitational direction, the impact caused by external water splashing or water droplets staying on the dehumidification element can be prevented, thereby reducing the risk of deterioration of elements of the dehumidification device, so as to have preferable reliability.

(55) FIG. 1A is a block diagram of a vehicle air conditioning system according to an embodiment of the disclosure; FIG. 1B is a schematic view of an air flow situation during a process of cooling air in the vehicle air conditioning system of FIG. 1A; FIG. 1C is a schematic view of an air flow situation during a process of warming the air in the vehicle air conditioning system of FIG. 1A; FIG. 2 is a schematic structural view of the vehicle air conditioning system of FIG. 1A; FIG. 3A is a schematic structural view of a dehumidification device of the vehicle air conditioning system of FIG. 2; FIG. 3B is a schematic side view of the dehumidification device of FIG. 3A; FIG. 3C is an exploded view of the dehumidification device of FIG. 3A; FIG. 4A to FIG. 4C are schematic cross-sectional views of the dehumidification device of FIG. 3A in different operating modes; FIG. 5A and FIG. 5B are schematic views comparing channel cross-sectional areas of different air flows of the vehicle air conditioning system of FIG. 2; FIG. 6 is a schematic view of relative positions of the dehumidification device and a blower of the vehicle air conditioning system of FIG. 2; FIG. 7A and FIG. 7B are schematic views of the dehumidification device of FIG. 3A when a moisture-absorbing surface is disposed in different directions.

(56) Please refer to FIG. 1A. In the embodiment, a vehicle air conditioning system **200** includes an air conditioning unit **210** and a dehumidification device **100** as a humidity adjustment unit. Specifically, the air conditioning unit **210** (heating, ventilation, and air conditioning, HVAC) can adjust the temperature in a vehicle compartment and includes an air intake end portion **211**, an air duct mechanism **212**, a blower **213**, a connection channel **214**, a temperature control module **215**, and an air supply end portion **216**. Further, as shown in FIG. 1A to FIG. 4C, the air intake end portion **211** of the air conditioning unit **210** includes an outer air intake end portion **211a** and an inner air intake end portion **211c**. The outer air intake end portion **211a** is used to absorb outside air OAR, the inner air intake end portion **211c** is used to absorb interior air IAR. The blower **213** is installed in the air duct mechanism **212** and may be controlled to be activated to create a negative pressure environment on the upstream side of the blower **213** and create a positive pressure environment on the downstream side of the blower **213**, thereby generating an air flow flowing from the outer air intake end portion **211a** or the inner air intake end portion **211c** through the air duct mechanism **212**, the connection channel **214**, and the temperature control module **215** to the air supply end portion **216**, wherein the outside air OAR and the interior air IAR merge to form air conditioning air AR after passing through the blower **213**. Moreover, in the embodiment, as shown in FIG. 1B and FIG. 1C, the temperature control module **215** has a refrigerating unit **215a** and a heating unit **215c**, which may cool or warm the air conditioning air AR flowing into the temperature control module **215** through the blower **213** according to requirements, so as to provide a comfortable ambient temperature in the vehicle compartment.

(57) Generally speaking, as shown in FIG. 1B, the refrigerating unit **215a** of the temperature control module **215** may be an evaporator of a refrigeration cycle system, has an inlet for refrigerant inflow and an outlet for refrigerant outflow, and is connected to a compressor **215b** to circulate the refrigerant for use. During the process of cooling the air conditioning air AR, the refrigerating unit **215a** exchanges heat between the air conditioning air AR from the blower **213** and the refrigerant, and the refrigerant absorbs heat to cool the air conditioning air AR. During the cooling process, that is, in a cooling mode of the vehicle air conditioning system **200**, since water vapor in the air conditioning air AR is converted into water droplets at the same time, the refrigerating unit **215a** of the temperature control module **215** may also have the function of dehumidification, and as shown in FIG. 1B, a comfortable ambient humidity in the vehicle compartment may be implemented without activating the dehumidification device **100**.

(58) On the other hand, during the process of warming the air flow, that is, in a warming mode of

the vehicle air conditioning system **200**, the air conditioning air AR from the blower **213** may be heated and warmed up through turning off the refrigerating unit **215a** and the compressor **215b** of the refrigeration cycle system and activating the heating unit **215c**. For example, in the embodiment, the heating unit **215c** may be a heater having a thermistor with a positive temperature coefficient (PTC) and may directly heat the air, a heater core that dissipates heat through heat exchange between a refrigerant heated by exhaust heat of an engine and passing air, a heater core that dissipates heat through heat exchange between a refrigerant heated by an electric heater and passing air, etc. In addition, when the air conditioning unit **210** is a heat pump type, the heating unit **215c** may be an indoor condenser, and the refrigerant compressed and heated by the compressor **215b** flows into the indoor condenser. In this case, when the air from the blower **213** passes through the heating unit **215c**, the air may exchange heat with the high temperature and high pressure refrigerant of the indoor condenser, and the refrigerant dissipates heat, which may also warm the air.

(59) However, in the warming mode of the vehicle air conditioning system **200**, when the external air temperature is low and the cooling unit **215c** operates, frost forms on the cooling unit **215c**, so the cooling unit **215c** cannot be used for dehumidification. Therefore, as shown in FIG. **1C**, dehumidification needs to be performed through activating the dehumidification device **100**, so as to implement a comfortable ambient humidity in the vehicle compartment.

(60) Furthermore, as shown in FIG. **1A** and FIG. **3C**, in the embodiment, the dehumidification device **100** has a dehumidification element DHE, which can adjust the humidity in the vehicle compartment. For example, as shown in FIG. **3C**, in the embodiment, the dehumidification element DHE is a thin dehumidification element and may contain composite material HASClay® synthesized from amorphous aluminum silicate and low crystallinity clay as an adsorbent to absorb moisture in the air, thereby dehumidifying air passing through the dehumidification element DHE. The composite material HASClay® has the advantages of high safety, high adsorption performance within a low humidity range, high speed adsorption or regeneration cycle, high regeneration efficiency, low power consumption regeneration, low ventilation resistance, high reliability, high heat resistance, light weight, and low cost. In addition, as the adsorbent, besides the composite material HASClay®, a hygroscopic agent such as zeolite, silica gel, and other polymer adsorbents that have high hygroscopicity under a specified humidity environment may also be used. In addition, the thin dehumidification element may, for example, be a honeycomb-shaped base material or a mesh-shaped base material, as long as a component that can be heated through energization is used as a base material that supports the hygroscopic agent. In addition, the thin dehumidification element may also have another type of structure, wherein a predetermined hygroscopic agent is carried on a pleated and air permeable sheet to form a moisture absorption portion, and a heater (a heating portion) of the thin dehumidification element directly contacts the carried moisture absorption portion and heats the moisture absorption portion. In this case, the heater is a plate-shaped heater extending along the direction of the air flow and directly contacts the moisture absorption portion in almost the entire longitudinal direction. Moreover, through using the structural configuration of the thin dehumidification element, the dehumidification device **100** can implement the smallest system volume under the condition of having the same dehumidification capacity. In other words, although the system volume changes according to the dehumidification capacity, since the thin dehumidification elements may be disposed in series, even if the dehumidification device **100** is provided with multiple thin dehumidification elements in order to increase the dehumidification capacity, the size increase caused by the series connection may still be controlled within a small range.

(61) On the other hand, when the amount of moisture adsorbed increases with the lapse of time, the adsorption capacity gradually decreases. Under the above condition, the dehumidification device **100** regenerates the dehumidification element DHE by directly heating the dehumidification element DHE through energization after moisture absorption through a built-in heater (not shown)

disposed therein to remove moisture from the adsorbent. In this way, the dehumidification element DHE may be directly heated through the built-in heater to replace air heating, so the regeneration process of the dehumidification element DHE may be efficiently completed in a short time. Also, in the embodiment, the built-in heater has a thermistor with a positive temperature coefficient (PTC) whose resistance value increases as the temperature rises. In this way, the built-in heater has a self-regulating characteristic that suppresses the temperature rise to a predetermined temperature during the regeneration process. Thereby, it is possible to suppress smoke and fire due to abnormal heating, while providing the necessary regeneration temperature to the dehumidification element DHE. In addition, since the dehumidification device **100** is located on the downstream side of the blower **213** and is in a positive pressure environment, heated humidified air MAR can leave the dehumidification device **100** based on ambient pressure, so that the adsorption capacity of the dehumidification element DHE is restored, thereby regenerating the dehumidification element DHE.

(62) Moreover, as shown in FIG. **1A** to FIG. **2**, in the embodiment, the dehumidification device **100** is disposed between the blower **213** and the temperature control module **215**, and a part of the air conditioning air AR flowing in from the blower **213** flows into the dehumidification device **100**. Moreover, as shown in FIG. **1A**, after the air conditioning air AR flowing into the dehumidification device **100** is dehumidified by the dehumidification device **100**, dried air conditioning air DAR dehumidified by the dehumidification device **100** may return to mix with the air conditioning air AR that is not dehumidified. In this way, the vehicle air conditioning system **200** may control the humidity of the air conditioning air AR flowing out of the air supply end portion **216** through mixing the dried air conditioning air DAR dehumidified by the dehumidification device **100** and the air conditioning air AR that is not dehumidified in a main flow channel MC, so that the dehumidification device **100** can be used as the humidity adjustment unit of the vehicle air conditioning system **200**. Moreover, through enabling a part of the air conditioning air AR pumped by the blower **213** of the air conditioning unit **210** to the temperature control module **215** to flow to the dehumidification device **100**, the dehumidification device **100** does not need to be equipped with a dedicated air supply component, which can simplify the structure and save cost.

(63) The control process and the specific structure when the dehumidification device **100** is used as the humidity adjustment unit of the vehicle air conditioning system **200** will be further explained below with reference to FIG. **3A** to FIG. **4C**.

(64) Specifically, as shown in FIG. **1A** and FIG. **3A** to FIG. **4C**, in the embodiment, the dehumidification device **100** is disposed on the connection channel **214** connecting the blower **213** of the air conditioning unit **210** and the temperature control module **215**. In this way, the impact on the size of the vehicle air conditioning system **200** when the dehumidification device **100** is installed therein can be minimized through using a dead zone between the blower **213** and the temperature control module **215**.

(65) Further, as shown in FIG. **1A** and FIG. **4A** to FIG. **4C**, the air conditioning unit **210** also includes the main flow channel MC and a branch flow channel BC. The main flow channel MC is communicated with the air intake end portion **211** and the air supply end portion **216** of the air conditioning unit **210** and is used for the air conditioning air AR flowing in to flow from the blower **213** to the temperature control module **215**. The branch flow channel BC diverges from the main flow channel MC, is communicated with the main flow channel MC and the dehumidification device **100**, and is used for a part of the air conditioning air AR flowing in from the blower **213** to flow into the dehumidification device **100**. Moreover, as shown in FIG. **4A** to FIG. **4C**, in the embodiment, the connection channel **214** is formed as a part of the main flow channel MC, and the branch flow channel BC is communicated with the connection channel **214**.

(66) Moreover, as shown in FIG. **3A** to FIG. **4C**, in the embodiment, the dehumidification device **100** further includes an air volume adjusting mechanism VA and an air path switching mechanism SW, wherein the air volume adjusting mechanism VA is used to form one of an air inflow channel

IN and an air discharge channel EX. The air path switching mechanism SW is used to form the other one of the air inflow channel IN and the air discharge channel EX, wherein the air inflow channel IN is communicated with the branch flow channel BC and may be used for the air conditioning air AR passing through the branch flow channel BC to flow into the dehumidification device **100**. The dehumidification element DHE is disposed on a flow path of the part of the air conditioning air AR flowing in from the blower **213** between the air volume adjusting mechanism VA and the air path switching mechanism SW.

(67) Furthermore, as shown in FIG. 3A to FIG. 4C, in the embodiment, the air volume adjusting mechanism VA is used to form the air inflow channel IN, and the air path switching mechanism SW is used to form the air discharge channel EX. For example, in the embodiment, the air volume adjusting mechanism VA and the air path switching mechanism SW both include a damper structure DP that can adjust the degree of opening, and as shown in FIG. 3C, the dehumidification device **100** also includes an actuator AC. The actuator AC is connected to the damper structure DP of the air volume adjusting mechanism VA and the damper structure DP of the air path switching mechanism SW through a mechanism. In this way, as shown in FIG. 3C to FIG. 4C, the actuator AC may be used to control the degree of opening of the damper structure DP to adjust the air volume of the air conditioning air AR flowing into the dehumidification device **100** and also control the degree of opening of the damper structure DP of the air path switching mechanism SW to switch the air discharge channel EX between a return air path RP and a discharge air path EP, wherein the return air path RP is an air path for returning the dehumidified dried air conditioning air DAR back to the main flow path MC of the air conditioning unit **210**, and the discharge air path EP is an air path for discharging the humidified air MAR generated after heating the dehumidification device **100** to the outside of the vehicle.

(68) In this way, the dehumidification device **100** may switch between dehumidification and regeneration processes through the air path selection of the air path switching mechanism SW, and the dried air conditioning air DAR dehumidified by the dehumidification device **100** can be adjusted to be supplied at a predetermined air volume and the humidified air MAR generated after heating the dehumidification device **100** may be discharged at a predetermined air volume through controlling the degree of opening of the damper structure DP of the air volume adjusting mechanism VA.

(69) Further, in the embodiment, there are multiple dehumidification devices **100**, including a first dehumidification device **100-1** and a second dehumidification device **100-2**, wherein when dehumidification is performed through the dehumidification element DHE of one of the first dehumidification device **100-1** and the second dehumidification device **100-2**, the other one of the first dehumidification device **100-1** and the second dehumidification device **100-2** heats the dehumidification element DHE of the other one to regenerate the other one of the first dehumidification device **100-1** and the second dehumidification device **100-2**. In this way, the dehumidification device **100** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100** through both the first dehumidification device **100-1** and the second dehumidification device **100-2** without interruption, and can also intermittently regenerate the first dehumidification device **100-1** and the second dehumidification device **100-2** respectively, thereby maintaining preferable dehumidification performance all the time.

(70) Further, as shown in FIG. 4A, in the embodiment, when the vehicle air conditioning system **200** cools the air, that is, in the cooling mode of the vehicle air conditioning system **200**, the dehumidification device **100** does not operate. At this time, in the dehumidification device **100**, the air volume adjusting mechanism VA of the first dehumidification device **100-1**, the air volume adjusting mechanism VA of the second dehumidification device **100-2**, the built-in heater of the first dehumidification device **100-1**, and the built-in heater of the second dehumidification device **100-2** are all turned off, and the air discharge channels EX of the air path switching mechanism SW of the first dehumidification device **100-1** and the air path switching mechanism SW of the second

dehumidification device **100-2** are both switched to the discharge air paths EP with the return air paths RP closed.

(71) On the other hand, when the vehicle air conditioning system **200** warms the air, that is, in the warming mode of the vehicle air conditioning system **200**, the dehumidification device **100** operates and sequentially switches in turn the sizes of the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** and the air volume adjusting mechanism VA of the second dehumidification device **100-2**, opening states of the built-in heater of the first dehumidification device **100-1** and the built-in heater of the second dehumidification device **100-2**, and switching states of the air path switching mechanism SW of the first dehumidification device of **100-1** and the air path switching mechanism SW of the second dehumidification device **100-2** between different paths.

(72) For example, as shown in FIG. 4B and FIG. 4C, in the embodiment, when dehumidification is performed through the first dehumidification device **100-1**, as shown in FIG. 4B, the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** is opened, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **100** for dehumidification, and the air path switching mechanism SW of the first dehumidification device **100-1** switches the air discharge channel EX of the first dehumidification device **100-1** to the return air path RP of the first dehumidification device **100-1**, so that the dried air conditioning air DAR dehumidified by the first dehumidification device **100-1** can return to the main flow channel MC of the air conditioning unit **210**. Also, at the same time, the built-in heater of the second dehumidification device **100-2** is also turned on to heat the dehumidification element DHE of the second dehumidification device **100-2**, so as to regenerate the second dehumidification device **100-2**. At this time, as shown in FIG. 4C, the air path switching mechanism SW of the second dehumidification device **100-2** switches the air discharge channel EX of the second dehumidification device **100-2** to the discharge air path EP of the second dehumidification device **100-2**, and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** is also opened, so that the humidified air MAR generated after heating the second dehumidification device **100-2** can leave the second dehumidification device **100-2** based on the ambient pressure and be discharged to the outside of the vehicle.

(73) Similarly, in the embodiment, when dehumidification is performed through the second dehumidification device **100-2**, the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** is also opened as shown in FIG. 4B, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **100** for dehumidification, and the air path switching mechanism SW of the second dehumidification device **100-2** switches the air discharge channel EX of the second dehumidification device **100-2** to the return air path RP of the second dehumidification device **100-2**, so that the dried air conditioning air DAR dehumidified by the second dehumidification device **100-2** can return to the main flow channel MC of the air conditioning unit **210**. Also, at the same time, the built-in heater of the first dehumidification device **100-1** is also turned on to heat the dehumidification element DHE of the first dehumidification device **100-1**, so as to regenerate the first dehumidification device **100-1**. At this time, the air path switching mechanism SW of the first dehumidification device **100-1** switches the air discharge channel EX of the first dehumidification device **100-1** to the discharge air path EP of the first dehumidification device **100-1** as shown in FIG. 4C, and the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** is also opened, so that the humidified air MAR generated after heating the second dehumidification device **100-2** can leave the second dehumidification device **100-2** based on the ambient pressure and be discharged to the outside of the vehicle.

(74) On the other hand, in the embodiment, the degree of opening of the damper structure DP of the air volume adjusting mechanism VA can be used to form and adjust the size of an adjustable cross-

sectional area of an inflow pathway of the branch flow channel BC, so that the sizes of the degrees of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** determine the air volume of the air conditioning air AR passing through the first dehumidification device **100-1** and the second dehumidification device **100-2** and an air supply volume. Moreover, the required air volumes of the first dehumidification device **100-1** and the second dehumidification device **100-2** during the dehumidification process and the regeneration process vary due to operating conditions. During the dehumidification process, in order to meet the requirements of humidity control, there is a certain requirement for the air supply volume of the air conditioning air AR during the dehumidification process. When the air supply volume of the dehumidified dried air conditioning air DAR fluctuates with time, the dehumidification performance also fluctuates with time, thereby affecting the anti-fog performance in the vehicle. On the other hand, during the regeneration process, if the air volume of the humidified air MAR on the regeneration side increases, the ambient temperature will decrease, and the dehumidification performance may also decrease. However, once the air supply volume of the humidified air MAR on the regeneration side decreases, the dew point temperature of the humidified air MAR may increase. In the case where the dew point temperature of the humidified air MAR exceeds a threshold value of the dew point temperature of air at a discharge port, condensation may easily occur during discharge from the vehicle, thereby risking deteriorating the vehicle body. Therefore, in the embodiment, the degree of opening of the damper structure DP of the air volume adjusting mechanism VA is maintained, so that the air supply volume of the dehumidified dried air conditioning air DAR and the air supply volume of the humidified air MAR generated after heating are both controlled in a certain manner. For example, in the embodiment, the air supply volume of the dehumidified dried air conditioning air DAR is 45 m.sup.3/h, and the air supply volume of the humidified air MAR generated after heating is 5 m.sup.3/h.

(75) In other words, in the embodiment, the air supply volume of the dehumidified dried air conditioning air DAR during the dehumidification process is greater than the air supply volume of the humidified air MAR generated after heating during the regeneration process. Therefore, as shown in FIG. 4B and FIG. 4C, in the embodiment, when dehumidification is performed through the second dehumidification device **100-2**, the degree of opening of the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** is greater than the degree of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1**, and when dehumidification is performed through the first dehumidification device **100-1**, the degree of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** is greater than the degree of opening of the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2**.

(76) In this way, through sequentially and synchronously switching in turn the sizes of the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** and the air volume adjusting mechanism VA of the second dehumidification device **100-2**, the opening states of the built-in heater of the first dehumidification device **100-1** and the built-in heater of the second dehumidification device **100-2**, and the switching states of the air path switching mechanism SW of the first dehumidification device of **100-1** and the air path switching mechanism SW of the second dehumidification device **100-2** between different paths, the dehumidification device **100** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100** through the first dehumidification device **100-1** and the second dehumidification device **100-2**, and regenerate the first dehumidification device **100-1** or the second dehumidification device **100-2** at the same time.

(77) In addition, the damper structure DP of the air volume adjusting mechanism VA of the first

dehumidification device **100-1** and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** may be respectively used to adjust the air volume of the air conditioning air AR flowing into the first dehumidification device **100-1** and the air volume of the air conditioning air AR flowing into the second dehumidification device **100-2**. Therefore, through adjusting the degrees of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2**, the dried air conditioning air DAR dehumidified by the dehumidification device **100** can be adjusted to be supplied at a predetermined air volume and the humidified air MAR generated after heating the dehumidification device **100** can be discharged at a predetermined air volume respectively when the dehumidification device **100** performs the dehumidification and regeneration processes on the air conditioning air AR flowing into the dehumidification device **100** through any one of the first dehumidification device **100-1** and the second dehumidification device **100-2**.

(78) In this way, the dehumidification device **100** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100** through both the first dehumidification device **100-1** and the second dehumidification device **100-2** without interruption, and can also intermittently regenerate the first dehumidification device **100-1** and the second dehumidification device **100-2** respectively, thereby maintaining preferable dehumidification performance all the time.

(79) Specifically, in the embodiment, the dehumidification device **100** can control the first dehumidification device **100-1** and the second dehumidification device **100-2** to alternately switch to execute the dehumidification or regeneration process at a predetermined time interval. In this way, since no additional elements are required, the dehumidification device **100** can switch between the dehumidification and regeneration processes with a simple structure and low cost. Also, through shortening the cycle of alternately switching the first dehumidification device **100-1** and the second dehumidification device **100-2** to dehumidify and regenerate the air conditioning air AR flowing into the dehumidification device **100**, the required hygroscopic material may be reduced, thereby reducing product cost and saving space. For example, in the embodiment, the time taken for the dehumidification device **100** to alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100** respectively through the first dehumidification device **100-1** and the second dehumidification device **100-2** and the time taken to regenerate the first dehumidification device **100-1** and the second dehumidification device **100-2** are approximately 3 minutes each, but the disclosure is not limited thereto. In other embodiments, the dehumidification device **100** can alternately switch the dehumidification cycle time and the regeneration cycle time of the first dehumidification device **100-1** and the second dehumidification device **100-2** according to actual requirements. For example, in another embodiment, the dehumidification device **100** may alternately switch the dehumidification or regeneration cycle time of the first dehumidification device **100-1** and the second dehumidification device **100-2** in batches based on information of a temperature and humidity sensor disposed on the air inflow channel IN or the air discharge channel EX of at least any one of the first dehumidification device **100-1** and the second dehumidification device **100-2**. In this way, based on the information of the temperature and humidity sensor disposed on the air inflow channel IN or the air discharge channel EX of at least any one of the first dehumidification device **100-1** and the second dehumidification device **100-2**, the dehumidification device **100** can more efficiently execute the dehumidification and regeneration processes.

(80) On the other hand, in the embodiment, the size relationship of the air volume of the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC relative to the air volume of the air conditioning air AR of the main flow channel MC may also be controlled through adjusting the sizes of the degrees of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-**

2. For example, as shown in FIG. 5A and FIG. 5B in the embodiment, the adjustable cross-sectional area of the inflow pathway of the branch flow channel BC is less than or equal to half of the cross-sectional area of the connection channel **214** (that is, the main flow channel MC). Thus, in the embodiment, the air volume of the part of the air conditioning air AR flowing into the dehumidification device **100** from the branch flow channel BC is less than or equal to the air volume of another part of the air conditioning air AR not flowing into the dehumidification device **100** in the main flow channel MC. In this way, through controlling the air volume of the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC to be less than the air volume of the air conditioning air AR of the main flow channel MC, increases in ventilation resistance in the air conditioning unit **210** can be suppressed and increases in power consumption of the blower **213** can be suppressed.

(81) On the other hand, as shown in FIG. 6, in the embodiment, the dehumidification device **100** installed in the connection channel **214** is installed on a side of a housing peripheral wall opposite to an air supply port of the blower **213** for connecting the main flow channel MC in a centrifugal direction. In this way, when air with water droplets from the air intake end portion **211** of the vehicle air conditioning system **200** is absorbed and discharged by the blower **213**, the water droplets are pushed out in the centrifugal direction, so as to prevent the water droplets from entering the dehumidification device **100** installed on the opposite side.

(82) In addition, as shown in FIG. 7A, in the embodiment, the moisture-absorbing surface of the dehumidification element DHE may be disposed parallel to a gravitational direction and perpendicular to a front side direction of the vehicle. In this way, even when the air containing water droplets is blown into the dehumidification device **100**, the water droplets may still slide down along the gravitational direction due to their own weight, thereby suppressing a water film from staying in the dehumidification device **100**. However, the disclosure is not limited thereto. In another embodiment, the moisture-absorbing surface of the dehumidification element DHE may also be disposed to be inclined to the front side direction of the vehicle relative to the gravitational direction, and the moisture-absorbing surface faces diagonally below a vehicle front side. In this way, the air containing water droplets may also slide down along the gravitational direction due to their own weight when blown into the dehumidification device **100** without staying in the dehumidification device **100**.

(83) In this way, the dehumidification device **100** may be integrated in the vehicle air conditioning system **200** as the humidity adjustment unit through sharing the structures of the blower **213** and the housing with the vehicle air conditioning system **200**, and through sharing the configuration of the air flow channel of the vehicle air conditioning system **200**, increases in the ventilation resistance and increases in the power consumption of the blower **213** can be suppressed. At the same time, through simplifying the necessary components of the vehicle air conditioning system **200**, even lower power consumption can be ensured while suppressing increases in cost.

(84) Moreover, through simply controlling the size of the degree of opening of the damper structure DP of the air volume adjusting mechanism VA of the dehumidification device **100**, the size relationship of the air volume of the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC relative to the air volume of the air conditioning air AR of the main flow channel MC can be controlled, and the air supply volume during the dehumidification and regeneration processes of the air conditioning air AR flowing into the dehumidification device **100** can be adjusted. In addition, through disposing the dehumidification device **100** on the side of the housing peripheral wall opposite to the air supply port of the blower **213** for connecting the main flow channel MC in the centrifugal direction and configuring the moisture-absorbing surface of the dehumidification element DHE of the dehumidification device **100** to be parallel to the gravitational direction or facing diagonally below the vehicle front side and inclined relative to the gravitational direction, the impact caused by external water splashing or water droplets staying on the dehumidification element DHE can be prevented, thereby reducing

the risk of deterioration of elements of the dehumidification device **100**, so as to have preferable reliability.

(85) In addition, through disposing the dehumidification device **100** as the humidity adjustment unit on the connection channel **214** connecting the blower **213** of the air conditioning unit **210** and the temperature control module **215**, the impact on the size of the vehicle air conditioning system **200** when the dehumidification device **100** is installed therein can be minimized through using the dead zone between the blower **213** and the temperature control module **215**. In addition, the dehumidification device **100** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100** through both the first dehumidification device **100-1** and the second dehumidification device **100-2** without interruption, and can also intermittently regenerate the first dehumidification device **100-1** and the second dehumidification device **100-2** respectively, thereby maintaining preferable dehumidification performance all the time.

(86) FIG. **8A** is a schematic structural view of another vehicle air conditioning system of FIG. **1A**; and FIG. **8B** and FIG. **8C** are schematic cross-sectional views of the dehumidification device of FIG. **3A** in a warming mode. Please refer to FIG. **8A** to FIG. **8C**. A vehicle air conditioning system **200A** and a dehumidification device **100A** of the embodiment are respectively similar to the vehicle air conditioning system **200** and the dehumidification device **100**, and the differences between the two are as follows. In the embodiment, the vehicle air conditioning system **200A** further includes a partition **811**. Specifically, in the embodiment, the partition **811** is disposed in the main flow channel MC and is used to divert a part of the air conditioning air AR in the main flow channel MC to the branch flow channel BC. Further, as shown in FIG. **8A** to FIG. **8C**, in the embodiment, the partition **811** faces an air inlet AI of the dehumidification device **100A**, and the partition **811** extends from an end of the air inlet AI of the dehumidification device **100A** to the other end of the air inlet AI of the dehumidification device **100A**. In this way, through the configuration of the partition **811**, a substantial boundary of the branch flow channel BC may be drawn in the main flow channel MC, and the part of the air conditioning air AR diverted to the branch flow channel BC can more efficiently flow into the air inlet AI of the dehumidification device **100A**.

(87) In addition, as shown in FIG. **8A** to FIG. **8C**, in the embodiment, the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA and the air path switching mechanism SW are linked through a connection mechanism LK. In this way, when the vehicle air conditioning system **200A** warms the air, that is, in the warming mode of the vehicle air conditioning system **200A**, the dehumidification device **100A** operates, and when the states of the first dehumidification device **100A-1** and the second dehumidification device **100A-2** are sequentially switched in turn, the sizes of the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA of the first dehumidification device **100A-1** and the air volume adjusting mechanism VA of the second dehumidification device **100A-2**, and the switching states of the air path switching mechanism SW of the first dehumidification device **100A-1** and the air path switching mechanism SW of the second dehumidification device **100A-2** between different paths may be linked to be switched through the connection mechanism LK.

(88) For example, as shown in FIG. **8B** and FIG. **8C**, in the embodiment, when dehumidification is performed through the first dehumidification device **100A-1**, as shown in FIG. **8B**, the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100A-1** is opened to a predetermined degree of opening, and the air path switching mechanism SW of the first dehumidification device **100A-1** links and switches the air discharge channel EX of the first dehumidification device **100A-1** to the return air path RP of the first dehumidification device **100A-1** through the connection mechanism LK. Also, at the same time, as shown in FIG. **8C**, the air path switching mechanism SW of the second dehumidification device **100A-2** switches the air discharge channel EX of the second dehumidification device **100A-2** to the discharge air path EP of the second dehumidification device **100A-2**, and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100A-2** is also opened to a

predetermined degree of opening through the connection mechanism LK, so that the humidified air MAR generated after heating the second dehumidification device **100A-2** can leave the second dehumidification device **100A-2** and be discharged to the outside of the vehicle based on the ambient pressure.

(89) Similarly, in the embodiment, when dehumidification is performed through the second dehumidification device **100A-2**, the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100A-2** is also opened to a predetermined degree of opening, and the air path switching mechanism SW of the second dehumidification device **100A-2** also links and switches the air discharge channel EX of the second dehumidification device **100A-2** to the return air path RP of the second dehumidification device **100A-2** through the connection mechanism LK. Also, at the same time, the air path switching mechanism SW of the first dehumidification device **100A-1** switches the air discharge channel EX of the first dehumidification device **100A-1** to the discharge air path EP of the first dehumidification device **100A-1** as shown in FIG. 8C, and the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100A-1** is also linked and opened to a predetermined degree of opening through the connection mechanism LK, so that the humidified air MAR generated after heating the second dehumidification device **100A-2** can leave the second dehumidification device **100A-2** and be discharged to the outside of the vehicle based on the ambient pressure.

(90) In this way, the dehumidification device **100A** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **100A** through both the first dehumidification device **100A-1** and the second dehumidification device **100A-2** without interruption, and can also intermittently regenerate the first dehumidification device **100A-1** and the second dehumidification device **100A-2**, thereby maintaining preferable dehumidification performance all the time. Moreover, since the structure of the dehumidification device **100A** is similar to the structure of the dehumidification device **100**, the dehumidification device **100A** can also achieve similar effects and advantages as those of the dehumidification device **100**, so details are not repeated here. Moreover, the vehicle air conditioning system **200A** adopting the dehumidification device **100A** can also achieve similar effects and advantages as those of the vehicle air conditioning system **200**, so details are also not repeated here.

(91) In addition, it is worth noting that in the foregoing embodiments, although the size relationship of the air volume of the air conditioning air AR flowing into the dehumidification device **100** or **100A** via the branch flow channel BC relative to the air volume of the air conditioning air AR of the main flow channel MC may be controlled through simply adjusting the sizes of the degrees of opening of the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **100-1** or **100A-1** and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **100-2** or **100A-2**, the disclosure is not limited thereto. In other embodiments, other mechanisms may also be disposed to more finely control the air volumes of the air conditioning air AR in the branch flow channel BC and the main flow channel MC. Further description will be made below with reference to FIG. 9A to FIG. 9E.

(92) FIG. 9A to FIG. 9E are schematic cross-sectional views of different vehicle air conditioning systems of FIG. 1A. Please refer to FIG. 9A to FIG. 9E. Vehicle air conditioning systems **200B**, **200C**, **200D**, **200E**, and **200F** of the embodiments are similar to the vehicle air conditioning system **200**, and the differences between the two are as follows.

(93) In the embodiments of FIG. 9A, FIG. 9B, and FIG. 9D, the vehicle air conditioning systems **200B**, **200C**, and **200E** further include a main flow air volume distribution mechanism **912**. In the embodiments, the main flow air volume distribution mechanism **912** is disposed in the main flow channel MC, wherein the main flow air volume distribution mechanism **912** includes a damper structure **912a** that may freely adjust a damper direction to be used to control the air volume of the air conditioning air AR in the main flow channel MC.

(94) For example, in the embodiment of FIG. 9A, the main flow air volume distribution mechanism **912** of the vehicle air conditioning system **200B** is located on a connection portion **214a** of the air supply port of the blower **213** for connecting the main flow channel MC and the connection channel **214** and extends toward the upstream side of the air supply port of the blower **213**. Also, as shown in FIG. 9A, through controlling the damper direction of the damper structure **912a** of the main flow air volume distribution mechanism **912**, the projection area of the damper structure **912a** of the main flow air volume distribution mechanism **912** on the cross-section of the connection channel **214** may be adjusted at the same time. In this way, the channel area of a flow inlet of the main flow channel MC in the connection channel **214** may be adjusted, thereby controlling the air volume of the air conditioning air AR flowing from the blower **213** into the main flow channel MC in the connection channel **214**.

(95) On the other hand, in the embodiment of FIG. 9B and FIG. 9D, the main flow air volume distribution mechanism **912** of the vehicle air conditioning system **200C** or **200E** is located on the flow path of the dehumidified dried air conditioning air DAR flowing from an exhaust port AE of the dehumidification device **100** to the temperature control module **215**, and the dehumidified dried air conditioning air DAR merges with another part of the air conditioning air AR that has not flowed into the dehumidification device **100** in the main flow path MC after passing through the main flow air volume distribution mechanism **912**. Moreover, as shown in FIG. 9B and FIG. 9D, through controlling the damper direction of the damper structure **912a** of the main flow air volume distribution mechanism **912**, the projection area of the damper structure **912a** of the main flow air volume distribution mechanism **912** on the cross-section of the connection channel **214** may also be adjusted at the same time. In this way, the channel area of the discharge port of the main flow channel MC in the connection channel **214** may be adjusted, thereby also controlling the air volume of the air conditioning air AR of the main flow channel MC in the connection channel **214**.

(96) In this way, in the embodiment of FIG. 9A, FIG. 9B and FIG. 9D, in the case where the air supply volume passing through the blower **213** of the vehicle air conditioning system **200B**, **200C**, or **200E** changes according to the temperature inside the vehicle, the air volume of the air conditioning air AR of the main flow channel MC in the connection channel **214** may be adjusted through adjusting the projection area of the damper structure **912a** of the main flow air volume distribution mechanism **912** on the cross-section of the connection channel **214**. In this way, even in the case where the air supply volume passing through the blower **213** of the vehicle air conditioning system **200B**, **200C**, or **200E** gradually decreases according to the temperature inside the vehicle to control the air supply volume of the high temperature air of the vehicle air conditioning system **200**, the channel area of the main flow channel MC in the connection channel **214** may also be reduced through the main flow air volume distribution mechanism **912**, so that the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC can still maintain a certain air volume.

(97) On the other hand, in the embodiments of FIG. 9C and FIG. 9E, the vehicle air conditioning systems **200D** and **200F** may also further extend the partition **811** of FIG. 8B, so that the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC can still maintain a certain air volume. For example, as shown in FIG. 9C and FIG. 9E, a partition **911** of the vehicle air conditioning system **200D** or **200F** faces the air inlet AI and the exhaust port AE of the dehumidification device **100**, and the partition **911** extends from the upstream side of the air supply port of the blower **213** for connecting the main flow channel MC to an end of the exhaust port AE of the dehumidification device **100** away from the air inlet AI. In this way, through extending the partition **911**, a certain proportion of the air volume of the air conditioning air AR from the blower **213** is introduced into the branch flow channel BC. Therefore, even in the case where the air supply volume passing through the blower **213** of the vehicle air conditioning system **200D** or **200F** gradually decreases according to the temperature inside the vehicle, the air conditioning air AR from the blower **213** can always be introduced into the dehumidification

device **100** at a fixed proportion.

(98) In addition, in the embodiment of FIG. **9C**, the vehicle air conditioning system **200D** may further include a windproof plate **913**. The windproof plate **913** is disposed in the main flow channel MC and is connected to the partition **911** to separate the air inflow channel IN and the air discharge channel EX. In this way, as shown in FIG. **9C**, the vehicle air conditioning system **200D** can more reliably introduce the part of the air conditioning air AR diverted to the branch flow channel BC into the dehumidification device **100**.

(99) In this way, the vehicle air conditioning system **200A**, **200B**, **200C**, **200D**, **200E**, or **200F** may more finely control the air volume of the air conditioning air AR in the branch flow channel BC and the main flow channel MC through the configuration of mechanisms such as the main flow air volume distribution mechanism **912**, the windproof plate **913**, and/or the partition **811** or **911**, so that the air volume of the air conditioning air AR flowing into the dehumidification device **100** via the branch flow channel BC can always maintain a certain air volume. Moreover, in the foregoing embodiments, since the vehicle air conditioning system **200A**, **200B**, **200C**, **200D**, **200E**, or **200F** also adopt the dehumidification device **100**, similar effects and advantages as those of the vehicle air conditioning system **200** can also be achieved, so details are also not repeated here.

(100) Please refer to FIG. **10A** to FIG. **12C**. A vehicle air conditioning system **400** and a dehumidification device **300** of the embodiment are respectively similar to the vehicle air conditioning system **200** and the dehumidification device **100**, and the differences between the two are as follows. Specifically, as shown in FIG. **10A** to FIG. **12C**, in the embodiment, the dehumidification device **300** is disposed in front of the evaporator EV of the temperature control module **215** of the vehicle air conditioning system **400** as the refrigerating unit **215a** of the cooling mode of the vehicle air conditioning system **400** and is configured in the temperature control module **215**. Moreover, as shown in FIG. **10B**, in the cooling mode of the vehicle air conditioning system **400**, since water vapor in the air conditioning air AR is converted into water droplets at the same time, the temperature control module **215** may also have the function of dehumidification, and a comfortable ambient humidity in the vehicle compartment can be implemented without activating the dehumidification device **300**. On the other hand, in the warming mode of the vehicle air conditioning system **400**, since the air conditioning unit **210** of the vehicle air conditioning system **400** cannot perform dehumidification through the temperature control module **215** at this time, as shown in FIG. **1C**, dehumidification needs to be performed through activating the dehumidification device **300**, so as to implement a comfortable ambient humidity in the vehicle compartment.

(101) Furthermore, as shown in FIG. **11A** to FIG. **12C**, in the embodiment, the dehumidification device **300** is disposed below the main flow channel MC, and the evaporator EV is disposed diagonally above the dehumidification device **300**. The air inflow channel IN of the branch flow channel BC and the dehumidification device **300** is formed through controlling the opening and closing of the damper structure DP of the air volume adjusting mechanism VA and may be used for the air conditioning air AR passing through the branch flow channel BC to flow into the dehumidification device **300**. On the other hand, in the embodiment, the air path switching mechanism SW is the damper structure DP with an air guide surface and can also switch the air discharge channel EX between the return air path RP and the discharge air path EP. In addition, the dehumidification device **300** can also be switched between the dehumidification and regeneration processes through the air path selection of the air discharge channel EX formed by the air path switching mechanism SW.

(102) For example, when the vehicle air conditioning system **400** cools the air, the dehumidification device **300** does not operate. At this time, as shown in FIG. **12A**, in the dehumidification device **300**, the air volume adjusting mechanism VA of a first dehumidification device **300-1** and the air volume adjusting mechanism VA of a second dehumidification device **300-2**, and the built-in heater of the first dehumidification device **300-1** and the built-in heater of

the second dehumidification device **300-2** are all turned off, and the air discharge channels EX of the air path switching mechanism SW of the first dehumidification device **300-1** and the air path switching mechanism SW of the second dehumidification device **300-2** are both switched to the discharge air path EP with the return air path RP closed.

(103) On the other hand, in the embodiment, when the vehicle air conditioning system **400** warms the air, that is, in the warming mode of the vehicle air conditioning system **400**, the dehumidification device **300** operates and sequentially switches in turn the sizes of the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA of the first dehumidification device **300-1** and the air volume adjusting mechanism VA of the second dehumidification device **300-2**, the opening states of the built-in heater of the first dehumidification device **300-1** and the built-in heater of the second dehumidification device **300-2**, and the switching states of the air path switching mechanism SW of the first dehumidification device of **300-1** and the air path switching mechanism SW of the second dehumidification device **300-2** between different paths.

(104) For example, as shown in FIG. **12B** and FIG. **12C**, in the embodiment, when dehumidification is performed through the first dehumidification device **300-1**, as shown in FIG. **12B**, the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **300-1** is opened, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **300** for dehumidification, and the air path switching mechanism SW of the first dehumidification device **300-1** switches the air discharge channel EX of the first dehumidification device **300-1** to the return air path RP of the first dehumidification device **300-1**, so that the dried air conditioning air DAR dehumidified by the first dehumidification device **300-1** can return to the main flow channel MC of the air conditioning unit **210**. Also, at the same time, the built-in heater of the second dehumidification device **300-2** is also turned on to heat the dehumidification element DHE of the second dehumidification device **300-2**, so as to regenerate the second dehumidification device **300-2**. At this time, as shown in FIG. **12C**, the air path switching mechanism SW of the second dehumidification device **300-2** switches the air discharge channel EX of the second dehumidification device **300-2** to the discharge air path EP of the second dehumidification device **300-2**, and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **300-2** is also opened, so that the humidified air MAR generated after heating the second dehumidification device **300-2** can leave the second dehumidification device **300-2** and be discharged to the outside of the vehicle based on the ambient pressure.

(105) Similarly, in the embodiment, when dehumidification is performed through the second dehumidification device **300-2**, the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **300-2** is also be opened as shown in FIG. **12B**, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **300** for dehumidification, and the air path switching mechanism SW of the second dehumidification device **300-2** switches the air discharge channel EX of the second dehumidification device **300-2** to the return air path RP of the second dehumidification device **300-2**, so that the dried air conditioning air DAR dehumidified by the second dehumidification device **300-2** can return to the main flow channel MC of the air conditioning unit **210**. Also, at the same time, the built-in heater of the first dehumidification device **300-1** is also turned on to heat the dehumidification element DHE of the first dehumidification device **300-1**, so as to regenerate the first dehumidification device **300-1**. At this time, the air path switching mechanism SW of the first dehumidification device **300-1** switches the air discharge channel EX of the first dehumidification device **300-1** to the discharge air path EP of the first dehumidification device **300-1** as shown in FIG. **12C**, and the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **300-1** is also opened, so that the humidified air MAR generated after heating the second dehumidification device **300-2** can leave the second dehumidification device

300-2 and be discharged to the outside of the vehicle based on the ambient pressure.

(106) In addition, as shown in FIG. **10A** and FIG. **12C**, in the embodiment, the heated humidified air MAR may also be discharged out of the vehicle through a drain port **217** of the temperature control module **215** of the air conditioning unit **210** after flowing out of the dehumidification device **300**. In this way, the humidified air MAR of the dehumidification device **300** may share the same path and share the drain port **217** with the discharge of condensed water W generated in the evaporator EV during the process of the temperature control module **215** of the air conditioning unit **210** cooling the air without newly providing a hole portion on the body of the vehicle air conditioning system **400**, so as to reduce cost and maintain a quiet performance.

(107) Moreover, when the dehumidification device **300** performs dehumidification through any one of the first dehumidification device **300-1** and the second dehumidification device **300-2**, since the temperature of the dehumidified dried air conditioning air DAR increases due to adsorption and heat generation, and the dehumidified dried air conditioning air DAR may be transported to the evaporator EV as the heater core within the shortest distance, heat loss during the transportation process can be minimized, thereby reducing the energy consumption of the system.

(108) In this way, the dehumidification device **300** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **300** through both the first dehumidification device **300-1** and the second dehumidification device **300-2** without interruption, and can also intermittently regenerate the first dehumidification device **300-1** and the second dehumidification device **300-2** respectively, thereby maintaining preferable dehumidification performance all the time. In addition, since the structure of the dehumidification device **300** is similar to the structure of the dehumidification device **100**, the dehumidification device **300** can also achieve similar effects and advantages as those of the dehumidification device **100**, so details are not repeated here. Moreover, the vehicle air conditioning system **400** of FIG. **10A** adopting the dehumidification device **100** can also achieve similar effects and advantages as those of the vehicle air conditioning system **200**, so details are also not repeated here.

(109) FIG. **13** is a block diagram of a vehicle air conditioning system according to yet another embodiment of the disclosure; and FIG. **14A** to FIG. **14C** are schematic cross-sectional views of the dehumidification device of FIG. **11A** when the vehicle air conditioning system of FIG. **13** is in different operating modes. Please refer to FIG. **13** to FIG. **14C**. A vehicle air conditioning system **600** and a dehumidification device **500** are respectively similar to the vehicle air conditioning system **400** and the dehumidification device **300**, and the differences between the two are as follows. In the embodiment, the evaporator EV is disposed directly above the dehumidification device **500**. Due to ambient wind pressure, when switching the dehumidification process and the regeneration process of the dehumidification device **500**, the positions of the air inflow channel IN and the air discharge channel EX change.

(110) Furthermore, as shown in FIG. **13**, FIG. **14B**, and FIG. **14C**, in the embodiment, the air path switching mechanism SW may be used to open and close a communication port of the branch flow path BC, so that a part of the air conditioning air AR flowing in from the blower **213** flows into the air inlet AI of the dehumidification device **500** to switch between the air volume adjusting mechanism VA and the air path switching mechanism SW. As shown in FIG. **14B**, when the dehumidification device **500** executes dehumidification, a part of the air conditioning air AR flowing in from the blower **213** flows into the air inlet AI of the dehumidification device **500** as the opening of the air path switching mechanism SW, that is, the air path switching mechanism SW is used to form the air inflow channel IN, and the air volume adjusting mechanism VA is used to form the air discharge channel EX. On the other hand, as shown in FIG. **14C**, when the dehumidification device **500** executes regeneration, a part of the air conditioning air AR flowing in from the blower **213** flows into the air inlet AI of the dehumidification device **500** as the opening of the air volume adjusting mechanism VA, that is, the air volume adjusting mechanism VA is used to form the air inflow channel IN, and the air path switching mechanism SW is used to form the air discharge

channel EX.

(111) Furthermore, when the vehicle air conditioning system **600** cools the air, the dehumidification device **500** does not operate. At this time, as shown in FIG. **14A**, in the dehumidification device **500**, the air volume adjusting mechanism VA of a first dehumidification device **500-1** and the air volume adjusting mechanism VA of a second dehumidification device **500-2**, and the built-in heater of the first dehumidification device **500-1** and the built-in heater of the second dehumidification device **500-2** are all turned off, and the first dehumidification device **500-1** and the second dehumidification device **500-2** both switch the opening of the air path switching mechanisms SW to be communicated with the drain port **217**, so as to close a path for a part of the air conditioning air AR flowing in from the blower **213** to flow into the dehumidification device **500**.

(112) On the other hand, in the embodiment, when the vehicle air conditioning system **600** warms the air, that is, in the warming mode of the vehicle air conditioning system **600**, the dehumidification device **500** operates and sequentially switches in turn the sizes of the degrees of opening of the damper structures DP of the air volume adjusting mechanism VA of the first dehumidification device **500-1** and the air volume adjusting mechanism VA of the second dehumidification device **500-2**, the opening states of the built-in heater of the first dehumidification device **500-1** and the built-in heater of the second dehumidification device **500-2**, and the switching states of the air path switching mechanism SW of the first dehumidification device of **500-1** and the air path switching mechanism SW of the second dehumidification device **500-2** between different paths.

(113) For example, as shown in FIG. **14B** and FIG. **14C**, in the embodiment, when dehumidification is performed through the first dehumidification device **500-1**, as shown in FIG. **14B**, the first dehumidification device **500-1** enables the opening of the air path switching mechanism SW to be communicated with the branch flow channel BC to form the air inflow channel IN of the first dehumidification device **500-1**, and enables the opening to form the air inlet AI of the first dehumidification device **500-1**, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **500** for dehumidification. Moreover, the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **500-1** is also opened, and the dried air conditioning air DAR dehumidified by the first dehumidification device **500-1** returns to the main flow channel MC of the air conditioning unit **210** through the air volume adjusting mechanism VA and is transferred to the evaporator EV, that is, the air volume adjusting mechanism VA of the first dehumidification device **500-1** forms the air discharge channel EX of the first dehumidification device **500-1**. Also, at the same time, the built-in heater of the second dehumidification device **500-2** is also turned on to heat the dehumidification element DHE of the second dehumidification device **500-2**, so as to regenerate the second dehumidification device **500-2**. At this time, as shown in FIG. **12C**, the air path switching mechanism SW of the second dehumidification device **500-2** switches the opening of the air path switching mechanism SW to be communicated with the drain port **217**, and the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **500-2** is also opened, so that the humidified air MAR generated after heating the second dehumidification device **500-2** can leave the second dehumidification device **500-2** and be discharged out of the vehicle based on the ambient pressure, that is, the air volume adjusting mechanism VA of the second dehumidification device **500-2** forms the air inflow channel IN of the second dehumidification device **500-2** at this time, and the air path switching mechanism SW of the second dehumidification device **500-2** forms the air discharge channel EX of the second dehumidification device **500-2**.

(114) Similarly, in the embodiment, when dehumidification is performed through the second dehumidification device **500-2**, the second dehumidification device **500-2** also enables the opening of the air path switching mechanism SW to be communication with the branch flow channel BC as shown in FIG. **14B** to form the air inflow channel IN of the second dehumidification device **500-2**,

and enables the opening to form the air inlet AI of the second dehumidification device **500-2**, so that the air conditioning air AR passing through the branch flow channel BC flows into the dehumidification device **500** for dehumidification. Moreover, the damper structure DP of the air volume adjusting mechanism VA of the second dehumidification device **500-2** is also opened, and the dried air conditioning air DAR dehumidified by the second dehumidification device **500-2** returns to the main flow channel MC of the air conditioning unit **210** through the air volume adjusting mechanism VA and is transferred to the evaporator EV, that is, the air volume adjusting mechanism VA of the second dehumidification device **500-2** forms the air discharge channel EX of the second dehumidification device **500-2**. Also, at the same time, the built-in heater of the first dehumidification device **500-1** is also turned on to heat the dehumidification element DHE of the first dehumidification device **500-1**, so as to regenerate the first dehumidification device **500-1**. At this time, the air path switching mechanism SW of the first dehumidification device **500-1** also switches the opening of the air path switching mechanism SW to be communicated with the drain port **217** as shown in FIG. **14C**, and the damper structure DP of the air volume adjusting mechanism VA of the first dehumidification device **500-1** is also opened, so that the humidified air MAR generated after heating the first dehumidification device **500-1** can leave the first dehumidification device **500-1** and be discharged out of the vehicle based on the ambient pressure, that is, the air volume adjusting mechanism VA of the first dehumidification device **500-1** forms the air inflow channel IN of the first dehumidification device **500-1** at this time, and the air path switching mechanism SW of the first dehumidification device **500-1** forms the air discharge channel EX of the first dehumidification device **500-1**.

(115) In this way, the dehumidification device **500** can alternately dehumidify the air conditioning air AR flowing into the dehumidification device **500** through both the first dehumidification device **500-1** and the second dehumidification device **500-2** without interruption, and can also intermittently regenerate the first dehumidification device **500-1** and the second dehumidification device **500-2** respectively, thereby maintaining preferable dehumidification performance all the time. Moreover, since the structure of the dehumidification device **500** is similar to the structure of the dehumidification device **300**, the dehumidification device **500** can also achieve similar effects and advantages as those of the dehumidification device **300**, so details are not repeated here. Moreover, the vehicle air conditioning system **600** of FIG. **13** adopting the dehumidification device **500** can also achieve similar effects and advantages as those of the vehicle air conditioning system **400**, so details are also not repeated here.

(116) In summary, in the vehicle air conditioning system of the embodiments of the disclosure, the dehumidification device may be integrated in the vehicle air conditioning system as the humidity adjustment unit through sharing the structures of the blower and the housing with the vehicle air conditioning system, and through sharing the configuration of the air flow channel of the vehicle air conditioning system, increases in ventilation resistance can be suppressed and increases in power consumption of the blower can be suppressed. At the same time, through simplifying necessary components of the vehicle air conditioning system, even lower power consumption can be ensured while suppressing increases in cost. Also, through disposing the dehumidification device on the side of the housing peripheral wall opposite to the air supply port of the blower for connecting the main flow channel in the centrifugal direction and configuring the moisture-absorbing surface of the dehumidification element of the dehumidification device to be parallel to the gravitational direction or facing diagonally below the vehicle front side and inclined relative to the gravitational direction, the impact caused by external water splashing or water droplets staying on the dehumidification element can be prevented, thereby reducing the risk of deterioration of elements of the dehumidification device, so as to have preferable reliability.

(117) Moreover, the dehumidification device can alternately dehumidify the air conditioning air flowing into the dehumidification device through both the first dehumidification device and the second dehumidification device, and can also intermittently regenerate the first dehumidification

device and the second dehumidification device respectively, thereby maintaining preferable dehumidification performance all the time.

(118) In addition, through disposing the dehumidification device as the humidity adjustment unit on the connection channel connecting the blower of the air conditioning unit and the temperature control module, the impact on the size of the vehicle air conditioning system when the dehumidification device is installed therein can be minimized through using the dead zone between the blower and the temperature control module.

(119) On the other hand, through disposing the dehumidification device as the humidity adjustment unit in front of the evaporator of the temperature control module, the humidified air of the dehumidification device may share the same path and share the drain port with the discharge of the condensed water generated in the evaporator during the process of the temperature control module of the air conditioning unit cooling the air without newly providing a hole portion on the body of the vehicle air conditioning system, so as to reduce cost and maintain a quiet performance.

Moreover, when the dehumidification device performs dehumidification, since the temperature of the dehumidified dried air conditioning air increases due to adsorption and heat generation, and the dehumidified dried air conditioning air may be transported to the evaporator as the heater core within the shortest distance, heat loss during the transportation process can be minimized, thereby reducing the energy consumption of the system.

(120) Finally, it should be noted that the above embodiments are only used to illustrate, but not to limit, the technical solutions of the disclosure. Although the disclosure has been described in detail with reference to the above embodiments, persons skilled in the art should understand that the technical solutions described in the above embodiments may still be modified or some or all of the technical features thereof may be equivalently replaced. However, the modifications or replacements do not cause the essence of the corresponding technical solutions to deviate from the scope of the technical solutions of the embodiments of the disclosure.

Claims

1. A vehicle air conditioning system, comprising: an air conditioning unit, configured to adjust a temperature in a vehicle compartment and comprising a blower and a temperature control module; and a dehumidification device, configured to adjust a humidity in the vehicle compartment, disposed between the blower and an evaporator of the temperature control module, and enabling a part of air conditioning air flowing in from the blower to flow into the dehumidification device.
2. The vehicle air conditioning system according to claim 1, wherein the air conditioning unit further comprises a main flow channel and a branch flow channel, the main flow channel is communicated with an air intake end portion and an air supply end portion of the air conditioning unit and is used for the air conditioning air flowing in from the blower to flow to the temperature control module, and the branch flow channel diverges from the main flow channel, is communicated with the main flow channel and the dehumidification device, and is used for the part of the air conditioning air flowing in from the blower to flow into the dehumidification device.
3. The vehicle air conditioning system according to claim 2, wherein an air volume of the part of the air conditioning air flowing from the branch flow path into the dehumidification device is less than or equal to an air volume of another part of air conditioning air that does not flow into the dehumidification device in the main flow path.
4. The vehicle air conditioning system according to claim 2, wherein the dehumidification device comprises: an air volume adjusting mechanism, used to form one of an air inflow channel and an air discharge channel, wherein the air inflow channel is communicated with the branch flow channel; an air path switching mechanism, used to form other one of the air inflow channel and the air discharge channel; a dehumidification element, disposed on a flow path of the part of the air conditioning air flowing in from the blower between the air volume adjusting mechanism and the

air path switching mechanism.

5. The vehicle air conditioning system according to claim 4, wherein there are a plurality of dehumidification devices, comprising a first dehumidification device and a second dehumidification device, wherein when dehumidification is performed through a dehumidification element of one of the first dehumidification device and the second dehumidification device, other one of the first dehumidification device and the second dehumidification device heats the dehumidification element of the other one to regenerate the other one of the first dehumidification device and the second dehumidification device.

6. The vehicle air conditioning system according to claim 5, wherein the dehumidification device alternately switches a cycle time of dehumidification or regeneration of the first dehumidification device and the second dehumidification device in batches based on information of a temperature and humidity sensor disposed on the air inflow channel or the air discharge channel of at least any one of the first dehumidification device and the second dehumidification device.

7. The vehicle air conditioning system according to claim 5, wherein the first dehumidification device and the second dehumidification device alternately switch to execute a dehumidification or regeneration process at a predetermined time interval.

8. The vehicle air conditioning system according to claim 5, wherein the air volume adjusting mechanism of any one of the first dehumidification device and the second dehumidification device is used to form the air inflow channel, comprises a damper structure configured to adjust a degree of opening, and is used to adjust an air volume of the part of the air conditioning air flowing into the air inflow channel of the any one, the air path switching mechanism is used to form the air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle, when dehumidification is performed through the first dehumidification device, the degree of opening of the damper structure of the first dehumidification device is greater than the degree of opening of the damper structure of the second dehumidification device, the air path switching mechanism of the first dehumidification device switches the air discharge channel of the first dehumidification device to the return air path of the first dehumidification device, and the air path switching mechanism of the second dehumidification device switches the air discharge channel of the second dehumidification device to the discharge air path of the second dehumidification device, when dehumidification is performed through the second dehumidification device, the degree of opening of the damper structure of the second dehumidification device is greater than the degree of opening of the damper structure of the first dehumidification device, the air path switching mechanism of the second dehumidification device switches the air discharge channel of the second dehumidification device to the return air path of the second dehumidification device, and the air path switching mechanism of the first dehumidification device switches the air discharge channel of the first dehumidification device to the discharge air path of the first dehumidification device.

9. The vehicle air conditioning system according to claim 5, wherein the air volume adjusting mechanism of any one of the first dehumidification device and the second dehumidification device comprises a damper structure configured to adjust a degree of opening, and the air path switching mechanism is used to open and close a communication port of the branch flow channel, so that a part of air conditioning air flowing in from the blower flows into an air inlet of the dehumidification device to switch between the air volume adjusting mechanism and the air path switching mechanism of the any one, wherein when the first dehumidification device executes dehumidification, the air path switching mechanism of the first dehumidification device is used to form the air inflow channel of the first dehumidification device, the air volume adjusting mechanism of the first dehumidification device is used to form the air discharge channel of the first

dehumidification device, the air volume adjusting mechanism of the second dehumidification device is used to form the air inflow channel of the second dehumidification device, the air path switching mechanism of the second dehumidification device is used to form the air discharge channel of the second dehumidification device, and the degree of opening of the damper structure of the first dehumidification device is greater than the degree of opening of the damper structure of the second dehumidification device, when the second dehumidification device executes dehumidification, the air path switching mechanism of the second dehumidification device is used to form the air inflow channel of the second dehumidification device, the air volume adjusting mechanism of the second dehumidification device is used to form the air discharge channel of the second dehumidification device, the air volume adjusting mechanism of the first dehumidification device is used to form the air inflow channel of the first dehumidification device, the air path switching mechanism of the first dehumidification device is used to form the air discharge channel of the first dehumidification device, and the degree of opening of the damper structure of the second dehumidification device is greater than the degree of opening of the damper structure of the first dehumidification device.

10. The vehicle air conditioning system according to claim 2, wherein the dehumidification device is disposed on a connection channel connecting the blower of the air conditioning unit and the temperature control module.

11. The vehicle air conditioning system according to claim 10, wherein an air volume adjusting mechanism is used to form an air inflow channel, an air path switching mechanism is used to form an air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle.

12. The vehicle air conditioning system according to claim 10, wherein the connection channel is formed as a part of the main flow channel, the branch flow channel is communicated with the connection channel, the air volume adjusting mechanism comprises a damper structure configured to adjust a degree of opening, the degree of opening of the damper structure is used to form and adjust a size of an adjustable cross-sectional area of an inflow pathway of the branch flow channel, and the adjustable cross-sectional area of the inflow pathway of the branch flow channel is less than or equal to half of a cross-sectional area of the connection channel.

13. The vehicle air conditioning system according to claim 10, wherein the dehumidification device installed in the connection channel is installed on a side of a housing peripheral wall opposite to an air supply port of the blower for connecting the main flow channel in a centrifugal direction.

14. The vehicle air conditioning system according to claim 10, wherein the dehumidification element has a moisture-absorbing surface, and the moisture-absorbing surface is disposed parallel to a gravitational direction and perpendicular to a front side direction of a vehicle.

15. The vehicle air conditioning system according to claim 10, wherein the dehumidification element has a moisture-absorbing surface, the moisture-absorbing surface is disposed to be inclined relative to a gravitational direction and a front side direction of a vehicle, and the moisture-absorbing surface faces diagonally below a vehicle front side.

16. The vehicle air conditioning system according to claim 10, wherein the air volume adjusting mechanism and the air path switching mechanism both comprise a damper structure configured to adjust a degree of opening, and the dehumidification device further comprises: an actuator; and a connection mechanism, wherein the actuator connects the air volume adjusting mechanism and the air path switching mechanism through connection mechanism to control the degrees of opening of the damper structures of the air volume adjusting mechanism and the air path switching mechanism.

17. The vehicle air conditioning system according to claim 16, wherein the degrees of opening of

the damper structures of the air volume adjusting mechanism and the air path switching mechanism are linked through the connection mechanism.

18. The vehicle air conditioning system according to claim 10, further comprising: a partition, disposed in the main flow channel and used to divert the part of the air conditioning air in the main flow channel to the branch flow channel.

19. The vehicle air conditioning system according to claim 18, wherein the partition faces an air inlet of the dehumidification device, and the partition extends from an end of the air inlet of the dehumidification device to other end of the air inlet of the dehumidification device.

20. The vehicle air conditioning system according to claim 18, wherein the partition faces an air inlet and an exhaust port of the dehumidification device, and the partition extends from an end of the air inlet of the dehumidification device to an end of the exhaust port of the dehumidification device away from the air inlet.

21. The vehicle air conditioning system according to claim 18, wherein the partition faces an air inlet and an exhaust port of the dehumidification device, and the partition extends from an upstream side of an air supply port of the blower for connecting the main flow channel to an end of the exhaust port of the dehumidification device away from the air inlet.

22. The vehicle air conditioning system according to claim 10, further comprising: a windproof plate, disposed in the main flow channel and connected to a partition, and used to separate an air inflow channel and an air discharge channel.

23. The vehicle air conditioning system according to claim 10, further comprising: a main flow air volume distribution mechanism, disposed in the main flow channel and used to control an air volume of air conditioning air in the main flow channel.

24. The vehicle air conditioning system according to claim 23, wherein the main flow air volume distribution mechanism is located on a connection portion of an air supply port of the blower for connecting the main flow channel and the connection channel, and extends toward an upstream side of the air supply port of the blower.

25. The vehicle air conditioning system according to claim 23, wherein the main flow air volume distribution mechanism is located on a flow path of dehumidified dried air conditioning air flowing from an exhaust port of the dehumidification device to the temperature control module, and the dehumidified air conditioning air merges with another part of air conditioning air that does not flow into the dehumidification device in the main flow channel after passing through the main flow air volume distribution mechanism.

26. The vehicle air conditioning system according to claim 2, wherein the dehumidification device is disposed in front of the evaporator and is configured in the temperature control module.

27. The vehicle air conditioning system according to claim 26, wherein the air conditioning unit has a drain port for discharging condensed water generated in the evaporator to an outside of a vehicle, and heated humidified air in the dehumidification device is discharged out of the vehicle through the drain port and shares a same path with a discharge of the condensed water generated in the evaporator.

28. The vehicle air conditioning system according to claim 26, wherein an air volume adjusting mechanism is used to form an air inflow channel, an air path switching mechanism is used to form an air discharge channel, and the air path switching mechanism switches the air discharge channel between a return air path and a discharge air path, wherein the return air path is an air path for returning dehumidified dried air conditioning air back to the main flow path of the air conditioning unit, and the discharge air path is an air path for discharging humidified air generated by heating the dehumidification device to an outside of a vehicle.

29. The vehicle air conditioning system according to claim 26, wherein an air path switching mechanism is used to open and close a communication port of the branch flow path, so that a part of air conditioning air flowing in from the blower flows into an air inlet of the dehumidification device to switch between an air volume adjusting mechanism and an air path switching mechanism,

wherein when the dehumidification device executes dehumidification, the air path switching mechanism is used to form an air inflow channel, and the air volume adjusting mechanism is used to form an air discharge channel, and when the dehumidification device executes regeneration, the air volume adjusting mechanism is used to form the air inflow channel, and the air path switching mechanism is used to form the air discharge channel.

30. The vehicle air conditioning system according to claim 1, wherein the dehumidification device has a built-in heater configured to directly heat through energization.
