

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386143
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kumar; Ankit et al.

Mechanism for dioptric adjustment of telescopic lenses

Abstract

The present disclosure provides a device for dioptric adjustment of a plurality of telescopic lenses against a focal plane array. The device includes a hollow cylinder developed onto a housing. In addition, the housing includes a plurality of pins. The device includes the focal plane array affixed with a support structure. Further, the device includes a barrel body. The barrel body includes a plurality of slots. Further, each of the plurality of pins is inserted in a slot of the plurality of slots of the barrel body. Furthermore, the device includes a dioptric adjusting knob coupled to the plurality of telescopic lenses with facilitation of the barrel body. Furthermore, the dioptric adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to thereby adjust an optical setting of the spotting scope.

Inventors: Kumar; Ankit (Bangalore, IN), Arvind; Kondangi Lakshmikumar (Singapore, SG), Sudarshan; Nelaji Mohanrao (Bangalore, IN)

Applicant: Tonbo Imaging Pte. Ltd. (Singapore, SG)

Family ID: 90834770

Assignee: Tonbo Imaging Pte. Ltd. (Singapore, SG)

Appl. No.: 18/051387

Filed: October 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240142745 A1	May. 02, 2024

Publication Classification

Int. Cl.: G02B7/04 (20210101); G02B7/02 (20210101); G02B23/16 (20060101); G02B25/00 (20060101)

U.S. Cl.:

CPC **G02B7/04** (20130101); **G02B7/021** (20130101); **G02B7/023** (20130101); **G02B23/16** (20130101); **G02B25/001** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0116704	12/2020	Rivas	N/A	G02B 27/0006

Primary Examiner: Kim; Richard H

Attorney, Agent or Firm: Kolisch Hartwell, P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to telescopic lenses and, in particular, to a mechanism for dioptric adjustment of telescopic lenses.

BACKGROUND

(2) Dioptric adjustment permits for fine-tuning of a device to focus according to a user's eyes. The process is critical to ensure that both the image on a focusing screen and a device display are in perfect focus. In addition, the dioptric adjustment ensures calibration of an optical device with respect to changing visual insight of the user's eyes. It is the device of a single lens to deliver well-matched focus when the user's eyes have changing visual insight. The outcome is less strain on the eyes that permits for best visual, depth and contrast focusing when composing a picture or viewing a target through a device made of lenses or lens elements. On the contrary, and while speaking about infrared optical devices, since the eye cannot sense infrared radiation, infrared sensing systems require sensor arrays such as focal plane arrays. In an example, CCD cameras. These focal plane arrays are straight-lined, with the focal plane array located at the focal plane of the corresponding telescopic element. After an infrared monocular is correctly attuned for the user's eye, it is significant the same be possible for any other user, probably with dissimilar visual insight.

(3) In light of the above-stated discussion, there is a need for a device which overcomes the above-stated shortcomings.

SUMMARY

(4) In an aspect, the present disclosure includes a device for dioptric adjustment of a plurality of telescopic lenses against a focal plane array. The device includes a hollow cylinder. In addition, the device includes the focal plane array affixed with a support structure. Further, the device includes a barrel body. The barrel body includes a plurality of slots. Furthermore, the device includes a dioptric adjusting knob coupled to a plurality of telescopic lenses with facilitation of the barrel body. The hollow cylinder is developed onto a housing. The housing includes a plurality of pins. The plurality of pins is formed onto the housing. The plurality of pins restricts rotational movement

of the barrel body. The each of the plurality of pins is inserted in a slot of the plurality of slots of the barrel body. In addition, the support structure is rigidly affixed inside the hollow cylinder of the housing. Further, the barrel body encapsulates the plurality of telescopic lenses. The barrel body is able to slide inside the hollow cylinder developed onto the housing. The barrel body and the plurality of telescopic lenses can move in forward and backward direction. Furthermore, the dioptic adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to thereby adjust an optical setting of the spotting scope. The dioptic adjusting knob is restricted to move axially with the facilitation of the plurality of pins. Moreover, the device enables dioptic adjustment of the plurality of telescopic lenses against the focal plane array without causing skew or distortion of view.

(5) In an embodiment of the present disclosure, the barrel body includes male threading machined onto the barrel body.

(6) In an embodiment of the present disclosure, the device includes a plurality of spacer. In addition, the plurality of spacer facilitates appropriate distance between the plurality of telescopic lenses.

(7) In an embodiment of the present disclosure, each telescopic lens in the plurality of telescopic lenses having fixed distance with respect to each other.

(8) In an embodiment of the present disclosure, the dioptic adjusting knob includes female threading. In addition, the female threading engages with the male threading. Further, the movement of the plurality of telescopic lenses in response to rotation of the dioptic adjusting knob changes a focus setting of the spotting scope.

(9) In an embodiment of the present disclosure, the focal plane array receives an optical axis. In addition, the optical axis is absolutely coaxial with the longitudinal axis of the barrel body. Further, the longitudinal axis of the barrel body passes through the center of the barrel body.

(10) In an embodiment of the present disclosure, the device includes a plurality of disk. In addition, the plurality disk is positioned onto the housing in a fixed position. Further, the plurality of disk locks the barrel body into position.

(11) In an embodiment of the present disclosure, the plurality of pins and the plurality of slots collectively enable limits of dioptic adjustment. In addition, the limits includes minimum and maximum number of diopters.

(12) In an embodiment of the present disclosure, the device includes a plurality of O-rings positioned between the housing and the barrel body. Further, the O-rings facilitates isolation of the device from an outer environment.

(13) In an embodiment of the present disclosure, the device includes an eye cup connected onto an eyepiece. In addition, the eye cup is assembled with the facilitation of a spring wire clip. Further, the eyepiece facilitates to see the view projected onto the focal plane array.

(14) In another aspect, the present disclosure includes a device for dioptic adjustment of a plurality of telescopic lenses against a focal plane array. The device includes a hollow cylinder developed onto a housing. In addition, the device includes the focal plane array affixed with a support structure. Further, the device includes a barrel body. The barrel body includes a plurality of slots. Furthermore, the device includes a plurality of disk positioned onto the housing in a fixed position. Moreover, the device includes a dioptic adjusting knob coupled to the plurality of telescopic lenses with facilitation of the barrel body. In addition, the housing includes a plurality of pins formed onto the housing. Further, the support structure is rigidly affixed inside the hollow cylinder of the housing. Furthermore, the plurality of pins restricts rotational movement of the barrel body. The each of the plurality of pins is inserted in a slot of the plurality of slots of the barrel body. The barrel body encapsulates a plurality of telescopic lenses. The plurality of pins and the plurality of slots collectively enable limits of dioptic adjustment. The limits having minimum and maximum number of diopters. Moreover, the barrel body is able to slide inside the hollow cylinder developed onto the housing. The barrel body and the plurality of telescopic lenses can move in forward and

backward direction. Also, the plurality of disk locks the barrel body into position. Also, the dioptic adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to thereby adjust an optical setting of the spotting scope. The dioptic adjusting knob is restricted to move axially with the facilitation of the plurality of pins. The device enables dioptic adjustment of the plurality of telescopic lenses against the focal plane array without causing skew or distortion of view.

(15) In an embodiment of the present disclosure, the barrel body includes male threading machined onto the barrel body.

(16) In an embodiment of the present disclosure, the device includes a plurality of spacer. In addition, the plurality of spacer facilitates appropriate distance between the plurality of telescopic lenses.

(17) In an embodiment of the present disclosure, each telescopic lens in the plurality of telescopic lenses having fixed distance with respect to each other.

(18) In an embodiment of the present disclosure, the dioptic adjusting knob includes female threading. In addition, the female threading engages with the male threading. Further, the movement of the plurality of telescopic lenses in response to rotation of the dioptic adjusting knob changes a focus setting of the spotting scope.

(19) In an embodiment of the present disclosure, the focal plane array receives an optical axis. In addition, the optical axis is absolutely coaxial with the longitudinal axis of the barrel body. Further, the longitudinal axis of the barrel body passes through the center of the barrel body.

(20) In an embodiment of the present disclosure, the device includes a plurality of O-rings positioned between the housing and the barrel body. In addition, the O-rings facilitates isolation of the device from an outer environment.

(21) In an embodiment of the present disclosure, the device includes an eye cup connected onto an eyepiece. In addition, the eye cup is assembled with the facilitation of a spring wire clip. Further, the eyepiece facilitates to see the view projected onto the focal plane array.

(22) In yet another aspect, the present disclosure includes a plurality of telescopic lenses against a focal plane array. The device includes a hollow cylinder. In addition, the device includes a focal plane array affixed with a support structure. Further, the device includes a barrel body. The barrel body includes a plurality of slots. Furthermore, the device includes a plurality of O-rings positioned between the housing and the barrel body. Moreover, the device includes a plurality of disk positioned onto the housing in a fixed position. Also, the device includes a dioptic adjusting knob coupled to the plurality of telescopic lenses with facilitation of the barrel body. In addition, the hollow cylinder is developed onto a housing. The housing includes a plurality of pins formed onto the housing. Further, the support structure is rigidly affixed inside the hollow cylinder of the housing. Furthermore, the plurality of pins restricts rotational movement of the barrel body. The each of the plurality of pins is inserted in a slot of the plurality of slots of the barrel body. The barrel body includes male threading machined onto the barrel body. The barrel body encapsulates a plurality of telescopic lenses. Moreover, the plurality of pins and the plurality of slots collectively enable limits of dioptic adjustment. The limits include minimum and maximum number of diopters. Also, the barrel body is able to slide inside the hollow cylinder developed onto the housing. The barrel body and the plurality of telescopic lenses can move in forward and backward direction. The focal plane array receives an optical axis. The optical axis is absolutely coaxial with a longitudinal axis of the barrel body. The longitudinal axis of the barrel body passes through the center of the barrel body. Also, the O-rings provides isolation of the device from an outer environment. Also, the plurality of disk locks the barrel body into position. Also, the dioptic adjusting knob is manually rotatable about the longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to thereby adjust an optical setting of the spotting scope. The dioptic adjusting knob is restricted to move axially with the facilitation of the plurality of pins. The dioptic adjusting knob includes female threading. The female threading engages with the male

threading. Also, the movement of the plurality of telescopic lenses in response to rotation of the dioptic adjusting knob changes a focus setting of the spotting scope. The device enables dioptic adjustment of the plurality of telescopic lenses against a focal plane array without causing skew or distortion of view.

(23) In an embodiment of the present disclosure, the device includes a plurality of spacer. In addition, the plurality of spacer facilitates appropriate distance between the plurality of telescopic lenses.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Having thus described the disclosure in general terms, reference will now be made to the accompanying figures, wherein;

(2) FIG. 1A illustrates an environment of a device, in accordance with an embodiment of the present disclosure;

(3) FIG. 1B illustrates a detailed exploded view of the device, in accordance with various embodiments of the present disclosure;

(4) FIG. 1C illustrates the detailed exploded view of the device from a different perspective angle, in accordance with various embodiments of the present disclosure;

(5) FIG. 2A illustrates a horizontal cut away view of the device, in accordance with various embodiments of the present disclosure;

(6) FIG. 2B illustrates a vertical cut away view of the device, in accordance with various embodiments of the present disclosure;

(7) FIG. 2C illustrates a detailed exploded view of a plurality of telescopic lenses of the device, in accordance with an embodiment of the present disclosure;

(8) FIG. 2D illustrates a view from a top of the device, in accordance with various embodiments of the present disclosure; and

(9) FIG. 2E illustrates a side view of the device, in accordance with various embodiments of the present disclosure.

(10) It should be noted that the accompanying figures are intended to present illustrations of exemplary embodiments of the present disclosure. These figures are not intended to limit the scope of the present disclosure. It should also be noted that accompanying figures are not necessarily drawn to scale.

DETAILED DESCRIPTION

(11) In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present technology. It will be apparent, however, to one skilled in the art that the present technology can be practiced without these specific details. In other instances, structures and devices are shown in block diagram form only in order to avoid obscuring the present technology.

(12) Reference in this specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present technology. The appearance of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Moreover, various features are described which may be exhibited by some embodiments and not by others. Similarly, various requirements are described which may be requirements for some embodiments but not other embodiments.

(13) Moreover, although the following description contains many specifics for the purposes of illustration, anyone skilled in the art will appreciate that many variations and/or alterations to said

details are within the scope of the present technology. Similarly, although many of the features of the present technology are described in terms of each other, or in conjunction with each other, one skilled in the art will appreciate that many of these features can be provided independently of other features. Accordingly, this description of the present technology is set forth without any loss of generality to, and without imposing limitations upon, the present technology.

(14) It should be noted that the terms “first”, “second”, and the like, herein do not denote any order, ranking, quantity, or importance, but rather are used to distinguish one element from another. Further, the terms “a” and “an” herein do not denote a limitation of quantity, but rather denote the presence of at least one of the referenced item.

(15) FIG. 1A illustrates an environment of a device **100**, in accordance with an embodiment of the present disclosure. FIG. 1B illustrates a detailed exploded view of the device **100**, in accordance with various embodiments of the present disclosure. FIG. 1C illustrates the detailed exploded view of the device **100** from different perspective angle, in accordance with various embodiments of the present disclosure. FIG. 2A illustrates a horizontal cut away view of the device **100**, in accordance with various embodiments of the present disclosure. FIG. 2B illustrates a vertical cut away view of the device **100**, in accordance with various embodiments of the present disclosure. FIG. 2C illustrates a detailed exploded view of a plurality of telescopic lenses of the device **100**, in accordance with various embodiments of the present disclosure. FIG. 2D illustrates a view from a top of the device **100**, in accordance with various embodiments of the present disclosure. FIG. 2E illustrates a side view of the device **100**, in accordance with various embodiments of the present disclosure.

(16) The device **100** includes a housing **102**, a plurality of pins **104**, a support structure **106**, a focal plane array **108**, a plurality of O-rings **110** and a barrel body **112**. In addition, the device **100** includes a plurality of disks **114**, a spring wire clip **116**, a dioptric adjusting knob **118**, an eye cup **120**, a plurality of slots **122**, a first spacer **124**, a second spacer **126**, a face sealing gasket **128** and a nut **130**.

(17) In an embodiment of the present disclosure, the device **100** corresponds to a device for dioptric adjustment of a plurality of telescopic lenses against the focal plane array **108**. In general, focal plane array refers to a sensing device, consisting of an array of light-sensing pixels at a focal plane of a lens that is sensitive to infrared radiation. The focal plane is the plane that is perpendicular to the axis of a lens or mirror and passes through the focal point. The focal plane array **108** operates by converting infrared photons to an electrical signal, and using it to construct an image of the sample. In another embodiment of the present disclosure, the focal plane array **108** includes an optical axis. The optical axis is coaxial with a longitudinal axis of the barrel body **112**. In general, longitudinal axis refers to the lengthwise direction of the figure or body, usually passing through its center of gravity. In yet another embodiment of the present disclosure, the longitudinal axis of the barrel body **112** passes through the center of the barrel body **112**. In yet another embodiment of the present disclosure, the distance between the plurality of telescopic lenses of the device **100** against the focal plane array **108** is adjusted to make the device **100** suitable for use by different individuals with different visual acuity. The adjustment of distance between the plurality of telescopic lenses of the device **100** against the focal plane array **108** is termed as dioptric adjustment or dioptric correction. In general, dioptric correction refers to the expression for the adjustment of the optical instrument to the varying visual acuity of a person's eyes. It is the adjustment of one lens to provide compatible focus when the viewer's eyes have differing visual capabilities.

(18) The device **100** enables the dioptric adjustment of the plurality of telescopic lenses against the focal plane array **108** without causing skew or distortion of view. In general, skew corresponds to slanting or misalignment of images formed on the focal plane of an imaging system. The device **100** enables the dioptric adjustment of the plurality of telescopic lenses against the focal plane array **108** without causing any distortion in the image.

(19) The environment of the device **100** as shown in FIG. **1A** includes a plurality of sections. The plurality of sections includes section A, section B, section C, section D, section E, section F, and section G. The section A includes a plurality of infrared lenses that through an appropriate field of view (hereinafter, FOV) and collects the emitted thermal energy from the outside environment under observation. In general, FOV refers to open observable area up to which a person can see through his or her eyes with an optical device. The optical device includes but not limited to camera, video sensing device, night vision device, thermal vision device, monocular, binocular, and the like. In case of optical devices, FOV describes angle through which devices can pick up electromagnetic radiations. In an embodiment of the present disclosure, the section B includes a thermal sensor. In general, thermal sensor refers to a device, which is used for measurement of temperature or heat, such as Resistance temperature detectors (RTD), thermocouple, thermistor, sensistor, and the like. In another embodiment of the present disclosure, the plurality of infrared lenses of the section A inside the device **100** focuses onto the thermal sensor of the section B.

(20) In an embodiment of the present disclosure, the thermal sensor of the section B transmits electrical signals to the section C. The section C includes a processing unit. The processing unit receives the electrical signals from the section B. The processing unit processes the received signals using specific algorithms and performs very fast image processing calculations to compose video streams that are directed towards the focal plane array **108** inscribed in the section D. The focal plane array **108** is mounted over a stack of PCBs that form the main processing unit.

(21) In an embodiment of the present disclosure, the section E includes a monocular carrying the main mechanism for the dioptric adjustment. In addition, the section F is the power unit of the device **100**. The power unit provides power to the various components of the device **100** to perform their intended functions. In another embodiment of the present disclosure, the power unit is battery powered. The battery can be of any type including Li-ion battery, Li-polymer battery, Nickel cadmium, and the like. Further, the section G is the housing **102** or a rigid shell of the device **100** that isolates the components located inside out of the external environment. The section G is filled with gasses like nitrogen, helium, krypton, and the like for the purpose of purging. In general, purging is carried out to avoid the possibility of an explosive air/gas mixture existing or forming in consumer piping, appliances or confined spaces. In an example, purging extends tolerable range of external temperature, external pressure, varying humidity levels, and the like. The neutral nature of the inert gas is most suitable for purging.

(22) The device **100** includes the housing **102**. In general, housing refers to a body, exterior case, rigid shell or enclosure used to protect an interior mechanism, including integrated fittings or brackets to keep internal components in place. The housing prevents the interior mechanism from being fouled by outside debris or to contain the internal components. Housing may be the body of the device. In an embodiment of the present disclosure, the device **100** includes a hollow cylindrical intrusion. The hollow cylindrical intrusion is developed onto the housing **102**. The hollow cylindrical intrusion is perfectly cylindrical from inner diameter. In an embodiment of the present disclosure, the hollow cylindrical intrusion can be of any shape. In an embodiment of the present disclosure, the housing **102** is made up of a suitable material. In an example, the suitable material may include but not limited to aluminum, alloy, metal, rubber, glass, wood, plastic and the like.

(23) The plurality of pins **104** is formed onto the housing **102**. In an embodiment of the present disclosure, the plurality of pins **104** includes a first pin, a second pin, and a third pin. In another embodiment of the present disclosure, the plurality of pins **104** can be of any number. In an example, the plurality of pins **104** is made of suitable material that can be similar to the housing **102** material or may be different.

(24) The focal plane array **108** is affixed with the support structure **106**. In addition, the focal plane array **108** and the support structure **106** are being supported rigidly over the stack of the PCBs that undertake the signal processing. The support structure **106** is rigidly affixed inside the housing **102**.

In an embodiment of the present disclosure, the support structure **106** is rigidly affixed inside the hollow cylindrical intrusion of the housing **102**. The support structure **106** provides mechanical support to the focal plane array **108** of the device **100**. In general, support structure corresponds to rigid structural element to provide mechanical support to various elements of an assembly. Also, the support structure can hold and support any device. The support structure provides a framework and mechanical support for all the machine components. In addition, the support structure encompasses important components such as the machine base, column, worktable, slide, spindle cases, carriages, and the like. In an example, when a person tries to displace the device **100**, the focal plane array **108** stays affixed in a position with the help of the support structure **106**.

(25) The device **100** includes the barrel body **112**. The barrel body **112** is a hollow body and has a cylindrical cross-section. The barrel body **112** includes a male threading. In general, male threading is considered as external threads. The external threads are of different shapes like U-shape, V-shape, and the like. The external threads are of two types, right-hand side external threads and left-hand side external threads. The male threading is machined onto the barrel body **112**. The barrel body **112** inserts into the housing **102** and can slide inside the housing **102**. In an embodiment of the present disclosure, the barrel body **112** inserts into the hollow cylindrical intrusion of the housing **102** and can slide inside the hollow cylindrical intrusion of the housing **102**. The barrel body **112** always has an outer diameter smaller than the inner diameter of the housing **102**.

(26) In addition, the barrel body **112** includes the plurality of slots **122**. In general, slot corresponds to a narrow opening or a slit in a body for receiving one or more components. In other words, hole corresponds to a circular recess or cavity in a body. Further, the barrel body **112** encapsulates the plurality of telescopic lenses. In an embodiment of the present disclosure, the plurality of telescopic lenses is steadily fixed with the barrel body **112** and coaxial with the optical axis of the focal plane array **108**. In general, telescopic lenses is referred as a lens that appears to magnify distant objects. To do that, the telescopic lenses need to have a focal length longer than that of a normal lens, or a lens that approximates the optical qualities of the human eye. In another embodiment of the present disclosure, each telescopic lens in the plurality of telescopic lenses holds fixed distance with respect to each other. The nut **130** fixes the plurality of telescopic lenses into position inside the barrel body **112**.

(27) In an embodiment of the present disclosure, the device **100** includes the plurality of O-rings **110**. In general, O-ring is referred to as gasket or seal in the form of a ring with a circular cross section, which is typically made of rubber and used especially in swiveling joints. The plurality of O-rings **110** is positioned between the housing **102** and the barrel body **112**. The plurality of O-rings **110** facilitates isolation of the device **100** from an outer environment. In addition, the plurality of O-rings **110** seals the plurality of telescopic lenses and the focal plane array **108** from the outside environment, against dust and humidity. Further, the face sealing gasket **128** is included along with the plurality of O-rings **110** as an additional measure of sealing the device **100** from the outside environment.

(28) In an embodiment of the present disclosure, the device **100** includes a plurality of spacers. The plurality of spacers includes the first spacer **124** and the second spacer **126**. In general, spacer is referred to as a device or structure that is used to provide distance between two parts or devices. In another embodiment of the present disclosure, the plurality of spacer can be of any number. The first spacer **124** and the second spacer **126** collectively facilitate appropriate distance between the plurality of telescopic lenses. In an example, the spacers are generally used in optical instruments to get an appropriate distance to have sharp focus of an object. In addition, the device **100** includes the plurality of disks **114**. The plurality of disks **114** includes a first disk and a second disk. In an embodiment of the present disclosure, the plurality of disks **114** may include any number of disks. The plurality of disks **114** is positioned onto the housing **102** in a fixed position. The plurality of disks **114** locks the barrel body **112** into position.

(29) In an embodiment of the present disclosure, the device **100** includes the dioptric adjusting

knob **118**. The dioptic adjusting knob **118** is coupled to the plurality of telescopic lenses with facilitation of the barrel body **112**. In an embodiment of the present disclosure, the dioptic adjusting knob **118** is manually rotatable about the longitudinal axis of the barrel body **112** for displacing the plurality of telescopic lenses to thereby, adjust an optical setting of the telescopic lens. In another embodiment of the present disclosure, the dioptic adjusting knob **118** is restricted to move axially with the facilitation of the plurality of pins **104**. The dioptic adjusting knob **118** includes a female threading. In general, female threading is considered as internal threads. The internal threads are of different shapes like U-shape, V-shape, and the like. The internal threads are of two types, right-hand side external threads and left-hand side external threads. The female threading of the dioptic adjusting knob **118** engages with the male threading of the barrel body **112**. The engagement of the threading locks the barrel body **112** into position with the facilitation of the plurality of disks **114**. In addition, the rotation of the dioptic adjusting knob **118** attempts to rotate the barrel body **112** through the engagement of the threading. Accordingly, the plurality of pins **104** restricts the barrel body **112** to rotate. Further, the movement of the plurality of telescopic lenses in response to rotation of the dioptic adjusting knob **118** alters focus setting of the spotting scope. Furthermore, the engagement of the threaded connection has very low coefficient of performance (hereinafter, COP), during the reverse action of the dioptic adjusting knob **118** a self-locking is achieved. The self-locking of the dioptic adjusting knob **118** prevents from image distortion due to accidentally change in diopter.

(30) In an embodiment of the present disclosure, the plurality of pins **104** along with the plurality of slots **122** ensure movement of the plurality of telescopic lenses against the focal plane array **108**. A pin of the plurality of pins **104** is inserted in a corresponding slot of the plurality of slots **122** of the barrel body **112**. The plurality of pins **104** along with the plurality of slots **122** restricts rotational movement of the barrel body **112**. The plurality of pins **104** along with the plurality of slots **122** enables the movement of the plurality of telescopic lenses along a straight horizontal line. The straight-line movement of the plurality of telescopic lenses results in elimination of skew or distortion in images formed on the focal plane. The device **100** enables a user for dioptic adjustment. In addition, the plurality of pins **104** and the plurality of slots **122** collectively enable limits of dioptic adjustment. The limits of dioptic adjustment incorporate minimum and maximum number of diopters. In general, diopter refers to is a unit of measurement of the optical power of a lens or curved mirror, which is equal to the reciprocal of the focal length measured in meters. For example, a 3-dioptre lens brings parallel rays of light to focus at $\frac{1}{3}$ meter. In another example, a flat window has an optical power of zero diopter, and does not converge or diverge light. In another embodiment of the present disclosure, the device **100** enables the user to temporarily lock the distance between the plurality of telescopic lenses and the focal plane array **108**. The device **100** enables users to lock the plurality of telescopic lenses and the focal plane array **108** at desired position. The device **100** enables symmetrical movement of the plurality of telescopic lenses. The device **100** eliminates skew or distortion caused by the dioptic adjustment.

(31) In an embodiment of the present disclosure, the user is an entity that has authority to use the device **100**. In addition, the user is any person who performs the dioptic adjustment. In another embodiment of the present disclosure, the user is any person who handles operation of the device **100**. In yet another embodiment of the present disclosure, the user is any person who performs maintenance of the device **100**. In yet another embodiment of the present disclosure, the user is any person that has knowledge to operate the device **100**.

(32) The device **100** includes an eyepiece. The eyepiece is mounted on telescopic element. In general, eyepiece correspond to a component that is closest to the eyes of the user when someone is looking through the imaging device. In addition, the device **100** includes the eye cup **120**. In general, eye cups on monocular or binoculars are the 'rings' that are situated around the ocular as it were. The eye cups can be made from silicon, which makes them flexible and easy to fold back, or from hard plastic. The eye cup **120** is connected onto the eyepiece and assembled with the

facilitation of the spring wire clip **116**. The eyepiece facilitates to see the view projected onto the focal plane array **108**. The eye cup **120** forms a substantial seal around the user's eye to restrict leakage of light. Further, the eye cup **120** used can be of two types; open type eye cup and closed type eye cup. The open type eye cup provides a constant opening for the eye to see through. The closed type eye cup provides shutters that open while the area around the eye is pressing the eye cup **120** axially, opening this way the shutters and allowing the eye to see through the plurality of telescopic lenses.

(33) The invention has been successfully incorporated so far, in more advanced imaging systems and thermal imagers containing a number of various sensors such as, thermal cameras, daylight cameras, focal plane arrays, laser range finders, and laser illuminators. In an embodiment of the present disclosure, the plurality of imaging systems includes any suitable imaging systems of the like. The device **100** provides satisfactory testing results for all different configurations.

(34) The device **100** enables dioptric adjustment by rotating the dioptric adjustment knob **118** in desired direction without applying any additional leverage. The dioptric adjustment of the device **100** is easily adjusted by applying force with hands of the user. The device **100** adjusts the dioptric adjustment such that orientation of the focal plane array **108** is always parallel to the barrel body **112**. The device **100** enables movement of the plurality of telescopic lenses with respect to the focal plane array **108**. The device **100** does not rotate or distort the imagery. Further, the device **100** provides smooth operation throughout travel of the plurality of telescopic lenses. In an embodiment the present disclosure, the device **100** is designed to meet needs of thermal infrared (IR) imaging; however, it is applicable to other viewing systems.

(35) The foregoing descriptions of pre-defined embodiments of the present technology have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the present technology to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the present technology and its practical application, to thereby enable others skilled in the art to best utilize the present technology and various embodiments with various modifications as are suited to the particular use contemplated. It is understood that various omissions and substitutions of equivalents are contemplated as circumstance may suggest or render expedient, but such are intended to cover the application or implementation without departing from the spirit or scope of the claims of the present technology.

(36) Accordingly, it is to be understood that the embodiments of the invention herein described are merely illustrative of the application of the principles of the invention. Reference herein to details of the illustrated embodiments is not intended to limit the scope of the claims, which themselves recite those features regarded as essential to the invention.

Claims

1. A device for dioptric adjustment of a plurality of telescopic lenses, the device comprising: a housing, wherein the housing comprises a plurality of pins, wherein the plurality of pins is formed onto the housing; a focal plane array, wherein the focal plane array is affixed with a support structure, wherein the support structure is rigidly affixed inside the housing; a barrel body, wherein the barrel body comprises a plurality of slots, wherein the plurality of pins restricts rotational movement of the barrel body, wherein a pin of the plurality of pins is inserted in a corresponding slot of the plurality of slots of the barrel body, wherein the barrel body encapsulates the plurality of telescopic lenses, wherein the barrel body slides inside the housing, wherein the barrel body and the plurality of telescopic lenses move in forward and backward direction; and a dioptric adjusting knob, wherein the dioptric adjusting knob is coupled to the plurality of telescopic lenses with facilitation of the barrel body, wherein the dioptric adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to adjust an

optical setting of the plurality of telescopic lenses, wherein the dioptric adjusting knob is restricted to move axially with facilitation of the plurality of pins, wherein the device enables the dioptric adjustment of the plurality of telescopic lenses against the focal plane array without causing skew or distortion of view.

2. The device as recited in claim 1, wherein the barrel body comprises male threading, wherein the male threading is machined onto the barrel body.

3. The device as recited in claim 1, further comprising a plurality of spacers, wherein the plurality of spacers facilitate appropriate distance between the plurality of telescopic lenses.

4. The device as recited in claim 1, wherein each telescopic lens of the plurality of telescopic lenses has a fixed distance with respect to each other.

5. The device as recited in claim 1, wherein the dioptric adjusting knob comprises a female threading, wherein the female threading engages with a male threading of the barrel body, wherein a movement of the plurality of telescopic lenses in response to rotation of the dioptric adjusting knob changes a focus setting of the plurality of telescopic lenses.

6. The device as recited in claim 1, wherein an optical axis of the focal plane array is coaxial with the longitudinal axis of the barrel body, wherein the longitudinal axis of the barrel body passes through a center of the barrel body.

7. The device as recited in claim 1, further comprising a plurality of disks, wherein the plurality of disks is positioned onto the housing in fixed position, wherein the plurality of disks locks the barrel body into position.

8. The device as recited in claim 1, wherein the plurality of pins and the plurality of slots collectively enable limits of the dioptric adjustment, wherein the limits comprises a minimum and a maximum number of diopters.

9. The device as recited in claim 1, further comprising a plurality of O-rings positioned between the housing and the barrel body, wherein the plurality of O-rings facilitates isolation of the device from an outer environment.

10. The device as recited in claim 1, further comprising an eye cup, wherein the eye cup is connected onto an eyepiece, wherein the eye cup is assembled with facilitation of a spring wire clip, wherein the eyepiece facilitates to see a view projected onto the focal plane array.

11. The device as recited in claim 1, further comprising an eye cup, wherein the eye cup is connected onto an eyepiece, wherein the eye cup is assembled with facilitation of a spring wire clip, wherein the eyepiece facilitates to see a view projected onto the focal plane array.

12. A device for dioptric adjustment of a plurality of telescopic lenses, the device comprising: a housing, wherein the housing comprises a plurality of pins, wherein the plurality of pins is formed onto the housing; a focal plane array, wherein the focal plane array is affixed with a support structure, wherein the support structure is rigidly affixed inside the housing; a barrel body, wherein the barrel body comprises a plurality of slots, wherein the plurality of pins restricts rotational movement of the barrel body, wherein a pin of the plurality of pins is inserted in a corresponding slot of the plurality of slots of the barrel body, wherein the barrel body encapsulates the plurality of telescopic lenses, wherein the barrel body slides inside the housing, wherein the barrel body and the plurality of telescopic lenses move in forward and backward direction; a plurality of disks, wherein the plurality of disk is positioned onto the housing in fixed position, wherein the plurality of disks lock the barrel body into position; and a dioptric adjusting knob, wherein the dioptric adjusting knob is coupled to the plurality of telescopic lenses with facilitation of the barrel body, wherein the dioptric adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to adjust an optical setting of the plurality of telescopic lenses, wherein the dioptric adjusting knob is restricted to move axially with facilitation of the plurality of pins, wherein the device enables the dioptric adjustment of the plurality of telescopic lenses against the focal plane array without causing skew or distortion of view.

13. The device as recited in claim 12, wherein the barrel body comprises male threading, wherein

the male threading is machined onto the barrel body.

14. The device as recited in claim 12, further comprising a plurality of spacers, wherein the plurality of spacers facilitate appropriate distance between the plurality of telescopic lenses.

15. The device as recited in claim 12, wherein each telescopic lens of the plurality of telescopic lenses has a fixed distance with respect to each other.

16. The device as recited in claim 12, wherein the dioptic adjusting knob comprises a female threading, wherein the female threading engages with a male threading of the barrel body, wherein a movement of the plurality of telescopic lenses in response to rotation of the dioptic adjusting knob changes a focus setting of the plurality of telescopic lenses.

17. The device as recited in claim 12, wherein an optical axis of the focal plane array is coaxial with the longitudinal axis of the barrel body, wherein the longitudinal axis of the barrel body passes through a center of the barrel body.

18. The device as recited in claim 12, wherein the plurality of pins and the plurality of slots collectively enable limits of the dioptic adjustment, wherein the limits comprises a minimum and a maximum number of diopters.

19. The device as recited in claim 12, further comprising a plurality of O-rings positioned between the housing and the barrel body, wherein the plurality of O-rings facilitates isolation of the device from an outer environment.

20. A device for dioptic adjustment of a plurality of telescopic lenses, the device comprising: a housing, wherein the housing comprises a plurality of pins, wherein the plurality of pins is formed onto the housing; a focal plane array, wherein the focal plane array is affixed with a support structure, wherein the support structure is rigidly affixed inside the housing; a barrel body, wherein the barrel body comprises a plurality of slots, wherein the plurality of pins restricts rotational movement of the barrel body, wherein a pin of the plurality of pins is inserted in a corresponding slot of the plurality of slots of the barrel body, wherein the barrel body encapsulates the plurality of telescopic lenses, wherein the barrel body slides inside the housing, wherein the barrel body and the plurality of telescopic lenses move in forward and backward direction, wherein an optical axis of the focal plane array is coaxial with the longitudinal axis of the barrel body, wherein the longitudinal axis of the barrel body passes through a center of the barrel body; a plurality of O-rings positioned between the housing and the barrel body, wherein the plurality of O-rings facilitates isolation of the device from an outer environment; a plurality of disks, wherein the plurality disk is positioned onto the housing in fixed position, wherein the plurality of disks lock the barrel body into position; and a dioptic adjusting knob, wherein the dioptic adjusting knob is coupled to the plurality of telescopic lenses with facilitation of the barrel body, wherein the dioptic adjusting knob is manually rotatable about a longitudinal axis of the barrel body for displacing the plurality of telescopic lenses to adjust an optical setting of the plurality of telescopic lenses, wherein the dioptic adjusting knob is restricted to move axially with facilitation of the plurality of pins, wherein the device enables the dioptic adjustment of the plurality of telescopic lenses against the focal plane array without causing skew or distortion of view.
