

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408626
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Marshall; Whitney

Feeding vessels and feeding vessel shields

Abstract

A feeding bowl assembly has a feeding bowl; a flexible removable shield to partially surround the feeding bowl; a pad for bowl placement having a plurality of arcuate slots to receive an end of the shield having a retaining lip configured to extend through one of the arcuate slots; a band having a pressure sensitive adhesive to attach to the shield; wherein the shield, the pad and the band are configured to be flat packable when unassembled; and wherein the band is configurable to be positioned on the shield to hold an edge of the feeding bowl off the pad. The feeding bowl's width by height may be one of 5 inches by 2 inches; 9.8 inches by 3 inches; 7 inches by 2.5 inches; 12.75 inches by 2.6 inches; and wherein the arcuate slots are configured receive the shield and allow placement of the feeding bowl.

Inventors:	Marshall; Whitney (Brooklyn, NY)
Applicant:	Marshall; Whitney (Brooklyn, NY)
Family ID:	82901614
Appl. No.:	17/738260
Filed:	May 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220264843 A1	Aug. 25, 2022

Related U.S. Application Data

continuation-in-part parent-doc US 16750943 20200123 ABANDONED child-doc US 17738260
us-provisional-application US 62796908 20190125

Publication Classification

Int. Cl.: A01K5/01 (20060101)

U.S. Cl.:

CPC **A01K5/0135** (20130101);

Field of Classification Search

CPC: A47G (23/0633); A47G (23/0303); A47G (2023/0691); A47G (23/032); A47G (19/03);
A47G (19/10); A47G (19/2266); A47G (19/32); A47G (19/34); A47F (7/00); A47F
(5/0006); A47F (7/0064); A47J (47/00); A47J (47/01); B65D (85/325); B65D (85/327)

USPC: 99/645; 206/561; 206/562; 206/564; 220/532; 220/730; 220/731

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1079261	12/1912	Park	N/A	N/A
2419834	12/1946	Grindstaff	N/A	N/A
2556844	12/1950	Istwan	206/139	A47G 23/0641
2589427	12/1951	Ossman	N/A	N/A
2608074	12/1951	Davis	229/5.5	A47G 23/032
2611510	12/1951	Willits	126/299C	A47J 36/064
2664722	12/1953	Barr	220/574	A47G 19/02
2766919	12/1955	Randall	294/159	A47G 23/06
2813509	12/1956	Bruno	D7/553.6	A01K 5/0135
2839028	12/1957	Routh	N/A	N/A
2891695	12/1958	Peters	D7/552.1	A47G 23/06
3651787	12/1971	Cooper	N/A	N/A
3698594	12/1971	Boehlert	119/61.5	A47G 19/03
D286507	12/1985	Drago	D6/535	N/A
4949678	12/1989	Demko	N/A	N/A
5316176	12/1993	Genest	220/731	A47G 23/0633
5492083	12/1995	Holladay	N/A	N/A
D385068	12/1996	Malcolm	N/A	N/A
5709168	12/1997	Walker	N/A	N/A
5755474	12/1997	Slomski	294/87.2	B65D 71/504
6032824	12/1999	Barrow	220/625	A01K 5/0135

6237532	12/2000	Derr	N/A	N/A
D471406	12/2002	Wellner	N/A	N/A
6561375	12/2002	Nagy	N/A	N/A
7124709	12/2005	Greer	119/61.5	A01K 5/0114
7395782	12/2007	Lindsay	119/51.02	A01K 5/025
7607387	12/2008	Stanczak	99/425	A47J 37/108
D606711	12/2008	Becattini, Jr. et al.	N/A	N/A
D642338	12/2010	Becattini, Jr. et al.	N/A	N/A
8146534	12/2011	Robertson	N/A	N/A
8286589	12/2011	Tsengas	N/A	N/A
D683190	12/2012	Shields	N/A	N/A
8690002	12/2013	Finell	220/731	A47G 19/10
9228331	12/2015	Weinstein	N/A	E03C 1/32
9486096	12/2015	Hertz	N/A	B65D 85/72
10251403	12/2018	Hartman	N/A	A21B 3/13
10548294	12/2019	Price	N/A	A01K 7/00
D880787	12/2019	Price	D30/121	N/A
2002/0162511	12/2001	Hollinger	N/A	N/A
2003/0066490	12/2002	Bourigault	N/A	N/A
2003/0230244	12/2002	Morrison	119/61.54	A01K 7/005
2004/0194716	12/2003	Morrison	119/61.1	A01K 7/005
2004/0231607	12/2003	Hollinger	N/A	N/A
2005/0211190	12/2004	Weinblatt	N/A	N/A
2006/0027177	12/2005	Busse	119/61.56	A01K 5/0135
2006/0249089	12/2005	Behunin	N/A	N/A
2007/0034161	12/2006	Thompson	N/A	N/A
2008/0289581	12/2007	Cox, Jr. et al.	N/A	N/A
2009/0241843	12/2008	Becattini, Jr. et al.	N/A	N/A
2010/0038512	12/2009	Esrich	248/346.5	A01K 5/0114
2010/0180827	12/2009	Becattini, Jr. et al.	N/A	N/A
2013/0104808	12/2012	Rocker et al.	N/A	N/A
2014/0165919	12/2013	O'Connor	119/51.01	A01M 29/12
2017/0055491	12/2016	Hsu	N/A	B65D 21/0216
2017/0280676	12/2016	Mendez	N/A	N/A

2020/0022332	12/2019	Nessy	N/A	A01K 5/0114
2020/0060227	12/2019	Bofill	N/A	A01M 29/34
2020/0288669	12/2019	Maring- Teichmann	N/A	B65D 5/22
2022/0055797	12/2021	Liu	N/A	B65D 21/086
2022/0136240	12/2021	Sollie	160/135	A47G 5/00
2022/0264842	12/2021	Ratliff	N/A	A01K 5/0114
2022/0361443	12/2021	Kamaleddine	N/A	A01K 5/0114
2023/0329191	12/2022	Mizrahi	N/A	A01K 5/0114

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2842121	12/2014	CA	N/A
2842121	12/2014	CA	A01K 5/01
686067	12/1952	GB	N/A
707192	12/1953	GB	N/A
1126278	12/1967	GB	N/A
2373494	12/2001	GB	A01K 5/0114
2404834	12/2004	GB	N/A
2599430	12/2021	GB	A01K 5/0114
2019019271	12/2018	KR	A01K 1/0107
2045181	12/2018	KR	A01K 5/008
WO-2010065983	12/2009	WO	A01K 5/0142
WO-2019018887	12/2018	WO	A01K 15/025

OTHER PUBLICATIONS

KR-2045181-B1 text (Year: 2019). cited by examiner

Neater Feeder Express Pet Bowls by Neater Pet Brands (<https://neaterpets.com/collections/neater-feeder/products/neater-feeder-express-for-cats>). cited by applicant

Primary Examiner: Truong; Katelyn T

Attorney, Agent or Firm: Fitch, Even, Tabin & Flannery, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation-in-part of U.S. application Ser. No. 16/750,943, filed Jan. 23, 2020, which claims priority from U.S. Provisional Patent Application 62/796,908, filed Jan. 25, 2019, which are hereby incorporated herein by reference in their entirety for all purposes.

FIELD

(1) Presented herein are feeding vessels and feeding vessel accessories, and in particular, feeding

vessels and feeding vessel accessories with a shield to prevent food spillage.

BACKGROUND

(2) Various vessels have been devised to contain food, in either solid or liquid form. Such vessels are usually sized and shaped to allow an animal, such as a pet, to easily feed from the vessel. Such vessels are normally sized and shaped to be no bigger than is needed to accommodate the animal for which the vessel is designed. One of the problems of this type of design is that it does not address an animal's lack of awareness of the spillage from the vessel while feeding.

(3) Some rudimentary efforts are known in the art to address this matter such as found in U.S. Pat. No. 1,079,261 to Park (for birds); U.S. Pat. No. 8,286,589 to Tsengas (attachable cover); GB2404834A to Weideger (small short collar); and US Pub. 20050211190 to (guard to hold back ears of floppy eared dog). Other devices include large elevated housings for multiple feeding vessels, such as one sold under the tradename NEATER FEEDER EXPRESS PET BOWLS by Neater Pet Brands (neaterpets.com/neater-feeder).

(4) Accordingly, while food vessels and some rudimentary food vessel shields are known, there remains a desire and a need in the art to provide a vessel or a detachable vessel accessory to reduce food spillage while a pet feeds from the vessel with minimal increase in floor footprint and expense.

SUMMARY

(5) Accordingly, to advance at least the aforementioned deficiencies in the art, described herein are feeding vessels and feeding vessel accessories, and in particular, feeding vessels and feeding vessel accessories with a shield to prevent food spillage.

(6) According to one approach, a feeding vessel assembly, is provided having a feeding bowl having a cavity to receive food and water and a rim or blunt edge defining an upper edge of the feeding bowl, a deformable shield which is detachable from the feeding bowl rim wherein the shield when installed encloses up to about 75 percent of the circumference of the top rim thus providing an opening for an animal to access the feeding bowl cavity, wherein the shield extends from the rim of the feeding bowl to a height of about 12 inches from the floor, and wherein the shield flares outwardly from the rim of the feeding bowl as it extends upwardly in the range of about 1 to 30 degrees and is configured to allow an animal to push food up an inside wall of the shield so that it can slide the food into its mouth when it opens its mouth. It is noted though that the height can be higher depending on the size of the animal. For example, the shield may need to be higher for a golden retriever than it would be for a pug.

(7) In this approach, the assembly may also include a pad having an opening to receive a base of the feeding bowl and a food dispenser which is configured to dispense food into a side feeding bowl. The shield can be formed from a deformable plastic, rubber, cardboard, combinations thereof, and the like.

(8) According to another approach, a feeding vessel assembly may have a feeding bowl having a cavity to receive food and water, a integral shield extending above the feeding bowl cavity wherein the shield encloses up to about 75 percent of the circumference of the top rim thus providing an opening for an animal to access the feeding bowl cavity, wherein the shield extends to a height of about 12 inches from the floor, and wherein the shield flares outwardly from the feeding bowl cavity as it extends upwardly in the range of about 1 to 30 degrees and is configured to allow an animal to push food up an inside wall of the shield so that it can slide into its mouth when it opens its mouth.

(9) According to another approach, a shield for a feeding bowl is provided having a trimmable and deformable shield wall having an adhesive layer to attach to contours of an interior wall of a feeding bowl cavity; the shield configured to, when installed on the feeding bowl, extend above the feeding bowl cavity wherein the shield encloses up to about 75 percent of the circumference of a top rim of the feeding bowl thus providing an opening for an animal to access the feeding bowl cavity, wherein the shield extends to a height of about 12 inches from the floor or from the height

of the bowl (i.e., it could add additional height to the already existing bowl, and wherein the shield flares outwardly from the feeding bowl cavity as it extends upwardly in the range of about 1 to 30 degrees and is configured to allow an animal to push food up an inside wall of the shield so that it can slide into its mouth when it opens its mouth.

(10) An optional feature of the present embodiments is to provide a disposable liner configured to line the interior cavity of the feeding bowl.

(11) According to another approach, a feeding bowl assembly is provided having a feeding bowl with a cavity to receive food and water; a flexible removable shield to partially surround the feeding bowl; a pad to place the feeding bowl on, the pad having a plurality of arcuate slots to receive an end of the flexible removable shield having a retaining lip configured to extend through one of the arcuate slots; a band having a pressure sensitive adhesive to attach to the shield; wherein the shield, the pad and the band are configured to be flat packable when unassembled; and wherein the band is configurable to be positioned on the shield to hold an edge of the feeding bowl off the pad. The feeding bowl's width by height may be one of 5 inches by 2 inches; 9.8 inches by 3 inches; 7 inches by 2.5 inches; 12.75 inches by 2.6 inches; and wherein the arcuate slots are configured receive the shield and allow placement of the feeding bowl.

(12) In some embodiments, the pad may be approximately 48 cm by 30 cm (i.e., approximately 18.9 inches by 11.8 inches). The shield that is inserted into the mat may itself be approximately 14 inches in height. The width of the shield may vary based on the size of the bowl and the desired opening of the shield to access the bowl (i.e., the amount of the circumference of the bowl the shield is configured to surround. A shield that is configured for placement on the lip/edge of the bowl may be approximately 12 in high. The difference is to accommodate the added height of the bowl so the combined height of the bowl and shield is similar to the 14 inch height of the shield attached to the mat.

(13) Other features will become more apparent to persons having ordinary skill in the art to which the assemblies pertain and from the following description and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a feeding vessel assembly including an exemplary shield, according to the present invention;

(2) FIG. 2 is an exploded perspective view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 1;

(3) FIG. 3 is a top view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 1;

(4) FIG. 4 is a front view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 1;

(5) FIG. 5 is a cross-sectional front view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 1 taken along lines V-V in FIG. 1;

(6) FIG. 6 is a side view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 1;

(7) FIG. 7 is a cross-sectional side view of a feeding vessel assembly in use including an exemplary shield, according to the present invention of FIG. 1 taken along lines VII-VII in FIG. 1;

(8) FIG. 8 is a perspective view of another feeding vessel assembly including an exemplary shield, according to the present invention;

(9) FIG. 9 is an exploded perspective view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 8;

(10) FIG. 10 is a front view of a feeding vessel assembly including an exemplary shield, according

to the present invention of FIG. 8;

(11) FIG. 11 is a cross-sectional front view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 8 taken along lines XI-XI in FIG. 8;

(12) FIG. 12 is a perspective view of another feeding vessel including an integral exemplary shield, according to the present invention;

(13) FIG. 13 is a front view of a feeding vessel including an exemplary shield, according to the present invention of FIG. 12;

(14) FIG. 14 is a cross-sectional front view of a feeding vessel including an exemplary shield, according to the present invention of FIG. 12 taken along lines XIV-XIV in FIG. 12;

(15) FIG. 15 is a side view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 12;

(16) FIG. 16 is a cross-sectional side view of a feeding vessel assembly in use including an exemplary shield, according to the present invention of FIG. 12 taken along lines XVI-XVI in FIG. 12;

(17) FIG. 17 is a perspective view of another feeding vessel including an exemplary shield, according to the present invention;

(18) FIG. 18 is a perspective view of an exemplary feeding vessel shield, according to the present invention;

(19) FIG. 19 is a perspective view of another feeding vessel assembly including the exemplary shield of FIG. 18, according to the present invention;

(20) FIG. 20 is an exploded perspective view of another feeding vessel assembly including the exemplary shield of FIG. 18, according to the present invention of FIG. 19;

(21) FIG. 21 is a side view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 19;

(22) FIG. 22 is a front perspective view of another feeding vessel including an integral exemplary shield, according to the present invention;

(23) FIG. 23 is a side, elevational view of a cross section of the feeding vessel including an integral exemplary shield of FIG. 22;

(24) FIG. 24 is a front perspective view of a disposable liner for a feeding vessel according to the present invention;

(25) FIG. 25 is a front perspective view of a disposable liner for a feeding vessel according to the present invention;

(26) FIG. 26 is a front perspective view of a disposable ramp/liner for a feeding vessel according to another approach;

(27) FIG. 27 is a front planar sectional view of a disposable ramp/liner for a feeding vessel according to FIG. 26;

(28) FIG. 28 is a front perspective view of an optional disposable wedge and protective cover for a feeding vessel according to one approach to the present invention;

(29) FIG. 29 is a side planar sectional view of the optional disposable wedge and protective cover according to FIG. 28;

(30) FIG. 30 is a side planar sectional view of an optional protective cover;

(31) FIG. 31 is a side planar sectional view on an injection molded feeding vessel according to another approach;

(32) FIG. 32 is a front perspective view of a feeding vessel according to another approach configured to receive a feed bowl;

(33) FIG. 33 is a side planar sectional view of the optional disposable wedge and protective cover according to FIG. 28 elevated above the bottom of the bowl;

(34) FIG. 34 is a side planar sectional view of the optional disposable wedge and protective cover according to a feeding vessel according to one approach to the present invention having a hook and the protective cover having openings to receive the hook;

(35) FIG. 35 is a front perspective view of a disposable ramp/liner for a feeding vessel according to another approach having a hook;

(36) FIG. 36 is a front planar sectional view of a disposable ramp/liner for a feeding vessel according to FIG. 35, with the feeding vessels having openings to receive the hook;

(37) FIG. 37 is a side planar sectional view of the feeding vessel of FIG. 38 taken along section line XXXVII-XXXVII of FIG. 38;

(38) FIG. 38 is a perspective view of an optional disposable wedge to a feeding vessel according to one approach to the present invention having a wedge hook and the feeding vessel having openings to receive the wedge hook. FIG. 39A is a side view of a wedge according to another approach;

(39) FIG. 39A is a side view of a wedge according to another approach;

(40) FIG. 39B is a side view of a wedge according to another approach;

(41) FIG. 39C is a side view of a wedge according to another approach;

(42) FIG. 39D is a side view of a wedge according to another approach;

(43) FIG. 40 is a perspective view of feeding vessel assembly including an exemplary shield, according to another approach;

(44) FIG. 41 is a cross-sectional front elevation view of the another feeding vessel assembly including multiple exemplary shields, according to the present invention of FIG. 43 taken along section lines XLI-XLI;

(45) FIG. 42 is an exploded perspective view of feeding vessel assembly according to another approach including two exemplary shields mountable to a raised pad portion and bowls;

(46) FIG. 43 is a perspective view of the feeding vessel assembly of FIG. 42;

(47) FIG. 44 is a cross-sectional side view of a feeding vessel assembly in use including an exemplary lipped shield, according to embodiment of FIG. 45;

(48) FIG. 45 is an exploded perspective view of feeding vessel assembly including an exemplary lipped shield, according to another approach present invention;

(49) FIG. 46 is a cross-sectional front elevation view of the feeding vessel assembly of FIG. 45;

(50) FIG. 47 is a perspective view of a feeding vessel assembly including an exemplary shield, according to another approach including one exemplary shield mountable to a raised pad portion and two bowls;

(51) FIG. 48 is a cross-sectional side view of a feeding vessel assembly of FIG. 47 in use including an exemplary lipped shield;

(52) FIG. 49 is a cross-sectional front elevation view of the feeding vessel assembly of FIG. 48 showing an optional lipped shield;

(53) FIG. 50 is an exploded perspective view of a feeding vessel assembly of FIG. 49 including an exemplary lipped shield;

(54) FIG. 51 is an exploded perspective view of feeding vessel assembly according to another approach including an alternate base configuration having a slotted ridge on the pad shaped to receive an exemplary lipped shield;

(55) FIG. 52 is an exploded perspective view of feeding vessel assembly according to another approach including an alternate base and tabbed shield configuration;

(56) FIG. 53 is a cross-sectional front elevation view of a feeding vessel assembly of FIG. 52;

(57) FIG. 54 is a cross-sectional front view of a feeding vessel assembly of FIG. 51 including an exemplary shield;

(58) FIG. 55 is an exploded view of a flat packed unassembled shield and mat of the feeding vessel of FIG. 50;

(59) FIG. 56 is an exploded view of a flat packed unassembled shield and mat of the feeding vessel of FIG. 52;

(60) FIG. 57 is a cross-sectional side view of the attachment portion of an exemplary shield to the mat of the feeding vessel assembly of FIG. 50;

(61) FIG. 58 is a cross-sectional side view of the attachment portion of an exemplary shield to the

mat of the feeding vessel assembly of FIG. 52;

(62) FIG. 59 is a cross-sectional side view of the attachment of an exemplary shield to the mat of the feeding vessel assembly of FIG. 51.

(63) FIG. 60 is a perspective view of feeding vessel assembly including an exemplary shield, according to another approach;

(64) FIG. 61 is an exploded view of disassembled stacked mats and shields of FIG. 60;

(65) FIG. 62 is an exploded perspective view of feeding vessel assembly including an exemplary shield, according to another approach similar to FIG. 45 having optional edge to receive a base of bowl 34;

(66) FIG. 63 is an assembled perspective view of the feeding vessel assembly including an exemplary shield of FIG. 62;

(67) FIG. 64 is a cross-sectional side view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 62;

(68) FIG. 65 is a perspective view of another feeding vessel assembly including an exemplary shield with pad retaining clips, according to the present invention;

(69) FIG. 66 is an exploded perspective view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. 65;

(70) FIG. 67 is a perspective view of another feeding vessel assembly including an exemplary collapsible shield, according to the present invention;

(71) FIG. 68 is the collapsible shield of FIG. 67, according to the present invention in the extended position;

(72) FIG. 69 is the collapsible shield of FIG. 67, according to the present invention in the collapsed position;

(73) FIG. 70 is an exploded perspective view of a feeding vessel assembly including an exemplary collapsible shield, according to the present invention of FIG. 67;

(74) FIG. 71 is a perspective view of a feeding vessel having integral shield/bowl/mat, according to the present invention;

(75) FIG. 72 is a cross-sectional side view of a feeding vessel of FIG. 71 taken along section lines LXXII-LXXII of FIG. 71;

(76) FIG. 73 is stackable feeding bowl according to another embodiment of the present invention with a raised back wall;

(77) FIG. 74 is a cross-sectional side view of the bowl of FIG. 73 taken along section lines LXXIV-LXXIV of FIG. 73;

(78) FIG. 75 is a cross-sectional side view of multiple stacked bowls of FIG. 73;

(79) FIG. 76 is a cross-sectional side view of the feeding bowl assembly of FIG. 77, taken along section lines LXXVI-LXXVI of FIG. 77;

(80) FIG. 77 is a perspective view of the feeding vessel assembly of FIG. 73 including of an exemplary shield, according to the present invention;

(81) FIG. 78 is a perspective view of flexible shield 241 that fits into a bowl 228;

(82) FIG. 79 is an exploded perspective view of a feeding vessel assembly including an exemplary bowl mat and shield, according to the present invention of FIG. 77;

(83) FIG. 80 is a cross-sectional side view of feeding bowl 228i of FIG. 73 according to another approach without an annular base ring 232;

(84) FIG. 81 is a cross-sectional side view of a stack of feeding bowls 228i;

(85) FIG. 82 is a cross-sectional side view of feeding bowl 228ii according to another approach without an annular base ring and a higher raised back wall portion;

(86) FIG. 83 is a cross-sectional side view of a stack of feeding bowls 228ii of FIG. 82;

(87) FIG. 84 is a perspective view of another feeding vessel assembly according to the present invention;

(88) FIG. 85 is an exploded perspective view of another feeding vessel assembly according to the

present invention;

(89) FIG. **86** is a perspective view of a feeding vessel assembly according to the present invention of FIG. **85**;

(90) FIG. **87** is a perspective view of a feeding assembly including an exemplary shield, according to the present invention of FIG. **88**;

(91) FIG. **88** is an exploded perspective view of the embodiment of FIG. **87**;

(92) FIG. **89** is a cross-sectional side view of the feeding assembly of FIG. **87** including an exemplary shield, according to the present invention of FIG. **87** taken along section lines LXXXIX-LXXXIX of FIG. **87**;

(93) FIG. **90** is an exploded perspective view of another feeding assembly including an exemplary shield, according to the present invention;

(94) FIG. **91** is a cross-sectional side view of the shield of FIG. **90**;

(95) FIG. **92** is a cross-sectional side view of an assembled feeding vessel assembly of FIG. **90**;

(96) FIG. **93** an exploded view of an unassembled feeding vessel assembly of FIG. **90**;

(97) FIG. **94** is a packaging/box/shrink wrap of the flat pack unassembled feeding vessel assembly of FIG. **90**;

(98) FIG. **95** shows optional stackable feeding bowls for the assembly of FIG. **90**;

(99) FIG. **96** shows optional stackable feeding bowls of varies sizes to match the slots for the mat for the assembly of FIG. **90**;

(100) FIG. **97** is a front view of another feeding assembly including an exemplary integral shield and feeding silo, according to the present invention;

(101) FIG. **98** is a cross-sectional side view of a feeding assembly including an exemplary shield, according to the present invention of FIG. **97** taken along section lines XCVIII-XCVIII of FIG. **97**;

(102) FIG. **99** is an exploded perspective view of the feeding bowl assemblies of FIG. **97** with an optional mat;

(103) FIG. **100** is an exploded perspective view of the feeding vessel of FIG. **97**;

(104) FIG. **101** is an exploded perspective view of the feeding vessel of FIG. **97** with a variation of the bottom lip of the partition silo;

(105) FIG. **102** is a front view of the feeding vessel of FIG. **101**;

(106) FIG. **103** is a cross section view of the feeding vessel of FIG. **102**, taken along section lines CIII-CIII of FIG. **102**;

(107) FIG. **104** is a front perspective view of another feeding assembly including an exemplary integral shield and feeding silo, according to the present invention;

(108) FIG. **105** is cross sectional view of the feeding vessel of FIG. **104** taken along section lines CV-CV of FIG. **104**;

(109) FIG. **106** is a rear perspective view of the feeding assembly of FIG. **104**;

(110) FIG. **107** is a front perspective view of another feeding assembly including an exemplary integral shield, according to the present invention;

(111) FIG. **108** is cross sectional view of the feeding vessel of FIG. **107** taken along section lines CVIII-CVIII of FIG. **107**;

(112) FIG. **109** is an exploded front perspective view of the feeding assembly of FIG. **107**;

(113) FIG. **110** is a front perspective view of another feeding assembly including an exemplary removable shield, according to the present invention;

(114) FIG. **111** is a closeup view of area CXI of FIG. **110**; and

(115) FIG. **112** is a front perspective view of another feeding assembly including an exemplary removable integral shield, according to the present invention.

(116) While the features described herein may be susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to be limiting to the particular form disclosed, but on the

contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the subject matter as defined by the appended claims.

DETAILED DESCRIPTION

(117) Many animals, such as household pets, including but not limited to cats and dogs, often eat and drink out of vessels or bowls made for human use or bowls that have a similar shape to bowls made for human use. For many animals, use of such bowls results in food or water spilling over the sides of the bowl because the animal uses the side of the bowl to help get food/water into its mouth. Also, just normal head motions of the animal can lead to spillage because the sides of the bowl are not tall enough.

(118) Keeping food in bowls is particularly difficult for flat-faced breeds of cats and dogs, known as brachycephalic breeds. Because they have flat faces, rather than a pointed snout, they have to rely on the sides of their feeding bowls as a surface to help them push food into their mouths. This results in food spillage and difficulty eating. The present embodiments provide food vessels and accessories that can help animals get food into their mouths and keep unconsumed food in the bowls. The present vessels are thus configured to prevent food from spilling out of the bowl and to assist animals to get food into their mouths.

(119) According to one approach of the present embodiments, a bowl is provided having an elongated back and sides. The front of the bowl is lower than the back and sides of the bowl. The front of the bowl is high enough to contain dry or wet food, preventing the food from spilling onto the floor. The back and sides of the bowl are configured to be high enough to allow an animal to push their food around during consumption without spillage. In one embodiment, the back and sides can be approximately twelve inches high, but may be higher to conform to the intended animal breed for the vessel. The height of the sides should be close to the height of the animal's shoulders when sitting upright—because that is the height of the animal's head when it comes up from scooping food into their mouths.

(120) The bottom of the bowl can be flat or rounded. The back and/or sides of the bowl may be straight or slanted towards the front of the bowl and create a funnel effect by tilting the back and sides towards the animal's mouth. This allows the animal to push food up against the taller side surface, lift their chins, and the pull of gravity then slides/drops the food into their mouths.

(121) The present embodiments provide several features and advantages not known in the art.

(122) The present food vessel is not an elevated stand for multiple food bowls. In one approach, it has no removable parts (i.e., it is a bowl with high sides and a high back). The tall back and sides of the present embodiments may also be slanted towards the center of the bowl (instead of being vertical). Also, the sides and back are all the same height, rather than slanted towards the front of the bowl, such as one where the sides are slanted lower in height than the back as it approaches the front of the vessel. The present embodiments do not have an automatic closure in the front that can be easily opened by the animal; nor does it have a cover at the top.

(123) The present embodiments may be formed from a variety of materials. If the bowl is one piece including the shield, it can be made from a variety of materials such as plastic, various metal compositions (e.g., stainless steel, and the like), glass, ceramic, stoneware, silicone, acrylics, wood, deformable compositions (e.g., rubber), and the like. The present embodiments and any of its optional components may be clear (transparent) or various degrees of opaqueness/translucence in any combination. Optional features can include a rubber layer (or a tacky/sticky/adhesive base material) on the bottom surface to reduce sliding on the floor when in use. Optionally, the present embodiments may also include weights in the bottom to prevent the bowl from tipping over if the vessel is not made of a heavy material.

(124) According to one approach where a prior art vessel is provided, a detachable shield can be provided. The shield could be configured to stand at least 12 inches off the floor or the bowl when installed in the food vessel. The detachable shield may be made of a material that is flexible and can take on the shape of the food vessel and allow attachment to the rim of the vessel. Such

materials may include plastic, metal, or any flexible/deformable material. Even though the material is deformable, it must be remain upright while in use (i.e., when the animal is feeding from the vessel) and strong enough that it will not fold over if the animal pushes their face up against it when getting food into their mouths.

(125) The detachable shield may be attached to the already-existing food bowl with an adhesive (removable/pressure sensitive adhesive or permanent adhesive), a suction cup configuration (i.e., a user wets the material and it retains a suction force to remain adhered to the vessel), clips, hook and loop fasteners (such as one sold under the tradename VELCRO), or has a lip shaped to match the rim of the feeding vessel to allow it to snap into place. The detachable shield may be attached on the inside of the bowl or on the outside of the bowl. Attachment inside the bowl would be preferred to reduce potential gaps of space between the food bowl and the shield and would allow the wall of the vessel to provide support to the shield when in use. The detachable shield can be disposable and formed from a variety of deformable materials such as plastic, paper (e.g., cardboard), rubber, and the like.

(126) The detachable shield may be adjustable/trimmable to adjust to the diameter of the food bowl already owned. The adhesive would provide a snug fit to the sides of the bowl so food cannot fall in between the holder and the bowl.

(127) Accordingly, the present embodiments provide a shield that should be at least 12 in. high all the way around, except for the front of the bowl (so the animal can walk up to the bowl and stick their head into the food). The tall shield does not go around the entire circumference of the bowl, but rather approximately $\frac{3}{4}$ around the bowl, leaving part of the bowl without a shield so the animal's face will be able to access the food in the bowl.

(128) Turning to the figures, FIGS. 1-7 show one approach to the present embodiments. A feeding Vessel Assembly 30 can have a shield/collar/apron ("shield") 32, which is detachable from a feeding vessel 34. Shield 32 can attach to a feeding vessel rim 38 by a deformable shield lip configured to match feeding vessel rim 40. A non-skid pad 36 can optionally be provided to reduce sliding of the animal and/or the feeding vessel while in use and to also keep a pet owner's floor clean. A feeding vessel bottom flange 42, which can also include weights to stabilize the assembly further, can be configured to be received by a pad opening 44. Pad opening 44 can be configured to receive a portion (including all) of feeding vessel bottom flange. Weight can range up to about 3 or 4 pounds. As mentioned herein, the shield does not cover the entire circumference of the rim of feeding vessel 34, but is provided with an opening 52 to allow an animal 56 to access the contents of the feeding vessel. As shown in FIGS. 4 and 5 a lower shield opening 46 can be in the range of 30-180 degrees; upper shield opening 48 can be in the range of 30-180 degrees; side taper 50 of shield 34 can be in the range of -45 to 80 degrees. A shield opening flare 54 can be in the range of -45 to 170 degrees (preferably about 30 to 90 degrees and most preferably about 35 degrees), and a shield taper 58 can be in the range of -45 to 170 degrees (preferably about 30 to 90 degrees and most preferably about 35 degrees). It is noted that within this range, the shield can be vertical.

(129) FIGS. 8-11 show another approach to the present embodiments. In this assembly, an optional food dispenser 60 is provided having a feeding vessel opening 62 to receive food from food dispenser opening 66 (FIG. 9). Here feed/food/liquid 64 can travel through food dispenser opening 66. FIG. 11 shows a food dispenser top hinged lid 68.

(130) FIGS. 12-16 show another approach to the present embodiments. In this assembly a feeding vessel 70 as an integrated shield 72 and a base 74. An optional rubber layer or other adhesive or antiskid layer 75 can be supplied where the base meets the floor. It is noted though that any of the embodiments described herein can have this antiskid feature. Feeding vessel 70 has a cavity to receive food/liquids 76 and an opening 78 for the animal to access the contents of the cavity. In this one piece embodiment, top opening dimension 80 and bottom opening dimension 82 can be in the proportional ratio ranges of 1:2 to 1:1 to 2:1 (i.e., the top can be in the range of half or double the dimension of the top opening dimension).

(131) FIG. 17 shows another approach to the present embodiments. In this assembly a cuboid or rectilinear feeding vessel is provided having a feeding vessel with shield **84** having side shields **86**, a back shield **88**, and a front shield **90** to form a cavity **92** to contain food/water. In this embodiment front shield height **92** can be in the range of 10 to 90 percent of side shield height **95**. As mentioned above side shield height **95** is preferably at least 12 inches above floor level. It is noted that the embodiment of FIG. 17 may also be configured in a variety of other ways, for example in the front **90** and sides (**86** and **84**) do not need to be planar, but could be curved toward the front so they connect to front shield **90**, but still configured so that there is just enough room for the animal's head. (Cf., FIG. 22 where it could be an angular version like this, with the pieces in the front)

(132) FIGS. 18-21 show another approach to the present embodiments. In this approach, an animal owner may already have a feeding vessel **96** to which the animal is accustomed. In this instance a deformable shield **100** can be provided having a shield wall **102** and an adhesive layer **104** (e.g., a pressure sensitive adhesive) to attach to the feeding vessel interior or exterior wall **98**. Shield **100** can deform to match the contours of feeding vessel **96** and can be made of a material, such as a rigid but deformable plastic, rubber or cardboard that can even be trimmed to allow for an adequate opening for the animal to access the contents of the feeding vessel. It is noted that shield **100** can be cut in two (for example) to fit to the sides of an automatic feeder to prevent the shield from blocking food from being dispensed by the automatic feeder.

(133) FIGS. 22 and 23 show cylindrical feeding vessel **106** including an integral exemplary shield **107**, according to the present invention according to another approach. In this embodiment, the feeding vessel has an integral shield and is configured to have parallel sides **110** and parallel edges **108** to opening **114** for an animal to access the feeding vessel cavity **120**. In other words, in this embodiment, the diameter **110** of feeding vessel is the same from top to bottom. Similarly, the opening **112** and feeding vessel back wall are also parallel. A front portion side height **116** can be approximately 10 percent of the height of feeding vessel and shield **118**. This embodiment can also have a cavity **120** that is defined by a curved wall sloping sides as shown at **122**. This shield can also be designed so that it too flares outward. It can rise vertically such as shown in the figure, but within the scope of the present embodiments some approaches can have a shield flares out like the bowls shown herein (See e.g., FIG. 6.) and have an adhesive at its bottom, such as a pressure sensitive adhesive.

(134) FIGS. 24 and 25 show optional disposable liners that can be applied for example to the feeding vessel of FIG. 1 prior to attaching shield **32** around vessel **34** lip **38**. Also, FIG. 25 shows an exemplary liner that can be installed on, for example, the feeding vessel of FIG. 12 or as shown as feeding vessel **134**.

(135) Specifically, FIG. 24 is a front perspective view of a feeding vessel disposable liner **124** for a feeding vessel **34**. Liner portion **126** is configured to line the interior cavity of the feeding vessel **34**; the liner can be optionally held in place by an elastic band **128** or other attachment means such as pressure sensitive adhesives, clips, hook and loop fasteners and the like. The elastic band would not be needed to hold the liner in place if it is installed prior to attaching shield **32** to feeding vessel **34** via lip **440** onto rim **38**. Once installed, liner portion **130** lines the interior of vessel cavity while liner portion **132** extends beyond elastic band to allow a pet owner to allow disposal of liner material

(136) FIG. 25 is a front perspective view of a feeding vessel according to another approach to the present invention. As shown, feeding vessel can have an integral shield **134**; a feeding bowl portion **136**; feeding vessel bottom flange **138**; feeding vessel cavity **139**; feeding vessel with integral shield disposable liner **140**; liner portion to cover shield **142**; liner portion to line interior of vessel cavity **144**; elastic band **146**; and liner portion **148** extending beyond elastic band to allow a pet owner to allow disposal of liner material. Liner portion **142** may optionally have pressure sensitive adhesive to hold the liner to the shield portion **141**. The liner portion may also attach to

the back shield only and one version may attach to the side shields as well. It is noted though that clips, hook and look fasteners could also be used. According to another approach, the disposable liner can conform to the embodiments of FIG. 22 and FIG. 17 that can be made from cardboard, for example, that can be placed inside an already existing bowl. It can come in small, medium, and large sizes to fit an already existing bowl or it can be adjustable. A reusable liner can also be configured according to another approach in the shape of the embodiment of FIG. 22 whereby the liner is placed into an already existing bowl and can be taken out to be cleaned.

(137) FIG. 26 is a front perspective view of a disposable ramp/liner 152 for a feeding vessel according another approach. This ramp can be added to any feeding vessel to provide an increased and removable ramp. FIG. 27 shows a planar sectional view of disposable ramp/liner 152 installed in an exemplary a feeding vessel 70.

(138) FIG. 28 shows a front perspective view of an optional disposable wedge e.g., disposable and or removable) 154 and protective cover 156 for a feeding vessel according to one approach to the present invention. As shown in FIG. 29, the optional disposable wedge 154 and optional protective cover 156 may also be placed in an exemplary feeding vessel 70 to increase the ramp angle. As shown, foldable flap 158 for the optional protective cover 156 can be wrapped over feeding vessel shield top 160.

(139) FIG. 30 is a side planar sectional view of an optional protective cover according to another approach. In this embodiment, protective cover 156i can made from rigid but deformable material (such as a thin aluminum plate (about 1 mm thick)) disposed along a back wall 182 of shield 70 that can be folded over 158 the top of shield 160. Lower portion 176 of protective cover 156i can be made from a more rigid material such as a thick aluminum plate (e.g., >1 mm) or rigid plastic or even wood. In use, a user may adjust the height and angle of lower portion 176 by lifting fold over portion 158 to the desired height and folded along the top of shield top 160.

(140) FIG. 31 is a side planar sectional view on an injection molded feeding vessel according to another approach. In this embodiment, feeding vessel 70 can be formed by a single piece injection molding process and have a void are 180 between the outside of the vessel and integral ramp 162.

(141) FIG. 32 shows a front perspective view of a feeding vessel according another approach. In this embodiment, a removable bowl 34i can placed within feeding vessel with shield 70. It is noted though that adding bowl 34i can be configured for placement within any of the feeding vessels.

(142) FIG. 33 is a side planar sectional view of the optional disposable/removable wedge and protective cover according to FIG. 29 elevated above the bottom of the bowl.

(143) FIG. 34 is a side planar sectional view of the optional disposable wedge and protective cover according to a feeding vessel according to one approach to the present invention having a hook 164 and the protective cover 156 having openings 166 to receive the hook. According to this approach, the user may raise and lower wedge 154 to a desired height.

(144) FIG. 35 is a front perspective view of a wedge 154i for a feeding vessel 70i according another approach. This ramp 152i can be added to any feeding vessel to provide an increased and removable ramp using hook 168 to any of the openings 170 of feeding vessel 70i as shown in FIG. 36.

(145) FIG. 38 is a perspective view of an optional disposable wedge 154i to a feeding vessel 70i according to one approach to the present invention having a wedge hook 172 and the feeding vessel 70i having openings 174 to receive wedge hook 172. FIG. 37 is a side planar sectional view of the feeding vessel of FIG. 38 taken along section line XXXVII-XXXVII of FIG. 38. In one approach, a plastic mold for a bowl may have an integral wedge that is part of the mold that just extends into the cavity of the bowl (See, e.g., FIG. 30).

(146) FIG. 39A-D are side views of a wedge according to other approaches. The optional hook is shown for reference, though would only be needed in those embodiments with the shield openings.

(147) FIGS. 40-112 provide additional approaches to the present embodiments. It is noted that the present embodiments may be used for liquid and solid foods. Accordingly, in some embodiments

the bowl may be a water bowl. In some embodiments, the mat can be a single piece with no movable or removable parts.

(148) It is also noted that although a removable bowl is shown, for example, in FIG. 32, other variations of the present embodiments may have no bowl inserted and the pet can just eat out of the shield itself. That is, the shield is the bowl. The detachable shield can be disposable and formed from a variety of deformable materials such as plastic, paper (e.g., cardboard), rubber, and the like. Liners may be used, such as shown in FIG. 25. The pad may also be disposable and formed from a variety of deformable materials such as plastic, paper (e.g., cardboard), rubber, non-skid surfaces and the like.

(149) FIG. 40 is a perspective view of feeding vessel assembly including an exemplary shield, according to another approach showing a mat 36 with a shield 32 attached (fixed permanently or removable). A bowl 34 can slide into and out of the shield.

(150) FIG. 41 is a cross-sectional front elevation view of the another feeding vessel assembly including multiple exemplary shields, according to the present invention of FIG. 43 taken along section lines XLI-XLI. The figure shows a back portion a mat 36 with two removable or permanent shields 32 attached and bowls 34 inside the shields 32 on top of the mat 36. FIG. 41 also shows an slotted portion 186 of an elevated portion 184 of mat 36.

(151) FIG. 42 is an exploded perspective view of a feeding vessel assembly according to another approach including two exemplary shields mountable to a raised pad portion and bowls. FIG. 42 shows the portion 184 of mat 36 section with slot/groove 186. The removable shields 32 fit into the slots 186. Elevated portion 184 is about ¼ inch to 1 inch higher than the mat 36 top surface.

(152) FIG. 43 is a perspective view of the feeding vessel assembly of FIG. 42. Mat 36 has two shields 32 inserted into the slots 186 housing two bowls that can slide in and out of the shields or up and out of the shields.

(153) FIG. 44 is a cross-sectional side view of a feeding vessel assembly in use including an exemplary lipped 188 shield 32, according to embodiment of FIG. 45. The figure shows a side view of a pet eating out of a bowl on the mat 36. The front opening of the shield is wide enough to allow an animal to stick its head inside to access the food in the bowl. This can be about a 45 degree to 100 degree opening, preferably about 50 degree to 120 degree opening.

(154) FIG. 45 is an exploded perspective view of feeding vessel assembly including an exemplary lipped 188 shield 32, according to another approach present invention. The figure shows A mat 36 with grooves, a removable shield that fits into the groove and a view of a bowl and how it fits in the shield on the mat.

(155) FIG. 46 is a cross-sectional front elevation view of the feeding vessel assembly of FIG. 45. The figure shows a mat 36 with one removable shield 32 attached to mat 36 through slot 186 by retaining lip 188 and a bowl 34 inside shield 32.

(156) FIG. 47 is a perspective view of a feeding vessel assembly including an exemplary shield, according to another approach including one exemplary shield mountable to a raised pad portion and two bowls. A mat 36 is shown having a raised platform 184 to accommodate one shield 32 and bowl 34. The other side of the mat 36 has open to allow for another item placement or just left open.

(157) FIG. 48 is a cross-sectional side view of a feeding vessel assembly of FIG. 47 in use including an exemplary lipped 188 shield 32. As shown in this figure a pet is sticking its head through the opening of the shield 32 and eating out of a bowl 34 on the raised portion 184 the mat 36. This is different from FIG. 44 because the bowl 34 is on an elevated surface 184.

(158) FIG. 49 is a cross-sectional front elevation view of the feeding vessel assembly of FIG. 48 showing an optional lipped 188 shield 32.

(159) FIG. 50 is an exploded perspective view of a feeding vessel assembly of FIG. 47-49 including an exemplary lipped 188 shield 32.

(160) FIG. 51 is an exploded perspective view of feeding vessel assembly according to another

approach including an alternate base configuration having a slotted ridge on the pad shaped to receive an exemplary lipped shield. A mat **36** is shown with an elevated groove/ridge section **190** (instead of carved into the mat) and a shield **32** with a lip **188** that slides into, hooks into, or snaps into the groove. As shown, retaining lip **188** fits into slot **192** of ridge **190** to receive and retain an exemplary lipped **188** shield **32**.

(161) FIG. **52** is an exploded perspective view of feeding vessel assembly according to another approach including an alternate base and tabbed shield configuration. A mat **36** is shown with three slots **194** to receive tabs **196** on shield **32** that fit into slots **194** on a raised portion **184** of mat **36**. It is noted that the length and number of slots and matching tabs may vary within the scope of this embodiment. It is noted that in some embodiments using a shield **32** such as shown in FIG. **52**, slots **194** may be large enough to accommodate two stacked shields **32** so that tabs **196** from each shield may be bent in opposite directions. Alternatively, tabs **196** may have at least one bendable strip **358** (such as a bendable metal wire or tab) attached to the shield tabs **196** to hold the tabs parallel to raised portion **184** when bent at right angles during installation. In an alternate embodiment, tabs **196** may not even need to be present and instead just have a plurality of bendable strips **358** may be attached to extend from the shield. These could be configured to function similar to a round head fastener.

(162) In another embodiment shield **32** may have two metal tabs like clips Another iteration though would be to have two L's like what's in the picture of the prototype I texted. I have also attached a picture of an office supply that demonstrates what I'm talking about with the two L shapes.

(163) FIG. **53** is a cross-sectional front elevation view of a feeding vessel assembly of FIG. **52**. Mat **36** from FIG. **52** is shown with an elevated portion **184** that has one removable shield attached and a bowl inside the shield. As shown with the installed shield **32**, tabs **196** extend through slots **194**. During installation, the tabs **196** may be bent to be parallel to the raised portion **184**. Tabs **196** may have a layer of adhesive, such as a pressure sensitive adhesive, to affix tab **196** to the underside of raised portion **184**.

(164) FIG. **54** is a cross-sectional front view of a feeding vessel assembly of FIG. **51** including an exemplary shield. The figure shows mat **36** from FIG. **51** with an elevated ridge **190** having groove **192** groove with one removable shield **32** attached and a bowl **34** inside the shield **32** by retaining lip **188**.

(165) FIG. **55** is an exploded view of a flat packed unassembled shield and mat of the feeding vessel of FIG. **50**. Mat **36** is shown with an elevated section **186** for the bowl and a slot **186** the shield laying flat on top (for product packaging purposes)(see FIG. **45-50**).

(166) Similarly FIG. **56** is an exploded view of a flat packed unassembled shield and mat of the feeding vessel of FIG. **52**. Mat **36** with three slots **194** and shield **32** with three tabs **196** that fit into the grooves laying flat on top of the mat **36** (for product packaging purposes) (see FIG. **52-53**).

(167) FIG. **57** is a cross-sectional side view of the attachment portion of an exemplary shield to the mat of the feeding vessel assembly of FIG. **50**. As shown shield **32** fits into a groove on carved into the mat **36**. The shield has a lip that can slide in and retainably snaps into slot **186** so the shield **32** stands straight up.

(168) FIG. **58** is a cross-sectional side view of the attachment portion of an exemplary shield to the mat of the feeding vessel assembly of FIG. **52**. A shield with a 90-degree angle that extends into slot **194** on mat **36** so shield **32** stands straight up.

(169) FIG. **59** is a cross-sectional side view of the attachment of an exemplary shield to the mat of the feeding vessel assembly of FIG. **51**. Mat **36** is shown with an elevated ridge **190** having a groove **192** and a shield that fits into the groove so the shield stands straight up.

(170) FIG. **60** is a perspective view of feeding vessel assembly including an exemplary shield, according to another approach. A mat **36** is shown with an integral and stackable bowl and shield combination **198** having a bowl portion **200**, a shield portion **202** and a base **204**. Base portion **204** is configured to be retainably held in mat opening **206** (which is an edge defining an opening to

configured to receive the base portion of integral and stackable bowl and shield combination). Base **204** may be held in place by a compression fit with opening **206**, or have a base ribbed edge, or both. In one embodiment base **204** may have threads and opening **206** is a threaded bore.

(171) FIG. **61** is an exploded view of disassembled stacked mats and shields of FIG. **60**. The figure shows how the bowl fits into the hole in the mat **36** prior to, for example, being screwed into the mat **36**. Stackability allows for efficient shipping and store placement of the components of this assembly.

(172) FIG. **62** is an exploded perspective view of feeding vessel assembly including an exemplary shield, according to another approach similar to FIG. **45** but having optional edge/opening **208** to receive a base **42** of bowl **34**.

(173) FIG. **63** is an assembled perspective view of the feeding vessel assembly including an exemplary shield of FIG. **62**. Opening **208** serves to assist the animal in getting food into its mouth by allowing bowl **34** to be held at an angle. Such as 15-45 degrees. But preferable about 30 degrees.

(174) FIG. **64** is a cross-sectional side view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIGS. **62** and **63**. The figure shows how base (feeding vessel bottom flange) **42** of bowl **34** extends into opening **208**.

(175) FIG. **65** is a perspective view of another feeding vessel assembly including an exemplary shield with pad retaining clips **210**, according to the present embodiments. The figure shows an embodiment similar for the shield assembly of FIG. **62** but has retaining clips **210** instead of pad slot **186** to hold shield **32**. Retaining clips **210** are configured to hold shield **210** by shield retaining lip **188**. Clips **210** may be formed from pad **36** mold or affixed to pad **36** by means such as gluing, welding and use of other such fastening means.

(176) FIG. **66** is an exploded perspective view of a feeding vessel assembly including an exemplary shield, according to the present invention of FIG. **65**. As shown, bowl **32** may be held at an angle within shield **32** by wedging bowl base **42** into edge retaining opening **208** of mat **32**.

(177) FIG. **67** is a perspective view of another feeding vessel assembly including an exemplary collapsible shield **212**, according to the present invention. A mat **36** is provided similar to the mat presented in FIGS. **65-66** with a ribbed shield **212** attached and a bowl placed on top of a wedge. Collapsible shield **212** as shown has a webbing **214** and a wire frame **216**. Webbing **214** may be made from a variety of materials and compositions such as knitted or mesh fabric that is collapsible that is affixed to wire frame **216**. Webbing **214** may be glued, clipped, or integrally woven into wire frame **216**. Wire frame **216** may be spiral and configured as a compression spring to extend to the desired shield height (free length) by compressible with less than 10 pounds of force by user to a stowed flattened position. The flattened position (such as shown in FIG. **69**), allows for efficient shipping and store placement of the components of this assembly. In other embodiments, collapsible shield **212** may use wire rings or spirals and may be held upright by attachment to at least one detachable rod **360** (e.g., FIG. **68**).

(178) FIG. **68** is the collapsible shield **212** of FIG. **67**, in the extended position. Collapsible shield **212** may be a textured shield. The purpose of a textured shield is to give a pet a surface they can use to get food into their mouths. This happens by scraping food up the shield with their mouths.

(179) FIG. **69** is the collapsible shield of FIGS. **67** and **68**, according to the present invention in the collapsed position.

(180) FIG. **70** is an exploded perspective view of a feeding vessel assembly including an exemplary collapsible shield **212**, according to the present invention of FIG. **67**. A mat **36** with clips **210** that hold a ribbed collapsible shield **212** in place to allow shielded placement of a tilted bowl **34** using opening **208**.

(181) FIG. **71** is a perspective view of a feeding vessel **218** having an integrally formed shield **222**/bowl **220**/mat **224**/base **226** portions, according to the present invention. Feeding vessel **218** may be form by various means including molding, 3-D printing and the like.

(182) FIG. 72 is a cross-sectional side view of a feeding vessel of FIG. 71 taken along section lines LXXII-LXXII of FIG. 71. The side view shows a bowl portion 220 with high sides 222 on mat portion 36.

(183) Figs. FIG. 73 shows stackable feeding bowl 228 according to another embodiment of the present invention with a raised back wall 234 relative to a front wall 236. Bowl 228 has a slanted interior cavity (concave portion) 232 with an annular ring (lip) 230 on the bowl bottom having a recessed groove 242 that a mat 238 and shield 242 can snap onto.

(184) FIG. 74 is a cross-sectional side view of the bowl of FIG. 73 taken along section lines LXXIV-LXXIV of FIG. 73. The side view of a slanted bowl 228 (see FIG. 73) shows an annular ring around the base of the bowl (lip) 230 that goes around the entire bottom of the bowl. Lip 230 has a recessed groove 242 that is configured to receive mat 238 inversed grooved portion 240 (FIG. 77). Recessed groove 242 is also configured to receive shield 241. Shield 241 and mat groove 240, as in other embodiments, may also have a ribbed edge to snap into groove 242. As shown in FIG. 74, the difference in height between the front wall 236 and raised back wall 234 may be around 50 percent to 150 percent higher, and preferable about 100 percent higher.

(185) FIG. 75 is a cross-sectional side view of multiple stacked bowls 228 of FIG. 73.

(186) FIG. 76 is a cross-sectional side view of the feeding bowl assembly of FIG. 77, taken along section lines LXXVI-LXXVI of FIG. 77. The side view of bowl 228 shows mat 238 hooked into groove 242 of lip 230 of bowl 228 as well as shield 241 hooked into.

(187) FIG. 77 is a perspective view of the feeding vessel assembly of FIG. 73 including of an exemplary shield, according to the present invention.

(188) FIG. 78 is a perspective view of flexible shield 241 that fits into a bowl 228.

(189) FIG. 79 is an exploded perspective view of a feeding vessel assembly including an exemplary bowl mat and shield, according to the present invention of FIG. 77.

(190) FIG. 80 is a cross-sectional side view of feeding bowl 228i of FIG. 73 according to another approach without an annular base ring 232. As shown bowl 228i also dips at the bottom and rises in an ergonomic manner so an animal can scrape food into its mouth easily.

(191) FIG. 81 is a cross-sectional side view of a stack of feeding bowls 228i.

(192) FIG. 82 is a cross-sectional side view of feeding bowl 228ii according to another approach without an annular base ring and a higher raised back wall portion 248. Bowl 228ii obviates the need for a shield. Bowl 228ii has a shorter dip and rises higher than FIGS. 80-81 that will allow an animal to scrape food into its mouth by pressing its face against the high part of the slant. As shown the height difference between front wall 236 in bowl area 250 and back wall 428 may be about 100 percent to 500 percent, but preferably about 300-400 percent higher.

(193) FIG. 83 is a cross-sectional side view of a stack of feeding bowls 228ii of FIG. 82.

(194) FIG. 84 is a perspective view of another feeding vessel assembly according to the present invention. In this embodiment feeding bowl 256 with sloped sides has a back wall 254; a front wall portion of bowl 254; an edge 258 defining opening of bowl; and a concave area 260 of bowl 256 to receive food.

(195) FIG. 85 is an exploded perspective view of another feeding vessel assembly according to the present invention having a slanted bowl 262 with slots 268 configured to receive tabs 266 of shield 264 on the outside of bowl 262. Bowl 262 sides 270 are vertical while having a sloped edge similar to other configurations herein and a concave portion 274 to receive food.

(196) FIG. 86 is a perspective view of a feeding vessel assembly according to the present invention of FIG. 85. A slanted bowl 262 has shield 264 attached by fitting tabs 266 into the slots 268 on the vertical side 70 of the outside of the bowl.

(197) FIG. 87 is a perspective view of a feeding assembly including an exemplary shield 32, according to the present invention of FIG. 88. A mat 36 in this embodiment is modified to include an integral or removable wedge 276 for a bowl 34 to sit on top of and a slot 278 for a shield 32 with a ribbed edge 188 to fit into.

(198) FIG. **88** is an exploded perspective view of the embodiment of FIG. **87**.

(199) FIG. **89** is a cross-sectional side view of the feeding assembly of FIG. **87** including an exemplary shield, according to the present invention of FIG. **87** taken along section lines LXXXIX-LXXXIX of FIG. **87**. The side view of a mat **36** with an integrally formed wedge **276** is shown, with shield **32** attached and a bowl sitting on top of the wedge at an angle **280**. Angle **280** may be in the range of 15 degrees to 45 degrees, and preferably about 30 degrees.

(200) FIG. **90** is an exploded perspective view of another feeding assembly including an exemplary shield, according to the present invention. A shield with a ledge built into it and a bowl with a lip on top and a mat **36** with a groove for the shield to fit into.

(201) FIG. **91** is a cross-sectional side view of the shield of FIG. **90**. The side view of a shield with removable or integral band **282** shown at a desired angle **286**. Angle **286** may be about 15 degrees to 45 degrees but preferable about 30 degrees.

(202) FIG. **92** is a cross-sectional side view of the assembled feeding vessel assembly of FIG. **90**. The side view shows a bowl **34** resting on the ledge **282** on the shield **32** sitting on mat **36** with grooves.

(203) FIG. **93** an exploded view of an unassembled feeding vessel assembly of FIG. **90**. In FIGS. **90-93**, three ring sizes **284** may be used to accommodate three sizes of bowls. For example, a bowl's width by height may be 5 inches by 2 inches; 9.8 inches by 3 inches; 7 inches by 2.5 inches; 12.75 inches by 2.6 inches; and the like. For example, as shown in FIG. **90** the feeding vessel assembly may have a bowl **34**, **34i**, **34ii**, the feeding bowl having a cavity to receive food and water and for placement on pad **36**. A flexible removable shield **32** is configured to partially surround the feeding bowl (e.g., 180 to 270 degrees) when inserted into one of the arcuate slots **284** and held in place by a retaining means such as a shield retaining lip **188**. A flexible bendable band **282** having on one side a having a pressure sensitive adhesive **288** may be attached on the interior side of shield **32** to hold an edge of the feeding bowl **34** off the surface of the pad **36** on one side, such as shown in FIG. **92**. In other words, the bowl **34** may be tilted to allow easier access the bowls contents. Accordingly, the slant of the bowl is adjustable based on the placement of the band **282**. As shown in FIGS. **93** and **94**, the pad, band and shield may be flattened and flat packed in their unassembled state and shrink wrapped **290** for site of sale.

(204) FIG. **94** is a packaging/box/shrink wrap **290** of the flat pack unassembled feeding vessel assembly of FIG. **90**. The side view of an automatic feeder with high sides and sides that jut forward in order to prevent food from spilling onto the sides of the feeder.

(205) FIG. **95** shows optional stackable feeding bowls for the assembly of FIG. **90**. A mat **36** with two automatic feeders and the lids of the automatic feeders. The Automatic feeders contain slanted bowls.

(206) FIG. **96** shows optional stackable feeding bowls of varies sizes to match the slots for the mat for the assembly of FIG. **90**

(207) FIGS. **97-106** show embodiments of the present invention having an optional feeding silo. Feeding silos may be configured to dry or wet foods or even fluids. FIG. **97** is a front view of another feeding assembly including an exemplary integral shield and feeding silo, according to the present invention. This embodiment allows an automatic feeder for dry or wet food or even liquids. The front view shows an automatic feeder with sides that jut out past the top compartment housing dry pet food.

(208) FIG. **98** is a cross-sectional side view of a feeding assembly including an exemplary shield, according to the present invention of FIG. **97** taken along section lines XCVIII-XCVIII of FIG. **97**.

(209) FIG. **99** is an exploded perspective view of the feeding bowl assemblies of FIG. **97** with an optional mat and integral feeding silo.

(210) Generally, feeding vessel **300** of FIGS. **97-103** may have a shield portion **302**; a silo partition **304**; a top silo opening **306**; sloped feeding bowl **308**; top cover **310** to cover opening **306**; mat **36** opening **312** to receive retaining lip **314** of feeding vessel **300**. Sloped feeding bowl **308** may have

a lip **316** (FIG. **100**) to rest on a front edge of feeding vessel **300** (See e.g., FIG. **103**). It is noted that the diameter of bowl **308** may be narrower than the diameter of shield **302** to allow its lip edge **316** to rest on the front opening of the shield.

(211) FIG. **100** is an exploded perspective view of the feeding vessel of FIG. **97**.

(212) FIG. **101** is an exploded perspective view of the feeding vessel of FIG. **97** with a variation of the bottom lip/valve **318** of the partition silo **304i**.

(213) FIG. **102** is a front view of the feeding vessel of FIG. **101**.

(214) FIG. **103** is a cross section view of the feeding vessel of FIG. **102**, taken along section lines CIII-CIII of FIG. **102**. In FIGS. **97-103**, it is noted that the silo portion **304** may accommodate solid foods and even liquids (See, e.g., FIG. **103**). The figure shows a side view of an automatic water dispenser with high sides that jut outward towards the animal. The purpose of the high sides is to prevent water from spilling onto the side or back of the bowl. Valve **318** allows predetermined amounts of liquid **320** to enter and be retained in bowl **308**.

(215) FIG. **104** is a front perspective view of another feeding assembly including an exemplary integral shield and feeding silo, according to the present invention.

(216) FIG. **105** is cross sectional view of the feeding vessel of FIG. **104** taken along section lines CV-CV of FIG. **104**.

(217) FIG. **106** is a rear perspective view of the feeding assembly of FIG. **104** including an exemplary integral shield and feeding silo, according to the present invention.

(218) In FIGS. **104-106** feeding vessel **322** has a silo **324** for food **326** and has a base **328** and bowl portion **330**. Feeding vessel **322** has a silo opening **332** and shield **334**.

(219) FIG. **107** is a front perspective view of another feeding assembly including an exemplary integral shield, according to the present invention.

(220) FIG. **108** is cross sectional view of the feeding vessel **336** of FIGS. **107** and **109** taken along section lines CVIII-CVIII of FIG. **107**. The Figure shows a bowl holder with a ledge on the back portion of the shield portion of the holder and a bowl that will rest on the ledge so the bowl is slanted once placed in the holder.

(221) FIG. **109** is an exploded front perspective view of the feeding assembly of FIG. **107**.

(222) In FIGS. **107-109**, a feeding vessel **336** has a shield **338**; a base **340**; a bowl lip **342**; a shield ridge to hold bowl **344** (which optionally may be a band **282** as described herein); a cavity to receive bowl **346**; and a front shield edge to receive bowl **348** as also described herein.

(223) FIG. **110** is a front perspective view of another feeding assembly including an exemplary removable shield, according to the present invention. In this embodiment an optional shield hook **350** is present and configured to adapted for insertion in bowl slot **352** on an optional mat **36** (see FIG. **111**).

(224) FIG. **111** is a closeup view of area CXI of FIG. **110**. In this figure more detail is given to an optional means to hold bowl shield combination **198** (See e.g., FIG. **60**) to mat **36**. As shown, hook **350** is configured to be inserted into slot **352** and rotated (clockwise in this embodiment) until a raised portion **354** of distal end of hook **350** is allowed to enter concave recess portion **356**. To achieve this, hook **350** is bendable and deformable to at least the height of raised portion **354** to travel during rotation into concave area **356**. Also, when installed hook portion **362** is adjacent to the underside travel area **364** of slot **352**.

(225) FIG. **112** is a front perspective view of another feeding assembly including an exemplary removable shield **100** with bowl **96** showing a similar hook **350** and slot **352** configuration. It is noted that this hook **350** and slot **352** arrangement, with or without a raised hook portion may be applied to most of the aforementioned removable shield configurations.

(226) It is noted that although embodiments with the various configurations of the feeding vessel with the integral shield are not shown, it is understood that these various shield configurations would also apply to shields attachable to a feeding bowl and are therefore within the scope of the present embodiments. It is also noted that the various profiles of the wedge elements **154** can be

integrally formed and stationary on the shield surface. It is also noted that the shield may have a variety of textures and compositions to add friction to the food as the animal eats. Such materials may include materials with a high coefficient of friction such as rubber or even a low tac pressure sensitive adhesive. A washboard or any of a variety of geometrical shapes (including but not limited to curves and angles) may also be used as a surface the animal uses to scrape food into its mouth.

(227) The drawings and the foregoing descriptions are not intended to represent the only forms of the feeding vessels and accessory assemblies in regard to the details of construction. Changes in form and in proportion of parts, as well as the substitution of equivalents, are contemplated as circumstances may suggest or render expedient.

(228) While the embodiments have been described in conjunction with specific embodiments, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art in light of the foregoing description. Accordingly, the present embodiments attempt to embrace all such alternatives, modifications and variations that fall within the spirit and scope of the appended claims. Throughout this specification and the drawings and figures associated with this specification, numerical labels of previously shown or discussed features may be reused in another drawing figure to indicate similar features.

LIST OF REFERENCE NUMBERS

(229) **30** feeding vessel assembly according on one approach **32** shield/collar/apron (“shield”) **34** feeding vessel **36** pad **38** feeding vessel rim **40** deformable shield lip to match feeding vessel rim **42** feeding vessel bottom flange, can also include weights **44** pad opening to receive a portion (including all) of feeding vessel bottom flange **46** lower shield opening (30-180 degrees) **48** upper shield opening (30-180 degrees) **50** side taper of shield (−45 to 80 degrees including vertical) **52** shield opening **54** opening flare (−45 to 170 degrees) **56** animal **58** shield taper (−45 to 170 degrees) **60** food dispenser **62** feeding vessel opening to receive food from food dispenser **60** opening **66** **64** feed/food/liquid **66** food dispenser opening **68** food dispenser top hinged lid **70** feeding vessel with shield **72** shield **74** base **75** rubber layer or other adhesive layer **76** cavity to receive food/liquids **78** opening **80** top opening dimension **82** bottom opening dimension (ratio proportions 1:2 to 1:1 to 2:1; that is the top can be half or double the dimension of the top opening dimension) **84** feeding vessel with shield **86** side shields **88** back shield **90** front shield **92** front shield height (10 to 90 percent of side shield height) **94** side shield height above front shield **90** **95** total side shield height (approximately 12 inches) **96** feeding vessel **98** feeding vessel interior wall **100** shield **102** shield wall **104** adhesive (e.g., a pressure sensitive adhesive) **106** cylindrical embodiment **107** integral shield **108** opening **114** sides (parallel) **110** feeding vessel diameter (parallel) **112** opening and feeding vessel back wall—parallel **114** feeding vessel **106** opening for animal to access cavity **116** front side height approximately 10 percent of height **118** **118** height of feeding vessel and shield **120** cavity **122** optional sloping sides of area to define cavity **124** feeding vessel disposable liner **126** disposable liner configured to line the interior cavity of the feeding vessel **34** **128** elastic band to mount to rim **38** **130** liner portion to line interior of vessel cavity **132** liner portion extending beyond elastic band to allow a pet owner to allow disposal of liner material **134** feeding vessel with integral shield **136** feeding vessel portion **138** feeding vessel bottom flange **139** feeding vessel cavity **140** feeding vessel with integral shield disposable liner **141** integral shield **142** liner portion to cover shield **144** liner portion to line interior of vessel cavity **146** elastic band **148** liner portion extending beyond elastic band to allow a pet owner to allow disposal of liner material **150** pressure sensitive adhesive **152** optional ramp **154** optional removable wedge **156** optional protective cover for optional removable wedge **158** foldable flap for optional protective cover for optional removable wedge **160** feeding vessel shield top **162** molded ramp for vessel **34i** **164** shield hook **166** optional protective cover for optional removable wedge opening for shield hook **168** optional ramp hook **170** opening in shield **70** for optional ramp hook **168** **172** optional removable wedge hook **174** feeding vessel shield series of openings **176** rigid portion of protective

shield 178 pliable portion of shield 154i 180 void of injection mold embodiment of FIG. 3'. 182
 back wall of feeding vessel 70 184 slotted elevated portion of pad 36 (FIG. 40) 186 slot for pad
 (FIGS. 40 and 45) 188 retaining lip for shield 190 ridge on the pad shaped to receive an exemplary
 lipped shield (FIG. 51) 192 slot of ridge 190 to receive an exemplary lipped shield 194 slots to
 receive tabs 196 (FIG. 52-53) 196 shield tabs 198 integral and stackable bowl and shield
 combination (FIG. 60) 200 bowl portion of integral and stackable bowl and shield combination 202
 shield portion of integral and stackable bowl and shield combination 204 base portion of integral
 and stackable bowl and shield combination 206 edge defining an opening to configured to receive
 the base portion of integral and stackable bowl and shield combination 208 edge defining an
 opening to receive an edge of the bowl 210 pad retaining clips (FIG. 65) 212 collapsible shield
 (FIG. 67) 214 webbing for collapsible shield 216 wire frame for collapsible shield 218 integral
 mat/bowl/shield embodiment feeding vessel (FIG. 71) 220 bowl portion of FIG. 71 feeding vessel
 222 shield portion of FIG. 71 feeding vessel 224 mat portion of FIG. 71 feeding vessel 226 bowl
 base portion of FIG. 71 feeding vessel 228 feeding bowl with sloped side (FIG. 73) 230 annular
 ring around base of feeding bowl 228 232 concave portion of feeding bowl 228 to receive food 234
 raised back wall portion of feeding bowl 228 236 front wall portion of feeding bowl 228 238 mat
 for feeding bowl 228 240 mat inversed grooved portion configured to extend into recessed groove
 242 241 shield for bowl 228 (FIGS. 73-77) 242 recessed groove of annular ring 230 244 height
 difference between back portion and front portion of feeding bowl 228 246 height difference
 between back portion and front portion of feeding bowl 228ii 248 back wall portion of bowl 228ii
 250 front wall portion of bowl 228ii 252 back wall of bowl 256 254 front wall portion of bowl 256
 256 feeding bowl with sloped side (FIG. 84) 258 edged defining opening of bowl 256 260 concave
 area of bowl 256 to receive food 262 feeding bowl with vertical parallel side and sloped opening
 (FIG. 85-86) 264 shield of FIG. 85 266 tabs of shield 264 268 slots to receive tabs 266 of shield
 264 270 vertical sides of bowl 276 272 sloped edge of bowl 276 274 concave portion of feeding
 bowl 276 to receive food 276 ramp/wedge for bowl of FIG. 88 278 mat slot 280 dimension of FIG.
 89 282 raised band/ledge integral or attachable with PSA to shield of FIGS. 90-92 284 plurality of
 slots for pad (FIG. 90) 286 dimension of FIG. 91 of band 282 288 pressure sensitive adhesive
 (PSA) 290 packaging/box/shrink wrap of the unassembled flat pack of FIG. 90 300 feeding vessel
 of FIGS. 97-103 302 shield portion for feeding vessel 300 304 silo partition for feeding vessel 300
 306 opening of silo for feeding vessel 300 308 sloped feeding bowl for feeding vessel 300 310 top
 cover for feeding vessel 300 312 mat opening for feeding vessel 300 314 retaining lip for feeding
 vessel 300 316 bowl lip FIG. 100 318 bottom lip/valve of silo partition of FIG. 101 320 liquid for
 water tight silo of FIG. 101 322 feeding vessel of FIGS. 104-106 324 silo for feeding vessel of
 FIG. 105 326 food shown for feeding vessel of FIG. 105 328 base for feeding vessel of FIG. 105
 330 bowl portion for feeding vessel of FIG. 105 332 silo opening for feeding vessel of FIG. 105
 334 shield for feeding vessel of FIG. 105 336 feeding vessel of FIGS. 107-109 338 shield of
 feeding assembly 336 340 base for of feeding assembly 336 342 bowl lip of feeding assembly 336
 344 shield ridge to hold bowl of feeding assembly 336 346 cavity to receive bowl of feeding
 assembly 336 348 front shield edge to receive bowl of feeding assembly 336 350 shield hook 352
 bowl slot to receive hook 350 (see FIG. 111) 354 raised rounded hook 350 end of hook 350 356
 concave portion configured to received raised round hook 350 end 358 bendable metal strip 360
 detachable rod to retain collapsible shield 212 in an extended (free) position 362 hook 350 portion
 364 underside travel area 364 of slot 352

Claims

1. A feeding vessel assembly, comprising: a feeding bowl having a cavity to receive food and water; a flexible removable shield to partially surround and be adjacent to a portion of an edge of the feeding bowl; a pad to place the feeding bowl on, the pad having a plurality of adjacent

concentric arcuate slots to accommodate a plurality of shield diameters and to receive an entire bottom end of the flexible removable shield having a retaining lip configured to extend through one of the arcuate slots; a band having a pressure sensitive adhesive to attach to the shield; wherein the shield, the pad and the band are configured to be flat packable when unassembled; wherein the band is configurable to be positioned on the shield to hold the portion of the edge of the feeding bowl adjacent to the shield off the pad, and wherein a bottom edge surface of the feeding bowl opposite the portion of the feeding bowl held by the band is adjacent to the pad.

2. The feeding assembly of claim 1, wherein the feeding bowl's width by height is one of be 5 inches by 2 inches; 9.8 inches by 3 inches; 7 inches by 2.5 inches; 12.75 inches by 2.6 inches.
