

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409914
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Cooper; Corey et al.

Modular inflatable platform system

Abstract

The present invention is directed to an inflatable and floatable modular platform system. The inflatable platform system of the present disclosure includes floating elements of differing nesting shapes and sizes configured to be interconnected in order to allow users to stand, sit, and walk between floating elements. Embodiments include inflatable platforms having circular, arc-shaped, rectangular, and L-shaped inflatable platforms.

Inventors:	Cooper; Corey (Destin, FL), May; Aaron (Parker, CO)
Applicant:	BOTE, LLC (Miramar Beach, FL)
Family ID:	82801070
Appl. No.:	18/633115
Filed:	April 11, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240262467 A1	Aug. 08, 2024

Related U.S. Application Data

continuation parent-doc US 17661726 20220502 US 11981401 child-doc US 18633115
continuation-in-part parent-doc US 29790858 20211217 US D1004726 20231104 child-doc US 17661726
continuation-in-part parent-doc US 29790861 20211217 US D1064161 child-doc US 17661726
continuation-in-part parent-doc US 29790864 20211217 US D1050326 child-doc US 17661726
continuation-in-part parent-doc US 29790871 20211217 US D1013816 20240206 child-doc US 17661726
continuation-in-part parent-doc US 29790860 20211217 US D1049289 child-doc US 17661726
continuation-in-part parent-doc US 29790857 20211217 US D968547 20221101 child-doc US

17661726
continuation-in-part parent-doc US 29790862 20211217 US D1049288 child-doc US 17661726
continuation-in-part parent-doc US 29790863 20211217 US D995682 20230815 child-doc US 17661726
continuation-in-part parent-doc US 29790859 20211217 US D1046047 child-doc US 17661726
continuation-in-part parent-doc US 17443504 20210727 ABANDONED child-doc US 17661726
continuation-in-part parent-doc US 17350845 20210617 ABANDONED child-doc US 17661726
continuation-in-part parent-doc US 29786720 20210602 US D982699 20230404 child-doc US 17661726
continuation-in-part parent-doc US 17165337 20210202 US 11685480 20230627 child-doc US 17661726
continuation-in-part parent-doc US 17033067 20200925 ABANDONED child-doc US 17661726

Publication Classification

Int. Cl.: B63B34/52 (20200101); B63B7/08 (20200101); B63B34/565 (20200101)

U.S. Cl.:

CPC B63B34/52 (20200201); B63B34/565 (20200201);

Field of Classification Search

CPC: B63B (34/52); B63B (34/565); B63B (3/08); B63B (7/085); B63B (35/58)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
67039	12/1866	Golding	441/128	B63C 9/28
4662852	12/1986	Schneider	297/452.13	A47C 15/006
4894033	12/1989	Chang	441/130	B63B 34/52
5020465	12/1990	Langford	403/70	B63B 34/52
5483914	12/1995	Wonka	114/345	B63B 3/08
5507674	12/1995	Yeung	441/131	B63B 34/52
5536009	12/1995	Edwards	273/287	A63F 9/10
6053790	12/1999	Langford	114/248	B63B 35/58
7137856	12/2005	Zheng	441/131	B63B 34/52
8702461	12/2013	d'Offay	441/40	B63B 34/52
9039472	12/2014	Whitehead	441/35	B63B 21/00
9376777	12/2015	Peterson	N/A	B63B 34/52
10633062	12/2019	Boonlikitcheva	N/A	B63B 35/34
11981401	12/2023	Cooper	N/A	B63B 34/565
2010/0229960	12/2009	Merker	137/223	F16K 15/20
2013/0267135	12/2012	Berenson	441/132	B63B 34/52

Primary Examiner: Smith; Nkeisha

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of U.S. patent application Ser. No. 17/661,726 entitled MODULAR INFLATABLE PLATFORM SYSTEM and filed on Dec. 17, 2021, U.S. patent application Ser. No. 17/443,504 entitled MAGNETIC CONNECTION APPARATUS and filed on Jul. 27, 2021, U.S. patent application Ser. No. 17/350,845 entitled MAGNETIC DRINKWARE and filed on Jun. 17, 2021, U.S. patent application Ser. No. 17/165,337 entitled DROP STITCH INFLATABLE SEAT and filed Feb. 2, 2021, U.S. patent application Ser. No. 17/033,067 entitled MAGNETIC ACCESSORY SURFACE MOUNT and filed on Sep. 25, 2020, U.S. patent application Ser. No. 29/786,720 entitled INFLATABLE DOCK and filed on Jun. 2, 2021, U.S. patent application Ser. No. 29/790,858 entitled INFLATABLE CHAIR and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,871 entitled INFLATABLE LOUNGE and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,857 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,859 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,860 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,861 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,862 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, U.S. patent application Ser. No. 29/790,863 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, and U.S. patent application Ser. No. 29/790,864 entitled INFLATABLE DOCK and filed on Dec. 17, 2021, the entire contents of each of which are incorporated herein by reference in their entirety for all purposes.

FIELD OF THE INVENTION

(2) The present invention is directed to an inflatable and floatable modular platform system. The inflatable platform system of the present disclosure includes floating elements of differing shapes and sizes configured to be interconnected in order to allow users to stand, sit, and walk between floating elements.

BACKGROUND OF THE INVENTION

(3) Inflatable furniture and inflatable products, referred herein as inflatables, devised for outdoor recreation provide a buoyancy to keep users partially or entirely above the surface of the water on which they are deployed.

(4) Traditional inflatables have been limited to spherical and cylindrical elements, including products such as rafts which relied upon adjoined cylindrical chambers which dictate the external form of the inflatable. Recent developments in technology, such as drop-stitch construction, enable the ability to manufacture inflatables in planar surfaces, i.e., with opposing surfaces substantially parallel to one another, and other non-planar forms which do not rely upon cylindrically shaped chambers.

(5) Inflatable furniture has traditionally been limited to individual units such as a raft, chair, or other unit, wherein the inflatable unit is used independently of other inflatable units. When multiple units are used in concert, maintaining proximity to other inflatable units to maintain a safe buoyant environment and socially conducive distance is challenging. Thus, a need for a modular inflatable platform system of interconnectable inflatable units has been identified, wherein each unit is configured to be used as an individual unit, and can be alternatively used modularly when interconnected with other inflatable units to produce a configurable system.

SUMMARY OF THE INVENTION

(6) It is an aspect of the present invention to provide a system of modularly interconnectable

inflatable platforms wherein each inflatable platform is individually usable as a floating platform, or interconnectable with other inflatable platforms.

(7) It is an aspect of certain embodiments of the present invention to provide a modular inflatable platform system comprising an inflatable platform wherein the inflatable platform comprises a recess for receiving a cooler, wherein the cooler is configured to keep beverages and other food items cool. The recess of the inflatable platform constrains the cooler therein to provide buoyancy and to prevent the tipping of the inflatable platform. Furthermore, placing the cooler within the recess allows the cooler to rest on a surface below the top surface of the inflatable platform resulting in a system having a lower center of gravity than a configuration of the cooler placed on the top surface of the inflatable platform.

(8) It is an aspect of certain embodiments of the present invention to provide a modular inflatable platform system which comprises a first inflatable platform and a second inflatable platform, wherein the inflatable platforms are interconnectable to result in a system of inflatable platforms. The inflatable platforms each comprise at least one interconnection point located proximal to the perimeter of the inflatable platforms, or upon a top surface of the inflatable platform. In certain embodiments the inflatable platforms comprise interconnection points in the form of interconnection points comprising a D-Ring, shackle, or other interconnection points configured to receiving a tether therethrough for interconnection of the first inflatable platform and the second inflatable platform.

(9) It is an aspect of certain embodiments of the present invention to provide at least one handle interconnected with a top surface of an inflatable platform. Alternate embodiments comprising handles interconnected with a side of an inflatable platform are within the spirit and scope of the present invention.

(10) It is an aspect of certain embodiments of the present invention to provide inflatable platforms which are configured to be interconnected wherein the first inflatable platform and the second inflatable platform are constrained to prevent relative movement between the first inflatable platform and the second inflatable platform. In certain embodiments, the interconnection between the first inflatable platform and the second inflatable platform comprises at least one tensile element spanning between the first inflatable platform and the second inflatable platform. Certain embodiments employ at least two points of contact between a first inflatable platform and a second inflatable platform, wherein an external perimeter of a first inflatable platform is interconnected with an internal perimetral aspect of a second inflatable platform. As discussed herein, perimetral aspects such as a convex elements, and reflex angles are considered external perimetral aspects for the purposes of the present application. Furthermore, perimetral aspects such as concave elements, and internal angles are considered internal perimetral aspects for the purposes of the present application.

(11) Certain embodiments of the present invention comprise a first inflatable platform comprising an external perimetral aspect, and a second inflatable platform comprising an internal perimetral aspect. The external perimetral aspect and the internal perimetral aspect are similarly shaped wherein the external perimetral aspect of the first inflatable platform is configured to be received by the internal perimetral aspect of the second inflatable platform, resulting in a substantially continuous nesting contact between the first inflatable platform and the second inflatable platform.

(12) It is an aspect of certain embodiments of the present invention to provide inflatable platforms which are configured to be interconnected wherein the first inflatable platform and the second inflatable platform are constrained to prevent relative movement between the first inflatable platform and the second inflatable platform. In certain embodiments the interconnection between the first inflatable platform and the second inflatable platform comprises two tensile elements spanning between the first inflatable platform and the second inflatable platform. For example, a first linear perimetral aspect of the first inflatable platform is abutted with a first linear perimetral aspect of the second inflatable platform, wherein each inflatable platform comprises a first

interconnection point and a second interconnection point, wherein the interconnection points of the inflatable platforms are configured to align with each other when the linear perimetral aspects of the inflatable platforms are abutted.

(13) The interconnection of inflatable platforms resulting in the constraint of the inflatable platforms in relation to each other, by interconnection points and/or substantially continuous nesting contact, allows users to enjoy a modular inflatable platform system wherein users can lay, sit, or walk along and between the interconnected inflatable platforms. The interconnection of the inflatable platforms to each other results in a more stable inflatable platform system which increases safety and allows for increased social interaction without the need for continual adjusting of inflatable platforms in relation to each other.

(14) It is an aspect of certain embodiments of the present invention to secure and interconnect beverages and other personal items to the top surface of an inflatable platform using magnetic apparatus. Personal items include, but are not limited to keys, cameras, pocket knives, or other items that have ferrous metal components that are desirably carried by outdoor sportspeople while engaged in fishing, paddling, boating, sailing, and other outdoor sports. Such technologies are disclosed by U.S. patent application Ser. No. 17/350,845 (“the '845 application”) and U.S. patent application Ser. No. 17/443,504 (“the '504 application”), both of which are incorporated by reference in their entirety for all purposes herein.

(15) Certain embodiments comprise an inflatable platform comprising an inflatable bolster or backrest which is configured to assist a user in laying or sitting upon the top surface of the inflatable platform. In certain embodiments a bolster comprises a circular cross-section inflatable device interconnected with a top surface allowing a user to lean against or rest their head upon the bolster. In certain embodiments a back rest comprises an inflatable panel hingedly interconnected to a top surface of the inflatable platform, thus allowing a user to configure the back rest between 0-degrees and 180-degrees from the top surface of the inflatable platform. Apparatus for connecting the bolster or backrest to the inflatable platform are disclosed by U.S. patent application Ser. No. 17/165,337 (“the '337 application”), which is incorporated by reference in its entirety for all purposes herein.

(16) These and other advantages will be apparent from the disclosure of the inventions contained herein. The above-described embodiments, objectives, and configurations are neither complete nor exhaustive. As will be appreciated, other embodiments of the invention are possible using, alone or in combination, one or more of the features set forth above or described in detail below. Further, this Summary is neither intended nor should it be construed as being representative of the full extent and scope of the present invention. The present invention is set forth in various levels of detail in this Summary, as well as in the attached drawings and the detailed description below, and no limitation as to the scope of the present invention is intended to either the inclusion or non-inclusion of elements, components, etc. in this Summary. Additional aspects of the present invention will become more readily apparent from the detailed description, particularly when taken together with the drawings, and the claims provided herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A—A perspective view of certain embodiments comprising an inflatable platform

(2) FIG. 1B—A top view of certain embodiments comprising an inflatable platform

(3) FIG. 1C—A side view of certain embodiments comprising an inflatable platform

(4) FIG. 1D—A cross-sectional view of certain embodiments comprising an inflatable platform as shown in FIG. 1B

(5) FIG. 1E—A bottom view of certain embodiments comprising an inflatable platform

- (6) FIG. 2A—A top view of certain embodiments comprising a first inflatable platform configured to interconnect with a second inflatable platform
- (7) FIG. 2B—A top view of certain embodiments comprising a plurality of inflatable platforms configured to interconnect with each other
- (8) FIG. 3A—A top view of certain embodiments comprising an inflatable platform
- (9) FIG. 3B—A side view of certain embodiments comprising an inflatable platform
- (10) FIG. 3C—A perspective view of certain embodiments comprising an inflatable platform
- (11) FIG. 4A—A top view of certain embodiments comprising an inflatable platform
- (12) FIG. 4B—A side view of certain embodiments comprising an inflatable platform
- (13) FIG. 4C—A perspective view of certain embodiments comprising an inflatable platform
- (14) FIG. 5A—A top view of certain embodiments comprising a first inflatable platform configured to interconnect with a second inflatable platform
- (15) FIG. 5B—A side view of certain embodiments comprising an inflatable platform
- (16) FIG. 5C—A perspective view of certain embodiments comprising an inflatable platform
- (17) FIG. 6A—A top view of certain embodiments comprising an inflatable platform
- (18) FIG. 6B—A side view of certain embodiments comprising an inflatable platform
- (19) FIG. 6C—A perspective view of certain embodiments comprising an inflatable platform
- (20) FIG. 7A—A top view of certain embodiments comprising a first inflatable platform configured to interconnect with a second inflatable platform
- (21) FIG. 7B—A top view of certain embodiments comprising a first inflatable platform configured to interconnect with a second inflatable platform
- (22) FIG. 7C—A top view of certain embodiments comprising a first inflatable platform configured to interconnect with a second inflatable platform

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS

- (23) Certain embodiments, as shown in FIG. 1A-FIG. 1E for example, of the present invention comprise an inflatable platform **1000**. The inflatable platform **1000** comprises a top surface **1010**, a bottom surface **1020**, and a perimeter **1050** which defines the shape of the inflatable platform. The bottom surface **1020** of the inflatable platform is intended for direct contact with a body of water. The bottom surface **1020** of the inflatable platform of certain embodiments comprises a planar surface, however embodiments are not limited to having planar bottom surfaces, and alternate embodiments comprising non-planar bottom surface are within the spirit and scope of the present invention. The top surface of **1020** the inflatable platform comprises a planar form configured to allow users to lay, sit, walk, and otherwise interact with the top surface. Alternate embodiments comprising a non-planar top surface are within the spirit and scope of the present invention.
- (24) Certain embodiments of the present invention comprise a top surface **1010** and a bottom surface **1020** wherein the top surface **1010** and bottom surface **1020** are interconnected by a plurality of threads, typically polyester, wherein the plurality of threads maintain a thickness **1100** between the top surface **1010** and the bottom surface **1020**. This interconnection between the top surface **1010** and the bottom surface **1002** is commonly referred to as drop-stitching. The volume contained between the top surface **1010** and the bottom surface **1020** comprises an air-tight chamber **1150** which is pressurized to inflate the chamber **1150**.
- (25) Certain embodiments of the present invention, as shown in FIG. 1A-FIG. 1B for example, comprise an inflatable platform wherein the top surface comprises grip enhancing surface treatment **1200**. Grip enhancing surface treatments **1200** include, but are not limited to: texturized coatings, material bonded to the top surface of the inflatable platform, rubberized coatings, surface depth variation, or other materials for enhancing grip known in the existing state of the art.
- (26) Certain embodiments of the present invention, as shown in FIG. 1A-FIG. 1B for example, comprise an inflatable platform **1000** comprising at least one interconnection point **1300** interconnected to a top surface **1010** of the inflatable platform. Alternate embodiments comprising an interconnection point **1300** interconnected to the perimeter surface **1050** of the inflatable

platform are within the spirit and scope of the present invention. The interconnection point **1300** comprises an aperture wherethrough a tethering device, such as a cord, webbing, bungee, chain, clip, carabiner, or other tensile load carrying device, can be passed to interconnect the inflatable platform to an interconnection point **1300** of a second inflatable platform. Alternate embodiments comprise an interconnection point comprising devices commonly referred to as lashing pots, such as cloverleaf lashing pots which allow lashing with a device commonly referred to as an elephant's foot, or a cleat. Other alternate embodiments comprise an interconnection point comprising a webbing strap and buckle or snap. Alternate embodiments comprising interconnection points known in the state of the art are within the spirit and scope of the present invention.

(27) Certain embodiments comprise an inflatable platform **1000** having a magnetic connection apparatus **1400** configured to receive and interconnect with drinkware and other ferrous objects as disclosed in the '845 application and the '504 application. An inflatable platform of such embodiments comprises at least one magnetic connection apparatus interconnected with the top surface **1010** of the inflatable platform. Certain embodiments comprise an inflatable platform comprising a plurality of magnetic connection apparatus **1300** distributed about the top surface **1010** of the inflatable platform.

(28) Certain embodiments of the present invention comprise an inflatable platform **1000** having a top surface **1010**, a bottom surface **1020**, and an inflatable chamber **1150** therebetween having a thickness **1100**. The inflatable platform **1000** further comprises a recess **1500** offset from a perimeter **1050** of the inflatable platform. The recess **1500** of certain embodiments (FIG. **1B**) is located centrally in relation to the perimeter **1050** of the inflatable platform. The recess **1500** extends from the top surface **1010** to the bottom surface of the inflatable platform, wherein the bottom **1520** of the recess comprises a membrane **1550**. In certain embodiments, the bottom surface **1020** and membrane **1550** are contiguous. In other embodiments, the membrane **1550** is interconnected to the bottom surface **1020**. The bottom of the recess **1500** of certain embodiments is coincident with the bottom surface **1020** of the inflatable platform wherein the depth of the recess is equal to the thickness **1100** of the inflatable platform. In alternate embodiments, the bottom **1020** of the recess is offset from the bottom surface **1020** of the inflatable platform wherein the depth of the recess is less than the thickness **1100** of the inflatable platform or the depth of the recess is more than the thickness **1100** of the inflatable platform. Alternate embodiments wherein the recess **1500** comprises a thru-hole extending from the top surface **1010** of the inflatable platform to the bottom surface **1020** of the inflatable platform are also within the spirit and scope of the present invention. In certain embodiments comprising a recess **1500**, the bottom **1520** of the recess comprises at least one aperture **1560** wherein water captured in the recess is permitted to drain from the recess in a process commonly referred to as "self-bailing."

(29) The recess **1500** of certain embodiments, as shown in FIG. **1B** for example, comprises a circular form. Alternative embodiments comprise a recess **1500** having a polygonal form, or other shapes as desired, are within the spirit and scope of the present invention. In certain embodiments the recess is configured to receive a cooler, such as disclosed in U.S. Pat. No. D812,981 ("the '981 patent") incorporated by reference herein for all purposes, while in alternate embodiments the recess can be configured to receive alternative objects as desired.

(30) Certain embodiments of the present invention, as shown in FIG. **1A**-FIG. **1E** for example, comprise an inflatable platform having a circular perimeter **1050**. Alternate embodiments comprising inflatable platforms **1000** having alternate perimetral shapes are within the spirit and scope of the present invention. Inflatable platforms having perimetral forms which are regular polygons, equilateral polygons, and equiangular polygons are within the spirit and scope of the present invention. Furthermore, irregular shapes and irregular polygonal shapes are within the spirit and scope of the present invention.

(31) In certain embodiments, as shown in FIG. **2A** for example, the interconnection of a first inflatable platform **1000** with a second inflatable platform **1000'** results in continuous contact

between a portion of the perimeter **1050** of the first inflatable platform and a portion of the perimeter **1050'** of the second inflatable platform.

(32) Certain embodiments of the present invention, as shown in FIG. 3A-FIG. 3B for example, comprise an arced shaped inflatable platform **2000** wherein a first side **2010** of the perimeter of the inflatable platform comprises an internal perimetral aspect **2080**. Although a first side **2010** comprising a constant radius arc is shown, embodiments comprising an internal perimetral aspect **2080** having a polygonal or variable radius arc shape are within the spirit and scope of the present invention. In certain embodiments, as shown in FIG. 2A-FIG. 2B, a portion of the perimeter **1050** of a first inflatable platform **1000** is configured to be received by and interconnect with a second inflatable platform **1000'** having an internal perimetral aspect **2080**. The perimeter **1050** of the first inflatable platform comprises an external perimetral aspect **1070**.

(33) Certain embodiments of the present invention comprise an arced inflatable platform **2000** having an arced internal perimetral aspect **2080**, an arced external perimetral aspect **2070**, and linear aspects **2090** extending therebetween. In certain embodiments, as shown, the linear aspects **2090** are orthogonal to the internal perimetral aspect **2080** and the external perimetral aspect **2070**. The arced internal perimetral aspect **2080** is configured to interconnect with a circular inflatable platform **1000** (as shown in FIG. 2A-FIG. 2B) resulting in substantially continuous contact between the internal perimetral aspect **2080** of the arced inflatable platform and a portion of the perimeter **1050** of the circular inflatable platform. It will be appreciated that the drop-stitch construction of the inflatable platforms will result in shapes that are imperfect such that there may be small gaps between interconnected inflatable platforms, but that the two inflatable platforms will be in substantially continuous contact along the internal and external perimetral aspects.

(34) In certain embodiments the arced inflatable platform **2000** comprises an internal perimetral aspect **2080** having an arc-angle which is a mathematical factor of 360 degrees, wherein a plurality of arced inflatable platforms **2000** are configured to fully surround the circular inflatable platform **1000**. In certain embodiments, as shown in FIGS. 2A, 3A and 5A, at least one interconnection point **1300** is interconnected to the inflatable platform within the chord **2081** of the internal perimetral aspect **2080**. In a preferred embodiment, the interconnection point **1300** is interconnected to a first inflatable platform **1000** at the apex of the external perimetral aspect **1070** of the first inflatable platform **1000**, and a corresponding interconnection point **1300** is interconnected to a second inflatable platform **1000'** at the apex of the nesting internal perimetral aspect **2080**. A deviation from the exact apex is acceptable so long as the interconnection points **1300** are within about 5 to 10 degrees or about 6 to 12 inches from the precise apex location. A deviation from the exact apex is acceptable so long as the interconnection points **1300** are within about 5 to 10 degrees or about 6 to 12 inches from the precise apex location. In an alternative embodiment, as shown in FIGS. 3A and 3C, at least two interconnection points **1300** are interconnected to the second inflatable platform within the chord **2081** of the internal perimetral aspect **2080**. A first inflatable platform would have corresponding interconnection points along the external perimetral aspect.

(35) In certain embodiments, as shown in FIG. 2A-FIG. 3C for example, an arced inflatable platform **2000** comprises an internal perimetral aspect **2080** having an arc-angle **2030** of about 120 degrees wherein the second inflatable platform **2000** is configured to interconnect with a first circular inflatable platform **1000**, wherein three second inflatable platforms interconnected with the first circular inflatable platform **1000** will result in fully surrounding the circular inflatable platform.

(36) As will be appreciated, the second inflatable platforms may have arc-angles that are mathematical factors of 360 degrees that, when interconnected together, would form a surrounding inflatable platform encircling a first inflatable platform. For example, and without limitation: a second inflatable platform having an arc-angle of about 270 degrees and a second inflatable platform having an arc-angle of about 90 degrees; two second inflatable platforms each having an arc-angle of about 180 degrees; three second inflatable platforms each having an arc-angle of about

120 degrees; four second inflatable platforms each having an arc-angle of about 90 degrees; a second inflatable platform having an arc-angle of about 180 degrees and two second inflatable platforms each having an arc-angle of about 90 degrees; a second inflatable platform having an arc-angle of about 240 degrees and a second inflatable platform having an arc-angle of about 120 degrees; or a single second inflatable platform having an arc-angle of about 360 degrees. As will also be appreciated, the first inflatable platform and the encircling second inflatable platform(s) may have other shapes beside the arcuate shapes shown in FIG. 2A-FIG. 3C. Additionally, the precise arc-angle of the second inflatable platform may be somewhat more or less than a standard mathematical factor of 360 degrees due to manufacturing tolerances or intentional design decisions. For example, a second inflatable platform having an arc-angle of about 120 degrees may be manufactured having an actual measured arc-angle that is about 1 to 5 degrees less than 120 degrees, resulting in some play in the fitting of the second inflatable platforms around the first inflatable platform. These tolerances ensure that the sum of arc-angles of the encircling second inflatable platforms will not exceed 360 degrees while maintaining close interconnections that will tend to prevent the arm or leg of a user from slipping through the interconnection between two inflatable platforms.

(37) As will also be appreciated, the second inflatable platform or platforms need not entirely encircle the first inflatable platform. For example, as shown in FIG. 5A, the circular inflatable platform **1000** may be interconnected to and only partially encircled by a second inflatable platform **4000**. Or additional second inflatable platforms **4000** may be interconnected to the circular inflatable platform **1000** to partially or fully surround the circular inflatable platform **1000**.

(38) In certain embodiments, as shown in FIG. 4A-FIG. 4C for example, an arced inflatable platform **3000** comprises an internal perimetral aspect **3080** having an arc-angle of less than 360 degrees. In certain embodiments, an arced inflatable platform comprises an internal perimetral aspect having an arc-angle **3030** of 240 degrees. Accordingly, an arced inflatable platform **3000** having an internal perimetral aspect having an arc-angle of 240 degrees, and an arced inflatable platform **2000** (FIG. 3A-FIG. 3C) having an arc-angle **2030** of 120 degrees interconnected with a circular inflatable platform **1000** results in fully surrounding the circular inflatable platform **1000**. It will also be appreciated that the arced inflatable platform **3000** having an internal perimetral aspect having an arc-angle of 240 degrees would encircle a circular first inflatable platform **1000** to a degree sufficient to encapsulate the first inflatable platform **1000** and help prevent it from disengaging with the arced inflatable platform **3000** in a lateral direction, even when the two platforms are not interconnected using the interconnection points **1300**.

(39) In certain embodiments, as shown in FIG. 5A-FIG. 5C, an inflatable platform **4000** comprises a rectangular shape **4050**. In certain embodiments a rectangular inflatable platform comprises a side with an internal perimetral aspect **4080**. For instance, as shown, the side of certain embodiments comprises a concave form configured to interconnect with an inflatable platform having an external perimetral aspect. For instance, the internal perimetral aspect **4080** as shown is configured to interconnect with a circular inflatable platform **1000** resulting in substantially continuous contact between the rectangular inflatable platform **4000** and the circular inflatable platform **1000**.

(40) In certain embodiments of the present invention, shown in FIG. 6A-FIG. 6C for example, an inflatable platform **5000** comprises internal and external perimetral aspects in the form of an L-shaped perimeter **5050**. In certain embodiments such as shown in FIG. 7A, the interconnection of an L-shaped internal perimetral aspect of inflatable platform **5000** with the external perimetral aspect of second inflatable platform, such as a circular inflatable platform **1000**, results in two points of contact between the inflatable platforms. In alternate embodiments such as shown in FIG. 7B, the interconnection of an L-shaped internal perimetral aspect of inflatable platform **5000** with the external perimetral aspect of second inflatable platform, such as a rectangular inflatable platform **4000**, results in the L-shaped inflatable platform **5000** having at least one side with substantially continuous contact with the second inflatable platform. In certain embodiments such

as shown in FIG. 7B, an L-shaped inflatable platform **5000** is interconnected with a rectangular shaped inflatable platform **4000** wherein the L-shaped inflatable platform **5000** has substantially continuous contact with two sides of the rectangular shaped inflatable platform **4000**. In further embodiments, such as shown in FIG. 7C, a first L-shaped inflatable platform **5000** is interconnected with a second L-shaped inflatable platform **5000** wherein the L-shaped inflatable platforms have 3 sides with substantially continuous contact. As shown in FIG. 7A-7C, the inflatable platforms may be interconnected using one or more interconnection points **1300**.

(41) In certain embodiments, such as shown in FIG. 6A-FIG. 6C, an inflatable platform comprises an inflatable bolster **6000** having a circular cross-section **6050**. The bolster **6000** is configured to interconnect with a top surface **1010** of the inflatable platform. In certain embodiments the bolster **6000** comprises a linear form, while alternative embodiments comprises an arced form such as shown in FIG. 3A-FIG. 4C. In certain embodiments, the bolster **6000** is interconnect with a top surface **1010** by a rail and track **6600** such as shown and described by FIG. 6 of the '337 application.

(42) In certain embodiments, as shown in FIG. 5A-FIG. 5C, an inflatable platform comprises an inflatable backrest **6500** configured to interconnect with a top surface **1010** of an inflatable platform wherein the backrest **6500** is configured to be hingedly affixed to the top surface of the inflatable platform, allowing the angle **6530** between the backrest **6500** and the top surface **1010** of the inflatable platform to be adjusted between 0 degrees and 180 degrees. In certain embodiments the backrest **6500** is fixed in the desired position using a first tether **6540** and a second tether **6541** which interconnect with interconnection points **1400** interconnected with the inflatable platform **4000**. In certain embodiments, the backrest **6500** is hingedly affixed to the top surface of the inflatable platform by a rail and track **6600** such as shown and described by FIG. 6 of the '337 application.

(43) While various embodiments of the present invention have been described in detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present invention. Further, the inventions described herein are capable of other embodiments and of being practiced or of being carried out in various ways. In addition, it is to be understood that the phraseology and terminology used herein is for the purposes of description and should not be regarded as limiting. The use of “including,” “comprising,” or “adding” and variations thereof herein are meant to encompass the items listed thereafter and equivalents thereof, as well as, additional items.

Claims

1. An inflatable platform system comprising: a first planar inflatable platform having a top surface, a bottom surface, and a perimeter; wherein the first inflatable platform comprises a first external curved perimetral aspect adapted to nest with an internal curved perimetral aspect of a second planar inflatable platform; wherein the first external curved perimetral aspect comprises an interconnection point having only a first magnetic connection apparatus adapted to interconnect with an interconnection point having only a second magnetic connection apparatus of the internal curved perimetral aspect of a second planar inflatable platform.
2. The inflatable platform system of claim 1, wherein the first curved external perimetral aspect comprises an arcuate shape.
3. The inflatable platform system of claim 1, wherein the first planar inflatable platform comprises a recess extending through the top surface of the first planar inflatable platform, the recess comprising a recess bottom surface.
4. The inflatable platform system of claim 3, wherein the top surface of the first planar inflatable platform comprises at least one magnetic connection adapted to interconnect with drinkware.

5. The inflatable platform system of claim 3, wherein the recess bottom surface comprises a membrane interconnected to the bottom surface of the first planar inflatable platform.
 6. The inflatable platform system of claim 1, wherein the interconnection point of the external curved perimetral aspect is interconnected to the top surface of the first planar inflatable platform, and wherein the interconnection point of the internal curved perimetral aspect is interconnected to the top surface of the second planar inflatable platform.
 7. The inflatable platform system of claim 1, wherein at least one of the first planar inflatable platform and the second planar inflatable platform comprises a recess extending through a top surface of the inflatable platform.
 8. The inflatable platform system of claim 1, wherein the internal curved perimetral aspect has substantially the same shape as the external curved perimetral aspect.
 9. The inflatable platform system of claim 8, wherein the internal curved perimetral aspect and the external curved perimetral aspect comprise an arcuate shape.
 10. The inflatable platform system of claim 1, wherein a top surface of the second planar inflatable platform comprises at least one magnetic connection adapted to interconnect with drinkware.
 11. The inflatable platform system of claim 1, wherein the internal curved perimetral aspect comprises an arc-angle which is a mathematical factor of 360.
 12. The inflatable platform system of claim 1, wherein the internal curved perimetral aspect comprises an arc-angle, and wherein the arc-angle comprises one of about 90 degrees, about 120 degrees, about 180 degrees, about 240 degrees, or about 270 degrees.
 13. The inflatable platform system of claim 1, further comprising: a third planar inflatable platform; wherein the first planar inflatable platform comprises a second external curved perimetral aspect; wherein the third planar inflatable platform comprises a second internal curved perimetral aspect adapted to nest to the second external curved perimetral aspect of the first inflatable platform; and wherein the second internal curved perimetral aspect comprises an interconnection point adapted to interconnect with an interconnection point of the second external curved perimetral aspect.
 14. The inflatable platform system of claim 13, wherein the third planar inflatable platform comprises a backrest hingedly interconnected to a top surface of the third planar inflatable platform.
 15. The inflatable platform system of claim 1, wherein the second planar inflatable platform comprises a backrest hingedly interconnected to a top surface of the second planar inflatable platform.
 16. An inflatable platform comprising: a first planar inflatable platform comprising: a top surface and a bottom surface; a first internal curved perimetral aspect; and wherein the first internal curved perimetral aspect comprises an interconnection point having only a first magnetic connection apparatus adapted to interconnect with an interconnection point having only a second magnetic connection apparatus of external curved perimetral aspect of a second planar inflatable platform.
 17. The inflatable platform of claim 16, wherein the first internal curved perimetral aspect comprises an arcuate shape.
 18. The inflatable platform of claim 16, wherein the top surface of the inflatable platform comprises at least one magnetic connection adapted to interconnect with drinkware.
 19. The inflatable platform of claim 16, wherein the inflatable platform comprises a backrest hingedly interconnected to the top surface.
-