

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410616
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Tian; Limin et al.

Reinforcement-confined circular steel tube member with enhanced end stiffness

Abstract

A reinforcement-confined circular steel tube member with enhanced end stiffness is provided. Two ends of a first end sleeve are respectively connected to a first end plate and a first connecting annular plate. Two ends of a second end sleeve are respectively connected to a second end plate and a second connecting annular plate. A first end of a circular steel tube passes through the first connecting annular plate to be inserted into the first end sleeve and fixed to the first end plate, and a second end of the circular steel tube sequentially passes through restraint rings and the second connecting annular plate to be inserted into the second end sleeve and fixed to the second end plate. Two ends of each steel bar are respectively provided with a first limit part and a second limit part.

Inventors:	Tian; Limin (Xi'an, CN), Bai; Chong (Xi'an, CN)
Applicant:	Xi'an University of Architecture and Technology (Xi'an, CN)
Family ID:	82968350
Assignee:	Xi'an University of Architecture and Technology (xi'an, CN)
Appl. No.:	18/154823
Filed:	January 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230151609 A1	May. 18, 2023

Foreign Application Priority Data

CN	202210778323.8	Jun. 29, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: E04C3/06 (20060101); **E04C3/04** (20060101)

U.S. Cl.:

CPC **E04C3/06** (20130101); E04C2003/0413 (20130101); E04C2003/0447 (20130101)

Field of Classification Search

CPC: E04C (2003/0404); E04C (2003/0408); E04C (2003/0413); E04C (2003/0439); E04C (2003/0447); E04C (3/04); E04C (3/06); E04C (3/32); E04C (3/34); E04B (2001/1927); E04B (2001/1933); E04B (2001/2445); E04B (1/92); E04B (1/943); E04B (1/945)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007597	12/1934	Dean	228/136	F16B 9/01
2248278	12/1940	Michelman	29/897.33	E04C 3/34
2016/0060886	12/2015	Cook	52/514	E04G 23/0225
2021/0054628	12/2020	Low	N/A	E04C 5/0618

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105625595	12/2015	CN	E04B 1/98
216689767	12/2021	CN	N/A
WO-2004038134	12/2003	WO	E01F 9/65
WO-2017029395	12/2016	WO	E04C 3/005

Primary Examiner: Adamos; Theodore V

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of priority from Chinese Patent Application No. 202210778323.8, filed on Jun. 29, 2022. The content of the aforementioned application, including any intervening amendments thereto, is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) This application relates to steel structures, and more particularly to a reinforcement-confined circular steel tube member with enhanced end stiffness.

BACKGROUND

(3) For the large-span space grid structure, the stability of key members is particularly important. If these members suffer instability, the stability of the overall structure will become extremely poor, which will cause progressive collapse, resulting in heavy casualties and serious economic losses. The existing measures, such as the double casing and local double-layer member, have large construction difficulty and large steel consumption, such that the fabricated member is heavy, and is difficult to transport.

SUMMARY

(4) In view of the deficiencies in the prior art, this application provides a reinforcement-confined

circular steel tube member with enhanced end stiffness, which is characterized by small steel consumption, convenient construction, and strong bearing capacity.

(5) Technical solutions of this application are described as follows.

(6) This application provides a reinforcement-confined circular steel tube member, including a first end plate, a first connecting annular plate, a first end sleeve, a second end plate, a second connecting annular plate, a second end sleeve, a circular steel tube, a plurality of restraint rings, and a plurality of reinforcing steel bars; and wherein the first end plate, the first connecting annular plate, the plurality of restraint rings, the second connecting annular plate and the second end plate are sequentially arranged; a first end of the first end sleeve is connected to the first end plate, and a second end of the first end sleeve is connected to the first connecting annular plate; a first end of the second end sleeve is connected to the second end plate, and a second end of the second end sleeve is connected to the second connecting annular plate; a first end of the circular steel tube passes through the first connecting annular plate to be inserted into the first end sleeve and fixed to the first end plate, and a second end of the circular steel tube passes through the plurality of restraint rings and the second connecting annular plate in turn to be inserted into the second end sleeve and fixed to the second end plate; the circular steel tube is in contact with an inner wall of a center through hole of each of the plurality of restraint rings; and a first end of each of the plurality of reinforcing steel bars is provided with a first limit part, and a second end of each of the plurality of reinforcing steel bars passes through the first connecting annular plate, the plurality of restraint rings, and the second connecting annular plate in turn, and is provided with a second limit part.

(7) In an embodiment, the plurality of reinforcing steel bars are evenly distributed along a circumferential direction of the circular steel tube.

(8) In an embodiment, each of the plurality of reinforcing steel bars is welded to the plurality of restraint rings.

(9) In an embodiment, each of the plurality of reinforcing steel bars is a threaded reinforcing steel bar or a prestressed reinforcing steel bar.

(10) In an embodiment, a plurality of first stiffeners are provided between the first end plate and the first connecting annular plate.

(11) In an embodiment, the plurality of first stiffeners are evenly distributed along a circumferential direction of the first end sleeve.

(12) In an embodiment, a plurality of second stiffeners are provided between the second end plate and the second connecting annular plate.

(13) In an embodiment, the plurality of second stiffeners are evenly distributed along a circumferential direction of the second end sleeve.

(14) In an embodiment, a first Belleville spring and a first washer are provided between the first end plate and the first connecting annular plate; the first Belleville spring and the washer are sleeved on the first end sleeve; and the first Belleville spring is provided between the first washer and the first end plate.

(15) In an embodiment, a second Belleville spring and a second washer are provided between the second end plate and the second connecting annular plate; the second Belleville spring and the second washer are sleeved on the second end sleeve; and the second Belleville spring is provided between the second washer and the second end plate.

(16) This application has the following beneficial effects.

(17) One end of the circular steel tube passes through the first connecting annular plate to be inserted into the first end sleeve, the other end of the circular steel tube passes through the restraint rings and the second connecting annular plate in turn to be inserted into the second end sleeve. The circular steel tube is in contact with the inner wall of the center through hole of each of the plurality of restraint rings. Each reinforcing steel bar passes through the first connecting annular plate, the restraint rings and the second connecting annular plate in turn and is provided with the second limit part. The reinforcing steel bar is combined with the restraint ring to increase the lateral constraint

of the circular steel tube and improve the stability of the member, thereby improving the overall structural stability and bearing capacity. The member has simple structure and small steel consumption.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an exploded view of a reinforcement-confined circular steel tube member according to one embodiment of the present disclosure in the presence of a stiffener;
 - (2) FIG. 2 is a structural diagram of the reinforcement-confined circular steel tube member according to one embodiment of the present disclosure in the presence of the stiffener;
 - (3) FIG. 3 is an exploded view of the reinforcement-confined circular steel tube member according to one embodiment of the present disclosure in the presence of a Belleville spring;
 - (4) FIG. 4 is a structural diagram of the reinforcement-confined circular steel tube member according to one embodiment of the present disclosure in the presence of the Belleville spring; and
 - (5) FIG. 5 shows a load-displacement curve of the circular steel tube member confined with a stiffener and a reinforcing bar according to one embodiment of the present disclosure.
- (6) In the figures: **11**—first end sleeve; **12**—second end sleeve; **21**—first limit part; **22**—second limit part; **31**—first connecting annular plate; **32**—second connecting annular plate; **4**—restraint ring; **5**—reinforcing steel bar; **6**—circular steel tube; **7**—welding seam; **81**—first stiffener; **82**—second stiffener; **91**—first end plate; **92**—second end plate; **101**—first Belleville spring; **102**—second Belleville spring; **111**—first washer; and **112**—second washer.

DETAILED DESCRIPTION OF EMBODIMENTS

- (7) The technical solutions of the disclosure will be described in detail below with reference to the accompanying drawings and embodiments to make those skilled in the art better understand the technical solutions disclosed herein. Obviously, described below are merely some embodiments of the disclosure, which are not intended to limit the disclosure. Further, the description of the well-known structure and techniques is omitted to avoid unnecessary confusion. For those skilled in the art, other embodiments obtained based on these embodiments without paying creative efforts should fall within the scope of the disclosure defined by the appended claims.
- (8) Embodiments of the disclosure are schematically shown in the accompanying drawings. The diagrams are not drawn in scale, where some details are enlarged, and some details are omitted for clarity. Various regions, shapes of the layers, and relative sizes and position relationships are merely illustrative. For those skilled in the art, regions/layers with different shapes, sizes, and relative positions may be designed as required.
- (9) Referring to FIGS. 1 to 4, a reinforcement-confined circular steel tube member provided herein includes a first end plate **91**, a first connecting annular plate **31**, a first end sleeve **11**, a second end plate **92**, a second connecting annular plate **32**, a second end sleeve **12**, a circular steel tube **6**, a plurality of restraint rings **4**, and a plurality of reinforcing steel bars **5**.
- (10) The first end plate **91**, the first connecting annular plate **31**, the plurality of the restraint rings **4**, the second connecting annular plate **32** and the second end plate **92** are sequentially arranged. A first end of the first end sleeve **11** is connected to the first end plate **91**, and a second end of the first end sleeve **11** is connected to the first connecting annular plate **31**. A first end of the second end sleeve **12** is connected to the second end plate **92**, and a second end of the second end sleeve **12** is connected to the second connecting annular plate **32**. A first end of the circular steel tube **6** passes through the first connecting annular plate **31** to be inserted into the first end sleeve **11** and fixed to the first end plate **91**. A second end of the circular steel tube **6** passes through the plurality of restraint rings **4** and the second connecting annular plate **32** in turn to be inserted into the second end sleeve **12** and fixed to the second end plate **92**. The circular steel tube **6** is in contact with an

inner wall of a center through hole of each of the plurality of the restraint rings **4**. A first end of each of the plurality of reinforcing steel bars **5** is provided with a first limit part **21**, and a second end of each of the plurality of reinforcing steel bars **5** passes through the first connecting annular plate **31**, the plurality of restraint rings **4**, and the second connecting annular plate **32** in turn and is provided with a second limit part **22**.

(11) In this embodiment, the plurality of reinforcing steel bars **5** are evenly distributed along a circumferential direction of the circular steel tube **6**, and each of the plurality of reinforcing steel bars **5** is welded to the plurality of restraint rings **4**. The reinforcing steel bar **5** is a threaded reinforcing steel bar or a prestressed reinforcing steel bar, that is, the reinforcing steel bar **5** and the restraint ring **4** are connected by a welding seam **7**.

(12) Further, a plurality of first stiffeners **81** are provided between the first end plate **91** and the first connecting annular plate **31**. The plurality of first stiffeners **81** are evenly distributed along the circumferential direction of the first end sleeve **11**. A plurality of second stiffeners **82** are provided between the second end plate **92** and the second connecting annular plate **32**, and the plurality of second stiffeners **82** are evenly distributed along the circumferential direction of the second end sleeve **12**.

(13) In this embodiment, a first Belleville spring **101** and a first washer **111** are provided between the first end plate **91** and the first connecting annular plate **31**. The first Belleville spring **101** and the first washer **111** are sleeved into the first end sleeve **11**. The first Belleville spring **101** is disposed between the first washer **111** and the first end plate **91**. A second Belleville spring **102** and a second washer **112** are provided between the second end plate **92** and the second connecting annular plate **32**. The second Belleville spring **102** and the second washer **112** are sleeved into the second end sleeve **12**. The second Belleville spring **102** is disposed between the second washer **112** and the second end plate **92**.

(14) Referring to FIG. 5, the reinforcing steel bar **5** combined with the restraint ring **4** increases the lateral constraint of the circular steel tube **6**, thereby improving the stability of the circular steel tube member, and finally improving the stability of the overall structure. The end of the circular steel tube **6** is reinforced by stiffeners to prevent local buckling at the end and improve the stiffness of the joint or strengthened by the Belleville spring to prevent local buckling at the end and improve the stiffness of the joint, while strengthening the energy consumption at the joint.

(15) Compared with the conventional circular steel tube, the stability bearing capacities of the circular steel tube confined with stiffening rib and reinforcement at the end and the circular steel tube confined with reinforcement are increased by 2.0 times and 3.1 times, respectively.

Claims

1. A reinforcement-confined circular steel tube member, comprising: a first end plate; a first connecting annular plate; a first end sleeve; a second end plate; a second connecting annular plate; a second end sleeve; a circular steel tube; a plurality of restraint rings; and a plurality of reinforcing steel bars; wherein the first end plate, the first connecting annular plate, the plurality of restraint rings, the second connecting annular plate and the second end plate are sequentially arranged; a first end of the first end sleeve is connected to the first end plate, and a second end of the first end sleeve is connected to the first connecting annular plate; a first end of the second end sleeve is connected to the second end plate, and a second end of the second end sleeve is connected to the second connecting annular plate; a first end of the circular steel tube passes through the first connecting annular plate to be inserted into the first end sleeve and fixed to the first end plate, and a second end of the circular steel tube passes through the plurality of restraint rings and the second connecting annular plate in turn to be inserted into the second end sleeve, and fixed to the second end plate; the circular steel tube is in contact with an inner wall of a center through hole of each of the plurality of restraint rings; and a first end of each of the plurality of reinforcing steel bars is

provided with a first limit part, and a second end of each of the plurality of reinforcing steel bars passes through the first connecting annular plate, the plurality of restraint rings, and the second connecting annular plate in turn, and is provided with a second limit part; a first Belleville spring and a first washer are provided between the first end plate and the first connecting annular plate; the first Belleville spring and the first washer are sleeved on the first end sleeve; and the first Belleville spring is provided between the first washer and the first end plate; and a second Belleville spring and a second washer are provided between the second end plate and the second connecting annular plate; the second Belleville spring and the second washer are sleeved on the second end sleeve; and the second Belleville spring is provided between the second washer and the second end plate.

2. The reinforcement-confined circular steel tube member of claim 1, wherein the plurality of reinforcing steel bars are evenly distributed along a circumferential direction of the circular steel tube.

3. The reinforcement-confined circular steel tube member of claim 1, wherein each of the plurality of reinforcing steel bars is welded to the plurality of restraint rings.

4. The reinforcement-confined circular steel tube member of claim 1, wherein each of the plurality of reinforcing steel bars is a threaded reinforcing steel bar or a prestressed reinforcing steel bar.
