

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413566
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Helfinstine; Charles A.

Systems and methods for network privacy

Abstract

A privacy gateway may communicate with user devices located at a plurality of premises. The privacy gateway may receive a data packet, from one of the user devices, indicating destinations, such as other computing devices, located external to the premises. The privacy gateway may decrypt at least a portion of the data packet to determine that at least a portion of data in the packet is associated with the user device. The privacy gateway may remove the data associated with the user device from the data packet and replace the removed data with data associated with the privacy gateway. The privacy gateway may send the data packet with the replaced data to a destination device. The privacy gateway may receive a response to the data packet from the destination device. The privacy gateway may encrypt a portion of the response and send the response to the user device.

Inventors:	Helfinstine; Charles A. (Wynnewood, PA)
Applicant:	Comcast Cable Communications, LLC (Philadelphia, PA)
Family ID:	82899953
Assignee:	Comcast Cable Communications, LLC (Philadelphia, PA)
Appl. No.:	18/340667
Filed:	June 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240106811 A1	Mar. 28, 2024

Related U.S. Application Data

continuation parent-doc US 17249285 20210225 US 11729154 child-doc US 18340667

Publication Classification

Int. Cl.: **H04L9/40** (20220101); **H04L9/32** (20060101); **H04L67/02** (20220101); **H04L67/52** (20220101)

U.S. Cl.:

CPC **H04L63/0471** (20130101); **H04L9/3268** (20130101); **H04L63/0428** (20130101); **H04L63/0478** (20130101); **H04L63/166** (20130101); **H04L67/02** (20130101); **H04L67/52** (20220501);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9356914	12/2015	Jeffrey	N/A	H04L 63/08
10681142	12/2019	Ong	N/A	H04L 63/10
10785058	12/2019	Lee	N/A	H04L 67/02
10924456	12/2020	Moore	N/A	H04L 63/0281
10924546	12/2020	Herbert	N/A	G06F 8/65
11159656	12/2020	Michon	N/A	H04L 12/1804
11283774	12/2021	Anderson	N/A	H04L 63/0869
11411949	12/2021	Moore	N/A	H04L 63/062
11483294	12/2021	Karabatis	N/A	G06F 21/6263
11611536	12/2022	Nagrockas	N/A	H04L 63/0272
11863421	12/2023	Kaciulis	N/A	H04L 45/02
2015/0288663	12/2014	Watanabe	380/28	H04L 63/166
2016/0134594	12/2015	Teo	713/171	H04L 63/045
2017/0208007	12/2016	Malhotra	N/A	H04L 65/70
2017/0359317	12/2016	Anderson	N/A	G06F 21/602
2019/0182223	12/2018	Wang et al.	N/A	N/A
2020/0028673	12/2019	Howe	N/A	H04L 9/30
2020/0059780	12/2019	Hess	N/A	H04W 12/041
2020/0274812	12/2019	Ouyang	N/A	H04L 43/062
2020/0412750	12/2019	Doron	N/A	H04L 63/1425
2021/0021579	12/2020	Thorslund	N/A	H04L 63/0464
2021/0194927	12/2020	Adel et al.	N/A	N/A
2021/0367921	12/2020	Baum et al.	N/A	N/A
2021/0392112	12/2020	Nagrockas	N/A	H04L 12/4633
2022/0116370	12/2021	Tate	N/A	H04L 9/3263
2022/0231944	12/2021	Jindal	N/A	H04L 45/74
2023/0103015	12/2022	Ong	709/225	H04L 63/101

OTHER PUBLICATIONS

Primary Examiner: Jacobs-Burton; Lashonda

Attorney, Agent or Firm: BakerHostetler

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/249,285, filed Feb. 25, 2021, now U.S. Pat. No. 11,729,154, which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) User network behavior and internet traffic may be tracked. For example, computing devices may communicate via a network, such as the Internet. The computing devices may communicate by sending and/or receiving data packets. The data packets may comprise information that is tracked, such as an address of a computing device, a location of the computing device, information associated with a user of the computing device, and/or contents of a message. Although use of an anonymity network and/or encryption of packet data may provide some privacy from monitoring devices, popular communication protocols, such as hypertext transfer protocol secure (HTTPS), may require that at least some of the data in a packet remain unencrypted and may not prevent a monitoring device from determining general information about a communication session. Therefore, improvements in network privacy are needed.

SUMMARY

(2) One or more user devices may be located at a premises. In order to communicate with one or more computing devices located external to the premises, such as web servers, one or more of the user devices may send an encrypted data packet to a gateway device. The gateway device may comprise a privacy gateway. The privacy gateway may comprise another computing device located external to the premises. The privacy gateway may maintain communication sessions with a plurality of user devices located at a plurality of premises. The privacy gateway may decrypt at least a portion of data in the encrypted data packet. The privacy gateway may determine that at least a portion of the decrypted data is associated with the user device, such as an address of the user device and/or data associated with a user of the user device or data associated with the premises. The privacy gateway may remove the data associated with the user device from the packet and add data associated with the privacy gateway. The privacy gateway may re-encrypt at least a portion of the packet. The privacy gateway may initiate a communication session with another computing device, such as one or more of the computing devices located external to the premises, and the other computing device may receive the packet with the added data. As a result, the other computing device and/or a monitoring device may not be able to determine the data associated with the user device and/or that the packet is associated with the premises by tracking the packet.

(3) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Furthermore, the claimed subject matter is not limited to limitations that solve any or all disadvantages noted in any part of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The following drawings show generally, by way of example, but not by way of limitation, various examples discussed in the present disclosure. In the drawings:

- (2) FIG. 1 shows an example system.
- (3) FIG. 2 shows an example method.
- (4) FIG. 3 shows an example method.
- (5) FIG. 4 shows an example method.
- (6) FIG. 5 shows an example method.
- (7) FIG. 6 shows an example method.
- (8) FIG. 7 shows an example method.
- (9) FIG. 8 shows an example system.

DETAILED DESCRIPTION

(10) FIG. 1 shows an example system **100**. The system **100** may comprise one or more user devices **101**. The user device **101** may comprise a mobile device, such as a mobile phone, a laptop computer, a tablet device, and/or a wearable device, as examples. The user device **101** may comprise a premises management system device, such as a sensor device, a camera device, a lighting device, an alarm device, a speaker device, a microphone device, a communication device, a gateway device, a control panel device, a smart home device, an appliance, an internet of things (IoT) device, and/or an automation device, as examples. The user device **101** may comprise one or more entertainment devices, such as a set-top box and/or a television. The user device **101** may comprise a router.

(11) The user device **101** may be located at a premises **102**. The premises **102** may comprise a residential premises, such as a house, an apartment, a condominium, and/or a mobile house. The premises **102** may comprise a group of residential premises, such as a neighborhood, an apartment building, and/or a hotel. The premises **102** may comprise a commercial premises, such as an office, a warehouse, and/or a retail shop. The premises **102** may comprise a group of commercial premises, such as a retail complex and/or a corporate campus. The premises **102** may comprise an educational premises, such as a school or a university. The premises **102** may comprise a governmental premises, such as a public service building and/or governmental office.

(12) The user device **101** may be configured to communicate with a computing device **103**. The computing device **103** may be located external to the premises **102**. The computing device **103** may comprise a server, such as a server hosting a database, a server hosting a website, a certificate authority server, a server providing content, and/or a server providing a service. The user device **101** may be configured to act as a client to the computing device **103**. The computing device **103** may comprise a user device. The computing device **103** may comprise a router.

(13) The user device **101** may be configured to communicate with the computing device **103** via a network **104**. The network **104** may comprise the Internet. The network **104** may comprise a wide area network (WAN). The network **104** may comprise an Internet Protocol (IP) network. The network **104** may comprise a broadband network. The network **104** may comprise a cellular network. The network **104** may comprise a 3G, 4G, LTE, or 5G network.

(14) The user device **101** may be configured to communicate with the computing device **103** by sending data to and/or receiving data from the computing device **103**. The user device **101** may be configured to communicate with the computing device **103** by sending data to and/or receiving data from a router. The router may be configured to send data received from the user device **101** to the computing device **103**. The router may be configured to send data received from the computing device **103** to the user device **101**.

(15) Data may be sent and/or received in one or more chunks. The chunks may comprise one or

more data packets. The data packets may be sent and/or received in streams. A data packet may comprise a portion of the data being communicated (e.g., a message). As a result of the data packets each only comprising a portion of the data being communicated, the data being communicated may not be determined from a single packet, such as if a single packet is intercepted by a device other than the user device **101** and/or the computing device **103**, such as a monitoring device.

(16) The data packets may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device **101**, an address of the computing device **103**, a geographic location of the user device **101**, and/or a geographic location of the computing device **103**. The identifying information may comprise an address of a router, such as a router at the premises **102**. For example, if the user device **101** is configured to communicate via the router, the router may replace an address of the user device **101** in one or more packets with an address of the router.

(17) The identifying information may be used to determine a source of the data packets (e.g., the user device **101** and/or a router used by the user device **101**). The identifying information may be used to determine where to send a response to the data packets (e.g., the user device and/or a router used by the user device **101**). The identifying information may be used to determine that the data packets sent from the user device **101** are associated. Based on determining the associated data packets, the data to be communicated (e.g., the message) may be determined. The data packets may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(18) At least a portion of one or more of the data packets may be encrypted. For example, the portion of the packet indicating the data to be communicated may be encrypted. The encryption of the portion of the data may prevent a monitoring device from determining the data. The user device **101** may encrypt the portion of the data using a key associated with the computing device **103**, such as a public key associated with the computing device **103**. The key may be received from the computing device **103**, such as in a session initiation and/or handshake between the user device **101** and the computing device **103**. The portion of the data may be encrypted such that the portion may be decrypted using a key associated with the computing device **103**, such as a private key associated with the computing device **103** and/or a key that is the corresponding pair to the key used to encrypt the portion of the data. The computing device **103** may have the key configured to decrypt the portion of the data.

(19) A portion of the data packet may not be encrypted. For example, one or more pieces of identifying information in a packet may not be encrypted. The address of the computing device **103** indicated in a packet may not be encrypted, for example, in order to route the packet to the computing device **103**.

(20) A portion of the data packet may not be encrypted based on a communication protocol used. The communication protocol may comprise hypertext transfer protocol secure (HTTPS), as an example. The communication protocol may rely on unencrypted data for routing data packets. For example, an address of the destination device may not be encrypted in a data packet to route the data packet. The destination address may not raise privacy concerns, such as compared to a source address. Therefore, the source address may be encrypted and the destination address may be unencrypted to facilitate routing of the data packets to the destination device. Therefore, data packets sent using the communication protocol may have one or more unencrypted portions.

(21) Communications from and/or to the user device **101** may be tracked. For example, the communications may be tracked by a monitoring device. The monitoring device may comprise a device other than the computing device **103**. The monitoring device may be configured to intercept one or more data packets sent by and/or to the user device **101**. If the one or more data packets comprise an address of the user device **101** and/or if the address is unencrypted, data packets may be determined to be associated with the user device, such as by the monitoring device. If user

devices **101** at the premises **102** are configured to communicate via a router, the monitoring device may be configured to determine that packets sent by the user devices **101** are associated with a common premises and/or group of devices, such as based on the packets sent by the user devices **101** indicating the address of the same router.

(22) The computing device **103** may be configured to track communications from and/or to the user device **101**. The computing device **103** may be configured to track the communications from the user device **101** to the computing device **103** and/or particular information in the communications (e.g., data associated with a user of the user device **101**). The computing device **103** may be configured to store the information. An entity associated with the computing device **103**, such as a company and/or an organization, may sell the information and/or may use the information, such as for advertising, marketing, and/or other purposes.

(23) The user device **101** may be configured to communicate with the computing device **103** using an anonymity network, such as an onion router (TOR). The anonymity network may comprise software on the user device **101**. The anonymity network may be configured to determine a virtual circuit. The virtual circuit may comprise a plurality of computing devices. The virtual circuit may comprise a sequence of the plurality of computing devices by which a data packet from the user device **101** may be sent. The computing devices may comprise other user devices. The computing devices may comprise other devices that are running anonymity networks. The computing devices and/or their sequence may be randomly determined.

(24) The anonymity network may be configured to encrypt a data packet from the user device **101** in one or more layers of encryption. The anonymity network may be configured to add an address associated with a computing device in the virtual circuit in layers of encryption. A layer of encryption may comprise an encryption of the data packet corresponding to a computing device in the virtual circuit. For example, a layer of encryption may comprise an encryption of the packet with a key associated with a computing device in the virtual circuit. An order of the layers of encryption may be associated with the sequence in which the data packet will be sent to the computing devices in the virtual circuit. For example, an outermost layer may be associated with a first computing device in the sequence. As a result, the outermost layer may be decrypted by the first computing device, which may reveal a next layer of encryption. Decryption of the outermost layer may reveal an address of a next computing device in the virtual circuit. The first computing device in the virtual circuit may be configured to send the data packet to the next computing device in the virtual circuit based on the address.

(25) The first computing device in the virtual circuit may be configured to receive the data packet from the user device **101** via a communication session with the user device **101**. The first computing device may be configured to send the data packet to the second computing device in the virtual circuit via a communication session with the second computing device. Each computing device in the virtual circuit may be configured to receive the data packet via a communication session with the previous and/or the next computing device in the sequence. The last computing device in the virtual circuit may be configured to send the data packet to the destination, such as the computing device **103**, via a communication session with the destination device. The communication session may comprise a secure communication session. The communication session may comprise an encrypted communication session. The communication session may comprise end-to-end encryption, such as a Secure Sockets Layer (SSL) or Transport Layer Security (TLS) communication session.

(26) Based on receiving the data packet, computing devices in the virtual circuit may be configured to decrypt a layer, revealing an address of a next computing device in the virtual circuit. Each computing device in the virtual circuit may be configured to determine from which device the computing device received the data packet and to which device the computing device is sending the data packet (e.g., the previous device in the sequence and the next device in the sequence).

However, a computing device in the virtual circuit may not be capable of determining from which

device the data packet originated. For example, one or more computing devices in the virtual circuit may not be able to determine that the data packet was originally sent by the user device **101**.

(27) An inner layer may be associated with a last computing device in the virtual circuit. Decryption of the innermost layer may reveal an address associated with a destination of the data packet, such as the computing device **103**. The last computing device in the virtual circuit may be configured to send the data packet to the computing device **103** based on the address.

(28) An innermost layer may be associated with the destination of the data packet, such as the computing device **103**. The computing device **103** may decrypt the final layer. Decryption of the final layer may reveal contents of the data packet, such as the data communicated by the user device **101** to the computing device **103** (e.g., the message).

(29) Computing devices in the virtual circuit may not be able to determine the destination of the data packet. The computing devices may be configured to determine to which device to send the data packet. However, addresses of later computing devices in the sequence, including that of the destination device, may be encrypted and unobservable. Although the last computing device in the sequence of the virtual circuit may be configured to determine the address of the destination device, such as the address of computing device **103**, the computing device may not be able to distinguish the destination device from another node in the virtual circuit.

(30) The computing device **103** may be configured to send one or more data packets. For example, the computing device **103** may be configured to send a data packet in response to the one or more data packets received from the user device **101** via the virtual network. The computing device **103** may not be configured to determine the address of the user device **101** based on the received data packets not comprising an indication of the address of the user device **101**. However, the computing device **103** may be configured to determine the device from which the computing device **103** received the data packets (e.g., the last computing device in the virtual network). Based on the address of the last computing device in the virtual network in the received data packets, the computing device **103** may be configured to send the data packets to the last computing device in the virtual network. The last computing device in the virtual network may be configured to relay the data packets from the computing device **103** to the previous computing device in the virtual network sequence. Each computing device in the virtual network may be configured to relay the data packets to the previous computing device in the virtual network sequence. The data packets may be routed through the virtual network in a reverse order of the sequence by which the data packets from the user device were sent to the computing device **103**. Based on receiving the data packets, the first computing device in the virtual network sequence may be configured to send the data packets to the user device **101**.

(31) Use of the anonymity network may prevent a monitoring device from determining from which device the data packet originated. However, even with the use of TOR, the monitoring device may be configured to determine information associated with the behavior, network traffic, and/or activity of the user device **101**. For example, the monitoring device may be configured to determine that communications with the computing device **103** occurred. If the computing device **103** hosts a website, provides content, and/or provides a service, the monitoring device may be configured to determine that the website was accessed, the content was accessed, and/or the service was utilized. The monitoring device may be configured to determine a duration of time and/or period of time that the website was accessed, the content was accessed, and/or the service was used. The monitoring device may be configured to determine a duration of time and/or period of time of a communication session with the computing device. The monitoring device may be configured to determine that an anonymity network was used. The monitoring device may be configured to determine an amount of data that was transferred to and/or from the computing device **103**.

(32) Vulnerabilities of an anonymity network and/or encryption may be addressed by using a privacy gateway **105**. The privacy gateway **105** may comprise a computing device or a plurality of computing devices. The privacy gateway **105** may comprise a software application on a computing

device. The software application may operate at a mid-point between communications of a client and a server. The privacy gateway may comprise a network appliance, a network switch or router, a virtual machine deployed in a private or public cloud, a serverless workload deployed in a private or public cloud, an application operating on a computer server, and/or an application operating on a host computer, as examples. The privacy gateway **105** may be configured to communicate with the user devices **101** and/or the computing device **103**. The privacy gateway **105** may be configured to communicate with user devices **101** located at a plurality of premises **102**. The plurality of premises **102** may be in different locations, such as different cities, counties, states, and/or countries. One or more of the premises **102** may be in a same location. The privacy gateway **105** may be located external to the premises **102**. The privacy gateway **105** may be located in a public location, such as a server farm and/or a service provider facility.

(33) The privacy gateway **105** may comprise a networking device **106**. The networking device **106** may comprise a VPN concentrator. The networking device **106** may comprise a software application. The networking device **106** may comprise a gateway endpoint for an end of an encrypted VPN tunnel. The networking device **106** may use hardware devices to perform encryption computation tasks. The networking device **106** may be implemented as a server, a network appliance, a firewall appliance, a router, and/or another network component.

(34) The networking device **106** may be configured to communicate with the user devices **101** and/or the computing device **103** via the network **104**. The networking device **106** may comprise a firewall **110**. The firewall **110** may be configured to block data from devices other than the user device **101**, such as untrusted devices.

(35) The networking device **106** may be configured to communicate with the user device **101** via a communication session **107**. The networking device **106** may comprise a VPN client **111** configured to initiate and/or setup the communication session **107**. The VPN client **111** may comprise an IPsec VPN client, such as a strongSwan VPN client.

(36) The communication session **107** may comprise a client-side connection in which the privacy gateway **105** acts as a server and the user device **101** acts as a client to the server. The communication session **107** may comprise a virtual private network (VPN) tunnel. The networking device **106** may comprise an exit node of the VPN tunnel. The communication session **107** may comprise an Internet Protocol Security (IPsec)-encrypted VPN tunnel. The communication session **107** may comprise a Layer 2 Tunneling Protocol (L2TP). The communication session **107** may comprise a Point to Point Tunneling Protocol (PPTP) VPN tunnel. The communication session may comprise an OpenVPN tunnel. The communication session **107** may comprise malware filtering functionality. The communication session **107** may comprise Flash and/or Javascript blocking functionality. The networking device **106** may be configured to communicate with a plurality of user devices **101** via a plurality of communication sessions **107**. The plurality of communication sessions **107** may use a same endpoint address to connect to the networking device **106**.

(37) The communication session **107** may be established based on an initiation and/or setup, such as by the user device **101** and/or the networking device **106**. The initiation and/or setup may be defined by a central access policy. The central access policy may comprise a function of the networking device **106** that provides user-access-control into the networking device **106**. Users may have login credentials for connecting to the networking device **106** and the central access policy may validate the credentials for access. For example, the central access policy may indicate an authentication method that must take place to establish the communication session **107**. The initiation and/or setup may comprise performing a handshake. The initiation and/or setup may comprise exchange of authentication items, such as digital certificates. An authentication item associated with the user device **101** may be created based an account associated with the user device. For example, an account may be created. An account profile may be created. The account and/or the profile may be created by a user using the user device **101**. The account and/or the profile may be associated with a service associated with the system **100**. The service may comprise

a communication service and/or a content service, as examples. Based on generation of the account and/or the profile, the user device **101** may be configured to send a request for the authentication item. The user device **101** may be configured to send the request for the authentication item to a computing device associated with the service and/or the system **100**. Based on the request, the user device **101** may receive the authentication item. The user device **101** may be configured to store the authentication item on the user device **101**.

(38) The user device **101** may be configured to send the networking device **106** the authentication item associated with the user device **101**. The networking device **106** may be configured to send the user device **101** an authentication item associated with the privacy gateway **105** and/or the networking device **106**. The authentication item may be stored to the privacy gateway **105** and/or the networking device **106**.

(39) The user device **101** and/or the networking device **106** may be configured to authenticate each other based on the received authentication items. For example, the user device **101** and/or the networking device **106** may be configured to determine that the authentication item is signed by a trusted third-party device, such as a certificate authority (CA). The user device **101** and/or the networking device **106** may be configured to send the authentication item to the trusted third-party device, such as the CA. The user device **101** and/or the networking device **106** may be configured to receive a response from the trusted third-party device indicating that the authentication item is associated with a trusted device. A trusted device may comprise a device that is known to be associated with a user, a service provider, and/or a manufacturer. A trusted device may comprise a device that has previously identified itself, such as by sending an authentication item, an indication of an associated user, an indication of a service provider, and/or an indication of a manufacturer. A trusted device may comprise a device that runs security software.

(40) The user device **101** and/or the networking device **106** may be configured to authenticate the other device based on validating the authentication item. Validating the authentication item may comprise comparing the authentication item to a known and/or saved authentication item. For example, one or more of the devices may be configured to determine that the authentication item matches a previously-received authentication item. The previously-received authentication item and/or an indication of the previously-received authentication item may be stored to the device.

(41) The user device **101** and/or the networking device **106** may be configured to exchange keys. The user device **101** and/or the networking device **106** may be configured to exchange keys based on authentication. The keys may be configured to encrypt data, such as data to be sent via the communication session **107**. The keys may be configured to decrypt data, such as data sent via the communication session **107**. The user device **101** may encrypt one or more data packets, such as using the key received from the networking device **106**. The user device **101** may send the encrypted data packets to the networking device **106**. The user device **101** may send the encrypted data packets to the networking device **106** using the communication session **107**. Based on the encryption of the data packets, a monitoring device may not be able to determine the contents of the data packets.

(42) The networking device **106** may be configured to receive one or more data packets, such as data packets from the user devices **101**. The networking device **106** may be configured to receive the data packets, such as via the communication session **107**. The data packets may be sent using a secure communication protocol, such as HTTPS, HTTP, TCP, UDP, and/or TLS. The networking device **106** may be configured to decrypt a data packet.

(43) The networking device **106** may be configured to determine a destination of the decrypted data packet, such as the computing device **103**, based on an address indicated in the data packet. Based on determining that the destination of the data packet is the computing device **103**, the networking device **106** may be configured to initiate a communication session **108** with the computing device **103**. Initiating the communication session **108** may comprise performing a handshake with the

computing device **103**. Initiating the communication session **108** may comprise sending a request to the computing device **103**. Based on the request, the computing device **103** may be configured to send an authentication item, such as a digital certificate, to the networking device **106**. The networking device **106** may be configured to send an authentication item to the computing device **103**. The networking device **106** may be configured to send an authentication item associated with the user device **101**, such as the digital certificate of the user device **101**, to the computing device **103**. The computing device **103** may send the authentication item back to the networking device **106** with a signature of the computing device **103**. The networking device **106** may be configured to send the authentication item back to the user device **101**. The networking device **106** may be configured to send the signed authentication item to the user device **101**. The networking device **106** may be configured to send the authentication item to the system, such as to the privacy concentrator **109**. The privacy concentrator **109** may comprise an anonymizer **115**. The anonymizer **115** may comprise a TLS proxy. The anonymizer **115** may comprise an enforced private browsing proxy. The anonymizer **115** may comprise an HTTP anonymizer. The anonymizer **115** may comprise a man-in-the-middle. The anonymizer **115** may be configured to set up parallel communication sessions, such as the communication session **107** with the user device **101** and a communication session **117** with the computing device **103**. The anonymizer **215** may be configured to aggregate devices on a public IP (Pub IP). The anonymizer **215** may be configured to aggregate the user devices **101**. The anonymizer **215** may be configured to aggregate the devices on a public IP in the CG NAT **116** where traffic from the devices may be made to appear to come from a fewer number of IP addresses. The networking device **106** may be configured to send the authentication item to the anonymizer **115**. The anonymizer **115** may be configured to sign the certificate. The anonymizer may be configured to send the signed certificate to the user device **101**.

(44) The networking device **106** may be configured to receive an authentication item associated with the computing device **103**, such as from the computing device **103**. The computing device **103** may be configured to send the authentication item associated with the computing device **103** based on receiving the authentication item associated with the user device **101**. The networking device **106** may be configured to send the authentication item associated with the computing device **103** to the user device **101**.

(45) The networking device **106** and/or the computing device **103** may be configured to authenticate each other. For example, the networking device **106** and/or the computing device **103** may be configured to authenticate each other by validating the exchanged authentication items. Based on authenticating one another, the networking device **106** and/or the computing device **103** may be configured to exchange keys. The keys may be configured to encrypt data to be sent via the communication session **108**. The keys may be configured to decrypt data sent via the communication session **108**.

(46) The networking device **106** may be configured to act as a client device, such as to the computing device **103**. The networking device **106** may be configured to act as an end device to the user device **101**. The networking device **106** may be configured to act as a man-in-the-middle device, such as by establishing and/or maintaining parallel communication sessions with one or more user devices **101** and/or one or more computing devices **103**. The parallel communication sessions may be at least partially contemporaneous.

(47) The privacy gateway **105** may comprise a privacy concentrator **109**. The privacy concentrator **109** may comprise a computing device distinct from the networking device **106**. The privacy concentrator **109** and the networking device **106** may comprise components on a same device (e.g., the privacy gateway **105**). The privacy concentrator **109** may comprise a transport layer security (TLS) proxy, a man-in-the-middle, and/or an S-cell proxy. The privacy concentrator **109** may be configured to receive data packages associated with the user device **101** from the networking device **106**.

(48) The networking device **106** may comprise a tunnel interface **112**. The tunnel interface **112** may

be configured to send the packages to the privacy concentrator **109**. The privacy concentrator **109** may comprise a tunnel interface **113**. The tunnel interface **113** of the privacy concentrator **109** may be configured to receive the packages from the tunnel interface **112** of the networking device. The tunnel interfaces **112**, **113** may be configured to communicate via a communication session **114**. The communication session **114** may comprise a tunnel. The communication session **114** may comprise tunnel (e.g., an unencrypted tunnel). The communication session **114** may comprise a cleartext tunnel. Via the communication session **114**, the networking device **106** may be configured to send data, such as packets, to the privacy concentrator **109** in cleartext and/or plaintext.

(49) A tunnel (e.g., an unencrypted tunnel) between the user device **101** and the computing device **103** may be established. The user device may send traffic intended for the computing device **103** through the tunnel to the privacy gateway. The privacy gateway may be configured to perform an HTTPS man in the middle and/or a network address translation (NAT) using a tunnel (e.g., an encrypted tunnel). Addressing on tunnel headers may be in cleartext. But, traffic between user devices **101** and a computing device **103** may be encrypted over HTTPS and sent via the tunnel.

(50) The anonymizer **115** may be configured to determine data associated with the user device **101**, such as in a data packet received from the user device **101**. The data associated with the user device **101** may comprise one or more pieces of information. The data associated with the user device **101** may comprise an address of the user device **101**. The data associated with the user device **101** may comprise an address of a router used by the user device **101**. The data associated with the user device **101** may comprise an indication of a geographic location of the user device **101**. The data associated with the user device **101** may comprise a browser running on the user device **101**. The data associated with the user device **101** may comprise a central processing unit (CPU) of the user device **101**. The data associated with the user device **101** may comprise data associated with a user of the user device **101**. Data associated with the user may comprise an account name of the user, an employer of the user, and/or a geographic location of the user. The data associated with the user device **101** may comprise data that is not encrypted in data packets according to a communication protocol, such as HTTPS. The data associated with the user device **101** may be in an HTTP header of the data packet.

(51) The anonymizer **115** may be configured to remove the data associated with the user device **101** from the data packet. Removing the data associated with the user device **101** may comprise generating a new data packet that does not comprise the data associated with the user device **101**. For example, based on a TCP connection, the data packet may terminate when it is received by the privacy gateway **105**. The anonymizer **115** may generate a new data packet without the data associated with the user device **101**. Removing the data associated with the user device **101** may comprise stripping the data from the data packet received from the user device **101**.

(52) The anonymizer **115** may be configured to replace the data associated with the user device **101** in the data packet. For example, the anonymizer **115** may be configured to replace the data associated with the user device **101** in the data packet with data associated with the privacy gateway **105**. The data associated with the privacy gateway **105** may comprise an address associated with the privacy gateway **105**. Replacing the data associated with the user device **101** with the data associated with the privacy gateway **105** may comprise generating a new data packet comprising the data associated with the privacy gateway **105**. Replacing the data associated with the user device **101** with the data associated with the privacy gateway **105** may comprise adding the data associated with the privacy gateway **105** to the data packet received from the user device **101**.

(53) The anonymizer **115** may be configured to re-encrypt at least a portion of the data packet. The anonymizer **115** may be configured to re-encrypt at least a portion of the data packet using a key associated with the computing device **103**, such as the public key of the computing device **103**. The anonymizer **115** may be configured to send the data packet to the computing device **103**, such as via the communication session **108**.

(54) The privacy concentrator **109** may comprise a carrier-grade network address translator (CG

NAT) **116**. The CG NAT **116** may be configured to send the data packet to the computing device **103**. The CG Nat **116** may be configured to send the data packet via a network **104** (e.g., the network **104** in FIG. 1). The CG Nat **116** may be configured to send the data packet via a communication session **117** with the computing device **103**. The communication session **117** may comprise a server-side connection wherein the privacy gateway **105** and/or the privacy concentrator **109** functions as a client to the computing device **103**. The privacy gateway **105** may be configured to maintain at least a portion of the communication session **107** with the user device **101** and at least a portion of the communication session **108** with the computing device **103** contemporaneously.

(55) An tunnel (e.g., an encrypted tunnel) between the user device **101** and the computing device **103** may be established. The user device **101** may send traffic intended for the computing device **103** through the tunnel to the privacy concentrator **109**. The privacy concentrator **109** may be configured to perform an HTTPS man in the middle and/or a network address translation (NAT) using an tunnel. For example, the privacy concentrator **109** may be configured to proxy the HTTPS connection inside the privacy concentrator **109** and/or the privacy gateway **102**. The privacy concentrator **102** may be configured to change data inside the HTTPS connections. The changes may comprise removing identifying information in the packets, such as to prevent the computing device **103** from identifying the user device **101** from which the packets originate. Addressing on tunnel headers may be in cleartext. But, traffic between the user devices **101** and the computing device **103** may be encrypted over HTTPS and sent via the tunnel.

(56) The privacy concentrator **109** may be configured to receive one or more data packets, such as from the computing device **103**. The privacy concentrator **109** may be configured to determine that the data packets are for the user device **101**. The privacy concentrator **109** may be configured to determine that the data packets are for the user device **101** by maintaining a session state of communications between a user device **101** and the server **103**. The privacy concentrator **109** may be configured to remember which connection from the server **103** is associated with which user device **101**. The privacy concentrator **109** may be configured to determine data in a data packet that is associated with the privacy gateway **105**. The privacy concentrator **109** may be configured to remove the data associated with the privacy gateway **105** from the data packet. The privacy concentrator **109** may be configured to add data associated with the user device **101** to the data packet. The privacy concentrator **109** may be configured to encrypt at least a portion of the data packet. The portion may comprise a message and/or contents of the package. A portion left unencrypted may comprise data that is needed to route the packet to the user device **101**, such as an address. The privacy concentrator **109** may be configured to send the data packet to the user device **101**, such as via the communication session **107**.

(57) The privacy gateway **105** may be configured to end the communication session **107** with the user device **101** and/or the communication sessions **108**, **117** with the computing device **103**. The privacy gateway **105** may be configured to end one or more sessions **107**, **108**, **117** based on sending one or more data packets to the computing device **103**. The privacy gateway **105** may be configured to end one or more sessions **107**, **108**, **117** based on sending one or more data packets to the user device **101**. The privacy gateway **105** may be configured to end one or more sessions **107**, **108**, **117** based on receiving an indication from the user device **101** to end communication sessions.

(58) One or more IP cookies may be deleted, such as based on ending one or more of the communication sessions **107**, **108**, **117**. A cookie may comprise identifying information associated with the user device **101**, the computing device **103**, and/or a user of the user device **101**. A cookie may comprise an indication of activity and/or communications during a communication session. The cookies may be stored to the user device **101**. The user device **101** may be configured to delete the cookies. The privacy gateway **105** may cause the cookies to be deleted. Canvas fingerprinting and/or browser fingerprinting may be deleted, such as based on ending one or more of the communication sessions **107**, **109**.

(59) A device monitoring traffic between the user device **101**, the privacy gateway **105**, and/or the computing device **103** may not be able to determine that the user device **101** is receiving data from the computing device **103**. For example, the monitoring device may not be able to determine websites, content, and/or services accessed by the computing device **103**. The monitoring device may not be able to determine a duration of time and/or period of time that the website was accessed, the content was accessed, and/or the service was used. The monitoring device may not be able to determine a duration of time and/or period of time of a communication session with the computing device. The monitoring device may not be able to determine an amount of data that was transferred to and/or from the computing device **103**. The privacy gateway **105** may be configured to perform one or more operations configured to hide an identity of a user device **101**. The operations may comprise deleting cookies, as an example.

(60) A monitoring device may not determine device associations. A monitoring device may not determine device associations based on the privacy gateway **105** being located external to the premises and being in communication with a plurality of devices at a plurality of premises. For example, the monitoring device may not determine that a plurality of user devices **101** use a same router. The monitoring device may not determine that the plurality of user devices **101** are located at same premises. Based on the privacy gateway **105** being in communication with a plurality of clients through the same addressing, the monitoring device cannot determine a connection used by a user device **101**.

(61) FIG. 2 shows an example method **200**. The method **200** may be performed by a system, such as the system **100** in FIG. 1, or any other computing device. The system may comprise a user device **201** (e.g., the user device **101** in FIG. 1). The system may comprise a privacy gateway (e.g., the privacy gateway **105** in FIG. 1). The privacy gateway may comprise a networking device **206** (e.g., the networking device **106** in FIG. 1). The privacy gateway may comprise a privacy concentrator **209** (e.g., the privacy concentrator **109** in FIG. 1). The system may comprise a network **204** (e.g., the network **104** in FIG. 1). The system may comprise a computing device **203** (e.g., the computing device **103** in FIG. 1). The method **200** may comprise a method for the user device **201** to communicate with the computing device **203**, such as via the privacy gateway.

(62) At step **217**, the user device **201** and the networking device **206** may perform a handshake. The handshake may comprise a TCP handshake. The handshake may be performed based on a user of the user device **201** navigating to a website over HTTPS. The handshake may be performed based on a browser on the user device **201** generating a query for the website's origin server, such as the computing device **203**. The handshake may be performed based on the user device **201** requesting data, content, and/or a service from the computing device **203**.

(63) The handshake may comprise the user device **201** sending one or more packets. The user device **201** may send the packets to the networking device **206**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the user device **201**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the user device **201**. The port numbers may comprise a port number of the networking device **206**. The port numbers may comprise a port number of the computing device **203**.

(64) The handshake may comprise the networking device **206** sending one or more packets. The networking device **206** may send the one or more packets to the user device **201**. The networking device **206** may send the one or more packets based on receiving one or more packets from the user device **201**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the networking device **206** received the one or more packets from the user device **201**. The packet may

comprise an indication of a sequence number. The sequence number may be determined by the networking device **206**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the user device **201** plus one.

(65) The handshake may comprise the user device **201** sending one or more packets. The client may send the one or more packets to the networking device **206**. The client may send the one or more packets based on receiving the one or more packets from the networking device **206**. A packet may comprise an indication that the user device **201** received the one or more packets from the networking device **206**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or client port. The packet may comprise an indication of the destination and/or server port. The packet may comprise an indication of a new sequence number associated with the user device **201**. The new sequence number may comprise the initial sequence number associated with the user device **201** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the networking device plus one. Based on performing the handshake, a communication session may be established, such as a TCP session.

(66) At step **218**, the user device **201** may send the networking device **206** a message. The message may comprise an indication to initiate another handshake, such as a TLS and/or SSL handshake. The message may comprise a “Client Hello” message. The message may be sent based on performing the handshake in step **217**. The message may be sent via the communication session established in step **217**. The message may comprise a packet, such as a TCP packet. The message may comprise an indication of an encryption and/or communication protocol supported by the user device **201**. The indication of the encryption and/or communication protocol may comprise an indication of a highest version of an encryption and/or communication protocol supported by the user device **201**, such as a highest version of TLS protocol that the user device supports. The message may comprise an indication of a random number generated by the user device **201**. The message may comprise an indication of one or more cipher suites supported by the user device **201**. The cipher suits may comprise one or more cryptographic algorithms, such as a server authentication algorithm, a key exchange algorithm, a bulk encryption algorithm, and/or a message integrity algorithm. The message may comprise an indication of a compression algorithm supported by the user device **201**. The message may comprise an indication of a session identifier. The session identifier may be used to resume an existing communication session instead of performing a handshake again. The networking device **206** may receive the message.

(67) At step **219**, the networking device **206** and the computing device may perform a handshake. The handshake may be performed via the network **204**. The handshake may be performed based on performing the handshake in step **217** and/or receiving the message from the user device **201** in step **218**. The handshake may comprise a TCP handshake.

(68) The handshake may comprise the networking device **206** sending one or more packets. The networking device **206** may send one or more packets to the computing device **203**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the networking device **206**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the networking device **206**. The port numbers may comprise a port number of the computing device **203**.

(69) The handshake may comprise the computing device **203** sending one or more packets. The computing device **203** may send the one or more packets to the networking device **206**. The computing device **203** may send the one or more packets based on receiving one or more packets

from the networking device **206**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the computing device **203** received the one or more packets from the networking device **206**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the computing device **203**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the networking device **206** plus one.

(70) The handshake may comprise the networking device **206** sending one or more packets. The client may send the one or more packets to the computing device **203**. The networking device **206** may send the one or more packets based on receiving the one or more packets from the computing device **203**. A packet may comprise an indication that the networking device **206** received the one or more packets from the computing device **203**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or networking device **206** port. The packet may comprise an indication of the destination and/or computing device **203** port. The packet may comprise an indication of a new sequence number associated with the networking device **206**. The new sequence number may comprise the initial sequence number associated with the networking device **206** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the computing device **203** plus one. Based on performing the handshake, a communication session may be established.

(71) At step **220**, the networking device **206** may send the computing device **203** a message. The message may be sent via the network **204**. The message may comprise an indication to initiate another handshake, such as a TLS and/or SSL handshake. The message may comprise a "Client Hello" message. The response may be sent based on performing the handshake in step **217**. The response may be sent via the communication session established in step **219**. The message may comprise a packet, such as a TCP packet. The message may comprise an indication of an encryption and/or communication protocol supported by the networking device **206**. The indication of the encryption and/or communication protocol may comprise an indication of a highest version of an encryption and/or communication protocol supported by the networking device **206**, such as a highest version of TLS protocol that the networking device **206** supports. The message may comprise an indication of a random number generated by the networking device **206**. The message may comprise an indication of one or more cipher suites supported by the networking device **206**. The cipher suits may comprise one or more cryptographic algorithms, such as a server authentication algorithm, a key exchange algorithm, a bulk encryption algorithm, and/or a message integrity algorithm. The message may comprise an indication of a compression algorithm supported by the networking device **206**. The message may comprise an indication of a session identifier. The session identifier may be used to resume an existing communication session instead of performing a handshake again. The computing device **203** may receive the message.

(72) At step **221**, the networking device **206** may receive a message. The message may be sent by the computing device **203**. The message may be sent via the network **204**. The message may be sent via the communication session established in step **219**. The message may comprise a "Server Hello" message. The message may be associated with initiation of a TLS and/or SSL handshake. The message may comprise a response to and/or an acknowledgement of receipt of the message sent and/or received in step **220**. The message may be sent based on finishing the handshake in step **219**.

(73) At step **222**, the networking device **206** and the computing device **203** may perform a handshake. The handshake may comprise a TLS and/or SSL handshake. The handshake may be performed based on the sending and/or receiving of the message from the computing device **203** in step **221**. The handshake may be performed based on the sending and/or receiving of the message

from the networking device **206** in step **220**.

(74) Performing the handshake may comprise sending one or more digital certificates. For example, the networking device **206** may receive a certificate from the computing device **203**. The certificate of the computing device **203** may comprise an indication of a public key associated with the computing device **203**. The certificate may be associated with a website associated with the computing device **203**. Receiving the certificate may cause a TLS encrypted connections setup to be initiated.

(75) Performing the handshake may comprise the networking device **206** validating the certificate. Validating the certificate may comprise determining that the certificate is signed by a CA. Validating the certificate may comprise determining that the certification authority is known and/or trusted. For example, the networking device **206** may have access and/or have stored a list of CA's that are trusted. The networking device **206** may determine that the CA that signed the certificate is on the list. The networking device **206** may validate the certificate by sending the certificate to an CA and receiving an indication from the CA that the computing device **203** is a trusted device.

(76) Performing the handshake may comprise the networking device **206** receiving one or more messages from the computing device **203**. The message may comprise a request for a certificate associated with the networking device **206**. The request may comprise an indication of one or more certificate authorities trusted by the computing device **203**. The request may comprise an indication of a type of the certificate. The message may comprise an indication that the computing device **203** is finished performing its steps of the handshake. For example, the message may comprise a "Server Hello Done" message. The networking device **206** may cache the certificate of the computing device **203**, such as on a memory of the networking device **206**. The networking device **206** may cache the public key of the computing device **203**.

(77) Performing the handshake may comprise the networking device **206** sending a digital certificate of the networking device **206** to the computing device **203**. The networking device **206** may send the certificate to the computing device **203** based on receiving the request for the certificate from the computing device **203**. The networking device **206** may send the certificate of the networking device **206** to a CA. The networking device **206** may send the certificate to a CA indicated in the request. If the certificate of the networking device **206** comprises a certificate of a certificate chain, the networking device **206** may send its public certificate and one or more other certificates in the chain to a root CA of the chain.

(78) Performing the handshake may comprise the computing device **203** validating the certificate of the networking device **206**. Validating the certificate may comprise determining that the certificate is signed by a known and/or trusted CA. The known and/or trusted CA may comprise a CA in the list sent to the networking device **206**. If the certificate is of a certificate chain, validating the certificate may comprise determining that one or more certificates in the chain and signed by a known and/or trusted CA.

(79) Performing the handshake may comprise the networking device **206** encrypting a premaster secret key. The networking device **206** may encrypt the premaster secret key based on validating the certificate of the computing device **203**. The networking device **206** may use the public key from the certificate to encrypt a premaster secret key. The premaster key may comprise a shared secret between the networking device **206** and the computing device **203**.

(80) Performing the handshake may comprise the networking device **206** sending computing device **203** a message. The message may comprise a "Client Key Exchange" message. The message may comprise the encrypted premaster secret key to the computing device **203**. The message may comprise an indication of an encryption and/or communication protocol. The encryption and/or communication protocol may be the same protocol indicated in the message sent by the networking device **206** in step **220**.

(81) Performing the handshake may comprise determining a master secret. The networking device **206** and/or the computing device **203** may determine the master secret. The master secret may be

determined using the random number of the networking device **206**, the random number of the computing device **203**, and/or the premaster secret. The networking device **206** may send a message (e.g., a “Change Cipher Spec” message) to the computing device **203** indicating that subsequent messages should be protected with the exchanged keys. The networking device **206** may send the computing device **203** a message (e.g., a “Finished” message) indicating a hash of a message flow of the handshake. The hash may be encrypted using the exchanged keys.

(82) The networking device **206** may receive a message from the computing device **203**. The computing device **203** may send the message based on receiving one or more of the messages from the networking device **206**. The message may comprise a “Change Cipher Spec” message. The message may indicate that the computing device **203** is ready to communicate using the exchanged keys. The message may comprise the hash of a message flow of the handshake. The hash may be encrypted with the exchanged keys.

(83) At step **223**, the handshake of step **224** may be finished. Based on completion of the handshake, there may be an encrypted channel (e.g., connection, communication session, etc.) between the networking device **206** and the computing device **203** (e.g., between the indicated ports of the devices). Based on completion of the handshake, the networking device **206** and the computing device **203** may communicate using the encrypted channel.

(84) At step **224**, the networking device **206** may send a message. The networking device **206** may send the message to the user device **201**. The message may be sent via the communication session established in step **217**. The message may comprise a “Server Hello” message. The message may be associated with initiation of a TLS and/or SSL handshake. The message may comprise a response to and/or an acknowledgement of receipt of the message sent and/or received in step **218**. The message may be sent based on receiving the message in step **218**. The message may be sent based on finishing the handshake in step **223**.

(85) At step **225**, the user device **201** and the networking device **206** may perform a handshake. The handshake may comprise a TLS and/or SSL handshake. The handshake may be performed based on the sending and/or receiving of the message from the networking device **206** in step **224**. The handshake may be performed based on the sending and/or receiving of the message from the user device **201** in step **218**.

(86) Performing the handshake may comprise sending one or more digital certificates. For example, the networking device may send the user device **201** a certificate of the privacy gateway and/or the networking device **206**. The certificate of the privacy gateway and/or the networking device **206** may comprise an indication of a public key associated with the privacy gateway and/or the networking device **206**. The networking device may send the user device **201** the certificate of the computing device **203** received in step **222**.

(87) Performing the handshake may comprise the user device **201** validating one or more of the certificates. Validating the certificate may comprise determining that the certificate is signed by a CA. Validating the certificate may comprise determining that the certification authority is known and/or trusted. For example, the user device **201** may have access and/or have stored a list of CA's that are trusted. The user device **201** may determine that the CA that signed the certificate is on the list.

(88) Performing the handshake may comprise the networking device **206** sending one or more messages to the user device **201**. The message may comprise a request for a certificate associated with the user device **201**. The request may comprise an indication of one or more certificate authorities trusted by the server. The request may comprise an indication of a type of the certificate. The message may comprise an indication that the networking device **206** is finished performing its steps of the handshake. For example, the message may comprise a “Server Hello Done” message.

(89) Performing the handshake may comprise the user device **201** sending a certificate of the user device **201** to the networking device **206**. The user device **201** may send the certificate to the networking device **206** based on receiving the request for the certificate from the networking

device **206**. The user device **201** may send the certificate of the user device **201** to a CA. The user device **201** may send the certificate to a CA indicated in the request. If the certificate of the user device **201** comprises a certificate of a certificate chain, the user device **201** may send its public certificate and one or more other certificates in the chain to a root CA of the chain.

(90) Performing the handshake may comprise the networking device validating the certificate of the user device **201**. Validating the certificate may comprise determining that the certificate is signed by a known and/or trusted CA. The known and/or trusted CA may comprise a CA in the list sent to the user device **201**. If the certificate is of a certificate chain, validating the certificate may comprise determining that one or more certificates in the chain are signed by a known and/or trusted CA.

(91) Performing the handshake may comprise the user device **201** encrypting a premaster secret key. The user device **201** may encrypt the premaster secret key based on validating the certificate of the privacy gateway and/or the networking device **206**. The user device **201** may use the public key from the certificate to encrypt a premaster secret key. The premaster key may comprise a shared secret between the user device **201** and the privacy gateway and/or the networking device **206**.

(92) Performing the handshake may comprise the user device **201** sending the networking device **206** a message. The message may comprise a “Client Key Exchange” message. The message may comprise the encrypted premaster secret key to the networking device **206**. The message may comprise an indication of an encryption and/or communication protocol. The encryption and/or communication protocol may be the same protocol indicated in the message sent by the user device **201** in step **218**.

(93) Performing the handshake may comprise determining a master secret. The user device **201** and/or the networking device **206** may determine the master secret. The master secret may be determined using the random number of the user device **201**, the random number of the networking device **208**, and/or the premaster secret. The user device **201** may send a message (e.g., a “Change Cipher Spec” message) to the networking device **206** indicating that subsequent messages should be protected with the exchanged keys. The user device **201** may send the networking device a message (e.g., a “Finished” message) indicating a hash of a message flow of the handshake. The hash may be encrypted using the exchanged keys.

(94) The networking device **206** may send the user device **201** a message based on receiving one or more of the messages from the user device **201**. The message may comprise a “Change Cipher Spec” message. The message may indicate that the networking device **206** is ready to communicate using the exchanged keys. The message may comprise the hash of a message flow of the handshake. The hash may be encrypted with the exchanged keys.

(95) At step **226**, the handshake of step **225** may be finished. Based on completion of the handshake, there may be an encrypted channel (e.g., connection, communication session, etc.) between the user device **201** and the networking device **206** (e.g., between the indicated ports of the devices). Based on completion of the handshake, the user device **201** and the networking device **206** may communicate using the encrypted channel.

(96) At step **227**, the networking device **206** may reset the connection between the networking device **206** and the computing device **203**. Resetting the connection may comprise ending the connection. The connection may be reset based on performing the handshake in step **225**. The connection may be reset to force the connection between the networking device **206** and the server **203** to reconnect. The first connection between the networking device **206** and the server **203** may be used to pull the server certificates from the server **203**. The server certificates pulled from the server **203** may be resigned back to the client. A second connection between the networking device **206** and the server **203** may be established to create a proxied connection. At least a portion of step **227** may be performed simultaneous with at least a portion of step **225**.

(97) At step **228**, the user device **201** may send a request. The request may comprise a request associated with the computing device **203**. For example, the request may comprise a request for

data, a service, and/or content from the computing device **203**. The request may comprise data for the computing device **203**. The request may comprise a request to communicate with the computing device **203**. The request may comprise an indication to relay the request to the computing device **203**. The request may comprise a website request, such as an HTTP GET request. The request may comprise a request for website information.

(98) The user device **201** may send the request to the networking device **206**. The request may be sent based on performing the handshake in step **225**. The request may be sent using the channel set-up by performing the handshake in step **225**. The request may comprise one or more chunks of data. The chunks may comprise one or more data packets. The request may comprise a stream of data packets.

(99) One or more of the data packets may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device **201**, an address of the computing device **203**, an address of the privacy gateway, an address of the networking device **206**, and/or a geographic location of the user device **201**. The identifying information may comprise an address of a router, such as a router at a premises where the user device **201** is located. The data packet may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(100) The one or more data packets may comprise one or more layers of encryption. For example, a data packet may be encrypted using the public key of the computing device **203** and/or the public key of the networking device. The user device **201** may encrypt a portion of the data packet using the public key of the computing device **203**. The user device **201** may not encrypt a portion of the data packet needed to send the data packet to the networking device **206**, such as an address of the networking device **206**. The user device **201** may encrypt a portion the encrypted data packet using the public key of the networking device.

(101) The networking device **206** may receive the request. The networking device **206** may decrypt one or more data packets of the request. The networking device **206** may decrypt a data packet using a private key of the networking device **206**. A packet may comprise more than one layer of encryption. An outermost layer of encryption of the packet may comprise an encryption with the public key of the networking device **206**. The networking device may decrypt the outermost layer of the packet.

(102) Based on decrypting at least a portion of one or more data packets, the networking device may determine that the request was sent by the user device **201**, such as based on the address of the user device. Based on decrypting at least a portion of the data packets, the networking device **206** may determine that the request is associated with the computing device **203**, such as based on an address of the computing device **203**.

(103) At step **229**, the networking device **206** and the privacy concentrator **209** may perform a handshake. The handshake may be performed based on the networking device **206** receiving the request in step **228**. The handshake may comprise a TCP handshake.

(104) The handshake may comprise the networking device **206** sending one or more packets. The networking device **206** may send one or more packets to the privacy concentrator **209**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the networking device **206**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the networking device **206**. The port numbers may comprise a port number of the privacy concentrator **209**.

(105) The handshake may comprise the privacy concentrator **209** sending one or more packets. The privacy concentrator **209** may send the one or more packets to the networking device **206**. The privacy concentrator **209** may send the one or more packets based on receiving one or more packets

from the networking device **206**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the privacy concentrator **209** received the one or more packets from the networking device **206**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the privacy concentrator **209**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the networking device **206** plus one.

(106) The handshake may comprise the networking device **206** sending one or more packets. The client may send the one or more packets to the privacy concentrator **209**. The networking device **206** may send the one or more packets based on receiving the one or more packets from the privacy concentrator **209**. A packet may comprise an indication that the networking device **206** received the one or more packets from the privacy concentrator **209**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or networking device **206** port. The packet may comprise an indication of the destination and/or privacy concentrator **209** port. The packet may comprise an indication of a new sequence number associated with the networking device **206**. The new sequence number may comprise the initial sequence number associated with the networking device **206** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the privacy concentrator **209** plus one. Based on performing the handshake, a communication session may be established.

(107) At step **230**, the networking device **206** may send a request. The networking device **206** may send the request to the privacy concentrator **209**. The networking device **206** may send the request based on performing the handshake in step **229**. The networking device **206** may send the request via the communication session established in step **229**. The request may comprise an indication of the request sent by the user device **201** in step **228**. The request may comprise one or more of the data packets sent by the user device **201** in step **228**. The request may comprise one or more data packets received from the user device **201** that were decrypted or at least partially decrypted by the networking device.

(108) The request may comprise a clear-text request. The clear-text request may be unencrypted. The clear-text request may comprise a portion that is unencrypted. The clear-text request may not have a layer of encryption. The clear-text request may comprise one or more data packets with one or more layers of encryption removed, such as by the networking device **206**. The privacy concentrator **209** may receive the request.

(109) At step **231**, the privacy concentrator **209** and the computing device **203** may perform a handshake. The privacy concentrator **209** may perform the handshake based on receiving the request in step **230**. The handshake may comprise a TCP handshake.

(110) The handshake may comprise the privacy concentrator **209** sending one or more packets. The privacy concentrator **209** may send one or more packets to the computing device **203**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the privacy concentrator **209**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the privacy concentrator **209**. The port numbers may comprise a port number of the computing device **203**.

(111) The handshake may comprise the computing device **203** sending one or more packets. The computing device **203** may send the one or more packets to the privacy concentrator **209**. The computing device **203** may send the one or more packets based on receiving one or more packets from the privacy concentrator **209**. A packet may comprise a TCP packet. The packet may comprise

an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the computing device **203** received the one or more packets from the privacy concentrator **209**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the computing device **203**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the privacy concentrator **209** plus one.

(112) The handshake may comprise the privacy concentrator **209** sending one or more packets. The privacy concentrator **209** may send the one or more packets to the computing device **203**. The privacy concentrator **209** may send the one or more packets based on receiving the one or more packets from the computing device **203**. A packet may comprise an indication that the privacy concentrator **209** received the one or more packets from the computing device **203**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or the privacy concentrator **209**. The packet may comprise an indication of the destination and/or computing device **203** port. The packet may comprise an indication of a new sequence number associated with the privacy concentrator **209**. The new sequence number may comprise the initial sequence number associated with the privacy concentrator **209** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the computing device **203** plus one. Based on performing the handshake, a communication session may be established.

(113) At step **232**, the privacy concentrator **209** may send a message. The privacy concentrator **209** may send the message via the network **204**. The privacy concentrator **209** may send the message to the computing device **203**. The privacy concentrator **209** may send the message based on performing the handshake in step **231**. The privacy concentrator **209** may send the message via the communication session established in step **231**. The message may comprise an indication to initiate another handshake, such as a TLS and/or SSL handshake. The message may comprise a “Client Hello” message. The message may be sent based on performing the handshake in step **231**. The computing device **203** may receive the response.

(114) The message may comprise a packet, such as a TCP packet. The message may comprise an indication of an encryption and/or communication protocol supported by the privacy concentrator **209**. The indication of the encryption and/or communication protocol may comprise an indication of a highest version of an encryption and/or communication protocol supported by the privacy concentrator **209**, such as a highest version of TLS protocol that the privacy concentrator **209** supports. The message may comprise an indication of a random number generated by the privacy concentrator **209**. The message may comprise an indication of one or more cipher suites supported by the privacy concentrator **209**. The cipher suits may comprise one or more cryptographic algorithms, such as a server authentication algorithm, a key exchange algorithm, a bulk encryption algorithm, and/or a message integrity algorithm. The message may comprise an indication of a compression algorithm supported by the privacy concentrator **209**. The message may comprise an indication of a session identifier. The session identifier may be used to resume an existing communication session instead of performing a handshake again. The computing device **203** may receive the message.

(115) At step **233**, a handshake may be performed between the privacy concentrator **209** and the computing device **203**. The handshake may be performed based on receiving the request in step **230**. The handshake may be performed based on sending and/or receiving the message in step **232**. The handshake may be performed based on a TCP connection being opened, such as by performing the handshake in step **231**. The handshake may comprise an SSL handshake.

(116) Performing the handshake may comprise sending one or more digital certificates. For example, the privacy concentrator **209** may receive a certificate from the computing device **203**. The certificate of the computing device **203** may comprise an indication of a public key associated

with the computing device **203**.

(117) Performing the handshake may comprise the privacy concentrator **209** validating the certificate. Validating the certificate may comprise determining that the certificate is signed by a CA. Validating the certificate may comprise determining that the certification authority is known and/or trusted. For example, the privacy concentrator **209** may have access and/or have stored a list of CA's that are trusted. The privacy concentrator **209** may determine that the CA that signed the certificate is on the list.

(118) Performing the handshake may comprise the privacy concentrator **209** receiving one or more messages from the computing device **203**. The message may comprise a request for a certificate associated with the privacy concentrator **209**. The request may comprise an indication of one or more certificate authorities trusted by the computing device **203**. The request may comprise an indication of a type of the certificate. The message may comprise an indication that the computing device **203** is finished performing its steps of the handshake. For example, the message may comprise a "Server Hello Done" message.

(119) Performing the handshake may comprise the privacy concentrator **209** sending a certificate of the privacy concentrator **209** to the computing device **203**. The privacy concentrator **209** may send the certificate to the computing device **203** based on receiving the request for the certificate from the computing device **203**. The networking device **206** may send the certificate of the privacy concentrator **209** to a CA. The privacy concentrator **209** may send the certificate to a CA indicated in the request. If the certificate of the privacy concentrator **209** comprises a certificate of a certificate chain, the privacy concentrator **209** may send its public certificate and one or more other certificates in the chain to a root CA of the chain.

(120) Performing the handshake may comprise the computing device **203** validating the certificate of the privacy concentrator **209**. Validating the certificate may comprise determining that the certificate is signed by a known and/or trusted CA. The known and/or trusted CA may comprise a CA in the list sent to the privacy concentrator **209**. If the certificate is of a certificate chain, validating the certificate may comprise determining that one or more certificates in the chain and signed by a known and/or trusted CA.

(121) Performing the handshake may comprise the privacy concentrator **209** encrypting a premaster secret key. The privacy concentrator **209** may encrypt the premaster secret key based on validating the certificate of the computing device **203**. The privacy concentrator **209** may use the public key from the certificate to encrypt a premaster secret key. The premaster key may comprise a shared secret between the privacy concentrator **209** and the computing device **203**.

(122) Performing the handshake may comprise the privacy concentrator **209** sending computing device **203** a message. The message may comprise a "Client Key Exchange" message. The message may comprise the encrypted premaster secret key to the computing device **203**. The message may comprise an indication of an encryption and/or communication protocol. The encryption and/or communication protocol may be the same protocol indicated in the message sent by the privacy concentrator **209** in step **220**.

(123) Performing the handshake may comprise determining a master secret. The privacy concentrator **209** and/or the computing device **203** may determine the master secret. The master secret may be determined using the random number of the privacy concentrator **209**, the random number of the computing device **203**, and/or the premaster secret. The privacy concentrator **209** may send a message (e.g., a "Change Cipher Spec" message) to the computing device **203** indicating that subsequent messages should be protected with the exchanged keys. The privacy concentrator **209** may send the computing device **203** a message (e.g., a "Finished" message) indicating a hash of a message flow of the handshake. The hash may be encrypted using the exchanged keys.

(124) The privacy concentrator **209** may receive a message from the computing device **203**. The computing device **203** may send the message based on receiving one or more of the messages from

the privacy concentrator **209**. The message may comprise a “Change Cipher Spec” message. The message may indicate that the computing device **203** is ready to communicate using the exchanged keys. The message may comprise the hash of a message flow of the handshake. The hash may be encrypted with the exchanged keys.

(125) At step **235**, the privacy concentrator **209** may send a request. The privacy concentrator **209** may send the request to the computing device **203**. The request may comprise one or more of the data packets from the user device **201** received from the networking device **206** in step **230**. The privacy concentrator **209** may encrypt one or more of the data packets, such as using the public key of the computing device **203**. The privacy concentrator **209** may encrypt a portion of a data packet. For example, the privacy concentrator **209** may not encrypt a portion of the data packet for routing the data packet to the computing device **203**, such as an address of the computing device **203**. The computing device **203** may receive the request.

(126) At step **236**, the privacy concentrator **209** may receive a response. The response may comprise a response to the request send and/or received in step **235**. The response may be encrypted. For example, the response may be encrypted using a public key of the privacy concentrator **209**. The privacy concentrator **209** may decrypt at least a portion of the response, such as using a private key of the privacy concentrator **209**.

(127) At step **237**, the privacy concentrator **209** may send a response. The privacy concentrator **209** may send the response to the networking device **206**. The response may be sent via the communication channel established in step **229**. The response may comprise an indication of the response received in step **236**. The response may comprise a clear-text response. The clear-text response may comprise the decrypted response received from the computing device **203**. The networking device **206** may receive the response.

(128) At step **238**, the networking device **206** may send a response. The networking device **206** may send the response to the user device **201**. The response may be sent using the channel set-up by performing the handshake in step **225**. The response may comprise an indication of the response received in step **237**. The response may comprise a response from the website. The response may comprise website data, such as hypertext markup language (HTML), images, and/or other data. The networking device **206** may encrypt the response received in step **237**, such as using a public key of the user device **201**. The networking device **206** may send the encrypted response to the user device **201**. The user device **201** may receive the response.

(129) FIG. **3** shows an example method **300**. The method **300** may comprise a method of communicating with one or more devices. The channels may be used to perform secure communications, such as using the method in FIG. **4**. The method **300** may be similar to the method **200** in FIG. **2**. As compared to the method **200** in FIG. **2**, the method **300** may insert the privacy functions in the networking device system. The networking device may establish a cleartext window in the encrypted path to the website and the privacy gateway may remove identifiable information from the website.

(130) The method **300** may be performed by a system, such as the system **100** in FIG. **1** and/or the system in FIG. **2**, or any other computing device. The system may comprise a user device **301** (e.g., the user device **101** in FIG. **1** and/or the user device **201** in FIG. **2**). The system may comprise a privacy gateway (e.g., the privacy gateway **105** in FIG. **1**). The privacy gateway may comprise a networking device **306** (e.g., the networking device **106** in FIG. **1** and/or the networking device **206** in FIG. **2**). The privacy gateway may comprise a privacy concentrator **309** (e.g., the privacy concentrator **109** in FIG. **1** and/or the privacy concentrator **209** in FIG. **2**). The system may comprise a network **304** (e.g., the network **104** in FIG. **1** and/or the network **204** in FIG. **2**). The system may comprise a computing device **303** (e.g., the computing device **103** in FIG. **1** and/or the computing device **203** in FIG. **2**). The method **300** may comprise a method for the user device **301** to communicate with the computing device **303**, such as via the privacy gateway. The method **300** may comprise the privacy gateway relaying communications to and/or from the user device **301**

and to and/or from the network **304** and/or the computing device **303**. The method **300** may comprise the privacy gateway acting as a proxy for the user device **301** in communicating with the network **304** and/or the computing device **303**.

(131) At step **339**, the user device **301** and the networking device **306** may perform a handshake. The handshake may comprise a TCP handshake. The handshake may be performed based on a user of the user device **301** navigating to a website over HTTPS. The handshake may be performed based on a browser on the user device **301** generating a query for the website's origin server, such as the computing device **303**.

(132) The handshake may comprise the user device **301** sending one or more packets. The user device **301** may send one or more packets to the networking device **306**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the user device **301**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the user device **301**. The port numbers may comprise a port number of the networking device **306**. The port numbers may comprise a port number of the computing device **303**.

(133) The handshake may comprise the networking device **306** sending one or more packets. The networking device **306** may send the one or more packets to the user device **301**. The networking device **306** may send the one or more packets based on receiving one or more packets from the user device **301**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the networking device **306** received the one or more packets from the user device **301**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the networking device **306**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the user device **301** plus one.

(134) The handshake may comprise the user device **301** sending one or more packets. The client may send the one or more packets to the networking device **306**. The client may send the one or more packets based on receiving the one or more packets from the networking device **306**. A packet may comprise an indication that the user device **301** received the one or more packets from the networking device **306**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or client port. The packet may comprise an indication of the destination and/or server port. The packet may comprise an indication of a new sequence number associated with the user device **301**. The new sequence number may comprise the initial sequence number associated with the user device **301** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the networking device plus one. Based on performing the handshake, a communication session may be established.

(135) At step **340**, the user device **301** may send a message. The user device **301** may send the networking device **306** the message. The user device **301** may send the message based on performing the handshake in step **339**. The user device **301** may send the message via the communication session established in step **339**. The message may comprise an indication to initiate another handshake, such as a TLS and/or SSL handshake. The message may comprise a "Client Hello" message. The response may be sent based on performing the handshake in step **317**. The message may comprise a packet, such as a TCP packet. The message may comprise an indication of an encryption and/or communication protocol supported by the user device **301**. The indication of the encryption and/or communication protocol may comprise an indication of a highest version of

an encryption and/or communication protocol supported by the user device **301**, such as a highest version of TLS protocol that the user device supports. The message may comprise an indication of a random number generated by the user device **301**. The message may comprise an indication of one or more cipher suites supported by the user device **301**. The cipher suites may comprise one or more cryptographic algorithms, such as a server authentication algorithm, a key exchange algorithm, a bulk encryption algorithm, and/or a message integrity algorithm. The message may comprise an indication of a compression algorithm supported by the user device **301**. The message may comprise an indication of a session identifier. The session identifier may be used to resume an existing communication session instead of performing a handshake again. The networking device **306** may receive the message.

(136) At step **341**, the networking device **306** may send a message. The networking device **306** may send the message to the user device **301**. The message may comprise a “Server Hello” message. The message may be associated with initiation of a TLS and/or SSL handshake. The message may comprise a response to and/or an acknowledgement of receipt of the message sent and/or received in step **340**.

(137) At step **342**, the user device **301** and the networking device **306** may perform a handshake. The handshake may comprise a TLS and/or SSL handshake. The handshake may be performed based on the sending and/or receiving of the message from the networking device **306** in step **341**. The handshake may be performed based on the sending and/or receiving of the message from the user device **301** in step **340**.

(138) Performing the handshake may comprise sending one or more digital certificates. For example, the networking device **306** may send the user device **301** a certificate of the privacy gateway and/or the networking device **306**. The certificate of the privacy gateway and/or the networking device **306** may comprise an indication of a public key associated with the privacy gateway and/or the networking device **306**. The networking device **306** may send the user device **301** the certificate of the computing device **303** (e.g., the certificate received in method **200** in FIG. 2).

(139) Performing the handshake may comprise the user device **301** validating one or more of the certificates. Validating the certificate may comprise determining that the certificate is signed by a CA. Validating the certificate may comprise determining that the certification authority is known and/or trusted. For example, the user device **301** may have access and/or have stored a list of CA's that are trusted. The user device **301** may determine that the CA that signed the certificate is on the list.

(140) Performing the handshake may comprise the networking device **306** sending one or more messages to the user device **301**. The message may comprise a request for a certificate associated with the user device **301**. The request may comprise an indication of one or more certificate authorities trusted by the server. The request may comprise an indication of a type of the certificate. The message may comprise an indication that the networking device **306** is finished performing its steps of the handshake. For example, the message may comprise a “Server Hello Done” message.

(141) Performing the handshake may comprise the user device **301** sending a certificate of the user device **301** to the networking device **306**. The user device **301** may send the certificate to the networking device **306** based on receiving the request for the certificate from the networking device **306**. The user device **301** may send the certificate of the user device **301** to a CA. The user device **301** may send the certificate to a CA indicated in the request. If the certificate of the user device **301** comprises a certificate of a certificate chain, the user device **301** may send its public certificate and one or more other certificates in the chain to a root CA of the chain.

(142) Performing the handshake may comprise the networking device validating the certificate of the user device **301**. Validating the certificate may comprise determining that the certificate is signed by a known and/or trusted CA. The known and/or trusted CA may comprise a CA in the list sent to the networking device **306**. If the certificate is of a certificate chain, validating the

certificate may comprise determining that one or more certificates in the chain and signed by a known and/or trusted CA.

(143) Performing the handshake may comprise the user device **301** encrypting a premaster secret key. The user device **301** may encrypt the premaster secret key based on validating the certificate of the privacy gateway and/or the networking device **306**. The user device **301** may use the public key from the certificate to encrypt a premaster secret key. The premaster key may comprise a shared secret between the user device **301** and the privacy gateway and/or the networking device **306**.

(144) Performing the handshake may comprise the user device **301** sending the networking device **306** a message. The message may comprise a “Client Key Exchange” message. The message may comprise the encrypted premaster secret key. The message may comprise an indication of an encryption and/or communication protocol. The encryption and/or communication protocol may be the same protocol indicated in the message sent by the user device **301** in step **340**.

(145) Performing the handshake may comprise determining a master secret. The user device **301** and/or the networking device **306** may determine the master secret. The master secret may be determined using the random number of the user device **301**, the random number of the networking device **306**, and/or the premaster secret. The user device **301** may send a message (e.g., a “Change Cipher Spec” message) to the networking device **306** indicating that subsequent messages should be protected with the exchanged keys. The user device **301** may send the networking device a message (e.g., a “Finished” message) indicating a hash of a message flow of the handshake. The hash may be encrypted using the exchanged keys.

(146) The networking device **306** may send the user device **301** a message based on receiving one or more of the messages from the user device **301**. The message may comprise a “Change Cipher Spec” message. The message may indicate that the networking device **306** is ready to communicate using the exchanged keys. The message may comprise the hash of a message flow of the handshake. The hash may be encrypted with the exchanged keys.

(147) At step **343**, the handshake of step **342** may be finished. Based on completion of the handshake, there may be an encrypted channel (e.g., connection, communication session, etc.) between the user device **301** and the networking device **306** (e.g., between the indicated ports of the devices). Based on completion of the handshake, the user device **301** and the networking device **306** may communicate using the encrypted channel.

(148) At step **344**, the user device **301** may send a request. The request may comprise a request associated with the computing device **303**. For example, the request may comprise a request for data, a service, and/or content from the computing device **303**. The request may comprise data for the computing device **303**. The request may comprise a request to communicate with the computing device **303**.

(149) The user device **301** may send the request to the networking device **306**. The request may be sent based on performing the handshake in step **339** and/or the handshake in step **342**. The request may be sent using the channel set-up by performing the handshake in step **342**. The request may comprise one or more chunks of data. The chunks may comprise one or more data packets. The request may comprise a stream of data packets.

(150) One or more of the data packets may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device **301**, an address of the computing device **303**, an address of the privacy gateway, an address of the networking device **306**, and/or a geographic location of the user device **301**. The identifying information may comprise an address of a router, such as a router at a premises where the user device **301** is located. The data packet may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(151) The one or more data packets may comprise one or more layers of encryption. For example, a data packet may be encrypted using the public key of the computing device **303** and/or the public key of the networking device **306**. The user device **301** may encrypt a portion of the data packet

using the public key of the computing device **303**. The user device **301** may not encrypt a portion of the data packet needed to send the data packet to the networking device **306**, such as an address of the networking device **306**. The user device **301** may encrypt a portion the encrypted data packet using the public key of the networking device.

(152) The networking device **306** may receive the request. The networking device **306** may decrypt one or more data packets of the request. The networking device **306** may decrypt a data packet using a private key of the networking device **306**. A packet may comprise more than one layer of encryption. An outermost layer of encryption of the packet may comprise an encryption with the public key of the networking device **306**. The networking device may decrypt the outermost layer of the packet.

(153) Based on decrypting at least a portion of one or more data packets, the networking device may determine that the request was sent by the computing device **303**, such as based on the address of the computing device. Based on decrypting at least a portion of the data packets, the networking device **206** may determine that the request is associated with the computing device **303**, such as based on an address of the computing device **303**.

(154) At step **345**, the networking device **306** and the privacy concentrator **309** may perform a handshake. The handshake may be performed based on the networking device **306** receiving the request in step **344**. The handshake may comprise a TCP handshake.

(155) The handshake may comprise the networking device **306** sending one or more packets. The networking device **306** may send one or more packets to the privacy concentrator **309**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the networking device **306**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the networking device **306**. The port numbers may comprise a port number of the privacy concentrator **309**.

(156) The handshake may comprise the privacy concentrator **309** sending one or more packets. The privacy concentrator **309** may send the one or more packets to the networking device **306**. The privacy concentrator **309** may send the one or more packets based on receiving one or more packets from the networking device **306**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the privacy concentrator **309** received the one or more packets from the networking device **306**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the privacy concentrator **309**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the networking device **306** plus one.

(157) The handshake may comprise the networking device **306** sending one or more packets. The client may send the one or more packets to the privacy concentrator **309**. The networking device **306** may send the one or more packets based on receiving the one or more packets from the privacy concentrator **309**. A packet may comprise an indication that the networking device **306** received the one or more packets from the privacy concentrator **309**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or networking device **306** port. The packet may comprise an indication of the destination and/or privacy concentrator **309** port. The packet may comprise an indication of a new sequence number associated with the networking device **306**. The new sequence number may comprise the initial sequence number associated with the networking device **306** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the privacy concentrator **309** plus one. Based on performing the handshake, a

communication session may be established.

(158) At step **346**, the networking device **306** may send a request. The networking device **306** may send the request to the privacy concentrator **309**. The networking device **306** may send the request based on performing the handshake in step **345**. The networking device **306** may send the request via the communication session established in step **345**. The networking device **306** may send the request based on performing the handshake in step **329**. The request may comprise an indication of the request sent by the user device **301** in step **328**. The request may comprise one or more of the data packets sent by the user device **301** in step **328**. The request may comprise one or more data packets received from the user device **301** that were decrypted or at least partially decrypted by the networking device.

(159) The request may comprise a clear-text request. The clear-text request may be unencrypted. The clear-text request may comprise a portion that is unencrypted. The clear-text request may not have a layer of encryption. The clear-text request may comprise one or more data packets with one or more layers of encryption removed, such as by the networking device **306**. The privacy concentrator **309** may receive the request.

(160) At step **347**, the privacy concentrator **309** and the computing device **303** may perform a handshake. The privacy concentrator **309** may perform the handshake based on receiving the request in step **346**. The handshake may comprise a TCP handshake.

(161) The handshake may comprise the privacy concentrator **309** sending one or more packets. The privacy concentrator **309** may send one or more packets to the computing device **303**. A packet may comprise a TCP packet. The packet may comprise a SYN packet. The packet may comprise an IP packet. The packet may comprise an indication of a sequence number. The sequence number may be determined by the privacy concentrator **309**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The port numbers may comprise a source number, a client number, a destination number, and/or a server number. The port numbers may comprise a port number of the privacy concentrator **309**. The port numbers may comprise a port number of the computing device **303**.

(162) The handshake may comprise the computing device **303** sending one or more packets. The computing device **303** may send the one or more packets to the privacy concentrator **309**. The computing device **303** may send the one or more packets based on receiving one or more packets from the privacy concentrator **309**. A packet may comprise a TCP packet. The packet may comprise an IP packet. The packet may comprise a SYN ACK packet. The packet may comprise an indication that the computing device **303** received the one or more packets from the privacy concentrator **309**. The packet may comprise an indication of a sequence number. The sequence number may be determined by the computing device **303**. The sequence number may be randomly determined. The packet may comprise an indication of one or more port numbers. The packet may comprise an indication of an acknowledgement number. The acknowledgement number may comprise the sequence number associated with the privacy concentrator **309** plus one.

(163) The handshake may comprise the privacy concentrator **309** sending one or more packets. The privacy concentrator **309** may send the one or more packets to the computing device **303**. The privacy concentrator **309** may send the one or more packets based on receiving the one or more packets from the computing device **303**. A packet may comprise an indication that the privacy concentrator **309** received the one or more packets from the computing device **303**. The one or more packets may comprise an ACK packet. A packet may comprise an indication of the source and/or the privacy concentrator **309**. The packet may comprise an indication of the destination and/or computing device **303** port. The packet may comprise an indication of a new sequence number associated with the privacy concentrator **309**. The new sequence number may comprise the initial sequence number associated with the privacy concentrator **309** plus one. The packet may comprise an indication of the acknowledgement number. The acknowledgement number may comprise the sequence number associated with the computing device **303** plus one. Based on

performing the handshake, a communication session may be established.

(164) At step **348**, the privacy gateway **309** may send a message. The privacy gateway **309** may send the message via the network **304**. The privacy concentrator **309** may send the message to the computing device **303**. The privacy gateway **309** may send the message based on performing the handshake in step **347**. The privacy concentrator **309** device may send the message via the communication session established in step **347**. The message may comprise an indication to initiate another handshake, such as a TLS and/or SSL handshake. The message may comprise a “Client Hello” message. The message may be sent based on performing the handshake in step **331**. The computing device **303** may receive the response.

(165) The message may comprise a packet, such as a TCP packet. The message may comprise an indication of an encryption and/or communication protocol supported by the privacy concentrator **309**. The indication of the encryption and/or communication protocol may comprise an indication of a highest version of an encryption and/or communication protocol supported by the privacy concentrator **309**, such as a highest version of TLS protocol that the privacy concentrator **309** supports. The message may comprise an indication of a random number generated by the privacy concentrator **309**. The message may comprise an indication of one or more cipher suites supported by the privacy concentrator **309**. The cipher suits may comprise one or more cryptographic algorithms, such as a server authentication algorithm, a key exchange algorithm, a bulk encryption algorithm, and/or a message integrity algorithm. The message may comprise an indication of a compression algorithm supported by the privacy concentrator **309**. The message may comprise an indication of a session identifier. The session identifier may be used to resume an existing communication session instead of performing a handshake again. The computing device **303** may receive the message.

(166) At step **349**, a handshake may be performed between the privacy concentrator **309** and the computing device **303**. The handshake may be performed based on receiving the request in step **330**. The handshake may be performed based on sending and/or receiving the message in step **332**. The handshake may be performed based on a TCP connection being opened, such as by performing the handshake in step **331**. The handshake may comprise an SSL handshake.

(167) Performing the handshake may comprise sending one or more digital certificates. For example, the privacy concentrator **309** may receive a certificate from the computing device **303**. The certificate of the computing device **303** may comprise an indication of a public key associated with the computing device **303**.

(168) Performing the handshake may comprise the privacy concentrator **309** validating the certificate. Validating the certificate may comprise determining that the certificate is signed by a CA. Validating the certificate may comprise determining that the certification authority is known and/or trusted. For example, the privacy concentrator **309** may have access and/or have stored a list of CA's that are trusted. The privacy concentrator **309** may determine that the CA that signed the certificate is on the list.

(169) Performing the handshake may comprise the privacy concentrator **309** receiving one or more messages from the computing device **303**. The message may comprise a request for a certificate associated with the privacy concentrator **309**. The request may comprise an indication of one or more certificate authorities trusted by the computing device **303**. The request may comprise an indication of a type of the certificate. The message may comprise an indication that the computing device **303** is finished performing its steps of the handshake. For example, the message may comprise a “Server Hello Done” message.

(170) Performing the handshake may comprise the privacy concentrator **309** sending a certificate of the privacy concentrator **309** to the computing device **303**. The privacy concentrator **309** may send the certificate to the computing device **303** based on receiving the request for the certificate from the computing device **303**. The networking device **206** may send the certificate of the privacy concentrator **309** to a CA. privacy concentrator **309** may send the certificate to a CA indicated in

the request. If the certificate of the privacy concentrator **309** comprises a certificate of a certificate chain, the privacy concentrator **309** may send its public certificate and one or more other certificates in the chain to a root CA of the chain.

(171) Performing the handshake may comprise the computing device **303** validating the certificate of the privacy concentrator **309**. Validating the certificate may comprise determining that the certificate is signed by a known and/or trusted CA. The known and/or trusted CA may comprise a CA in the list sent to the privacy concentrator **309**. If the certificate is of a certificate chain, validating the certificate may comprise determining that one or more certificates in the chain and signed by a known and/or trusted CA.

(172) Performing the handshake may comprise the privacy concentrator **309** encrypting a premaster secret key. The privacy concentrator **309** may encrypt the premaster secret key based on validating the certificate of the computing device **303**. The privacy concentrator **309** may use the public key from the certificate to encrypt a premaster secret key. The premaster key may comprise a shared secret between the privacy concentrator **309** and the computing device **303**.

(173) Performing the handshake may comprise the privacy concentrator **309** sending computing device **303** a message. The message may comprise a “Client Key Exchange” message. The message may comprise the encrypted premaster secret key to the computing device **303**. The message may comprise an indication of an encryption and/or communication protocol. The encryption and/or communication protocol may be the same protocol indicated in the message sent by the privacy concentrator **309** in step **320**.

(174) Performing the handshake may comprise determining a master secret. The privacy concentrator **309** and/or the computing device **303** may determine the master secret. The master secret may be determined using the random number of the privacy concentrator **309**, the random number of the computing device **303**, and/or the premaster secret. The privacy concentrator **309** may send a message (e.g., a “Change Cipher Spec” message) to the computing device **303** indicating that subsequent messages should be protected with the exchanged keys. The privacy concentrator **309** may send the computing device **303** a message (e.g., a “Finished” message) indicating a hash of a message flow of the handshake. The hash may be encrypted using the exchanged keys.

(175) The privacy concentrator **309** may receive a message from the computing device **303**. The computing device **303** may send the message based on receiving one or more of the messages from the privacy concentrator **309**. The message may comprise a “Change Cipher Spec” message. The message may indicate that the computing device **303** is ready to communicate using the exchanged keys. The message may comprise the hash of a message flow of the handshake. The hash may be encrypted with the exchanged keys. At step **350**, the handshake may be finished.

(176) At step **351**, the privacy concentrator **309** may send a request. The privacy concentrator **309** may send the request to the computing device **303**. The request may comprise one or more of the data packets from the user device **301** received from the networking device **306** in step **330**. The privacy concentrator **309** may encrypt one or more of the data packets, such as using the public key of the computing device **303**. The privacy concentrator **309** may encrypt a portion of a data packet. For example, the privacy concentrator **309** may not encrypt a portion of the data packet for routing the data packet to the computing device **303**, such as an address of the computing device **303**. The computing device **303** may receive the request.

(177) At step **352**, the privacy concentrator **309** may receive a response. The response may comprise a response to the request send and/or received in step **351**. The response may be encrypted. For example, the response may be encrypted using a public key of the privacy concentrator **309**. The privacy concentrator **309** may decrypt at least a portion of the response, such as using a private key of the privacy concentrator **309**.

(178) At step **353**, the privacy concentrator **309** may send a response. The privacy concentrator **309** may send the response to the networking device **306**. The response may be sent via the

communication channel established in step **345**. The response may comprise an indication of the response received in step **352**. The response may comprise a clear-text response. The clear-text response may comprise the decrypted response received from the computing device **303**. The networking device **306** may receive the response.

(179) At step **354**, the networking device **306** may send a response. The networking device **306** may send the response to the user device **301**. The response may be sent using the channel set-up by performing the handshake in step **342**. The response may comprise an indication of the response received in step **353**. The networking device **206** may encrypt the response received in step **353**, such as using a public key of the user device **301**. The networking device **306** may send the encrypted response to the user device **301**. The user device **301** may receive the response.

(180) FIG. **4** shows an example method **400**. The method **400** may be performed by an element of the system **100** shown in FIG. **1** or any other computing device. The method **400** may be performed by a networking device (e.g., the networking device **106** in FIG. **1**, the networking device **206** in FIG. **2**, and/or the networking device **306** in FIG. **3**). At step **410**, an indication of a computing device may be received. The indication of the computing device may be received from a user device. The user device may comprise user device **101** in FIG. **1**, user device **201** in FIG. **2**, and/or user device **301** in FIG. **3**. The indication of the computing device may be received based on the user device navigating to a website over HTTPS. The indication of the computing device may be received based on a browser on the user device **201** generating a query for the web site's origin server, such as the computing device.

(181) The receiving the indication of the computing device may comprise performing a handshake with the user device, such as in one or more of steps **217**, **218**, **224**, **225**, **226**, and/or **228** of method **200** in FIG. **2** and/or one or more of steps **339**, **340**, **341**, **342**, **343**, and/or **344** of method **300** in FIG. **3**. The receiving the indication of the computing device may comprise receiving one or more data packets from the user device. The data packets may comprise one or more TCP packets, SYN packets, and/or IP packets.

(182) The indication of the computing device may comprise a port number of the computing device. The indication of the computing device may comprise an address associated with the computing device. The computing device may comprise the computing device **103** in FIG. **1**, the computing device **203** in FIG. **2**, and/or the computing device **303** in FIG. **3**.

(183) At step **415**, a digital certificate may be received. The digital certificate may be associated with the computing device. The digital certificate may be received based on communicating with the computing device. Communicating with the computing device may comprise sending the computing device a request for the digital certificate. Communicating with the computing device may comprise performing a handshake with the computing device, such as in one or more of steps **219**, **220**, **221**, **222**, and/or **223** of the method **200** in FIG. **2**.

(184) At step **420**, the digital certificate may be sent. The digital certificate may be sent to the user device. The digital certificate may be sent to the user device via a communication session established, such as in step **410** and/or by performing a handshake. The digital certificate may be signed by a certificate authority, such as a local certificate authority. A key, such as a public key, associated with the networking device may be sent to the user device. The public key may be signed by a certificate authority, such as a local certificate authority.

(185) At step **425**, a data packet may be received. The data packet may be received from the user device. The data packet may be received based on the digital certificate in step **420**. The data packet may be received based on the user device authenticating the digital certificate. One or more of the data packets may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device, an address of the computing device, an address of the privacy gateway, an address of the networking device, and/or a geographic location of the user device. The identifying information may comprise an address of a router, such as a router at a premises where the user device is located.

The data packet may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(186) The one or more data packets may comprise one or more layers of encryption. For example, a data packet may be encrypted using the public key of the computing device and/or the public key of the networking device. The data packet may be encrypted using the public key of the computing device, such as by the user device. A portion of the data packet needed to send the data packet to the networking device, such as an address of the networking device, may remain unencrypted.

(187) At step **430**, at least a portion of a data packet may be decrypted. The portion of the data packet may be decrypted using a private key of the networking device. A packet may comprise more than one layer of encryption. An outermost layer of encryption of the packet may comprise an encryption with the public key of the networking device. The outermost layer of the packet may be decrypted.

(188) Based on decrypting at least a portion of one or more data packets, the networking device may determine that the request was sent by the user device, such as based on the data packet comprising an indication of the user device. Based on decrypting at least a portion of the data packets, the networking device may determine that the request is associated with the computing device, such as based the data packet comprising an indication of the computing device.

(189) At step **435**, the data packet may be sent. The data packet may be sent to a privacy gateway. The privacy gateway may comprise the privacy gateway **109** in FIG. **1**, the privacy gateway in FIG. **2**, and/or the privacy gateway **309** in FIG. **3**. The data packet may be sent via a communication session established with the privacy gateway. The communication session may be established by performing a handshake. The communication session may be established using a method similar to one or more of step **229** and/or step **230** in FIG. **2** and/or steps **345** and/or step **346** in FIG. **3**.

(190) At step **440**, a response may be received. The response may be received from the privacy gateway. The response may be from the computing device. The response may be to the data packet. The response may be received based on the privacy gateway sending the data packet to the computing device. At least a portion of the response may be decrypted, such as by the privacy gateway. The response may comprise data requested by the user device. The response may comprise content, such as a web page, requested by the user device.

(191) At step **445**, at least a portion of the response may be encrypted. The portion of the response may be encrypted using a key associated with the user device, such as a public key of the user device. The portion of the response may be encrypted using a key associated with the networking device, such as a private key associated with the networking device.

(192) The portion that is encrypted may comprise a portion that is not needed to be left unencrypted for delivery of the response, such as to the user device. For example, an address on the response may be left unencrypted.

(193) At step **450**, the response may be sent to the user device. The response may be sent to the user device using a communication session established in one or more of the prior steps.

(194) FIG. **5** shows an example method **500**. The method **500** may be performed by an element of the system **100** shown in FIG. **1** or any other computing device. The method **400** may be performed by a privacy concentrator (e.g., the privacy concentrator **109** in FIG. **1**, the privacy concentrator **209** in FIG. **2**, and/or the privacy concentrator **309** in FIG. **3**).

(195) At step **510**, a data packet may be received. The data packet may be received from a networking device. The networking device may comprise the networking device **106** in FIG. **1**, the networking device **206** in FIG. **2**, and/or the networking device **306** in FIG. **3**, as examples. The data packet may be associated with a user device. The user device may comprise user device **101** in FIG. **1**, user device **201** in FIG. **2**, and/or user device **301** in FIG. **3**. For example, the networking device may receive the data packet from the user device and send the data packet to the privacy concentrator.

(196) The data packet may comprise a TCP data packet. The data packet may comprise an

indication of a computing device. The computing device may comprise the computing device **103** in FIG. 1, the computing device **203** in FIG. 2, and/or the computing device **303** in FIG. 3. The indication of the computing device may comprise an indication of an address of the computing device. The indication of the computing device may comprise an indication of a port of the computing device.

(197) The data packet may comprise a request associated with the computing device. For example, the data packet may comprise a request for data from the computing device. The data packet may comprise a request for content from the computing device.

(198) At step **515**, data associated with the user device in the data packet may be determined. The data associated with the user device may comprise one or more pieces of information. The data associated with the user device may comprise an address of the user device. The data associated with the user device may comprise an address of a router used by the user device. The data associated with the user device may comprise an indication of a geographic location of the user device. The data associated with the user device may comprise a browser running on the user device. The data associated with the user device may comprise a central processing unit (CPU) of the user device. The data associated with the user device may comprise data associated with a user of the user device. Data associated with the user may comprise an account name of the user, an employer of the user, and/or a geographic location of the user. The data associated with the user device may comprise data that is not encrypted in data packets according to a communication protocol, such as HTTPS. The data associated with the user device may be in an HTTP header of the data packet.

(199) At step **520**, the data associated with the user device may be replaced. The data may be replaced with data associated with the privacy concentrator. The data associated with the privacy concentrator may comprise an address associated with the privacy concentrator. Replacing the data associated with the user device with the data associated with the privacy concentrator may comprise generating a new data packet comprising the data associated with the privacy concentrator. Replacing the data associated with the user device with the data associated with the privacy concentrator may comprise adding the data associated with the privacy concentrator to the data packet received from the user device.

(200) At step **525**, at least a portion of the data packet may be encrypted. The portion of the data packet may be encrypted using a key associated with the computing device, such as a public key associated with the computing device. The key may be received from the networking device.

(201) At step **530**, the data packet may be sent. The data packet may be sent to the computing device. The data packet may be sent to the computing device via a communication session. The communication session may have been established prior to step **530**. The communication session may be established at step **530**. The communication session may be established by performing a handshake with the computing device.

(202) At step **535**, a response to the data packet may be received. The response may be received from the computing device. The response may be received via the communication session. The response may be received based on the sending the data packet to the computing device. At least a portion of the response may be decrypted, such as by the privacy gateway. The response may comprise content, such as a web page, requested by the user device.

(203) At step **540**, at least a portion of the response may be decrypted. The portion of the response may comprise all portions of the response that are encrypted. The portion may comprise a portion that is encrypted using a key associated with the privacy concentrator, such as a public key of the privacy concentrator. The portion of the response may be decrypted using a private key of the privacy concentrator.

(204) At step **545**, a response may be sent. For example, the response may comprise the response to the data packet and/or received from the computing device. The response may be sent to the networking device. The response may be sent to the networking device via a communication

session established prior to step **545**. The response may be sent to the networking device via a communication session established at step **545**.

(205) FIG. **6** shows an example method **600**. The method **600** may be performed by an element of the system **100** shown in FIG. **1** or any other computing device. The method **600** may be performed by a privacy gateway (e.g., the privacy gateway **105** in FIG. **1**) or any other computing device. The privacy gateway may comprise a networking device (e.g., the networking device **106** in FIG. **1**, the networking device **206** in FIG. **2**, and/or the networking device **306** in FIG. **3**). The privacy gateway may comprise a privacy concentrator (e.g., the privacy concentrator **109** in FIG. **1**, the privacy concentrator **209** in FIG. **2**, and/or the privacy concentrator **309** in FIG. **3**). The privacy gateway may comprise one device. The privacy gateway may comprise a plurality of devices.

(206) At step **610**, an indication of a computing device may be received. The indication of the computing device may be received from a user device. The user device may comprise user device **101** in FIG. **1**, user device **201** in FIG. **2**, and/or user device **301** in FIG. **3**. The indication of the computing device may be received based on the user device navigating to a website over HTTPS. The indication of the computing device may be received based on a browser on the user device **201** generating a query for the website's origin server, such as the computing device.

(207) The receiving the indication of the computing device may comprise performing a handshake with the user device, such as in one or more of steps **217**, **218**, **224**, **225**, **226**, and/or **228** of method **200** in FIG. **2** and/or one or more of steps **339**, **340**, **341**, **342**, **343**, and/or **344** of method **300** in FIG. **3**. The receiving the indication of the computing device may comprise receiving one or more data packets from the user device. The data packets may comprise one or more TCP packets, SYN packets, and/or IP packets.

(208) The indication of the computing device may comprise a port number of the computing device. The indication of the computing device may comprise an address associated with the computing device. The computing device may comprise the computing device **103** in FIG. **1**, the computing device **203** in FIG. **2**, and/or the computing device **303** in FIG. **3**.

(209) At step **615**, a digital certificate may be received. The digital certificate may be associated with the computing device. The digital certificate may be received based on communicating with the computing device. Communicating with the computing device may comprise sending the computing device a request for the digital certificate. Communicating with the computing device may comprise performing a handshake with the computing device, such as in one or more of steps **219**, **220**, **221**, **222**, and/or **223** of the method **200** in FIG. **2**.

(210) At step **620**, the digital certificate may be sent. The digital certificate may be sent to the user device. At step **420**, the digital certificate may be sent. The digital certificate may be sent to the user device. The digital certificate may be sent to the user device via a communication session established, such as in step **410** and/or by performing a handshake. The digital certificate may be signed by a certificate authority, such as a local certificate authority. A key, such as a public key, associated with the networking device may be sent to the user device. The public key may be signed by a certificate authority, such as a local certificate authority.

(211) At step **625**, a data packet may be received. The data packet may be received from the user device. The data packet may be received based on the digital certificate in step **620**. The data packet may be received based on the user device validating the digital certificate. One or more of the data packets may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device, an address of the computing device, an address of the privacy gateway, an address of the networking device, and/or a geographic location of the user device. The identifying information may comprise an address of a router, such as a router at a premises where the user device is located. The data packet may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(212) The one or more data packets may comprise one or more layers of encryption. For example, a

data packet may be encrypted using the public key of the computing device and/or the public key of the networking device. The data packet may be encrypted using the public key of the computing device, such as by the user device. A portion of the data packet needed to send the data packet to the networking device, such as an address of the networking device, may remain unencrypted. (213) At step **630**, at least a portion of a data packet may be decrypted. The portion of the data packet may be decrypted using a private key of the networking device. A packet may comprise more than one layer of encryption. An outermost layer of encryption of the packet may comprise an encryption with the public key of the networking device. The outermost layer of the packet may be decrypted.

(214) Based on decrypting at least a portion of one or more data packets, the networking device may determine that the request was sent by the user device, such as based on the data packet comprising an indication of the user device. Based on decrypting at least a portion of the data packets, the networking device may determine that the request is associated with the computing device, such as based the data packet comprising an indication of the computing device.

(215) At step **635**, data associated with the user device in the data packet may be determined. The data associated with the user device may comprise one or more pieces of information. The data associated with the user device may comprise an address of the user device. The data associated with the user device may comprise an address of a router used by the user device. The data associated with the user device may comprise an indication of a geographic location of the user device. The data associated with the user device may comprise a browser running on the user device. The data associated with the user device may comprise a central processing unit (CPU) of the user device. The data associated with the user device may comprise data associated with a user of the user device. Data associated with the user may comprise an account name of the user, an employer of the user, and/or a geographic location of the user. The data associated with the user device may comprise data that is not encrypted in data packets according to a communication protocol, such as HTTPS. The data associated with the user device may be in an HTTP header of the data packet.

(216) At step **640**, the data associated with the user device may be replaced. The data may be replaced with data associated with the privacy concentrator and/or the privacy gateway. The data associated with the privacy concentrator and/or the privacy gateway may comprise an address associated with the privacy concentrator and/or the privacy gateway. Replacing the data associated with the user device with the data associated with the privacy concentrator and/or the privacy gateway may comprise generating a new data packet comprising the data associated with the privacy concentrator and/or the privacy gateway. Replacing the data associated with the user device with the data associated with the privacy concentrator and/or the privacy gateway may comprise adding the data associated with the privacy concentrator and/or the privacy gateway to the data packet received from the user device.

(217) At step **645**, at least a portion of the data packet may be encrypted. The portion of the data packet may be encrypted using a key associated with the computing device, such as a public key associated with the computing device.

(218) At step **650**, the data packet may be sent. The data packet may be sent to the computing device. The data packet may be sent to the computing device via a communication session. The communication session may have been established prior to step **650**. The communication session may be established at step **650**. The communication session may be established by performing a handshake with the computing device.

(219) At step **655**, a response to the data packet may be received. The response may be received from the computing device. The response may be received via the communication session. The response may be received based on the sending the data packet to the computing device. At least a portion of the response may be decrypted, such as by the privacy gateway. The response may comprise content, such as a web page, requested by the user device.

(220) At step **660**, at least a portion of the response may be decrypted. The portion of the response may comprise all portions of the response that are encrypted. The portion may comprise a portion that is encrypted using a key associated with the privacy concentrator, such as a public key of the privacy concentrator. The portion of the response may be decrypted using a private key of the privacy concentrator.

(221) At step **665**, at least a portion of the response may be encrypted. The portion of the response may be encrypted using a key associated with the user device, such as a public key of the user device. The portion of the response may be encrypted using a key associated with the networking device, such as a private key associated with the networking device.

(222) The portion that is encrypted may comprise a portion that is not needed to be left unencrypted for delivery of the response, such as to the user device. For example, an address on the response may be left unencrypted.

(223) At step **670**, the response may be sent. The response may be sent to the user device. The response may be sent to the user device using a communication session established in one or more of the prior steps.

(224) FIG. 7 shows an example method **700**. The method **700** may be performed by an element of the system **100** shown in FIG. 1. The method **700** may be performed by a user device (e.g., the user device **101** in FIG. 1, the user device **201** in FIG. 2, and/or the user device **301** in FIG. 3), or any other computing device.

(225) At step **710**, an indication of a computing device may be sent. The computing device may comprise the computing device **103** in FIG. 1, the computing device **203** in FIG. 2, and/or the computing device **303** in FIG. 3. The indication of the computing device may be sent to a privacy gateway (e.g., the privacy gateway **105** in FIG. 1). The privacy gateway may comprise a networking device (e.g., the networking device **106** in FIG. 1, the networking device **206** in FIG. 2, and/or the networking device **306** in FIG. 3). The privacy gateway may comprise a privacy concentrator (e.g., the privacy concentrator **109** in FIG. 1, the privacy concentrator **209** in FIG. 2, and/or the privacy concentrator **309** in FIG. 3). The privacy gateway may comprise one device. The privacy gateway may comprise a plurality of devices.

(226) The indication of the computing device may be sent based on a user of the user device navigating to a website, such as over HTTPS. The indication of the computing device may be sent based on a browser on the user device generating a query for the website's origin server, such as the computing device.

(227) At step **715**, a digital certificate may be received. The digital certificate may be associated with the computing device. The digital certificate may be received from the privacy gateway and/or the networking device. The digital certificate may be received via a communication session with the privacy gateway and/or the networking device. The communication session may be established prior to step **715**. The communication session may be established at step **715**. The communication session may be established by performing a handshake.

(228) The digital certificate may be signed by a certificate authority, such as a local certificate authority. A key, such as a public key, associated with the networking device and/or the privacy gateway may be received. The public key may be received from the networking device and/or the privacy gateway. The public key may be signed by a certificate authority, such as a local certificate authority.

(229) At step **720**, the digital certificate may be validated. Validating the digital certificate may comprise determining that the certificate is signed by a CA. Validating the digital certificate may comprise determining that the certification authority is known and/or trusted. For example, a list of certification authorities that are trusted may be stored and/or accessible. The digital certificate may be validated based on determining that the CA that signed the certificate is on the list.

(230) Validating the digital certificate may comprise that the certificate matches a previously received digital certificate. The previously received digital certificate may be known to be

associated with a trusted device, such as by previously validating the digital certificate. The previously received digital certificate and/or an indication of the previously received digital certificate may be stored, such as to the user device.

(231) At step **725**, at least one data packet may be sent. The data packet may be sent to the privacy gateway and/or the networking device. The data packet may be sent based on validating the digital certificate in step **720**. The data packet may comprise identifying information. The identifying information may comprise an address (e.g., a MAC address, IP address, URL, port number, etc.) of the user device, an address of the computing device, an address of the privacy gateway, an address of the networking device, and/or a geographic location of the user device. The identifying information may comprise an address of a router, such as a router at a premises where the user device is located. The data packet may comprise other data, such as a time that the packet was sent, a query parameter, a header, and/or a cookie.

(232) The data packet may comprise one or more layers of encryption. For example, the data packet may be encrypted using the public key of the computing device and/or the public key of the networking device and/or the privacy gateway. The data packet may be encrypted using the public key of the computing device, such as by the user device. A portion of the data packet needed to send the data packet to the networking device, such as an address of the networking device, may remain unencrypted.

(233) At step **730**, a response may be received. The response may be received from the privacy gateway and/or the networking device. The response may be received via a communication session, such as a communication session between the user device and the privacy gateway and/or the networking device. The communication session may be established at step **730**. The communication session may be established prior to the step **730** and/or at a previous step in the method **700**.

(234) The response may comprise a response to the data packet. At least a portion of the response may be encrypted. The portion of the response may be encrypted using a key associated with the user device, such as a public key of the user device. The portion of the response may be encrypted using a key associated with the privacy gateway and/or the networking device, such as a private key associated with the privacy gateway and/or the networking device.

(235) The portion that is encrypted may comprise a portion that is not needed to be left unencrypted for delivery of the response, such as to the user device. For example, an address on the response may be left unencrypted.

(236) At step **740**, data may be output. The data may be output based on the response. The data may comprise an indication of the response. If the response comprises content, outputting the data may comprise outputting the content. The data may be output via the user device, such as via a display of the user device. The data may be output via a device in communication with the user device, such as via an external display device. The data may be output via a web browser displayed via the user device.

(237) FIG. **8** shows an example system **800**. The system **800** may comprise a computing device **801**. The computing device **801** may comprise one or more of the devices in FIG. **1**, FIG. **2**, and/or FIG. **3**. The computing device **801** may comprise a system bus **813**. The system bus **813** may comprise one or more bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. The architectures may comprise an Industry Standard Architecture (ISA) bus, a Micro Channel Architecture (MCA) bus, an Enhanced ISA (EISA) bus, a Video Electronics Standards Association (VESA) local bus, an Accelerated Graphics Port (AGP) bus, and a Peripheral Component Interconnects (PCI), a PCI-Express bus, a Personal Computer Memory Card Industry Association (PCMCIA), Universal Serial Bus (USB) and the like. The bus **813**, and all buses specified in this description may also be implemented over a wired or wireless network connection and the subsystems, including the processor **803**, a mass storage device **804**, an

operating system **805**, content playback management software **806**, content playback management data **807**, a network adapter **808**, system memory **812**, an Input/Output Interface **810**, a display adapter **809**, a display device **811**, and a human machine interface **802**, may be contained within one or more remote computing devices **814a,b,c** at physically separate locations, connected through buses of this form, in effect implementing a fully distributed system.

(238) The computing device **801** may comprise a variety of computer readable media. Exemplary readable media may be any available media that is accessible by the computing device **801** and comprises, for example and not meant to be limiting, both volatile and non-volatile media, removable and non-removable media. The system memory **812** comprises computer readable media in the form of volatile memory, such as random access memory (RAM), and/or non-volatile memory, such as read only memory (ROM). The system memory **812** may store data such as content playback management data **807** and/or program modules such as operating system **805** and content playback management software **806** that are immediately accessible to and/or are presently operated on by the processing unit **803**.

(239) The computing device **801** may comprise other removable/non-removable, volatile/non-volatile computer storage media. FIG. **8** shows a mass storage device **804** which may provide non-volatile storage of computer code, computer readable instructions, data structures, program modules, and other data for the computing device **801**. For example and not meant to be limiting, a mass storage device **804** may be a hard disk, a removable magnetic disk, a removable optical disk, magnetic cassettes or other magnetic storage devices, flash memory cards, CD-ROM, digital versatile disks (DVD) or other optical storage, random access memories (RAM), read only memories (ROM), electrically erasable programmable read-only memory (EEPROM), and the like.

(240) Optionally, any number of program modules may be stored on the mass storage device **804**, including for example, an operating system **805** and content playback management software **806**. The operating system **805** and content playback management software **806** (or some combination thereof) may comprise elements of the programming and the content playback management software **806**. Content playback management data **807** may also be stored on the mass storage device **804**. Content playback management data **807** may be stored in any of one or more databases known in the art. Examples of such databases comprise, DB2®, Microsoft® Access, Microsoft® SQL Server, Oracle®, mySQL, PostgreSQL, and the like. The databases may be centralized or distributed across multiple systems.

(241) The user may enter commands and information into the computing device **801** via an input device (not shown). Examples of such input devices comprise, but are not limited to, a keyboard, a pointing device (e.g., a “mouse”), a microphone, a joystick, a scanner, tactile input devices such as gloves, and other body coverings, and the like. These and other input devices may be connected to the processing unit **803** via a human machine interface **802** that is coupled to the system bus **813**, but may be connected by other interface and bus structures, such as a parallel port, game port, an IEEE 1394 Port (also known as a Firewire port), a serial port, or a universal serial bus (USB).

(242) A display device **811** may also be connected to the system bus **813** via an interface, such as a display adapter **809**. It is contemplated that the computing device **801** may have more than one display adapter **809** and the computing device **801** may have more than one display device **811**. For example, a display device may be a monitor, an LCD (Liquid Crystal Display), or a projector. In addition to the display device **811**, other output peripheral devices may comprise components such as speakers (not shown) and a printer (not shown) which may be connected to the computing device **801** via Input/Output Interface **810**. Any step and/or result of the methods may be output in any form to an output device. Such output may be any form of visual representation, including, but not limited to, textual, graphical, animation, audio, tactile, and the like. The display **811** and computing device **801** may be part of one device, or separate devices.

(243) The computing device **801** may operate in a networked environment using logical connections to one or more remote computing devices **814a,b,c**. The remote computing devices

814a,b,c, may comprise one or more of the devices from FIG. 1, FIG. 2, and/or FIG. 3. A remote computing device may be a personal computer, portable computer, a smart phone, a server, a router, a network computer, a peer device or other common network node, and so on. Logical connections between the computing device **801** and a remote computing device **814a,b,c** may be made via a network **815**, such as a local area network (LAN) and a general wide area network (WAN). Such network connections may be through a network adapter **808**. A network adapter **808** may be implemented in both wired and wireless environments. Such networking environments are conventional and commonplace in dwellings, offices, enterprise-wide computer networks, intranets, and the Internet.

(244) Application programs and other executable program components such as the operating system **805** are shown herein as discrete blocks, although it is recognized that such programs and components reside at various times in different storage components of the computing device **801**, and are executed by the data processor(s) of the computer. An implementation of content playback management software **806** may be stored on or sent across some form of computer readable media. Any of the disclosed methods may be performed by computer readable instructions embodied on computer readable media or any other computing device. Computer readable media may be any available media that may be accessed by a computer. For example and not meant to be limiting, computer readable media may comprise “computer storage media” and “communications media.” “Computer storage media” comprise volatile and non-volatile, removable and non-removable media implemented in any methods or technology for storage of information such as computer readable instructions, data structures, program modules, or other data. Exemplary computer storage media comprises, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by a computer.

Claims

1. A method comprising: receiving, by a first computing device and from a user device, one or more data packets; and sending, to a second computing device and based on the one or more data packets, one or more updated data packets, wherein at least one updated data packet of the one or more updated data packets comprises data, associated with the first computing device, that replaces identifying information associated with the user device.
2. The method of claim 1, wherein the identifying information associated with the user device comprises at least one of: an address of the user device, a location of the user device, or a location of the first computing device.
3. The method of claim 2, wherein the address of the user device comprises at least one of: MAC address, an IP address, a URL, or port number.
4. The method of claim 1, wherein the first computing device comprises at least one of: a networking device, a server, a network appliance, a firewall appliance, or a networking component.
5. The method of claim 1, wherein the user device is of a plurality of user devices, and wherein the first computing device communicates with the plurality of user devices located at a plurality of premises.
6. The method of claim 1, wherein the second computing device comprises a server hosting at least one of: a database, a website, a certificate authority server, content, or a service.
7. The method of claim 1, wherein the second computing device is located external to a premises associated with the user device.
8. A device comprising: one or more processors; and instructions that, when executed by the one or more processors, cause the first computing device to: receive, from a user device, one or more data packets; and send, to a computing device and based on the one or more data packets, one or more

updated data packets, wherein at least one updated data packet of the one or more updated data packets comprises data, associated with the device, that replaces identifying information associated with the user device.

9. The device of claim 8, wherein the identifying information associated with the user device comprises at least one of: an address of the user device, a location of the user device, or a location of the device.

10. The device of claim 9, wherein the address of the user device comprises at least one of: MAC address, an IP address, a URL, or port number.

11. The device of claim 8, wherein the device comprises at least one of: a networking device, a server, a network appliance, a firewall appliance, or a networking component.

12. The device of claim 8, wherein the user device is of a plurality of user devices, and wherein the device communicates with the plurality of user devices located at a plurality of premises.

13. The device of claim 8, wherein the computing device comprises a server hosting at least one of: a database, a website, a certificate authority server, content, or a service.

14. The device of claim 8, wherein the computing device is located external to a premises associated with the user device.

15. A non-transitory computer-readable medium storing instructions that, when executed, cause: receiving, by a first computing device and from a user device, one or more data packets; and sending, to a second computing device and based on the one or more data packets, one or more updated data packets, wherein at least one updated data packet of the one or more updated data packets comprises data, associated with the first computing device, that replaces identifying information associated with the user device.

16. The non-transitory computer-readable medium of claim 15, wherein the identifying information associated with the user device comprises at least one of: an address of the user device, a location of the user device, or a location of the first computing device.

17. The non-transitory computer-readable medium of claim 16, wherein the address of the user device comprises at least one of: MAC address, an IP address, a URL, or port number.

18. The non-transitory computer-readable medium of claim 15, wherein the first computing device comprises at least one of: a networking device, a server, a network appliance, a firewall appliance, or a networking component.

19. The non-transitory computer-readable medium of claim 15, wherein the second computing device comprises a server hosting at least one of: a database, a website, a certificate authority server, content, or a service.

20. The non-transitory computer-readable medium of claim 15, wherein the second computing device is located external to a premises associated with the user device.
