

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12414165

Kind Code

B1

Date of Patent

September 09, 2025

Inventor(s)

Singh; Maheshwar et al.

Formulation and enforcement of a connectivity policy in a wireless network environment

Abstract

The formulation and execution of a connectivity policy is disclosed herein to improve the performance of a wireless network (WN). A wireless access point (WAP) within the WN identifies electronic devices that have been granted access to the WN and/or are associated with the WAP to provide a connectivity catalog that forms the basis of the connectivity policy. This connectivity catalog is communicated to other WAPs within the network. In some situations, these other WAPs can execute the connectivity policy to deny access to electronic devices within the connectivity catalog to their corresponding networks. For example, these other WAPs can execute the connectivity policy on those electronic devices that are within a prescribed connectivity distance from the WAP that provided the connectivity catalog.

Inventors: Singh; Maheshwar (Roslyn Heights, NY), Patel; Jiten (Wantagh, NY), Hess; Paul (Rocky Point, NY)

Applicant: CSC Holdings, LLC (Bethpage, NY)

Family ID: 83007905

Assignee: CSC Holdings, LLC (Bethpage, NY)

Appl. No.: 17/878239

Filed: August 01, 2022

Related U.S. Application Data

continuation parent-doc US 16731469 20191231 US 11432345 child-doc US 17878239

Publication Classification

Int. Cl.: H04W76/10 (20180101); H04W4/02 (20180101)

U.S. Cl.:

CPC **H04W76/10** (20180201); **H04W4/023** (20130101);

Field of Classification Search

CPC: H04W (4/023); H04W (76/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6208631	12/2000	Kim	N/A	N/A
9775037	12/2016	Huber et al.	N/A	N/A
9930670	12/2017	Yi et al.	N/A	N/A
10172047	12/2018	Zhang	N/A	H04W 36/0061
2009/0325566	12/2008	Bell	455/419	H04W 8/22
2010/0330957	12/2009	Harada	455/406	H04M 15/51
2011/0130138	12/2010	Lee et al.	N/A	N/A
2013/0155851	12/2012	Koodli et al.	N/A	N/A
2014/0185469	12/2013	Marmolejo-Meillon et al.	N/A	N/A
2015/0341834	12/2014	Lee	370/332	H04L 5/1438
2016/0226705	12/2015	Toner	N/A	H04L 67/55
2016/0292799	12/2015	DeRosia et al.	N/A	N/A
2017/0078956	12/2016	LeBlanc	N/A	N/A
2017/0272317	12/2016	Singla et al.	N/A	N/A
2017/0347388	12/2016	Cai et al.	N/A	N/A
2018/0137078	12/2017	Kohtz et al.	N/A	N/A
2019/0075469	12/2018	Mahonet et al.	N/A	N/A
2019/0174426	12/2018	Lee	N/A	N/A
2019/0303807	12/2018	Gueye	N/A	N/A
2019/0320385	12/2018	Bhartia	N/A	H04W 76/10
2021/0112487	12/2020	Sasabe	N/A	H04W 48/16

Primary Examiner: Phuong; Dai

Attorney, Agent or Firm: Lowenstein Sandler LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/731,469, filed Dec. 31, 2019, now U.S. Pat. No. 11,432,345, which is incorporated herein by reference herein in its entirety.

BACKGROUND

(1) A service provider of a service provider system provides a service, such as communication of video, audio, and/or data to provide some examples, to one or more subscriber devices of the

service. The conventional point-to-multipoint communication system often includes multiple access points through which the one or more subscriber devices can access the service.

Description

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

- (1) The present disclosure is described with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements. Additionally, the left most digit(s) of a reference number identifies the drawing in which the reference number first appears. In the accompanying drawings:
- (2) FIG. 1 graphically illustrates a wireless network (WN) according to an exemplary embodiment of the present disclosure;
- (3) FIG. 2A graphically illustrates an exemplary underlying wireless network within the exemplary WN according to an exemplary embodiment of the present disclosure;
- (4) FIG. 2B illustrates a flowchart of an exemplary operation of the exemplary WN to formulate the connectivity policy according to an exemplary embodiment of the present disclosure;
- (5) FIG. 3 graphically illustrates a first exemplary execution of the exemplary connectivity policy according to an exemplary embodiment of the present disclosure;
- (6) FIG. 4A through FIG. 4D graphically illustrates a second exemplary execution of the exemplary connectivity policy according to exemplary embodiments of the present disclosure;
- (7) FIG. 5 illustrates a first flowchart of an exemplary operation of the exemplary WN to execute the connectivity policy according to an exemplary embodiment of the present disclosure;
- (8) FIG. 6 illustrates a second flowchart of an exemplary operation of the exemplary WN to execute the connectivity policy according to an exemplary embodiment of the present disclosure; and
- (9) FIG. 7 graphically illustrates a simplified block diagram of a computer system suitable for use with embodiments described herein, as well as circuit design and circuit embodiments of the technology, according to an exemplary embodiment of the present disclosure.
- (10) The present disclosure will now be described with reference to the accompanying drawings.

DETAILED DESCRIPTION OF THE DISCLOSURE

(11) Overview

(12) The formulation and execution of a connectivity policy is disclosed herein to improve the performance of a wireless network (WN). A wireless access point (WAP) within the WN identifies electronic devices that have been granted access to the WN and/or are associated with the WAP to provide a connectivity catalog that forms the basis of the connectivity policy. This connectivity catalog is communicated to other WAPs within the network. In some situations, these other WAPs can execute the connectivity policy to deny access to electronic devices within the connectivity catalog to their corresponding networks. For example, these other WAPs can execute the connectivity policy on those electronic devices that are within a prescribed connectivity distance from the WAP that provided the connectivity catalog.

(13) Exemplary Wireless Networks

(14) FIG. 1 graphically illustrates a wireless network (WN) according to an exemplary embodiment of the present disclosure. A WN **100** provides wireless communication between an electronic device **102** and wireless access points (WAPs) **104.1** through **104.n** within geographical coverage areas **106.1** through **106.n**. The electronic device **102** can represent a mobile telephony device, such as a mobile phone, a mobile computing device, a mobile internet device, such as a tablet computer and/or a laptop computer, a video game console, a portable media player, a peripheral device, such as mouse, keyboard, monitor, printer and scanner, an internet capable appliance and/or any other suitable communication device that is capable of wireless communication within the WN **100**.

Moreover, as illustrated in FIG. 1, the geographical coverage areas **106.1** through **106.n** can represent relatively small areas, such as within a person's reach, to form a one or more wireless personal area networks (WPANs), short distances within structures, such as homes, schools, computer laboratory, or office buildings, to form one or more wireless local area networks (WLANs), one or more large areas, such as between neighboring towns and cities or a city and suburb, to form one or more wireless wide area network (WWANs), and/or any combination of WPANs, WLANs, and/or WWANs that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure.

(15) As illustrated in FIG. 1, the WAPs **104.1** through **104.n** represent gateways between the electronic device **102** and a service provider system **108**. The electronic device **102** utilizes its corresponding WAP from among the WAPs **104.1** through **104.n** to communicate with the service provider system **108**. In the exemplary embodiment illustrated in FIG. 1, the WAPs **104.1** through **104.n** can include one or more private WAPs and/or one or more public WAPs. The private WAPs represent wireless access points commonly used in residential, office, and enterprise environments to which access is restricted, namely private, through the use of various security measures, such as authentication and/or authorization to provide some examples. The public WAPs represent wireless access points without any such access restrictions wherein anyone, namely the general public, is granted access.

(16) The service provider system **108** represents one or more centralized computing networks to provide a service, such bi-directional communication of information, for example, video, audio, and/or data, to the electronic device **102**. For example, the service provider system **108** can provide the electronic device **102** with connectivity to other networks, such as the public Internet to provide an example. As another example, the service provider system **108** can provide media, such as movies, television programs, and/or advertising, to the electronic device **102**. As used herein, the term “downstream direction” refers to the transfer of information from the service provider system **108** to the electronic device **102**. The term “upstream direction” refers to the transfer of information from the electronic device **102** to the service provider system **108**. In the exemplary embodiment illustrated in FIG. 1, the electronic device **102** can also be referred to as a subscriber device. However, the teachings described herein can be readily applied to any point-to-multipoint communication system that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure.

(17) In some situations, the geographical coverage areas **106.1** through **106.n** can overlap each other allowing the electronic device **102** to communicate with multiple WAPs from among the WAPs **104.1** through **104.n**. For example, one or more geographical coverage areas from among the geographical coverage areas **106.1** through **106.n** can overlap one or more other geographical coverage areas from among the geographical coverage areas **106.1** through **106.n**. As a result, the electronic device **102** can communicate with the service provider system **108** through multiple corresponding WAPs from among the WAPs **104.1** through **104.n**. As to be described in further detail below, the WN **100** can implement a connectivity policy to cause the WAPs **104.1** through **104.n** to selectively allow and/or to selectively deny access to the electronic device **102** to their corresponding networks. For example, the geographical coverage area **106.1** of the WAP **104.1** can overlap at least some of the geographical coverage area **106.2** of the WAP **104.2**. In this example, the WAP **104.1** and the WAP **104.2** can be situated within the same residential, office, and enterprise environments with the WAP **104.1** being a private WAP and the WAP **104.2** being a public WAP. In this example, the connectivity policy, when implemented by the WN **100**, can cause the WAP **104.1** to allow the electronic device **102** access to its corresponding network and the WAP **104.2** to deny the electronic device **102** access to its corresponding network.

(18) Generally, the service provider system **108** selectively monitors one or more parameters, characteristics, and/or attributes of a WAP, for example, the WAP **104.1**, within the WN **100** and/or of the electronic device **102** and thereafter intelligently executes the connectivity policy in response

to the one or more parameters, characteristics, and/or attributes. In an exemplary embodiment, the service provider system **108** monitors a distance between the WAP and the electronic device **102**. For example, the service provider system **108** can identify first latitude and first longitude coordinates for the WAP. Then, in this example, the service provider system **108** can identify second latitude and second longitude coordinates for a WAP within the WN **100** that the electronic device **102** is presently associated with. Finally, the service provider system **108** can determine the approximate distance, expressed in feet (ft), between the WAP and the electronic device **102** by using the Haversine formula:

$$(19) = 2r \arcsin(\sqrt{\sin^2(\frac{\phi_{\text{sub.1}} - \phi_{\text{sub.2}}}{2}) + \cos(\phi_{\text{sub.1}}) \cos(\phi_{\text{sub.2}}) \sin^2(\frac{\lambda_{\text{sub.1}} - \lambda_{\text{sub.2}}}{2})})$$

where r represents an approximation of the radius of the Earth expressed in feet, for example, 20,914,080 feet, $\phi_{\text{sub.1}}$ and $\phi_{\text{sub.2}}$ represent the first latitude and the second latitude, respectively, as described above, and $\lambda_{\text{sub.1}}$ and $\lambda_{\text{sub.2}}$ represent the first longitude and the second longitude, respectively, as described above. In this exemplary embodiment, the service provider system **108** executes the connectivity policy when the electronic device **102** is within a prescribed connectivity distance from the WAP. This prescribed connectivity distance can be a predetermined-fixed distance, for example, one hundred (100) feet, and can be different for varying population densities. Alternatively, or in addition to, the prescribed connectivity distance can be based on one or more parameters, characteristics, and/or attributes of the WAP and/or the electronic device **102**. The one or more parameters, characteristics, and/or attributes can include a speed of the downstream direction, a speed of the upstream direction, a transmission power of the WAP and/or the electronic device **102**, a received signal strength of the WAP and/or the electronic device **102**, and/or an error rate of the downstream direction and/or the upstream direction to provide some examples. As described in further detail below, the WN **100**, when executing the connectivity policy, causes the WAP to selectively allow the electronic device **102** access to its corresponding network and public WAPs within connectivity range of the electronic device **102**, for example, one or more of the WAPs **104.2** through **104.n**, to selectively deny the electronic device **102** access to their corresponding networks.

Formulation of an Exemplary Connectivity Policy

(20) FIG. 2A graphically illustrates an exemplary underlying wireless network within the exemplary WN according to an exemplary embodiment of the present disclosure. In the exemplary embodiment illustrated in FIG. 2A, a wireless network (WN) **200** includes a wireless access point (WAP) **202**. The WAP **202** can represent an exemplary embodiment of one or more of the WAPs **104.1** through **104.n**. In an exemplary embodiment, the WAP **202** represents a private wireless access point as described above. In this exemplary embodiment, this WAP can be communicatively coupled to various electronic devices to form a private wireless network. Generally, the private network represents a wireless network of wirelessly capable electronic devices to which access to this wireless network is restricted, namely private, through the use of various security measures, such as authentication and/or authorization to provide some examples. In an exemplary embodiment, this private network can be situated within residential, office, and/or enterprise environments. In contrast, a public network represents a wireless network of wirelessly capable electronic devices without any such access restrictions allowing anyone, namely the general public, access. Although, the discussion of the WN **200** to follow describes various electronic devices that can be within the WN **200**, these electronic devices are for exemplary purposes only and not limiting. Those skilled in the relevant art(s) will recognize other suitable electronic devices having wireless communication capabilities can also be situated within the WN **200** without departing from the spirit and scope of the present disclosure.

(21) In the exemplary embodiment illustrated in FIG. 2A, the WAP **202** represents a wireless capable communication device that manages communications within the WN **200**. In some situations, the WAP **202** can also manage communications between the WN **200** and other wireless

networks, wired networks, and/or other electronic devices, such as the service provider system **108** as described above in FIG. **1**. In these situations, the WAP **202** effectively operates as a gateway between the WN **200** and these other wireless networks, wired networks, and/or other electronic devices. As illustrated in FIG. **2A**, the WN **200** can include, but is not limited to, one or more wireless media devices **204**, one or more wireless automation devices **206**, one or more wireless appliance devices **208**, and/or one or more mobile communication devices **210**. As noted above, these various devices are merely representative of the electronic devices that can be included within the WN **200** and are not limiting. Those skilled in the relevant art(s) will recognize the WN **200** can include any suitable electronic devices having wireless communication capabilities without departing from the spirit and scope of the present disclosure.

(22) The one or more wireless media devices **204**, as illustrated in FIG. **2A**, represent suitable wirelessly capable electronic devices that provide electronic media for consumption. In the exemplary embodiment illustrated in FIG. **2A**, the one or more wireless media devices **204** can include one or more media display devices, such as a television **212**, one or more media access devices, such as a set-top box **214**, and/or one or more entertainment devices, such as a video gaming console **216**. Generally, the one or more wireless automation devices **206** and the one or more wireless appliance devices **208** represent electronic devices that are embedded with electronics, software, sensors, actuators, and network connectivity which enable these devices to communicate, also referred to as the Internet of Things (IoT). In the exemplary embodiment illustrated in FIG. **2A**, the one or more wireless automation devices **206** can include one or more environmental control devices, such as a wirelessly capable electronic thermostat **218**, one or more wireless security devices, such as a wireless capable video doorbell **220**, and/or one or more wirelessly capable control devices, such as a wirelessly capable virtual assistant electronic device **222**. In the exemplary embodiment illustrated in FIG. **2A**, the one or more wireless appliance devices **208** can include one or more wirelessly capable appliances, such as a wireless capable refrigerator **226** and/or a wireless capable coffee maker **226**. The one or more mobile communication devices **210** represent suitable wirelessly capable electronic devices to provide wireless audio, video, and/or data communication. In the exemplary embodiment illustrated in FIG. **2A**, the one or more mobile communication devices **210** can include one or more mobile telephony devices, such as a mobile smartphone **228**, one or more mobile computing devices, such as a tablet computer **230**, and/or one or more mobile internet devices, such as a laptop computer **232**.

(23) In the exemplary embodiment illustrated in FIG. **2A**, the WAP **202** stores a connectivity catalog **234** which specifies those wirelessly capable electronic devices, such as the one or more wireless media devices **204**, the one or more wireless automation devices **206**, the one or more wireless appliance devices **208**, and/or the one or more mobile communication devices **210**, that have been granted access to the WN **200** and/or are associated with the WAP **202**. As to be described in further detail below, the connectivity catalog **234** is to form the basis of the connectivity policy. In an exemplary embodiment, each of these wirelessly capable electronic devices undergoes authentication procedure, for example, comparison of usernames and/or passwords, and/or an authorization procedure with the WAP **202** before being granted access to the WN **200**. In this exemplary embodiment, once each of these wirelessly capable electronic devices has completed the authentication procedure and/or the authorization procedure, each of these wirelessly capable electronic devices becomes associated with the WAP **202** and is granted access to the WN **200**. Thereafter, one or more unique identifiers ID.sub.1 through ID.sub.N which uniquely identify those wirelessly capable electronic devices that are granted access to the WN **200** and/or are associated with the WAP **202** are stored in the connectivity catalog **234**. In the exemplary embodiment illustrated in FIG. **2A**, the one or more unique identifiers ID.sub.1 through ID.sub.N can include one or more Internet Protocol (IP) addresses, one or more media access controller (MAC) address, and/or one or more other suitable unique identifiers that will be recognized by those skilled in the relevant art(s) without departing from the spirit and scope of the

present disclosure. For example, as illustrated in FIG. 2A, the unique identifier ID.sub.1 shown in the connectivity catalog **234** can represent a unique identifier for the television **212** indicating that the television **212** has been granted access to the WN **200** and/or is associated with the WAP **202**. (24) FIG. 2B illustrates a flowchart of an exemplary operation of the exemplary WN to formulate the connectivity policy according to an exemplary embodiment of the present disclosure. The disclosure is not limited to this operational description. Rather, it will be apparent to ordinary persons skilled in the relevant art(s) that other operational control flows are within the scope and spirit of the present disclosure. The following discussion describes an exemplary operational control flow **250** to formulate the connectivity policy as described above. The operational control flow **250** to be described in further detail below can be executed by a service provider system, such as the service provider system **108** as described above, to formulate the connectivity policy as described above.

(25) At operation **252**, the operational control flow **250** identifies a wireless access point (WAP), such as the WAP **104.1** as described above in FIG. 1 and/or the WAP **202** as described above in FIG. 2A, within a wireless network (WN), such as the WN **100** as described above in FIG. 1 and/or the WN **200** as described above in FIG. 2A, that is associated with an electronic device, such as the electronic device **102** as described above in FIG. 1 and/or any of the electronic devices as described above in FIG. 2A. In an exemplary embodiment, the electronic device represents a subscriber device that has entered into a service agreement with a service provider to provide a service to a residential, office, or enterprise environment. In this exemplary embodiment, the WAP represents a private WAP as described above.

(26) At operation **254**, the operational control flow **250** identifies one or more other devices, for example, as described above in FIG. 2A, that are associated with the WAP from operation **252**. These other devices are often communicatively coupled to the WAP from operation **252** to form a private network as described above and can include one or more wireless media devices, one or more wireless automation devices, one or more wireless appliance devices, and/or one or more mobile communication devices as described above in FIG. 2A.

(27) At operation **256**, the operational control flow **250** updates a connectivity catalog, such as the connectivity catalog **234** as described above in FIG. 2A, to include the electronic device from operation **252** and the one or more other electronic devices from operation **254**. The connectivity catalog is updated to include one or more unique identifiers which uniquely identify the electronic device from operation **252** and the one or more other electronic devices from operation **254**. In the exemplary embodiment illustrated in FIG. 2B, the one or more unique identifiers can include one or more Internet Protocol (IP) addresses, one or more media access controller (MAC) address, and/or one or more other suitable unique identifiers that will be recognized by those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure.

(28) At operation **258**, the operational control flow **250** sends the connectivity catalog from operation **256** to one or more other WAPs, such as one or more of the WAPs **104.2** through WAP **104.n** as described above in FIG. 1, within the WN to formulate the connectivity policy. In an exemplary embodiment, the one or more other WAPs represent public WAPs as described above.

(29) Execution of the Exemplary Connectivity Policy

(30) Referring back to FIG. 2A, the WAP **202** communicates the connectivity catalog **234** to neighboring WAPs within the WN **100** to restrict access of the wirelessly capable electronic devices included within the connectivity catalog **234** to the WAP **202**. The wirelessly capable electronic devices included within the connectivity catalog **234** are denied access to corresponding networks of the neighboring WAPs within the WN **100**. For example, assuming the WAP **202** is an exemplary embodiment of the WAP **104.1** as described in FIG. 1 and the electronic device **102** as described in FIG. 1 is included within the connectivity catalog **234**, the WAP **104.1** communicates the connectivity catalog **234** to one or more of the WAPs **104.2** through WAP **104.n**. In this example, those WAPs having the electronic device **102** within their connectivity catalog **234** deny

access to the electronic device **102** to their corresponding networks. To these neighboring WAPs, the connectivity catalog **234** represents an access control mechanism, also referred to as a “Blacklist,” which causes these neighboring WAPs to grant access to all wirelessly capable electronic devices to their corresponding networks except to the wirelessly capable electronic devices included within the connectivity catalog **234**.

(31) FIG. **3** graphically illustrates a first exemplary execution of the exemplary connectivity policy according to an exemplary embodiment of the present disclosure. As illustrated in FIG. **3**, an exemplary wireless network (WN) **300** provides wireless communication between electronic devices **302.1** through **302.3** and wireless access points (WAPs) **304.1** through **304.3**. In an exemplary embodiment, the WAP **304.1** represents a private wireless access point as described above and/or the WAP **304.2** and **304.3** represent public WAPs as described above. Those skilled in the relevant art(s) will recognize the WN **300** can include WAPs than as illustrated in FIG. **3** without departing from the spirit and scope of the present disclosure. However, to ease explanation, geographical coverage areas of the private WAP **302** and/or public WAPs **304.1** through **304.3** are not illustrated in FIG. **3**. In the exemplary embodiment illustrated in FIG. **3**, the geographical coverage areas of the WAPs **304.1** through **304.3** overlap each other such that the electronic devices **302.1** through **302.3** can communicate with any combination or combinations of the WAPs **304.1** through **304.3**. The WN **300** can represent an exemplary embodiment of the WN **100** as described above in FIG. **1**. As such, the electronic devices **302.1** through **302.3** can each represent an exemplary embodiment of the electronic device **102** as described above in FIG. **1**.

(32) As illustrated in FIG. **3**, the WAPs **304.1** and **304.2** are situated within a residential, office, or enterprise environment **306.1**, the WAP **304.3** is situated within a residential, office, or enterprise environment **306.2**, and the WAP **304.4** is situated outside of these residential, office, or enterprise environments. In an exemplary embodiment, a user or users of the electronic devices **302.1** through **302.3** enter into a service agreement with a service provider to provide a service to the residential, office, or enterprise environment **306.1**. The service agreement often defines a quality of service (QOS), for example, a speed of the downstream direction or a speed of the upstream direction, between the WAP **304.1** when within the residential, office, or enterprise environment **306.1** and a service provider system of the service provider, such as the service provider system **108** to provide an example. The WAP **304.1** provides a connectivity catalog, such as the connectivity catalog **234** to provide an example, to the WAPs **304.2** through **304.4** that includes the electronic devices **302.1** through **302.3** in a substantially similar manner as described above in FIG. **2A**. The WAPs **304.2** through **304.4** utilize the connectivity catalog to form a connectivity policy to determine whether to restrict and/or to grant access of the electronic devices **302.1** through **302.3** to their corresponding networks.

(33) In the exemplary embodiment illustrated in FIG. **1**, the electronic devices **302.1** through **302.3** send connectivity requests to establish communication with one or more of the WAPs **304.1** through **304.3**. Thereafter, the electronic devices **302.1** through **302.3** and the one or more of the WAPs **304.1** through **304.3** undergo a handshaking procedure to establish the communication. As part of this handshaking procedure, the one or more of the WAPs **304.1** through **304.3** determine whether to enforce the connectivity policy. As part of this determination, the one or more of the WAPs **304.1** through **304.3** search the connectivity catalog for the electronic devices **302.1** through **302.3** before the communication is established. The one or more of the WAPs **304.1** through **304.3** refuse communication from a corresponding electronic device from among the electronic devices **302.1** through **302.3** when the corresponding electronic device is located within the connectivity catalog. As such, these WAPs thereafter deny access to the corresponding electronic device to their corresponding networks. Otherwise, one or more of the WAPs **304.1** through **304.3** accept communication from the corresponding electronic device from among the electronic devices **302.1** through **302.3** when the corresponding electronic device is not located within the connectivity catalog. As such, these WAPs thereafter become associated with the corresponding electronic

device and/or grant access to the corresponding electronic device to their corresponding networks. (34) As illustrated in FIG. 3, the electronic device **306.1** is situated within the residential, office, or enterprise environment **306.1**, the electronic device **306.2** is situated within the neighboring residential, office, or enterprise environment **310**, and the electronic device **306.3** is outside of the residential, office, or enterprise environment **306.1** and the neighboring residential, office, or enterprise environment **310**. In the exemplary embodiment illustrated in FIG. 3, the WAP **304.1** grants access to the electronic devices **302.1** through **302.3** to its corresponding network as indicated by “YES” in FIG. 3. In contrast, the connectivity policy, when enforced by the WAPs **304.2** through **304.4**, causes the WAPs **304.2** through **304.4** to deny access to the electronic devices **302.1** through **302.3** to their corresponding networks as indicated by “NO” in FIG. 3 since the electronic devices **302.1** through **302.3** are included within the connectivity catalog stored by the WAPs **304.2** through **304.4**. Even though the electronic device **306.2** and the electronic device **306.3** are closer in geographical location to the WAP **304.3** and the WAP **304.4**, respectively, these WAPs deny access to the electronic device **306.2** and the electronic device **306.3** to their corresponding networks when the connectivity policy is enforced on the WN **300**.

(35) FIG. 4A through FIG. 4D graphically illustrates a second exemplary execution of the exemplary connectivity policy according to exemplary embodiments of the present disclosure. As illustrated in FIG. 4A through FIG. 4D, an exemplary wireless network (WN) **400** provides wireless communication between electronic devices **402.1** through **402.4** and wireless access points (WAPs) **404.1** through **404.6**. In an exemplary embodiment, the WAP **404.1** represents a private wireless access point as described above and/or the WAPs **404.2** through **404.6** represent public WAPs as described above. Those skilled in the relevant art(s) will recognize the WN **400** can include WAPs than as illustrated in FIG. 4A through FIG. 4D without departing from the spirit and scope of the present disclosure. However, to ease explanation, geographical coverage areas of the WAPs **404.1** through **404.6** are not illustrated in FIG. 4A through FIG. 4D. In the exemplary embodiment illustrated in FIG. 4A through FIG. 4D, the geographical coverage areas of the WAPs **404.1** through **404.6** overlap each other such that the electronic devices **402.1** through **402.4** can communicate with any combination or combinations of the WAPs **404.1** through **404.6**. The WN **400** can represent an exemplary embodiment of the WN **100** as described above in FIG. 1. As such, the electronic devices **402.1** through **402.4** can each represent exemplary embodiments of the electronic device **102** as described above in FIG. 1.

(36) As illustrated in FIG. 4A through FIG. 4D, the WAPs **404.1** and **404.2** are situated within a residential, office, or enterprise environment **406.1**, the WAP **404.3** is situated within a residential, office, or enterprise environment **406.2**, the WAP **404.5** is situated within a residential, office, or enterprise environment **406.3**, and the WAP **404.4** and **404.6** are situated outside of these residential, office, or enterprise environments. In an exemplary embodiment, a user or users of the electronic devices **402.1** through **402.4** enter into a service agreement with a service provider to provide a service to the residential, office, or enterprise environment **406.1** in a substantially similar manner as described above in FIG. 3. The WAP **404.1** provides a connectivity catalog, such as the connectivity catalog **244** to provide an example, to the WAPs **404.2** through **404.6** that includes the electronic devices **402.1** through **402.4** in a substantially similar manner as described above in FIG. 2A. The WAPs **404.2** through **404.6** utilize the connectivity catalog to form a connectivity policy to determine whether to restrict and/or to grant access of the electronic devices **402.1** through **402.4** to their corresponding networks.

(37) Moreover, in the exemplary embodiments illustrated in FIG. 4A through FIG. 4D, the WN **400** selectively monitors one or more parameters, characteristics, and/or attributes of the WAP **404.1** and/or of the electronic devices **402.1** through **402.4** and thereafter intelligently executes the connectivity policy in response to the one or more parameters, characteristics, and/or attributes. In an exemplary embodiment, the WAP **404.1** monitors distances between the WAP **404.1** and the electronic devices **402.1** through **402.4**. In this exemplary embodiment, the WN **400** executes the

connectivity policy on those the electronic devices from among the electronic devices **402.1** through **402.4** situated within a prescribed connectivity distance D from the WAP **404.1**. This prescribed connectivity distance D can be a predetermined-fixed distance, for example, one hundred (100) feet, and can be different for varying population densities and/or be based upon one or more signaling characteristics of the WAP **404.1**. The one or more signaling characteristics can include a speed of the downstream direction, a speed of the upstream direction, a transmission power of the WAP **404.1** and/or the electronic devices **402.1** through **402.4**, a received signal strength of the WAP **404.1** and/or the electronic devices **402.1** through **402.4**, and/or an error rate of the downstream direction and/or the upstream direction to provide some examples.

(38) In the exemplary embodiments illustrated in FIG. 4A through FIG. 4D, the WAP **404.1** monitors distances between the electronic devices **402.1** through **402.3** and the WAP **404.1**. Because the electronic devices **402.1** through **402.3** are situated within the prescribed connectivity distance D from the WAP **404.1** as illustrated in FIG. 4A through FIG. 4C, the WAP **404.1** signals the WAPs **404.2** through **404.6** to enforce the connectivity policy. Alternatively, the WAP **404.1** can provide the connectivity catalog to the WAPs **404.2** through **404.6** to cause the WAPs **404.2** execute the connectivity policy. In the exemplary embodiments illustrated in FIG. 4A through FIG. 4C, the WAP **404.1** grants access to the electronic devices **402.1** through **402.3** to its corresponding network as indicated by “YES” and the WAPs **404.2** through **404.6** deny access to the electronic devices **402.1** through **402.3** to their corresponding networks as indicated by “NO” in FIG. 4A through FIG. 4C in a substantially similar manner as described above in FIG. 3. Because the electronic device **402.4** is situated outside of the prescribed connectivity distance D from the WAP **404.1** as illustrated in FIG. 4D, the WAP **404.1** signals the WAPs **404.2** through **404.6** to not enforce the connectivity policy with the electronic device **402.4**. In this situation, any of the WAPs **404.1** through **404.6** can grant access to the electronic device **402.4** to their corresponding network and/or can be associated with the electronic device **402.4** as appropriate as indicated by “YES” in FIG. 4D.

(39) FIG. 5 illustrates a first flowchart of an exemplary operation of the exemplary WN to execute the connectivity policy according to an exemplary embodiment of the present disclosure. The disclosure is not limited to this operational description. Rather, it will be apparent to ordinary persons skilled in the relevant art(s) that other operational control flows are within the scope and spirit of the present disclosure. The following discussion describes an exemplary operational control flow **500** to execute the connectivity policy as described above. The operational control flow **500** to be described in further detail below can be executed by a service provider system, such as the service provider system **108** as described above, to execute the connectivity policy as described above.

(40) At operation **502**, the operational control flow **500** monitors a distance between a wireless access point (WAP), such as the WAP **104.1** as described above in FIG. 1 and/or the WAP **202** as described above in FIG. 2A, within a wireless network (WN), such as the WN **100** as described above in FIG. 1 and/or the WN **200** as described above in FIG. 2A, and an electronic device, such as the electronic device **102** as described above in FIG. 1. In the exemplary embodiment illustrated in FIG. 5, the electronic device can be characterized as being associated with the WAP and/or has been granted access to a corresponding network of the WAP. In an exemplary embodiment, the corresponding network of the WAP represents a private network as described above with the WAP being a private WAP.

(41) At operation **504**, the operational control flow **500** compares the distance from operation **502** with a prescribed connectivity distance, such as the prescribed connectivity distance as described above in FIG. 4A through FIG. 4D. This prescribed connectivity distance D can be a predetermined-fixed distance, for example, one hundred (100) feet, and can be different for varying population densities and/or be based upon one or more signaling characteristics of the WAP from operation **502**. The one or more signaling characteristics can include a speed of the downstream

direction, a speed of the upstream direction, a transmission power of the WAP from operation **502** and/or the electronic device from operation **502**, a received signal strength of the WAP from operation **502** and/or the electronic device from operation **502**, and/or an error rate of the downstream direction and/or the upstream direction to provide some examples. The operational control flow **500** proceeds to operation **506** when the distance from operation **502** is less than or equal to the prescribed connectivity distance. Otherwise, the operational control flow **500** proceeds to operation **506** when the distance from operation **502** is greater than the prescribed connectivity distance.

(42) At operation **506**, the operational control flow **500** enforces the connectivity policy. In this situation, one or more neighboring WAPs, such as one or more of the WAPs **104.2** through **104.n** as described above in FIG. **1**, search the connectivity catalog for the electronic device from operation **502**. The one or more neighboring WAPs deny access to the electronic device from operation **502** to their corresponding networks when the connectivity catalog includes the electronic device from operation **502**. Otherwise, the electronic device from operation **502** can become freely associated with the WAP from operation **502** and/or any of the one or more neighboring WAPs and/or be freely granted access to any of the corresponding networks of the WAP from operation **502** and/or the one or more neighboring WAPs as appropriate when the connectivity catalog does not include the electronic device from operation **502**.

(43) At operation **506**, the operational control flow **500** does not enforce the connectivity policy. In this situation, the electronic device from operation **502** can become freely associated with the WAP from operation **502** and/or any of the one or more neighboring WAPs from operation **506** and/or be freely granted access to any of the corresponding networks of the WAP from operation **502** and/or one or more neighboring WAPs from operation **506** as appropriate.

(44) FIG. **6** illustrates a second flowchart of an exemplary operation of the exemplary WN to execute the connectivity policy according to an exemplary embodiment of the present disclosure. The disclosure is not limited to this operational description. Rather, it will be apparent to ordinary persons skilled in the relevant art(s) that other operational control flows are within the scope and spirit of the present disclosure. The following discussion describes an exemplary operational control flow **600** to execute the connectivity policy as described above. The operational control flow **600** to be described in further detail below can be executed by a service provider system, such as the service provider system **108** as described above, to execute the connectivity policy as described above. The operational control flow **600** can represent an alternative to or be in addition to the operational control flow **500** as described above in FIG. **5**.

(45) At operation **602**, the operational control flow **600** identifies an optimum usage for electronic devices, such as the electronic device **102** as described above in FIG. **1**, utilizing a wireless network (WN), such as the WN **100** as described above in FIG. **1** and/or the WN **200** as described above in FIG. **2A**, to a usage threshold. The operational control flow **600** can quantify this optimum usage in terms of total sessions, total minutes, and/or data passed to provide some examples.

(46) At operation **604**, the operational control flow **600** identifies a number of connectivity related customer interactions from users of the electronic devices from operation **602** utilizing or attempting to utilize the WN from operation **602**. These connectivity related customer interactions can represent, for example, service calls to the service provider relating to usage of the WN from operation **602**.

(47) At operation **606**, the operational control flow **600** analyzes the optimum usage from operation **602** and/or the number of connectivity related customer interactions from operation **604** to determine whether to enforce the connectivity policy. In an exemplary embodiment, the operational control flow **600** can convert the optimum usage from operation **602** and/or the number of connectivity related customer interactions from operation **604** into a normalized standard range based on the cumulative probability. These standard ranges for the optimum usage from operation

602 and/or the number of connectivity related customer interactions from operation **604** can be thereafter weighted to provide a weighted score as follows:

(48) TABLE-US-00001 Variable Weight Total Sessions 20% Total Minutes 20% Data Passed 10% Total Connectivity Calls 50%

The operational control flow **600** can compare the result weighted score to an impact threshold to determine whether to enforce the connectivity policy. An exemplary analysis performed by the operational control flow **600** is illustrated below for exemplary users, denoted by User IDs of 130, 50, and 88 in the charts below:

(49) TABLE-US-00002 Total Total Minutes Data Passed Sessions User Total (Normal- Data (Normal- Total (Normal- ID Minutes ized) Passed ized) Sessions ized) 130 5000 0.9982 440 0.4550 442 0.9999 50 10632 1.000 48 0.3760 224 0.9613 88 4258 0.9923 174 0.4010 90 0.7155

(50) TABLE-US-00003 Connectivity Connectivity Customer User Customer Interactions Weighted ID Interactions (Normalized) Score 130 2 0.9978 0.9440 50 4 1.0000 0.9299 88 2 0.9978 0.8806

As denoted by the charts above, the user having the User ID of 130 has a weighted score of 0.9440, the user having the User ID of 50 has a weighted score of 0.9299, and the user having the User ID of 88 has a weighted score of 0.8806 indicating that enforcement of the connectivity policy on the user having the User ID of 130 can have more of an impact in improving performance of the WN from operation **602** for this user as compared to the User ID of 50.

Exemplary Computer System that can be Utilized to Implement Devices within the Exemplary Wireless Network

(51) FIG. 7 graphically illustrates a simplified block diagram of a computer system suitable for use with embodiments described herein, as well as circuit design and circuit embodiments of the technology, according to an exemplary embodiment of the present disclosure. The various electronic devices, wireless access points (WAPs), and/or service provider systems as described above can be implemented in hardware, firmware, software, or any combination thereof. The discussion of FIG. 7 to follow describes an exemplary computer system **710** that can be used for these implementations.

(52) In the exemplary embodiment illustrated in FIG. 7, the computer system **710** typically includes at least one processor **714** which communicates with a number of peripheral devices via bus subsystem **712**. Typically, the at least processor **714** can include, or can be, any of a microprocessor, graphics processing unit, or digital signal processor, and their electronic processing equivalents, such as an Application Specific Integrated Circuit ('ASIC') or Field Programmable Gate Array ('FPGA'). As used herein, the term 'processor' signifies a tangible data and information processing device that physically transforms data and information, typically using a sequence transformations (also referred to as 'operations'). Data and information can be physically represented by an electrical, magnetic, optical or acoustical signal that is capable of being stored, accessed, transferred, combined, compared, or otherwise manipulated by the processor. The term 'processor' can signify a singular processor and multi-core systems or multi-processor arrays, including graphic processing units, digital signal processors, digital processors or combinations of these elements. The processor can be electronic, for example, comprising digital logic circuitry (for example, binary logic), or analog (for example, an operational amplifier). The processor may also operate to support performance of the relevant operations in a 'cloud computing' environment or as a 'software as a service' (SaaS). For example, at least some of the operations may be performed by a group of processors available at a distributed or remote system, these processors accessible via a communications network (e.g., the Internet) and via one or more software interfaces (e.g., an application program interface (API).)

(53) The computer system typically includes an operating system, such as Microsoft's Windows, Sun Microsystems's Solaris, Apple Computer's MacOS, Linux or UNIX. The computer system also typically can include a Basic Input/Output System (BIOS) and processor firmware. The operating system, BIOS and firmware are used by the processor to control subsystems and interfaces coupled

to the processor. Typical processors compatible with these operating systems include the Pentium and Itanium from Intel, the Opteron and Athlon from Advanced Micro Devices, and the ARM processor from ARM Holdings.

(54) As illustrated in FIG. 7, these peripheral devices may include a storage subsystem **724**, comprising a memory subsystem **726** and a file storage subsystem **728**, user interface input devices **722**, user interface output devices **720**, and a network interface subsystem **716**. The input and output devices allow user interaction with computer system **710**. In the exemplary embodiment illustrated in FIG. 7, the network interface subsystem **716** provides an interface to outside networks, including an interface to a communication network **718**, and is coupled via a communication network **718** to corresponding interface devices in other computer systems or machines. The communication network **718** may comprise many interconnected computer systems, machines and communication links. These communication links may be wireline links, optical links, wireless links, or any other devices for communication of information. The communication network **718** can be any suitable computer network, for example a wide area network such as the Internet, and/or a local area network such as Ethernet. The communication network **718** can be wired and/or wireless, and the communication network can use encryption and decryption methods, such as is available with a virtual private network. The communication network uses one or more communications interfaces, which can receive data from, and transmit data to, other systems. Embodiments of communications interfaces typically include an Ethernet card, a modem (e.g., telephone, satellite, cable, or ISDN), (asynchronous) digital subscriber line (DSL) unit, Firewire interface, USB interface, and the like. One or more communications protocols can be used, such as HTTP, TCP/IP, RTP/RTSP, IPX and/or UDP.

(55) The user interface input devices **722** may include an alphanumeric keyboard, a keypad, pointing devices such as a mouse, trackball, touchpad, stylus, or graphics tablet, a scanner, a touchscreen incorporated into the display, audio input devices such as voice recognition systems or microphones, eye-gaze recognition, brainwave pattern recognition, and other types of input devices. Such devices can be connected by wire or wirelessly to a computer system. In general, use of the term 'input device' is intended to include all possible types of devices and ways to input information into the computer system **710** or onto the communication network **718**. The user interface input devices **722** typically allow a user to select objects, icons, text and the like that appear on some types of user interface output devices, for example, a display subsystem.

(56) The user interface output devices **720** may include a display subsystem, a printer, a fax machine, or non-visual displays such as audio output devices. The display subsystem may include a cathode ray tube (CRT), a flat-panel device such as a liquid crystal display (LCD), a projection device, or some other device for creating a visible image such as a virtual reality system. The display subsystem may also provide non-visual display such as via audio output or tactile output (e.g., vibrations) devices. In general, use of the term 'output device' is intended to include all possible types of devices and ways to output information from the computer system **710** to the user or to another machine or computer system.

(57) The memory subsystem **726** typically includes a number of memories including a main random-access memory ('RAM') **730** (or other volatile storage device) for storage of instructions and data during program execution and a read only memory ('ROM') **732** in which fixed instructions are stored. The file storage subsystem **728** provides persistent storage for program and data files, and may include a hard disk drive, a floppy disk drive along with associated removable media, a CD-ROM drive, an optical drive, a flash memory, or removable media cartridges. The databases and modules implementing the functionality of certain embodiments may be stored by file storage subsystem **728**.

(58) The bus subsystem **712** provides a device for letting the various components and subsystems of the computer system **710** communicate with each other as intended. Although the bus subsystem **712** is shown schematically as a single bus, alternative embodiments of the bus subsystem may use

multiple busses. For example, RAM-based main memory can communicate directly with file storage systems using Direct Memory Access ('DMA') systems.

CONCLUSION

(59) The Detailed Description referred to accompanying figures to illustrate exemplary embodiments consistent with the disclosure. References in the disclosure to "an exemplary embodiment" indicates that the exemplary embodiment described can include a particular feature, structure, or characteristic, but every exemplary embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same exemplary embodiment. Further, any feature, structure, or characteristic described in connection with an exemplary embodiment can be included, independently or in any combination, with features, structures, or characteristics of other exemplary embodiments whether or not explicitly described.

(60) The Detailed Description is not meant to limiting. Rather, the scope of the disclosure is defined only in accordance with the following claims and their equivalents. It is to be appreciated that the Detailed Description section, and not the Abstract section, is intended to be used to interpret the claims. The Abstract section can set forth one or more, but not all exemplary embodiments, of the disclosure, and thus, are not intended to limit the disclosure and the following claims and their equivalents in any way.

(61) The exemplary embodiments described within the disclosure have been provided for illustrative purposes and are not intended to be limiting. Other exemplary embodiments are possible, and modifications can be made to the exemplary embodiments while remaining within the spirit and scope of the disclosure. The disclosure has been described with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined so long as the specified functions and relationships thereof are appropriately performed.

(62) Embodiments of the disclosure can be implemented in hardware, firmware, software application, or any combination thereof. Embodiments of the disclosure can also be implemented as instructions stored on a machine-readable medium, which can be read and executed by one or more processors. A machine-readable medium can include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computing circuitry). For example, a machine-readable medium can include non-transitory machine-readable mediums such as read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; and others. As another example, the machine-readable medium can include transitory machine-readable medium such as electrical, optical, acoustical, or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.). Further, firmware, software application, routines, instructions can be described herein as performing certain actions. However, it should be appreciated that such descriptions are merely for convenience and that such actions in fact result from computing devices, processors, controllers, or other devices executing the firmware, software application, routines, instructions, etc.

(63) The Detailed Description of the exemplary embodiments fully revealed the general nature of the disclosure that others can, by applying knowledge of those skilled in relevant art(s), readily modify and/or adapt for various applications such exemplary embodiments, without undue experimentation, without departing from the spirit and scope of the disclosure. Therefore, such adaptations and modifications are intended to be within the meaning and plurality of equivalents of the exemplary embodiments based upon the teaching and guidance presented herein. It is to be understood that the phraseology or terminology herein is for the purpose of description and not of limitation, such that the terminology or phraseology of the present specification is to be interpreted by those skilled in relevant art(s) in light of the teachings herein.

Claims

1. A wireless network, comprising: a first wireless access point from among a plurality of wireless access points within the wireless network, the first wireless access point being configured to store a connectivity catalog that specifies an electronic device; and a second wireless access point from among the plurality of wireless access points configured to: receive the connectivity catalog from the first wireless access point, determine that the electronic device is specified in the connectivity catalog in response to the electronic device attempting to access the second wireless access point, restrict access by the electronic device to the second wireless access point when a distance between the electronic device and the first wireless access point is less than or equal to a prescribed connectivity distance, and grant the electronic device access to the second wireless access point when the distance between the electronic device and the first wireless access point is greater than the prescribed connectivity distance.
2. The wireless network of claim 1, wherein the first wireless access point is configured to store the electronic device within the connectivity catalog in response to the electronic device becoming associated with the first wireless access point and being granted access to the wireless network.
3. The wireless network of claim 2, wherein the first wireless access point is configured to store the electronic device within the connectivity catalog in response to the electronic device completing an authentication procedure or an authorization procedure with the first wireless access point before becoming associated with the first wireless access point and before being granted access to the wireless network.
4. The wireless network of claim 1, wherein the second wireless access point is further configured to receive a connectivity request from the electronic device to establish communication with the second wireless access point.
5. The wireless network of claim 4, wherein the second wireless access point is configured to: deny the connectivity request from the electronic device when the distance between the electronic device and the first wireless access point is less than or equal to the prescribed connectivity distance; and grant the connectivity request from the electronic device when the distance between the electronic device and the first wireless access point is greater than the prescribed connectivity distance.
6. The wireless network of claim 1, wherein the prescribed connectivity distance is based on a population density of a geographical area of the wireless network.
7. A wireless access point from among a plurality of wireless access points within a wireless network, the wireless access point comprising: a memory that stores a connectivity catalog that specifies a plurality of electronic devices; and a processor configured to execute instructions stored in the memory, the instructions, when executed by the processor, configuring the processor to: determine whether an electronic device attempting to access the wireless access point is from among the plurality of electronic devices specified within the connectivity catalog, when the electronic device is from among the plurality of electronic devices specified in the connectivity catalog: restrict the electronic device access to the wireless access point when a distance between the electronic device and a second wireless access point from among the plurality of wireless access points is less than or equal to a prescribed connectivity distance, and grant the electronic device access to the wireless access point when the distance between the electronic device and the second wireless access point is greater than the prescribed connectivity distance, and when the electronic device is not from among the plurality of electronic devices specified in the connectivity catalog, grant the electronic device access to the wireless access point regardless of the distance between the electronic device and the second wireless access point.
8. The wireless access point of claim 7, wherein the plurality of electronic devices specified in the connectivity catalog have become associated with the second wireless access point and have been granted access to the wireless network.

9. The wireless access point of claim 8, wherein the plurality of electronic devices have completed an authentication procedure or an authorization procedure with the second wireless access point before becoming associated with the second wireless access point and before being granted access to the wireless network.

10. The wireless access point of claim 7, wherein the instructions, when executed by the processor, further configure the processor to receive a connectivity request from the electronic device to establish communication with the wireless access point.

11. The wireless access point of claim 10, wherein the instructions, when executed by the processor, configure the processor to: deny the connectivity request from the electronic device when the distance between the electronic device and the second wireless access point is less than or equal to the prescribed connectivity distance; and grant the connectivity request from the electronic device when the distance between the electronic device and the second wireless access point is greater than the prescribed connectivity distance.

12. The wireless access point of claim 7, wherein the prescribed connectivity distance is based on a population density of a geographical area of the wireless network.

13. The wireless access point of claim 7, wherein the prescribed connectivity distance comprises a predetermined-fixed distance.

14. A method for executing a connectivity policy within a wireless network, the method comprising: receiving, by a wireless access point that is outside of a residential, office, or enterprise environment that receives a service from a service provider, a connectivity catalog that specifies a plurality of electronic devices; determining, by the wireless access point, whether an electronic device attempting to access the wireless access point is from among the plurality of electronic devices specified within the connectivity catalog, when the electronic device is from among the plurality of electronic devices specified in the connectivity catalog; restricting, by the wireless access point, the electronic device access to the wireless access point when a distance between the electronic device and a second wireless access point within the residential, office, or enterprise environment from among a plurality of wireless access points is less than or equal to a prescribed connectivity distance, and granting, by the wireless access point, the electronic device access to the wireless access point when the distance between the electronic device and the second wireless access point is greater than the prescribed connectivity distance, and when the electronic device is not from among the plurality of electronic devices specified in the connectivity catalog, granting, by the wireless access point, the electronic device access to the wireless access point regardless of the distance between the electronic device and the second wireless access point.

15. The method of claim 14, wherein the plurality of electronic devices specified in the connectivity catalog have become associated with the second wireless access point and have been granted access to the wireless network.

16. The method of claim 15, wherein the plurality of electronic devices have completed an authentication procedure or an authorization procedure with the second wireless access point before becoming associated with the second wireless access point and before being granted access to the wireless network.

17. The method of claim 14, further comprising receiving, by the wireless access point, a connectivity request from the electronic device to establish communication with the wireless access point.

18. The method of claim 17, wherein the restricting the electronic device access to the wireless access point when the distance between the electronic device and the second wireless access point is less than or equal to the prescribed connectivity distance comprises denying the connectivity request from the electronic device when the distance between the electronic device and the second wireless access point is less than or equal to the prescribed connectivity distance, wherein the granting the electronic device access to the wireless access point when the distance between the electronic device and the second wireless access point is greater than the prescribed connectivity

distance comprises granting the connectivity request from the electronic device when the distance between the electronic device and the second wireless access point is greater than the prescribed connectivity distance.

19. The method of claim 14, wherein the prescribed connectivity distance is based on a population density of a geographical area of the wireless network.

20. The method of claim 14, wherein the prescribed connectivity distance comprises a predetermined-fixed distance.
