

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275780

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

QUILLIN; DANIEL T.

ASPIRATION MEDICAL DEVICE

Abstract

Aspiration medical devices and methods for making and using aspiration medical devices are disclosed. An example aspiration medical device may include a catheter shaft having a distal end region and defining an inflow orifice adjacent to the distal end region. An aspiration member may be disposed within the catheter shaft. The aspiration member may have a plurality of axially-spaced fluid jets formed therein. A collar may be disposed over the aspiration member. The collar may have a jet support region disposed adjacent to at least one of the fluid jets and a wall support region disposed adjacent to a wall of the catheter shaft.

Inventors: QUILLIN; DANIEL T. (EDEN PRAIRIE, MN)

Applicant: BOSTON SCIENTIFIC SCIMED, INC. (MAPLE GROVE, MN)

Family ID: 81750651

Assignee: BOSTON SCIENTIFIC SCIMED, INC. (MAPLE GROVE, MN)

Appl. No.: 19/211803

Filed: May 19, 2025

Related U.S. Application Data

parent US continuation 18631786 20240410 parent-grant-document US 12303151 child US 19211803

parent US continuation 17736244 20220504 parent-grant-document US 11969176 child US 18631786

us-provisional-application US 63183856 20210504

Publication Classification

Int. Cl.: A61B17/22 (20060101); A61M25/00 (20060101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/631,786, filed Apr. 10, 2024, which is a continuation of U.S. patent application Ser. No. 17/736,244, filed May 4, 2022, now issued as U.S. Pat. No. 11,969,176, which claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 63/183,856 filed on May 4, 2021, the disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure pertains to medical devices, and methods for manufacturing medical devices. More particularly, the present disclosure pertains to aspiration medical devices.

BACKGROUND

[0003] A wide variety of medical devices have been developed for medical use, for example, intravascular use. Some of these devices include guidewires, catheters, and the like. These devices are manufactured by any one of a variety of different manufacturing methods and may be used according to any one of a variety of methods. Of the known medical devices and methods, each has certain advantages and disadvantages. There is an ongoing need to provide alternative medical devices as well as alternative methods for manufacturing and using medical devices.

BRIEF SUMMARY

[0004] This disclosure provides design, material, manufacturing method, and use alternatives for medical devices. An aspiration medical device is disclosed. The aspiration medical device comprises: a catheter shaft having a distal end region and defining an inflow orifice adjacent to the distal end region; an aspiration member disposed within the catheter shaft, the aspiration member having a plurality of axially-spaced fluid jets formed therein; and a collar disposed over the aspiration member, the collar having a jet support region disposed adjacent to at least one of the fluid jets and a wall support region disposed adjacent to a wall of the catheter shaft.

[0005] Alternatively or additionally to any of the embodiments above, the aspiration member has a closed distal end.

[0006] Alternatively or additionally to any of the embodiments above, at least some of the fluid jets are angled proximally.

[0007] Alternatively or additionally to any of the embodiments above, at least some of the fluid jets are oriented in a direction that is normal to a longitudinal axis of the aspiration member.

[0008] Alternatively or additionally to any of the embodiments above, the jet support region includes a jet opening that is aligned with one of the fluid jets.

[0009] Alternatively or additionally to any of the embodiments above, the jet opening is angled proximally.

[0010] Alternatively or additionally to any of the embodiments above, the jet support region and the wall support region are coaxially arranged.

[0011] Alternatively or additionally to any of the embodiments above, the jet support region is radially offset from a longitudinal axis of the wall support region.

[0012] Alternatively or additionally to any of the embodiments above, further comprising a second collar disposed over the aspiration member.

[0013] Alternatively or additionally to any of the embodiments above, the second collar includes a second jet support region that is aligned with one of the fluid jets.

[0014] Alternatively or additionally to any of the embodiments above, the collar is axially spaced apart from the second collar.

[0015] An aspiration medical device is disclosed. The aspiration medical device comprises: a catheter shaft having a distal end region, the catheter shaft including an inflow orifice adjacent to the distal end region and an outflow orifice disposed proximally of the inflow orifice; an aspiration member disposed within the catheter shaft, the aspiration member having a plurality of axially-spaced fluid jets formed therein including a first fluid jet; and a first collar disposed along the aspiration member and positioned adjacent to the first fluid jet, the first collar having a jet support region and a wall support region.

[0016] Alternatively or additionally to any of the embodiments above, the first fluid jet is oriented orthogonally to a longitudinal axis of the aspiration member.

[0017] Alternatively or additionally to any of the embodiments above, the jet support region includes a first jet opening that is aligned with the first fluid jet.

[0018] Alternatively or additionally to any of the embodiments above, the first jet opening is angled proximally.

[0019] Alternatively or additionally to any of the embodiments above, the plurality of axially-spaced fluid jets includes a second fluid jet; and further comprising a second collar disposed along the aspiration member and positioned adjacent to the second fluid jet.

[0020] Alternatively or additionally to any of the embodiments above, the first collar is co-axially disposed within the catheter shaft.

[0021] Alternatively or additionally to any of the embodiments above, the first collar includes a second jet opening.

[0022] Alternatively or additionally to any of the embodiments above, the aspiration member includes a second fluid jet disposed opposite the first fluid jet, and wherein the first collar includes a first jet opening aligned with the first fluid jet and a second jet opening aligned with the second fluid jet.

[0023] An aspiration medical device is disclosed. The aspiration medical device, comprises: a catheter shaft having a distal end region and an inflow orifice disposed along the distal end region; an aspiration tube disposed within the catheter shaft, the aspiration tube having a closed distal end and having a plurality of axially-spaced fluid jets formed therein; wherein the plurality of axially-spaced fluid jets includes a first fluid jet; and a metallic 3-D printed collar disposed along the aspiration tube and aligned with the first fluid jet, the collar having a jet support region configured to support the first fluid jet and a wall support region configured to support a wall region of the catheter shaft disposed opposite the first fluid jet.

[0024] The above summary of some embodiments is not intended to describe each disclosed embodiment or every implementation of the present disclosure. The Figures, and Detailed Description, which follow, more particularly exemplify these embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] The disclosure may be more completely understood in consideration of the following detailed description in connection with the accompanying drawings, in which:

[0026] FIG. 1 is a side view of an example aspiration medical device;

[0027] FIG. 2 is a cross-sectional side view of a portion of an example aspiration medical device.

[0028] FIG. 3 is a cross-sectional side view of a portion of an example aspiration member.

[0029] FIG. 4 is a cross-sectional side view of a portion of an example aspiration medical device.

[0030] FIG. 5 is a cross-sectional view of an example collar.

[0031] FIG. 6 is a cross-sectional side view of a portion of an example aspiration member

including an example collar.

[0032] FIG. **7** is a cross-sectional side view of a portion of an example aspiration member including a plurality of example collars.

[0033] FIG. **8** is a cross-sectional view of an example collar.

[0034] FIG. **9** is an end view of an example collar.

[0035] FIG. **10** is a cross-sectional side view of a portion of an example aspiration member including an example collar.

[0036] FIG. **11** is a cross-sectional side view of a portion of an example aspiration member including a plurality of example collars.

[0037] FIG. **12** is a cross-sectional view of an example collar.

[0038] FIG. **13** is an end view of an example collar.

[0039] FIG. **14** is a cross-sectional side view of a portion of an example aspiration member including an example collar.

[0040] FIG. **15** is a cross-sectional side view of a portion of an example aspiration member including a plurality of example collars.

[0041] While the disclosure is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DETAILED DESCRIPTION

[0042] For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

[0043] All numeric values are herein assumed to be modified by the term “about”, whether or not explicitly indicated. The term “about” generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (e.g., having the same function or result). In many instances, the terms “about” may include numbers that are rounded to the nearest significant figure.

[0044] The recitation of numerical ranges by endpoints includes all numbers within that range (e.g. 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

[0045] As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

[0046] It is noted that references in the specification to “an embodiment”, “some embodiments”, “other embodiments”, etc., indicate that the embodiment described may include one or more particular features, structures, and/or characteristics. However, such recitations do not necessarily mean that all embodiments include the particular features, structures, and/or characteristics. Additionally, when particular features, structures, and/or characteristics are described in connection with one embodiment, it should be understood that such features, structures, and/or characteristics may also be used connection with other embodiments whether or not explicitly described unless clearly stated to the contrary.

[0047] The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

[0048] FIG. **1** is a side view of an example aspiration medical device **10**. The aspiration medical device **10** may include a tubular member or catheter shaft **12** having a proximal end region **14** and a distal end region **16**. A hub or manifold **18** (depicted schematically) may be coupled to the proximal end region **14**. A tip member **20** may be coupled to the distal end region **16**. The catheter

shaft **12** may include a number of additional features. For example, one or more markers **26** (e.g., radiopaque marker bands) may be disposed along the catheter shaft **12**.

[0049] The catheter shaft **12** may have a plurality of openings or orifices. For example, the catheter shaft **12** may have a first or inflow orifice **22**. The inflow orifice **22** may be disposed proximally of the distal end of the catheter shaft. The catheter shaft **12** may also include a second or outflow orifice **24**. The outflow orifice **24** may be disposed proximally of the inflow orifice **22**. In some instances, the inflow orifice **22** and the outflow orifice **24** may be axially aligned along the catheter shaft **12**. In other instances, the inflow orifice **22** and the outflow orifice **24** may be circumferentially offset from one another about the catheter shaft **12**. In some instances, the inflow orifice **22** and the outflow orifice **24** may have the same size, shape, or both. In other instances, the inflow orifice **22** and the outflow orifice **24** may differ in size, shape, or both.

[0050] FIG. 2 is a cross-sectional view of a portion of the aspiration medical device **10** that schematically depicts how the aspiration medical device **10** may be used to aspirate material (e.g., embolic material, thrombus/thrombogenic material, stenotic material, etc.) from a patient. Here it can be seen that an aspiration assembly **28** may be disposed within a lumen **29** of the catheter shaft **12**. The aspiration assembly **28** may include a tubular member or inner tube **30** defining a lumen **32**. A fluid jet **34** may be coupled to the inner tube **30**. In some instances, the fluid jet **34** may be understood to be or otherwise take the form of a fluid jet orifice or fluid jet orifice member. The fluid jet **34** may be in fluid communication with the lumen **32**. In some instances, the fluid jet **34** may be oriented at an angle relative to the inner tube **30**. For example, the fluid jet **34** may be disposed at an angle that is normal to the inner tube **30**. In at least some instances, the fluid jet **34** may have an annular arrangement. However, other arrangements and/or configurations are contemplated.

[0051] The fluid jet **34** may have one or more jet orifices **36** define therein. In some instances, the fluid jet **34** includes one jet orifice **36**. In other instances, the fluid jet **34** may include two, three, four, five, six, seven, eight, or more jet orifices **36**. The jet orifices **36** may take the form of openings in the fluid jet **34** that allow fluid infused through the lumen **32** to be jetted in a generally proximal direction within the lumen **29** of the catheter shaft **12** as depicted by lines in FIG. 2 projecting proximally from the jet orifices **36**. The jet orifices **36** may be spaced evenly along the fluid jet **34**. Alternatively, the jet orifices may be arranged in an uneven manner or distributed along only a portion of the fluid jet **34**.

[0052] Infusion of a fluid (e.g., a motive fluid, a liquid, a gas or air, steam, a fluid with particles disposed therein, or the like) through the lumen **32** of the inner tube **30** may cause the fluid to be jetted or otherwise exit the jet orifices **36**. As the fluid moves proximally through the lumen **29**, the fluid may generate an aspiration force that can draw entrainment material into the lumen **29** through the inflow orifice **22**. The material drawn into the lumen **29** may be aspirated through the lumen **29** and out from a patient. In addition or in the alternative, some or all of the thrombogenic material drawn into the lumen **29** may exit that catheter shaft **12** through the outflow orifice **24**. The material may recirculate and the action of recirculation may help to break up the thrombogenic material in order to ease removal. For example, the material may enter the inflow orifice **22** where it can be aspirated from the patient and/or further recirculated.

[0053] FIGS. 3-4 illustrates an example aspiration member **128** (e.g., that may be similar in form and function to other aspiration members/assemblies disclosed herein) that may be used in an aspiration medical device **110**. The aspiration medical device **110** (e.g., a portion of which is depicted in FIG. 4) may be similar in form and function to other aspiration medical devices disclosed herein. For example, the aspiration medical device **110** may include a catheter shaft **112** having a distal end region **116** and defining a lumen **129**. The catheter shaft **112** may also include a first or inflow orifice (e.g., similar to the inflow orifice **22**) and a second or outflow orifice (e.g., similar to the outflow orifice **24**). For simplicity purposes, the inflow and outflow orifices are not shown in FIGS. 3-4.

[0054] The aspiration member **128** may be disposed in the lumen **129** of the catheter shaft **112**. The aspiration member **128** may include a shaft **130** defining a lumen or fluid pathway **132**. In at least some instances, the aspiration member **128** has a closed distal end. Because of this, fluid may be able to pass through the fluid pathway **132** but not exit the distal end the same way fluid may pass through the distal opening of a tube. In some instances, the aspiration member **128** may have an open distal end. Furthermore, the aspiration member **128** may differ from the aspiration assembly **28** (e.g., as shown in FIG. 2) in that the aspiration member **128** may lack a fluid jet **34**.

[0055] A plurality of jet orifices **138** may be defined along the shaft **130**. For example, the shaft **130** may include two, three, four, five, six, or more jet orifices **138**. In some instances, some or all of the jet orifices **138** may be axially aligned along the shaft **130**. In other instances, one or more of the jet orifices **138** may be circumferentially offset from one another about the shaft **130**. A number of patterns are contemplated including a helical pattern, a regular pattern where no two jet orifices **138** are disposed at the same axial location, a regular pattern including two or more jet orifices **138** disposed at the same axial location, an irregular pattern (where some of the jet orifices **138** may or may not be disposed at the same axial location), etc. The jet orifices **138** may be formed using a suitable method such as electron discharge machining, etching, cutting (e.g., including laser cutting), or the like. In some instances, one or more of the jet orifices **138** have a substantially round shape. In other instances, one or more of the jet orifices **138** have a substantially non-round shape (e.g., oval, polygonal, irregular, etc.). In some instances, the jet orifices **138** may be beveled or otherwise include a beveled surface.

[0056] The jet orifices **138** may be designed to infuse fluid (e.g., a motive fluid, a liquid, a gas or air, steam, a fluid with particles disposed therein, or the like) through the jet orifices **138** and into the lumen **129** of the catheter shaft **112** in a generally proximal direction as depicted by lines projecting generally proximally from the jet orifices **138** in FIGS. 3-4. In some instances, the jet orifices **138** may be oriented at an angle relative to the longitudinal axis of the shaft **130**. For example, the jet orifices **138** may be oriented at an acute angle relative to the longitudinal axis of the shaft **130** and/or oriented at an angle greater than zero degrees and less than ninety degrees relative to the longitudinal axis of the shaft **130**. In other instances, the jet orifices **138** may be oriented at ninety degrees relative to the longitudinal axis of the shaft **130**. The angle may or may not be the same for all the jet orifice **138**. Infusion of motive fluid through the lumen **132** of the shaft **130** may result in fluid being jetted through the jet orifices **138** (e.g., generally in the proximal direction) and the generation of an aspiration force.

[0057] In at least some instances, the jet orifices **138** may be understood as being arranged in series. In other words, the jet orifices **138** may be arranged at various locations along the longitudinal axis of the shaft **130**. This may position the jet orifices **138** at spaced apart axially locations within the catheter shaft **112**. Accordingly, motive fluid leaves via the jet orifices forming a jetted motive fluid. This jetted motive fluid enters an entrainment material where the shear layer between the two causes turbulence, mixing, and transfer of momentum. Entrainment material may enter the inflow orifice (not shown, may be similar to the inflow orifice **22**) and then may be urged proximally by momentum transfer. As the mixture of jetted motive fluid and entrainment material migrates proximally, the material may sequentially approach a number of jet orifices **138**. Upon interaction with the jetted motive fluid from each individual jet orifice **138**, the momentum in the entrainment material mixture may increase, and the thrombogenic material may more readily flow through the catheter shaft **112** for removal. The increase in momentum may allow for the catheter shaft **112** to be used without a second or outflow orifice (e.g., positioned proximally of the inflow orifice and that may be similar to the outflow orifice **24** as depicted in FIG. 2). Alternatively, some of the entrapped thrombogenic material may exit the catheter shaft **112** through a second orifice (not shown) positioned proximally of the inflow orifice, recirculate to the inflow orifice (e.g., one or more times), and then move through the lumen **129**.

[0058] It can be appreciated that a relatively high volume of fluid, traveling at a high rate and

pressure (e.g., on the order of about 290-580 miles per hour), may travel through the jet orifices **138**. It may be desirable to reinforce the structural integrity of the jet orifices **138** and/or the catheter shaft **112**. Disclosed herein are aspiration medical devices that include structural features configured to reinforce the structural integrity of the jet orifices **138** and/or the catheter shaft **112**. [0059] FIG. 5 illustrates an example collar **240** that may be used with any of the aspiration medical devices disclosed herein. The collar **240** includes a body **242** having a jet support region **244**. In general, the jet support region **244** is designed to support the jet orifices **138** in the aspiration member **128**. A jet opening **246** may be formed in the collar **240**, for example along the jet support region **244**. The collar **240** may comprise a metal (e.g., titanium, aluminum, stainless steel and/or stainless steel alloys, etc.), polymer, or composite material that is capable of withstanding high volumes of fluid, traveling at a high rate and pressure, adjacent thereto. For example, the collar **240** may comprise a metal that can be positioned adjacent to a jet orifice and be capable of withstanding fluid passing through the jet orifice and contacting the collar **240**. In some instances, the collar **240** may be a 3D printed collar **240** that can have a variety of different shapes and/or configurations. [0060] FIG. 6 illustrates the collar **240** disposed over/along the aspiration member **128**. The collar **240** may be secured to the aspiration member **128** using a suitable securing technique such as adhesive bonding, thermal bonding, welding, etc. In this example, fluid passing through the jet orifices **138** may exit the aspiration member at a relatively high velocity. Due to the fluid traveling at a high velocity, it may be desirable to try to reduce the likelihood that the fluid could erode or otherwise impact the structural integrity of the jet orifices **138**. As such, by disposing the collar **240** over/along the aspiration member **128**, the collar **240** can enhance the structural integrity of the aspiration member **128**, the jet orifices **138**, and/or the aspiration medical device **110**. [0061] The jet opening **246** in the collar **240** may be aligned with one of the jet orifices **138**. In some instances, the jet opening **246** is proximally angled and/or otherwise designed to direct fluid passing therethrough toward the proximal end of the aspiration medical device **110**. This configuration may allow the jet orifice(s) **138** to be “square cut”, oriented in a direction that is normal to a longitudinal axis of the aspiration member, and/or otherwise not be proximally angled. This may desirably impact the manufacturing the aspiration member **128** by simplifying the formation of the jet orifices **138**. This may also help to reduce erosion or wear of the aspiration member **128** by virtue of the jet orifice **138** not having to be directed proximally as the proximally angled orientation of the jet opening **246** being sufficient to direct fluid proximally. Furthermore, because the collar **240** and the jet opening **246** therein may be formed using a process such as 3D printing (e.g., which allows for the formation of structure with a variety of configurations and designs including complex designs), the design of proximally angled cuts/openings (e.g., such as the jet opening **246**) may be able to be controlled and manufactured more efficiently. [0062] In FIG. 6, a single collar **340** is shown disposed over/along the aspiration member **128**. The jet orifice **138** that is aligned with the jet opening **246** is square cut (e.g., not proximally angled) whereas the jet opening **246** is proximally angled. Fluid passing through the jet orifice **138** may pass through the proximally angled jet opening **246** and, thus, be directed proximally. In some instances, other jet orifices **138** along the aspiration member (e.g., which do not have a collar **340** disposed thereover in FIG. 6) may be proximally angled as shown in FIG. 6. However, this need not be the case. In some instances, the other jet orifices **138** may also be square cut. In such cases, the collar **340** may be extended to fit over multiple jet orifices **138** and include multiple jet openings **246** that each align with a jet orifice **138**. Alternatively, a plurality of collars **240** may be disposed over/along the aspiration member **128** as shown in FIG. 7. This may include 2, 3, 4, 5, 6, or more collars **240** and/or all a suitable number of collars **240** to align with each/all of the jet orifices **138**. In this example, each jet orifice **138** may be square cut and each collar **240** may include a proximally angled jet opening **246** that is proximally angled and aligned with respective jet orifices **138**. Other configurations are contemplated. [0063] FIGS. 8-9 illustrate another example collar **340** that may be similar in form and function to

other collars disclosed herein. The collar **340** includes a body **342** having a jet support region **344**. A jet opening **346** may be formed in the collar **340**, for example along the jet support region **344**. In general, the jet support region **344** is designed to support the jet orifices **138** in the aspiration member **128**. The jet support region **344** may have a cylindrical or tubular configuration that is configured to fit over/along the aspiration member **128**. The collar **340** may also include a wall support region **348**. In general, the wall support region **348** is designed to support the wall of the catheter shaft **112** (e.g., to reduce the likelihood that fluid passing through the jet orifices **138** could impact the integrity of the wall of the catheter shaft **112**). The wall support region **348** may have a tubular and/or partially tubular/cylindrical configuration. In some instances, the shape of the wall support region **348** may be described as having an angled end, being skived, or have a flap or tailing end region.

[0064] FIG. **10** illustrates the collar **340** disposed over/along the aspiration member **128**. The collar **340** may be secured to the aspiration member **128** using a suitable securing technique such as adhesive bonding, thermal bonding, welding, etc. Just like the collar **240**, the collar **340** may be arranged so that the jet opening **346** may be aligned with the jet orifice **138** of the aspiration member **128**. Because the jet opening **346** may be proximally angled, the jet orifice **138** may be square cut. The wall support region **348** may be positioned along an interior wall of the catheter shaft **112**, generally opposite the jet orifice **138**. This may help to reduce the likelihood that fluid passing through the jet orifices **138** could impact the integrity of the wall of the catheter shaft **112**. In some instances, a single collar **340** may be used with the aspiration member **128**. Alternatively, a plurality of collars **340** may be disposed over/along the aspiration member **128** as shown in FIG. **11**. This may include 2, 3, 4, 5, 6, or more collars **340** and/or all a suitable number of collars **340** to align with each/all of the jet orifices **138**.

[0065] FIGS. **12-13** illustrate another example collar **440** that may be similar in form and function to other collars disclosed herein. The collar **440** includes a body **442** having a jet support region **444**. In general, the jet support region **444** is designed to support the jet orifices **438** in the aspiration member **428** (e.g., the aspiration member **428** is shown in FIGS. **14-15**). The jet support region **444** may have a cylindrical or tubular configuration that is configured to fit over/along the aspiration member **428**. One or more jet openings **446** may be formed in the collar **440**, for example along the jet support region **444**. In this example, the jet support region **444** is substantially centered within the collar **440** and has a pair of opposing jet openings **446**. Other configurations/arrangements are contemplated. The collar **440** may also include a wall support region **448** and a connecting region **450** extending between the jet support region **444** and the wall support region **448**. In general, the wall support region **448** is designed to support the wall of the catheter shaft **112** (e.g., to reduce the likelihood that fluid passing through the jet orifices **438** could impact the integrity of the wall of the catheter shaft **112**). The wall support region **448** may have a tubular and/or partially tubular/cylindrical configuration. In some instances, the shape of the wall support region **448** may be described as having an angled end, being skived, or have a flap or tailing end region.

[0066] FIG. **14** illustrates the collar **440** disposed over/along the aspiration member **428**. The collar **440** may be secured to the aspiration member **428** using a suitable securing technique such as adhesive bonding, thermal bonding, welding, etc. In this example, the aspiration member **428** and the collar **440** coupled thereto may be substantially centered within the catheter shaft **112**. Just like the collars **240**, **340**, the collar **440** may be arranged so that the jet opening **446** may be aligned with the jet orifice(s) **438** of the aspiration member **428**. Because the jet openings **446** may be proximally angled, the jet orifice **438** may be square cut. The wall support region **448** may be positioned along an interior wall of the catheter shaft **112**, generally opposite the jet orifices **438**. This may help to reduce the likelihood that fluid passing through the jet orifices **438** could impact the integrity of the wall of the catheter shaft **112**. In some instances, a single collar **440** may be used with the aspiration member **428**. Alternatively, a plurality of collars **440** may be disposed

over/along the aspiration member **128** as shown in FIG. **15**. This may include 2, 3, 4, 5, 6, or more collars **440** and/or all a suitable number of collars **440** to align with each/all of the jet orifices. [0067] The materials that can be used for the various components of the aspiration medical device **10** (and/or other aspiration medical devices disclosed herein) and the various components thereof may include those commonly associated with medical devices. For simplicity purposes, the following discussion refers to the catheter shaft **12** of the aspiration medical device **10**. However, this is not intended to limit the devices and methods described herein, as the discussion may be applied to other catheter shaft and/or components of any of the aspiration medical devices disclosed herein.

[0068] The catheter shaft **12** may be made from a metal, metal alloy, polymer (some examples of which are disclosed below), a metal-polymer composite, ceramics, combinations thereof, and the like, or other suitable material. Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly(alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), Marlex high-density polyethylene, Marlex low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), poly paraphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro (propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly(styrene-b-isobutylene-b-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, ionomers, biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like. In some embodiments the sheath can be blended with a liquid crystal polymer (LCP). For example, the mixture can contain up to about 6 percent LCP.

[0069] Some examples of suitable metals and metal alloys include stainless steel, such as 304V, 304L, and 316LV stainless steel; mild steel; nickel-titanium alloy such as linear-elastic and/or super-elastic nitinol; other nickel alloys such as nickel-chromium-molybdenum alloys (e.g., UNS: N06625 such as INCONEL® 625, UNS: N06022 such as HASTELLOY® C-22®, UNS: N10276 such as HASTELLOY® C276®, other HASTELLOY® alloys, and the like), nickel-copper alloys (e.g., UNS: N04400 such as MONEL® 400, NICKELVAC® 400, NICORROS® 400, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nickel-molybdenum alloys (e.g., UNS: N10665 such as HASTELLOY® ALLOY B2®), other nickel-chromium alloys, other nickel-molybdenum alloys, other nickel-cobalt alloys, other nickel-iron alloys, other nickel-copper alloys, other nickel-tungsten or tungsten alloys, and the like; cobalt-chromium alloys; cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNOX®, and the like); platinum enriched stainless steel; titanium; combinations thereof; and the like; or any other suitable material.

[0070] In at least some embodiments, portions or all of the catheter shaft **12** may also be doped with, made of, or otherwise include a radiopaque material. Radiopaque materials are understood to be materials capable of producing a relatively bright image on a fluoroscopy screen or another imaging technique during a medical procedure. This relatively bright image aids the user of the

catheter shaft **12** in determining its location. Some examples of radiopaque materials can include, but are not limited to, gold, platinum, palladium, tantalum, tungsten alloy, polymer material loaded with a radiopaque filler, and the like. Additionally, other radiopaque marker bands and/or coils may also be incorporated into the design of the catheter shaft **12** to achieve the same result.

[0071] In some embodiments, a degree of Magnetic Resonance Imaging (MRI) compatibility is imparted into the catheter shaft **12**. For example, the catheter shaft **12**, or portions thereof, may be made of a material that does not substantially distort the image and create substantial artifacts (e.g., gaps in the image). Certain ferromagnetic materials, for example, may not be suitable because they may create artifacts in an MRI image. The catheter shaft **12**, or portions thereof, may also be made from a material that the MRI machine can image. Some materials that exhibit these characteristics include, for example, tungsten, cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNEX®, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-NR and the like), nitinol, and the like, and others.

[0072] U.S. Patent Application Pub. No. US 2017/0252057 is incorporated herein by reference.

[0073] U.S. Patent Application Pub. No. US 2019/0209745 is incorporated herein by reference.

[0074] It should be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of steps without exceeding the scope of the disclosure. This may include, to the extent that it is appropriate, the use of any of the features of one example embodiment being used in other embodiments. The invention's scope is, of course, defined in the language in which the appended claims are expressed.

Claims

1. An aspiration medical device, comprising: a catheter shaft having an aspiration lumen defined therein; an aspiration member disposed within the aspiration lumen, the aspiration member having a plurality of fluid openings formed therein; wherein at least one of the plurality of fluid openings is angled proximally; and a wall support region disposed along the catheter shaft at a position opposite at least one of the plurality of fluid openings, the wall support region being configured to support the integrity of the catheter shaft when fluid is passed through the plurality of fluid openings.
2. The aspiration medical device of claim 1, wherein at least one of the plurality of fluid openings is oriented in a direction that is substantially normal to a longitudinal axis of the aspiration member.
3. The aspiration medical device of claim 1, wherein the plurality of fluid openings includes a first fluid opening and a second fluid opening disposed distally of the first fluid opening, wherein the first fluid opening is angled proximally, and wherein the second fluid opening is oriented in a direction that is substantially normal to a longitudinal axis of the aspiration member.
4. The aspiration medical device of claim 1, wherein a collar is disposed along the aspiration member.
5. The aspiration medical device of claim 4, wherein the collar includes a fluid opening support region disposed adjacent to at least one of the plurality of fluid openings.
6. The aspiration medical device of claim 4, wherein the collar includes the wall support region.
7. The aspiration medical device of claim 1, wherein the aspiration member has a closed distal end.
8. The aspiration medical device of claim 1, wherein the catheter shaft has an open distal end.
9. The aspiration medical device of claim 1, wherein at least some of the plurality of fluid openings are circumferentially offset from one another.
10. A medical device, comprising: a catheter shaft having an aspiration lumen defined therein; a fluid infusion tube disposed within the aspiration lumen, the fluid infusion tube having a first fluid opening formed therein and a second fluid opening formed therein that is axially spaced from the first fluid opening; and wherein the catheter shaft includes a support region extending along a position opposite the first fluid opening, the support region being configured to support the catheter

shaft when fluid is passed through the first fluid opening.

11. The medical device of claim 10, wherein the first fluid opening is angled proximally.

12. The medical device of claim 10, wherein the first fluid opening is oriented in a direction that is substantially normal to a longitudinal axis of the fluid infusion tube.

13. The medical device of claim 10, wherein the first fluid opening is angled proximally and wherein the second fluid opening is oriented in a direction that is substantially normal to a longitudinal axis of the fluid infusion tube.

14. The medical device of claim 10, wherein a collar is disposed along the fluid infusion tube.

15. The medical device of claim 14, wherein the collar includes a fluid opening support region disposed adjacent to the first fluid opening.

16. The medical device of claim 14, wherein the collar includes the support region.

17. The medical device of claim 10, wherein the catheter shaft has an open distal end.

18. The medical device of claim 10, wherein the first fluid opening and the second fluid opening are circumferentially offset.

19. An aspiration medical device, comprising: a catheter shaft having a distal end region, the catheter shaft including an open distal end and an outflow orifice disposed proximally of the open distal end; an aspiration member disposed within the catheter shaft, the aspiration member having a plurality of axially-spaced fluid jets formed therein including a first fluid jet and a second fluid jet disposed distally of the first fluid jet; wherein the first fluid jet is angled proximally; and a reinforcement disposed along the catheter shaft, the reinforcement being configured to support the catheter shaft when fluid is passed through the first fluid jet.

20. The aspiration medical device of claim 19, wherein the reinforcement is defined by a collar.
