

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277914

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

McLellan; Charles P. et al.

MOBILE DELIVERY DEVICE METHODS AND SYSTEMS

Abstract

A system and method for tracking mobile devices. The system can include a data center and a plurality of mobile devices in communication with the data center via the network. Each mobile device can include at least one sensor configured to periodically generate tracking data records, a memory, and a processor in communication with the at least one sensor and the memory. The mobile devices can transmit sets of tracking data records to the data center using reduced bandwidth relative to the original records by implement compression algorithms that can include delta encoding and/or numeric base conversion of number valued fields, as well as additional compression techniques that may be reversed at the data center to reconstruct the original records or otherwise decompress the data.

Inventors: McLellan; Charles P. (Fairfax, VA), Apgar; Collier C. (Washington, DC)

Applicant: United States Postal Service (Washington, DC)

Family ID: 76317856

Appl. No.: 19/212203

Filed: May 19, 2025

Related U.S. Application Data

parent US continuation 18745586 20240617 parent-grant-document US 12306317 child US 19212203

parent US continuation 17119990 20201211 parent-grant-document US 12019172 child US 18745586

us-provisional-application US 62946913 20191211

Publication Classification

Int. Cl.: G01S19/42 (20100101); **H04W4/02** (20180101); **H04W4/024** (20180101); **H04W4/029** (20180101)

U.S. Cl.:

CPC G01S19/42 (20130101); **H04W4/029** (20180201); H04W4/024 (20180201); H04W4/025 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] Any applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57. This application is a continuation of U.S. application Ser. No. 18/745,586, filed Jun. 17, 2024, which is a continuation of U.S. application Ser. No. 17/119,990, filed Dec. 11, 2020, now U.S. Pat. No. 12,019,172, issued Jun. 25, 2024, which claims the benefit of priority to U.S. Provisional Application Ser. No. 62/946,913, filed Dec. 11, 2019, entitled MOBILE DELIVERY DEVICE METHODS AND SYSTEMS, which is incorporated by reference herein in its entirety.

FIELD

[0002] This disclosure relates to systems and methods for mobile delivery devices, and in particular, to systems and methods for efficient transmission of information from the mobile device to a remote device, including mobile delivery device location coordinates and acceleration data.

BACKGROUND

[0003] Delivery services and corresponding routes are frequently serviced by carriers assisted by mobile delivery devices. Mobile delivery devices can include GPS or other location tracking functionality and may transmit related location data to a remote computer system for real-time tracking and/or analysis of the location data. In distribution networks employing a large number of carriers servicing a large number of routes simultaneously, the amount of location data being generated at the carriers' mobile delivery devices may be very large, and can be cumbersome, inefficient, and costly to transmit over a wireless network such as a cellular network, mobile data connection, etc.

SUMMARY

[0004] Methods and apparatuses or devices disclosed herein each have several aspects, no single one of which is solely responsible for its desirable attributes. Without limiting the scope of this disclosure, for example, as expressed by the claims which follow, its more prominent features will now be discussed briefly. After considering this discussion, and particularly after reading the section entitled "Detailed Description" one will understand how the described features provide advantages.

[0005] In a first aspect, a system for tracking one or more mobile devices in a distribution network comprises a data center in communication with a network and a plurality of mobile delivery devices in communication with the data center via the network. Each mobile delivery device comprises one or more sensors configured to periodically generate tracking data records, a memory, and a processor in communication with the one or more sensors and the memory. The processor is configured to receive the tracking data records from the one or more sensors; cause the received tracking data records to be stored in the memory; select, from the stored tracking data records, a set of tracking data records for compression; compress the set of tracking data records, by at least applying delta encoding or numeric base conversion to one or more number valued fields of at least a subset of the set of tracking data records, to generate a compressed data set; and

transmit the compressed data set to the data center via the network.

[0006] In some embodiments, the data center comprises a data store and a server in communication with the network and the data store, the server configured to receive the compressed data set via the network. In some embodiments, the server is further configured to decompress the compressed data set to generate a set of reconstructed tracking data records and cause the set of reconstructed tracking data records to be stored in the data store. In some embodiments, the server is further configured to cause the compressed data set to be stored in the data store and retrieve the compressed data set from the data store prior to decompressing the compressed data set. In some embodiments, the one or more sensors comprise a GPS receiver, and the tracking data records comprise GPRMC location data records. In some embodiments, the one or more sensors comprise an accelerometer, and the tracking data records comprise 3-axis acceleration data records. In some embodiments, the set of tracking data records is selected from the individual tracking data records based on a periodic schedule. In some embodiments, the processor is configured to transmit subsequent compressed data sets to the data center periodically at a predetermined time interval, and the processor is configured to select subsequent sets of tracking data records for compression at the predetermined time interval, each subsequent set comprising the tracking data records received since a preceding set of tracking data records was selected.

[0007] In a second aspect, a mobile device configured for efficient device tracking comprises a GPS receiver configured to periodically generate location data records and to transmit the location data records, a memory, and a processor in communication with the GPS receiver, the memory, and a wireless data network. The processor is configured to receive the location data records from the GPS receiver; cause the received location data records to be stored in the memory; select, from the stored location data records, a set of location data records for compression; compress the set of location data records by at least applying delta encoding and numeric base conversion to one or more number valued fields of at least a subset of the set of location data records, to generate a compressed location data set; and transmit the compressed location data set to a remote computing device via the wireless data network.

[0008] In some embodiments, the location data records generated by the GPS receiver are GPRMC records. In some embodiments, the compressed location data set comprises a set of compressed records having an average size of less than 10 bytes per record. In some embodiments, the delta encoding comprises replacing at least a time value, a latitude value, or a longitude value of each record in the subset with a delta value calculated based on a corresponding value in a preceding record. In some embodiments, the numeric base conversion comprises replacing at least one field value with one or more characters generated by converting the field value from a decimal value to a base-62 value. In some embodiments, compressing the set of location data records further comprises eliminating at least one field and at least one field separator from each record in the subset. In some embodiments, compressing the set of location data records further comprises deleting at least a date portion of a device time field each record in the subset.

[0009] In a third aspect, a mobile device configured for efficient device tracking comprises an accelerometer configured to periodically generate acceleration data records and to transmit the acceleration data records, a memory, and a processor in communication with the accelerometer, the memory, and a wireless data network. The processor is configured to receive the acceleration data records from the accelerometer; cause the received acceleration data records to be stored in the memory; select, from the stored acceleration data records, a set of acceleration data records for compression; compress the set of acceleration data records by at least applying delta encoding and numeric base conversion to at least a subset of the acceleration data records, to generate a compressed acceleration data set; and transmit the compressed acceleration data set to a remote computing device via the wireless data network.

[0010] In some embodiments, the acceleration data records generated by the accelerometer comprise a device time field and a 3-axis acceleration field. In some embodiments, applying the

delta encoding comprises replacing a value in the device time field of each record in the subset with a delta value calculated based on an entry in the device time field of a preceding record. In some embodiments, applying the numeric base conversion comprises replacing the delta value of each record in the subset with one or more Unicode characters corresponding to a hexadecimal value calculated based on the delta value. In some embodiments, applying the numeric base conversion comprises replacing each value in the 3-axis acceleration field of each record in the subset with an ASCII symbol corresponding to a 2-digit number calculated based on the value.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] These drawings and the associated description herein are provided to illustrate specific embodiments of the invention and are not intended to be limiting.

[0012] FIG. 1 is a block diagram schematically illustrating an example set of mobile devices in communication with a remote computer system.

[0013] FIG. 2 is a block diagram schematically illustrating components of an example mobile device.

[0014] FIG. 3 is a flow chart illustrating an example method of collecting and transmitting location data and/or acceleration data.

[0015] FIG. 4 is a flow chart illustrating an example method of compressing GPS location data records.

[0016] FIG. 5 is a flow chart illustrating a particular example algorithm for compressing location data records.

[0017] FIG. 6 is a flow chart illustrating a particular example algorithm for decompressing compressed GPRMC location data records.

[0018] FIG. 7 is a flow chart illustrating an example method of compressing acceleration data records.

DETAILED DESCRIPTION

[0019] The features, aspects, and advantages of the present development will now be described with reference to the drawings of several embodiments which are intended to be within the scope of the embodiments herein disclosed. These and other embodiments will become readily apparent to those skilled in the art from the following detailed description of the embodiments having reference to the attached figures, the development not being limited to any particular embodiment(s) herein disclosed.

[0020] The present disclosure relates to systems and methods for efficient handling and transmission of location data, including, for example, Global Positioning System (GPS) and/or accelerometer data. In some embodiments, the location and/or accelerometer data may be obtained at a mobile device such as a mobile delivery device carried by an item carrier of a distribution network. A distribution network may deliver and/or pick up items, such as mail pieces, letters, flats, magazines, periodicals, packages, parcels, and the like, over a large geographic area that is divided into one or more delivery routes. Modern distribution networks, such as the United States Postal Service (USPS), often utilize mobile delivery devices that are used by item carriers who pick up and deliver the items. The mobile devices may perform or facilitate a variety of functions, such as displaying instructions to the item carrier, scanning certain items at a time of delivery or pick up, and tracking the item carrier's progress along the item carrier's assigned route. In order to enable location tracking, mobile devices may include a GPS module that periodically determines GPS location records based on GPS satellite signals. A mobile device may store the determined GPS location records and transmit the records to a remote computing system, such as a central, regional, or local data center, server, or data store of the distribution network.

[0021] In some implementations, a distribution network may utilize a large number of mobile devices, and the amount of location data to be transmitted to the remote computing device of the distribution network may be large enough to be hampered by battery, hardware, software, and/or bandwidth issues which can impose significant costs or delays when the data is transferred over a wireless network, for example, over a cellular data network. In one example, a mobile device measures and collects GPS data and location coordinate data at a given periodicity, such as once a second, 10 times a second, or other periodicity. This periodicity generates a large amount of data. In some embodiments, the location coordinate data can be stored in an NMEA format such as the GPRMC record. In some embodiments, location coordinate data can be transmitted to a remote server at a frequency of once per second, once per minute, or at some other frequency. Due to demands of a wireless network, battery, hardware, bandwidth or the like, in some embodiments, location coordinate data can be recorded and/or sampled more frequently than the periodicity at which the data is transmitted to a remote computer or server. By taking location data more frequently than transmitting the location data, the amount of data transmitted can be reduced. However, this can result in an inaccurate or incomplete picture of the movement of a mobile computing device during a day. In some embodiments, the location coordinate data accumulated for a period of time can be sent to the remote server in a batch, for example, at the end of the day, or when a device is in wired communication with the remote server. In some embodiments, the location coordinates recorded for a period of time can be averaged and sent to a remote computer or server.

[0022] As an example, if a mobile device is used for approximately 8 to 10 hours over the course of one day, the mobile device collects between 28,800 and 36,000 data records. Raw location coordinate data, such as GPRMC records may vary in length, but are typically approximately 90 bytes long. Thus, 8 to 10 hours of use may result in between 2.6 MB and 3.24 MB of data that must be transferred to the remote computing system. In addition, location GPRMC data is not the only data that mobile devices are transmitting. They are also transmitting scan data, receiving notifications, and more. The distribution network may have many carriers. In the case of the USPS, there are more than 340,000 postal carriers. If each carrier's mobile device is generating data records and transmitting, the amount of data to be transmitted is very large. Accordingly, it may be desirable to reduce the amount of data to be transferred, while still sending the same number of GPS location coordinate data records and without unduly delaying the transfer of data to the remote computing system, or through compression, being able to send location coordinate data records at an increased frequency. Although the following example embodiments will be described with reference to mobile devices within a distribution network, it will be understood that the systems and methods described herein may equally be used for data compression in any mobile device.

[0023] FIG. 1 schematically illustrates components of a distribution network **100** including a plurality of mobile devices **110**. The distribution network **100** includes the plurality of mobile devices **110**, a server **140**, and a data store **150**. The distribution network **100** may include any number of mobile devices **110** suitable for the scale of operation of the distribution network. For example, an interstate, nationwide, or international distribution network such as the United States Postal Service, may include hundreds of thousands of mobile devices **110**, some or all of which may be in simultaneous operation as item carriers pick up and deliver items.

[0024] The mobile devices **110** include a GPS receiver or other receiver configured to receive signals from GPS satellites **120** or other radionavigation-satellite service (RNSS) signal. The mobile devices **110** are further in communication with a remote server **140** or other remote computing system, such as a central, regional, or local data center, via a wired or wireless network **130**. The remote server **140** is in communication with a data store **150** which may store GPS data, accelerometer data, and/or other location or utilization data received at the server **140** from the mobile device **110**. The server **140** may further be configured to process GPS or accelerometer data received from the mobile devices **110**. For example, if data received at the server **140** is

compressed as will be described in greater detail herein, the server **140** may be configured to perform one or more extraction or decompression algorithms prior to and/or subsequent to storing the data in the data store **150**. In some embodiments, the data store **150** may store the GPS or accelerometer data in a compressed format such that other downstream systems accessing the data may individually extract or decompress the data, further reducing the processing workload on the server **140**.

[0025] FIG. **2** is a block diagram schematically depicting example components of a mobile device **110**. The mobile device **110** may be, for example, any one of the mobile devices **110** illustrated in FIG. **1**. In some embodiments, the mobile device **110** can include a system hub **160**, a GPS receiver **164**, an accelerometer **168**, a display **172**, an input device **176**, a communications device **180**, and a camera **184**.

[0026] The system hub **160** may comprise or be a component of a processing system implemented with one or more processors. The system hub **160** may include a network of interconnected processors. The one or more processors may be implemented with any combination of general-purpose microprocessors, microcontrollers, digital signal processors (DSPs), field programmable gate arrays (FPGAs), programmable logic devices (PLDs), controllers, state machines, gated logic, discrete hardware components, dedicated hardware finite state machines, or any other suitable entities that may perform calculations or other manipulations of information. The system hub **160** may comprise a processor **161** such as, for example, a microprocessor an ARM or MIPS® processor, a Qualcomm Snapdragon® processor, a microcontroller, an Intel single or multiple core processor, such as i9®, i7®, i5®, or i3® processors, Apple A12, A14, etc. processors, Exynos processor, AMD Ryzen®, Phenom®, Athlon®, A-series®, or FX® processor, or the like. The processor **161** typically has conventional address lines, conventional data lines, and one or more conventional control lines. The processor **161** may be in communication with a processor memory **162**, which may include, for example, RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. The processor memory **162** may include, for example, software, at least one software module, instructions, steps of an algorithm, or any other information. In some embodiments, the processor **161** performs processes in accordance with instructions stored in the processor memory **162**. These processes may include, for example, controlling features and/or components of the mobile device **110**, and controlling access to and from, and transmitting information and data to and from the system hub **160** and the constituent components of the mobile device **110**, as will be described herein.

[0027] The system hub **160** comprises a system memory **163**, configured to store information, such as data received from the GPS receiver **164**, the accelerometer **168**, the input device **176**, the communications device **180**, and/or the camera **184**. The system memory **163** may comprise a database, a comma delimited file, a text file, or the like. The system hub **160** is configured to coordinate and direct the activities of the components of the mobile device **110**.

[0028] In some embodiments, the processor **161** is connected to a communication feature **165**. The communication feature **165** is configured for wired and/or wireless communication. In some embodiments, the communication feature **165** communicates via telephone, cable, fiber-optic, or any other wired communication network. In some embodiments, the communication feature **165** may communicate via cellular networks, WLAN networks, or any other wireless network. The communication feature **165** is configured to receive instructions and to transmit and receive information among components of the mobile device **110**, and in some embodiments, with a remote server (not shown) or the databases, or other resources outside the mobile device **110**, as desired.

[0029] In some embodiments, the various components of the mobile device **110** such as the GPS receiver **164**, the accelerometer **168**, the display **172**, the input device **176**, the communications device **180**, or the camera **184** can be configured to use the processor **161**, processor memory **162**, system memory **163**, or communications feature **165** or other components of the mobile device

system hub **160**, or to have their own memory, processor, system memory, or communications feature or other components as desired.

[0030] The GPS receiver **164** is in communication with GPS satellites and can discover the specific location of the mobile device **110** through its communications with the GPS satellites **120** as shown in FIG. **1**. In some embodiments the GPS receiver **164** uses other position determining systems to determine its exact location, such as GLONASS, COMPASS, multilateration, Wi-Fi detection, triangulation, or LORAN. In some embodiments, the GPS receiver **164** records the location of the mobile device **110** periodically, such as at a specific time interval (e.g., at 0.01 seconds, 0.1 seconds, every 0.5 seconds, every second, every 2 seconds, every 5 seconds, every 10 seconds, every 30 seconds, every 60 seconds, or at any other suitable time interval). When the GPS receiver **164** determines the location of the mobile device **110**, the GPS receiver **164** creates a location data record which is stored in internal memory of the GPS receiver **164** and/or in the system memory **163**. In some embodiments, the system memory **163** stores a database file, comma delimited file, or text file of location data records, and the GPS receiver **164** may cause an additional location data record to be added to the file of location data records each time the GPS receiver **164** determines the location of the mobile device **110**. The location data records may be stored in accordance with any suitable location data record format, for example, an NMEA format such as GPRMC records.

[0031] The accelerometer **168** is configured to measure acceleration of the mobile device **110**. In some embodiments, the accelerometer **168** is configured to measure acceleration in three dimensions, such as x, y, and z axes. In some embodiments, the accelerometer can be or include a gyroscope. The accelerometer **168** may be any suitable type of accelerometer as commonly included in consumer electronic devices. In some embodiments, the accelerometer **168** records the measured acceleration of the mobile device **110** periodically, such as at a specific time interval (e.g., every 0.05 seconds, every 0.1 seconds, every 0.5 seconds, every second, or at any other suitable time interval). When the accelerometer **168** determines the acceleration of the mobile device **110**, the accelerometer **168** creates an acceleration data record which is stored in internal memory of the accelerometer **168** and/or in the system memory **163**. In some embodiments, the system memory **163** stores a database file, comma delimited file, or text file of acceleration data records, and the accelerometer **168** may cause an additional acceleration data record to be added to the file of acceleration data records each time the accelerometer **168** determines the acceleration of the mobile device **110**. The acceleration data records may be stored in a format that stores x, y, and z-axis acceleration values in association with a device time corresponding to the acceleration measurement.

[0032] In some embodiments, the mobile device **110** can also include a display **172**. In some embodiments, display **172** is a display screen, touch screen, or other method of displaying information. In some embodiments, the display **172** can display information to the user. For example, the display **172** can display information to alert or instruct an item carrier, information to instruct the item carrier regarding a delivery or pickup location, or the like.

[0033] In some embodiments, the mobile device **110** can also include an input device **176**. The input device **176** can be a key board, touch screen, or the like. For example, a touch screen may comprise both the display **172** and the input device **176**. The input device **176** can be used by the user of the mobile device **110**, such as an item carrier, to control the operations of the mobile device **110**.

[0034] In some embodiments, the mobile device **110** can also include a communications device **180**. In some embodiments, the communications device **180** may communicate via cellular networks, WLAN networks, or any other wireless or wired network. The communications device **180** can be used to receive or send information to the server **140** of FIG. **1**, or any other remote computing system that the mobile device **110** may need to communicate with. For example, the communications device **180** may be used to periodically send GPS location data and/or acceleration data from the system memory **163** to the server **140** (e.g., once per second, every 5

seconds, every 10 seconds, every 30 seconds, every minute, every two minutes, every five minutes, every 10 minutes, or any other suitable time interval).

[0035] In some embodiments, the mobile device **110** can also include a camera **184**. In some embodiments, camera **184** can be used to capture images. Images may be stored in the system memory **163**. In some embodiments, the camera **184** can be used to scan barcodes, QR codes, or other visual identifiers, such as on labels affixed to items being picked up or delivered. The mobile device **110** can then use this information to identify items that are being delivered or picked up. In some embodiments, the mobile device **110** can use a dedicated scanner instead of the camera to scan barcodes, QR codes, or other visual identifiers.

[0036] FIG. **3** is a flow chart illustrating an example method **300** of collecting and transmitting location data and/or acceleration data. The method **300** may be performed by any mobile device capable of obtaining and transmitting location data and/or acceleration data. For example, the method **300** may be performed by the mobile device **110** of FIGS. **1** and **2**. The method **300** may be performed repeatedly any number of times as data is collected. For example, the mobile device **110** may perform the method **300** once over each time period corresponding to the time interval of data reporting (e.g., once per minute if the mobile device **110** is configured to transmit data to a remote computing system such as the server **140** once per minute).

[0037] The method **300** begins at block **305**, when a mobile device **110** begins collecting location data and/or acceleration data. For example, the mobile device **110** may begin collecting location data and/or acceleration data when it is powered on for the first time on a particular day, when an item carrier begins a route while carrying the mobile device **110**, or at any other time. In some embodiments, the mobile device **110** may be configured to automatically begin collecting location data and/or acceleration data based on the movement or location of the mobile device **110**, or the mobile device may begin collecting data at block **305** in response to an input received at the input device **176** such as a button or touchscreen input from the item carrier in possession of the mobile device **110**. When the mobile device **110** has begun collecting location data and/or acceleration data, the method **300** continues to block **310**.

[0038] At block **310**, the mobile device **110** determines the location coordinates of the mobile device **110**, and/or records acceleration information for the mobile device **110** using the accelerometer **168**. Location data may be determined by the GPS receiver **164** based on signals received from one or more satellites **120**. Acceleration data may be determined by the accelerometer **168** based on acceleration measured at one or more sensors within the accelerometer **168**. Location data and/or acceleration data may be sent from the GPS receiver **164** and/or the accelerometer **168** to the system memory **163**. In some embodiments, the determined GPS location data sent from the GPS receiver to the system memory **163** may be in a standard GPS data format, such as an NMEA format (e.g., a GPRMC record). The acceleration data may include one or more directional acceleration quantities, such as x-, y-, and z-direction acceleration values (e.g., in m/s² or other suitable acceleration unit), as well as a device timestamp corresponding to a device time of the mobile device **110** when the acceleration measurement was determined. When location data and/or acceleration data has been determined, the method **300** continues to block **315**.

[0039] At block **315**, the mobile device **110** creates a record corresponding to the determined location data or acceleration data. For example, a component of the mobile device **110** such as the processor **161** may cause an entry to be added to a location data log file (e.g., a database file, comma delimited file, text file, or the like) or to an acceleration data log file (e.g., a database file, comma delimited file, text file, or the like) stored in the system memory **163**. The new log file entry corresponding to the newly determined acceleration or location data record may be added as an additional record in a database file, as one or more comma delimited values appended to the end of a text file, etc., such that the item of location data or acceleration data determined at block **310** is stored as the most recent item in the corresponding log file in the system memory **163**. After the record has been created, the method **300** may return to block **310** to determine the next location

data point or acceleration data point. After repeating blocks **310** and **315** for a suitable time period, the method **300** continues to block **320**.

[0040] At block **320**, the mobile device **110** determines that a data transmission is indicated. The mobile device **110** may determine that a transmission is indicated in accordance with a predetermined data reporting time interval. For example, the mobile device **110** may determine that a transmission is indicated when the predetermined time interval has elapsed since the last transmission of location data or acceleration data (e.g., a mobile device **110** configured to transmit location data every minute may determine that a transmission is required at block **320** when one minute has elapsed since a timestamp associated with the most recent location data transmission). In some embodiments, the mobile device **110** may determine that a transmission is indicated based on a count of location data or acceleration data records. For example, the processor **161** of a mobile device **110** configured to determine the device location and create a record every second may increment a record counter each time a record is added to a log file at block **315**, and may determine that a transmission is indicated at block **320** each time the counter reaches a multiple of 60 so as to initiate a transfer every minute. When the mobile device **110** determines that a transmission is indicated, the method **300** continues to sub-process **325**. In some embodiments, the data transmission is indicated at a given time based on a clock signal. In some embodiments, the data transmission can be indicated each time location and/or acceleration data is recorded.

[0041] At sub-process **325**, the mobile device **110** compresses the records that will be transmitted. As will be described in greater detail with reference to FIGS. **4-7**, the mobile device **110** may compress the location data and/or acceleration data records by various methods that reduce the number of bytes to be transmitted. If the log file includes records obtained prior to the previous data transmission, the mobile device may isolate only the new records that have been added to the log file since the initiation of the previous data compression and transmission. When the records to be transmitted have been compressed at sub-process **325**, the method **300** continues to block **330**.

[0042] At block **330**, the method **300** terminates as the mobile device **110** transmits data to a remote computing system. The transmitted data includes the compressed location data and/or acceleration data. The remote computing system may be, for example, the server **140** illustrated in FIG. **1**. The mobile device **110** may transmit the data to the remote computing system by any suitable wired or wireless transmission method, such as using a cellular data network, via the internet or any other suitable public or private network. The mobile device **110** may continue repeating the method **300** indefinitely to continue collecting, storing, compressing, and transmitting location data and/or acceleration data.

Location Data Compression

[0043] As described above, mobile devices such as the mobile devices **110** of the distribution network **100** may determine GPS location data records, and may send the GPS location data to a remote computing device such as the server **140** and/or the data store **150** of the distribution network **100**. In some example implementations, such as for mobile devices carried by distribution network item carriers, the mobile devices may generate large amounts of GPS data each day storing location data as GPRMC records. However, it may be desirable to transmit most or all records to a remote computing system while limiting the total amount of data transferred, such as to less than one megabyte or a fraction thereof (e.g., less than 500 kilobytes, less than 250 kilobytes, etc.) per day.

[0044] Accordingly, the GPS information may be compressed in order to reduce the amount of data required to send large numbers of GPS location information points from a mobile device to a remote computing system. In some aspects, the mobile devices **110** of the distribution network **100** may automatically perform such GPS data compression. In various embodiments, the data compression methods described herein may be performed continuously, such as for each GPS record as it is captured, may be performed periodically on a set of GPS data records, such as every 10 seconds, every 30 seconds, every minute, every 5 minutes, every 10 minutes, or at any other

suitable time interval. In other embodiments, the compression of GPS data may be performed on an event-based schedule. For example, GPS records may be determined and stored at a mobile device in a standard format such as the NMEA format until a set of records are to be sent to the remote computing device, and the full set of records may be compressed shortly before the transmission of GPS data occurs. The compression methods described herein may reduce location coordinate data records or other data records from an average size of approximately 90 bytes per record to an average size of approximately 9.14 bytes per record, such that 8-10 hours of GPRMC records obtained at a rate of one record per second will result in only 263 kilobytes to 329 kilobytes of data. Further compression may be achieved using data compression methods such as GZIP or the like.

[0045] An example set of data records is provided in Table 1 below. The set of six data records provided in Table 1 is relatively small and is provided for illustrative purposes. It will be understood that significantly larger data sets, including tens, hundreds, thousands, or millions of records, or more, may be compressed using the same methods disclosed herein.

TABLE-US-00001 TABLE 1 Example data records Aug. 2, 2018

15:59:46.228|\$GPRMC,155949.00,A,2756.93981,N,08229.49572,W,0.004,,020818,,,D*65| Aug. 2, 2018 15:59:47.223|\$GPRMC,155950.00,A,2756.93979,N,08229.49572,W,0.018,,020818,,,D*67| Aug. 2, 2018

15:59:48.234|\$GPRMC,155951.00,A,2756.93977,N,08229.49573,W,0.037,,020818,,,D*64| Aug. 2, 2018 15:59:49.233|\$GPRMC,155952.00,A,2756.93971,N,08229.49572,W,0.061,,020818,,,D*63| Aug. 2, 2018

15:59:50.226|\$GPRMC,155953.00,A,2756.93965,N,08229.49568,W,0.018,74.91,020818,,,D*62| Aug. 2, 2018

15:59:51.236|\$GPRMC,155954.00,A,2756.93961,N,08229.49574,W,0.018,359.52,020818,,,D*6D|

[0046] The fields included in each GPRMC data record are provided in Table 2 below. Note that some fields may be omitted from any particular GPRMC data record.

TABLE-US-00002 TABLE 2 Data record fields

Field Name	Description	Format	Device	Time
Local time of device (hour/minute/second)	mm-dd-yyyy hh:mm:ss.sss	Record Type	NMEA	GPS
record type	\$GPRMC	UTC Time	Time of fix in UTC (hour/minute/second)	hhmmss.ss
Validity	Whether GPS fix is valid	A = valid, V = invalid, NULL	Latitude	Latitude of GPS fix (degrees/minutes) ddm.mmmmm
North/South	Northern or Southern hemisphere	N = north, S = south, NULL	Longitude	Longitude of GPS fix (degrees/minutes) ddm.mmmmm
East/West	Eastern or Western hemisphere	E = east, W = west, NULL	Speed	Ground speed (knots) Decimal (6, 3), NULL
Course	Direction of travel (degrees)	Decimal (5, 2), NULL	UTC Date	Date of fix in UTC (day/month/year) ddmmyy
Variation	Magnetic variation (degrees)	Decimal (5.2), NULL	Variation E/W	Direction of magnetic variation E = east, W = west, NULL
Mode	GPS fix mode	N = data not valid A = autonomous mode D = differential mode E = estimated mode	Checksum	Record checksum *##

[0047] FIG. 4 is a flow chart illustrating an example method 400 of compressing GPS location data records. The method 400 may be performed by any mobile device capable of obtaining and transmitting location data. For example, the method 400 may be performed by the mobile device 110 of FIGS. 1 and 2. The method 400 may be performed repeatedly any number of times as data is collected. For example, the mobile device 110 may perform the method 400 once each time a set of collected data is prepared for transmission. In some embodiments, the method 400 may be performed as subprocess 325 of the method 300 described above with reference to FIG. 3.

[0048] The method 400 begins at block 405, when GPS data compression is initiated. In some embodiments, GPS data compression may be initiated in the context of method 300 described above with reference to FIG. 3. For example, GPS data compression may be initiated when the method 300 proceeds to subprocess 325. When GPS data compression has been initiated, the method 400 continues to block 410.

[0049] At block 410, GPS data records are prepared for compression. The processor 161 or other

component of the mobile may transform a list or table of raw GPS data records using one or more preparation steps, for example, to reduce the number of fields in each record, eliminate unnecessary information (e.g., information that is not intended to be collected and/or information that is the same for all records in the set), reduce the number of different characters used, or the like. In some embodiments, the processor **161** receives a set of data records and performs one or more of the following example data preparation steps. In one example, the processor **161** identifies and removes from the set all records in the set having a “V” or NULL value in the Validity field (e.g., all records that do not have an “A” in the validity field). Because only “A” records contain valid GPS data, the records having a “V” or NULL Validity value need not be transmitted with the GPS data. In another example, the Record Type field may be deleted from all records, as all records in the set are set as the same type, e.g., GPRMC type records, rendering the \$GPRMC string redundant. In another example, the Speed field and/or the Course field may be rounded to a desired decimal place, such as to decimal (4,1) (e.g., to the nearest 1/10 knot or 1/10 degree) and NULL values may be replaced with “0”, as the additional precision provided by three decimal places may be unnecessary. In another example, the Variation and Variation E/W fields may be deleted from all records, for example, in the case of a mobile device **110** that is not configured to capture magnetic variation data. In another example, the vertical bar field separator (“|”) may be replaced with a comma or a semicolon (e.g., may be replaced by a comma between the Device Time and Record Type fields, and by a semicolon at the end of each record). In another example, the original checksum value may be deleted from the end of each record. Because each record is being modified, the original checksum becomes invalid, and may be replaced by a new checksum at the end of the GPS data compression, if desired. The example block of data records of Table 1, as transformed by performance of all of the example steps above, is shown in Table 3 below.

TABLE-US-00003 TABLE 3 Example data records following data preparation Aug. 2, 2018

15:59:46.228,155949.00,A,2756.93981,N,08229.49572,W,0,,020818,D; Aug. 2, 2018
 15:59:47.223,155950.00,A,2756.93979,N,08229.49572,W,0,,020818,D; Aug. 2, 2018
 15:59:48.234,155951.00,A,2756.93977,N,08229.49573,W,0,,020818,D; Aug. 2, 2018
 15:59:49.233,155952.00,A,2756.93971,N,08229.49572,W,0.1,,020818,D; Aug. 2, 2018
 15:59:50.226,155953.00,A,2756.93965,N,08229.49568,W,0,74.91,020818,D; Aug. 2, 2018
 15:59:51.236,155954.00,A,2756.93961,N,08229.49574,W,0,359.52,020818,D;

[0050] Accordingly, the more compact record format for the prepared GPS data in the example of Table 3 above is provided in Table 4 below.

TABLE-US-00004 TABLE 4 Prepared data record fields

Field Name	Description	Format	Device
Time	Local time of device (hour/minute/second)	mm-dd-yyyy hh:mm:ss.sss	UTC Time
Time	Time of fix in UTC (hour/minute/second)	hhmmss.ss	Validity
Validity	Whether GPS fix is valid	A = valid, V = invalid, NULL	Latitude
Latitude	Latitude of GPS fix (degrees/minutes)	ddmm.mmmmm	North/South
North/South	Northern or Southern hemisphere	N = north, S = south, NULL	Longitude
Longitude	Longitude of GPS fix (degrees/minutes)	ddmm.mmmmm	East/West
East/West	Eastern or Western hemisphere	E = east, W = west, NULL	Speed
Speed	Ground speed (knots)	Decimal (6, 3), NULL	Course
Course	Direction of travel (degrees)	Decimal (5, 2), NULL	UTC Date
UTC Date	Date of fix in UTC (day/month/year)	ddmmyy	Mode
Mode	GPS fix mode	N = data not valid A = autonomous mode D = differential mode E = estimated mode	

[0051] When the raw data records have been prepared for compression, the method **400** continues to block **415**.

[0052] At block **415**, the processor **161** applies delta encoding to further reduce the size of the GPS data records. Some or all of the fields having numerical values may be converted from their original values to differential values calculated relative to the preceding record. For example, the number valued fields of the first record in the set of records may be left as whole values to serve as a starting point from which the delta values are calculated. In various embodiments one or more, up to all, of the numerical values in the GPS records may be compressed using delta encoding. In the example prepared GPS data records of Table 3 above, the Device Time, UTC Time, Latitude,

Longitude, Speed, Course, and UTC Date fields all have numerical values and can be converted to smaller delta values using delta encoding. Additionally, the decimal points in decimal values may be shifted such that each delta value is stored as an integer value to further simplify the records. In an example algorithm in which all numerical fields other than course are modified by delta encoding and decimal values are converted to integers, the prepared GPS data records of Table 3 would be converted to the delta encoded format provided in Table 5 below. In the example records of Table 5, spaces are inserted following certain entries and prior to the following comma delimiting characters. These extra spaces are included for illustrative clarity, to vertically align corresponding record fields, and may not be present in actual delta encoded records produced in accordance with the present technology. For example, although the record in line 2 of Table 5 is shown as [0053] “995, 100, A, -20, N, W, 0, D;” the corresponding record may be stored as “995, 100, A, -20, N, W, 0, D;” in an actual implementation.

TABLE-US-00005 TABLE 5 Example data records following delta encoding Aug. 2, 2018

15:59:46.228,155949.00,A,2756.93981,N,08229.49572,W,0 , , 020818,D; 995 ,100 ,A,-20 ,N, ,W,0 , , ,D; 1011 ,100 ,A,-20 ,N,10 ,W,0 , , ,D; 999 ,100 ,A,-60 ,N,-10 ,W,1 , , ,D; 993 ,100 ,A,-60 ,N,-40 ,W,-1,749 , , ,D; 1010 ,100 ,A,-40 ,N,60 ,W,0 ,3595, ,D;

[0054] In some embodiments, it may be desirable not to use delta encoding with regard to the course value because the course value often is not necessarily recorded for every data record, and thus frequently is not present. When present, the course value may change significantly from one value to the next. In the example data of Table 5, the total amount of data in the reduced records is about $\frac{1}{3}$ the size of the original GPS data records as shown in Table 1. When the GPS data records have been delta encoded, the method **400** continues to block **420**.

[0055] In some embodiments, encoding of the data can be accomplished using methods in addition to or instead of delta encoding. For example, one GPS location data point from Table 3 has a value of 2756.93981, N, 08229.49572, W. This can be read to mean 27 degrees 56.93981 minutes, or 56 minutes, 56.3886 seconds. In order to reduce the amount of data transmitted to the server **140**, the processor **161** can encode the data using a truncation feature. For example, one degree of latitude is about 69 miles, one minute of latitude is 6068 feet, or 1.15 miles. One-tenth of a minute of latitude is equal to 60.68 feet, and one second of latitude equals 80 feet. The distance between longitude lines varies from north to south.

[0056] A carrier may traverse a fixed route, or may follow a route that stays mainly or entirely within a geographic area. The geographic area in which a carrier operates may not include any minute lines, or degree lines. In this case, the minutes field of the GPS location may not change regardless of where in the area the carrier goes. In other geographic areas, a minute line, or a degree line may run through the geographic area, and a carrier may cross the minute or degree line one or more times as the carrier traverses a route. In this case, the degrees and/or minutes would change each time the carrier crosses the line.

[0057] The processor **161** can analyze a carrier's route, and/or the geographic area in which the carrier travels, and identify latitude and longitude lines that the carrier is likely to cross, or is unlikely to cross. For example, if a carrier does not cross a particular minute line of latitude or longitude throughout the route, the degrees and minutes fields in the GPS data will not change for any location on the route. So, if the carrier is assigned to a route which includes the GPS location 2756.93981 N, 8229.49572 W, the carrier may not cross the 27 degree line, as the 28 degree line is about 69 miles away, and the carrier's route does not travel that far. In that case, the processor **161** can, for a given mobile delivery device in a known area, omit the numeral places which do not change over the route. So, in this example, the processor **161** in step **415**, can truncate the 27 in the degree's place, as it will not change. The “27” in the latitude coordinate, or whatever values do not change, for the given mobile device degrees can be transmitted an initial time when the mobile delivery device is first operated on the route, or the server **140** can determine what the degrees for

the GPS location would be based on the identity of the mobile device assigned to a given route. The same process can occur for the minutes place, e.g., the “56” in the latitude example above, or for any other digits in the latitude or longitude measurements.

[0058] In some embodiments, the mobile device can determine whether a particular line of latitude or longitude will be crossed, once or frequently, as a carrier travels an assigned route based on input regarding the carrier's route. For example, in some embodiments, when a carrier logs in to a mobile computing device, or when a carrier identifies a route to be travelled via the input device **176**, the route information for that route can be obtained from the memory **162** or from a remote system. The route information received can include the latitude/longitude values or other coordinate values for the extreme ends of the route, or the extremes of travel between the most distant points on the route, both in a north-south direction and in an east-west direction. If between the most distant points there is a major line latitude or longitude, such as a degree line or a minute line, the processor **161** can determine whether to truncate or exclude the value in the degree's place, the minute's place, etc. The location data transmitted from the processor **161** can include a message that the degree line or minute line is the same for each data record and will only transmit that value once. In some embodiments, the processor **161** can check each record for a change in the degree's place or the minute's place. If no change occurs, the prepared record can truncate the degrees or minutes place for the records where that value does not change. When the value does change, the processor **161** can include the changed value in the next record.

[0059] In some embodiments, where a device frequently crosses a degree or minute line, such as the 27 degrees or 56 minutes in the latitude example above, the 56 may not be truncated, but may still be reduced, converted, and transmitted to the server **140** as described herein.

[0060] In some embodiments, the truncation or adjustment of GPS location data described herein can be performed prior to performing delta encoding as described above.

[0061] At block **420**, the processor **161** implements further data reduction by removing one or more fields from the delta encoded GPS data records. The fields removed at block **420** may be removed because they are not necessary and/or redundant. In some embodiments, the UTC Time field may be deleted from the delta encoded records, as its value for any of the records may be reproduced based on the corresponding Device Time entries and the UTC Time entry in the initial record. For the same reason, in some embodiments, the Device Time field may be removed from the delta encoded records rather than the UTC Time entry. In another example, the Validity field may be removed, as only type “A” valid records remain in the data set following the data preparation operations of block **410**. In another example, the North/South, East/West, and/or UTC Date fields may be removed, as their values may be reproduced based on the series of delta encoded Latitude, Longitude, and Device Time or UTC Time entries and the corresponding entries in the initial record. In an example algorithm in which the UTC Time, Validity, North/South, East/West, and UTC Date fields are all removed from the delta encoded records, the delta encoded records of Table 5 would be converted to the field reduced format provided in Table 6 below. Similar to Table 5, spaces are inserted for clarity of illustration.

TABLE-US-00006 TABLE 6 Example data records following field reduction Aug. 2, 2018

15:59:46.228,155949.00,A,2756.93981,N,08229.49572,W,0,,020818,D; 995,-20,0,0,,D;
1011,-20,10,0,,D; 999,-60,-10,1,,D; 993,-60,-40,-1,749,,D; 1010,-40,60,
0,3595,,D;

[0062] Thus, following field reduction at block **420**, the data set includes an initial record in the original prepared format as produced at block **410**, followed by a series of delta encoded records each including a total of six fields: Device Time, Latitude, Longitude, Speed, Course, and Mode. When the fields of the delta encoded records have been reduced, the method **400** continues to block **425**.

[0063] At block **425**, the processor **161** applies numeric base conversion and value mapping to the numerical value fields to further reduce the size of the GPS data records. In one example base

appropriate, the method **400** continues to block **435**.

[0068] At block **435**, the method **400** terminates as the processor **161** produces the final data set for transmission. In some embodiments, the processor **161** computes a new checksum for each record to preserve the integrity of the reduced records and to replace the original checksums in the GPRMC data, which were eliminated at block **410**. Various checksum processes, such as a CRC32 checksum or any other suitable checksum process may be used. Each checksum may be appended at the end of the corresponding record in the data set. In some embodiments, the new checksum for each record may be computed based on a previous version of the record, rather than based on the final record for transmission. For example, in some embodiments the new checksum is calculated based on prepared records generated at block **410** (e.g., the records shown in Table 3), such that the checksum serves as confirmation of the accuracy both for the compression steps of blocks **415-425** and for any subsequent reconstruction performed on the transmitted data. In addition, the processor **161** may perform one or more other compression methods, such as using GZIP or another known data compression protocol, in finalizing the set of GPS data records for transmission.

[0069] FIG. 5 is a flow chart illustrating a particular example algorithm **500** for compressing location data records. The algorithm **500** illustrated in FIG. 5 is associated with the method **400** of FIG. 4, and includes the example operations used to convert the initial data set of Table 1 into the final data set of Table 8. The algorithm **500** may be performed by any one or more components of a mobile device such as the mobile device **110**, for example, the processor **161** and/or any other circuitry of the mobile device **110**. In some embodiments, the processor **161** performs the algorithm **500** periodically before each time a GPS data transfer is scheduled to occur, such as once every 10 seconds, every 30 seconds, every minute, every hour, etc., based on the set of data records recorded at the mobile device **110** since the preceding data transfer. In the algorithm **500**, blocks **510** and **515** may correspond to preparing records at block **410** of the method **400**; block **520** may correspond to the delta encoding at block **415** of the method **400**; blocks **525**, **530**, **540**, and **545** may correspond to the data reduction, base conversion, and value mapping at blocks **425** and **430** of the method **400**; blocks **535**, **550**, and **555** may correspond to the elimination of field separators at block **430** of the method **400**; and blocks **560** and **565** may correspond to the production of a data set for transmission at block **435** of the method **400**.

[0070] FIG. 6 is a flow chart illustrating a particular example algorithm **600** for decompressing compressed GPRMC location data records. The algorithm **600** illustrated in FIG. 6 is consistent with a substantially reversed iteration of the algorithm **500** and/or of the method **400**, and is suitable for reconstructing a set of prepared data records after the compressed records are received from a mobile device. For example, the algorithm **500** would be suitable for reconstructing the set of prepared data records of Table 3, based on receiving the compressed data set of Table 8, optionally with a new checksum appended to each record. The algorithm **600** may be performed by any one or more computing devices in communication with the mobile device transmitting the compressed GPS data records. For example, in the distribution network example of FIG. 1, the algorithm **600** may be performed by the server **140** based on compressed GPS data received from any or all of the mobile devices **110**. In some embodiments, the server **140** causes the compressed records to be stored in the data store **150** in their compressed state for future reconstruction, or the server **140** may reconstruct the data records upon receipt and cause the reconstructed records to be stored in the data store **150**. In the algorithm **600**, blocks **605** and **610** may correspond to a reverse operation of operations performed in the final production of a data set for transmission at block **435** of the method **400**; blocks **615**, **620**, **630**, **635**, and **640** may correspond to an analysis of the compressed records accounting for the elimination of some field separators at block **430** of the method **400**; blocks **625** and **645** may correspond to a reverse operation of the base conversion and value mapping applied at block **425** of the method **400**; block **650** may correspond to reverse operations of the delta encoding and data reduction applied at blocks **415** and **420** of the method **400**; and blocks **655** and **660** may correspond to reverse operations of the record preparation at

block **410** of the method **400**.

Acceleration Data Compression

[0071] As described above, mobile devices such as the mobile devices **110** of the distribution network **100** may determine acceleration data records, and may send the acceleration data to a remote computing device such as the server **140** and/or the data store **150** of the distribution network **100**. In some example implementations, such as for mobile devices carried by distribution network item carriers, the mobile devices may generate a large quantity of acceleration data. For example, in some embodiments a mobile device **110** may be configured to obtain and record an acceleration data record from an accelerometer **168** or the like, periodically during operation, such as every 0.05 seconds, every 0.1 seconds, every 0.5 seconds, every second, etc. Thus, similar to GPS location data records, a mobile device **110** may generate up to several megabytes of acceleration data each day when the records are stored as full acceleration data records. However, it may be desirable to transmit all records to a remote computing system while limiting the total amount of data transferred, such as to less than one megabyte or a fraction thereof (e.g., less than 500 kilobytes, less than 250 kilobytes, etc.) per day.

[0072] Accordingly, the acceleration data may be compressed in order to reduce the amount of data required to send large numbers of acceleration data points from a mobile device to a remote computing system. In some aspects, the mobile devices **110** of the distribution network **100** may automatically perform such acceleration data compression. In various embodiments, the data compression methods described herein may be performed continuously, such as for each acceleration data record as it is captured, may be performed periodically on a set of acceleration data records, such as every 10 seconds, every 30 seconds, every minute, every 5 minutes, every 10 minutes, or at any other suitable time interval. In other embodiments, the compression of acceleration data may be performed on an event-based schedule. For example, acceleration data records may be determined and stored at a mobile device in a full or raw data record format until a set of records are to be sent to the remote computing device, and the full set of records may be compressed shortly before the transmission of acceleration data occurs. Further compression may be achieved using known data compression methods such as GZIP or the like.

[0073] An example set of raw acceleration data records is provided in Table 9 below.

TABLE-US-00009 TABLE 9 Example raw acceleration data records

Jan. 29, 2019 12:17:10.310	AccOutput: [X = 3, Y = 21, Z = -4]	Jan. 29, 2019 12:17:10.463	AccOutput: [X = 4, Y = 21, Z = -4]	Jan. 29, 2019 12:17:10.577	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:10.685	AccOutput: [X = 3, Y = 21, Z = -3]	Jan. 29, 2019 12:17:10.792	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:10.898	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:11.037	AccOutput: [X = 2, Y = 21, Z = -4]	Jan. 29, 2019 12:17:11.148	AccOutput: [X = 3, Y = 21, Z = -4]	Jan. 29, 2019 12:17:11.255	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:11.395	AccOutput: [X = 3, Y = 21, Z = -4]	Jan. 29, 2019 12:17:11.543	AccOutput: [X = 2, Y = 21, Z = -4]	Jan. 29, 2019 12:17:11.647	AccOutput: [X = 3, Y = 22, Z = -4]	Jan. 29, 2019 12:17:11.761	AccOutput: [X = 2, Y = 21, Z = -4]	Jan. 29, 2019 12:17:11.866	AccOutput: [X = 3, Y = 22, Z = -4]	Jan. 29, 2019 12:17:11.971	AccOutput: [X = 2, Y = 20, Z = -3]	Jan. 29, 2019 12:17:12.076	AccOutput: [X = 3, Y = 21, Z = -4]	Jan. 29, 2019 12:17:12.180	AccOutput: [X = 2, Y = 21, Z = -4]	Jan. 29, 2019 12:17:12.285	AccOutput: [X = 4, Y = 20, Z = -3]	Jan. 29, 2019 12:17:12.390	AccOutput: [X = 2, Y = 21, Z = -4]	Jan. 29, 2019 12:17:12.496	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:12.601	AccOutput: [X = 3, Y = 21, Z = -5]	Jan. 29, 2019 12:17:12.761	AccOutput: [X = 3, Y = 20, Z = -3]	Jan. 29, 2019 12:17:13.094	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:13.225	AccOutput: [X = 4, Y = 21, Z = -5]	Jan. 29, 2019 12:17:13.330	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 12:17:13.435	AccOutput: [X = 2, Y = 22, Z = -5]	Jan. 29, 2019 12:17:13.568	AccOutput: [X = 3, Y = 20, Z = -4]	Jan. 29, 2019 13:11:31.348	AccOutput: [X = 2, Y = 20, Z = -4]	Jan. 29, 2019 13:11:31.541	AccOutput: [X = 4, Y = 21, Z = -4]	Jan. 29, 2019 13:11:31.677	AccOutput: [X = 3, Y = 21, Z = -5]	Jan. 29, 2019 13:11:31.781	
----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	------------------------------------	----------------------------	--

|AccOutput: [X = 4, Y = 21, Z = -4] | Jan. 29, 2019 13:11:31.885 |AccOutput: [X = 3, Y = 20, Z = -4] | Jan. 29, 2019 13:11:31.989 |AccOutput: [X = 1, Y = 20, Z = -3] | Jan. 29, 2019 13:11:32.095 |AccOutput: [X = 3, Y = 21, Z = -4] | Jan. 29, 2019 13:11:32.198 |AccOutput: [X = 4, Y = 22, Z = -4] | Jan. 29, 2019 13:11:32.303 |AccOutput: [X = 2, Y = 20, Z = -4] | Jan. 29, 2019 13:11:32.407 |AccOutput: [X = 3, Y = 21, Z = -4] | Jan. 29, 2019 13:11:32.511 |AccOutput: [X = 4, Y = 20, Z = -3] | Jan. 29, 2019 13:11:32.616 |AccOutput: [X = 2, Y = 22, Z = -3] | Jan. 29, 2019 13:11:32.720 |AccOutput: [X = 3, Y = 21, Z = -4] | Jan. 29, 2019 13:11:32.824 |AccOutput: [X = 3, Y = 21, Z = -4] | Jan. 29, 2019 13:11:32.928 |AccOutput: [X = 3, Y = 21, Z = -4] |

[0074] The fields included in each raw acceleration data record are provided in Table 10 below. Note that some fields may be omitted from any particular acceleration data record.

TABLE-US-00010 TABLE 10 Acceleration data record fields

Field Name	Description	Format
Device Time	Local time of device	mm-dd-yyyy hh:mm:ss.sss (hour/minute/second)
3-axis m/s.sup.2	for each axis X = #, Y = #, Z = #	Acceleration between -31 and 32

[0075] FIG. 7 is a flow chart illustrating an example method **700** of compressing acceleration data records. The method **700** may be performed by any mobile device capable of obtaining and transmitting acceleration data. For example, the method **700** may be performed by the mobile device **110** of FIGS. 1 and 2. The method **700** may be performed repeatedly any number of times as data is collected. For example, the mobile device **110** may perform the method **700** once each time a set of collected data is prepared for transmission. In some embodiments, the method **700** may be performed as subprocess **325** of the method **300** described above with reference to FIG. 3.

[0076] The method **700** begins at block **705**, when acceleration data compression is initiated. In some embodiments, acceleration data compression may be initiated in the context of method **300** described above with reference to FIG. 3. For example, acceleration data compression may be initiated when the method **300** proceeds to subprocess **325**. When acceleration data compression has been initiated, the method **700** continues to block **710**.

[0077] At block **710**, the processor **161** implements data reduction to remove unnecessary and/or redundant portions of the raw acceleration data records. In the Device Time field, the date may be removed from the second record and all subsequent records, with the date remaining in the first record to serve as an anchor for the following records. In the 3-axis Acceleration field, “AccOutput: [X=”, “Y=”, “Z=”, and “]” may be removed from all records, as these portions of each 3-axis Acceleration entry are the same in every record and thus are not necessary. After the fields of the raw acceleration data records have been reduced, the method **700** continues to block **715**.

[0078] At block **715**, the processor **161** applies delta encoding to further reduce the size of the GPS data records. In some embodiments, only the Device Time field or both the Device Time and 3-axis Acceleration fields may be converted by delta encoding to reduce the size of each record. For Device Time, the field includes only a HH:MM:SS.SSS formatted time value following the data reduction at block **710**. Thus, the HH:MM:SS.SSS time value of each record may be converted to seconds and multiplied by 1000 to produce an integer value. The second record and all subsequent records may then be delta encoded by replacing the Device Time entry with the difference between the full Device Time entry and the full Device Time entry of the preceding acceleration data record. In the event of an entry lacking a Device Time entry timestamp, or having an inaccurate timestamp, the record may be omitted, and the following record may be kept in its reduced (non-delta encoded) format to serve as a new anchor for subsequent records. It will be understood that a similar delta encoding may be applied to the 3-axis Acceleration field, but delta encoding may be less useful for this field as the full range of possible values is from -31 to 32, such that the delta between consecutive acceleration values may include as many characters as the reduced value because device acceleration can often change frequently. When the acceleration data records have been delta encoded, the method **700** continues to block **720**.

[0079] At block **720**, the processor **161** applies numeric base conversion and value mapping to the Device Time and 3-axis Acceleration fields to further reduce the size of the GPS data records. In

one example base conversion method for the Device Time field, the processor **161** converts the time values to Unicode. In a first step, the processor **161** may first add a constant value such as 1000 to each of the delta encoded values. For example, a time difference of 5000 milliseconds would result in a value of 6000. Next, the processor **161** treats the new value directly as a hexadecimal value. For example, a value of 6000 in decimal becomes 0x6000, having a decimal value of 24576. Next, the processor **161** uses the hexadecimal value to generate the equivalent Unicode character corresponding to the decimal value of the hexadecimal value. For example, a value of 0x6000 would result in the generation of “custom-character”, corresponding to the decimal value 24576.

[0080] If the time difference value, alone or after addition of 1000 or other constant, is greater than 9999 (e.g., 10000 or greater), two Unicode characters may be used to represent the value. In this case, the four least significant (e.g., right-most) digits of the time difference value are directly translated into a new hexadecimal value as described above. For example, a value 266000 would have 6000 as the four least significant decimal digits. Thus, the least significant Unicode character for this value would be “custom-character” for 0x6000. Next, the significant decimal digits are shifted right by dividing by 10000, and any remainder from the division is dropped. For the example value of 266000, 266000/10000 becomes 26. The divided value is then treated as a hexadecimal value similarly (e.g., 0x26). The hexadecimal value is then converted to the Unicode value corresponding to the decimal equivalent of the hexadecimal value. In this case, the decimal equivalent of 0x26 is 38, and the corresponding Unicode value is “&”. The record then comprises the most significant Unicode character followed by the least significant Unicode character (e.g., “&custom-character” corresponding to decimal values of 38 and 24576).

[0081] In an example base conversion method for the 3-axis Acceleration field, a constant value may be added to the field entry for each record to make all values positive. For example, adding a constant such as 65 to each of the values that range from -31 to 32 would result in a positive value for each record. Moreover, the constant-added values are unique in that their minimum value is 34, greater than the largest value before the addition of a constant. Following addition of a constant to yield all positive numbers, each 2-digit 3-axis Acceleration field value can be converted to its corresponding ASCII symbol. When the acceleration data records have undergone base conversion and value mapping, the method **700** continues to block **725**.

[0082] At block **725**, the method **700** terminates as the processor **161** produces the final data set for transmission. In some embodiments, the processor appends the 3-axis Acceleration value to the end of the Device Time value to yield a reduced data set. For example, the raw acceleration data set of Table 10 above, processed using the method **700**, would yield the reduced set of acceleration data records as shown in Table 11 below.

TABLE-US-00011 TABLE 11 Reduced acceleration data records 1547764230310DV= DU>

custom-character EV= custom-character DU= custom-character DU= custom-character
EV< custom-character DV> custom-character DU= custom-character DU=
custom-character CW< custom-character DU= custom-character DU= custom-character
CV= custom-character CU= custom-character DV= custom-character EV=
custom-character DU= custom-character DV< ΔDV= custom-character EV=
custom-character CV= custom-character DU= custom-character DW= custom-character
BU> custom-character CV= custom-character .sup. DV= custom-character DW=
custom-character EW= custom-character CU> custom-character CU= custom-character
DV= custom-character DV= custom-character CV= custom-character EU>
custom-character EU> custom-character CW> custom-character CV= custom-character
DV= custom-character DU= custom-character DV= custom-character DV<
custom-character DV=

[0083] In addition, the processor **161** may perform one or more other compression methods, such as using GZIP or another known data compression protocol, in finalizing the set of acceleration

data records for transmission. It will be understood that the original raw acceleration data records may be reconstructed, such as at the remote computing device following transmission, by reversing the steps of the data reduction method **700** as described herein.

[0084] Those of skill will recognize that the various illustrative logical blocks, modules, circuits, and algorithm steps described as follows, and in connection with the embodiments disclosed herein may be implemented as electronic hardware, software stored on a computer readable medium and executable by a hardware processor, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

[0085] The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0086] The steps of a method or algorithm described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such the processor reads information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC.

[0087] While the above detailed description has shown, described, and pointed out novel features of the development as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the device or process illustrated may be made by those skilled in the art without departing from the spirit of the development. As will be recognized, the present development may be embodied within a form that does not provide all of the features and benefits set forth herein, as some features may be used or practiced separately from others. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

[0088] A person skilled in the art will recognize that each of these sub-systems may be interconnected and controllably connected using a variety of techniques and hardware and that the present disclosure is not limited to any specific method of connection or connection hardware.

[0089] The technology is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well-known computing systems, environments, and/or configurations that may be suitable for use with the invention include, but are not limited to, personal computers, server computers, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, a microcontroller or microcontroller based system, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

[0090] As used herein, instructions refer to computer-implemented steps for processing information

in the system. Instructions may be implemented in software, firmware or hardware and include any type of programmed step undertaken by components of the system.

[0091] A microprocessor may be any conventional general purpose single- or multi-chip microprocessor such as a Pentium® processor, a Pentium® Pro processor, a 8051 processor, a MIPS® processor, a Power PC® processor, or an Alpha® processor. In addition, the microprocessor may be any conventional special purpose microprocessor such as a digital signal processor or a graphics processor. The microprocessor typically has conventional address lines, conventional data lines, and one or more conventional control lines.

[0092] The system may be used in connection with various operating systems such as Linux®, UNIX®, MacOS® or Microsoft Windows®.

[0093] The system control may be written in any conventional programming language such as C, C++, BASIC, Pascal, .NET (e.g., C #), or Java, and ran under a conventional operating system. C, C++, BASIC, Pascal, Java, and FORTRAN are industry standard programming languages for which many commercial compilers may be used to create executable code. The system control may also be written using interpreted languages such as Perl, Python or Ruby. Other languages may also be used such as PHP, JavaScript, and the like.

[0094] The foregoing description details certain embodiments of the systems, devices, and methods disclosed herein. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the systems, devices, and methods may be practiced in many ways. As is also stated above, it should be noted that the use of particular terminology when describing certain features or aspects of the invention should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the technology with which that terminology is associated.

[0095] It will be appreciated by those skilled in the art that various modifications and changes may be made without departing from the scope of the described technology. Such modifications and changes are intended to fall within the scope of the embodiments. It will also be appreciated by those of skill in the art that parts included in one embodiment are interchangeable with other embodiments; one or more parts from a depicted embodiment may be included with other depicted embodiments in any combination. For example, any of the various components described herein and/or depicted in the Figures may be combined, interchanged or excluded from other embodiments.

[0096] With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art may translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

[0097] The term “comprising” as used herein is synonymous with “including,” “containing,” or “characterized by,” and is inclusive or open-ended and does not exclude additional, unrecited elements or method steps.

[0098] All numbers expressing quantities of ingredients, reaction conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term “about.” Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should be construed in light of the number of significant digits and ordinary rounding approaches.

[0099] The above description discloses several methods and materials of the present development. This development is susceptible to modifications in the methods and materials, as well as alterations in the fabrication methods and equipment. Such modifications will become apparent to those skilled in the art from a consideration of this disclosure or practice of the development

disclosed herein. Consequently, it is not intended that this development be limited to the specific embodiments disclosed herein, but that it cover all modifications and alternatives coming within the true scope and spirit of the development as embodied in the attached claims.

[0100] As will be understood by those of skill in the art, in some embodiments, the processes set forth in the following material may be performed on a computer network. The computer network having a central server, the central server having a processor, data storage, such as databases and memories, and communications features to allow wired or wireless communication with various parts of the networks, including terminals and any other desired network access point or means.

Claims

1. A system for data transmission, the system comprising: one or more processors configured to: receive a plurality of data record, each of the data record comprising a plurality of fields; remove one or more of the plurality of fields from each of the plurality of data records to generate a plurality of reduced data records; identify one or location fields within the plurality of fields; modify values in the location fields; add a separation character to the end of each of the plurality of reduced data records; identify one or more fields in a first reduced data record which differ by less than a threshold amount from corresponding one or more fields in a second reduced data record; apply delta encoding to the identified one or more fields which differ by less than the threshold amount; and transmit the plurality of reduced data records.
2. The system of claim 1, wherein the one or more processors are further configured to: identify fields of the delta encoded fields which have a value smaller than a threshold value; add a constant value to the identified fields which have a value smaller than the threshold value to generate updated fields; encode the updated fields.
3. The system of claim 2, wherein the one or more processors are configured to encode the updated fields using base-62 encoding.
4. The system of claim 1, wherein one or more processors are configured to identify one or more of the plurality of fields which contain redundant or unnecessary information, wherein the removed one or more of the plurality of fields are corresponding fields in each of the plurality of data records.
5. The system of claim 1, wherein the processors are further configured to: identify data records of the plurality of data records which are null records; and remove, from the plurality of data records the identified data records which are null records.
6. The system of claim 1, wherein the one or more processors are configured to modify the values in the location fields by shifting a decimal a determined number of places to result in an integer value in the location fields.
7. The system of claim 1, wherein data of the first reduced data record was generated prior to the generation of data of the second reduced data record.
8. The system of claim 1, wherein the one or more processors are in a mobile delivery device traversing a delivery route, and wherein the threshold amount is based on a route identifier of the delivery route.
9. The system of claim 1 wherein the one or more processors are further configured to: determine a checksum for each of the reduced data records; append the determined checksum to each of the reduced data records;
10. A method for data transmission, the method comprising: receiving a plurality of data record, each of the data record comprising a plurality of fields; removing one or more of the plurality of fields from each of the plurality of data records to generate a plurality of reduced data records; identifying one or location fields within the plurality of fields; modifying values in the location fields; adding a separation character to the end of each of the plurality of reduced data records; identifying one or more fields in a first reduced data record which differ by less than a threshold

amount from corresponding one or more fields in a second reduced data record; applying delta encoding to the identified one or more fields which differ by less than the threshold amount; and transmitting the plurality of reduced data records.

11. The method of claim 10, further comprising: identifying fields of the delta encoded fields which have a value smaller than a threshold value; adding a constant value to the identified fields which have a value smaller than the threshold value to generate updated fields; and encoding the updated fields.

12. The method of claim 11, wherein encoding the updated fields comprises encoding the updated fields using base-62 encoding.

13. The method of claim 10, further comprising: identifying one or more of the plurality of fields which contain redundant or unnecessary information, wherein the removed one or more of the plurality of fields are corresponding fields in each of the plurality of data records.

14. The method of claim 10, further comprising: identifying data records of the plurality of data records which are null records; and removing, from the plurality of data records the identified data records which are null records.

15. The method of claim 14, wherein modifying the values in the location fields comprises shifting a decimal point by a determined number of places to result in an integer value in the location fields.

16. The method of claim 10, wherein data of the first reduced data record was generated prior to the generation of data of the second reduced data record.

17. The method of claim 10, wherein each of the data records are generated by a mobile delivery device traversing a delivery route, and wherein the threshold amount is based on a route identifier of the delivery route.

18. The method of claim 10 further comprising: determining a checksum for each of the reduced data records; and appending the determined checksum to each of the reduced data records.

19. A system for data transmission, the system comprising: a mobile delivery device traversing a delivery route, the mobile delivery device comprising one or more processors; wherein the one or more processors are configured to: generate a plurality of data record, each of the data record comprising a plurality of fields; remove one or more of the plurality of fields from each of the plurality of data records to generate a plurality of reduced data records; identify one or location fields within the plurality of fields; receive a route identifier corresponding to the delivery route; identify geographic information of the delivery route based on the route identifier; identify values of the identified location fields which are unlikely to change based on the identified geographic information; remove the identified values of the identified location fields which are unlikely to change to generate a plurality of reduced data records; and transmit the plurality of reduced data records.

20. The system of claim 19, wherein the geographic information comprises longitude and latitude lines, and wherein the one or more processors are configured to identify values which are unlikely to change based on the longitude and latitude lines that the mobile delivery device is unlikely to cross while traversing the delivery route.
