

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278710

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Finch; Paul et al.

SECURE REAL-TIME TRANSACTIONS

Abstract

A computer-implemented method including receiving, at a system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant by the consumer for a payment amount, a request comprising a merchant identifier associated with the merchant. The method also can include determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant maintained by the merchant financial institution. The method also can include sending the first information from the system to the consumer financial institution. The method also can include receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items. The method also can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive an account number of the consumer account of the consumer. The consumer does not receive an account number of the merchant account of the merchant.

Inventors: Finch; Paul (Scottsdale, AZ), Alexander; Lou Anne (Scottsdale, AZ)

Applicant: Early Warning Services, LLC (Scottsdale, AZ)

Family ID: 82308710

Assignee: Early Warning Services, LLC (Scottsdale, AZ)

Appl. No.: 19/205536

Filed: May 12, 2025

Related U.S. Application Data

parent US continuation 18595076 20240304 parent-grant-document US 12299658 child US 19205536

parent US continuation 17738934 20220506 parent-grant-document US 11922387 child US

18595076
parent US continuation 16716322 20191216 parent-grant-document US 11386410 child US
17738934
parent US continuation 14805214 20150721 parent-grant-document US 10438175 child US
15170781
parent US continuation-in-part 15873549 20180117 parent-grant-document US 11062290 child US
16716322
parent US continuation-in-part 15873533 20180117 parent-grant-document US 11037122 child US
15873549
parent US continuation-in-part 15873508 20180117 parent-grant-document US 10956888 child US
15873533
parent US continuation-in-part 15873481 20180117 parent-grant-document US 11037121 child US
15873508
parent US continuation-in-part 15873463 20180117 parent-grant-document US 10963856 child US
15873481
parent US continuation-in-part 15873440 20180117 parent-grant-document US 10970695 child US
15873463
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873549
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873533
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873508
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873481
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873463
parent US continuation-in-part 15170781 20160601 parent-grant-document US 10762477 child US
15873440
us-provisional-application US 62779987 20181214

Publication Classification

Int. Cl.: G06Q20/20 (20120101); G06Q20/02 (20120101); G06Q20/32 (20120101); G06Q20/36 (20120101); G06Q20/38 (20120101)

U.S. Cl.:

CPC G06Q20/20 (20130101); G06Q20/027 (20130101); G06Q20/206 (20130101); G06Q20/3223 (20130101); G06Q20/363 (20130101); G06Q20/3674 (20130101); G06Q20/38215 (20130101); G06Q20/385 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/595,076, filed Mar. 4, 2024, which is a continuation of U.S. patent application Ser. No. 17/738,934, filed May 6, 2022, which is a continuation of U.S. patent application Ser. No. 16/716,322, filed Dec. 16, 2019, which is a continuation-in-part of U.S. patent application Ser. No. 15/873,549, filed Jan. 17, 2018; U.S. patent application Ser. No. 15/873,533,

filed Jan. 17, 2018; U.S. patent application Ser. No. 15/873,508, filed Jan. 17, 2018; U.S. patent application Ser. No. 15/873,481, filed Jan. 17, 2018; U.S. patent application Ser. No. 15/873,463, filed Jan. 17, 2018; and U.S. patent application Ser. No. 15/873,440, filed Jan. 17, 2018. U.S. patent application Ser. Nos. 15/873,549, 15/873,533, 15/873,508, 15/873,481, 15/873,463, and 15/873,440 are each a continuation-in-part of U.S. patent application Ser. No. 15/170,781, filed Jun. 1, 2016, which is a continuation of U.S. patent application Ser. No. 14/805,214, filed Jul. 21, 2015. U.S. patent application Ser. No. 16/716,322 also claims the benefit of U.S. Provisional Application No. 62,779,987, filed Dec. 14, 2018. U.S. Provisional Application No. 62,779,987 and U.S. patent application Ser. Nos. 18/595,076, 17/738,934, 16/716,322, 15/873,549, 15/873,533, 15/873,508, 15/873,481, 15/873,463, 15/873,440, 15/170,781, and 14/805,214 are incorporated herein by reference in their entirety.

TECHNICAL FIELD

[0002] This disclosure relates generally to secure processing of transactions, and relates more particularly to providing secure transactions with offline devices.

BACKGROUND

[0003] In a typical transaction involving a mobile device, a mobile wallet application in the mobile device generally needs to communicate (e.g., through the Internet) with a mobile wallet provider during the transaction, such as to initiate the transaction and/or to authorize the transaction. When the mobile device is unable access the mobile wallet provider, such as due to the mobile device being unable to access the Internet, the transaction generally cannot proceed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] To facilitate further description of the embodiments, the following drawings are provided in which:

[0005] FIG. 1 illustrates a block diagram of a system that can be employed for a secure real-time payment transaction network, according to an embodiment;

[0006] FIG. 2 illustrates a flow chart for a method, according to an embodiment;

[0007] FIG. 3 illustrates a flow chart for a method, according to another embodiment;

[0008] FIG. 4 illustrates a flow chart for a method, according to another embodiment;

[0009] FIG. 5 illustrates a flow chart for a method, according to another embodiment;

[0010] FIG. 6 illustrates a flow chart for a method, according to another embodiment;

[0011] FIG. 7 illustrates a computer that is suitable for implementing an embodiment of components of the system of FIG. 1;

[0012] FIG. 8 illustrates a representative block diagram of an example of elements included in circuit boards inside a chassis of the computer of FIG. 7;

[0013] FIG. 9 illustrates a flow chart for a method, according to another embodiment;

[0014] FIG. 10 illustrates a flow chart for a method, according to another embodiment;

[0015] FIG. 11 illustrates a flow chart for a method, according to another embodiment;

[0016] FIG. 12 illustrates a flow chart for a method, according to another embodiment;

[0017] FIG. 13 illustrates a flow chart for a method, according to another embodiment;

[0018] FIG. 14 illustrates a flow chart for a method, according to another embodiment;

[0019] FIG. 15 illustrates a flow chart for a method, according to another embodiment;

[0020] FIG. 16 illustrates a flow chart for a method, according to another embodiment;

[0021] FIG. 17 illustrates an exemplary user interface display to allow the consumer of FIG. 1 to approve a transaction on the mobile device of FIG. 1;

[0022] FIG. 18 illustrates an exemplary user interface display to allow the consumer of FIG. 1 to choose to use another account for the payment transaction when the approved account has

insufficient funds or limited funds;

[0023] FIG. **19** illustrates an exemplary user interface display to allow the consumer of FIG. **1** to select another account for the payment transaction when the approved account has insufficient funds;

[0024] FIG. **20** illustrates an exemplary user interface display to allow the consumer of FIG. **1** to select the amount to pay using the other account selected the user interface display of FIG. **19**;

[0025] FIG. **21** illustrates an exemplary user interface display to confirm that a payment request has been sent from the mobile device of FIG. **1**;

[0026] FIG. **22** illustrates an exemplary user interface display to confirm that the payment transaction to the merchant of FIG. **1** has successfully completed;

[0027] FIG. **23** illustrates a flow chart for a method, according to another embodiment;

[0028] FIG. **24** illustrates a flow chart for a method, according to another embodiment;

[0029] FIG. **25** illustrates a flow chart for a method, according to another embodiment;

[0030] FIG. **26** illustrates a flow chart for a method, according to another embodiment;

[0031] FIG. **27** illustrates a flow chart for a method, according to another embodiment; and

[0032] FIG. **28** illustrates a flow chart for a method, according to another embodiment.

[0033] For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different figures denote the same elements.

[0034] The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.

[0035] The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

[0036] The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements mechanically and/or otherwise. Two or more electrical elements may be electrically coupled together, but not be mechanically or otherwise coupled together. Coupling may be for any length of time, e.g., permanent or semi-permanent or only for an instant. “Electrical coupling” and the like should be broadly understood and include electrical coupling of all types. The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable.

[0037] As defined herein, two or more elements are “integral” if they are comprised of the same piece of material. As defined herein, two or more elements are “non-integral” if each is comprised of a different piece of material.

[0038] As defined herein, “approximately” can, in some embodiments, mean within plus or minus ten percent of the stated value. In other embodiments, “approximately” can mean within plus or minus five percent of the stated value. In further embodiments, “approximately” can mean within plus or minus three percent of the stated value. In yet other embodiments, “approximately” can mean within plus or minus one percent of the stated value.

[0039] As defined herein, “real-time” can, in some embodiments, be defined with respect to operations carried out as soon as practically possible upon occurrence of a triggering event. A triggering event can include receipt of data necessary to execute a task or to otherwise process information. Because of delays inherent in transmission and/or in computing speeds, the term “real time” encompasses operations that occur in “near” real time or somewhat delayed from a triggering event. In a number of embodiments, “real time” can mean real time less a time delay for processing (e.g., determining) and/or transmitting data. The particular time delay can vary depending on the type and/or amount of the data, the processing speeds of the hardware, the transmission capability of the communication hardware, the transmission distance, etc. However, in many embodiments, the time delay can be less than approximately one second, five seconds, ten seconds, thirty seconds, one minute, or five minutes.

DESCRIPTION OF EXAMPLES OF EMBODIMENTS

[0040] Various embodiments include a system including one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules and perform certain acts. The acts can include receiving, at a first financial institution from a mobile device of a consumer, a first request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The first request can include first information including a merchant identifier, a transaction identifier, and the payment amount. The first information can be sent to the first financial institution from a mobile application running on a mobile device used by the consumer at a store of the merchant to pay for one or more items to be purchased from the merchant by the consumer for the payment amount. The merchant identifier can be associated with the merchant. The mobile application can be associated with the first account. The acts also can include determining, at the first financial institution, second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system. The first system can be in data communication with the first financial institution and the second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The acts additionally can include authorizing, at the first financial institution, a payment from the first account to the second account. The acts further can include sending, from the first financial institution to the first system, payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the first system to the second financial institution such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0041] A number of embodiments include a method being implemented via one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules. The method can include receiving, at a first financial institution from a mobile device of a consumer, a first request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The first request can include first information including a merchant identifier, a transaction identifier, and the payment amount. The first information can be sent to the first financial institution from a mobile application running on a mobile device used by the consumer at a store of the merchant to pay for one or more items to be purchased from the merchant by the consumer for

the payment amount. The merchant identifier can be associated with the merchant. The mobile application can be associated with the first account. The method also can include determining, at the first financial institution, second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system. The first system can be in data communication with the first financial institution and the second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The method additionally can include authorizing, at the first financial institution, a payment from the first account to the second account. The method further can include sending, from the first financial institution to the first system, payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the first system to the second financial institution such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0042] Additional embodiments include a system including one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules and perform certain acts. The acts can include receiving, at a first system from a first entity, a request including a merchant identifier. The merchant identifier can be associated with a merchant. The first system can be in data communication with a first financial institution and a second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The first financial institution can maintain a first account of a consumer. The first system can be in data communication with a merchant account database. The acts also can include determining, at the first system, using the merchant account database, first information including an account identifier of a second account of the merchant maintained by a second financial institution. The account identifier can be associated with the merchant identifier in the merchant account database. The acts additionally can include sending the first information from the first system to the first financial institution. The acts further can include receiving, at the first system from the first financial institution, payment information regarding a payment to be made to the second account from the first account to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. The consumer can use a mobile device at a store of the merchant to pay for the one or more items. The mobile device can run a mobile application associated with the first account. The payment information can include a transaction identifier, the account identifier of the second account, and the payment amount. The acts additionally can include sending, from the first system to the second financial institution, the payment information such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer.

[0043] Further embodiments include a method being implemented via one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules. The method can include receiving, at a first system from a first entity, a request including a merchant identifier. The merchant identifier can be associated with a merchant. The first system can be in data communication with a first financial institution and a second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The first financial institution can maintain a first account of a consumer. The first system can be in data communication with a merchant account database. The method also can include determining, at the first system, using the merchant account database, first information including an account identifier of a second account of the merchant maintained by a second financial institution. The account

identifier can be associated with the merchant identifier in the merchant account database. The method additionally can include sending the first information from the first system to the first financial institution. The method further can include receiving, at the first system from the first financial institution, payment information regarding a payment to be made to the second account from the first account to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. The consumer can use a mobile device at a store of the merchant to pay for the one or more items. The mobile device can run a mobile application associated with the first account. The payment information can include a transaction identifier, the account identifier of the second account, and the payment amount. The method additionally can include sending, from the first system to the second financial institution, the payment information such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer.

[0044] Still further embodiments include one or more non-transitory memory storage units including computer instructions that, when executed by one or more processors, perform various acts. The acts can include receiving, at a first system from a first entity, a request including a merchant identifier. The merchant identifier can be associated with a merchant. The first system can be in data communication with a first financial institution and a second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The first financial institution can maintain a first account of a consumer. The first system can be in data communication with a merchant account database. The acts also can include determining, at the first system, using the merchant account database, first information including an account identifier of a second account of the merchant maintained by a second financial institution. The account identifier can be associated with the merchant identifier in the merchant account database. The acts additionally can include sending the first information from the first system to the first financial institution. The acts further can include receiving, at the first system from the first financial institution, payment information regarding a payment to be made to the second account from the first account to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. The consumer can use a mobile device at a store of the merchant to pay for the one or more items. The mobile device can run a mobile application associated with the first account. The payment information can include a transaction identifier, the account identifier of the second account, and the payment amount. The acts additionally can include sending, from the first system to the second financial institution, the payment information such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer.

[0045] Additional embodiments include a method being implemented via one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules. The method can include performing, at a mobile device, a preliminary identity authentication of a consumer using the mobile device. The method also can include receiving at the mobile device first information from a point-of-sale terminal. The first information can include a merchant identifier, a transaction identifier, and a payment amount. The merchant identifier can uniquely correspond to the point-of-sale terminal at a store of a merchant. The mobile device can run a mobile application that is associated with a first account of the consumer using the mobile device. The first account of the consumer can be maintained by a first financial institution. The method further can include sending, from the mobile device to the first financial institution, a first request to pay the merchant for the payment amount from the first account for one or more items to be purchased from the merchant by the consumer. The first request can include the first information, such that the first financial institution, upon receiving the first request, determines second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based

on the merchant identifier and third information obtained from a first system, and such that the first financial institution sends to the first system payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the first system to the second financial institution such that the second financial institution, upon receiving the payment information, can notify the merchant to satisfy an expectation of the merchant for payment from the consumer. The first system can be in data communication with the first financial institution and the second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. The payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account.

[0046] The method additionally can include, after sending the first request to pay the merchant and before the payment information is sent to the first system from the first financial institution: receiving, at the mobile device from the first financial institution, an additional authentication request to perform an additional identity authentication of the consumer using the mobile device; performing, at the mobile device, the additional identity authentication of the consumer using the mobile device; and sending, from the mobile device to the first financial institution, a response to the additional authentication request.

[0047] Performing the additional identity authentication of the consumer can include performing the additional authentication of the consumer based at least in part on at least one of: determining biometrics of the consumer using the mobile device; or requesting the consumer to enter additional information in the mobile device.

[0048] The method further can include prior to sending the first request to pay the merchant: sending, from the mobile device to the first financial institution, a preliminary request for account information; and receiving, at the mobile device from the first financial institution, the account information comprising an account balance and an account status of the first account. The account information can include an account balance and an account status of the first account.

[0049] Further embodiments include a method being implemented via one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules. The method can include determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer. The method also can include sending first information from the point-of-sale terminal to a mobile device used by the consumer. The first information can include a merchant identifier, a transaction identifier, and the payment amount. The merchant identifier can uniquely correspond to the point-of-sale terminal at the store of the merchant. The mobile device can run a mobile application that is associated with a first account of the consumer using the mobile device. The first account of the consumer can be maintained by a first financial institution. The mobile device, upon receiving the first information, can send a first request to pay the merchant for the payment amount from the first account. The first request can include the first information, such that the first financial institution, upon receiving the first request, determines second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system, and such that the first financial institution sends to the first system payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the first system to the second financial institution. The first system can be in data communication with the first financial institution and the second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The payment

information can include the transaction identifier, the account identifier of the second account, and the payment amount. The payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account. The method further can include receiving, at the point-of-sale terminal from the second financial institution, a notification to satisfy an expectation of the merchant for payment from the consumer. [0050] Sending the first information from the point-of-sale terminal to the mobile device can include sending the first information from the point-of-sale terminal to the mobile device using a proximity-based wireless data communication protocol.

[0051] The method additionally can include receiving, at the point-of-sale terminal from the mobile device, information about the consumer.

[0052] Still further embodiments include a method being implemented via one or more processing modules and one or more non-transitory memory storage modules storing computing instructions configured to run on the one or more processing modules. The method can include receiving, at a second financial institution from a first system, payment information regarding a payment to be made to a second account of a merchant maintained by the second financial institution from a first account of a consumer maintained by a first financial institution to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. The payment information can be sent from the first financial institution to the first system and routed through the first system to the second financial institution. The first system can be in data communication with the first financial institution and the second financial institution. The first system can be maintained by an entity that is different from the first financial institution and the second financial institution. The consumer can use a mobile device at a store of the merchant to pay for the one or more items. The mobile device can run a mobile application associated with the first account. The payment information can include a transaction identifier, an account identifier of the second account, and the payment amount. The first financial institution can determine the account identifier of the second account based on a merchant identifier and based on third information obtained from the first system. The merchant identifier can uniquely correspond to a point-of-sale terminal at the store of a merchant. The mobile device can send a request to pay the merchant for the payment amount from the first account. The request can include first information including the merchant identifier, a transaction identifier, and the payment amount. The payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account. The method also can include sending, from the second financial institution to the point-of-sale terminal, a notification to satisfy an expectation of the merchant for payment from the consumer.

[0053] The method also can include, before sending the notification, crediting the second account with the payment amount.

[0054] Sending the notification to satisfy the expectation of the merchant for payment from the consumer can include notifying the merchant that funds for the payment amount are immediately available in the second account.

[0055] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The acts also can include generating a transaction code including a merchant public identifier, the payment amount, a transaction identifier for the transaction, and a digital signature. The acts additionally can include providing the transaction code to a mobile device being used by the consumer, such that the mobile device verifies the digital signature and sends a request to pay the merchant for the payment amount from

a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, and such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can be routed through the transaction system to the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. The acts further can include receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0056] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The method also can include generating a transaction code including a merchant public identifier, the payment amount, a transaction identifier for the transaction, and a digital signature. The method additionally can include providing the transaction code to a mobile device being used by the consumer, such that the mobile device verifies the digital signature and sends a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, and such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can be routed through the transaction system to the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. The method further can include receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0057] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant. The transaction code can include a merchant public identifier being associated with the merchant, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, a transaction identifier for the transaction, and a digital signature. The acts also can include verifying the digital signature for the transaction code. The acts additionally can include sending, from the mobile device, a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The transaction system can be maintained by an entity that is different from the merchant, the first

financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0058] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant. The transaction code can include a merchant public identifier being associated with the merchant, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, a transaction identifier for the transaction, and a digital signature. The method also can include verifying the digital signature for the transaction code. The method additionally can include sending, from the mobile device, a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0059] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The request to pay can include information including a merchant public identifier, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. The mobile device can be used by the consumer at a store of the merchant to pay for the transaction. The information can be received by the mobile device from a point-of-sale terminal at the store of the merchant as part of a transaction code. The transaction code can be verified by the mobile device using a digital signature of the transaction code. The acts also can include retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant public identifier. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The acts additionally can include sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the transaction system to the second financial institution. The point-of-sale terminal can receive a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0060] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The request to pay can include information including a merchant public identifier, a payment amount for one or more

items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. The mobile device can be used by the consumer at a store of the merchant to pay for the transaction. The information can be received by the mobile device from a point-of-sale terminal at the store of the merchant as part of a transaction code. The transaction code can be verified by the mobile device using a digital signature of the transaction code. The method also can include retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant public identifier. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The method additionally can include sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the first account. The payment information can be routed through the transaction system to the second financial institution. The point-of-sale terminal can receive a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0061] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving, at a transaction system from a first entity, a request including a merchant public identifier associated with a merchant. The transaction system can be in data communication with a first financial institution that maintains a first account of a consumer and a second financial institution that maintains a second account of the merchant. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The consumer can use a mobile device at a store of the merchant to pay for one or more items in a transaction. The mobile device can receive a transaction code from a point-of-sale terminal at the store. The transaction code can include a transaction identifier, a payment amount for the transaction, the merchant public identifier, and a digital signature. The transaction code can be verified by the mobile device using the digital signature of the transaction code. The acts also can include determining, at the transaction system, an account identifier of the second account based on the merchant public identifier using a merchant account database. The acts additionally can include sending the account identifier to the first financial institution. The acts further can include receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the first account. The payment information can include the account identifier of the second account, the payment amount, and the transaction identifier. The acts additionally can include sending, from the transaction system to the second financial institution, the payment information, such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0062] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a transaction system from a first entity, a request including a merchant public identifier associated with a merchant. The transaction system can be in data communication with a first financial institution that maintains a first account of a consumer and a second financial institution that maintains a second account of the merchant. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The consumer can use a mobile device at a store of the merchant to pay for one or more items in a transaction. The mobile device can receive a transaction code from a point-of-sale terminal at the store. The transaction code can include a transaction identifier, a payment amount for the transaction, the merchant public identifier, and a

digital signature. The transaction code can be verified by the mobile device using the digital signature of the transaction code. The method also can include determining, at the transaction system, an account identifier of the second account based on the merchant public identifier using a merchant account database. The method additionally can include sending the account identifier to the first financial institution. The method further can include receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the first account. The payment information can include the account identifier of the second account, the payment amount, and the transaction identifier. The method additionally can include sending, from the transaction system to the second financial institution, the payment information, such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0063] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include performing, at a mobile device being used by a consumer, an identity authentication of the consumer. The acts also can include receiving, at the mobile device, first information from a point-of-sale terminal at a store of a merchant. The first information can include a merchant identifier, a transaction identifier, and a payment amount. The merchant identifier can be associated with the merchant. The payment amount can be for one or more items to be purchased from the merchant by the consumer in a transaction. The transaction identifier can be associated with the transaction. The acts additionally can include sending, from the mobile device, a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0064] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include performing, at a mobile device being used by a consumer, an identity authentication of the consumer. The method also can include receiving, at the mobile device, first information from a point-of-sale terminal at a store of a merchant. The first information can include a merchant identifier, a transaction identifier, and a payment amount. The merchant identifier can be associated with the merchant. The payment amount can be for one or more items to be purchased from the merchant by the consumer in a transaction. The transaction identifier can be associated with the transaction. The method additionally can include sending, from the mobile device, a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the

second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0065] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from one or more first accounts of the consumer maintained by the first financial institution. The one or more first accounts can include at least one non-demand deposit account. The request to pay can include information including a merchant identifier, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. The mobile device can be used by the consumer at a store of the merchant to pay for the transaction. The information can be received by the mobile device from a point-of-sale terminal at the store of the merchant. The acts also can include retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant identifier. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The acts additionally can include sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0066] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from one or more first accounts of the consumer maintained by the first financial institution. The one or more first accounts can include at least one non-demand deposit account. The request to pay can include information including a merchant identifier, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. The mobile device can be used by the consumer at a store of the merchant to pay for the transaction. The information can be received by the mobile device from a point-of-sale terminal at the store of the merchant. The method also can include retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant identifier. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The method additionally can include sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount.

[0067] Additional embodiments include a system including one or more processors and one or

more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include receiving, at a transaction system from a first entity, a request including a merchant identifier associated with a merchant. The transaction system can be in data communication with a first financial institution that maintains one or more first accounts of a consumer and a second financial institution that maintains a second account of the merchant. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The consumer can use a mobile device at a store of the merchant to authorize paying a payment amount for one or more items in a transaction using the one or more first accounts. The acts also can include determining, at the transaction system, an account identifier of the second account of the merchant maintained by a second financial institution using a merchant account database. The acts additionally can include sending the account identifier from the transaction system to the first financial institution. The acts further can include receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the one or more first accounts. The payment information can include a transaction identifier, the account identifier of the second account, and the payment amount. The acts additionally can include sending, from the transaction system to the second financial institution, the payment information, such that a point-of-sale terminal at the store of the merchant receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0068] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a transaction system from a first entity, a request including a merchant identifier associated with a merchant. The transaction system can be in data communication with a first financial institution that maintains one or more first accounts of a consumer and a second financial institution that maintains a second account of the merchant. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The consumer can use a mobile device at a store of the merchant to authorize paying a payment amount for one or more items in a transaction using the one or more first accounts. The method also can include determining, at the transaction system, an account identifier of the second account of the merchant maintained by a second financial institution using a merchant account database. The method additionally can include sending the account identifier from the transaction system to the first financial institution. The method further can include receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the one or more first accounts. The payment information can include a transaction identifier, the account identifier of the second account, and the payment amount. The method additionally can include sending, from the transaction system to the second financial institution, the payment information, such that a point-of-sale terminal at the store of the merchant receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0069] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The acts also can include sending first information from the point-of-sale terminal to a mobile device used by the consumer. The first information can include a merchant identifier, a transaction identifier, and the payment amount, such that the mobile device sends a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, such that the first

financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the one or more first accounts, and such that the payment information is routed through the transaction system to the second financial institution. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. The acts additionally can include receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0070] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The method also can include sending first information from the point-of-sale terminal to a mobile device used by the consumer. The first information can include a merchant identifier, a transaction identifier, and the payment amount, such that the mobile device sends a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the one or more first accounts, and such that the payment information is routed through the transaction system to the second financial institution. The one or more first accounts can include at least one non-demand deposit account. The transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. The method additionally can include receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant.

[0071] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving a preauthorization code at a mobile device while the mobile device is in data communication with a mobile wallet provider. The preauthorization code can include a preauthorization amount, an expiration time, and a digital signature. The acts also can include storing the preauthorization code in the mobile device. The acts additionally can include receiving, at the mobile device, an authorization from a user of the mobile device for a transaction having a transaction amount while the user is at a point-of-sale terminal of a first entity. The acts further can include determining that the mobile device is unable to communicate with the mobile wallet provider. The acts additionally can include verifying that the transaction amount is less than or equal to the preauthorization amount. The acts further can include, while the mobile device is unable to communicate with the mobile wallet provider, providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity. The transaction code can include the preauthorization code, a transaction identifier, and the transaction amount.

[0072] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving a preauthorization code at a mobile device while the mobile device is in data communication with a mobile wallet provider. The preauthorization code can include a preauthorization amount, an expiration time, and a digital signature. The method also can include storing the preauthorization code in the mobile device. The method additionally can include receiving, at the mobile device, an authorization from a user of the mobile device for a transaction having a transaction amount while the user is at a point-of-sale terminal of a first entity. The method further can include determining that the mobile device is unable to communicate with the mobile wallet provider. The method additionally can include verifying that the transaction amount is less than or equal to the preauthorization amount. The method further can include, while the mobile device is unable to communicate with the mobile wallet provider, providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity. The transaction code can include the preauthorization code, a transaction identifier, and the transaction amount.

[0073] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving a transaction amount and a preauthorization code from a first entity. The preauthorization code can include a preauthorization amount, an expiration time, and a digital signature. The transaction amount is for a transaction authorized by a user of a mobile device at a point-of-sale terminal of the first entity. The transaction amount is less than or equal to the preauthorization amount. The mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with a mobile wallet provider. The mobile device provided a transaction code to the point-of-sale terminal while the mobile device was unable to communicate with the mobile wallet provider. The transaction code includes the preauthorization code, a transaction identifier for the transaction, and the transaction amount. The acts also can include verifying the preauthorization code using the digital signature of the preauthorization code. The acts additionally can include sending an approval for the transaction to the first entity in real-time while the user remains at the point-of-sale terminal of the first entity.

[0074] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving a transaction amount and a preauthorization code from a first entity. The preauthorization code can include a preauthorization amount, an expiration time, and a digital signature. The transaction amount is for a transaction authorized by a user of a mobile device at a point-of-sale terminal of the first entity. The transaction amount is less than or equal to the preauthorization amount. The mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with a mobile wallet provider. The mobile device provided a transaction code to the point-of-sale terminal while the mobile device was unable to communicate with the mobile wallet provider. The transaction code includes the preauthorization code, a transaction identifier for the transaction, and the transaction amount. The method also can include verifying the preauthorization code using the digital signature of the preauthorization code. The method additionally can include sending an approval for the transaction to the first entity in real-time while the user remains at the point-of-sale terminal of the first entity.

[0075] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving a transaction

code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider. The transaction code can include a preauthorization code, a transaction identifier for a transaction authorized by a user of the mobile device at the point-of-sale terminal, and a transaction amount for the transaction. The mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with the mobile wallet provider. The preauthorization code includes a preauthorization amount, an expiration time, and a digital signature. The transaction amount is less than or equal to the preauthorization amount. The acts also can include sending the transaction amount and the preauthorization code to a transaction system. The acts additionally can include receiving an approval for the transaction from the transaction system in real-time while the user remains at the point-of-sale terminal.

[0076] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider. The transaction code can include a preauthorization code, a transaction identifier for a transaction authorized by a user of the mobile device at the point-of-sale terminal, and a transaction amount for the transaction. The mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with the mobile wallet provider. The preauthorization code includes a preauthorization amount, an expiration time, and a digital signature. The transaction amount is less than or equal to the preauthorization amount. The method also can include sending the transaction amount and the preauthorization code to a transaction system. The method additionally can include receiving an approval for the transaction from the transaction system in real-time while the user remains at the point-of-sale terminal.

[0077] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one more processors and perform various acts. The acts can include receiving, at a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount for a transaction, and a transaction identifier for the transaction. The acts also can include receiving an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, the mobile device running a mobile application that is associated with a mobile wallet provider. The acts additionally can include determining that the mobile device is unable to communicate with the mobile wallet provider. The acts further can include generating an encrypted transaction code. The encrypted transaction code can include a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The acts additionally can include sending the encrypted transaction code from the mobile device to the point-of-sale terminal to cause the encrypted transaction code to be sent through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, to cause the payment information to be routed through the transaction system to the second financial institution, and to cause the point-of-sale terminal to receive a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0078] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory

computer-readable media. The method can include receiving, at a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount for a transaction, and a transaction identifier for the transaction. The method also can include receiving an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, the mobile device running a mobile application that is associated with a mobile wallet provider. The method additionally can include determining that the mobile device is unable to communicate with the mobile wallet provider. The method further can include generating an encrypted transaction code. The encrypted transaction code can include a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The method additionally can include sending the encrypted transaction code from the mobile device to the point-of-sale terminal to cause the encrypted transaction code to be sent through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, to cause the payment information to be routed through the transaction system to the second financial institution, and to cause the point-of-sale terminal to receive a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0079] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include receiving, at a transaction system being situated along a proxy communication channel extending from a point-of-sale terminal of a first entity to a mobile wallet provider, an encrypted transaction code. The encrypted transaction code can be generated and sent to the point-of-sale terminal by a mobile device that runs a mobile application associated with the mobile wallet provider. The mobile device receives from a point-of-sale terminal an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction, receives an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, and determines that the mobile device is unable to communicate with the mobile wallet provider. The encrypted transaction code includes a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The acts also can include sending the encrypted transaction code through the proxy communication channel to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user. The acts additionally can include receiving, from the first financial institution, a request comprising the identifier of the first entity. The acts further can include determining an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity. The acts additionally can include sending the account identifier of the second account to the first financial institution. The acts further can include receiving, from the first financial institution, payment information regarding a payment to be made to the second account from the first account for the transaction. The acts additionally can include sending the payment information to the second financial institution, to cause the point-of-sale terminal to receive a notification in real-time while the user remains at the point-of-sale terminal.

[0080] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include receiving, at a transaction system being situated along a proxy communication channel extending from a point-of-sale terminal of a first entity to a

mobile wallet provider, an encrypted transaction code. The encrypted transaction code can be generated and sent to the point-of-sale terminal by a mobile device that runs a mobile application associated with the mobile wallet provider. The mobile device receives from a point-of-sale terminal an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction, receives an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, and determines that the mobile device is unable to communicate with the mobile wallet provider. The encrypted transaction code includes a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The method also can include sending the encrypted transaction code through the proxy communication channel to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user. The method additionally can include receiving, from the first financial institution, a request comprising the identifier of the first entity. The method further can include determining an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity. The method additionally can include sending the account identifier of the second account to the first financial institution. The method further can include receiving, from the first financial institution, payment information regarding a payment to be made to the second account from the first account for the transaction. The method additionally can include sending the payment information to the second financial institution, to cause the point-of-sale terminal to receive a notification in real-time while the user remains at the point-of-sale terminal.

[0081] Additional embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions configured to run on the one or more processors and perform various acts. The acts can include sending, to a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction. The mobile device runs a mobile application that is associated with a mobile wallet provider, receives an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, determines that the mobile device is unable to communicate with the mobile wallet provider, and generates an encrypted transaction code. The encrypted transaction code includes a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The acts also can include receiving the encrypted transaction code from the mobile device. The acts additionally can include sending the encrypted transaction code through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, and to cause the payment information to be routed through the transaction system to the second financial institution. The acts further can include receiving, at the point-of-sale terminal, a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0082] Further embodiments include a method being implemented via execution of computing instructions configured to run at one or more processors and stored at one or more non-transitory computer-readable media. The method can include sending, to a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction. The mobile device runs a mobile application that is associated with a mobile wallet provider, receives an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal, determines that the mobile device

is unable to communicate with the mobile wallet provider, and generates an encrypted transaction code. The encrypted transaction code includes a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The method also can include receiving the encrypted transaction code from the mobile device. The method additionally can include sending the encrypted transaction code through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, and to cause the payment information to be routed through the transaction system to the second financial institution. The method further can include receiving, at the point-of-sale terminal, a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0083] Additional embodiments include a system including one or more processors. The system also includes a merchant account database including a plurality of merchant identifiers being associated with a plurality of merchants. A plurality of account identifiers can be associated with the plurality of merchants. A mapping can associate the plurality of merchant identifiers with the plurality of account identifiers. The system additionally includes a transaction database. The system further includes one or more non-transitory computer-readable media storing computing instructions that, when executed by the one or more processors, cause the one or more processors to perform certain acts. The acts can include receiving, at the system and from a mobile device being used by a consumer, a request including a merchant identifier of the plurality of merchant identifiers. The merchant identifier can be associated with a merchant of the plurality of merchants. The consumer can use the mobile device to pay for one or more items to be purchased from the merchant by the consumer for a payment amount. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The acts also can include determining, at the system and using the merchant account database, first information including a second account identifier for a second account of the merchant at the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The acts additionally can include sending the first information from the system to the first financial institution. The acts further can include receiving in real time over a network, at the system and from the first financial institution, payment information regarding a payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include a transaction identifier, the second account identifier of the second account, and the payment amount. The acts additionally can include logging the payment information in the transaction database. The acts further can include sending in real time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive a first account identifier of the first account of the consumer. The consumer does not receive the second account identifier of the second account of the merchant.

[0084] Further embodiments include a method implemented by one or more processors. The method can include receiving, at a system and from a mobile device being used by a consumer, a request comprising a merchant identifier. The merchant identifier can be associated with a merchant. The system can include a merchant account database and a transaction database. The

merchant account database can include a plurality of merchant identifiers being associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The plurality of merchants can include the merchant. The plurality of merchant identifiers can include the merchant identifier. The consumer can use the mobile device to pay for one or more items to be purchased from the merchant by the consumer for a payment amount. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The method also can include determining, at the system and using the merchant account database, first information comprising a second account identifier for a second account of the merchant maintained by the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The method additionally can include sending the first information from the system to the first financial institution. The method further can include receiving in real time over a network, at the system and from the first financial institution, payment information regarding a payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include a transaction identifier, the second account identifier of the second account, and the payment amount. The method additionally can include logging the payment information in the transaction database. The method further can include sending in real time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive a first account identifier of the first account of the consumer. The consumer does not receive the second account identifier of the second account of the merchant.

[0085] Additional embodiments include one or more non-transitory computer-readable media comprising computer instructions that, when executed by one or more processors, perform certain acts. The acts can include receiving, at a system and from a mobile device being used by a consumer, a request comprising a merchant identifier. The merchant identifier can be associated with a merchant. The system can include a merchant account database and a transaction database. The merchant account database can include a plurality of merchant identifiers being associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The plurality of merchants can include the merchant. The plurality of merchant identifiers can include the merchant identifier. The consumer can use the mobile device to pay for one or more items to be purchased from the merchant by the consumer for a payment amount. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The acts also can include determining, at the system and using the merchant account database, first information comprising a second account identifier for a second account of the merchant maintained by the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The acts additionally can include sending the first information from the system to the first financial institution. The acts further can include receiving in real time over a network, at the system and from the first financial institution, payment information regarding a payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include a transaction identifier, the second account identifier of the second account, and the payment amount. The acts additionally can include

logging the payment information in the transaction database. The acts further can include sending in real time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive a first account identifier of the first account of the consumer. The consumer does not receive the second account identifier of the second account of the merchant.

[0086] Further embodiments include a system including one or more processors. The system also can include a merchant account database including a plurality of merchant identifiers being associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The system additionally can include a transaction database. The system further can include one or more non-transitory computer-readable media storing computing instructions that, when executed by the one or more processors, cause the one or more processors to perform certain operations. The operations can include receiving, at the system and based on a consumer using a mobile device to initiate a payment for one or more items to be purchased from a merchant by the consumer for a payment amount, a message including a merchant identifier of the plurality of merchant identifiers. The merchant identifier can be associated with the merchant of the plurality of merchants. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The operations also can include determining, at the system and using the merchant account database, first information including a second account identifier for a second account of the merchant at the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The operations additionally can include sending the first information from the system to the first financial institution. The operations further can include receiving in real-time over a network, at the system and from the first financial institution, payment information regarding the payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include information about the second account identifier of the second account and the payment amount. The operations additionally can include logging the payment information in the transaction database. The operations further can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. An account number of the first account of the consumer can remain undisclosed to the merchant.

[0087] Additional embodiments can include a method implemented by one or more processors. The method can include receiving, at a system and based on a consumer using a mobile device to initiate a payment for one or more items to be purchased from a merchant by the consumer for a payment amount, a message including a merchant identifier of a plurality of merchant identifiers associated with a plurality of merchants in a merchant account database. The merchant identifier can be associated with the merchant of the plurality of merchants. The merchant account database further can include a plurality of account identifiers associated with the plurality of merchants and a mapping associating the plurality of merchants identifiers with the plurality of account identifiers. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The method also can include determining, at the system and using the merchant account database, first information including a second account identifier for a second account of the merchant at the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The method

additionally can include sending the first information from the system to the first financial institution. The method further can include receiving in real-time over a network, at the system and from the first financial institution, payment information regarding the payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include information about the second account identifier of the second account and the payment amount. The method additionally can include logging the payment information in a transaction database. The method further can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. An account number of the first account of the consumer can remain undisclosed to the merchant.

[0088] Further embodiments can include one or more non-transitory computer-readable media including computer instructions that, when executed by one or more processors, perform certain operations. The operations can include receiving, at a system and based on a consumer using a mobile device to initiate a payment for one or more items to be purchased from a merchant by the consumer for a payment amount, a message including a merchant identifier of a plurality of merchant identifiers associated with a plurality of merchants in a merchant account database. The merchant identifier can be associated with the merchant of the plurality of merchants. The merchant account database further can include a plurality of account identifiers associated with the plurality of merchants and a mapping associating the plurality of merchants identifiers with the plurality of account identifiers. The mobile device can obtain the merchant identifier using a data communication protocol. The system can be in data communication with a first financial institution and a second financial institution. The system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The operations also can include determining, at the system and using the merchant account database, first information including a second account identifier for a second account of the merchant at the second financial institution. The second account identifier can be associated with the merchant identifier in the merchant account database. The plurality of account identifiers can include the second account identifier. The operations additionally can include sending the first information from the system to the first financial institution. The operations further can include receiving in real-time over a network, at the system and from the first financial institution, payment information regarding the payment to the second account from a first account of the consumer at the first financial institution to pay the merchant the payment amount for the one or more items. The payment information can include information about the second account identifier of the second account and the payment amount. The operations additionally can include logging the payment information in a transaction database. The operations further can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. An account number of the first account of the consumer can remain undisclosed to the merchant.

[0089] Additional embodiments include a system including one or more processors. The system can include a merchant account database comprising a plurality of merchant identifiers being associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The system also can include a transaction database. The system additionally can include one or more non-transitory computer-readable media storing computing instructions that, when executed by the one or more processors, cause the one or more processors to perform certain operations. The operations also can include receiving, at the system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant of the plurality of merchants by the consumer for a payment amount, a request comprising a merchant identifier of the plurality of merchant identifiers associated with the merchant. The mobile device obtains the merchant identifier using a data communication protocol. The system is in data communication with a consumer financial institution and a merchant financial

institution. The system is maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution. The operations also can include determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant at the merchant financial institution. The merchant account identifier is associated with the merchant identifier in the merchant account database. The plurality of account identifiers comprise the merchant account identifier. The operations also can include sending the first information from the system to the consumer financial institution. The operations also can include receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items. The payment information comprises a transaction identifier, the merchant account identifier of the merchant account, and the payment amount. The operations also can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive an account number of the consumer account of the consumer. The consumer does not receive an account number of the merchant account of the merchant.

[0090] Further embodiments include a computer-implemented method comprising receiving, at a system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant by the consumer for a payment amount, a request comprising a merchant identifier associated with the merchant. The system comprises a merchant account database and a transaction database, The merchant account database comprises a plurality of merchant identifiers associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The plurality of merchants comprise the merchant. The plurality of merchant identifiers comprise the merchant identifier. The mobile device obtains the merchant identifier using a data communication protocol. The system is in data communication with a consumer financial institution and a merchant financial institution. The system is maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution. The method also can include determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant maintained by the merchant financial institution. The merchant account identifier is associated with the merchant identifier in the merchant account database. The plurality of account identifiers comprise the merchant account identifier. The method also can include sending the first information from the system to the consumer financial institution. The method also can include receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items. The payment information comprises a transaction identifier, the merchant account identifier of the merchant account, and the payment amount. The method also can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive an account number of the consumer account of the consumer. The consumer does not receive an account number of the merchant account of the merchant.

[0091] Further embodiments include one or more non-transitory computer-readable media comprising computer instructions that, when executed by one or more processors, perform certain operations. The operations can include receiving, at a system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant by the consumer for a payment amount, a request comprising a merchant identifier associated with the merchant. The system comprises a merchant account database and a transaction database, The merchant account

database comprises a plurality of merchant identifiers associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers. The plurality of merchants comprise the merchant. The plurality of merchant identifiers comprise the merchant identifier. The mobile device obtains the merchant identifier using a data communication protocol. The system is in data communication with a consumer financial institution and a merchant financial institution. The system is maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution. The operations also can include determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant maintained by the merchant financial institution. The merchant account identifier is associated with the merchant identifier in the merchant account database. The plurality of account identifiers comprise the merchant account identifier. The operations also can include sending the first information from the system to the consumer financial institution. The operations also can include receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items. The payment information comprises a transaction identifier, the merchant account identifier of the merchant account, and the payment amount. The operations also can include sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant. The merchant does not receive an account number of the consumer account of the consumer. The consumer does not receive an account number of the merchant account of the merchant.

[0092] Turning to the drawings, FIG. 1 illustrates a block diagram of a system **100** that can be employed for a secure real-time payment transaction network, according to an embodiment. System **100** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. The system can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of system **100** can perform various procedures, processes, and/or activities. In other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements, systems, or modules of system **100**.

[0093] In some embodiments, system **100** can include one or more point-of-sale terminals, such as point-of-sale terminal **110**; one or more mobile devices, such as mobile device **120**; two or more financial institutions, such as financial institutions **130** and **150**; and/or a transaction system **140**. In other embodiments, system **100** also can include a wallet provider **160**. In a number of embodiments, each of the point-of-sale terminals, the one or more mobile devices, the two or more financial institution, and the transaction system can be or include a computer system, such as computer system **700**, as shown in FIG. 7 and described below, and can be a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. In many embodiments, various components (e.g., **110**, **120**, **130**, **140**, **150**, **160**) of system **100** can be in data communication with various other components (e.g., **110**, **120**, **130**, **140**, **150**, **160**) of system **100**, such as through one or more networks. The networks can be the Internet and/or other suitable public and/or private data communication networks.

[0094] In various embodiments, point-of-sale terminal **110** can be located within a store of a merchant, such as merchant **119**. In several embodiments, the store can be a place of business, which can offer and/or sell items, such as products and/or services. In a number of embodiments, point-of-sale terminal **110** can be used to checkout a consumer **129** using mobile device **120** for one or more items to be purchased by consumer **129**. In many embodiments, point-of-sale terminal **110** can include one or more systems, such as a checkout system **111**, a communication system **112**, a payment system **113**, a consumer information system **114**, a security system **115**, a

preauthorization system **116**, a proxy communication system **117**, and/or other suitable systems. For example, in various embodiments, checkout system **111** can be used to determine the payment amount, communication system **112** can communicate with other components of system **100**, payment system **113** can determine whether consumer **129** has satisfactorily paid for the one or more items to be purchased, consumer information system **114** can store information regarding consumer **129**, security system **115** can be used to generate a merchant security transaction code, preauthorization system **116** can handle a preauthorization code from mobile device **120** when mobile device **120** is offline, and/or proxy communication system **117** can handle proxy communications through point-of-sale terminal **110** when mobile device **120** is offline, as described below in further detail. In many embodiments, point-of-sale terminal **110** can be a register (e.g., cash register) that includes a card reader and communications with one or more card networks (e.g., STAR network, VISA network, etc.). In other embodiments, point-of-sale terminal **110** can be a register that is without a card reader or the ability to communicate with card networks.

[0095] In a number of embodiments, mobile device **120** can be used by consumer **129** to initiate a payment to merchant **119** for the one or more items to be purchased. In various embodiments, mobile device **120** can run a mobile application **123**, such as a mobile wallet, which can be employed to facilitate paying merchant **119**. In a number of embodiments, mobile device **120** and/or mobile application **123** can include one or more systems, such as an authentication system **121**, an account system **122**, a communication system **124**, a security system **125**, a loan system **126**, a stand-in credit system **127**, a proxy communication system **128**, and/or other suitable systems. For example, in various embodiments, authentication system **121** can verify the identity of consumer **129**, account system **122** can provide information regarding a consumer account of consumer **129**, communication system **124** can communicate with other components of system **100**, security system **125** can decipher and/or decode the merchant security transaction code and/or verify the digital signature of the merchant security transaction code, loan system **126** can present options and receive instructions regarding processing the transaction at least partially using a loan or credit charge, stand-in credit system **127** can handle a preauthorization code to facilitate payment when mobile device **120** is offline, and/or proxy communication system **128** can handle proxy communications with point-of-sale terminal **110** when mobile device **120** is offline, as described below in further detail.

[0096] In several embodiments, when consumer **129** using mobile device **120** is at point-of-sale terminal **110** to checkout, point-of-sale terminal **110** can determine the payment amount for the one or more items, and can communicate information to mobile device **120**, such as the payment amount, a merchant identifier, and/or a transaction identifier. In some embodiments, the merchant identifier can uniquely identify point-of-sale terminal **110**. For example, in some embodiments, each point-of-sale terminal can have a unique merchant identifier. In a number of embodiments, the merchant identifier can uniquely identify the merchant (e.g., merchant **119**). For example, each merchant (e.g., merchant **119**) can have a unique merchant identifier. In some embodiments, the merchant identifier can be a token that can be associated with merchant **119** and/or point-of-sale terminal **110**. In many embodiments, when merchant **119** sets up, configures, and/or reconfigures, point-of-sale terminal **110**, the merchant identifier can be created and/or assigned to point-of-sale terminal **110**. In the same or different embodiments, one part of the merchant identifier can uniquely identify merchant **119**, and another part of the merchant identifier can uniquely identify point-of-sale terminal **110**, such that the part of the merchant identifier that uniquely identifies merchant **119** is the same for all point-of-sale terminals owned or used by merchant **119**.

[0097] In various embodiments, mobile device **120** and point-of-sale terminal **110** can communicate with each other (either one-way or two-way) using a wireless data communication protocol. In some examples, the communication protocol can allow for one-way or two-way communication. For example, the wireless data communication protocol can be a proximity-based wireless data communication protocol, such as Near Field Communication (NFC), Bluetooth,

Bluetooth Low Energy (BLE), iBeacon, etc. In other embodiments, mobile device **120** and/or point-of-sale terminal **110** can communicate with each other using another suitable form of communication. For example, in some embodiments, point-of-sale terminal **110** can provide a barcode (such as a QR (Quick Response) code), which can be scanned using a camera of mobile device **120**, and/or mobile device **120** can provide a barcode (such as a QR code), which can be scanned using an optical scanner of point-of-sale terminal **110**. In a number of embodiments, communication system **112** can provide communication functionality for point-of-sale terminal **110**, and/or communication system **124** can provide communication functionality for mobile device **120**.

[0098] In several embodiments, transaction system **140** can be in data communication with various financial institutions, such as financial institution **130** and/or financial institution **150**, and can provide for interaction, facilitate communications, and/or facilitate transactions between the financial institutions, such as financial institutions **130** and **150**. In a number of embodiments, transaction system **140** can include one or more systems, such as a communication system **143**, an account system **144**, a transaction system **145**, a security system **146**, a preauthorization system **147**, a proxy communication system **148**, and/or other suitable systems. In some embodiments, communication system **143** can be used to provide communications with the financial institutions (e.g., **130**, **150**). In many embodiments, transaction system **140** can include a merchant account database **141** and/or a transaction database **142**, as described below in further detail. In some embodiments, account system **144** can interface with merchant account database **141**, and/or transaction system **145** can interface with transaction database **142**. In a number of embodiments, security system **146** can interface with security system **115** to facilitate providing a merchant security code, as described below in further detail. In several embodiments, preauthorization system **147** can handle a preauthorization code from mobile device **120** when mobile device **120** is offline, and/or proxy communication system **148** can handle proxy communications through transaction system **140** when mobile device **120** is offline, as described below in further detail. In many embodiments, transaction system **140** can include a network system that facilitates communications between the various financial institutions (e.g., financial institution **130** and financial institution **150**). This network system can have any suitable topology, such as hub and spoke, peer-to-peer, or another suitable topology.

[0099] In a number of embodiments, the financial institutions (e.g., **130**, **150**) can be depository financial institutions, such as savings banks, credit unions, savings and loan associations, card issuing financial institutions, or other forms of financial institutions. In a number of embodiments, financial institution **130** can include one or more consumer accounts **131** associated with consumer **129**. In various embodiments, consumer accounts **131** can include one or more demand deposit accounts (e.g., a checking account, savings account, or cash balance account), and non-demand deposit accounts (i.e., an account other than a demand deposit account), such as a lending account (e.g., a loan account or a credit account) or another type of account (e.g., a points account). In some embodiments, financial institution **130** can include one or more systems, such as a communication system **132**, an authorization system **133**, an account system **134**, a loan system **135**, a preauthorization system **136**, a proxy communication system **137**, and/or other suitable systems. For example, in some embodiments, account system **134** can interface with consumer account **134** to provide information regarding the status of one or more of consumer accounts **131**, and/or can store and/or determine information regarding other accounts. In a number of embodiments, communication system **132** can communicate with other components of system **100**. In various embodiments, authorization system **133** can authorize payments from one or more of consumer accounts **131**. In a number of embodiments, account system **134** can obtain information, such as balances and statuses, about one or more of consumer accounts **131**. In several embodiments, preauthorization system **136** can handle generating a preauthorization code for mobile device **120** to facilitate transactions when mobile device **120** is offline, and/or proxy communication system

137 can handle proxy communications through financial institution **130** when mobile device **120** is offline, as described below in further detail.

[0100] In a number of embodiments, financial institution **150** can include a merchant account **151** associated with merchant **119**. In various embodiments, merchant account **151** can be a deposit account or another suitable type of account. In some embodiments, financial institution **150** can include one or more systems, such as communication system **152**, account system **153**, a proxy communication system **154**, and/or other suitable systems, as described below in further detail. For example, in some embodiments, account system **153** can interface with merchant account **151** to provide information regarding the status of merchant account **151**, and/or can store and determine information regarding other accounts. In a number of embodiments, communication system **152** can communicate with other components of system **100**. In some embodiments, proxy communication system **154** can handle proxy communications through financial institution **150** when mobile device **120** is offline, as described below in further detail.

[0101] In several embodiments, merchant account database **141** of transaction system **140** can store information regarding merchants (e.g., merchant **119**) and merchant accounts. For example, in a number of embodiments, merchant account database **141** can store a mapping between merchant identifiers and merchant accounts. For example, a certain merchant identifier can be associated with merchant **119** and merchant account **151** of merchant **119** maintained by financial institution **150**. When provided with the merchant identifier, account system **144** and merchant account database **141** can be used by transaction system **140** to determine an account identifier (e.g., an account number) of merchant account **151**, the name of merchant **119**, a location of merchant **119**, a location of point-of-sale terminal **110**, and/or other information regarding merchant **119** and/or the merchant account. For example, in some embodiments, transaction system **140** can provide risk information (e.g., a risk score) regarding merchant **119** and/or merchant account **151**. In some embodiments, a merchant can have three point-of-sale terminals, such as point-of-sale terminal **110**, each with a unique identifier, which can each be associated with a single account of merchant **119**, specifically, merchant account **151**.

[0102] In many embodiments, the merchant identifier can be a public identifier that serves as an alias to identify merchant **119** and/or point-of-sale terminal **110** of merchant **119** among the various components (e.g., **110**, **120**, **130**, **140**, **150**, **160**) of system **100**. In a number of embodiments, merchant **119** can enroll and/or register with transaction system **140** through financial institution **150**, through a merchant consortium, or directly. In several embodiments, the merchant identifier for merchant **119** and or point-of-sale terminal **110** of merchant **119** can be selected and/or assigned at the time of enrollment or registration. In some embodiments, the merchant identifier can be a phone number, an email address, a terminal identifier, or another suitable identifier. As part of enrollment and/or registration transaction system **140** can verify that merchant **119** is a legitimate (e.g., bona fide) merchant, such as by vetting merchant **119** through financial institution **150** and/or another enrollment entity.

[0103] In several embodiments, upon or after enrolling and/or registering with transaction system **140**, merchant **119** and/or point-of-sale terminal **110** can be provided with a security system **115**, which can be computing instructions that are used to create a merchant security transaction code. In some embodiments, security system **115** of point-of-sale terminal **110** can communicate with security system **146** of transaction system **140**, such as through application programming interface (API) calls. In other embodiments, security system **115** of point-of-sale terminal **110** can be self-contained computing instructions (i.e., that do not call security system **146** of transaction system **140**) that are provided by transaction system **140** (e.g., at the time of enrollment and/or registration), or are based on instructions and/or a software development kit (SDK) provided by transaction system **140** (e.g., at the time of enrollment and/or registration).

[0104] In many embodiments, security system **115** can be used by merchant **119** during a transaction to generate a merchant security transaction code. In many embodiments, the merchant

security transaction code can include various information, such as the payment amount for the transaction, a transaction identifier that uniquely identifies the transaction to merchant **119** and/or point-of-sale terminal **110**, the merchant identifier, a date and/or time of the transaction, a list of the items purchased, a digital signature, and/or other suitable information. In many embodiments, this information can be encoded in the merchant security transaction code using a suitable data encoding method. In many embodiments, the digital signature can be generated based on the data in the merchant security transaction code. The digital signature can be generated using a suitable digital signature code signing algorithm as part of a digital signature scheme. For example, the code signing algorithm can be public-key cryptography signing algorithm, such as those used in public key infrastructure (PKI), a cryptographic hash function, such as one of the Secure Hash Algorithm (SHA) published by the National Institutes of Standards and Technology (NIST) (e.g., SHA-256), or another suitable signing algorithm. The digital signature can be used to verify that merchant **119** created the merchant security transaction code and/or that the data in the merchant security transaction code has not been corrupted or tampered with after having being created by security system **115**.

[0105] In several embodiments, the merchant security transaction code can be a data code that can be transmitted between point-of-sale terminal **110** and mobile device **120** using a wireless data communication channel, as described above. In other embodiments, the merchant security transaction code can be encoded as a barcode, such as a one-dimensional (1D), two-dimensional (2D), or three-dimensional (3D) barcode, which can be optically ready by mobile device **120**, such as by using a camera on mobile device **120**, as described above. For example, the merchant security transaction code can be encoded as a matrix barcode, such as a QR code, and displayed on point-of-sale terminal **110** to be scanned by a camera on mobile device **120**. In still other embodiments, the merchant security transaction code can be transferred manually from point-of-sale terminal **110** to mobile device **120** by the merchant security transaction code being displayed on point-of-sale terminal **110** and then being manually entered in mobile application **123** of mobile device **120**.

[0106] In many embodiments, system **100** can provide a transaction network for secure real-time payments. In several embodiments, mobile application **123** of mobile device **120** can be used by consumer **129** to push a payment from one or more of consumer accounts **131** to merchant account **151** to satisfy an expectation of payment while consumer **129** is waiting at point-of-sale terminal **110**. In a number of embodiments, mobile application **123** can be associated with and/or configured to be associated with financial institution **130** and/or one or more of consumer accounts **131**. For example, account system **122** can associate mobile application **123** with one or more of consumer accounts **131** at financial institution **130**. In some embodiments, mobile application **123** can be provided by financial institution **130** as a mobile application for use on mobile device **120**. In other embodiments, mobile application **123** can be associated with multiple different financial institutions and accounts of consumer **129** at those financial institutions.

[0107] In some embodiments, mobile device **120** can be designed to be in data communication with mobile wallet provider **160**. In many embodiments, mobile wallet provider **160** can communicate with mobile application **123** on mobile device **120**. In several embodiments, mobile wallet provider **160** can be part of, or provided by, financial institution **130**. For example, mobile application **123** can be an application provided by financial institution **130** for installation on mobile device **120**. In other embodiments, mobile wallet provider **160** can be part of, or provided by, transaction system **140**. For example, mobile application **123** can be an application provided by the entity that operates transaction system **140** for installation on mobile device **120**. In still other embodiments, mobile wallet provider **160** can be part of, or provided by, another entity. For example, mobile wallet provider **160** can be another suitable mobile wallet provider, and can be similar or identical to Apple Pay by Apple, Inc. of Cupertino, California, or Google Pay by Google, LLC of Mountain View, California, for example. In a number of embodiments, mobile wallet provider **160** can include a proxy communication system **161**. In several embodiments, proxy

communication system **161** can handle proxy communications through mobile wallet provider **160** when mobile device **120** is offline, as described below in further detail.

[0108] In some embodiments, mobile wallet provider **160** can communicate with mobile device **120** through communication channel **171**, mobile device **120** can communicate with point-of-sale terminal **110** through communication channel **172**, point-of-sale terminal **110** can communicate with financial institution **150** through communication channel **173**, transaction system **140** can communicate with financial institution **150** through a communication channel **174**, transaction system **140** can communicate with financial institution **130** through a communication channel **175**, mobile wallet provider **160** can communicate with financial institution through communication channel **176**, transaction system **140** can communicate with mobile wallet provider through communication channel **177**, and/or transaction system **140** can communicate with point-of-sale terminal **110** through communication channel **178**. As described above, communication channel **171** can be a wireless data communication channel. In other embodiments, communications between mobile device **120** and point-of-sale terminal **110** can be through done through optical scanning or manual methods, as described above. In many embodiments, communication channels **173**, **174**, **175**, **176**, **177**, and/or **178** can be through the Internet or other suitable networks. In some embodiments, transaction system **140** does not communicate with mobile wallet provider **160**, such that communication channel **177** does not exist. In some embodiments, transaction system **140** does not communicate with point-of-sale terminal, such that communication channel **178** does not exist. [0109] In many embodiments, communication channel **171** can be dependent on mobile device **120** being able to communicate with mobile wallet provider **160**. For example, mobile **120** can communicate with the Internet through a cellular data network or through a wireless local area network. If either of these communication channels is unavailable or not working, or if the Internet link to mobile wallet provider **160** is not working, and thus communication channel **171** is not working, mobile device **120** can be called “offline,” or unable to communicate with mobile wallet provider **160**. When communication channel **171** is working, mobile device **120** can be called “online,” or in data communication with mobile wallet provider **160**.

[0110] In several embodiments, financial institution **130** can generate a preauthorization code that includes a preauthorization amount and, in some embodiments, an expiration time. In many embodiments, the preauthorization code can include a digital signature that indicates that financial institution **130** is the source of the preauthorization code. In many embodiments, preauthorization system **136** can generate the preauthorization code. In a number of embodiments, the preauthorization amount of the preauthorization code can be based on the account balance of one or more consumer accounts **131**. For example, the preauthorization amount can be determined by preauthorization system **136** based on the current balance and/or historical trends of the account balance. In several embodiments, the expiration time can be a predetermined length of time, such as 30 minutes, 1 hour, 2 hours, 3 hours, 6 hours, 12 hours, 24 hours, 2 days, 3 days, or 1 week, from the time that the preauthorization code is generated. In other embodiments, the expiration time can be determined based on the account balance, the preauthorization amount, historical trends of the account balance, and/or other factors. In some embodiments, the digital signature can be generated using a suitable digital signature code signing algorithm as part of a digital signature scheme, similarly as described above for the merchant security transaction code. In many embodiments, the preauthorization code can be sent through mobile wallet provider **160** to mobile device **120** and stored in mobile device **120** while mobile device **120** is online. In several embodiments, the preauthorization code can provide a “stand-in” credit in mobile device **120**, which can allow consumer **129** to conduct a transaction using mobile device **120** if mobile device **120** is offline at the time of the transaction. For example, the stand-in credit can allow consumer **129** to conduct a transaction that does not exceed the preauthorization amount, provided that the expiration time has not yet passed.

[0111] In many embodiments, the preauthorization code can be verified by point-of-sale terminal

110, merchant **119**, financial institution **150**, and/or transaction system **140**. For example, the digital signature in the preauthorization code can be verified to ensure that the preauthorization code was authorized by financial institution **130** and/or mobile wallet provider **160**. In some embodiments, this verification can be done at merchant **119**, such as in point-of-sale terminal **110**, or can be done in financial institution **150** and/or transaction system **140**. For example, a public key of financial institution **130** can be used to verify the digital signature.

[0112] In many embodiments, merchant account **151** at financial institution **150** can receive payment from consumer account **131** at financial institution **130**, based on the verified preauthorization. In some embodiments, a debit pull can be done in real time or later (e.g., in nightly batch processing), but funds can be made available immediately to merchant **151** based on the preauthorized promise from financial institution **130**. In other embodiments, the payment can be effectuated later after mobile device **120** comes back online and communicates with mobile wallet provider **160** to initiate the payment, or after a timeout period.

[0113] In several embodiments, mobile application **123** can provide information to consumer **129** regarding the status of one or more of consumer accounts **131** and availability of funds in one or more of consumer accounts **131**, or the stand-in credit amount stored in mobile device **120**. For example, account system **122** of mobile device **120** can obtain information from account system **134** of financial institution **130** regarding one or more of consumer accounts **131** and provide that information to consumer **129**. For example, if one of consumer accounts **131** has an available balance and/or available credit of \$500, mobile application **123** can communicate the amount of the available funds for one or more of consumer accounts **131** to consumer **129**, which can allow consumer **129** to know the amount of the available funds for spending before shopping for items and/or before attempting to purchase items. In a number of embodiments, account system **134** can provide account system **122** with various other information, such as the current status of one or more of consumer accounts **131**, such as whether one or more of consumer accounts **131** is open and in good status (or closed), whether one or more of consumer accounts **131** has had recent not sufficient funds (NSF) activity, whether one or more of consumer accounts **131** has a stop payment order, and/or a buying power index of consumer **129** at least partially based on information about one or more of consumer accounts **131**.

[0114] In some embodiments, mobile application **123** can be used on mobile device **120** at point-of-sale terminal **110** to conduct a transaction. In several embodiments, mobile device **120** can receive the merchant identifier and other transaction information from point-of-sale terminal **110** of merchant **119**. The merchant identifier can be associated with merchant account **151** of merchant **119**. After receiving the merchant identifier, mobile application **123** can initiate a push payment from one or more of consumer accounts **131** at financial institution **130** to merchant account **151** at financial institution **150** to complete the transaction in real-time before the consumer leaves the store of merchant **119**. In many embodiments, mobile device **120** can receive the merchant identifier and other transaction information from point-of-sale terminal **110** as part of the merchant security transaction code.

[0115] In various embodiments, authentication system **121** can verify the identity of consumer **129**. For example, authentication system **121** can verify the identity of consumer **129** using a personal identification number (PIN), a password, one or more fingerprints, voice recognition, other biometrics (e.g., mobile phone bio-measurements), and/or other suitable authentication methods, to ensure that consumer **129** is authorized to associate mobile application **123** with one or more of consumer accounts **131** and/or make payments using mobile application **123**.

[0116] In a number of embodiments, when mobile application **123** is used to conduct a transaction, mobile device **120** can be put in the proximity of point-of-sale terminal **110** to allow communication system **124** to receive information from point-of-sale terminal **110**, such as the payment amount, the merchant identifier, a transaction identifier, and/or other information, such as the merchant name, the date and time, a list of SKUs (stock keeping units) of the one or more items

to be purchased, etc. In many embodiments, mobile device **120** can receive the merchant identifier and other transaction information from point-of-sale terminal **110** as part of the merchant security transaction code. In several embodiments, security system **125** of mobile device **120** can verify the digital signature in the merchant security transaction code. For example, security system **125** can verify the digital signature using a signature verifying algorithm that is part of the same digital signature scheme that was used to digitally sign the merchant security transaction code. For example, a public key for merchant **119** can be used to verify the digital signature and the merchant security transaction code. By verifying the digital signature of the merchant security transaction code, security system **125** can verify that the merchant identifier is from point-of-sale terminal **110** of merchant **119** and is accurate, which can advantageously ensure that the funding from consumer accounts **131** will be sent to an account actually associated with the merchant instead of a fraudster. [0117] In some embodiments, mobile application **123** can be configured to allow one-click checkout, which can be enabled by selecting a button on mobile application **123** or by placing mobile device **120** in the proximity of a data transmitter on point-of-sale terminal **110**. In some embodiments, mobile application **123** can be configured to scan items and conduct transactions in real-time as items are taken from the shelf and scanned by mobile device **120** or placed within a “smart” shopping cart, such that checkout can take place in an aisle of the store, rather than at point-of-sale terminal **110**. In other embodiments, checkout can take place automatically when consumer **129** exits the store of merchant **119**. In a number of embodiments, mobile application **123** can receive the merchant identifier upon entering the store of merchant **119** or from a shopping cart having data transmitted in the store of merchant **119**.

[0118] In some embodiments, the mobile application **123** can send information from mobile device **120** to point-of-sale terminal **110**, such as information regarding consumer **129**, such as personally identifiable information, loyalty rewards number(s), shopping patterns, points, buying power index, and/or other suitable information. In several embodiments, consumer information system **114** can process the information provided from mobile application **123** to provide information to merchant **119** regarding consumer **129**. In some embodiments, mobile device **120** can communicate information, such as a buying power index, to point-of-sale terminal **110** and/or merchant **119** upon entering the store of merchant **119**.

[0119] In several embodiments, consumer **129** can decide whether to authorize the transaction using mobile device **120**. For example, mobile device **120** can ask consumer **129** to approve the transaction in mobile application **123**. In a number of embodiments, mobile application **123** can present the one or more of consumer accounts **131** to consumer **129** to select which of the consumer accounts **131** to use to fund the transaction. In some embodiments, consumer **129** can choose to split the funding of the transaction among multiple accounts. For example, consumer **129** can choose to fund 20% of the transaction from a demand deposit account (e.g., a debit account) and 80% of the transaction from a non-demand deposit account (e.g., by a charge to a credit account). In some embodiments, if an account of the one or more of consumer accounts **131** has an account balance that is less than the amount of the transaction (or the portion of the transaction that consumer **129** has chosen to allocate to the account), loan system **126** of mobile device **120** can determine that there is a deficiency and can present an option to fund the transaction (or a portion of the transaction) using a non-demand deposit account, such as a loan account, a credit account, or a points account. In other embodiments, loan system **126** can present the option for funding the transaction through a non-demand deposit account even if there is no deficiency in the one or more of consumer accounts **129**.

[0120] In some embodiments, the loan account can be a new account that is created upon consumer **129** choosing to fund the transaction (or portion thereof) with the loan account. In other embodiments, the loan account can be for a previously authorized loan. In some embodiments, the loan account can have a pre-existing loan balance, which can be increased based on the amount of loan used to fund the transaction. In several embodiments, the loan can be a small loan, and can

be labeled a “micro-loan”), but can be treated the same as credit line for a loan instead of an overdraw of an account.

[0121] In several embodiments, consumer **129** can make the decision from which account or accounts to fund the transaction, and/or to authorize a loan or a credit transaction, while at or near the point-of-sale terminal **110** in the store of merchant **119**. In the same or other embodiments, loan system **126** can allow consumer **129** to choose the one or more accounts from which to fund the transaction after consumer **129** has left the store. In many embodiments, financial institution **130** can fund the transaction temporarily from a shadow account that the bank uses to fund overdraft transaction, which can be reimbursed from the one or more accounts selected by consumer **129**. For example, consumer **129** can authorize a transaction at point-of-sale terminal **110** in the store, and financial institution **130** can authorize transfer of funds to financial institution **150** to pay merchant **119**, and after consumer **129** leaves the store of merchant **129**, loan system **126** can push a message to consumer **129** asking for one or more of consumer accounts **131** that consumer **129** wants to use to fund the transaction. The options of consumer accounts **131** can include the option to open a new loan account, or to add to the balance of an existing loan account. In some embodiments, consumer **129** can setup a list (e.g., prioritized list) of consumer accounts **131** to use for transaction using mobile device **120**, and/or can setup before-hand an amount and/or percentage to use from one or more of the accounts. For example, consumer **129** can choose to use a debit account for the first \$50 and then use a credit account for the rest. As another example, consumer **129** can choose to use a debit account for 40% of the transaction, and use a new micro-loan for the rest.

[0122] In some embodiments, a points account can be used to pay for all or at least a portion of the payment. For example, consumer **129** can have a points account at financial institution **130**, which can have a balance of points earned by consumer **129** at financial institution **130**. In many embodiments, these points can have an exchange value, such that the points can be redeemed to pay for all or at least a portion of the payment.

[0123] In a number of embodiments, if mobile device **120** is offline, the stand-in credit can be presented as an option to fund the transaction. In other embodiments, if mobile device **120** is offline, mobile device **120** can communicate with point-of-sale terminal **110** to communicate through a proxy communication channel. In many embodiments, the proxy communication channel can extend from point-of-sale terminal **110** to mobile wallet provider **160**. For example, in some embodiments, the proxy communication channel can comprise communication channels **173**, **174**, and **177**, and can extend through financial institution **150** and transaction system **140**. In other embodiments, the proxy communication channel can comprise communication channels **173**, **174**, **175**, and **176**, and can extend through financial institution **150**, transaction system **140**, and financial institution **130**. In still other embodiments, the proxy communication channel can comprise communication channels **178** and **177**, and can extend through transaction system **140**. In yet other embodiments, the proxy communication channel can comprise communication channels **178**, **175**, and **176**, and can extend through transaction system **140** and financial institution **130**. In a number of embodiments, the proxy communication channel also can include communication channel **172**, and can extend through point-of-sale terminal **110**. When mobile device **120** is offline, communication channel **171** is unavailable, so mobile device **120** can communicate with mobile wallet provider **160** instead using the proxy communication channel.

[0124] In many embodiments, proxy communication system **128** can facilitate proxy communications being sent from or received by mobile device **120**. In a number of embodiments, proxy communication system **117** can facilitate proxy communications sent from, received by, or through point-of-sale terminal **110**. In some embodiments, proxy communication system **154** can facilitate proxy communications through financial institution **150**. In several embodiments, proxy communication system **148** can facilitate proxy communications through transaction system **140**. In a number of embodiments, proxy communication system **137** can facilitate proxy communications through financial institution **130**. In several embodiments, proxy communication

system **161** can facilitate proxy communications received by or sent from mobile wallet provider **160**.

[0125] In several embodiments, communications through the proxy communication channel can be encrypted. For example, a one-way message from mobile device **120** to mobile wallet provider **160** through the proxy communication channel can be encrypted using a public key of mobile wallet provider **160**, such that only mobile wallet provider **160** can decrypt the message using the private key of the mobile wallet provider, using a public-key encryption algorithm. In some embodiments, a message from mobile device **120** to mobile wallet provider **160** can be digitally signed by mobile device **120**, such that the mobile wallet provider can verify that the message originated from consumer **129** using mobile device **120**. In other embodiments, two-way encrypted communications can be established using another suitable cryptographic protocol, such as performing a cryptographic handshake to create a secure encrypted connection through the proxy communication channel using symmetric cryptography with a private key, similar to Transport Layer Security (TLS). When the proxy communication channel is used to send a message from mobile device **120** to mobile wallet provider **160**, the message received by mobile wallet provider **160** through the proxy communication channel can be treated the same by mobile wallet provider **160** as a message from mobile device **120** received by mobile wallet provider **160** through communication channel **171**.

[0126] In many embodiments, after mobile device **120** has communicated with point-of-sale terminal **110** using communication system **124** to receive the merchant identifier and other transaction information, and consumer **129** has authorized the transaction, mobile device **120** can communicate with financial institution **130** and/or transaction system **140**, through mobile wallet provider **160** (which, in some embodiments, can be part of financial institution **130** or transaction system **140**), to request a payment be made to merchant account **151** of merchant **119** from one or more of consumer accounts **131**. When mobile device **120** is online, mobile device **120** can communicate with mobile wallet provider **160** through communication channel **170**. In some embodiments, when mobile device **120** is offline, mobile device **120** can communicate with mobile wallet provider **160** through the proxy communication channel described above, and then the request can be sent from mobile wallet provider **160** to financial institution **130**. In some such embodiments, mobile device **120** can generate an encrypted transaction code to be sent through the proxy communication channel to mobile wallet provider **160**. In many embodiments, the encrypted transaction code can include a preauthorization from consumer **129** to pay a transaction amount. In a number of embodiments, the preauthorization can be digitally signed by mobile device **120**, such that the preauthorization can be verified by mobile wallet provider **160**. In other embodiments, the stand-in credit can be used, as described above and below in further detail.

[0127] In a number of embodiments, when mobile device **120** communicates with financial institution **130** (such as through mobile wallet provider **160**, which, in some embodiments, can be part of financial institution **130**) to request a payment be made, account system **134** of financial institution **130** can determine account information about merchant account **151**, such as the account identifier of merchant account **151**, at least partially based on the merchant identifier received from mobile device **120**. In some embodiments, financial institution **130** can communicate with transaction system **140** to get the account information about merchant account **151**, which can be stored in merchant account database **141**. In some embodiments, financial institution **130** can save the account information about merchant account **151** so financial institution does not need to query the account information from merchant account database **141** in transaction system **140** for future transaction involving the same merchant identifier. In other embodiments, financial institution **130** can query for the account information from merchant account database **141** in transaction system **140** for each new transaction, or at occasional and/or regular intervals. In other embodiments, when mobile device **120** communicates with transaction system **140** through mobile wallet provider **160** to request a payment be made, transaction system **140** can provide the account information about

merchant account **151** to first financial institution **130**. In still other embodiments, mobile device **120** can communicate to mobile wallet provider **160** through the proxy communication channel, as described above.

[0128] In many embodiments, having the account information about merchant account **151**, financial institution **130** can initiate a payment to financial institution **150** from one or more of consumer accounts **131** to merchant account **151**. In several embodiments, before initiating payment, authorization system **133** can determine whether to authorize payment from one or more of consumer accounts **131**. For example, financial institution **130** can determine whether the payment amount is within the available funds in one or more of consumer accounts **131**, determine whether one or more of consumer accounts **131** is currently open and in good status (or closed), authenticate the identity of consumer **129** using mobile device **120**, and/or perform other actions. For example, in some embodiments, authentication system **121** can authenticate the identity of consumer **129**, and that information can be communicated from mobile device **120** to financial institution **130**. In some embodiments, mobile device **120** can prompt consumer **129** to authenticate before and/or after mobile device **120** receives the merchant identifier and/or the transaction information from point-of-sale terminal **110**.

[0129] In some embodiments, authorization system **133** can request additional authentication from authentication system **121** (which can be directly through a network between financial institution **130** and mobile device **120**, or can be through mobile wallet provider **160** and/or through transaction system **140**) after receiving the request for payment from mobile device **120** and/or after receiving the information about merchant **119** and/or merchant account **151**. In a number of embodiments, authorization system **133** of financial institution **130** can perform different and/or varying levels of authentication based on various factors. For example, authentication system **121** and/or authorization system **133** can determine whether mobile device **120** used to send the request for payment has been previously used by consumer **129** for transaction with financial institution **130**, whether biometrics of the consumer match stored biometrics of consumer **129**, whether the requested transaction and associated details (e.g., the identity of merchant **119**, the location of merchant **119**, the payment amount, the one or more items to be purchased (e.g., a list of SKUs), and/or other suitable factors) are consistent with spending patterns of consumer **129**, whether consumer **129** has reported mobile device **120** lost or stolen, whether consumer **129** has reported that credit cards, debit cards, or other information about one or more of consumer accounts **131** have been lost or stolen, and/or other suitable factors. In various embodiments, financial institution **130** can adjust the level of authentication used to verify the identity of consumer **129** based on one or more of these factors, and/or based on the payment amount, the identity of merchant **119**, the location of merchant **119**, historical spending of consumer **129**, and/or other relevant information.

[0130] In some embodiments, if one or more of consumer accounts **131** chosen by consumer **129** for the transaction is short on funds or otherwise cannot be fully used, loan system **135** can communicate with loan system **126** to present other funding options to consumer **129**, such as the option for a micro-loan to fund all or part of the transaction, as described above.

[0131] In many embodiments, after receiving authorization from authorization system **133**, financial institution **130** can initiate a payment to financial institution **150** to transfer funds from one or more of consumer accounts **131** to merchant account **151**. In a number of embodiments, the payment can be effected by sending payment information regarding a payment to be made to merchant account **151** from one or more of consumer accounts **131**. In a number of embodiments, the payment information transferred from financial institution **130** to financial institution **150** can effectuate an authenticated credit push, which can irrevocably satisfy payment to the merchant and/or ensure that the merchant has good funds when consumer **129** leaves the store of merchant **119**. For example, the payment can be a settlement credit push of funds for the payment amount from one or more of consumer accounts **131** to merchant account **151**, which can be settled immediately. In various embodiments, the payment information transferred from financial

institution **130** to financial institution **150** can effectuate a push promise to pay, which can provide an irrevocable guarantee of payment from financial institution **130** to financial institution **150**. In several embodiments, for example, the payment can be an ACH (Automated Clearing House) credit push, which can provide an irrevocable funding guarantee.

[0132] In many embodiments, the payment and/or the guarantee of payment can be sent in real-time from financial institution **130** to financial institution **150**, which can happen for each such transaction. In some embodiments, the settlement of the transaction can happen later, such as in a nightly batch fashion, and in some embodiments, can happen through a different network, such as an ACH network or a credit network. In other embodiments, the real-time payment and/or guarantee of payment can be processed through an ACH network or a credit network. In some embodiments, the consumer can provide instructions to financial institution **130** to label the transaction as a debit or a credit transaction in one or more of consumer accounts **131**, and in some embodiments can provide such instructions with the request to pay, or before or after the request to pay. In some embodiments, a credit transaction can be treated as a micro-loan, as described above. In certain embodiments, a debit pull with guaranteed promise to pay can be used, such that financial institution **150** can receive a guaranteed promise to pay from financial institution **130** and pull the funds using a debit pull.

[0133] In various embodiments, transaction system **140** can store information regarding each transaction in transaction database **142**. In several embodiments, transaction system **140** can serve as a central auditor for transactions between the financial institutions (e.g., **130**, **150**) in data communication with transaction system **140**. In some embodiments, transaction system **140** can receive some or all of the information from the merchant security transaction code. In various embodiments, one or more portions of the merchant security transaction code can be encrypted by security system **115**. For example, the merchant security transaction code can include an encrypted portion that can be decrypted by security system **146** of transaction system **140**, which can be used to ensure that the message has not been tampered. In other embodiments, the merchant security transaction code is not encrypted, but is digitally signed, as described above, and the digital signature can be verified, in some embodiments, by security system **146**, which can advantageously ensure that the merchant identifier correctly identifies merchant **119**, so that the funds are paid to merchant account **151** corresponding to merchant **119**.

[0134] In a number of embodiments, financial institution **150**, upon receiving payment and/or guarantee of payment, can notify point-of-sale terminal **110** and/or merchant **119** in real-time that merchant **119** has satisfactorily received payment from consumer **129**. For example, the notification can include various information, such as the transaction identifier, the amount received in payment (or guarantee), the merchant identifier, and/or other information. Receiving the notice of good funds can allow merchant **119** to proceed, such as, for example, to allow consumer to leave the store of merchant **119** with the items. In some embodiments, for example, point-of-sale terminal **110** can match the notification to the pending transaction in point-of-sale terminal **110** using the transaction identifier. In certain embodiments, merchant **119** can match the notification to the point-of-sale terminal using the merchant identifier. In some embodiments, consumer **129** can receive a notification on mobile device **120** that the transaction has cleared, such as shown in FIG. 22 and described below.

[0135] In several embodiments, system **100** can advantageously provide a number of technological improvements that can overcome technological problems in conventional systems. For example, in several embodiments, system **100** can beneficially allow consumer **129** to send payment directly and/or immediately to merchant **119** when consumer **129** is checking out at point-of-sale terminal **110**. In many embodiments, the payment systems and methods provided by system **100** described herein can eliminate the acquirer model that is conventionally used in payment card transactions. In several embodiments, the payment systems and methods provided by system **100** described herein can advantageously streamline payments by eliminating the need for the financial institution (i.e.,

the acquirer) of merchant **119** to request payment from the financial institution (i.e., the issuer) of consumer **129**. For example, in many embodiments, financial institution **150** does not need to request payment from financial institution **130**. In many embodiments, the payment systems and methods provided by system **100** described herein can beneficially ensure merchants (e.g., merchant **119**) are paid by consumers (e.g., consumer **129**) while eliminating and/or reducing many of the transaction fees paid to various entities in the conventional model.

[0136] In a number of embodiments, the payment systems and methods provided by system **100** described herein can advantageously eliminate the chargeback liability of merchants for fraudulent transactions. In the conventional acquirer-issuer model, the merchant (e.g., **119**) is responsible for verifying the credit or debit card to ensure that the card is not being used fraudulently. In several embodiments, the payment systems and methods provided by system **100** described herein can beneficially place the liability on the financial institution (e.g., **130**) of the consumer (e.g., **129**), which can be in a better position (e.g., with more and/or better information) than the merchant (e.g., **119**) to determine if the request to pay is a legitimate, authentic transaction requested by the consumer (e.g., **129**) and/or if the consumer's account is still open and in good status (or closed), has sufficient funds, etc. In various embodiments, the payment systems and methods provided by system **100** described herein can advantageously allow the financial institution (e.g., **130**) of the consumer (e.g., **129**) to choose how to authenticate the consumer (e.g., **129**), and/or can beneficially allow the financial institution (e.g., **130**) of the consumer (e.g., **129**) to choose the level of authentication, which can be tailored for each consumer (e.g., **129**) and/or for each transaction (e.g., the financial institution (e.g., **130**) can decide, at least partially based on its risk determination, that a transaction with a higher payment amount warrants a higher level of authentication). In several embodiments, the liability for fraudulent use of one or more of the consumer accounts (e.g., **131**) can be placed on the consumer (e.g., **129**), and/or the consumer (e.g., **129**) can choose the level of authentication used by the financial institution (e.g., **130**) of the consumer (e.g., **129**). In many embodiments, unauthorized access to one or more of consumer accounts **131** can beneficially be reduced and/or eliminated using the payment method provided by system **100** and described herein.

[0137] In several embodiments, the payment systems and methods provided by system **100** described herein can beneficially provide the ability for financial institution **130** to communicate directly with consumer **129** at point-of-sale terminal **110** when making a transaction. In many embodiments, the payment systems and methods provided by system **100** described herein can provide information to consumer **129**, such as account balance, insufficient funds, lock/freeze on one or more of consumer accounts **131**, etc., in real-time before consumer **129** requests payments, which can advantageously eliminate and/or reduce negative experiences of consumer **129**, such as attempting to transact with insufficient funds or a freeze on one or more of consumer accounts **131**. In a number of embodiments, the payment systems and methods provided by system **100** described herein can beneficially provide consumer **129** with the ability the ability to split the payment with one or more other accounts or a new loan, such as a micro-loan, which can allow consumer **129** to successfully make the payment and reduce negative experiences of consumer **129**.

[0138] In some embodiments, account information about one or more of consumer accounts **131** can beneficially be better protected from theft by the payment systems and methods provided by system **100** described herein, because, in a number of embodiments, the account information of one or more of consumer accounts **131** and/or personally identifiable information of consumer **129** can be undisclosed to third parties other than financial institution **130**, which maintains consumer accounts **131**. For example, in some embodiments, the account information of consumer accounts **131** and/or personally identifiable information of consumer **129** can be undisclosed to point-of-sale terminal **110**, merchant **119**, transaction system **140**, and/or financial institution **150**. In many embodiments, the account identifier (e.g., account number) of consumer accounts **131** is not sent across any networks, but resides solely in financial institution **130**, which can beneficially prevent

that information from being stolen. For example, the many recent large-scale data breaches of merchant systems that have exposed consumer account information and personally identifiable information of millions of consumers could have been mitigated by using the payment systems and methods provided by system **100** and described herein.

[0139] In other embodiments, consumer **129** can choose to provide account information of one or more of consumer accounts **131** and/or personally identifiable information of consumer **129** to one or more third parties. For example, in some embodiments consumer **129** can set privacy instructions in mobile device **120** and/or with financial institution **130** regarding what information can be disclosed to third parties. For example, consumer **129** can elect to disclose certain information to merchant **119** in order to receive discounts, point, and/or other perks from merchant **119**. For example, in some embodiments, financial institution **130** can send certain personally identifiable information of consumer **129** through transaction system **140** to financial institution **150** along with the payment information, and financial institution **150** can provide the information to merchant **119**. In the same or other embodiments, mobile device **120** can provide certain personally identifiable information of consumer **129** to merchant **119**, such as through the wireless data communication protocol. Examples of such personally identifiable information can include a name, a home address, a telephone number, a social security number, a tax identification number, an age, an income level, marital status, a number of dependents, a frequent shopper identifier, shopping preferences, etc.

[0140] In various embodiments, the payment systems and methods provided by system **100** described herein also can beneficially shield the account information about merchant account **151** from being disclosed outside a network of financial institutions (e.g., **130**, **150**) and transaction system **140**, which can beneficially prevent theft and misuse of the account information about merchant account **151**.

[0141] In a number of embodiments, the payment systems and methods provided by system **100** described herein can advantageously allow mobile device **120** to make a payment to merchant **119** when mobile device **120** is offline or unable to communicate with mobile wallet provider **160**. For example, as described herein, mobile device **120** can store a stand-in credit that can be used to initiate payment when mobile device **120** cannot communicate with mobile wallet provider **160** and/or when financial institution **130** is unavailable for communication. As another example, as described herein, mobile device can communicate to point-of-sale terminal to communicate through a proxy communication channel to mobile wallet provider **160**.

[0142] Turning ahead in the drawings, FIG. **2** illustrates a flow chart for a method **200**, according to an embodiment. In some embodiments, method **200** can be a method of facilitating secure payment transactions. Method **200** is merely exemplary and is not limited to the embodiments presented herein. Method **200** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **200** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **200** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **200** can be combined or skipped. In some embodiments, method **200** can be performed by financial institution **130** (FIG. **1**).

[0143] Referring to FIG. **2**, in some embodiments, method **200** can optionally include one or more preliminary blocks, such as a block **201** and a block **202**, described below. Specifically, method **200** can include block **201** of receiving, at a first financial institution from a mobile device, a preliminary request for account information. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The mobile device can be similar or identical to mobile device **120** (FIG. **1**).

[0144] In several embodiments, method **200** additionally can include block **202** of sending, from the first financial institution to the mobile device, the account information. In some embodiments,

the account information can include an account balance and an account status of a first account. The first account can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). [0145] In a number of embodiments, method **200** further optionally can include a block **203** of receiving, at a first financial institution from a mobile device of a consumer, a first request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The consumer can be similar or identical to consumer **129** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). In many embodiments, the first request can include first information, which can include a merchant identifier, a transaction identifier, and/or the payment amount. In several embodiments, the first information can be sent to the first financial institution from a mobile application running on a mobile device used by the consumer at a store of the merchant to pay for one or more items to be purchased from the merchant by the consumer for the payment amount. The mobile application can be similar or identical to mobile application **123** (FIG. **1**). In some embodiments, the one or more items to be purchased can include at least one of one or more products or one or more services. In many embodiments, the merchant identifier can be associated with the merchant. In a number of embodiments, the mobile application can be associated with the first account. In some embodiments, the merchant identifier can uniquely correspond to a point-of-sale terminal at the store of the merchant. In various embodiments, the merchant identifier can be obtained by the mobile device from the point-of-sale terminal using a proximity-based wireless data communication protocol.

[0146] In many embodiments, method **200** additionally can include a block **204** of determining, at the first financial institution, second information. In many embodiments, the second information can include an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system. The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The first system can be similar or identical to transaction system **140** (FIG. **1**). In a number of embodiments, the account identifier can be or include an account number. In some embodiments, the first system can be in data communication with the first financial institution and the second financial institution. In many embodiments, the first system can be maintained by an entity that is different from the first financial institution and the second financial institution. In some embodiments, the second information further can include a name of the merchant and/or a location of the store of the merchant.

[0147] In some embodiments, block **204** of determining second information optionally can include a block **205** of determining, at the first financial institution, the second information at least partially based on the merchant identifier and the third information. In a number of embodiments, the third information can be received by the first financial institution from the first system prior to receiving the first request to pay the merchant from the mobile device. For example, the third information can be stored at the first financial institution from a previous query to the first system. In many embodiments, the third information can include the account identifier of the second account. In some embodiments, the second information can include the third information.

[0148] In other embodiments, block **204** of determining second information optionally can include a block **206** and a block **207**, described below. For example, block **204** can include block **206** of sending, from the first financial institution to the first system, a second request to determine the second information. In several embodiments, the second request can include the merchant identifier.

[0149] In these same other embodiments, block **204** can include block **207** of receiving, at the first financial institution from the first system, the third information. The third information can include the account identifier of the second account. In many embodiments, the second information can include the third information.

[0150] In some embodiments, method **200** can continue after block **204** with a block **208** of authorizing, at the first financial institution, a payment from the first account to the second account. [0151] In a number of embodiments, block **208** of authorizing the payment from the first account to the second account optionally can include blocks **209**, **210**, and **211**. Block **209** can include authenticating an identity of the consumer that used the mobile device to send the first request to pay the merchant from the first account. In some embodiments, block **209** of authenticating the identity of the consumer can include authenticating the identity of the consumer based at least in part on whether the mobile device used to send the first request has previously been used by the consumer in transaction involving the first financial institution, whether biometrics of the consumer using the mobile device match stored biometrics of the consumer, and/or whether at least one of an identity of the merchant, a location of the merchant, or the payment amount is consistent with historical patterns of behavior by the consumer.

[0152] In a number of embodiments, the first information further can include the one or more items to be purchased, and block **209** of authenticating the identity of the consumer further can include authenticating the identity of the consumer based at least in part on the one or more items to be purchased by the consumer for the payment amount from the merchant.

[0153] In a number of embodiments, block **209** of authenticating the identity of the consumer further can include adjusting a level of authentication at least partially based on the payment amount to be paid to the merchant, whether the mobile device used to send the first request has previously been used by the consumer in transaction involving the first financial institution, whether biometrics of the consumer using the mobile device match stored biometrics of the consumer, and/or whether at least one of an identity of the merchant, a location of the merchant, the payment amount, or the one or more items to be purchased is consistent with historical patterns of behavior by the consumer.

[0154] In many embodiments, block **210** can include determining a current status of the first account. For example, the first financial institution can determine whether the first account is open and in good status, or has a freeze or hold status.

[0155] In several embodiments, block **211** can include determining available funds of the first account. For example, the first financial institution can use the determination of the available funds of the first account to determine whether the payment amount can be covered by the available funds of the first account.

[0156] In a number of embodiments, method **200** can continue after block **208** with a block **212** of sending, from the first financial institution to the first system, payment information regarding a payment to be made to the second account from the first account. In several embodiments, the payment information can be routed through the first system to the second financial institution such that the second financial institution, upon receiving the payment information, can notify the merchant in order to satisfy an expectation of the merchant for payment from the consumer. In some embodiments, the payment information can include the transaction identifier, the account identifier of the second account, and/or the payment amount. In a number of embodiments, the payment information can include the merchant identifier.

[0157] In some embodiments, the payment information further can include a settlement credit push of funds for the payment amount from the first account to the second account. In other embodiments, the payment information further can include an irrevocable promise to pay the payment amount from the first account to the second account. In several embodiments, the payment information further can include a set of personally identifiable information of the consumer. In a number of embodiments, the set of personally identifiable information can be at least partially based on privacy instructions sent by the consumer to the first financial institution.

[0158] Turning ahead in the drawings, FIG. **3** illustrates a flow chart for a method **300**, according to an embodiment. In some embodiments, method **300** can be a method of facilitating secure payment transactions. Method **300** is merely exemplary and is not limited to the embodiments

presented herein. Method **300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **300** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **300** can be combined or skipped. In some embodiments, method **300** can be performed by transaction system **140** (FIG. 1).

[0159] Referring to FIG. 3, method **300** can include a block **301** of receiving, at a first system from a first entity, a request. The first system can be similar or identical to transaction system **140** (FIG. 1). In some embodiments, the first entity can be a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). In other embodiments, the first entity can be a mobile device being used by a consumer. In yet other embodiments, the first entity can be a mobile wallet provider in data communication with the mobile device being used by the consumer. In a number of embodiments, the request can include a merchant identifier. In several embodiments, the merchant identifier can be associated with a merchant. The merchant can be similar or identical to merchant **119** (FIG. 1). In many embodiments, the first system can be in data communication with the first financial institution and a second financial institution. The second financial institution can be similar or identical to financial institution **150** (FIG. 1). In various embodiments, the first system can be maintained by an entity that is different from the first financial institution and the second financial institution. In some embodiments, the first financial institution can maintain a first account of a consumer. The first account can be similar or identical to one or more of consumer accounts **131** (FIG. 1). The consumer can be similar or identical to consumer **129** (FIG. 1). In many embodiments, the first system can be in data communication with a merchant account database. The merchant account database can be similar or identical to merchant account database **141** (FIG. 1). In a number of embodiments, the first system can include the merchant account database. In some embodiments, the first system can include a transaction database. The transaction database can be similar or identical to transaction database **142** (FIG. 1). In a number of embodiments, the merchant identifier can uniquely correspond to a point-of-sale terminal at the store of the merchant. In various embodiments, the merchant identifier can be obtained by the mobile device from the point-of-sale terminal using a proximity-based wireless data communication protocol.

[0160] In many embodiments, method **300** additionally can include a block **302** of determining, at the first system, using the merchant account database, first information. In several embodiments, the first information can include an account identifier of a second account of the merchant maintained by a second financial institution. The second account can be similar or identical to merchant account **151** (FIG. 1). The second financial institution can be similar or identical to financial institution **150** (FIG. 1). In some embodiments, the account identifier can be associated with the merchant identifier in the merchant account database. In a number of embodiments, the first information further can include a name of the merchant and/or a location of a store of the merchant.

[0161] In many embodiments, method **300** further can include a block **303** of sending the first information from the first system to the first financial institution.

[0162] In several embodiments, method **300** additionally can include a block **304** of receiving, at the first system from the first financial institution, payment information regarding a payment to be made to the second account from the first account to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. In a number of embodiments, the consumer can use a mobile device at the store of the merchant to pay for the one or more items. The mobile device can be similar or identical to mobile device **120** (FIG. 1). In some embodiments, the mobile device can be running a mobile application associated with the first account. The mobile application can be similar or identical to mobile application **123** (FIG. 1). In

many embodiments, the payment information can include a transaction identifier, the account identifier of the second account, and/or the payment amount. In a number of embodiments, the one or more items to be purchased can include at least one of one or more products or one or more services.

[0163] In a number of embodiments, method **300** optionally can include a block **305** of storing the payment information in the transaction database.

[0164] In many embodiments, method **300** can continue after block **304** with a block **306** of sending, from the first system to the second financial institution, the payment information such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer.

[0165] In some embodiments, the payment information further can include a settlement credit push of funds for the payment amount from the first account to the second account. In other embodiments, the payment information further can include an irrevocable promise to pay the payment amount from the first account to the second account. In several embodiments, the payment information further can include a set of personally identifiable information of the consumer. In a number of embodiments, the set of personally identifiable information can be at least partially based on privacy instructions sent by the consumer to the first financial institution.

[0166] Turning ahead in the drawings, FIG. **4** illustrates a flow chart for a method **400**, according to an embodiment. In some embodiments, method **400** can be a method of facilitating secure payment transactions. Method **400** is merely exemplary and is not limited to the embodiments presented herein. Method **400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **400** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **400** can be combined or skipped. In some embodiments, method **400** can be performed by mobile device **120** (FIG. **1**).

[0167] Referring to FIG. **4**, method **400** can include a block **401** of performing, at a mobile device, a preliminary identity authentication of a consumer using the mobile device. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**).

[0168] In many embodiments, method **400** additionally can include a block **402** of receiving at the mobile device first information from a point-of-sale terminal. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). In several embodiments, the first information can include a merchant identifier, a transaction identifier, and/or a payment amount. In some embodiments, the merchant identifier can uniquely correspond to the point-of-sale terminal at a store of a merchant. The merchant can be similar or identical to merchant **119** (FIG. **1**). In a number of embodiments, the mobile device can run a mobile application that is associated with a first account of the consumer using the mobile device. The mobile application can be similar or identical to mobile application **123** (FIG. **1**). The first account can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). In several embodiments, the first account of the consumer can be maintained by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**).

[0169] In some embodiments, method **400** optionally can include various blocks before or after block **402** of receiving at the mobile device first information from a point-of-sale terminal. For example, method **400** optionally can include a block **403** of sending, from the mobile device to the first financial institution, a preliminary request for account information. In several embodiments, the account information can include an account balance and an account status of the first account.

[0170] In a number of embodiments, method **400** further optionally can include, after block **403** of sending the preliminary request for account information, a block **404** of receiving, at the mobile

device from the first financial institution, the account information.

[0171] In many embodiments, method **400** can continue after block **402** with a block **405** of sending, from the mobile device to the first financial institution, a first request to pay the merchant for the payment amount from the first account for one or more items to be purchased from the merchant by the consumer. In a number of embodiments, the first request can include the first information, such that the first financial institution, upon receiving the first request, can determine second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system, and such that the first financial institution can send to the first system payment information regarding a payment to be made to the second account from the first account. The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The first system can be similar or identical transaction system **140** (FIG. **1**).

[0172] In a number of embodiments, the payment information can be routed through the first system to the second financial institution such that the second financial institution, upon receiving the payment information, can notify the merchant to satisfy an expectation of the merchant for payment from the consumer. In several embodiments, the first system can be in data communication with the first financial institution and the second financial institution. In various embodiments, the first system can be maintained by an entity that is different from the first financial institution and the second financial institution. In a number of embodiments, the payment information can include the transaction identifier, the account identifier of the second account, and the payment amount. In some embodiments, the payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account.

[0173] In some embodiments, method **400** optionally can include additional blocks after sending the first request to pay the merchant and before the payment information is sent to the first system from the first financial institution. For example, in a number of embodiments, after block **405**, method **400** optionally can include a block **406** of receiving, at the mobile device from the first financial institution, an additional authentication request to perform an additional identity authentication of the consumer using the mobile device.

[0174] In various embodiments, method **400** optionally further can include a block **407** of performing, at the mobile device, the additional identity authentication of the consumer using the mobile device. In many embodiments, block **407** can include performing the additional authentication of the consumer based at least in part on determining biometrics of the consumer using the mobile device and/or requesting the consumer to enter additional information in the mobile device.

[0175] In several embodiments, method **400** optionally and additionally can include a block **408** of sending, from the mobile device to the first financial institution, a response to the additional authentication request.

[0176] Turning ahead in the drawings, FIG. **5** illustrates a flow chart for a method **500**, according to an embodiment. In some embodiments, method **500** can be a method of facilitating secure payment transactions. Method **500** is merely exemplary and is not limited to the embodiments presented herein. Method **500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **500** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **500** can be combined or skipped. In some embodiments, method **500** can be performed by point-of-sale terminal **110** (FIG. **1**).

[0177] Referring to FIG. 5, method **500** can include a block **501** of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. 1). The merchant can be similar or identical to merchant **119** (FIG. 1). The consumer can be similar or identical to consumer **129** (FIG. 1).

[0178] In several embodiments, method **500** additionally can include a block **502** of sending first information from the point-of-sale terminal to a mobile device used by the consumer. The mobile device can be similar or identical to mobile device **120** (FIG. 1). In a number of embodiments, the first information can be sent from the point-of-sale terminal to the mobile device using a proximity-based wireless data protocol. In several embodiments, the first information can include a merchant identifier, a transaction identifier, and/or the payment amount. In a number of embodiments, the merchant identifier can uniquely correspond to the point-of-sale terminal at the store of the merchant. In various embodiments, the mobile device can run a mobile application that is associated with a first account of the consumer using the mobile device. The mobile application can be similar or identical to mobile application **123** (FIG. 1). The first account can be similar or identical to one or more of consumer accounts **131** (FIG. 1). In a number of embodiments, the first account of the consumer can be maintained by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). In several embodiments, the mobile device, upon receiving the first information, can send a first request to pay the merchant for the payment amount from the first account. In a number of embodiments, the first request can include the first information, such that the first financial institution, upon receiving the first request, can determine second information including an account identifier of a second account of the merchant maintained by a second financial institution, at least partially based on the merchant identifier and third information obtained from a first system, and such that the first financial institution sends to the first system payment information regarding a payment to be made to the second account from the first account. The second account can be similar or identical to merchant account **151** (FIG. 1). The second financial institution can be similar or identical to financial institution **150** (FIG. 1). The first system can be similar or identical to transaction system **140** (FIG. 1).

[0179] In some embodiments, the payment information can be routed through the first system to the second financial institution. In various embodiments, the first system can be in data communication with the first financial institution and the second financial institution. In many embodiments, the first system can be maintained by an entity that is different from the first financial institution and the second financial institution. In several embodiments, the payment information can include the transaction identifier, the account identifier of the second account, and/or the payment amount. In some embodiments, the payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account.

[0180] In various embodiments, method **500** optionally can include a block **503** of receiving at the point-of-sale terminal from the mobile device, information about the consumer. In some embodiments, block **503** can be performed before or after block **501** of determining the payment amount for the one or more items to be purchased from the merchant by the consumer, before or after block **502** of sending the first information from the point-of-sale terminal to the mobile device used by the consumer, or before or after block **504**, described below.

[0181] In many embodiments, method **500** can continue after block **502** with a block **504** of receiving, at the point-of-sale terminal from the second financial institution, a notification to satisfy an expectation of the merchant for payment from the consumer.

[0182] Turning ahead in the drawings, FIG. 6 illustrates a flow chart for a method **600**, according to an embodiment. In some embodiments, method **600** can be a method of facilitating secure

payment transactions. Method **600** is merely exemplary and is not limited to the embodiments presented herein. Method **600** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **600** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **600** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **600** can be combined or skipped. In some embodiments, method **600** can be performed by financial institution **150** (FIG. 1).

[0183] Referring to FIG. 6, method **600** can include a block **601** of receiving, at a second financial institution from a first system, payment information regarding a payment to be made to a second account of a merchant maintained by the second financial institution from a first account of a consumer maintained by a first financial institution to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount. The second financial institution can be similar or identical to financial institution **150** (FIG. 1). The first system can be similar or identical to transaction system **140** (FIG. 1). The second account can be similar or identical to merchant account **151** (FIG. 1). The first account can be similar or identical to one or more of consumer accounts **131** (FIG. 1). The consumer can be similar or identical to consumer **129** (FIG. 1). The first financial institution can be similar or identical to financial institution **130** (FIG. 1).

[0184] In a number of embodiments, the payment information can be sent from the first financial institution to the first system and routed through the first system to the second financial institution. In several embodiments, the first system can be in data communication with the first financial institution and the second financial institution. In various embodiments, the first system can be maintained by an entity that is different from the first financial institution and the second financial institution. In many embodiments, the consumer can use a mobile device at a store of the merchant to pay for the one or more items. The mobile device can be similar or identical to mobile device **120** (FIG. 1). In a number of embodiments, the mobile device can run a mobile application associated with the first account. The mobile application can be similar or identical to mobile application **123** (FIG. 1). In several embodiments, the payment information can include a transaction identifier, an account identifier of the second account, and/or the payment amount. In a number of embodiments, the first financial institution can determine the account identifier of the second account based on a merchant identifier and based on third information obtained from the first system. In several embodiments, the merchant identifier can uniquely correspond to a point-of-sale terminal at the store of a merchant. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. 1).

[0185] In a number of embodiments, the mobile device can send a request to pay the merchant for the payment amount from the first account. In many embodiments, the request can include first information including the merchant identifier, a transaction identifier, and/or the payment amount. In several embodiments, the payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account.

[0186] In several embodiments, method **600** optionally can include a block **602** of crediting the second account with the payment amount. For example, after the second financial institution has received the payment information, the second account can be credited with the payment amount.

[0187] In many embodiments, method **600** can continue after block **601** with a block **603** of sending, from the second financial institution to the point-of-sale terminal, a notification to satisfy an expectation of the merchant for payment from the consumer. In some embodiments, block **603** can include notifying the merchant that funds for the payment amount are immediately available in the second account.

[0188] Jumping ahead in the drawings, FIG. 9 illustrates a flow chart for a method **900**, according

to an embodiment. In some embodiments, method **900** can be a method of facilitating secure payment transactions. Method **900** is merely exemplary and is not limited to the embodiments presented herein. Method **900** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **900** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **900** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **900** can be combined or skipped. In some embodiments, method **900** can be performed by point-of-sale terminal **110** (FIG. **1**). In some embodiments, method **900** and other blocks in method **900** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0189] Referring to FIG. **9**, method **900** can include a block **901** of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**).

[0190] In several embodiments, method **900** also can include a block **902** of generating a transaction code including a merchant public identifier, the payment amount, a transaction identifier for the transaction, and a digital signature. In many embodiments, the transaction code can be similar or identical to the merchant security transaction code described above. In some embodiments, the transaction code can further include one or more SKUs for the one or more items to be purchased in the transaction. In some embodiments, the digital signature can be similar or identical to the digital signature described above. In many embodiments, the merchant public identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through a transaction system, such as transaction system **140** (FIG. **1**).

[0191] In some embodiments, block **902** of generating a transaction code including a merchant public identifier can include point-of-sale terminal **110** (FIG. **1**) cryptographically signing the digital signature for the transaction code. In other embodiments, block **902** of generating a transaction code including a merchant public identifier can include point-of-sale terminal **110** (FIG. **1**) calling the transaction system, such as transaction system **140** (FIG. **1**), to generate the transaction code.

[0192] In a number of embodiments, method **900** additionally can include a block **903** of providing the transaction code to a mobile device being used by the consumer, such that the mobile device verifies the digital signature and sends a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, and such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The first account can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In many embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. In some embodiments, the payment

information can be routed through the transaction system to the second financial institution. In many embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information.

[0193] In some embodiments, the payment information can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account. In many embodiments, the mobile device can send the request to pay after receiving from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device.

[0194] In many embodiments, block **903** of providing the transaction code to a mobile device being used by the consumer can include displaying the transaction code as a matrix barcode on a screen of the point-of-sale terminal. For example, the transaction code can be displayed as a QR code on a screen of the point-of-sale terminal, which can be scanned using a camera of the mobile device. In other embodiments, block **903** of providing the transaction code to a mobile device being used by the consumer can include transmitting the transaction code from the point-of-sale terminal to the mobile device using a proximity-based wireless data communication protocol. In yet other embodiments, the point-of-sale terminal can display the transaction code such that it can be manually input into the mobile device.

[0195] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0196] In several embodiments, method **900** further can include a block **904** of receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In many embodiments, the notification of the payment can be received by the merchant and/or at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received by the merchant and/or at the point-of-sale terminal from the second financial institution system.

[0197] Proceeding to the next drawing, FIG. **10** illustrates a flow chart for a method **1000**, according to an embodiment. In some embodiments, method **1000** can be a method of facilitating secure payment transactions. Method **1000** is merely exemplary and is not limited to the embodiments presented herein. Method **1000** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1000** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1000** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1000** can be combined or skipped. In some embodiments, method **1000** can be performed by mobile device **120** (FIG. **1**) and/or mobile application **123** (FIG. **1**).

[0198] Referring to FIG. **10**, method **1000** can include a block **1001** of receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**). In many embodiments, the transaction code can be similar or identical to the merchant security transaction code described above. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**).

[0199] In many embodiments, the transaction code can include a merchant public identifier being associated with the merchant, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, a transaction identifier for the transaction, and a digital

signature. In various embodiments, the transaction code further can include one or more SKUs for the one or more items to be purchased in the transaction. In many embodiments, the merchant public identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through a transaction system, such as transaction system **140** (FIG. **1**). In some embodiments, the digital signature can be similar or identical to the digital signature described above. In some embodiments, the digital signature of the transaction code is cryptographically signed by the point-of-sale terminal. In other embodiments, the transaction system can be called by the point-of-sale terminal to generate the transaction code.

[0200] In some embodiments, block **1001** of receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant can include using a camera of the mobile device to scan the transaction code as a matrix barcode from a screen of the point-of-sale terminal. For example, the transaction code can be displayed as a QR code on a screen of the point-of-sale terminal, which can be scanned using a camera of the mobile device. In other embodiments, block **1001** of receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant can include receiving the transaction code from the point-of-sale terminal using a proximity-based wireless data communication protocol. In yet other embodiments, the mobile device can receive the transaction code through manual input.

[0201] In several embodiments, method **1000** also can include a block **1002** of verifying the digital signature for the transaction code. For example, the digital signature can be verified using a public-key signature verifying algorithm, as described above, or another suitable verification algorithm.

[0202] In a number of embodiments, method **1000** optionally can include a block **1003** of receiving an approval for the transaction from the consumer through a user interface on the mobile device. For example, the consumer can authorize the transaction, as described above. The user interface can be similar to user interface display **1700** (FIG. **17**), as described below in further detail.

[0203] In several embodiments, method **1000** further can continue after block **1002** with a block **1004** of sending, from the mobile device, a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant public identifier, such that the first financial institution sends to the transaction system payment information regarding a payment to be made to the second account from the first account, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In some embodiments, the payment information including the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information.

[0204] The first account can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In many embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**).

[0205] In some embodiments, the payment information can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account. In many embodiments, the notification of the payment can be received at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received

at the point-of-sale terminal from the second financial institution system.

[0206] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0207] Turning ahead in the drawings, FIG. **11** illustrates a flow chart for a method **1100**, according to an embodiment. In some embodiments, method **1100** can be a method of facilitating secure payment transactions. Method **1100** is merely exemplary and is not limited to the embodiments presented herein. Method **1100** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1100** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1100** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1100** can be combined or skipped. In some embodiments, method **1100** can be performed by financial institution **130** (FIG. **1**). In some embodiments, method **1100** and other blocks in method **1100** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0208] Referring to FIG. **11**, method **1100** can include a block **1101** of receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). In many embodiments, the first account can be similar or identical to one or more of consumer accounts **131** (FIG. **1**).

[0209] In some embodiments, the request to pay can include information including a merchant public identifier, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. In many embodiments, the merchant public identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through a transaction system, such as transaction system **140** (FIG. **1**).

[0210] In various embodiments, the mobile device can be used by the consumer at a store of the merchant to pay for the transaction. In a number of embodiments, the information can be received by the mobile device from a point-of-sale terminal at the store of the merchant as part of a transaction code. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). In many embodiments, the transaction code can be similar or identical to the merchant security transaction code described above. In some embodiments, the transaction code can further include one or more SKUs for the one or more items to be purchased in the transaction. In several embodiments, the transaction code can be verified by the mobile device using a digital signature of the transaction code. In some embodiments, the digital signature can be similar or identical to the digital signature described above.

[0211] In many embodiments, the mobile device can receive the transaction code by using a camera on the mobile device to scan the transaction code as a matrix barcode from a screen of the point-of-sale terminal. For example, the transaction code can be displayed as a QR code on a screen of the point-of-sale terminal, which can be scanned using a camera of the mobile device. In other embodiments, the mobile device can receive the transaction code using a proximity-based wireless

data communication protocol. In yet other embodiments, the mobile device can receive the transaction code through manual input. In some embodiments, the digital signature of the transaction code can be cryptographically signed by the point-of-sale terminal. In other embodiments, the transaction system can be called by the point-of-sale terminal to generate the transaction code.

[0212] In a number of embodiments, the request to pay can be received at the first financial institution after the mobile device receives from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, as described above.

[0213] In several embodiments, method **1100** also can include a block **1102** of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant public identifier. The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In some embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**).

[0214] In a number of embodiments, method **1100** additionally can include a block **1103** of sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the first account, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In many embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information. In several embodiments, the payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account. In some embodiments, the notification of the payment can be received at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received at the point-of-sale terminal from the second financial institution system.

[0215] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0216] Proceeding to the next drawing, FIG. **12** illustrates a flow chart for a method **1200**, according to an embodiment. In some embodiments, method **1200** can be a method of facilitating secure payment transactions. Method **1200** is merely exemplary and is not limited to the embodiments presented herein. Method **1200** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1200** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1200** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1200** can be combined or skipped. In some embodiments, method **1200** can be performed by transaction system **140** (FIG. **1**). In some embodiments, method **1200** and other blocks in method **1200** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0217] Referring to FIG. 12, method **1200** can include a block **1201** of receiving, at a transaction system from a first entity, a request including a merchant public identifier associated with a merchant. The transaction system can be similar or identical to transaction system **140** (FIG. 1). In many embodiments, the merchant public identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through the transaction system. The merchant can be similar or identical to merchant **119** (FIG. 1). In some embodiments, the first entity can be at least one of the first financial institution, a mobile device being used by a consumer, or a mobile wallet provider in data communication with the mobile device being used by the consumer. For example, the first financial institution can be similar or identical to financial institution **130** (FIG. 1), the mobile device can be similar or identical to mobile device **120** (FIG. 1), the consumer can be similar or identical to consumer **129** (FIG. 1), and/or the mobile wallet provider can be similar or identical to mobile application **123** (FIG. 1).

[0218] In some embodiments, the transaction system can be in data communication with a first financial institution that maintains a first account of a consumer and a second financial institution that maintains a second account of the merchant. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). The first account can be similar or identical to one or more of consumer accounts **131** (FIG. 1). The consumer can be similar or identical to consumer **129** (FIG. 1). The second financial institution can be similar or identical to financial institution **150** (FIG. 1). The second account can be similar or identical to merchant account **151** (FIG. 1). In many embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution.

[0219] In several embodiments, the consumer can use a mobile device at a store of the merchant to pay for one or more items in a transaction. The mobile device can be similar or identical to mobile device **120** (FIG. 1). In some embodiments, the mobile device can receive a transaction code from a point-of-sale terminal at the store. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. 1). In many embodiments, the transaction code can include a transaction identifier, a payment amount for the transaction, the merchant public identifier, and a digital signature. In many embodiments, the transaction code can be similar or identical to the merchant security transaction code described above. In some embodiments, the transaction code can further include one or more SKUs for the one or more items to be purchased in the transaction. In some embodiments, the digital signature can be similar or identical to the digital signature described above. In some embodiments, the digital certificate of the transaction code can be cryptographically signed. In many embodiments, the transaction system can be called by the point-of-sale terminal to generate the transaction code before the transaction system receives the request. In a number of embodiments, the transaction code can be verified by the mobile device using a digital signature of the transaction code.

[0220] In some embodiments, the mobile device can receive the transaction code by using a camera on the mobile device to scan the transaction code as a matrix barcode from a screen of the point-of-sale terminal. For example, the transaction code can be displayed as a QR code on a screen of the point-of-sale terminal, which can be scanned using a camera of the mobile device. In other embodiments, the mobile device can receive the transaction code using a proximity-based wireless data communication protocol. In yet other embodiments, the mobile device can receive the transaction code through manual input.

[0221] In several embodiments, method **1200** also can include a block **1202** of determining, at the transaction system, an account identifier of the second account based on the merchant public identifier using a merchant account database. The merchant account database can be similar or identical to merchant account database **141** (FIG. 1).

[0222] In a number of embodiments, method **1200** additionally can include a block **1203** of sending the account identifier to the first financial institution.

[0223] In several embodiments, method **1200** further can include a block **1204** of receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the first account. In some embodiments, the payment information can include the account identifier of the second account, the payment amount, the transaction identifier, and/or other suitable information. In many embodiments, the payment information further can include one of: (a) a settlement credit push of funds for the payment amount from the first account to the second account, or (b) an irrevocable promise to pay the payment amount from the first account to the second account.

[0224] In a number of embodiments, method **1200** additionally can include a block **1205** of sending, from the transaction system to the second financial institution, the payment information, such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In many embodiments, the notification of the payment can be received at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received at the point-of-sale terminal from the second financial institution system.

[0225] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0226] Turning ahead in the drawings, FIG. **13** illustrates a flow chart for a method **1300**, according to an embodiment. In some embodiments, method **1300** can be a method of facilitating secure payment transactions. Method **1300** is merely exemplary and is not limited to the embodiments presented herein. Method **1300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1300** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1300** can be combined or skipped. In some embodiments, method **1300** can be performed by mobile device **120** (FIG. **1**) and/or mobile application **123** (FIG. **1**).

[0227] Referring to FIG. **13**, method **1300** can include a block **1301** of performing, at a mobile device being used by a consumer, an identity authentication of the consumer. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**).

[0228] In several embodiments, method **1300** also can include a block **1302** of receiving, at the mobile device, first information from a point-of-sale terminal at a store of a merchant. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). In some embodiments, the first information can include a merchant identifier, a transaction identifier, a payment amount, and/or other suitable information. In many embodiments, the merchant identifier can be associated with the merchant. In some embodiments, the payment amount can be for one or more items to be purchased from the merchant by the consumer in a transaction. The transaction identifier can be associated with the transaction.

[0229] In a number of embodiments, method **1300** additionally can include a block **1303** of sending, from the mobile device, a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, such that the first financial institution, upon receiving the request to pay, retrieves from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier, such that the first financial institution sends to the transaction

system payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The one or more first accounts can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). In several embodiments, the one or more first accounts can include at least one non-demand deposit account. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In some embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**).

[0230] In several embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information. In some embodiments, the payment information further can include one of: (a) one or more settlement credit pushes of funds that collectively total the payment amount from the one or more first accounts to the second account, or (b) one or more irrevocable promises to pay that collectively total the payment amount from the one or more first accounts to the second account. In many embodiments, the mobile device can send the request to pay after receiving from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device, such as shown in user interface displays **1700** (FIG. **17**), as shown described below in further detail.

[0231] In many embodiments, the one or more first accounts can include the loan account, and in some embodiments, the loan account can be created after receiving the first information from the point-of-sale terminal. In several embodiments, the loan account can be used to fund at least a first portion of the payment amount of the transaction, and in various embodiments, a second portion of the payment amount can be funded from a demand deposit account of the consumer maintained at the first financial institution.

[0232] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0233] In many embodiments, method **1300** can include one or more optional blocks **1304-1308**, described below. In some embodiments, one or more of blocks **1304-1308** can be performed before block **1303**, and in some embodiments, can be performed before block **1302**. In the same or other embodiments, one or more of block **1304-1308** can be performed after block **1303**.

[0234] In several embodiments, method **1300** optionally can include block **1304** of receiving, from the first financial institution, an account balance of a demand deposit account of the consumer maintained by the first financial institution.

[0235] In a number of embodiments, method **1300** optionally can include block **1305** of displaying the account balance of the demand deposit account to the consumer on a user interface of the mobile device. The user interface can be similar to user interface display **1700** (FIG. **17**), as described below in further detail.

[0236] In several embodiments, method **1300** optionally can include block **1306** of determining that the account balance of the demand deposit account is less than the payment amount of the transaction. In some embodiments, the determining of block **1306** can involve a comparison in the mobile device of the payment account against the account balance. In other embodiments, another system, such as the first financial institution, can perform the comparison of the payment account

against the account balance, and the determining of block **1306** can involve receiving, from the other system, such as from the first financial institution, information about, or based on, the results of the comparison.

[0237] In a number of embodiments, method **1300** optionally can include block **1307** of presenting to the consumer an option on a user interface of the mobile device to at least partially fund the transaction using the at least one non-demand deposit account. The user interface can be similar to user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail.

[0238] In several embodiments, method **1300** optionally can include block **1308** of receiving from the consumer through the user interface a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account. The user interface can be similar to user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail. In some embodiments, the one or more first accounts further can include the demand deposit account. In many embodiments, a first portion of the payment amount of the transaction can be funded from the demand deposit account, and in some embodiments, a second portion of the payment amount of the transaction can be funded from the at least one non-demand deposit account. In other embodiments, the demand deposit account can be devoid of being used to fund the payment amount of the transaction, and the payment amount of the transaction can be funded wholly from the at least one non-demand deposit account.

[0239] Turning ahead in the drawings, FIG. **14** illustrates a flow chart for a method **1400**, according to an embodiment. In some embodiments, method **1400** can be a method of facilitating secure payment transactions. Method **1400** is merely exemplary and is not limited to the embodiments presented herein. Method **1400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1400** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1400** can be combined or skipped. In some embodiments, method **1400** can be performed by financial institution **130** (FIG. **1**). In some embodiments, method **1400** and other blocks in method **1400** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0240] Referring to FIG. **14**, method **1400** can include a block **1401** of receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from one or more first accounts of the consumer maintained by the first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). The one or more first accounts can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). The one or more first accounts can include at least one non-demand deposit account.

[0241] In many embodiments, the request to pay can include information including a merchant identifier, a payment amount for one or more items to be purchased from the merchant by the consumer in a transaction, and a transaction identifier for the transaction. In a number of embodiments, the mobile device can be used by the consumer at a store of the merchant to pay for the transaction. In some embodiments, the information can be received by the mobile device from a point-of-sale terminal at the store of the merchant. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**).

[0242] In various embodiments, the one or more first accounts can include the loan account, and

the loan account can be created after receiving the request to pay the merchant. In the same or other embodiments, the loan account can be used to fund at least a first portion of the payment amount of the transaction, and in a number of embodiments, a second portion of the payment amount can be funded from a demand deposit account of the consumer maintained at the first financial institution. [0243] In some embodiments, the at least one non-demand deposit account can include a credit account. In a number of embodiments, at least a portion of the payment can be funded from a charge to the credit account. In various embodiments, the at least one non-demand deposit account can include a points account.

[0244] In several embodiments, method **1400** also can include a block **1402** of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant identifier. The second account can be similar or identical to merchant account **151** (FIG. 1). The second financial institution can be similar or identical to financial institution **150** (FIG. 1). The transaction system can be similar or identical to transaction system **140** (FIG. 1). In some embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution.

[0245] In a number of embodiments, method **1400** additionally can include a block **1403** of sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information is routed through the transaction system to the second financial institution, and such that the point-of-sale terminal receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In many embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable include. In some embodiments, the payment information further can include one of: (a) one or more settlement credit pushes of funds that collectively total the payment amount from the one or more first accounts to the second account, or (b) one or more irrevocable promises to pay that collectively total the payment amount from the one or more first accounts to the second account. In many embodiments, the mobile device can send the request to pay after receiving from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device, such as shown in user interface display **1700** (FIG. 17), as shown described below in further detail.

[0246] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0247] In many embodiments, method **1400** can include one or more optional blocks **1404-1407**, described below. In some embodiments, one or more of blocks **1404-1407** can be performed before one or more of blocks **1401-1403**. In the same or other embodiments, one or more of blocks **1404-1407** can be performed after block **1403**.

[0248] In several embodiments, method **1400** optionally can include block **1404** of sending, to the mobile device, an account balance of a demand deposit account of the consumer maintained by the first financial institution. For example, the account balance can be displayed on the mobile device on a user interface, such as shown in user interface display **1700** (FIG. 17), as shown described below in further detail.

[0249] In a number of embodiments, method **1400** optionally can include block **1405** of determining that the account balance of the demand deposit account is less than the payment amount of the transaction.

[0250] In several embodiments, method **1400** optionally can include block **1406** of sending, to the mobile device, an option to at least partially fund the transaction using the at least one non-demand deposit account. For example, the option can be displayed on the mobile device using a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail.

[0251] In a number of embodiments, method **1400** optionally can include block **1407** of receiving, from the mobile device, a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account. For example, the selection can be received on the mobile device through a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail. In many embodiments, the one or more first accounts further can include the demand deposit account. In some embodiments, a first portion of the payment amount of the transaction can be funded from the demand deposit account, and a second portion of the payment amount of the transaction can be funded from the at least one non-demand deposit account. In other embodiments, the demand deposit account can be devoid of being used to fund the payment amount of the transaction, and the payment amount of the transaction can be funded wholly from the at least one non-demand deposit account.

[0252] Turning ahead in the drawings, FIG. **15** illustrates a flow chart for a method **1500**, according to an embodiment. In some embodiments, method **1500** can be a method of facilitating secure payment transactions. Method **1500** is merely exemplary and is not limited to the embodiments presented herein. Method **1500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1500** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1500** can be combined or skipped. In some embodiments, method **1500** can be performed by transaction system **140** (FIG. **1**). In some embodiments, method **1500** and other blocks in method **1500** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0253] Referring to FIG. **15**, method **1500** can include a block **1501** of receiving, at a transaction system from a first entity, a request including a merchant identifier associated with a merchant. The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In many embodiments, the merchant identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through the transaction system. The merchant can be similar or identical to merchant **119** (FIG. **1**). In some embodiments, the first entity can be at least one of the first financial institution, a mobile device being used by a consumer, or a mobile wallet provider in data communication with the mobile device being used by the consumer. For example, the first financial institution can be similar or identical to financial institution **130** (FIG. **1**), the mobile device can be similar or identical to mobile device **120** (FIG. **1**), the consumer can be similar or identical to consumer **129** (FIG. **1**), and/or the mobile wallet provider can be similar or identical to mobile application **123** (FIG. **1**) and/or mobile wallet provider **160** (FIG. **1**).

[0254] In some embodiments, the transaction system can be in data communication with a first financial institution that maintains one or more first accounts of a consumer and a second financial institution that maintains a second account of the merchant. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The one or more first accounts can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). In many embodiments, the one or more first accounts can include one or more of at least one non-demand deposit account.

The consumer can be similar or identical to consumer **129** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The second account can be similar or identical to merchant account **151** (FIG. **1**). In many embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution. In several embodiments, the consumer can use a mobile device at a store of the merchant to pay a payment amount for one or more items in a transaction using the one or more first accounts. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). [0255] In several embodiments, the first financial institution can be configured to send to the mobile device an account balance of a demand deposit account of the consumer maintained by the first financial institution. For example, the account balance can be displayed on the mobile device on a user interface, such as shown in user interface display **1700** (FIG. **17**), as shown described below in further detail.

[0256] In some embodiments, the first financial institution can be configured to determine that the account balance of the demand deposit account is less than the payment amount of the transaction.

[0257] In many embodiments, the first financial institution can be configured to send to the mobile device an option to at least partially fund the transaction using the at least one non-demand deposit account. For example, the option can be displayed on the mobile device using a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail.

[0258] In a number of embodiments, the first financial institution can be configured to receive from the mobile device a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account. For example, the selection can be received on the mobile device through a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail. In many embodiments, the one or more first accounts further can include the demand deposit account. In some embodiments, a first portion of the payment amount of the transaction can be funded from the demand deposit account, and a second portion of the payment amount of the transaction can be funded from the at least one non-demand deposit account. In other embodiments, the demand deposit account can be devoid of being used to fund any portion of the payment amount of the transaction, and the payment amount of the transaction can be funded wholly from the at least one non-demand deposit account.

[0259] In various embodiments, the one or more first accounts can include the loan account, and the loan account can be created after the consumer authorizes paying the payment amount. In the same or other embodiments, the loan account can be used to fund at least a first portion of the payment amount of the transaction, and in a number of embodiments, a second portion of the payment amount can be funded from a demand deposit account or another non-demand deposit account of the consumer maintained at the first financial institution.

[0260] In some embodiments, the at least one non-demand deposit account can include a credit account. In a number of embodiments, at least a portion of the payment can be funded from a charge to the credit account. In various embodiments, the at least one non-demand deposit account can include a points account.

[0261] In several embodiments, method **1500** also can include a block **1502** of determining, at the transaction system, an account identifier of the second account of the merchant maintained by a second financial institution using a merchant account database. The merchant account database can be similar or identical to merchant account database **141** (FIG. **1**).

[0262] In a number of embodiments, method **1500** additionally can include a block **1503** of sending the account identifier from the transaction system to the first financial institution.

[0263] In several embodiments, method **1500** further can include a block **1504** of receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the one or more first accounts. In some embodiments, the

payment information can include a transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information. In many embodiments, the payment information further can include one or more of: (a) one or more settlement credit pushes of funds that collectively total the payment amount from the one or more first accounts to the second account, or (b) one or more irrevocable promises to pay that collectively total the payment amount from the one or more first accounts to the second account. In many embodiments, the mobile device can send the request to pay after receiving from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device, such as shown in user interface display **1700** (FIG. **17**), as shown described below in further detail.

[0264] In a number of embodiments, method **1500** additionally can include a block **1505** of sending, from the transaction system to the second financial institution, the payment information, such that a point-of-sale terminal at the store of the merchant receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). In many embodiments, the notification of the payment can be received at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received at the point-of-sale terminal from the second financial institution system.

[0265] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0266] Proceeding to the next drawing, FIG. **16** illustrates a flow chart for a method **1600**, according to an embodiment. In some embodiments, method **1600** can be a method of facilitating secure payment transactions. Method **1600** is merely exemplary and is not limited to the embodiments presented herein. Method **1600** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **1600** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **1600** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **1600** can be combined or skipped. In some embodiments, method **1600** can be performed by point-of-sale terminal **110** (FIG. **1**). In some embodiments, method **1600** and other blocks in method **1600** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0267] Referring to FIG. **16**, method **1600** can include a block **1601** of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The merchant can be similar or identical to merchant **119** (FIG. **1**). The consumer can be similar or identical to consumer **129** (FIG. **1**).

[0268] In several embodiments, method **1600** also can include a block **1602** of sending first information from the point-of-sale terminal to a mobile device used by the consumer. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). In many embodiments, the first information can include a merchant identifier, a transaction identifier, and the payment amount. In many embodiments, the merchant identifier can be similar to the merchant identifier described above. For example, in many embodiments, the merchant identifier can be setup and/or registered through a transaction system, such as transaction system **140** (FIG. **1**). In many embodiments, the

mobile device can send a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The one or more first accounts can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). In many embodiments, the one or more first accounts can include one or more of at least one non-demand deposit account. In a number of embodiments, the first financial institution, upon receiving the request to pay, can retrieve from a transaction system an account identifier of a second account of the merchant maintained by a second financial institution based on the merchant identifier. The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The second account can be similar or identical to merchant account **151** (FIG. **1**). The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In some embodiment, the first financial institution can send to the transaction system payment information regarding a payment to be made to the second account from the one or more first accounts, such that the payment information can be routed through the transaction system to the second financial institution. In a number of embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the payment amount, and/or other suitable information. In many embodiments, the transaction system can be maintained by an entity that is different from the merchant, the first financial institution, and the second financial institution.

[0269] In some embodiments, the payment information further includes one or more of: (a) one or more settlement credit pushes of funds that collectively total the payment amount from the one or more first accounts to the second account, or (b) one or more irrevocable promises to pay that collectively total the payment amount from the one or more first accounts to the second account. In many embodiments, the mobile device can send the request to pay after receiving from the consumer an approval for the transaction. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device. For example, the consumer can authorize the transaction, after which the request to pay can be sent from the mobile device, such as shown in user interface display **1700** (FIG. **17**), as shown described below in further detail.

[0270] In several embodiments, the first financial institution can be configured to send to the mobile device an account balance of a demand deposit account of the consumer maintained by the first financial institution. For example, the account balance can be displayed on the mobile device on a user interface, such as shown in user interface display **1700** (FIG. **17**), as shown described below in further detail.

[0271] In some embodiments, the first financial institution can be configured to determine that the account balance of the demand deposit account is less than the payment amount of the transaction.

[0272] In many embodiments, the first financial institution can be configured to send to the mobile device an option to at least partially fund the transaction using the at least one non-demand deposit account. For example, the option can be displayed on the mobile device using a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail.

[0273] In a number of embodiments, the first financial institution can be configured to receive from the mobile device a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account. For example, the selection can be received on the mobile device through a user interface, such as shown in user interface display **1800** (FIG. **18**), user interface display **1900** (FIG. **19**), and/or user interface display **2000** (FIG. **20**), as described below in further detail. In many embodiments, the one or more first accounts further can include the demand deposit account. In some embodiments, a first portion of the payment amount of the transaction can be funded from the demand deposit account, and a second portion of the payment amount of the transaction can be funded from the at least one non-demand deposit account. In other embodiments, the demand deposit account can be devoid of being used to fund any portion of the payment amount of the transaction, and the payment amount of the transaction can be funded

wholly from the at least one non-demand deposit account.

[0274] In various embodiments, the one or more first accounts can include the loan account, and the loan account can be created after receiving the request to pay the merchant. In the same or other embodiments, the loan account can be used to fund at least a first portion of the payment amount of the transaction, and in a number of embodiments, a second portion of the payment amount can be funded from a demand deposit account or another non-demand deposit account of the consumer maintained at the first financial institution.

[0275] In some embodiments, the at least one non-demand deposit account can include a credit account. In a number of embodiments, at least a portion of the payment can be funded from a charge to the credit account. In various embodiments, the at least one non-demand deposit account can include a points account.

[0276] In certain embodiments, the first financial institution does not have access to a second account number for the second account for the transaction, and the second financial institution does not have access to a first account number for the first account for the transaction. In other embodiments, the first financial institution can have access to a second account number for the second account for the transaction, and/or the second financial institution can have access to a first account number for the first account for the transaction.

[0277] In several embodiments, method **1600** further can include a block **1603** of receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant. In many embodiments, the notification of the payment can be received by the merchant and/or at the point-of-sale terminal from the transaction system. In other embodiments, the notification of the payment can be received by the merchant and/or at the point-of-sale terminal from the second financial institution system.

[0278] Turning ahead in the drawings, FIG. **17** illustrates an exemplary user interface display **1700** to allow a consumer (e.g., **129** (FIG. **1**)) to approve a transaction on a mobile device (e.g., **120** (FIG. **1**)). User interface display **1700** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. In many embodiments, mobile application **123** (FIG. **1**) can provide an interface for display on mobile device **120** (FIG. **1**), which can include user interface display **1700**. In a number of embodiments, the interface can allow consumer **129** (FIG. **1**) to approve or decline a transaction request received from point-of-sale terminal **110** (FIG. **1**).

[0279] In a number of embodiments, user interface display **1700** can include a title bar **1701**, a descriptor **1710**, a payment amount field **1720**, a merchant field **1730**, a transaction identifier field **1740**, a prompt **1750**, an approving selection button **1760**, and/or a declining selection button **1770**. In many embodiments, title bar **1701** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. **1**)). In a number of embodiments, descriptor **1710** can describe that a transaction request was received. For example, after mobile device **120** (FIG. **1**) receives information, such as the transaction code, the merchant identifier, the payment amount, the transaction identifier, and/or other information from point-of-sale terminal **110** (FIG. **1**), then user interface display **1700** can be displayed on mobile device **120** (FIG. **1**) to consumer **129** (FIG. **1**).

[0280] In several embodiments, user interface display **1700** can include a number of fields to display information about the transaction, such as payment amount field **1720**, merchant field **1730**, and/or transaction identifier field **1740**. In many embodiments, payment amount field **1720** can display the payment amount received from point-of-sale terminal **110** (FIG. **1**). In several embodiments, merchant field **1730** can display the name of merchant **119** (FIG. **1**). In some embodiments, the name of the merchant can be received from point-of-sale terminal **110** (FIG. **1**). In other embodiment, the merchant identifier received from point-of-sale terminal **110** (FIG. **1**) can be used to retrieve the name of the merchant, such as by mobile device **120** (FIG. **1**) querying transaction system **140** (FIG. **1**) directly or through mobile wallet provider **160** (FIG. **1**) and/or

financial institution **130** (FIG. 1). In a number of embodiments, transaction identifier field **1740** can display the transaction identifier received from point-of-sale terminal **110** (FIG. 1). In other embodiments, user interface display **1700** can include additional or other suitable fields to display information about the transaction.

[0281] In several embodiments, prompt **1750** can ask consumer **129** (FIG. 1) to confirm the transaction using an account (e.g., consumer account **131** (FIG. 1)) that has been provisioned to or otherwise associated with mobile application **123** (FIG. 1), such as Checking Account A. When more than one account (e.g., consumer account **131** (FIG. 1)) has been provisioned to or otherwise associated with mobile application **123** (FIG. 1), the user interface display (e.g., **1700**) can include a request to select one of the accounts (e.g., consumer account **131** (FIG. 1)) to use for the payment transaction. In many embodiments, approving selection button **1760** can be selected by consumer **129** (FIG. 1) to approve the transaction using the account. In some embodiments, declining selection button **1770** can be selected by consumer **129** (FIG. 1) to decline the transaction using the account.

[0282] Proceeding to the next drawing, FIG. **18** illustrates an exemplary user interface display **1800** to allow a consumer (e.g., **129** (FIG. 1)) to choose to use another account for the payment transaction when the approved account has insufficient funds or limited funds. User interface display **1800** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. User interface display **1800** can be similar to user interface display **1700** (FIG. 17), and various elements of user interface display **1800** can be similar or identical to various elements of user interface display **1700** (FIG. 17). In many embodiments, mobile application **123** (FIG. 1) can provide an interface for display on mobile device **120** (FIG. 1), which can include user interface display **1800**. In a number of embodiments, the interface can allow consumer **129** (FIG. 1) to choose whether to use another account for the payment transaction when the approved account has insufficient or limited funds.

[0283] In a number of embodiments, user interface display **1800** can include a title bar **1801**, an account balance field **1810**, a payment amount field **1820**, a prompt **1830**, an account selection button **1840**, and/or a canceling selection button **1850**. In many embodiments, title bar **1801** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. 1)). Title bar **1801** can be similar or identical to title bar **1701** (FIG. 17).

[0284] In several embodiments, user interface display **1800** can include a number of fields to display information about the transaction request using the account approved in user interface display **1700** (FIG. 17). For example, the fields can include account balance field **1810** and payment amount field **1820**. In some embodiments, account balance field can show the balance of the account that was approved for payment using user interface display **1700** (FIG. 17). In many embodiments, payment amount field **1820** can display the payment amount. Payment amount field **1820** can be similar or identical to payment amount field **1720** (FIG. 17). In many embodiments, user interface display **1800** can be displayed when the account balance is less than the payment amount. In other embodiments, user interface display **1800** can be displayed when the account balance is more than the payment amount, but the difference between the account balance and the payment amount is less than a threshold amount, such as \$10, \$50, \$100, \$500, or another suitable threshold amount.

[0285] In several embodiments, prompt **1830** can ask consumer **129** (FIG. 1) whether to use another account or loan to pay for the payment amount. In many embodiments, account selection button **1840** can be selected by consumer **129** (FIG. 1) to indicate that another account or loan should be used to at least partially pay for the payment amount. In some embodiments, canceling selection button **1850** can be selected by consumer **129** (FIG. 1) to cancel the transaction. In some embodiments, such as when the account balance is sufficient to cover the payment amount, another

selection button (not shown) can be included in the user interface display (e.g., **1800**) to authorize proceeding with the payment transaction using the account approved in user interface display **1700** (FIG. 17).

[0286] Proceeding to the next drawing, FIG. **19** illustrates an exemplary user interface display **1900** to allow a consumer (e.g., **129** (FIG. 1)) to select another account for the payment transaction when the approved account has insufficient funds. User interface display **1900** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. User interface display **1900** can be similar to user interface display **1700** (FIG. 17) and/or user interface display **1800** (FIG. 18), and various elements of user interface display **1900** can be similar or identical to various elements of user interface display **1700** (FIG. 17) and/or user interface display **1800** (FIG. 18). In many embodiments, mobile application **123** (FIG. 1) can provide an interface for display on mobile device **120** (FIG. 1), which can include user interface display **1900**. In a number of embodiments, the interface can allow consumer **129** (FIG. 1) to select another account for the payment transaction when the approved account has insufficient or limited funds.

[0287] In a number of embodiments, user interface display **1900** can include a title bar **1901**, a prompt **1910**, an option **1911**, an option **1912**, an option **1913**, an option **1914**, a proceeding selection button **1920**, and/or a canceling selection button **1930**. In many embodiments, title bar **1901** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. 1)). Title bar **1901** can be similar or identical to title bar **1701** (FIG. 17) and/or title bar **1801** (FIG. 18).

[0288] In many embodiments, prompt **1910** can ask consumer **129** (FIG. 1) to select another account or loan to use for the payment transaction. In various embodiments, user interface display **1900** can include one or more options of other accounts or loan options that the user can select, such as options **1911-1914**. In some embodiments, the options can include one or more existing accounts, such as Savings Account B displayed in option **1911**, Credit Account C displayed in option **1912**, and Points Account D displayed in option **1914**. For example, Savings Account B, Credit Account C, and/or Points Account D can be others of consumer accounts **131** (FIG. 1) held by consumer **129** (FIG. 1) at financial institution **130** (FIG. 1). In a number of embodiments, the options can include the opportunity to open a new loan, as displayed in option **1913**. For example, the new loan can be a micro-loan to pay at least partially for the payment amount, as described above. In some embodiments, user interface display **1900** can allow consumer **129** (FIG. 1) to select one of options **1911-1914**. In other embodiments, user interface display **1900** can allowed consumer **129** (FIG. 1) to select more than one of options **1911-1914**.

[0289] In many embodiments, proceeding selection button **1920** can be selected by consumer **129** (FIG. 1) to indicate that accounts corresponding to the one or more options (e.g., **1911-1914**) should be used for the payment transaction. In some embodiments, canceling selection button **1930** can be selected by consumer **129** (FIG. 1) to cancel the transaction.

[0290] Proceeding to the next drawing, FIG. **20** illustrates an exemplary user interface display **2000** to allow a consumer (e.g., **129** (FIG. 1)) to select the amount to pay using the other account selected in user interface display **1900** (FIG. 19). User interface display **2000** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. User interface display **2000** can be similar to user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), and/or user interface display **1900** (FIG. 19), and various elements of user interface display **2000** can be similar or identical to various elements of user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), and/or user interface display **1900** (FIG. 19). In many embodiments, mobile application **123** (FIG. 1) can provide an interface for display on mobile

device **120** (FIG. 1), which can include user interface display **2000**. In a number of embodiments, the interface can allow consumer **129** (FIG. 1) to select the amount to pay using the other account selected in user interface display **1900** (FIG. 19).

[0291] In a number of embodiments, user interface display **2000** can include a title bar **2001**, a prompt **2010**, an option **2011**, an option **2012**, an approving selection button **2020**, and/or a canceling selection button **2030**. In many embodiments, title bar **2001** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. 1)). Title bar **2001** can be similar or identical to title bar **1701** (FIG. 17), title bar **1801** (FIG. 18), and/or title bar **1901** (FIG. 19).

[0292] In many embodiments, prompt **2010** can ask consumer **129** (FIG. 1) to select the amount to pay using the other account or payment option selected in user interface display **1900** (FIG. 19), such as a new loan. In various embodiments, user interface display **2000** can include one or more options that consumer **129** (FIG. 1) can select, such as options **2011-2012**. For example, option **2011** can include the option to pay the full payment amount using the other account (e.g., new loan) selected in user interface display **1900** (FIG. 19). As another example, option **2012** can include the option to partially pay the payment amount using the other account (e.g., new loan) selected in user interface display **1900** (FIG. 19), and can allow consumer **129** (FIG. 1) to enter the amount to be used for the partial payment from the other account. When more than one account was selected using user interface display **1900** (FIG. 19), the user interface display (e.g., **2000**) can include a prompt (e.g., **2010**) and options (e.g., **2011-2012**) for each of the other accounts selected in user interface display **1900** (FIG. 19). In many embodiments, only one of options **2011** and **2012** can be selected, per account, by consumer **129** (FIG. 1) and approved by consumer **129** (FIG. 1) via approving selection button **2020**.

[0293] In many embodiments, approving selection button **2020** can be selected by consumer **129** (FIG. 1) to indicate that amount selected in one of options **2011-2012** should be used to pay for the payment transaction. In some embodiments, canceling selection button **2030** can be selected by consumer **129** (FIG. 1) to cancel the transaction.

[0294] Proceeding to the next drawing, FIG. 21 illustrates an exemplary user interface display **2100** to confirm that a payment request has been sent from mobile device **120** (FIG. 1). User interface display **2100** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. User interface display **2100** can be similar to user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), and/or user interface display **2000** (FIG. 20), and various elements of user interface display **2100** can be similar or identical to various elements of user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), and/or user interface display **2000** (FIG. 20). In many embodiments, mobile application **123** (FIG. 1) can provide an interface for display on mobile device **120** (FIG. 1), which can include user interface display **2100**. In a number of embodiments, the interface can display a confirmation to consumer **129** (FIG. 1) that a request has been sent for the payment authorized in user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), and/or user interface display **2000** (FIG. 20).

[0295] In a number of embodiments, user interface display **2100** can include a title bar **2101**, a descriptor field **2110**, and/or a selection button **2120**. In many embodiments, title bar **2101** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. 1)). Title bar **2101** can be similar or identical to title bar **1701** (FIG. 17), title bar **1801** (FIG. 18), title bar **1901** (FIG. 19), and/or title bar **2001** (FIG. 20).

[0296] In many embodiments, descriptor field **2110** can include information about the payment that was requested, such as the amount that was requested to be paid out of each of the accounts that

were authorized for payment by consumer **129** (FIG. 1). For example, if consumer **129** (FIG. 1) choose to partially pay for the payment amount using a new loan in the amount of \$83.20, then descriptor field **2110** can display that \$60.00 from Account A was used and \$83.20 from New Loan was used, as shown in FIG. 21.

[0297] In several embodiments, selection button **2120** can be selected by consumer **129** (FIG. 1) to dismiss the message displayed in user interface display **2100**.

[0298] Proceeding to the next drawing, FIG. 22 illustrates an exemplary user interface display **2200** to confirm that payment transaction to merchant **119** (FIG. 1) has successfully completed. User interface display **2200** is merely exemplary, and embodiments of the user interface display are not limited to the embodiments presented herein. The user interface display can be employed in many different embodiments or examples not specifically depicted or described herein, and can include other suitable elements. User interface display **2200** can be similar to user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), user interface display **2000** (FIG. 20), and/or user interface display **2100** (FIG. 21), and various elements of user interface display **2200** can be similar or identical to various elements of user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), user interface display **2000** (FIG. 20), and/or user interface display **2100** (FIG. 21). In many embodiments, mobile application **123** (FIG. 1) can provide an interface for display on mobile device **120** (FIG. 1), which can include user interface display **2200**. In a number of embodiments, the interface can display a confirmation to consumer **129** (FIG. 1) that payment to merchant **119** (FIG. 1) has successfully completed for the payment authorized in user interface display **1700** (FIG. 17), user interface display **1800** (FIG. 18), user interface display **1900** (FIG. 19), and/or user interface display **2000** (FIG. 20).

[0299] In a number of embodiments, user interface display **2200** can include a title bar **2201**, a descriptor field **2210**, and/or a selection button **2220**. In many embodiments, title bar **2201** can include the name of the mobile wallet or mobile application (e.g., mobile application **123** (FIG. 1)). Title bar **2201** can be similar or identical to title bar **1701** (FIG. 17), title bar **1801** (FIG. 18), title bar **1901** (FIG. 19), title bar **2001** (FIG. 20), and/or title bar **2101** (FIG. 21).

[0300] In many embodiments, descriptor field **2210** can include a message about the success or failure of the payment request, for example, that the payment is complete. If the request failed, the message can indicate that the payment failed.

[0301] In several embodiments, selection button **2220** can be selected by consumer **129** (FIG. 1) to dismiss the message displayed in user interface display **2200**.

[0302] Turning ahead in the drawings, FIG. 23 illustrates a flow chart for a method **2300**, according to an embodiment. In some embodiments, method **2300** can be a method of facilitating secure payment transactions. Method **2300** is merely exemplary and is not limited to the embodiments presented herein. Method **2300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2300** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2300** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2300** can be combined or skipped. In some embodiments, method **2300** can be performed by mobile device **120** (FIG. 1) and/or mobile application **123** (FIG. 1).

[0303] Referring to FIG. 23, method **2300** can include a block **2301** of receiving a preauthorization code at a mobile device while the mobile device is in data communication with a mobile wallet provider. For example, the mobile device can be in data communication with the mobile wallet provider, such as through communication channel **171** (FIG. 1). The mobile device can be similar or identical to mobile device **120** (FIG. 1). The mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. 1). In some embodiments, the preauthorization code can be similar or identical to the preauthorization code described above. In a number of embodiments, the

preauthorization code can include a preauthorization amount, an expiration time, and a digital signature.

[0304] In several embodiments, the mobile wallet provider can be operated by a first financial institution that maintains a first account of a user of the mobile device. The user of the mobile device can be similar or identical to consumer **129** (FIG. **1**). The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. **1**). In other embodiments, the mobile wallet provider can be operated by an entity that is different from the first financial institution. In several embodiments, the digital signature of the preauthorization code can be cryptographically signed by the first financial institution that maintains the first account of the user.

[0305] In several embodiments, method **2300** also can include a block **2302** of storing the preauthorization code in the mobile device. In many embodiments, the preauthorization code can be stored in the mobile device in an encrypted form.

[0306] In a number of embodiments, method **2300** additionally can include a block **2303** of receiving, at the mobile device, an authorization from a user of the mobile device for a transaction having a transaction amount while the user is at a point-of-sale terminal of a first entity. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The first entity can be similar or identical to merchant **119** (FIG. **1**). The authorization from the user can be similar or identical to the authorization described above. In many embodiments, the transaction can be for a purchase by the user of one or more items from the first entity.

[0307] In several embodiments, method **2300** further can include a block **2304** of determining that the mobile device is unable to communicate with the mobile wallet provider. For example, the mobile device can be “offline,” as described above. As an example, the mobile device can be unable to communicate with the mobile wallet provider when a connection between the two, such as communication channel **171** (FIG. **1**), is down.

[0308] In a number of embodiments, method **2300** additionally can include a block **2305** of verifying that the transaction amount is less than or equal to the preauthorization amount.

[0309] In several embodiments, method **2300** further can include a block **2306** of providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity. The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In many embodiments, block **2306** can be performed while the mobile device is unable to communicate with the mobile wallet provider. The transaction code can be similar or identical to the transaction code described above. In some embodiments, the transaction code can include the preauthorization code, a transaction identifier, and the transaction amount.

[0310] In some embodiments, block **2306** of providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity can include displaying the transaction code as a matrix barcode on a screen of the mobile device. In many embodiments, the point-of-sale terminal can scan the matrix barcode from the screen of the mobile device. In other embodiment, block **2306** of providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity can include transmitting the transaction code from the mobile device to the point-of-sale terminal using a proximity-based wireless data communication protocol.

[0311] In some embodiments, the approval can include one of: (a) a settlement credit push of funds

for the transaction amount from the first account of the user to a second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account. The second account can be similar or identical to merchant account **151** (FIG. **1**).

[0312] In various embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity through a second financial institution that maintains the second account of the first entity, such as through communication channels **173** and **174** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). In other embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity directly, such as communication channel **178** (FIG. **1**).

[0313] Turning ahead in the drawings, FIG. **24** illustrates a flow chart for a method **2400**, according to an embodiment. In some embodiments, method **2400** can be a method of facilitating secure payment transactions. Method **2400** is merely exemplary and is not limited to the embodiments presented herein. Method **2400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2400** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2400** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2400** can be combined or skipped. In some embodiments, method **2400** can be performed by transaction system **140** (FIG. **1**). In some embodiments, method **2400** and other blocks in method **2400** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0314] Referring to FIG. **24**, method **2400** can include a block **2401** of receiving a transaction amount and a preauthorization code from a first entity. The first entity can be similar or identical to merchant **119** (FIG. **1**). In some embodiments, the preauthorization code can be similar or identical to the preauthorization code described above. In many embodiments, the preauthorization code can include a preauthorization amount, an expiration time, and a digital signature. In some embodiments, the transaction amount can be for a transaction authorized by a user of a mobile device at a point-of-sale terminal of the first entity. The user of the mobile device can be similar or identical to consumer **129** (FIG. **1**). The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**).

[0315] In many embodiments, the transaction amount can be less than or equal to the preauthorization amount. In some embodiments, the mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with a mobile wallet provider, such as through communication channel **171** (FIG. **1**). The mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. **1**). In many embodiments, the mobile device provided a transaction code to the point-of-sale terminal while the mobile device was unable to communicate with the mobile wallet provider. For example, the mobile device can be “offline,” as described above. As an example, the mobile device can be unable to communicate with the mobile wallet provider when a connection between the two, such as communication channel **171** (FIG. **1**), is down.

[0316] In some embodiments, the transaction code can include the preauthorization code, a transaction identifier for the transaction, and the transaction amount. In many embodiments, the transaction code can be provided from the mobile device to the point-of-sale terminal by the mobile device displaying the transaction code as a matrix barcode on a screen of the mobile device, and the point-of-sale terminal scanning the matrix barcode from the screen of the mobile device. In other embodiments, the transaction code can be provided from the mobile device to the point-of-sale terminal by the mobile device transmitting the transaction code from the mobile device to the

point-of-sale terminal using a proximity-based wireless data communication protocol. [0317] In some embodiments, the digital signature of the preauthorization code can be cryptographically signed by a first financial institution that maintains a first account of the user. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. **1**).

[0318] In some embodiments, the transaction can be for a purchase by the user of one or more items from the first entity. In many embodiments, the mobile wallet provider can be operated by the first financial institution that maintains the first account of the user. In other embodiments, the mobile wallet provider can be operated by an entity that is different from the first financial institution. In some embodiments, the preauthorization code can be stored in the mobile device in an encrypted form.

[0319] In several embodiments, method **2400** also can include a block **2402** of verifying the preauthorization code using the digital signature of the preauthorization code. In some embodiments, block **2402** of verifying the preauthorization code using the digital signature of the preauthorization code can include verifying that the transaction amount is less than or equal to the preauthorization amount, and verifying that the expiration time is at a future time (e.g., not yet expired).

[0320] In a number of embodiments, method **2400** additionally can include a block **2403** of sending an approval for the transaction to the first entity in real-time while the user remains at the point-of-sale terminal of the first entity. In some embodiments, the approval can include one of: (a) a settlement credit push of funds for the transaction amount from the first account of the user to a second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account. The second account can be similar or identical to merchant account **151** (FIG. **1**).

[0321] In various embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity through a second financial institution that maintains the second account of the first entity, such as through communication channels **173** and **174** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). In other embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity directly, such as communication channel **178** (FIG. **1**).

[0322] Turning ahead in the drawings, FIG. **25** illustrates a flow chart for a method **2500**, according to an embodiment. In some embodiments, method **2500** can be a method of facilitating secure payment transactions. Method **2500** is merely exemplary and is not limited to the embodiments presented herein. Method **2500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2500** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2500** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2500** can be combined or skipped. In some embodiments, method **2500** can be performed by point-of-sale terminal **110** (FIG. **1**). In some embodiments, method **2500** and other blocks in method **2500** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0323] Referring to FIG. **25**, method **2500** can include a block **2501** of receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The first entity can be similar or identical to merchant **119** (FIG. **1**). The

mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. 1). In many embodiments, the transaction code can include a preauthorization code, a transaction identifier for a transaction authorized by a user of the mobile device at the point-of-sale terminal, and a transaction amount for the transaction. The user of the mobile device can be similar or identical to consumer **129** (FIG. 1).

[0324] In many embodiments, the mobile device received the preauthorization code and stored the preauthorization code in the mobile device while the mobile device was in data communication with the mobile wallet provider, such as through communication channel **171** (FIG. 1). In some embodiments, the preauthorization code includes a preauthorization amount, an expiration time, and a digital signature. In many embodiments, the transaction amount can be less than or equal to the preauthorization amount.

[0325] In some embodiments, block **2501** of receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider can include scanning a matrix barcode displayed on the screen of the mobile device. The matrix barcode can include the transaction code. In other embodiments, block **2501** of receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider can include receiving a transmission of the transaction code from the mobile device using a proximity-based wireless data communication protocol.

[0326] In many embodiments, the digital signature of the preauthorization code can be cryptographically signed by a first financial institution that maintains a first account of the user. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. 1). In some embodiments, the transaction can be for a purchase by the user of one or more items from the first entity. In many embodiments, the mobile wallet provider can be operated by the first financial institution that maintains the first account of the user. In other embodiments, the mobile wallet provider can be operated by an entity that is different from the first financial institution. In some embodiments, the preauthorization code can be stored in the mobile device in an encrypted form.

[0327] In several embodiments, method **2500** also can include a block **2502** of sending the transaction amount and the preauthorization code to a transaction system. The transaction system can be similar or identical to transaction system **140** (FIG. 1). In many embodiments, the transaction system can verify the preauthorization code using the digital signature of the preauthorization code before sending the approval for the transaction.

[0328] In various embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity through a second financial institution that maintains a second account of the first entity, such as through communication channels **173** and **174** (FIG. 1). The second financial institution can be similar or identical to financial institution **150** (FIG. 1). The second account can be similar or identical to merchant account **151** (FIG. 1). In other embodiments, the transaction amount and the preauthorization code can be sent to the transaction system from the first entity directly, such as communication channel **178** (FIG. 1).

[0329] In a number of embodiments, method **2500** additionally can include a block **2503** of receiving an approval for the transaction from the transaction system in real-time while the user remains at the point-of-sale terminal. In a number of embodiments, the approval can include one of: (a) a settlement credit push of funds for the transaction amount from the first account of the user to the second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account.

[0330] Turning ahead in the drawings, FIG. **26** illustrates a flow chart for a method **2600**, according to an embodiment. In some embodiments, method **2600** can be a method of facilitating secure payment transactions. Method **2600** is merely exemplary and is not limited to the embodiments

presented herein. Method **2600** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2600** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2600** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2600** can be combined or skipped. In some embodiments, method **2600** can be performed by mobile device **120** (FIG. 1) and/or mobile application **126** (FIG. 1).

[0331] Referring to FIG. 26, method **2600** can include a block **2601** of receiving, at a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount for a transaction, and a transaction identifier for the transaction. The mobile device can be similar or identical to mobile device **120** (FIG. 1). The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. 1). The first entity can be similar or identical to merchant **119** (FIG. 1). In some embodiments, the identifier of the first entity, the transaction amount, and the transaction identifier can be received from the point-of-sale terminal as part of a digitally signed transaction code. In several embodiments, the digitally signed transaction code can be cryptographically signed by the point-of-sale terminal, and/or the digitally signed transaction code can be verified by the mobile device.

[0332] In many embodiments, the transaction can be for a purchase by a user of one or more items from the first entity. The user of the mobile device can be similar or identical to consumer **129** (FIG. 1). In some embodiments, first information about the one or more items can be scanned into the mobile application by the user in a store of the first entity. In various embodiments, the first information about the one or more items can be provided by the mobile device to the point-of-sale terminal to cause the point-of-sale terminal to generate the transaction amount for the transaction.

[0333] In several embodiments, method **2600** also can include a block **2602** of receiving an authorization from the user of the mobile device for the transaction while the user is at the point-of-sale terminal. In many embodiments, the mobile device can run a mobile application that is associated with a mobile wallet provider. The mobile application can be similar or identical to mobile application **123** (FIG. 1). The mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. 1). In several embodiments, the mobile wallet provider can be operated by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). In other embodiments, the mobile wallet provider can be operated by an entity that is different from the first financial institution.

[0334] In a number of embodiments, method **2600** additionally can include a block **2603** of determining that the mobile device is unable to communicate with the mobile wallet provider. For example, the mobile device can be “offline,” as described above. As an example, the mobile device can be unable to communicate with the mobile wallet provider when a connection between the two, such as communication channel **171** (FIG. 1), is down.

[0335] In several embodiments, method **2600** further can include a block **2604** of generating an encrypted transaction code. In many embodiments, the encrypted transaction code can include a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by the first financial institution. The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. 1). In some embodiments, the preauthorization from the user can be digitally signed by the mobile device, such that the encrypted transaction code includes a digital signature. In many embodiments, the encrypted transaction code can be encrypted by the mobile device using a public key of the mobile wallet provider.

[0336] In a number of embodiments, method **2600** additionally can include a block **2605** of sending the encrypted transaction code from the mobile device to the point-of-sale terminal to cause the encrypted transaction code to be sent through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the

preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, to cause the payment information to be routed through the transaction system to the second financial institution, and to cause the point-of-sale terminal to receive a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal. The transaction system can be similar or identical to transaction system **140** (FIG. **1**). The second account can be similar or identical to merchant account **151** (FIG. **1**). The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The proxy communication channel can be similar or identical to various embodiments of the proxy communication channel described above. For example, in some embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend through the second financial institution between the point-of-sale terminal and the transaction system. In other embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend between the point-of-sale terminal and the transaction system without including the transaction system. In many embodiments, the transaction system can be maintained by an entity that is different from the first entity, the first financial institution, and the second financial institution.

[0337] In some embodiments, the mobile wallet provider can verify the preauthorization from the user using the digital signature. In various embodiments, the encrypted transaction code can be decrypted by the mobile wallet provider using a private key of the mobile wallet provider. In a number of embodiments, block **2605** can include displaying the encrypted transaction code as a matrix barcode on a screen of the mobile device. The point-of-sale terminal can scan the matrix barcode from the screen of the mobile device. In other embodiments, block **2605** can include transmitting the encrypted transaction code from the mobile device to the point-of-sale terminal using a proximity-based wireless data communication protocol.

[0338] In many embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the transaction amount, and/or one of: (a) a settlement credit push of funds for the transaction amount from the first account of the user to the second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account.

[0339] Turning ahead in the drawings, FIG. **27** illustrates a flow chart for a method **2700**, according to an embodiment. In some embodiments, method **2700** can be a method of facilitating secure payment transactions. Method **2700** is merely exemplary and is not limited to the embodiments presented herein. Method **2700** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2700** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2700** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2700** can be combined or skipped. In some embodiments, method **2700** can be performed by transaction system **140** (FIG. **1**). In some embodiments, method **2700** and other blocks in method **2700** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0340] Referring to FIG. **27**, method **2700** can include a block **2701** of receiving, at a transaction system being situated along a proxy communication channel extending from a point-of-sale terminal of a first entity to a mobile wallet provider, an encrypted transaction code. The transaction system can be similar or identical to transaction system **140** (FIG. **1**). The point-of-sale terminal

can be similar or identical to point-of-sale terminal **110** (FIG. 1). The first entity can be similar or identical to merchant **119** (FIG. 1). The mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. 1).

[0341] In many embodiments, the encrypted transaction code can be generated and sent to the point-of-sale terminal by a mobile device that runs a mobile application associated with the mobile wallet provider. The mobile device can be similar or identical to mobile device **120** (FIG. 1). The mobile application can be similar or identical to mobile application **123** (FIG. 1). In some embodiments, the mobile device can receive from a point-of-sale terminal an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction. The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. 1). In various embodiments, the mobile device can receives an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal. The user of the mobile device can be similar or identical to consumer **129** (FIG. 1). In some embodiments, the mobile device can determine that the mobile device is unable to communicate with the mobile wallet provider. For example, the mobile device can be “offline,” as described above. As an example, the mobile device can be unable to communicate with the mobile wallet provider when a connection between the two, such as communication channel **171** (FIG. 1), is down.

[0342] In many embodiments, the encrypted transaction code can include a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. 1). The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. 1).

[0343] The proxy communication channel can be similar or identical to various embodiments of the proxy communication channel described above. For example, in some embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend through a second financial institution between the point-of-sale terminal and the transaction system. The second financial institution can be similar or identical to financial institution **150** (FIG. 1). In other embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend between the point-of-sale terminal and the transaction system without including the transaction system.

[0344] In some embodiments, the transaction system can be maintained by an entity that is different from the first entity, the first financial institution, and the second financial institution. In various embodiments, the mobile wallet provider can be operated by the first financial institution. In many embodiments, the identifier of the first entity, the transaction amount, and the transaction identifier can be sent from the point-of-sale terminal to the mobile device as part of a digitally signed transaction code.

[0345] In many embodiments, the digitally signed transaction code can be cryptographically signed by the point-of-sale terminal, and/or the digitally signed transaction code can be verified by the mobile device. In some embodiments, the preauthorization from the user can be digitally signed by the mobile device, such that the encrypted transaction code includes a digital signature. In several embodiments, the encrypted transaction code can be encrypted by the mobile device using a public key of the mobile wallet provider.

[0346] In some embodiments, the transaction can be for a purchase by the user of one or more items from the first entity. In many embodiments, first information about the one or more items can be scanned into the mobile application by the user in a store of the first entity. In various embodiments, the first information about the one or more items can be received at the point-of-sale terminal from the mobile device to cause the point-of-sale terminal to generate the transaction amount for the transaction.

[0347] In many embodiments, the point-of-sale terminal can receive the encrypted transaction code by scanning the encrypted transaction code as a matrix barcode from a screen of the mobile device.

In other embodiments, the point-of-sale terminal can receive the encrypted transaction from the mobile device using a proximity-based wireless data communication protocol.

[0348] In several embodiments, method **2700** also can include a block **2702** of sending the encrypted transaction code through the proxy communication channel to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user. In many embodiments, the mobile wallet provider can verify the preauthorization from the user using the digital signature. In some embodiments, the encrypted transaction code can be decrypted by the mobile wallet provider using a private key of the mobile wallet provider.

[0349] In a number of embodiments, method **2700** additionally can include a block **2703** of receiving, from the first financial institution, a request including the identifier of the first entity.

[0350] In several embodiments, method **2700** also can include a block **2704** of determining an account identifier of a second account of the first entity maintained by the second financial institution based on the identifier of the first entity. The second account can be similar or identical to merchant account **151** (FIG. **1**). For example, the account identified of the second account can be determined using merchant account database **141** (FIG. **1**) and/or the identifier of the first entity.

[0351] In a number of embodiments, method **2700** additionally can include a block **2705** of sending the account identifier of the second account to the first financial institution.

[0352] In several embodiments, method **2700** also can include a block **2706** of receiving, from the first financial institution, payment information regarding a payment to be made to the second account from the first account for the transaction. In some embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the transaction amount, and/or one of: (a) a settlement credit push of funds for the transaction amount from the first account of the user to the second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account.

[0353] In a number of embodiments, method **2700** additionally can include a block **2707** of sending the payment information to the second financial institution, to cause the point-of-sale terminal to receive a notification in real-time while the user remains at the point-of-sale terminal.

[0354] Turning ahead in the drawings, FIG. **28** illustrates a flow chart for a method **2800**, according to an embodiment. In some embodiments, method **2800** can be a method of facilitating secure payment transactions. Method **2800** is merely exemplary and is not limited to the embodiments presented herein. Method **2800** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the procedures, the processes, and/or the activities of method **2800** can be performed in the order presented. In other embodiments, the procedures, the processes, and/or the activities of method **2800** can be performed in any suitable order. In still other embodiments, one or more of the procedures, the processes, and/or the activities of method **2800** can be combined or skipped. In some embodiments, method **2800** can be performed by point-of-sale terminal **110** (FIG. **1**). In some embodiments, method **2800** and other blocks in method **2800** can include using a distributed network including distributed memory architecture to perform the associated activity. This distributed architecture can reduce the impact on the network and system resources to reduce congestion in bottlenecks while still allowing data to be accessible from a central location.

[0355] Referring to FIG. **28**, method **2800** can include a block **2801** of sending, to a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction. The mobile device can be similar or identical to mobile device **120** (FIG. **1**). The point-of-sale terminal can be similar or identical to point-of-sale terminal **110** (FIG. **1**). The first entity can be similar or identical to merchant **119** (FIG. **1**).

[0356] In many embodiments, the mobile device can run a mobile application that is associated with a mobile wallet provider. The mobile application can be similar or identical to mobile

application **123** (FIG. **1**). The mobile wallet provider can be similar or identical to mobile wallet provider **160** (FIG. **1**). In several embodiments, the mobile device can receive an authorization from a user of the mobile device for the transaction while the user is at the point-of-sale terminal. The user of the mobile device can be similar or identical to consumer **129** (FIG. **1**). In some embodiments, the mobile device can determine that the mobile device is unable to communicate with the mobile wallet provider. For example, the mobile device can be “offline,” as described above. As an example, the mobile device can be unable to communicate with the mobile wallet provider when a connection between the two, such as communication channel **171** (FIG. **1**), is down. In many embodiments, the mobile device can generate an encrypted transaction code. In some embodiments, the encrypted transaction code can include a preauthorization from the user to pay the first entity for the transaction amount from a first account of the user maintained by a first financial institution. The first financial institution can be similar or identical to financial institution **130** (FIG. **1**). The first account of the user can be similar or identical to one or more of consumer accounts **131** (FIG. **1**).

[0357] In some embodiments, the mobile wallet provider can be operated by the first financial institution. In various embodiments, the identifier of the first entity, the transaction amount, and the transaction identifier can be sent from the point-of-sale terminal to the mobile device as part of a digitally signed transaction code. In many embodiments, the digitally signed transaction code can be cryptographically signed by the point-of-sale terminal. In a number of embodiments, the digitally signed transaction code can be verified by the mobile device. In some embodiments, the identifier of the first entity, the transaction amount, and the transaction identifier can be sent from the point-of-sale terminal to the mobile device as part of a digitally signed transaction code. In several embodiments, the digitally signed transaction code can be cryptographically signed by the point-of-sale terminal. In many embodiments, the digitally signed transaction code can be verified by the mobile device. In some embodiments, the encrypted transaction code can be encrypted by the mobile device using a public key of the mobile wallet provider. In several embodiments, the encrypted transaction code can be decrypted by the mobile wallet provider using a private key of the mobile wallet provider.

[0358] In a number of embodiments, the transaction can be for a purchase by the user of one or more items from the first entity. In some embodiments, first information about the one or more items can be scanned into the mobile application by the user in a store of the first entity. In various embodiments, the first information about the one or more items can be received at the point-of-sale terminal from the mobile device to cause the point-of-sale terminal to generate the transaction amount for the transaction.

[0359] In several embodiments, method **2800** also can include a block **2802** of receiving the encrypted transaction code from the mobile device. In some embodiments, block **2802** of receiving the encrypted transaction code from the mobile device can include scanning the encrypted transaction code as a matrix barcode from a screen of the mobile device. In other embodiments, block **2802** of receiving the encrypted transaction code from the mobile device can include receiving the encrypted transaction code from the mobile device using a proximity-based wireless data communication protocol.

[0360] In a number of embodiments, method **2800** additionally can include a block **2803** of sending the encrypted transaction code through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, and to cause the payment information to be routed through the transaction system to the second

financial institution. The second financial institution can be similar or identical to financial institution **150** (FIG. **1**). The second account can be similar or identical to merchant account **151** (FIG. **1**). The transaction system can be similar or identical to transaction system **140** (FIG. **1**). In several embodiments, the transaction system can be maintained by an entity that is different from the first entity, the first financial institution, and the second financial institution.

[0361] In many embodiments, the proxy communication channel can be similar or identical to various embodiments of the proxy communication channel described above. For example, in some embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend through the second financial institution between the point-of-sale terminal and the transaction system. In other embodiments, the proxy communication channel from the point-of-sale terminal to the mobile wallet provider can extend between the point-of-sale terminal and the transaction system without including the transaction system.

[0362] In several embodiments, the payment information can include the transaction identifier, the account identifier of the second account, the transaction amount, and/or one of: (a) a settlement credit push of funds for the transaction amount from the first account of the user to the second account of the first entity, or (b) an irrevocable promise to pay the transaction amount from the first account to the second account.

[0363] In several embodiments, method **2800** also can include a block **2804** of receiving, at the point-of-sale terminal, a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0364] Returning again to FIG. **1**, as described above, point-of-sale terminal **110** can include one or more systems, such as checkout system **111**, communication system **112**, payment system **113**, consumer information system **114**, security system **115**, preauthorization system **116**, and/or proxy communication system **117**. Point-of-sale terminal **110** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Point-of-sale terminal **110** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of point-of-sale terminal **110** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0365] In many embodiments, checkout system **111** can at least partially perform block **501** (FIG. **5**) of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer, block **901** (FIG. **9**) of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction, and/or block **1601** (FIG. **16**) of determining, at a point-of-sale terminal at a store of a merchant, a payment amount for one or more items to be purchased from the merchant by a consumer in a transaction.

[0366] In several embodiments, communication system **112** can at least partially perform block **502** (FIG. **5**) of sending first information from the point-of-sale terminal to a mobile device used by the consumer, block **503** (FIG. **5**) of receiving at the point-of-sale terminal from the mobile device, information about the consumer, block **504** (FIG. **5**) of receiving, at the point-of-sale terminal from the second financial institution, a notification to satisfy an expectation of the merchant for payment from the consumer, block **903** (FIG. **9**) of providing the transaction code to a mobile device being used by the consumer, block **904** (FIG. **9**) of receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant, block **1602** (FIG. **16**) of sending first information from the point-of-sale terminal to a mobile device used by the consumer, block **1603** (FIG. **16**) of receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant, block **2501** (FIG. **25**) of receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider, block **2502** (FIG. **25**) of sending the transaction amount and the preauthorization

code to a transaction system, and/or block **2801** (FIG. **28**) of sending, to a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction.

[0367] In a number of embodiments, payment system **113** can at least partially perform block **504** (FIG. **5**) of receiving, at the point-of-sale terminal from the second financial institution, a notification to satisfy an expectation of the merchant for payment from the consumer, block **904** (FIG. **9**) of receiving, at the point-of-sale terminal, a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant, block **2503** (FIG. **25**) of receiving an approval for the transaction from the transaction system in real-time while the user remains at the point-of-sale terminal, and/or block **2804** (FIG. **28**) of receiving, at the point-of-sale terminal, a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0368] In various embodiments, consumer information system **114** can at least partially perform block **503** (FIG. **5**) of receiving at the point-of-sale terminal from the mobile device, information about the consumer.

[0369] In a number of embodiments, security system **115** can at least partially perform block **902** (FIG. **9**) of generating a transaction code including a merchant public identifier, the payment amount, a transaction identifier for the transaction, and a digital signature, and/or block **2801** (FIG. **28**) of sending, to a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount of a transaction, and a transaction identifier for the transaction.

[0370] In a number of embodiments, preauthorization system **116** can at least partially perform block **2501** (FIG. **25**) of receiving a transaction code from a mobile device at a point-of-sale terminal of a first entity while the mobile device is unable to communicate with a mobile wallet provider, and/or block **2502** (FIG. **25**) of sending the transaction amount and the preauthorization code to a transaction system.

[0371] In many embodiments, proxy communication system **117** can at least partially perform block **2802** (FIG. **28**) of receiving the encrypted transaction code from the mobile device, and/or block **2803** (FIG. **28**) of sending the encrypted transaction code through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, and to cause the payment information to be routed through the transaction system to the second financial institution

[0372] Continuing with FIG. **1**, as described above, mobile device **120** can include one or more systems, such as authentication system **121**, account system **122**, communication system **124**, security system **125**, loan system **126**, stand-in credit system **127**, and/or proxy communication system **128**. Mobile device **120** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Mobile device **120** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of mobile device **120** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0373] In many embodiments, authentication system **121** can at least partially perform block **401** (FIG. **4**) of performing, at a mobile device, a preliminary identity authentication of a consumer using the mobile device, block **407** (FIG. **4**) of performing, at the mobile device, the additional identity authentication of the consumer using the mobile device, and/or block **1301** (FIG. **13**) of performing, at a mobile device being used by a consumer, an identity authentication of the

consumer.

[0374] In several embodiments, account system **122** can at least partially perform block **403** (FIG. **4**) of sending, from the mobile device to the first financial institution, a preliminary request for account information, block **404** (FIG. **4**) of receiving, at the mobile device from the first financial institution the account information, block **1304** (FIG. **13**) of receiving, from the first financial institution, an account balance of a demand deposit account of the consumer maintained by the first financial institution, and/or block **2303** (FIG. **23**) of receiving, at the mobile device, an authorization from a user of the mobile device for a transaction having a transaction amount while the user is at a point-of-sale terminal of a first entity.

[0375] In a number of embodiments, communication system **124** can at least partially perform block **402** (FIG. **4**) of receiving at the mobile device first information from a point-of-sale terminal, block **403** (FIG. **4**) of sending, from the mobile device to the first financial institution, a preliminary request for account information, block **404** (FIG. **4**) of receiving, at the mobile device from the first financial institution, the account information, block **405** (FIG. **4**) of sending, from the mobile device to the first financial institution, a first request to pay the merchant for the payment amount from the first account for one or more items to be purchased from the merchant by the consumer, block **406** (FIG. **4**) of receiving, at the mobile device from the first financial institution, an additional authentication request to perform an additional identity authentication of the consumer using the mobile device, block **408** (FIG. **4**) of sending, from the mobile device to the first financial institution, a response to the additional authentication request, block **1001** (FIG. **10**) of receiving, at a mobile device being used by a consumer, a transaction code from a point-of-sale terminal at a store of a merchant, block **1003** (FIG. **10**) of receiving from the consumer an approval for the transaction, block **1004** (FIG. **10**) of sending, from the mobile device, a request to pay the merchant for the payment amount from a first account of the consumer maintained by a first financial institution, block **1302** (FIG. **13**) of receiving, at the mobile device, first information from a point-of-sale terminal at a store of a merchant, block **1303** (FIG. **13**) of sending, from the mobile device, a request to pay the merchant for the payment amount from one or more first accounts of the consumer maintained by a first financial institution, block **1305** (FIG. **13**) of displaying the account balance of the demand deposit account to the consumer, block **2301** (FIG. **23**) of receiving a preauthorization code at a mobile device while the mobile device is in data communication with a mobile wallet provider, block **2304** (FIG. **23**) of determining that the mobile device is unable to communicate with the mobile wallet provider, block **2306** (FIG. **23**) of providing a transaction code from the mobile device to the point-of-sale terminal to cause the first entity to send the transaction amount and the preauthorization code to a transaction system, and to cause the transaction system to send an approval for the transaction in real-time while the user remains at the point-of-sale terminal of the first entity, block **2601** (FIG. **26**) of receiving, at a mobile device from a point-of-sale terminal of a first entity, an identifier of the first entity, a transaction amount for a transaction, and a transaction identifier for the transaction, block **2602** (FIG. **26**) of receiving an authorization from the user of the mobile device for the transaction while the user is at the point-of-sale terminal, block **2603** (FIG. **26**) of determining that the mobile device is unable to communicate with the mobile wallet provider, and/or block **2605** (FIG. **26**) of sending the encrypted transaction code from the mobile device to the point-of-sale terminal to cause the encrypted transaction code to be sent through a proxy communication channel extending from the point-of-sale terminal, through a transaction system, to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user, to cause the first financial institution to retrieve from the transaction system an account identifier of a second account of the first entity maintained by a second financial institution based on the identifier of the first entity and send to the transaction system payment information regarding a payment to be made to the second account from the first account for the transaction, to cause the payment information to be routed through the transaction system to the second financial institution, and to cause the point-of-sale

terminal to receive a notification of the payment for the transaction in real-time while the user remains at the point-of-sale terminal.

[0376] In several embodiments, security system **125** can at least partially perform block **1002** (FIG. **10**) of verifying the digital signature for the transaction code.

[0377] In a number of embodiments, loan system **126** can at least partially perform block **1305** (FIG. **13**) of displaying the account balance of the demand deposit account to the consumer, block **1307** (FIG. **13**) of presenting to the consumer an option to at least partially fund the transaction using the at least one non-demand deposit account, and/or block **1308** (FIG. **13**) of receiving from the consumer a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account.

[0378] In a number of embodiments, stand-in credit system **127** can at least partially perform block **2301** (FIG. **23**) of receiving a preauthorization code at a mobile device while the mobile device is in data communication with a mobile wallet provider, block **2302** (FIG. **23**) of storing the preauthorization code in the mobile device, and/or block **2305** (FIG. **23**) of verifying that the transaction amount is less than or equal to the preauthorization amount.

[0379] In many embodiments, proxy communication system **128** can at least partially perform block **2604** (FIG. **26**) of generating an encrypted transaction code.

[0380] Continuing with FIG. **1**, as described above, financial institution **130** can include one or more systems, such as communication system **132**, authorization system **133**, account system **134**, loan system **135**, preauthorization system **136**, and/or proxy communication system **137**. Financial institution **130** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Financial institution **130** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of financial institution **130** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0381] In many embodiments, communication system **132** can at least partially perform block **201** (FIG. **2**) of receiving, at a first financial institution from a mobile device, a preliminary request for account information, block **202** (FIG. **2**) of sending, from the first financial institution to the mobile device, the account information, block **203** (FIG. **2**) of receiving, at a first financial institution from a mobile device of a consumer, a first request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution, block **206** (FIG. **2**) of sending, from the first financial institution to the first system, a second request to determine the second information, block **207** (FIG. **2**) of receiving, at the first financial institution from the first system, the third information, block **212** (FIG. **2**) of sending, from the first financial institution to the first system, payment information regarding a payment to be made to the second account from the first account, block **1101** (FIG. **11**) of receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from a first account of the consumer maintained by the first financial institution, block **1102** (FIG. **11**) of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant public identifier, block **1103** (FIG. **11**) of sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the first account, block **1401** (FIG. **14**) of receiving, at a first financial institution from a mobile device being used by a consumer, a request to pay a merchant for a payment amount from one or more first accounts of the consumer maintained by the first financial institution, block **1402** (FIG. **14**) of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant identifier, block **1403** (FIG. **14**) of sending, from the first financial institution to the transaction system, payment information regarding a payment to be made to the second account from the one

or more first accounts, block **1404** (FIG. 14) of sending, to the mobile device, an account balance of a demand deposit account of the consumer maintained by the first financial institution, block **1406** (FIG. 14) of sending, to the mobile device, an option to at least partially fund the transaction using the at least one non-demand deposit account, and/or block **1407** (FIG. 14) of receiving, from the mobile device, a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account.

[0382] In some embodiments, authorization system **133** can at least partially perform block **208** (FIG. 2) of authorizing, at the first financial institution, a payment from the first account to the second account, and/or block **209** (FIG. 2) of authenticating an identity of the consumer that used the mobile device to send the first request to pay the merchant from the first account.

[0383] In a number of embodiments, account system **134** can at least partially perform block **201** (FIG. 2) of receiving, at a first financial institution from a mobile device, a preliminary request for account information, block **202** (FIG. 2) of sending, from the first financial institution to the mobile device, the account information, block **204** (FIG. 2) of determining, at the first financial institution, second information, block **205** (FIG. 2) of determining, at the first financial institution, the second information at least partially based on the merchant identifier and the third information, block **209** (FIG. 2) of authenticating an identity of the consumer that used the mobile device to send the first request to pay the merchant from the first account, block **210** (FIG. 2) of determining a current status of the first account, block **211** (FIG. 2) of determining available funds of the first account, block **1102** (FIG. 11) of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant public identifier, block **1402** (FIG. 14) of retrieving, at the first financial institution from a transaction system, an account identifier for a second account of the merchant maintained by a second financial institution based on the merchant identifier, and/or block **1404** (FIG. 14) of sending, to the mobile device, an account balance of a demand deposit account of the consumer maintained by the first financial institution.

[0384] In some embodiments, loan system **135** can at least partially perform block **1405** (FIG. 14) of determining that the account balance of the demand deposit account is less than the payment amount of the transaction, block **1406** (FIG. 14) of sending, to the mobile device, an option to at least partially fund the transaction using the at least one non-demand deposit account, block **1407** (FIG. 14) of receiving, from the mobile device, a selection to at least partially fund the payment amount of the transaction using the at least one non-demand deposit account, and/or creating the loan account.

[0385] In a number of embodiments, preauthorization system **136** can at least partially perform generating the preauthorization code.

[0386] In many embodiments, proxy communication system **137** can at least partially perform transmitting the encrypted transaction code along the proxy communication channel.

[0387] Continuing with FIG. 1, as described above, transaction system **140** can include one or more systems, such as communication system **143**, account system **144**, transaction system **145**, security system **146**, preauthorization system **147**, and/or proxy communication system **148**.

Transaction system **140** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Transaction system **140** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of transaction system **140** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0388] In many embodiments, communication system **143** can at least partially perform block **301** (FIG. 3) of receiving, at a first system from a first financial institution, a request, block **303** (FIG. 3) of sending the first information from the first system to the first financial institution, block **304** (FIG. 3) of receiving, at the first system from the first financial institution, payment information

regarding a payment to be made to the second account from the first account to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount, block **306** (FIG. 3) of sending, from the first system to the second financial institution, the payment information such that the second financial institution, upon receiving the payment information, notifies the merchant to satisfy an expectation of the merchant for payment from the consumer, block **1201** (FIG. 12) of receiving, at a transaction system from a first entity, a request including a merchant public identifier associated with a merchant, block **1203** (FIG. 12) of sending the account identifier to the first financial institution, block **1204** (FIG. 12) of receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the first account, block **1205** (FIG. 12) of sending, from the transaction system to the second financial institution, the payment information, block **1501** (FIG. 15) of receiving, at a transaction system from a first entity, a request including a merchant identifier associated with a merchant, block **1503** (FIG. 15) of sending the account identifier from the transaction system to the first financial institution, block **1504** (FIG. 15) of receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the one or more first accounts, block **1505** (FIG. 15) of sending, from the transaction system to the second financial institution, the payment information, such that a point-of-sale terminal at the store of the merchant receives a notification of payment for the transaction in real-time while the consumer remains at the store of the merchant, block **2401** (FIG. 24) of receiving a transaction amount and a preauthorization code from a first entity, block **2403** (FIG. 24) of sending an approval for the transaction to the first entity in real-time while the user remains at the point-of-sale terminal of the first entity, block **2703** (FIG. 27) of receiving, from the first financial institution, a request including the identifier of the first entity, block **2705** (FIG. 27) of sending the account identifier of the second account to the first financial institution, block **2706** (FIG. 27) of receiving, from the first financial institution, payment information regarding a payment to be made to the second account from the first account for the transaction, and/or block **2707** (FIG. 27) of sending the payment information to the second financial institution, to cause the point-of-sale terminal to receive a notification in real-time while the user remains at the point-of-sale terminal.

[0389] In some embodiments, account system **144** can at least partially perform block **302** (FIG. 3) of determining, at the first system, using the merchant account database, first information, block **1202** (FIG. 12) of determining, at the transaction system, an account identifier of the second account based on the merchant public identifier using a merchant account database, block **1502** (FIG. 15) of determining, at the transaction system, an account identifier of the second account of the merchant maintained by a second financial institution using a merchant account database, and/or block **2704** (FIG. 27) of determining an account identifier of a second account of the first entity maintained by the second financial institution based on the identifier of the first entity.

[0390] In a number of embodiments, transaction system **145** can at least partially perform block **305** (FIG. 3) of storing the payment information in the transaction database, block **1204** (FIG. 12) of receiving, at the transaction system from the first financial institution, payment information regarding a payment to be made to the second account from the first account, block **1205** (FIG. 12) of sending, from the transaction system to the second financial institution, the payment information, block **2706** (FIG. 27) of receiving, from the first financial institution, payment information regarding a payment to be made to the second account from the first account for the transaction, and/or block **2707** (FIG. 27) of sending the payment information to the second financial institution, to cause the point-of-sale terminal to receive a notification in real-time while the user remains at the point-of-sale terminal.

[0391] In some embodiments, account system **146** can at least partially perform generating the transaction code and/or merchant security transaction code.

[0392] In a number of embodiments, preauthorization system **147** can at least partially perform

block **2402** (FIG. **24**) of verifying the preauthorization code using the digital signature of the preauthorization code, block **2701** (FIG. **27**) of receiving, at a transaction system being situated along a proxy communication channel extending from a point-of-sale terminal of a first entity to a mobile wallet provider, an encrypted transaction code, and/or block **2702** (FIG. **27**) of sending the encrypted transaction code through the proxy communication channel to the mobile wallet provider, to cause the mobile wallet provider to decrypt the encrypted transaction code and verify the preauthorization from the user.

[0393] In many embodiments, proxy communication system **148** can at least partially perform transmitting the encrypted transaction code along the proxy communication channel.

[0394] Continuing with FIG. **1**, as described above, financial institution **150** can include one or more systems, such as communication system **152**, account system **153**, and/or proxy communication system **154**. Financial institution **150** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Financial institution **150** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of financial institution **150** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0395] In many embodiments, communication system **152** can at least partially perform block **601** (FIG. **6**) of receiving, at a second financial institution from a first system, payment information regarding a payment to be made to a second account of a merchant maintained by the second financial institution from a first account of a consumer maintained by a first financial institution to pay the merchant for one or more items to be purchased from the merchant by the consumer for the payment amount, and/or block **603** (FIG. **6**) of sending, from the second financial institution to the point-of-sale terminal, a notification to satisfy an expectation of the merchant for payment from the consumer.

[0396] In various embodiments, account system **153** can at least partially perform block **602** (FIG. **6**) of crediting the second account with the payment amount.

[0397] In many embodiments, proxy communication system **154** can at least partially perform transmitting the encrypted transaction code along the proxy communication channel.

[0398] Continuing with FIG. **1**, as described above, mobile wallet provider **160** can include one or more systems, such as proxy communication system **161**. Mobile wallet provider **160** and the systems therein are merely exemplary and are not limited to the embodiments presented herein. Mobile wallet provider **160** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements, systems, or modules of mobile wallet provider can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements, systems, or modules.

[0399] In many embodiments, proxy communication system **161** can at least partially perform decrypting the encrypted transaction code, and/or verifying the preauthorization from the user.

[0400] Turning ahead in the drawings, FIG. **7** illustrates a computer **700**, all of which or a portion of which can be suitable for implementing an embodiment of at least a portion of point-of-sale terminal **110** (FIG. **1**), mobile device **120** (FIG. **1**), financial institution **130** (FIG. **1**), transaction system **140** (FIG. **1**), financial institution **150** (FIG. **1**), and/or the techniques described in method **200** (FIG. **2**), method **300** (FIG. **3**), method **400** (FIG. **4**), method **500** (FIG. **5**), method **600** (FIG. **6**), method **900** (FIG. **9**), method **1000** (FIG. **10**), method **1100** (FIG. **11**), method **1200** (FIG. **12**), method **1300** (FIG. **13**), method **1400** (FIG. **14**), method **1500** (FIG. **15**), and/or method **1600** (FIG. **16**). Computer **700** includes a chassis **702** containing one or more circuit boards (not shown), a USB (universal serial bus) port **712**, a Compact Disc Read-Only Memory (CD-ROM) and/or Digital Video Disc (DVD) drive **716**, and a hard drive **714**. A representative block diagram of the elements included on the circuit boards inside chassis **702** is shown in FIG. **8**. A central processing

unit (CPU) **810** in FIG. **8** is coupled to a system bus **814** in FIG. **8**. In various embodiments, the architecture of CPU **810** can be compliant with any of a variety of commercially distributed architecture families.

[0401] Continuing with FIG. **8**, system bus **814** also is coupled to memory **808** that includes both read only memory (ROM) and random access memory (RAM). Non-volatile portions of memory storage unit **808** or the ROM can be encoded with a boot code sequence suitable for restoring computer **700** (FIG. **7**) to a functional state after a system reset. In addition, memory **808** can include microcode such as a Basic Input-Output System (BIOS). In some examples, the one or more memory storage units of the various embodiments disclosed herein can comprise memory storage unit **808**, a USB-equipped electronic device, such as, an external memory storage unit (not shown) coupled to universal serial bus (USB) port **712** (FIGS. **7-8**), hard drive **714** (FIGS. **7-8**), and/or CD-ROM or DVD drive **716** (FIGS. **7-8**). In the same or different examples, the one or more memory storage units of the various embodiments disclosed herein can comprise an operating system, which can be a software program that manages the hardware and software resources of a computer and/or a computer network. The operating system can perform basic tasks such as, for example, controlling and allocating memory, prioritizing the processing of instructions, controlling input and output devices, facilitating networking, and managing files. Some examples of common operating systems can comprise Microsoft® Windows® operating system (OS), Mac® OS, UNIX® OS, and Linux® OS.

[0402] As used herein, “processor” and/or “processing module” means any type of computational circuit, such as but not limited to a microprocessor, a microcontroller, a controller, a complex instruction set computing (CISC) microprocessor, a reduced instruction set computing (RISC) microprocessor, a very long instruction word (VLIW) microprocessor, a graphics processor, a digital signal processor, or any other type of processor or processing circuit capable of performing the desired functions. In some examples, the one or more processors of the various embodiments disclosed herein can comprise CPU **810**.

[0403] In the depicted embodiment of FIG. **8**, various I/O devices such as a disk controller **804**, a graphics adapter **824**, a video controller **802**, a keyboard adapter **826**, a mouse adapter **806**, a network adapter **820**, and other I/O devices **822** can be coupled to system bus **814**. Keyboard adapter **826** and mouse adapter **806** are coupled to a keyboard **704** (FIGS. **7** and **8**) and a mouse **710** (FIGS. **7** and **8**), respectively, of computer **700** (FIG. **7**). While graphics adapter **824** and video controller **802** are indicated as distinct units in FIG. **8**, video controller **802** can be integrated into graphics adapter **824**, or vice versa in other embodiments. Video controller **802** is suitable for refreshing a monitor **706** (FIGS. **7** and **8**) to display images on a screen **708** (FIG. **7**) of computer **700** (FIG. **7**). Disk controller **804** can control hard drive **714** (FIGS. **7** and **8**), USB port **712** (FIGS. **7** and **8**), and CD-ROM or DVD drive **716** (FIGS. **7** and **8**). In other embodiments, distinct units can be used to control each of these devices separately.

[0404] In some embodiments, network adapter **820** can comprise and/or be implemented as a WNIC (wireless network interface controller) card (not shown) plugged or coupled to an expansion port (not shown) in computer system **700** (FIG. **7**). In other embodiments, the WNIC card can be a wireless network card built into computer system **700** (FIG. **7**). A wireless network adapter can be built into computer system **700** (FIG. **7**) by having wireless communication capabilities integrated into the motherboard chipset (not shown), or implemented via one or more dedicated wireless communication chips (not shown), connected through a PCI (peripheral component interconnector) or a PCI express bus of computer system **700** (FIG. **7**) or USB port **712** (FIG. **7**). In other embodiments, network adapter **820** can comprise and/or be implemented as a wired network interface controller card (not shown).

[0405] Although many other components of computer **700** (FIG. **7**) are not shown, such components and their interconnection are well known to those of ordinary skill in the art. Accordingly, further details concerning the construction and composition of computer **700** and the

circuit boards inside chassis **702** (FIG. 7) need not be discussed herein.

[0406] When computer **700** in FIG. 7 is running, program instructions stored on a USB drive in USB port **712**, on a CD-ROM or DVD in CD-ROM and/or DVD drive **716**, on hard drive **714**, or in memory **808** (FIG. 8) are executed by CPU **810** (FIG. 8). A portion of the program instructions, stored on these devices, can be suitable for carrying out all or at least part of the techniques described herein. In various embodiments, computer **700** can be reprogrammed with one or more modules, applications, and/or databases to convert a general purpose computer to a special purpose computer.

[0407] Although computer system **700** is illustrated as a desktop computer in FIG. 7, there can be examples where computer system **700** may take a different form factor while still having functional elements similar to those described for computer system **700**. In some embodiments, computer system **700** may comprise a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. Typically, a cluster or collection of servers can be used when the demand on computer system **700** exceeds the reasonable capability of a single server or computer. In certain embodiments, computer system **700** may comprise a portable computer, such as a laptop computer. In certain other embodiments, computer system **700** may comprise a mobile device, such as a smartphone. For example, mobile device **120** (FIG. 1) can be a mobile device, such as a smartphone. In certain additional embodiments, computer system **700** may comprise an embedded system.

[0408] Although secure real-time payment transactions have been described with reference to specific embodiments, it will be understood by those skilled in the art that various changes may be made without departing from the spirit or scope of the disclosure. Accordingly, the disclosure of embodiments is intended to be illustrative of the scope of the disclosure and is not intended to be limiting. It is intended that the scope of the disclosure shall be limited only to the extent required by the appended claims. For example, to one of ordinary skill in the art, it will be readily apparent that any element of FIGS. 1-28 may be modified, and that the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments. For example, one or more of the procedures, processes, or activities of FIGS. 2-6, 9-14, and/or 23-28 may include different procedures, processes, and/or activities and be performed by many different modules, in many different orders, and/or one or more of the procedures, processes, or activities of FIGS. 2-6, 9-14, and/or 23-28 may include one or more of the procedures, processes, or activities of another different one of FIGS. 2-6, 9-14, and/or 23-28.

[0409] Replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are stated in such claim.

[0410] Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

Claims

1. A system comprising: one or more processors; a merchant account database comprising a plurality of merchant identifiers being associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers; a transaction database; and one or more non-transitory computer-readable media storing computing instructions that, when

executed by the one or more processors, cause the one or more processors to perform operations comprising: receiving, at the system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant of the plurality of merchants by the consumer for a payment amount, a request comprising a merchant identifier of the plurality of merchant identifiers associated with the merchant, the mobile device obtaining the merchant identifier using a data communication protocol, the system being in data communication with a consumer financial institution and a merchant financial institution, and the system being maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution; determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant at the merchant financial institution, the merchant account identifier being associated with the merchant identifier in the merchant account database, and the plurality of account identifiers comprising the merchant account identifier; sending the first information from the system to the consumer financial institution; receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items, the payment information comprising a transaction identifier, the merchant account identifier of the merchant account, and the payment amount; and sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant, wherein: the merchant does not receive an account number of the consumer account of the consumer; and the consumer does not receive an account number of the merchant account of the merchant.

2. The system of claim 1, wherein: the first information further comprises a name of the merchant.

3. The system of claim 1, wherein: the merchant identifier uniquely corresponds to the merchant.

4. The system of claim 1, wherein: the one or more items to be purchased comprise at least one of one or more products or one or more services.

5. The system of claim 1, wherein: the payment information further comprises a set of personally identifiable information of the consumer.

6. The system of claim 5, wherein: the set of personally identifiable information is at least partially based on privacy instructions sent by the consumer to the consumer financial institution.

7. The system of claim 1, wherein: the mobile device of the consumer is configured to receive consumer account authentication information to facilitate processing the payment.

8. A computer-implemented method comprising: receiving, at a system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant by the consumer for a payment amount, a request comprising a merchant identifier associated with the merchant, the system comprising a merchant account database and a transaction database, the merchant account database comprising a plurality of merchant identifiers associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers, the plurality of merchants comprising the merchant, the plurality of merchant identifiers comprising the merchant identifier, the mobile device obtaining the merchant identifier using a data communication protocol, the system being in data communication with a consumer financial institution and a merchant financial institution, and the system being maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution; determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant maintained by the merchant financial institution, the merchant account identifier being associated with the merchant identifier in the merchant account database, and the plurality of account identifiers comprising the merchant account identifier; sending the first information from the system to the consumer financial institution; receiving in real-time over a network, at the system and from the consumer

financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items, the payment information comprising a transaction identifier, the merchant account identifier of the merchant account, and the payment amount; and sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant, wherein: the merchant does not receive an account number of the consumer account of the consumer; and the consumer does not receive an account number of the merchant account of the merchant.

9. The computer-implemented method of claim 8, wherein: the first information further comprises a name of the merchant.

10. The computer-implemented method of claim 8, wherein: the merchant identifier uniquely corresponds to the merchant.

11. The computer-implemented method of claim 8, wherein: the one or more items to be purchased comprise at least one of one or more products or one or more services.

12. The computer-implemented method of claim 8, wherein: the payment information further comprises a set of personally identifiable information of the consumer.

13. The computer-implemented method of claim 12, wherein: the set of personally identifiable information is at least partially based on privacy instructions sent by the consumer to the consumer financial institution.

14. The computer-implemented method of claim 8, wherein: the mobile device of the consumer is configured to receive consumer account authentication information to facilitate processing the payment.

15. One or more non-transitory computer-readable media comprising computer instructions that, when executed by one or more processors, perform operations comprising: receiving, at a system and from a mobile device being used by a consumer to pay for one or more items to be purchased from a merchant by the consumer for a payment amount, a request comprising a merchant identifier associated with the merchant, the system comprising a merchant account database and a transaction database, the merchant account database comprising a plurality of merchant identifiers associated with a plurality of merchants, a plurality of account identifiers associated with the plurality of merchants, and a mapping associating the plurality of merchant identifiers with the plurality of account identifiers, the plurality of merchants comprising the merchant, the plurality of merchant identifiers comprising the merchant identifier, the mobile device obtaining the merchant identifier using a data communication protocol, the system being in data communication with a consumer financial institution and a merchant financial institution, and the system being maintained by an entity that is different from the merchant, the consumer financial institution, and the merchant financial institution; determining, at the system and using the merchant account database, first information comprising a merchant account identifier for a merchant account of the merchant maintained by the merchant financial institution, the merchant account identifier being associated with the merchant identifier in the merchant account database, and the plurality of account identifiers comprising the merchant account identifier; sending the first information from the system to the consumer financial institution; receiving in real-time over a network, at the system and from the consumer financial institution, payment information regarding a payment to the merchant account from a consumer account of the consumer at the consumer financial institution to pay the merchant the payment amount for the one or more items, the payment information comprising a transaction identifier, the merchant account identifier of the merchant account, and the payment amount; and sending in real-time over the network, from the system to the merchant, a notification of the payment from the consumer to the merchant, wherein: the merchant does not receive an account number of the consumer account of the consumer; and the consumer does not receive an account number of the merchant account of the merchant.

16. The one or more non-transitory computer-readable media of claim 15, wherein: the first

information further comprises a name of the merchant.

17. The one or more non-transitory computer-readable media of claim 15, wherein: the merchant identifier uniquely corresponds to the merchant.

18. The one or more non-transitory computer-readable media of claim 15, wherein: the one or more items to be purchased comprise at least one of one or more products or one or more services.

19. The one or more non-transitory computer-readable media of claim 15, wherein: the payment information further comprises a set of personally identifiable information of the consumer; and the set of personally identifiable information is at least partially based on privacy instructions sent by the consumer to the consumer financial institution.

20. The one or more non-transitory computer-readable media of claim 15, wherein: the mobile device of the consumer is configured to receive consumer account authentication information to facilitate processing the payment.
