



US 20250280280A1

(19) **United States**

(12) **Patent Application Publication**
Williams et al.

(10) **Pub. No.: US 2025/0280280 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **PAIRABLE DEVICES AND SYSTEMS AND METHODS FOR PROVIDING ASSISTED PAIRING OF DEVICES TO PARTICULAR LOCATIONS**

(71) Applicant: **Hill-Rom Services, Inc.**, Batesville, IN (US)

(72) Inventors: **Jason M. Williams**, Cary, NC (US);
Richard Schuman, Cary, NC (US)

(73) Assignee: **Hill-Rom Services, Inc.**, Batesville, IN (US)

(21) Appl. No.: **19/212,076**

(22) Filed: **May 19, 2025**

Related U.S. Application Data

(63) Continuation of application No. 17/551,683, filed on Dec. 15, 2021, now Pat. No. 12,342,413.

(60) Provisional application No. 63/127,629, filed on Dec. 18, 2020.

Publication Classification

(51) **Int. Cl.**
H04W 8/00 (2009.01)
G16H 40/63 (2018.01)
G16H 40/67 (2018.01)

H04W 76/14 (2018.01)

H04W 76/30 (2018.01)


(52) **U.S. Cl.**

CPC **H04W 8/005** (2013.01); **G16H 40/63** (2018.01); **G16H 40/67** (2018.01); **H04W 76/14** (2018.02); **H04W 76/30** (2018.02)

(57)

ABSTRACT

Systems and methods include a medical device that scans for wireless broadcasts based upon received input or satisfying a scanning criterion. The medical device, based upon the scan, identifies data wirelessly broadcast from a control device. The medical device outputs information to the interface identifying the control device. The medical device receives input from the interface selecting the control device. The medical device receives a command from the control device. The medical device physically interacts with a user based upon the command received from the control device. The medical device sends wireless confirmation of pairing to the control device. The medical device subsequently sends wireless confirmation of unpairing to the control device. The medical device performs a scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.







FIG. 1A






FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

**PAIRABLE DEVICES AND SYSTEMS AND
METHODS FOR PROVIDING ASSISTED
PAIRING OF DEVICES TO PARTICULAR
LOCATIONS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] This application is a continuation of U.S. patent application Ser. No. 17/551,683, filed Dec. 15, 2021, entitled, “PAIRABLE DEVICES AND SYSTEMS AND METHODS FOR PROVIDING ASSISTED PAIRING OF DEVICES TO PARTICULAR LOCATIONS,” which claims priority to U.S. Provisional Patent Application Ser. No. 63/127,629, filed Dec. 18, 2020, entitled, “PAIRABLE DEVICES AND SYSTEMS AND METHODS FOR PROVIDING ASSISTED PAIRING OF DEVICES TO PARTICULAR LOCATIONS,” the contents of which each are incorporated herein by reference in their respective entireties.

BACKGROUND

Field

[0002] The present disclosure generally relates to systems and/or methods for pairing a medical device and a control device, and more specifically, to systems and/or methods for pairing a medical device and a control device using wireless links.

Technical Background

[0003] A medical facility may include a plurality of rooms where each room may include one or more medical devices. Each medical device (MD) may be permanently fixed within a room or movable between the plurality of rooms. In addition, each medical device may be wirelessly controlled by a respective control device (CD) and the control device may be permanently fixed within a room or movable between the plurality of rooms. Accordingly, given the portable nature of medical devices and/or control devices, as well as the use of such devices with a plurality of subjects, systems and/or methods are desirable to ensure that a particular medical device is in wireless communication with a particular control device.

[0004] Wireless radios typically can transmit in excess of many meters. In a hospital environment, where there may be a wall unit or other device used to communicate with devices in a room, this could mean a plurality of devices could appear in a list of devices to pair with in a typical wireless pairing scenario, including devices in neighboring rooms or areas. A caregiver may not be able to easily select which device is in their room. For example, if a hospital bed were to be paired with the incorrect wall unit, the nurse call and bed data would be associated with the incorrect bed/occupant. This could delay care or result in improper dosage of medication (due to incorrect subject weight). Thus, the pairing process benefits from being as automated as possible and easier for the caregiver to select the proper room device.

SUMMARY

[0005] In one aspect, a pairable medical device may include a communication system configured to communicate via a communication channel, a processor, a display device configured to display an interface, and a memory

storing program instructions. The program instructions, when executed by the processor, cause the processor to scan for wireless broadcasts based upon received input or satisfying a scanning criterion. The program instructions also cause the process to receive, based upon the scan, identifying data wirelessly broadcast from a control device. The program instructions further cause the processor to output information to the interface identifying the control device. The program instructions further cause the processor to receive input from the interface selecting the control device. The program instructions further cause the processor to receive a command from the control device. The program instructions further cause the processor to physically interact with a user based upon the command received from the control device. The program instructions further cause the processor to send wireless confirmation of pairing to the control device and subsequently send wireless confirmation of unpairing to the control device. The program instructions further cause the processor to perform a scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.

[0006] In such an aspect, according to some aspects, the pairable medical device comprises a medical bed, a pump, a rail-mounted lift, or a computer. In an additional aspect, the scanning criterion is based upon the medical device being plugged in for power. In another aspect, the scanning criterion is based upon the medical device having brakes engaged. In yet another aspect, the pairable control device further receives identifying data wirelessly broadcast from a plurality of control devices. In a further aspect, the identifying data received from the plurality of control devices is presented on the interface according to a filtering criterion and a sorting criterion. In an additional aspect, the filtering criterion comprises a device manufacturer, a device type, or a device model. In yet another aspect, the sorting criterion comprises respective signal strengths of each wireless broadcast or location information within the identifying data.

[0007] In a further aspect, a pairable control device may comprise a communication system configured to communicate via a communication channel, a processor, and a memory storing program instructions. The program instructions, when executed by the processor, cause the processor to wirelessly broadcast self-identifying data based upon being unpaired. The program instructions further cause the processor to receive pairing confirmation from a medical device. The program instructions further cause the processor to stop the wireless broadcast in response to the received pairing confirmation. The program instructions additionally cause the processor to receive a subsequent unpairing confirmation from the medical device. The program instructions further cause the processor to resume broadcasting the self-identifying data in response to receiving the unpairing confirmation.

[0008] In such another aspect, according to some aspects, the self-identifying data comprises a first data field comprising a device name and a second data field comprises manufacturer data. In other aspects, the second manufacturer data further comprises an identifier unique to a manufacturer, followed by between 1 to 31 octets of data.

[0009] In a further aspect, a system for assisted pairing of devices may include a pairable control device that may include a first communication system configured to communicate via a communication channel, a first processor, and

a memory storing first program instructions. The memory storing program instructions, when executed by the first processor, cause the first processor to wirelessly broadcast self-identifying data based upon being unpaired. The program instructions further cause the first processor to receive pairing confirmation from a medical device. The program instructions further cause the first processor to stop the wireless broadcast in response to the received pairing confirmation. The program instructions further cause the first processor to receive a subsequent unpairing confirmation from the medical device. The program instructions further cause the first processor to resume broadcasting the self-identifying data in response to receiving the unpairing confirmation. The medical device may include a display device configured to display an interface a second communication system configured to communicate via the communication channel. The medical device may be additionally configured to scan for wireless broadcasts based upon received input or satisfying a scanning criterion. The medical device may be further configured to receive, based upon the scan, identifying data wirelessly broadcast from a control device. The medical device may be further configured to output information to the interface identifying the control device. The medical device may be further configured to receive input from the interface selecting the control device. The medical device may be further configured to send wireless confirmation of pairing to the control device. The medical device may be further configured to subsequently send wireless confirmation of unpairing to the control device. The medical device may be further configured to perform a scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.

[0010] In such a further aspect, according to some aspects, self-identifying data comprises a first data field comprising a device name and a second data field comprises manufacturer data comprises an identifier unique to a manufacturer, followed by between 1 to 31 octets of data. In other aspects, the scanning criterion is based upon the medical device being plugged in or the medical device having brakes engaged. Some additional aspects include receiving identifying data wirelessly broadcast from a plurality of control devices and presenting the received identifying data on the interface according to a filtering criterion and a sorting criterion. The filtering criterion may include a device manufacturer, a device type, or a device model. The sorting criterion may also include respective signal strengths of each wireless broadcast or location information within the identifying data.

[0011] In yet another aspect, a method for assisted medical device wireless pairing with a control device may include scanning, at the medical device, for wireless broadcasts based upon received input or satisfying a scanning criterion. The method may further include receiving, based upon the scan, identifying data wirelessly broadcast from the control device. The method may further include outputting, to an interface at the medical device, information identifying the control device. The method may further include receiving input from the interface selecting the control device. The method may further include sending wireless confirmation of pairing to the control device. The method may further include receiving a command from the control device. The method may further include physically interacting with a user based upon the command received from the control

device. The method may further include subsequently sending wireless confirmation of unpairing to the control device. The method may further include performing an updated scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.

[0012] In such still a further aspect, according to some aspects, the pairable medical device comprises a medical bed, a pump, a rail-mounted lift, or a computer. In another such aspect, the scanning criterion may be based upon the medical device being plugged in. In other such aspects, the scanning criterion may be based upon the medical device having brakes engaged. Still other such aspects may include receiving identifying data wirelessly broadcast from a plurality of control devices. In other such aspects, the identifying data received from the plurality of control devices may be presented on the interface according to a filtering criterion and a sorting criterion. Additional such aspects may include a filtering criterion comprising a device manufacturer, a device type, or a device model. In other such aspects, the sorting criterion may comprise respective signal strengths of each wireless broadcast or location information within the identifying data.

[0013] In still a further aspect, a method for assisted control device wireless pairing with a medical device may include wirelessly broadcasting self-identifying data from the control device based upon being unpaired. The method may further include receiving pairing confirmation from the medical device. The method may further include stopping the wireless broadcast in response to the received pairing confirmation. The method may further include receiving a subsequent unpairing confirmation from the medical device. The method may further include resuming broadcasting of the self-identifying data in response to receiving the unpairing confirmation.

[0014] In such still a further aspect, according to some aspects, the self-identifying data may comprise a first data field comprising a device name and a second data field comprises manufacturer data. Still other such aspects may include the second manufacturer data further comprising an identifier unique to a manufacturer, followed by between 1 to 31 octets of data.

[0015] In still a further aspect, a method for assisted wireless pairing of a medical device and a control device may include wirelessly broadcasting, from the control device, self-identifying data based upon being unpaired. The method may further include scanning, at the medical device, for wireless broadcasts based upon received input or satisfying a scanning criterion. The method may further include receiving at the medical device, based upon the scan, identifying data wirelessly broadcast from the control device. The method may further include outputting, from the medical device to the interface, information identifying the control device. The method may further include receiving input from the interface selecting the control device. The method may further include sending wireless confirmation of pairing from the medical device to the control device.

[0016] The method may further include receiving, at the control device, pairing confirmation from the medical device. The method may further include stopping the wireless broadcast from the control device in response to the received pairing confirmation. The method may further include subsequently sending wireless confirmation of unpairing from the medical device to the control device. The method may further include receiving at the control device

a subsequent unpairing confirmation from the medical device. The method may further include resuming broadcasting of the self-identifying data at the control device in response to receiving the unpairing confirmation from the medical device. The method may further include performing an updated scan for wireless broadcasts at the medical device in response to the unpairing, based upon received input or satisfying the scanning criterion.

[0017] In such yet a further aspect, according to some aspects, the self-identifying data may include a first data field comprising a device name and a second data field comprises manufacturer data comprises an identifier unique to a manufacturer, followed by between 1 to 31 octets of data. The scanning criterion may be based upon the medical device being plugged in or the medical device having brakes engaged. The method may further include receiving identifying data wirelessly broadcast from a plurality of control devices and presenting the received identifying data on the interface according to a filtering criterion and a sorting criterion. In other such aspects, the filtering criterion may include a device manufacturer, a device type, or a device model. In yet another aspect, the sorting criterion may include respective signal strengths of each wireless broadcast or location information within the identifying data.

[0018] Additional features and advantages of the embodiments described herein will be set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the embodiments described herein, including the detailed description which follows, the claims, as well as the appended drawings.

[0019] It is to be understood that both the foregoing general description and the following detailed description describe various embodiments and are intended to provide an overview or framework for understanding the nature and character of the claimed subject matter. The accompanying drawings are included to provide a further understanding of the various embodiments, and are incorporated into and constitute a part of this specification. The drawings illustrate the various embodiments described herein, and together with the description serve to explain the principles and operations of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1A depicts a block diagram illustrating control devices wirelessly advertising to a medical device and a plurality of medical devices wirelessly paired to other control devices that are distributed amongst a plurality of rooms of a medical facility, according to one or more embodiments shown and described herein;

[0021] FIG. 1B depicts a block diagram illustrating a control device wirelessly advertising to medical devices and a plurality of medical devices wirelessly paired to other control devices that are distributed amongst the plurality of rooms of the medical facility, according to one or more embodiments shown and described herein;

[0022] FIG. 1C depicts an exemplary medical device graphical interface illustrating a plurality of wireless control devices selectable according to signal strength and/or room location within the medical facility, according to one or more embodiments shown and described herein;

[0023] FIG. 2A depicts illustrative internal components of a control device that are communicatively coupled to one another to provide wireless identification and pairing to a

medical device and wireless control of the medical device, according to one or more embodiments shown and described herein;

[0024] FIG. 2B depicts illustrative internal components of a medical device that are communicatively coupled to one another, receive identification from a control device, and receive wireless control from a control device, according to one or more embodiments shown and described herein;

[0025] FIG. 3 depicts an illustrative wireless link pairing system including a rail-mounted lift as a medical device, and a tethered hand control unit, a wireless hand control unit, and/or a wall-mounted control unit as control devices, according to one or more embodiments shown and described herein;

[0026] FIG. 4A depicts an illustrative sling bar control unit as a control device, according to one or more embodiments shown and described herein;

[0027] FIG. 4B depicts an illustrative coupling control unit as a control device, according to one or more embodiments shown and described herein;

[0028] FIG. 5 depicts a flow diagram of an illustrative method for pairing a medical device and a control device using a wireless channel, according to one or more embodiments shown and described herein; and

[0029] FIG. 6 depicts a flow diagram of an illustrative method for a control device to issue commands or control inputs to a paired medical device, according to one or more embodiments shown and described herein.

DETAILED DESCRIPTION

[0030] Reference will now be made in detail to embodiments to pair a medical device and a control device using wireless radio frequency, examples of which are illustrated in the accompanying drawings. Whenever possible, the same reference numerals will be used throughout the drawings to refer to the same or like parts. Various embodiments of the present disclosure are depicted in FIG. 1A. In general, a medical facility 100 may include a plurality of rooms and/or a plurality of floors (e.g., Rooms A and B on one floor, other rooms may be on other floors). In such aspects, one or more medical devices (e.g., MD_A, MD_B, and/or MD_C) and one or more control devices (CD_A, CD_B, CD_C, and/or CD_D), may be distributed amongst the rooms, floors (see FIGS. 1A-1B), and/or within sub-spaces within a given room (e.g., a large triage room with multiple beds, hospital rooms that are shared by 2 or more subjects, etc.).

[0031] In one aspect, referring to FIG. 1A, a control device (e.g., CD_D) and a medical device (e.g., MD_C) may be fixedly positioned within a room (e.g., Room B). A control device CD may be any device capable of pairing/unpairing (also referred to herein as connecting/disconnecting) with a medical device, and sending commands to control a medical device. By way of non-limiting example, a control device may be any device capable of wirelessly pairing with a medical device and issuing commands to the medical device, such as a tethered hand control unit, a wireless hand control unit, a wall mounted control unit, any type of computer (tablet, smartphone, laptop, desktop, etc.), and the like. A medical device may any medical device capable of wirelessly pairing/unpairing with a control device, and implementing commands received from a control device. By way of non-limiting example, a medical device may be a medical bed, a pump, a rail-mounted lift, a computer, and the like. In this aspect, a control device (CD_A, CD_B, CD_C, CD_D,

and/or the like) may be permanently located in a particular location, such as room A or room B. When unpaired, a control device may broadcast data having multiple fields, such as a device name field. A device name field (hereinafter also referred to as an identifier) may be any suitable text, such as a location descriptor (“Control Device A Room A East”) that would typically be human-readable and descriptive of its location. In some aspects, a control device may be relocated to another location and/or have its device name field updated accordingly. A manufacturer-specific data field may include customized data used in the advertising of packets as part of the data broadcast. In aspects, some utilizing Bluetooth for wireless communications, the manufacturer-specific data field may include a company identifier, brand identifier, model identifier, device-type identifier, and the like. In some aspects, this may be followed by additional data, such as 31 octets of data, although any suitable amount/type of data may be utilized in other aspects. Any suitable wireless protocol may be utilized, such as Bluetooth, BLE, Zigbee, Z-Wave, 6LoWPAN, Thread, and the like.

[0032] In some aspects, control devices (CD_A, CD_B, CD_C, CD_D, and/or the like) may wirelessly transmit (e.g., via a Bluetooth RF signal and/or radio frequency identification (RFID)) their identifiers (CD_AID, CD_BID, CD_CID, CD_DID, and/or the like) and/or manufacturer-specific data fields (CD_AManu, CD_BManu, CD_CManu, CD_DManu, and/or the like) to medical devices (MD_A, MD_B, MD_C, and/or the like). Since a wireless signal may penetrate the walls and/or floors of the medical facility 100, a number of medical devices within range (e.g., up to 300 feet for Class 1. Bluetooth, up to 33 feet for Class 2. Bluetooth, and/or the like) may wirelessly receive the control device identifiers (CD_AID, CD_BID, CD_CID, and/or the like). Another control device CD_A resides in a different room, namely room A. Both CD_A and CD_D are broadcasting data, which include the respective device name fields (CD_AID and CD_DID) and the respective manufacturer-specific data fields (CD_AManu and CD_DManu). By contrast, other control devices are paired with medical devices, and therefore not broadcasting data. Within room A, medical device MD_A is paired with control device CD_B. Similarly, within room B, medical device MD_B is paired with control device CD_C. Paired control devices CD_B and CD_C are not broadcasting data in this aspect because, once paired, control devices may not broadcast data again until unpaired. In other aspects, control devices may continue broadcasting data to other medical devices during pairing. Each medical device (e.g., MD_C) may be configured to scan its wireless communication channel (e.g., Bluetooth channel). Medical device MD_C scans the identifiers and manufacturer-specific data received from control devices CD_A and CD_D. A medical device in this aspect may not continue to scan once paired to a control device. In other aspects a medical device may continue to scan while paired to a control device.

[0033] Continuing with the same aspect, FIG. 1B depicts a block diagram illustrating control devices wirelessly advertising to a medical device and a plurality of medical devices wirelessly paired to other control devices that are distributed amongst the plurality of rooms of the medical facility. In some aspects, a control device CD_A may pair with a medical device MD_C such that the medical device MD_C pairs to the identified control device CD_A. Once paired, the control device CD_A may transmit control signals to the

medical device MD_C and the medical device MD_C may begin to receive control signals (also known as instructions herein) from the control device CD_A. Additionally, the medical device MD_C may transmit status updates to the control device CD_A and the medical device MD_C may receive status updates from the control device CD_A. Since the medical device MD_C is now paired, control device CD_A is no longer broadcasting data. By contrast, control device CD_D is still not paired and thus continues broadcasting data. In another aspect, if the medical device MD_C stops receiving instructions (or any other data in some aspects) from control device CD_A, medical device MD_C may be configured to automatically disassociate from control device CD_C over their respective wireless communication channels and/or vice versa if the control device CD_C no longer receives any data from the medical device MD_C. As discussed herein, a medical device and/or control device may provide an indicator (visual, audio, and the like) of pairing and/or unpairing.

[0034] Continuing with the aspect of FIGS. 1A-1B, FIG. 1C depicts an exemplary medical device graphical interface 110 illustrating a plurality of wireless control devices selectable according to signal strength 114 and/or room location within the medical facility. The medical device graphical interface 110 in this aspect is presented on a touch display located on a medical device, although any suitable device capable of displaying a graphical interface 110 may be utilized. Here, the medical device is scanning for data broadcast from control devices after having been wheeled into room A. As discussed herein, medical device actions such as applying the brakes or being plugged into the wall for power may initiate the medical device to begin scanning. As shown in the medical device graphical interface 110, three control devices are presented as selectable options. Each medical device may be presented with its device name field 112, which in this aspect may include the room number in the device name. In some aspects, the device name field 112 may be updated by any appropriate user or administrator. In other aspects, any other suitable identifying information may be included (floor, building, control device type, and the like) in the device name field 112. Other types of data fields may be utilized for display such as room number, floor number, building, and the like, by which control devices may be sorted and/or filtered. Control devices may be filtered by any suitable criteria, such as manufacturer or control device type, which may be contained in the manufacturer-specific data field. In this aspect, control devices from other manufacturers are not displayed even if they are broadcasting data. This can help ensure compatibility and the integrity of communications between the medical device and any control devices satisfying the filtering criteria. Among control devices that meet the filtering criteria, such as being from a specified manufacturer, control device options may be sorted by any suitable criteria. In this aspect, control devices CD_A, CD_E, CD_F, are sorted by their respective Bluetooth signal strengths 114, although any quantity and/or type of sorting criteria may be utilized, such as room number, floor number, manufacturer, and the like.

[0035] FIG. 2A depicts illustrative internal components of a control device 200 that are communicatively coupled to one another to provide wireless link pairing with and control of a medical device, according to one or more embodiments of the present disclosure. As shown in FIG. 2A, the control device 200 may include a local interface 202 (e.g., a bus)

that communicatively interconnects the various components, including, but not limited to, a processing device **204**, memory **206**, input/output hardware **208**, network interface hardware **210**, and/or a data storage device **212**.

[0036] The processing device **204**, such as a computer processing unit (CPU), may be the central processing unit of the control device **200**, performing calculations and logic operations required to execute a program. The processing device **204**, alone or in conjunction with one or more of the other elements disclosed in FIG. 2A, is an illustrative processing device, computing device, processor, or combination thereof, as such terms are used in this disclosure.

[0037] The memory **206**, such as read only memory (ROM) and random access memory (RAM), may constitute illustrative memory devices (i.e., non-transitory, processor-readable storage media). Such memory **206** may include one or more programming instructions thereon that, when executed by the processing device **204**, cause the processing device **204** to complete various processes, such as the processes described herein. Optionally, the program instructions may be stored on a tangible computer-readable medium such as a digital disk, flash memory, a memory card, a USB drive, an optical disc storage medium (e.g., Blu-ray™, CD, DVD), and/or other non-transitory processor-readable storage media.

[0038] In some embodiments, the program instructions contained on the memory **206** may be embodied as a plurality of software modules, where each module provides programming instructions for completing one or more tasks. For example, as shown in FIG. 2A, the memory **206** may contain one or more of operating logic **214**, communications logic **216**, and UI logic **218**. It should be understood that the various logic modules described herein with respect to FIG. 2A are merely illustrative, and that other logic modules, including logic modules that combine the functionality of two or more of the modules described hereinabove, may be used without departing from the scope of the present disclosure.

[0039] Still referring to FIG. 2A, the data storage device **212**, which may generally be a storage medium that is separate from the memory **206**, may contain a data repository for storing electronic data and/or the like relating to the location of the control device **200**, an identification of the control device **200**, configuration settings, UI data, and/or the like. The data storage device **212** may be any physical storage medium, including, but not limited to, a hard disk drive (HDD), memory, removable storage, and/or the like. While the data storage device **212** is depicted as a local device, it should be understood that the data storage device **212** may be a remote storage device that is remotely located from the control device **200**, such as, for example, a server computing device or the like. Illustrative data that may be contained within the data storage device **212** may include, for example, location data **220**, configuration data **222**, UI data **224**, pairing data **226**, and/or the like. Pairing data **226** may include identification data (serial number, etc.) one or more medical device identifiers to which the control device **200** is or has been paired via the methods as described herein.

[0040] The input/output hardware **208** may generally include a wireless system **230**, an indicator **232**, a location system **234**, and a user interface system **236**. The wireless system **230** may include a transceiver **242** configured to transmit and to receive wireless signals (e.g., RF, Bluetooth,

UWB, and/or the like) according to the respective wireless protocols. In some aspects, data transmission techniques including encryption/decryption, forward error correction, and/or the like may be instituted. The indicator **232** may include a light emitting diode, indicator light, and/or the like. The location system **234** may include a Global Positioning System (GPS), a Global Navigation Satellite System (GLO-NASS), a Wi-Fi locating system, and/or the like. The user interface system **236** may include a display **244** and/or user interface controls **246** configured to receive control inputs for transmission via the input/output hardware **208** and to display outputs received from the input/output hardware **208**.

[0041] The network interface hardware **210** may generally provide the control device **200** with an ability to interface with one or more external devices, such as, for example, a medical facility server, a nurse station, and/or the like. Communication with external devices may occur using various communication ports (not shown). An illustrative communication port may be attached to a communications network, such as the Internet, an intranet, a local network, a direct connection, and/or the like.

[0042] It should be understood that in some embodiments, the input/output hardware **208** and the network interface hardware **210** may be combined into a single device that allows for communications with other devices, regardless of whether such other devices are located within the control device **200**.

[0043] It should be understood that the components illustrated in FIG. 2A are merely illustrative and are not intended to limit the scope of the present disclosure. More specifically, while the components in FIG. 2A are illustrated as residing within the control device, this is a non-limiting example. In some embodiments, one or more of the components may reside external to the control device. Similarly, one or more of the components may be embodied in other devices not specifically described herein. Furthermore, various control devices are described herein (e.g., FIG. 3) and are non-limiting examples. Other control devices may include a user's personal cell-phone, a nurse's call system device, and/or the like with wireless communication channel capabilities.

[0044] FIG. 2B depicts illustrative internal components of a medical device **250** that are communicatively coupled to one another to provide wireless link pairing with a control device, according to one or more embodiments of the present disclosure. As shown in FIG. 2B, the medical device **250** may include a local interface **252** (e.g., a bus) that communicatively interconnects the various components, including, but not limited to, a processing device **254**, memory **256**, input/output hardware **258**, network interface hardware **260**, and/or a data storage device **262**.

[0045] The processing device **254**, such as a computer processing unit (CPU), may be the central processing unit of the medical device **250**, performing calculations and logic operations required to execute a program. The processing device **254**, alone or in conjunction with one or more of the other elements disclosed in FIG. 2B, is an illustrative processing device, computing device, processor, or combination thereof, as such terms are used in this disclosure.

[0046] The memory **256**, such as read only memory (ROM) and random access memory (RAM), may constitute illustrative memory devices (i.e., non-transitory, processor-readable storage media). Such memory **256** may include one

or more programming instructions thereon that, when executed by the processing device 254, cause the processing device 254 to complete various processes, such as the processes described herein. Optionally, the program instructions may be stored on a tangible computer-readable medium such as a digital disk, flash memory, a memory card, a USB drive, an optical disc storage medium (e.g., Blu-ray™, CD, DVD), and/or other non-transitory processor-readable storage media.

[0047] In some embodiments, the program instructions contained on the memory 256 may be embodied as a plurality of software modules, where each module provides programming instructions for completing one or more tasks. For example, as shown in FIG. 2B, the memory 256 may contain one or more of operating logic 264, communications logic 266, and movement logic 268. It should be understood that the various logic modules described herein with respect to FIG. 2B are merely illustrative, and that other logic modules, including logic modules that combine the functionality of two or more of the modules described hereinabove, may be used without departing from the scope of the present disclosure.

[0048] Still referring to FIG. 2B, the data storage device 262, which may generally be a storage medium that is separate from the memory 256, may contain a data repository for storing electronic data and/or the like relating to the location of the medical device 250, an identification of the medical device 250, configuration settings, and/or the like. The data storage device 262 may be any physical storage medium, including, but not limited to, a hard disk drive (HDD), memory, removable storage, and/or the like. While the data storage device 262 is depicted as a local device, it should be understood that the data storage device 262 may be a remote storage device that is remotely located from the medical device 250, such as, for example, a server computing device or the like.

[0049] Illustrative data that may be contained within the data storage device 262 may include, for example, location data 270, configuration data 272, pairing data 274, and/or the like. Pairing data 274 may include one or more control device identifiers to which the medical device 250 is or has been paired via the methods as described herein.

[0050] The input/output hardware 258 may generally include a user interface system 278, a wireless system 280, an indicator 282, and a location system 284. The user interface system 278 may include a display 288 and/or user interface controls 290 configured to receive control inputs for transmission via the input/output hardware 258 and to display outputs received from the input/output hardware 258. The wireless system 280 may include a transceiver 292 configured to transmit and to receive wireless signals (e.g., RFID, RF, Bluetooth, UWB, and/or the like) according to the respective wireless protocols. In some aspects, data transmission techniques including encryption/decryption, forward error correction, and/or the like may be instituted. The indicator 282 may include a light emitting diode, indicator light, and/or the like. The location system 284 may include a Global Positioning System (GPS), a Global Navigation Satellite System (GLONASS), a Wi-Fi locating system, and/or the like.

[0051] The network interface hardware 260 may generally provide the medical device 250 with an ability to interface with one or more external components, such as, for example, a medical facility server, a nurse station, and/or the like.

Communication with external devices may occur using various communication ports (not shown). An illustrative communication port may be attached to a communications network, such as the Internet, an intranet, a local network, a direct connection, and/or the like.

[0052] It should be understood that in some embodiments, the input/output hardware 258 and the network interface hardware 260 may be combined into a single device that allows for communications with other devices, regardless of whether such other devices are located within the medical device 250.

[0053] It should be understood that the components illustrated in FIG. 2B are merely illustrative and are not intended to limit the scope of this disclosure. More specifically, while the components in FIG. 2B are illustrated as residing within the medical device 250, this is a non-limiting example. In some embodiments, one or more of the components may reside external to the medical device 250. Similarly, one or more of the components may be embodied in other devices not specifically described herein.

[0054] FIG. 3 depicts one illustrative wireless link pairing system 300 including a rail-mounted lift 302 as an illustrative medical device and a plurality of remote devices 304, 306, 308, as control devices, according to one or more embodiments of the present disclosure. Referring to FIG. 3, the rail-mounted lift 302 is coupled to a rail 310. According to various aspects, the rail 310 may extend along a ceiling of a room (e.g., Room A of FIG. 1), along a ceiling of more than one room (e.g., Room A and Room B of FIG. 1), and/or the like. More specifically, the rail-mounted lift 302 includes a lift unit 312 that is slidably coupled to the rail 310 via a carriage 314. The lift unit 312 may be used to support and/or lift a subject with a lifting strap 316 which is coupled to a motor (not shown) contained within the lift unit 312. The motor facilitates extending or retracting the lifting strap 316 from the lift unit 312, thereby raising and lowering a subject attached to the lifting strap 316. According to various embodiments, a subject may be attached to the lifting strap 316 with a sling bar 318 or a similar accessory attached to the lifting strap 316 via a coupling 317. The sling bar 318 or a similar accessory may be attached to a harness or a sling in which the subject is positioned, thereby facilitating the lifting operation.

[0055] Various components of the rail-mounted lift 302, such as the lift unit 312 and/or components thereof, may be operated with a tethered hand control unit 304, a wireless hand control unit 306 and/or a wall-mounted control unit 308 communicatively coupleable to the lift unit 312. In view of FIG. 3, the tethered hand control unit 304 may be directly wired to the lift unit 312 and/or wirelessly coupled or paired to the lift unit 312 (e.g., according to the methods described herein) to facilitate remote operation of the rail-mounted lift 302. According to various aspects, the tethered hand control unit 304 may include a display 320 and one or more user interface controls 322A (e.g., to extend lifting strap 316), 322B (e.g., to retract lifting strap 316). Similarly, the wireless hand control unit 306 may be wirelessly coupled or paired to the lift unit 312 (e.g., according to the methods described herein) and may include a display 324 and one or more user interface controls 326A (e.g., to extend lifting strap 316), 326B (e.g., to retract lifting strap), 326C (e.g., to translate lift unit 312 in a first lateral direction L1 along rail 310), 326D (e.g., to translate lift unit 312 in a second lateral direction L2 along rail 310), and the wall-mounted control

unit **308** may be wirelessly coupled or paired to the lift unit **312** (e.g., according to the methods described herein) and may include a display **328** and one or more user interface controls **330A** (e.g., to extend lifting strap **316**), **330B** (e.g., to retract lifting strap **316**), **330C** (e.g., to translate lift unit **312** in a first lateral direction **L1** along rail **310**), **330D** (e.g., to translate lift unit **312** in a second lateral direction **L2** along rail **310**). Further user interface controls of the wall-mounted control unit **308** may activate the lift unit **312**, pair a subject with the lift unit **312**, return the lift unit **312** to a “home” position/location, receive information from the lift unit **312** (e.g., battery status, magnitude of load supported by the lift unit, and/or the like), actuate an emergency stop of the lift unit **312**, reset the lift unit **312**, and/or the like.

[0056] Referring to FIGS. **4A** and **4B**, according to further aspects of the present disclosure, the rail-mounted lift **302** (e.g., FIG. **3**) may be operated with a sling bar control unit **400** positioned on the sling bar **318** and/or a coupling control unit **410** positioned on the coupling **317** attached to a distal “D” end of the lifting strap **316**. The sling bar control unit **400** may be wirelessly coupled or paired to the lift unit **312** (e.g., according to the methods described herein) and may include one or more user interface controls **402A** (e.g., to extend lifting strap **316**), **402B** (e.g., to retract lifting strap **316**). Similarly, the coupling control unit **410** may be wirelessly coupled or paired to the lift unit **312** (e.g., according to the methods described herein) and may include one or more user interface controls **412A** (e.g., to extend lifting strap **316**), **412B** (e.g., to retract lifting strap **316**).

[0057] In light of FIGS. **3**, **4A** and **4B**, a plurality of control devices (e.g., a tethered hand control unit **304**, a wireless hand control unit **306**, a wall-mounted control unit **308**, a sling bar control unit **400**, a coupling control unit **410**, and/or the like) may already be physically present in a room in the aspect. In other aspects, control devices may be physically brought into the room, and/or physically taken out of the room. According to some aspects of the present disclosure, a medical device (e.g., the rail-mounted lift **302**) may be fixedly positioned within a room. In such aspects, referring to FIGS. **3** and **4B**, control devices that physically remain in that room (e.g., wall-mounted control unit **308**) and physically remain coupled to the medical device itself in that room (e.g., tethered hand control unit **304**, coupling control unit **410**), remain wirelessly connected to the medical device, and the medical device may be configured to remain paired with one or more of such control devices. For example, the rail-mounted lift **302** may store pairing data (FIG. **2B**, reference **274**, e.g., associated CD IDs in a fixed pairings file), in its data storage device (FIG. **2B**, reference **262**) for each control device that physically remains in its room and/or physically remains coupled to the rail-mounted lift **302**. Further in such aspects, referring to FIGS. **3** and **4A**, one or more control devices may not physically remain in that room (e.g., wireless hand control unit **306**, sling bar control unit **400**). In such aspects, the medical device may be configured to not only pair with such control devices as they are brought into a room but also periodically or continually monitor pairings with such control devices. Periodically, as described herein, may refer to a regularly occurring interval or time period (e.g., every “X” seconds, every “Y” minutes, and/or the like). Continuing the example, the rail-mounted lift **302** may store pairing data (e.g., FIG. **2B**, reference **274**, e.g., associated CD IDs in a transient pairings file), in its data storage device (e.g., FIG. **2B**, reference **262**) for each control

device that may not physically remain in its room and the rail-mounted lift **302** may periodically determine whether each control device identifier (e.g., CD ID) is still being received over its wireless communication channel. According to various aspects, if control device input (e.g., stored in a transient pairings file) is still being wirelessly received, the medical device (e.g., rail-mounted lift) may remain paired with that control device and if the paired control device identifier is not still being wirelessly received, the medical device may automatically disassociate from that control device (e.g., the medical device considered as physically taken out of the room).

[0058] According to other aspects of the present disclosure, a medical device (e.g., a rail-mounted lift **302**) may not be fixedly positioned within a room. For example, a lift unit may be moved along a rail **310** (FIG. **3**) from one room (e.g., FIG. **1**, Room A) to another room (e.g., FIG. **1**, Room B). In such aspects, referring to FIGS. **3** and **4B**, control devices that physically remain coupled to the medical device itself (e.g., tethered hand control unit **304**, coupling control unit **410**), remain wirelessly connected to the medical device and the medical device may be configured to remain paired with all such control devices. For example, the rail-mounted lift **302** may store pairing data (FIG. **2B**, reference **274**, e.g., associated CD IDs in a fixed pairings file), in its data storage device (FIG. **2B**, reference **262**) for each control devices that physically remains coupled to the rail-mounted lift **302**. Further in such aspects, referring to FIGS. **3** and **4A**, one or more control devices may not be physically coupled to the medical device itself. This may include control devices that physically remain in a given room (e.g., wall-mounted control units **308**) and/or control devices that may not physically remain in any given room (e.g., wireless hand control unit **306**, sling bar control unit **400**). In such aspects, the medical device may be configured to not only pair with such control devices but also periodically or continually monitor pairings with such control devices. Continuing the example, the rail-mounted lift **302** may store pairing data (e.g., FIG. **2B**, reference **274**, e.g., associated CD IDs in a transient pairings file), in its data storage device (e.g., FIG. **2B**, reference **262**) for each control device that physically remains in a given room and that may not physically remain in any given room and the rail-mounted lift **302** may periodically determine whether each control device identifier (e.g., CD ID) is still communicating with the rail-mounted lift **302** over its wireless communication channel.

[0059] According to various aspects, upon detecting movement (e.g., translation along rail **310**) the medical device may be configured to continually monitor pairings with such control devices. Accordingly, if a control device identifier (e.g., CD ID of a wireless hand control unit **306** being used to translate or move the rail-mounted lift **302** between rooms, CD ID of a sling bar control unit **400** being moved with the rail-mounted lift **302** between rooms) or other data is still being wirelessly received, the medical device (e.g., rail-mounted lift) may remain paired with the control device(s) and if the control device identifier (e.g., CD ID of a wall-mounted control unit **308** in a former room, CD ID of a sling bar control unit **400** not moved to a new room) or other data from the control device is not still being wirelessly received, the medical device may automatically disassociate from any such control device(s). Further in such an aspect, the medical device may be configured to provide on its graphical interface **110** for pairing new control devices

(e.g., wall-mounted control unit **308** in new room) as the medical device transitions between rooms.

[0060] FIG. 5 depicts a flow diagram of an illustrative method **500** for pairing a medical device and a control device using a wireless channel, according to one or more embodiments of the present disclosure. Referring to FIG. 5, a medical device MD_X **502** may identify and pair with a control device CD_X **504**, wherein the dashed vertical line in the center of the flow diagram demarcates the respective operations of the medical device MD_X **502** and the control device CD_X **504**. At block **506**, the CD_X may be unpaired and wirelessly broadcast self-identifying data, which may include a device name and/or manufacturer-specific data (manufacturer, brand, model, device, type, and the like). At block **508**, the MD_X may scan for wireless broadcasts based upon receiving input (such as a user pressing a button on MD_X or a button within the medical device interface) or satisfying a scanning criterion. For example, MD_X may be a bed, in which setting its brakes or being plugged into a wall for power may automatically cause MD_X to scan for control devices. Setting the brakes or being plugged into the wall may be criteria that indicate, for example, that MD_X has reached its intended destination (such as a particular room or partition within a room) and scanning is now appropriate. In this way, MD_X can conserve power by avoiding unnecessary scanning until a destination has been reached.

[0061] At block **510**, the medical device MD_X may receive the identifying data wirelessly broadcast from CD_X . Although the wireless broadcast from CD_X in block **506** is depicted as intersecting within the flowchart prior to the scanning by MD_X at block **508**, the wireless broadcast in block **506** may intersect at any point up and/or including reception of the CD_X at block **510**. At block **512**, the medical device MD_X may output information to the interface (e.g., FIG. 1C) identifying the control device CD_X , in which the manufacturer-specific data may be filtered (e.g., handheld control devices from a specific manufacturer may be displayed for selection on the interface). At block **514**, the medical device MD_X may receive input at the interface selecting the control device. For example, a user may touch a screen selecting CD_X from among other eligible control devices. At block **516**, the medical device MD_X may send wireless confirmation of the pairing to the control device CD_X . In this aspect, the medical device interface may add the medical device MD_X to the list of selectable medical devices. At block **518**, the control device CD_X may receive pairing confirmation. In some aspects, the control device CD_X may provide an indication of pairing/unpairing events, such as the indicator **232** in FIG. 2A, which may be a light such as an LED. At block **520**, the control device CD_X may stop its wireless broadcast due to being paired with a medical device MD_X . At block **522**, the control device CD_X may send one or more commands to the medical device MD_X . At block **524**, the medical device MD_X may receive the one or more commands from the control device CD_X . At block **526**, based on the received command(s), the medical device MD_X may physically interact with a user. As used herein, physical interaction with a user may include, by way of non-limiting examples, taking diagnostics or measurements (size/proportions, weight, temperature, heart rate, glucose, blood pressure, brainwaves, biorhythms, and the like) of a user, introducing or removing any suitable substance from any part of a user, diagnosing and/or alleviating/

treating any disease or other ailment of a user, and/or assisting with the support, mobility, positioning, restraint, and/or comfort of the user.

[0062] At block **528**, the medical device MD_X may send wireless confirmation of unpairing, which may be accomplished via the medical device interface. This may be, for example, when the medical device MD_X (a bed in this non-limiting example) is being moved to another room. At block **530**, the control device CD_X may receive subsequent confirmation of the unpairing. In some aspects, this may entail a visual, audio, or other indication associated with the control device CD_X , such as the indicator **232** in FIG. 2A. At block **532**, the control device CD_X may resume broadcasting self-identifying data in order to become paired with another medical device, such as a different bed that may be wheeled into the room in which CD_X resides. At block **534**, the medical device MD_X may perform an updated scan for wireless broadcasts. This may be done, for example, when the medical device MD_X has been wheeled into another room such that the brakes are engaged and/or the medical device MD_X is plugged into the wall.

[0063] FIG. 6 depicts a flow diagram of an illustrative method **600** for a control device to issue commands or control inputs to a paired medical device, according to one or more embodiments of the present disclosure. According to various aspects, method **600** may be utilized for all control functions or only certain functions (e.g., actuating a motor, turning on a pump, and/or the like). Referring to FIG. 6, at block **602**, a control device CD_X may be paired with a medical device MD_X over its wireless communication channel, as described herein. At decision block **604**, the control device CD_X may be configured to determine (e.g., based on inputs received via user interface controls **246** of FIG. 2A) whether a command or control input is to be issued or transmitted to the medical device MD_X . If it is determined that a command or control input is not to be issued or transmitted to MD_X , the control device CD_X may remain paired with the medical device identifier MD_XID over its wireless communication channel at block **602**. If it is determined that a command or control input is to be issued or transmitted to the medical device MD_X , the control device CD_X may be configured to determine whether the wireless communication channel is weak (e.g., below a predetermined threshold wireless signal strength) at decision block **606**.

[0064] If it is determined that the wireless communication channel is weak, the control device CD_X may be configured to automatically disassociate from the medical device MD_X over the wireless communication channel at block **608**. At block **610** (shown in phantom as an optional operation), the control device CD_X may be configured to update its visual indicator to reflect the disassociation (e.g., LED off). If it is determined that the wireless communication channel is not weak, the control device CD_X may be configured to, at block **620**, issue the command or control input to the medical device MD_X over its wireless communication channel. According to such aspects, if a medical device MD_X is moved to an out-of-range location (e.g., no longer within the wireless range of the control device CD_X), then the control device CD_X may be unable to issue a command or control input to the medical device MD_X , despite being otherwise able to over a strong wireless communication channel.

[0065] According to another embodiment, referring back to FIGS. 2A-2B, the control device **200** may include a

location system **234** and the medical device **250** may include a location system **284**. In such aspects, the medical device **250** and/or the control device **200** may be configured to further transmit their respective location information (e.g., MD LOC, CD LOC) with their respective identifiers (e.g., MD ID, CD ID) as described herein. In such aspects, the control device **200** may be configured to compare a received MD LOC (from the medical device) with its CD LOC as part of its process of pairing with a medical device. In some aspects, an initial range (e.g., about 2 m to about 5 m radius) may be used for initial pairing and a control range (e.g., average size of room) may be used for disassociation. In further aspects, the control device **200** may be configured to adjust/correct its CD LOC as well as the received MD LOC using a medical facility location MF LOC location beacon with known coordinates. Likewise, the medical device **250** may be configured to adjust/correct its MD LOC using a medical facility location MF LOC location beacon with known coordinates. According to various embodiments, such aspects may be used to further confirm the other identification methods as described herein. According to the various embodiments described herein, each wireless communication channel (e.g., Bluetooth channel) may be configured as a single-path communication channel or a dual-path communication channel.

[0066] It should be appreciated that while elements are described as optional, this is only with respect to one or more illustrative embodiments, such as program instructions stored in **206** FIG. 2A and **256** FIG. 2B, as well as the features depicted in **234** FIG. 2A, **284** FIG. 2B, and **610** FIG. 6. That is, these elements may be required in other embodiments. In addition, the depiction of these elements as optional does not imply that the processes described with respect to other elements in the respective figures are required.

[0067] It should now be understood that the systems and methods described herein are suitable for pairing a medical device and a control device using a wireless link (e.g., Bluetooth channel). In particular, the systems and methods described herein identify a configurable, pairable wireless connection (e.g. Bluetooth channel) to be used to execute control actions for a medical device (e.g., a portable medical bed) to ensure that the control inputs are coming from a control device (e.g., a tethered hand control unit, a wireless hand control unit, a wall-mounted control unit, a sling bar control unit, a coupling control unit, and/or the like) located in the same room as the medical device. Such systems and methods ensure that the control inputs coming from the control device are only directed to a medical device based upon user input received at the medical device that selects for pairing and/or control of the medical device.

[0068] While particular embodiments have been illustrated and described herein, it should be understood that various other changes and modifications may be made without departing from the spirit and scope of the claimed subject matter. Moreover, although various aspects of the claimed subject matter have been described herein, such aspects need not be utilized in combination. It is therefore intended that the appended claims cover all such changes and modifications that are within the scope of the claimed subject matter.

1. A method for assisted medical device wireless pairing with a control device, the method comprising:

scanning, at the medical device, for wireless broadcasts based upon received input or satisfying a scanning criterion;

receiving, based upon the scan, identifying data wirelessly broadcast from a plurality of control devices;

outputting, to an interface at the medical device, information identifying the plurality of control devices, wherein:

the identifying data received from the plurality of control devices is presented on the interface according to a filtering criterion and a sorting criterion, and the sorting criterion comprises location information within the identifying data or respective signal strengths of each wireless broadcast;

receiving input from the interface selecting one of the plurality of control devices;

sending wireless confirmation of pairing to the selected control device;

receiving a command from the control device;

physically interacting with a user based upon the command received from the control device;

subsequently sending wireless confirmation of unpairing to the control device; and

performing an updated scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.

2. The method of claim 1, wherein the pairable medical device comprises a medical bed, a pump, a rail-mounted lift, or a computer.

3. The method of claim 1, wherein the scanning criterion is based upon the medical device being plugged in or having brakes engaged.

4. The method of claim 1, wherein the filtering criterion comprises a device manufacturer, a device type, or a device model.

5. (canceled)

6. (canceled)

7. (canceled)

8. (canceled)

9. A pairable medical device, comprising:

a communication system configured to communicate via a communication channel;

an interface;

a processor; and

a memory storing program instructions that, when executed by the processor, cause the processor to:

scan for wireless broadcasts based upon received input or satisfying a scanning criterion;

receive, based upon the scan, identifying data wirelessly broadcast from a plurality of control devices;

output, to the interface, information identifying the plurality of control devices, wherein:

the identifying data received from the plurality of control devices is presented on the interface according to a filtering criterion and a sorting criterion, and

the sorting criterion comprises location information within the identifying data or respective signal strengths of each wireless broadcast;

receive input from the interface selecting one of the plurality of control devices;

send wireless confirmation of pairing to the selected control device;

receive a command from the control device;

physically interact with a user based upon the command received from the control device;
 subsequently send wireless confirmation of unpairing to the control device; and
 perform an updated scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion.

10. The pairable medical device of claim **9**, wherein the pairable medical device comprises a medical bed, a pump, a rail-mounted lift, or a computer.

11. The pairable medical device of claim **9**, wherein the scanning criterion is based upon the medical device being plugged in or having brakes engaged.

12. The pairable medical device of claim **9**, wherein the filtering criterion comprises a device manufacturer, a device type, or a device model.

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. A non-transitory, processor-readable storage medium comprising instructions that, when executed by at least one processor, cause the at least one processor to perform one or more operations comprising:

scanning, at a medical device, for wireless broadcasts based upon received input or satisfying a scanning criterion;

receiving, based upon the scan, identifying data wirelessly broadcast from a plurality of control devices;

outputting, to an interface at the medical device, information identifying the plurality of control devices;
 receiving input from the interface selecting one of the plurality of control devices;

sending a wireless confirmation of pairing to the selected control device;

receiving a command from the control device;

physically interacting with a user based upon the command received from the control device;

subsequently sending wireless confirmation of unpairing to the selected control device; and

performing an updated scan for wireless broadcasts in response to the unpairing, based upon received input or satisfying the scanning criterion, wherein:

the identifying data received from the plurality of control devices is presented on the interface according to a filtering criterion and a sorting criterion, and

the sorting criterion comprises location information within the identifying data or respective signal strengths of each wireless broadcast.

18. The non-transitory, processor-readable storage medium of claim **17**, wherein the scanning criterion is based upon the medical device being plugged in or having brakes engaged.

19. (canceled)

20. (canceled)

* * * * *