

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414630
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Doner; Drew Steven

Hanging ribbed chair

Abstract

A hanging chair may comprise a front frame and a plurality of support members. The front frame may define a front opening. The plurality of support members may be coupled to the front frame and may extend from a top portion of the front frame to a bottom portion of the front frame. The plurality of support members may extend axially rearward the front frame. The hanging chair may comprise a first side opening defined between the front frame and a first outer support member of the plurality of support members. The hanging chair may comprise a second side opening defined between the front frame and a second outer support member of the plurality of support members. The first side opening, the second side opening, and the front opening may be in fluid communication.

Inventors:	Doner; Drew Steven (Walsh, CO)
Applicant:	Doner; Drew Steven (Walsh, CO)
Family ID:	1000008820672
Appl. No.:	17/993801
Filed:	November 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230165369 A1	Jun. 01, 2023

Related U.S. Application Data

us-provisional-application US 63282861 20211124

Publication Classification

Int. Cl.: A47C3/025 (20060101)

U.S. Cl.:

CPC A47C3/0255 (20130101);

Field of Classification Search

CPC: A47C (3/0255)

USPC: 297/277

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
719301	12/1902	Campbell	297/423.1	N/A
6585319	12/2002	Tseng	297/277	A47C 3/0255
9468284	12/2015	Wehner	N/A	A47C 4/18
10912386	12/2020	Xuemin	N/A	A47C 3/0255
11369201	12/2021	Yu	N/A	A47C 3/0255

Primary Examiner: Barfield; Anthony D

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a nonprovisional filing of, and claims priority to and the benefit of, U.S. Provisional Patent Application No. 63/282,861, filed Nov. 24, 2021, and entitled “HANGING RIBBED CHAIR,” which is hereby incorporated by reference in its entirety.

FIELD

(1) The present disclosure relates to chairs, and more specifically, to chairs configured to suspend in the air by hanging from an external support structure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The subject matter of the present disclosure is particularly pointed out and distinctly claimed in the concluding portion of the specification. A more complete understanding of the present disclosure, however, may best be obtained by referring to the detailed description and claims when considered in connection with the following illustrative figures. In the following figures, like reference numbers refer to similar elements and steps throughout the figures.

(2) FIG. 1A illustrates a front perspective view of a chair, in accordance with various embodiments:

(3) FIG. 1B illustrates a side perspective view of a chair, in accordance with various embodiments:

(4) FIG. 1C illustrates a top perspective view of a chair, in accordance with various embodiments:

(5) FIG. 2A illustrates a side perspective view of a chair in a rest position, in accordance with various embodiments:

- (6) FIG. 2B illustrates a side perspective view of a chair in a load position, in accordance with various embodiments;
- (7) FIG. 3 illustrates a front perspective view of a chair with a covering, in accordance with various embodiments;
- (8) FIG. 4 illustrates a front perspective view of a chair with accessories, in accordance with various embodiments;
- (9) FIG. 5 illustrates a side perspective view of a chair with a deployable footrest, in accordance with various embodiments; and
- (10) FIG. 6 illustrates a front perspective view of a chair with removable couplings, in accordance with various embodiments.
- (11) Elements and steps in the figures are illustrated for simplicity and clarity and have not necessarily been rendered according to any particular sequence. For example, steps that may be performed concurrently or in different order are illustrated in the figures to help to improve understanding of embodiments of the present disclosure.

DETAILED DESCRIPTION

(12) The detailed description of exemplary embodiments herein makes reference to the accompanying drawings, which show exemplary embodiments by way of illustration. While these embodiments are described in sufficient detail to enable those skilled in the art to practice the disclosures, it should be understood that other embodiments may be realized and that logical changes and adaptations in design and construction may be made in accordance with this disclosure and the teachings herein. Thus, the detailed description herein is presented for purposes of illustration only and not of limitation.

(13) The scope of the disclosure is defined by the appended claims and their legal equivalents rather than by merely the examples described. For example, the steps recited in any of the method or process descriptions may be executed in any order and are not necessarily limited to the order presented. Furthermore, any reference to singular includes plural embodiments, and any reference to more than one component or step may include a singular embodiment or step. Also, any reference to attached, fixed, coupled, connected or the like may include permanent, removable, temporary, partial, full and/or any other possible attachment option. Additionally, any reference to without contact (or similar phrases) may also include reduced contact or minimal contact. Surface shading lines may be used throughout the figures to denote different parts but not necessarily to denote the same or different materials.

(14) In various embodiments, and with reference to FIGS. 1A-1C, a chair **100** is disclosed. Chair **100** (e.g., a hanging chair, a suspension chair, a ribbed hanging chair, etc.) may be configured to couple to an overhead, external support structure to suspend in the air (e.g., to hang from the support structure above a surface of the ground). For example, chair **100** may be configured to couple to and suspend from a frame, a tree, a ceiling, a building beam, and/or any other external structure capable of providing support for chair **100**.

(15) In various embodiments, chair **100** may be sized, shaped, and configured to decrease weight in chair **100** compared to other chairs configured for suspension. For example, in some embodiments chair **100** may weigh less than 30 lbs. (13.6 kg). In some embodiments, chair **100** may decrease weight by decreasing relative supporting components compared (e.g., structure, design, building materials, etc.) to a typical chair configured for suspension.

(16) In various embodiments, chair **100** may be sized, shaped, and configured for assembly and disassembly during travel and shipping (e.g., as discussed further with reference to FIG. 6). In that regard, chair **100** may safely assemble and disassembly while also remaining sturdy and safe for use during occupancy (e.g., while a user sits in chair **100**).

(17) In various embodiments, chair **100** may be sized, shaped, and configured to optimize user comfort during use of chair **100**. Chair **100** may be configured to optimize reclining and body position in response to a user sitting in chair **100**. For example, chair **100** may be configured to

transition from a rest position to a load position in response to a user sitting in chair **100** (e.g., as discussed further with reference to FIGS. 2A and 2B). In the load position, and in some embodiments, chair **100** may be positioned to increase user comfort relative to the rest position.

(18) In various embodiments, chair **100** may comprise a front and a back. The front may be defined by a front frame **110**. The back may be defined by a plurality of support members **120**. The front may be axially forward the back. The front and the back may define an interior of chair **100**. The interior of chair **100** may be sized and shaped to receive a user of chair **100** (e.g., to enable a user to enter and exit chair **100**, sit within chair **100**, etc.). The interior of chair **100** may be defined between front frame **110** and a forward surface of one or more support members **120**. Chair **100** may comprise a first side and a second side defined between the front and the back. The first side (e.g., a right side) may be defined by a first armrest **160-1**. The second side (e.g., a left side) may be defined by a second armrest **160-2**.

(19) In various embodiments, front frame **110** may define a front opening **115**. Front frame **110** may circumferentially define front opening **115**. Front opening **115** may enable a user of chair **100** to enter and exit chair **100** (e.g., to sit within chair **100**). In that regard, front opening **115** may be in fluid communication with an interior of chair **100**. Front frame **110** may be sized and shaped to allow the user of chair **100** to enter and exit chair **100** via front opening **115**. Front frame **110** may comprise any suitable or desired shape. For example, front frame **110** may comprise a circular shape, a rectangular shape, a square shape, and/or the like. Front frame **110** may comprise an oval shape. Front frame **110** may comprise a pill shape. Front frame **110** may comprise a shape wherein a vertical length (e.g., a longitudinal length) of front frame **110** is greater than a horizontal length (e.g., a latitudinal length) of front frame **110** (wherein the “vertical length” refers to the longest vertical length of front frame **110** and the “horizontal length” refers to the longest horizontal length of front frame **110**). Front frame **110** may comprise a symmetrical shape wherein a top half of front frame **110** is substantially the same as a bottom half of frame **110** (e.g., a top half of front frame **110** mirrors a bottom half of frame **110**).

(20) In various embodiments, front frame **110** may comprise any suitable and/or desired material. For example, front frame **110** may comprise a rigid material. Front frame **110** may comprise a wood material. Front frame **110** may comprise a metal material, such as stainless steel, steel, aluminum, and/or the like. In some embodiments, front frame **110** may comprise a reinforced steel material (e.g., rebar). In some embodiments, front frame **110** may comprise an about ½-inch (1.27 cm) steel rebar (wherein “about” as used in this sentence refers only to ± 0.01 inches (0.0254 cm)).

(21) In various embodiments, support members **120** may comprise one or more inner support members and one or more out support members. For example, support members **120** may each comprise a first outer support member **130-1** (e.g., a right outer support member) and a second outer support member **130-2** (e.g., a left outer support member). First outer support member **130-1** may comprise a top end **131-1** (e.g., a first outer support member top end, a right outer support member top end, etc.) opposite a bottom end **131-2** (e.g., a first outer support member bottom end, a right outer support member bottom end, etc.). First outer support member **130-1** may comprise a body (e.g., a first outer support member body) defined between top end **131-1** and bottom end **131-2**. Top end **131-1** and/or bottom end **131-2** may be axially forward the body. Top end **131-1** and/or bottom end **131-2** may be radially outward the body. Second outer support member **130-2** may comprise a top end **132-1** (e.g., a second outer support member top end, a left outer support member top end, etc.) opposite a bottom end **132-2** (e.g., a second outer support member bottom end, a left outer support member bottom end, etc.). Second outer support member **130-2** may comprise a body (e.g., a second outer support member body) defined between top end **132-1** and bottom end **132-2**. Top end **132-1** and/or bottom end **132-2** may be axially forward the body. Top end **132-1** and/or bottom end **132-2** may be radially outward the body.

(22) As a further example, support members **120** may comprise a first inner support member **140-1**

(e.g., a left inner support member) and a second inner support member **140-2** (e.g., a right inner support member). First inner support member **140-1** may comprise a top end **141-1** (e.g., a first inner support member top end, a right inner support member top end, etc.) opposite a bottom end **141-2** (e.g., a first inner support member bottom end, a right inner support member bottom end, etc.). First inner support member **140-1** may comprise a body (e.g., a first inner support member body) defined between top end **141-1** and bottom end **141-2**. Top end **141-1** and/or bottom end **141-2** may be axially forward the body. Top end **141-1** and/or bottom end **141-2** may be radially outward the body. Second inner support member **140-2** may comprise a top end **142-1** (e.g., a second inner support member top end, a left inner support member top end, etc.) opposite a bottom end **142-2** (e.g., a second inner support member bottom end, a left inner support member bottom end, etc.). Second inner support member **140-2** may comprise a body (e.g., a second inner support member body) defined between top end **142-1** and bottom end **142-2**. Top end **142-1** and/or bottom end **142-2** may be axially forward the body. Top end **142-1** and/or bottom end **142-2** may be radially outward the body.

(23) Each support member **120** may be coupled to front frame **110**. For example, top end **131-1**, top end **141-1**, top end **142-1**, and top end **132-1** may each be coupled to front frame **110** on a top half of frame **110**. Bottom end **131-2**, bottom end **141-2**, bottom end **142-2**, and bottom end **132-2** may each be coupled to frame **110** on a bottom half of frame **110**. In that respect, the top end of each support member **120** may be coupled to frame **110** opposite the coupling of the bottom end of each support member **120** to frame **110**.

(24) In various embodiments, top end **131-1** of first outer support member **130-1** may be coupled to front frame **110** at a first top coupling point **101** (e.g., a first coupling point). Top end **132-1** of second outer support member **130-2** may be coupled to front frame **110** at a second top coupling point **102** (e.g., a second coupling point). Top end **141-1** of first inner support member **140-1** may be coupled to front frame **110** at a third top coupling point **103** (e.g., a third coupling point). Top end **142-1** of second inner support member **140-2** may be coupled to front frame **110** at a fourth top coupling point **104** (e.g., a fourth coupling point).

(25) First top coupling point **101**, second top coupling point **102**, third top coupling point **103**, and fourth top coupling point **104** may each be located on a top half of front frame **110**. First top coupling point **101**, second top coupling point **102**, third top coupling point **103**, and fourth top coupling point **104** may each comprise separate coupling locations on front frame **110**. For example, each of first top coupling point **101**, second top coupling point **102**, third top coupling point **103**, and fourth top coupling point **104** may be circumferentially separated on front frame **110**.

(26) First top coupling point **101** may be circumferentially outward from third top coupling point **103**. First top coupling point **101** may be radially inward from third top coupling point **103** and/or fourth top coupling point **104**. First top coupling point **101** may be colinear with second top coupling point **102**.

(27) Second top coupling point **102** may be circumferentially outward from fourth top coupling point **104**. Second top coupling point **102** may be radially inward from third top coupling point **103** and/or fourth top coupling point **104**. Second top coupling point **102** may be colinear with first top coupling point **101**.

(28) Third top coupling point **103** may be circumferentially inward from first top coupling point **101**. Third top coupling point **103** may be radially outward from first top coupling point **101** and/or second top coupling point **102**. Third top coupling point **103** may be colinear with fourth top coupling point **104**.

(29) Fourth top coupling point **104** may be circumferentially inward from second top coupling point **102**. Fourth top coupling point **104** may be radially outward from first top coupling point **101** and/or second top coupling point **102**. Fourth top coupling point **104** may be colinear with third top coupling point **103**.

(30) Third top coupling point **103** and fourth top coupling point **104** may be located between first top coupling point **101** and second top coupling point **102**. First top coupling point **101** may be circumferentially separated from second top coupling point **102** by third top coupling point **103** and fourth top coupling point **104**.

(31) In various embodiments, bottom end **131-2** of first outer support member **130-1** may be coupled to front frame **110** at a first bottom coupling point **111** (e.g., a fifth coupling point). Bottom end **132-2** of second outer support member **130-2** may be coupled to front frame **110** at a second bottom coupling point **112** (e.g., a sixth coupling point). Bottom end **141-2** of first inner support member **140-1** may be coupled to front frame **110** at a third bottom coupling point **113** (e.g., a seventh coupling point). Bottom end **142-2** of second inner support member **140-2** may be coupled to front frame **110** at a fourth bottom coupling point **114** (e.g., an eighth coupling point).

(32) First bottom coupling point **111**, second bottom coupling point **112**, third bottom coupling point **113**, and fourth bottom coupling point **114** may each be located on a top bottom of front frame **110**. First bottom coupling point **111**, second bottom coupling point **112**, third bottom coupling point **113**, and fourth bottom coupling point **114** may each comprise separate coupling locations on front frame **110**. For example, each of first bottom coupling point **111**, second bottom coupling point **112**, third bottom coupling point **113**, and fourth bottom coupling point **114** may be circumferentially separated on front frame **110**.

(33) First bottom coupling point **111** may be circumferentially outward from third bottom coupling point **113**. First bottom coupling point **111** may be radially inward from third bottom coupling point **113** and/or fourth bottom coupling point **114**. First bottom coupling point **111** may be colinear with second bottom coupling point **112**. First bottom coupling point **111** may be colinear with first top coupling point **101**.

(34) Second bottom coupling point **112** may be circumferentially outward from fourth bottom coupling point **114**. Second bottom coupling point **112** may be radially inward from third bottom coupling point **113** and/or fourth bottom coupling point **114**. Second bottom coupling point **112** may be colinear with first bottom coupling point **111**. Second bottom coupling point **112** may be colinear with second top coupling point **102**.

(35) Third bottom coupling point **113** may be circumferentially inward from first bottom coupling point **111**. Third bottom coupling point **113** may be radially outward from first bottom coupling point **111** and/or second bottom coupling point **112**. Third bottom coupling point **113** may be colinear with fourth bottom coupling point **114**. Third bottom coupling point **113** may be colinear with third top coupling point **103**.

(36) Fourth bottom coupling point **114** may be circumferentially inward from second bottom coupling point **112**. Fourth bottom coupling point **114** may be radially outward from first bottom coupling point **111** and/or second bottom coupling point **112**. Fourth bottom coupling point **114** may be colinear with third bottom coupling point **113**. Fourth bottom coupling point **114** may be colinear with fourth top coupling point **104**.

(37) Third bottom coupling point **113** and fourth bottom coupling point **114** may be located between first bottom coupling point **111** and second bottom coupling point **112**. First bottom coupling point **111** may be circumferentially separated from second bottom coupling point **112** by third bottom coupling point **113** and fourth bottom coupling point **114**.

(38) In various embodiments, first top coupling point **101** may be coplanar with first bottom coupling point **111**. In various embodiments, second top coupling point **102** may be coplanar with second bottom coupling point **112**. In various embodiments, third top coupling point **103** may be coplanar with third bottom coupling point **113**. In various embodiments, fourth top coupling point **104** may be coplanar with fourth bottom coupling point **114**.

(39) In various embodiments, each coupling (e.g., coupling point) between a support member **120** and front frame **110** may comprise any suitable or desired type of coupling. For example, one or more support members **120** may be fixably coupled or removably coupled to front frame **110**. As a

further example, one or more support members **120** may be coupled to front frame **110** via welding, an adhesive, and/or the like. As a further example, one or more support members **120** may be coupled to front frame **110** using a rope, a weave, a thread, and/or the like.

(40) In various embodiments, each support member **120** may be vertically positioned (e.g., vertically displaced) within chair **100**. One or more support members **120** may be positioned proximate a middle section of chair **100**. Support members **120** may be configured to form a three-dimensional shape. Support members **120** may be configured to form a C-shape. Support members **120** may be configured to form a D-shape. Support members **120** may be configured to form a seat in chair **100**. In that respect, support members **120** may form a first platform configured to support a user sitting in chair **100**, a second platform configured to provide a back support for the user sitting in chair **100**, and/or a third platform configured to provide a top surface (e.g., a roof, a shelter, a shade, etc.) in chair **100**. The first platform may be substantially similar (e.g., in size, shape, surface area, volume, etc.) to the third platform. The second platform may comprise a surface area greater than the first platform and/or the third platform. The first platform and/or the third platform may be axially inward from the second platform (e.g., the second platform may be axially outward from the first platform and/or the third platform). The first platform and/or the third platform may be radially outward from the second platform (e.g., the second platform may be radially inward from the first platform and/or the third platform). The second platform may be at least partially surrounded by the first platform and/or the third platform. The second platform may be surrounded by the first platform, the third platform, first side opening **135**, and/or second side opening **145**.

(41) Each support member **120** may comprise any suitable shape. For example, one or more support members **120** may comprise a curved shape, a bowed shape, and/or the like. In that respect, each end of the one or more support members **120** may be inward relative to a remaining body of each of the one or more support members **120**. As a further example, one or more support members **120** may comprise a symmetrical shape. In various embodiments, one or more of support members **120** may comprise a different shape from one or more of the remaining support members **120**.

(42) In various embodiments, outer support members **130-1**, **130-2** may each comprise a first shape and inner support members **140-1**, **140-2** may each comprise a second shape. The first shape may be different from the second shape. In some embodiments, the first shape may comprise a first vertical length (e.g., a longitudinal length) and the second shape may comprise a second vertical length (wherein a “vertical length” refers to a length measurement from end to end of each respective support member). The first vertical length of the first shape may be different from the second vertical length of the second shape. The first vertical length of the first shape may be smaller than the second vertical length of the second shape (e.g., the second vertical length of the second shape may be bigger than the first vertical length of the first shape) (e.g., as depicted in FIG. 1A).

(43) In various embodiments, first outer support member **130-1** may comprise a first shape, second outer support member **130-2** may comprise a second shape, first inner support members **140-1** may comprise a third shape, and second inner support members **140-2** may comprise a fourth shape. The first shape may be different from the third shape and/or the fourth shape. The first shape may be similar to the second shape. The first shape may be the same as the second shape. The second shape may be different from the third shape and/or the fourth shape. The third shape may be different from the first shape and/or the second shape. The third shape may be similar to the fourth shape. The third shape may be the same as the fourth shape. The fourth shape may be different from the first shape and/or the second shape.

(44) In various embodiments, one or more ends of one or more support members **120** may be displaced (e.g., disposed, positioned, curved, bent, etc.) at an angle relative to a remaining body (e.g., a middle portion) of the respective support member **120**. For example, first end **131-1** may be displaced at a first angle relative to a middle portion of first outer support member **130-1** and

second end **131-2** may be displaced at a second angle relative to a middle portion of first outer support member **130-1**. As a further example, first end **132-1** may be displaced at a third angle relative to a middle portion of second outer support member **130-2** and second end **132-2** may be displaced at a fourth angle relative to a middle portion of second outer support member **130-2**. As a further example, first end **141-1** may be displaced at a fifth angle relative to a middle portion of first inner support member **140-1** and second end **141-2** may be displaced at a sixth angle relative to a middle portion of first inner support member **140-1**. As a further example, first end **142-1** may be displaced at a seventh angle relative to a middle portion of second inner support member **140-2** and second end **142-2** may be displaced at an eighth angle relative to a middle portion of second inner support member **140-2**.

(45) In various embodiments, the first angle, the second angle, the third angle, the fourth angle, the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle may each be greater than about 90°. The first angle, the second angle, the third angle, the fourth angle, the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle may each be less than about 180°. The first angle, the second angle, the third angle, the fourth angle, the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle may each be greater than about 90° and less than about 180° (wherein “about” as used in this paragraph refers only to +/-) 5°.

(46) In various embodiments, one or more of the first angle, the second angle, the third angle, and/or the fourth angle may be different from one or more of the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle. In that regard, the angles of outer support members **130-1**, **130-2** may be different from the angles of inner support members **140-1**, **140-2**. In various embodiments, one or more of the first angle, the second angle, the third angle, and/or the fourth angle may be less than one or more of the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle. In that regard, the angles of outer support members **130-1**, **130-2** may be less than the angles of inner support members **140-1**, **140-2**.

(47) In various embodiments, one or more of the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle may be different from one or more of the first angle, the second angle, the third angle, and/or the fourth angle. In that regard, the angles of inner support members **140-1**, **140-2** may be different from the angles of outer support members **130-1**, **130-2**. In various embodiments, one or more of the fifth angle, the sixth angle, the seventh angle, and/or the eighth angle may be greater than one or more of the first angle, the second angle, the third angle, and/or the fourth angle. In that regard, the angles of inner support members **140-1**, **140-2** may be greater than the angles of outer support members **130-1**, **130-2**.

(48) In various embodiments, the first angle and the second angle of first outer support member **130-1** may be about equal (e.g., the first angle is about equal to the second angle, etc.). The third angle and the fourth angle of second outer support member **130-2** may be about equal (e.g., the third angle is about equal to the fourth angle, etc.). The first angle of first outer support member **130-1** may be about equal to one or more of the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2** (e.g., the first angle is about equal to the second angle, the first angle is about equal to the third angle, the first angle is about equal to the fourth angle, etc.). The second angle of first outer support member **130-1** may be about equal to one or more of the first angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2** (e.g., the second angle is about equal to the first angle, the second angle is about equal to the third angle, the second angle is about equal to the fourth angle, etc.). The third angle of second outer support member **130-2** may be about equal to one or more of the first angle of first outer support member **130-1**, second angle of first outer support member **130-1**, and/or the fourth angle of second outer support member **130-2** (e.g., the third angle is about equal to the first angle, the third angle is about equal to the second angle, the third angle is about equal to the fourth angle, etc.). The fourth angle of second outer support

member **130-2** may be about equal to one or more of the first angle of first outer support member **130-1**, second angle of first outer support member **130-1**, and/or the third angle of second outer support member **130-2** (e.g., the fourth angle is about equal to the first angle, the fourth angle is about equal to the second angle, the fourth angle is about equal to the third angle, etc.) (wherein “about” as used in this paragraph refers only to +/-) 5°.

(49) In various embodiments, the fifth angle and the sixth angle of first inner support member **140-1** may be about equal (e.g., the fifth angle is about equal to the sixth angle, etc.). The seventh angle and the eighth angle of second inner support member **140-2** may be about equal (e.g., the seventh angle is about equal to the eighth angle, etc.). The fifth angle of first inner support member **140-1** may be about equal to one or more of the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2** (e.g., the fifth angle is about equal to the sixth angle, the fifth angle is about equal to the seventh angle, the fifth angle is about equal to the eighth angle, etc.). The sixth angle of first inner support member **140-1** may be about equal to one or more of the fifth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2** (e.g., the sixth angle is about equal to the fifth angle, the sixth angle is about equal to the seventh angle, the sixth angle is about equal to the eighth angle, etc.). The seventh angle of first inner support member **140-1** may be about equal to one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, and/or the eighth angle of second inner support member **140-2** (e.g., the seventh angle is about equal to the fifth angle, the seventh angle is about equal to the sixth angle, the seventh angle is about equal to the eighth angle, etc.). The eighth angle of first inner support member **140-1** may be about equal to one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, and/or the seventh angle of second inner support member **140-2** (e.g., the eighth angle is about equal to the fifth angle, the eighth angle is about equal to the sixth angle, the eighth angle is about equal to the seventh angle, etc.) (wherein “about” as used in this paragraph refers only to +/-) 5°.

(50) In various embodiments, the first angle of first outer support member **130-1** may be different from one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**. In various embodiments, the first angle of first outer support member **130-1** may be less than one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**.

(51) In various embodiments, the second angle of first outer support member **130-1** may be different from one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**. In various embodiments, the second angle of first outer support member **130-1** may be less than one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**.

(52) In various embodiments, the third angle of second outer support member **130-2** may be different from one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**. In various embodiments, the third angle of second outer support member **130-2** may be less than one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**.

(53) In various embodiments, the fourth angle of second outer support member **130-2** may be different from one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**. In various embodiments, the fourth angle of second outer support member **130-2** may be less than one or more of the fifth angle of first inner support member **140-1**, the sixth angle of first inner support member **140-1**, the seventh angle of second inner support member **140-2**, and/or the eighth angle of second inner support member **140-2**.

(54) In various embodiments, the fifth angle of first inner support member **140-1** may be different from one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**. In various embodiments, the fifth angle of first inner support member **140-1** may be greater than one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**.

(55) In various embodiments, the sixth angle of first inner support member **140-1** may be different from one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**. In various embodiments, the sixth angle of first inner support member **140-1** may be greater than one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**.

(56) In various embodiments, the seventh angle of second inner support member **140-2** may be different from one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**. In various embodiments, the seventh angle of second inner support member **140-2** may be greater than one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**.

(57) In various embodiments, the eighth angle of second inner support member **140-2** may be different from one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**. In various embodiments, the eighth angle of second inner support member **140-2** may be greater than one or more of the first angle of first outer support member **130-1**, the second angle of first outer support member **130-1**, the third angle of second outer support member **130-2**, and/or the fourth angle of second outer support member **130-2**.

(58) In various embodiments, each support member **120** may comprise any suitable and/or desired material. For example, each support member **120** may comprise a rigid material. Each support member **120** may comprise a wood material. Each support member **120** may comprise a metal material, such as stainless steel, steel, aluminum, and/or the like. In some embodiments, each support member **120** may comprise a reinforced steel material (e.g., rebar). In some embodiments, each support member **120** may comprise an about 3/8-inch (0.9525 cm) steel rebar (wherein “about” as used in this sentence refers only to ± 0.01 inches (0.0254 cm)). In some embodiments, support members **120** may comprise a same material as front frame **110**. In some embodiments, support members **120** may comprise a material having a diameter less than a diameter of a material of front frame **110** (e.g., front frame **110** may comprise a first material having a first diameter,

support members **120** may comprise a second material having a second diameter, and the first diameter may be greater than the second diameter).

(59) In various embodiments, a first distance may be defined between first outer support member **130-1** and second outer support member **130-2**. The first distance may vary in the vertical direction (e.g., the first distance may vary radially in chair **100**). For example, the first distance proximate the top ends of first outer support member **130-1** and second outer support member **130-2** may be different from the first distance proximate a middle portion of first outer support member **130-1** and second outer support member **130-2**. The first distance proximate the top ends of first outer support member **130-1** and second outer support member **130-2** may be greater than the first distance proximate a middle portion of first outer support member **130-1** and second outer support member **130-2**. As a further example, the first distance proximate the bottom ends of first outer support member **130-1** and second outer support member **130-2** may be different from the first distance proximate a middle portion of first outer support member **130-1** and second outer support member **130-2**. The first distance proximate the bottom ends of first outer support member **130-1** and second outer support member **130-2** may be greater than the first distance proximate a middle portion of first outer support member **130-1** and second outer support member **130-2**. As a further example, the first distance proximate the top ends of first outer support member **130-1** and second outer support member **130-2** may be substantially similar to the first distance proximate the bottom ends of first outer support member **130-1** and second outer support member **130-2**.

(60) In various embodiments, a second distance may be defined between first inner support member **140-1** and second inner support member **140-2**. The second distance may vary in the vertical direction (e.g., the second distance may vary radially in chair **100**). For example, the second distance proximate the top ends of first inner support member **140-1** and second inner support member **140-2** may be different from the second distance proximate a middle portion of first inner support member **140-1** and second inner support member **140-2**. The second distance proximate the top ends of first inner support member **140-1** and second inner support member **140-2** may be greater than the second distance proximate a middle portion of first inner support member **140-1** and second inner support member **140-2**. As a further example, the second distance proximate the bottom ends of first inner support member **140-1** and second inner support member **140-2** may be different from the second distance proximate a middle portion of first inner support member **140-1** and second inner support member **140-2**. The second distance proximate the bottom ends of first inner support member **140-1** and second inner support member **140-2** may be greater than the second distance proximate a middle portion of first inner support member **140-1** and second inner support member **140-2**. As a further example, the second distance proximate the top ends of first inner support member **140-1** and second inner support member **140-2** may be substantially similar to the second distance proximate the bottom ends of first inner support member **140-1** and second inner support member **140-2**.

(61) In various embodiments, a third distance may be defined between first outer support member **130-1** and first inner support member **140-1**. The third distance may vary in the vertical direction (e.g., the third distance may vary radially in chair **100**). For example, the third distance proximate the top ends of first outer support member **130-1** and first inner support member **140-1** may be different from the third distance proximate a middle portion of first outer support member **130-1** and first inner support member **140-1**. The third distance proximate the top ends of first outer support member **130-1** and first inner support member **140-1** may be greater than the third distance proximate a middle portion of first outer support member **130-1** and first inner support member **140-1**. As a further example, the third distance proximate the bottom ends of first outer support member **130-1** and first inner support member **140-1** may be different from the third distance proximate a middle portion of first outer support member **130-1** and first inner support member **140-1**. The third distance proximate the bottom ends of first outer support member **130-1** and first inner support member **140-1** may be greater than the third distance proximate a middle portion of

first outer support member **130-1** and first inner support member **140-1**. As a further example, the third distance proximate the top ends of first outer support member **130-1** and first inner support member **140-1** may be substantially similar to the third distance proximate the bottom ends of first outer support member **130-1** and first inner support member **140-1**.

(62) In various embodiments, a fourth distance may be defined between second inner support member **140-2** and second outer support member **130-2**. The fourth distance may vary in the vertical direction (e.g., the fourth distance may vary radially in chair **100**). For example, the fourth distance proximate the top ends of second inner support member **140-2** and second outer support member **130-2** may be different from the fourth distance proximate a middle portion of second inner support member **140-2** and second outer support member **130-2**. The fourth distance proximate the top ends of second inner support member **140-2** and second outer support member **130-2** may be greater than the fourth distance proximate a middle portion of second inner support member **140-2** and second outer support member **130-2**. As a further example, the fourth distance proximate the bottom ends of second inner support member **140-2** and second outer support member **130-2** may be different from the fourth distance proximate a middle portion of second inner support member **140-2** and second outer support member **130-2**. The fourth distance proximate the bottom ends of second inner support member **140-2** and second outer support member **130-2** may be greater than the fourth distance proximate a middle portion of second inner support member **140-2** and second outer support member **130-2**. As a further example, the fourth distance proximate the top ends of second inner support member **140-2** and second outer support member **130-2** may be substantially similar to the fourth distance proximate the bottom ends of second inner support member **140-2** and second outer support member **130-2**.

(63) In various embodiments, chair **100** may comprise one or more cross members **150**. Each cross member **150** may be coupled to one or more support members **120**. Cross members **150** may be configured to provide structural support and/or reinforcement to chair **100**. Cross members **150** may be horizontally positioned in chair **100**. Cross members **150** may be positioned perpendicular to one or more support members **120**. One or more cross members **150** may be parallel to one or more other cross members **150**.

(64) In various embodiments, chair **100** may comprise any suitable number of cross members **150**. For example, chair **100** may comprise a first cross member **150-1**, a second cross member **150-2**, and/or a third cross member **150-3**. First cross member **150-1** may be positioned proximate a top end of one or more support members **120**. Second cross member **150-2** may be positioned proximate a middle portion of one or more support members **120**. Third cross member **150-3** may be positioned proximate a bottom end of one or more support members **120**. First cross member **150-1** may be positioned radially upward (e.g., outward) from second cross member **150-2** and/or third cross member **150-3**. Second cross member **150-2** may be positioned between first cross member **150-1** and third cross member **150-3**. Third cross member **150-3** may be radially downward (e.g., outward) from second cross member **150-2** and/or first cross member **150-1**. In some embodiments, first cross member **150-1** may be symmetrical with third cross member **150-3**.

(65) In various embodiments, first cross member **150-1** may be coupled to one or more of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. For example, first cross member **150-1** may be coupled to first outer support member **130-1** at a location radially inward from first end **131-1** of first outer support member **130-1**. First cross member **150-1** may be coupled to first inner support member **140-1** at a location radially inward from first end **141-1** of first inner support member **140-1**. First cross member **150-1** may be coupled to second inner support member **140-2** at a location radially inward from first end **142-1** of second inner support member **140-2**. First cross member **150-1** may be coupled to second outer support member **130-2** at a location radially inward from first end **132-1** of second outer support member **130-2**.

(66) In some embodiments, first cross member **150-1** may comprise a single component (e.g., a

unitary component. In that respect, the single component of first cross member **150-1** may extend between and couple to each of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. In some embodiments, first cross member **150-1** may comprise a plurality of components. For example, first cross member **150-1** may comprise a first part, a second part, and/or a third part. Each part may comprise separate objects. The first part may extend between and couple to first outer support member **130-1** and first inner support member **140-1**. The second part may extend between and couple to first inner support member **140-1** and second inner support member **140-2**. The third part may extend between and couple to second inner support member **140-2** and second outer support member **130-2**.

(67) In various embodiments, second cross member **150-2** may be coupled to one or more of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. For example, second cross member **150-2** may be coupled to first outer support member **130-1** at a location proximate a middle portion of first outer support member **130-1**. Second cross member **150-2** may be coupled to first inner support member **140-1** at a location proximate a middle portion of first inner support member **140-1**. Second cross member **150-2** may be coupled to second inner support member **140-2** at a location proximate a middle portion of second inner support member **140-2**. Second cross member **150-2** may be coupled to second outer support member **130-2** at a location proximate a middle portion of second outer support member **130-2**.

(68) In some embodiments, second cross member **150-2** may comprise a single component (e.g., a unitary component). In that respect, the single component of second cross member **150-2** may extend between and couple to each of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. In some embodiments, second cross member **150-2** may comprise a plurality of components. For example, second cross member **150-2** may comprise a first part, a second part, and/or a third part. Each part may comprise separate objects. The first part may extend between and couple to first outer support member **130-1** and first inner support member **140-1**. The second part may extend between and couple to first inner support member **140-1** and second inner support member **140-2**. The third part may extend between and couple to second inner support member **140-2** and second outer support member **130-2**.

(69) In various embodiments, third cross member **150-3** may be coupled to one or more of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. For example, third cross member **150-3** may be coupled to first outer support member **130-1** at a location radially inward from second end **131-1** of first outer support member **130-1**. Third cross member **150-3** may be coupled to first inner support member **140-1** at a location radially inward from second end **141-2** of first inner support member **140-1**. Third cross member **150-3** may be coupled to second inner support member **140-2** at a location radially inward from second end **142-2** of second inner support member **140-2**. Third cross member **150-3** may be coupled to second outer support member **130-2** at a location radially inward from second end **132-2** of second outer support member **130-2**.

(70) In some embodiments, third cross member **150-3** may comprise a single component (e.g., a unitary component). In that respect, the single component of third cross member **150-3** may extend between and couple to each of first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and/or second outer support member **130-2**. In some embodiments, third cross member **150-3** may comprise a plurality of components. For example, third cross member **150-3** may comprise a first part, a second part, and/or a third part. Each part may comprise separate objects. The first part may extend between and couple to first outer support member **130-1** and first inner support member **140-1**. The second part may extend between and couple to first inner support member **140-1** and second inner support member **140-2**. The third part

may extend between and couple to second inner support member **140-2** and second outer support member **130-2**.

(71) In various embodiments, each coupling (e.g., coupling point) between a cross member **150** and a support member **120** may comprise any suitable or desired type of coupling. For example, one or more cross members **150** may be fixably coupled or removably coupled to a respective support member **120**. As a further example, one or more cross members **150** may be coupled to a respective support member **120** via welding, an adhesive, and/or the like. As a further example, one or more cross members **150** may be coupled to a respective support member **120** using a rope, a weave, a thread, and/or the like.

(72) In various embodiments, each cross member **150** may comprise any suitable and/or desired material. For example, each cross member **150** may comprise a rigid material. Each cross member **150** may comprise a wood material. Each cross member **150** may comprise a metal material, such as stainless steel, steel, aluminum, and/or the like. In some embodiments, one or more cross member **150** may comprise a ¼-inch (0.635 cm) smooth rolled steel rod. In some embodiments, one or more cross member **150** may comprise a reinforced steel material (e.g., rebar). In some embodiments, one or more cross members **150** may comprise an about ⅜-inch (0.9525 cm) steel rebar. In some embodiments, cross members **150** may comprise a same material as front frame **110** and/or support members **120**. In some embodiments, cross members **150** may comprise a material having a diameter less than a diameter of a material of front frame **110** (e.g., front frame **110** may comprise a first material having a first diameter, cross members **150** may comprise a third material having a third diameter, and the first diameter may be greater than the third diameter). In some embodiments, cross members **150** may comprise a material having a diameter about equal to a diameter of a material of support members **120** (e.g., support members **120** may comprise a second material having a second diameter, cross members **150** may comprise a third material having a third diameter, and the third diameter may be about equal to the second diameter) (wherein “about” as used in this sentence refers only to ± 0.01 inches (0.0254 cm)).

(73) In various embodiments, chair **100** may comprise one or more armrests **160**. For example, chair **100** may comprise a first armrest **160-1** (e.g., a right armrest) and a second armrest **160-2**. Each armrest **160** may be sized and shaped to receive an arm (or a portion of an arm) of a user sitting within chair **100**. For example, while sitting in chair **100** a user may rest her right arm on first armrest **160-1** and/or her left arm on second armrest **160-2**. In some embodiments, a user of chair **100** may also position or place an object on an armrest **160** while sitting in chair **100**.

(74) In various embodiments, first armrest **160-1** may be positioned on a right side of chair **100** between front frame **110** and first outer support member **130-1**. First armrest **160-1** may be coupled at a front end (e.g., a first armrest front end) to front frame **110**. First armrest **160-1** may be coupled at a rear end (e.g., a first armrest rear end) to first outer support member **130-1**. In some embodiments, first armrest **160-1** may be positioned perpendicular to one or both of front frame **110** and/or first outer support member **130-1**.

(75) In various embodiments, first armrest **160-1** may comprise an inner armrest member **165-1** and an outer armrest member **167-1**. Inner armrest member **165-1** and outer armrest member **167-1** may define a perimeter of first armrest **160-1**. Inner armrest member **165-1** may be positioned inward from outer armrest member **167-1**. Outer armrest member **167-1** may be positioned outward from inner armrest member **165-1**. In some embodiments, outer armrest member **167-1** may be parallel to inner armrest member **165-1**. In some embodiments, outer armrest member **167-1** may be vertically offset from inner armrest member **165-1**.

(76) In various embodiments, inner armrest member **165-1** and outer armrest member **167-2** may comprise different shapes (e.g., inner armrest member **165-1** may comprise a first shape, outer armrest member **167-1** may comprise a second shape, and the first shape may be different from the second shape). For example, inner armrest member **165-1** may comprise a straight shape (e.g., a straight line) and outer armrest member **167-1** may comprise a curved shape (e.g., a bent shape, a

bowed shape, etc.). The curved shape of outer armrest member **167-1** may curve outward relative to inner armrest member **165-1**.

(77) In various embodiments, each of inner armrest member **165-1** and outer armrest member **167-2** may be coupled directly to front frame **110** and/or first outer support member **130-1**. In various embodiments, one of inner armrest member **165-1** and outer armrest member **167-2** may be coupled to the other of inner armrest member **165-1** and outer armrest member **167-2**, and the other of inner armrest member **165-1** and outer armrest member **167-2** may be coupled directly to front frame **110** and/or first outer support member **130-1**.

(78) In various embodiments, each coupling (e.g., coupling point) between an armrest **160** and a support member **120** and/or front frame **110** may comprise any suitable or desired type of coupling. For example, armrests **160** may be fixably coupled or removably coupled to a respective support member **120** and/or front frame **110**. As a further example, armrests **160** may be coupled to a respective support member **120** and/or front frame **110** via welding, an adhesive, and/or the like. As a further example, armrests **160** may be coupled to a respective support member **120** and/or front frame **110** using a rope, a weave, a thread, and/or the like.

(79) In various embodiments, each armrest **160** may comprise any suitable and/or desired material. For example, each armrest **160** may comprise a rigid material. Each armrest **160** may comprise a wood material. Each armrest **160** may comprise a metal material, such as stainless steel, steel, aluminum, and/or the like. In some embodiments, each armrest **160** may comprise a reinforced steel material (e.g., rebar). In some embodiments, each armrest **160** may comprise an about $\frac{3}{8}$ -inch (0.9525 cm) steel rebar. In some embodiments, armrests **160** may comprise a same material as front frame **110**, support members **120**, and/or cross members **150**. In some embodiments, armrests **160** may comprise a material having a diameter less than a diameter of a material of front frame **110** (e.g., front frame **110** may comprise a first material having a first diameter, armrests **160** may comprise a fourth material having a fourth diameter, and the first diameter may be greater than the fourth diameter). In some embodiments, armrests **160** may comprise a material having a diameter about equal to a diameter of a material of support members **120** and/or cross members **150** (e.g., support members **120** may comprise a second material having a second diameter, cross members **150** may comprise a third material having a third diameter, armrests **160** may comprise a fourth material having a fourth diameter, and the fourth diameter may be about equal to the second diameter and the third diameter) (wherein “about” as used in this sentence refers only to ± 0.01 inches (0.0254 cm)).

(80) In various embodiments, chair **100** may comprise a first side opening **135** (e.g., a right side opening) and a second side opening **145** (e.g., a left side opening). Each side opening **135**, **145** may be in fluid communication with an interior of chair **100** and front opening **115** (e.g., first side opening **135**, an interior of chair **100**, front opening **115**, and second side opening **145** are each and all in fluid communication). First side opening **135** may be defined by front frame **110** and first outer support member **130-1** (e.g., a perimeter of first side opening **135** may be defined by front frame **110** and first outer support member **130-1**). First side opening **135** may be defined by a portion of front frame **110** between first end **131-1** and second end **131-2** of first outer support member **130-1**, and first outer support member **130-1**. Second side opening **145** may be defined by front frame **110** and second outer support member **130-2** (e.g., a perimeter of second side opening **145** may be defined by front frame **110** and second outer support member **130-2**). Second side opening **145** may be defined by a portion of front frame **110** between first end **132-1** and second end **132-2** of second outer support member **130-2**, and second outer support member **130-2**.

(81) In various embodiments, first side opening **135** may be intersected by first armrest **160-1**. In that regard, first side opening **135** may comprise a plurality of different openings (e.g., sections) created by the intersection of first armrest **160-1** through first side opening **135**. For example, first side opening **135** may comprise a first side top opening **137-1** and a first side bottom opening **137-2**. First side top opening **137-1** may define first side opening **135** above first armrest **160-1**. First

side bottom opening **137-2** may define first side opening **135** below first armrest **160-1**.

(82) First side top opening **137-1** may be defined by front frame **110**, first outer support member **130-1**, and a top surface of first armrest **160-1** (e.g., a perimeter of first side top opening **137-1** may be defined by front frame **110**, first outer support member **130-1**, and a top surface of first armrest **160-1**). First side top opening **137-1** may be defined by a portion (e.g., a first frame portion) of front frame **110** between the coupling of first end **131-1** of first outer support member **130-1** to front frame **110** and the coupling of first armrest **160-1** to front frame **110**, a portion (e.g., a first member portion) of first outer support member **130-1** between the coupling of first end **131-1** of first outer support member **130-1** to front frame **110** and the coupling of first armrest **160-1** to first outer support member **130-1**, and a top surface of first armrest **160-1**.

(83) First side bottom opening **137-2** may be defined by front frame **110**, first outer support member **130-1**, and a bottom surface of first armrest **160-1** (e.g., a perimeter of first side bottom opening **137-2** may be defined by front frame **110**, first outer support member **130-1**, and a bottom surface of first armrest **160-1**). First side bottom opening **137-2** may be defined by a portion (e.g., a second frame portion) of front frame **110** between the coupling of second end **131-2** of first outer support member **130-1** to front frame **110** and the coupling of first armrest **160-1** to front frame **110**, a portion (e.g., a second member portion) of first outer support member **130-1** between the coupling of second end **131-2** of first outer support member **130-1** to front frame **110** and the coupling of first armrest **160-1** to first outer support member **130-1**, and a bottom surface of first armrest **160-1**.

(84) In various embodiments, first side top opening **137-1** and first side bottom opening **137-2** may comprise different surface areas. For example, first side top opening **137-1** may comprise a first surface area and first side bottom opening **137-2** may comprise a second surface area. The first surface area may be greater than the second surface area. The first surface area may be twice as large as the second surface area. The first surface area may be greater than the second surface area but less than twice as large as the second surface area. The first surface area may be between 10% and 50% larger than the second surface area. The first surface area may be between 50% and 100% larger than the second surface area. The first surface area may be greater than 100% larger than the second surface area.

(85) In various embodiments, second side opening **145** may be intersected by second armrest **160-2**. In that regard, second side opening **145** may comprise a plurality of different openings (e.g., sections) created by the intersection of second armrest **160-2** through second side opening **145**. For example, second side opening **145** may comprise a second side top opening **147-1** and a second side bottom opening **147-2**. Second side top opening **147-1** may define second side opening **145** above second armrest **160-2**. Second side bottom opening **147-2** may define second side opening **145** below second armrest **160-2**.

(86) Second side top opening **147-1** may be defined by front frame **110**, second outer support member **130-2**, and a top surface of second armrest **160-2** (e.g., a perimeter of second side top opening **147-1** may be defined by front frame **110**, second outer support member **130-2**, and a top surface of second armrest **160-2**). Second side top opening **147-1** may be defined by a portion (e.g., a third frame portion) of front frame **110** between the coupling of first end **132-1** of second outer support member **130-2** to front frame **110** and the coupling of second armrest **160-2** to front frame **110**, a portion (e.g., a third member portion) of second outer support member **130-2** between the coupling of first end **132-1** of second outer support member **130-2** to front frame **110** and the coupling of second armrest **160-2** to second outer support member **130-2**, and a top surface of second armrest **160-2**.

(87) Second side bottom opening **147-2** may be defined by front frame **110**, second outer support member **130-2**, and a bottom surface of second armrest **160-2** (e.g., a perimeter of second side bottom opening **147-2** may be defined by front frame **110**, second outer support member **130-2**, and a bottom surface of second armrest **160-2**). Second side bottom opening **147-2** may be defined by a

portion (e.g., a fourth frame portion) of front frame **110** between the coupling of second end **132-2** of second outer support member **130-2** to front frame **110** and the coupling of second armrest **160-2** to front frame **110**, a portion (e.g., a fourth member portion) of second outer support member **130-2** between the coupling of second end **132-2** of second outer support member **130-2** to front frame **110** and the coupling of second armrest **160-2** to second outer support member **130-2**, and a bottom surface of second armrest **160-2**.

(88) In various embodiments, second side top opening **147-1** and second side bottom opening **147-2** may comprise different surface areas. For example, second side top opening **147-1** may comprise a third surface area and second side bottom opening **147-2** may comprise a fourth surface area. The third surface area may be greater than the fourth surface area. The third surface area may be twice as large as the fourth surface area. The third surface area may be greater than the fourth surface area but less than twice as large as the fourth surface area. The third surface area may be between 10% and 50% larger than the fourth surface area. The third surface area may be between 50% and 100% larger than the fourth surface area. The third surface area may be greater than 100% larger than the fourth surface area.

(89) In various embodiments, first side top opening **137-1** may be similar to second side top opening **147-1**. First side top opening **137-1** and second side top opening **147-1** may share similar sizes, shapes, and physical characteristics. First side top opening **137-1** may be symmetrical to second side top opening **147-1**. The first surface area of first side top opening **137-1** may be about the same as the third surface area of second side top opening **147-1**. The first surface area of first side top opening **137-1** may be greater than the fourth surface area of second side bottom opening **147-2**. The third surface area of second side top opening **147-1** may be greater than the second surface area of first side bottom opening **137-2**.

(90) In various embodiments, first side bottom opening **137-2** may be similar to second side bottom opening **147-2**. First side bottom opening **137-2** and second side bottom opening **147-2** may share similar sizes, shapes, and physical characteristics. First side bottom opening **137-2** may be symmetrical to second side bottom opening **147-2**. The second surface area of first side bottom opening **137-2** may be about the same as the fourth surface area of second side bottom opening **147-2**. The second surface area of first side bottom opening **137-2** may be less than the third surface area of second side top opening **147-1**. The fourth surface area of second side bottom opening **147-2** may be less than the first surface area of first side top opening **137-1**.

(91) In various embodiments, chair **100** may comprise an anchor **170**. Anchor **170** may be configured to allow chair **100** to be suspended (e.g., hung) from an object. For example, anchor **170** may be configured to couple to a chain, a rope, or the like suspended from a stationary object. As a further example, anchor may be configured to couple to a suspension frame, a stationary object, or the like.

(92) Anchor **170** may be coupled to a top portion of front frame **110**. Anchor **170** may be coupled to front frame **110** between third top coupling point **103** and fourth top coupling point **104**. In various embodiments, a center point of anchor **170** (e.g., an anchor center point) may be aligned with a center point between third top coupling point **103** and fourth top coupling point **104**. In various embodiments, anchor **170** may be coupled to front frame **110** at a location equidistant from each of third top coupling point **103** and fourth top coupling point **104**. In various embodiments, anchor **170** may couple to front frame **110** at a location independent of first top coupling point **101**, second top coupling point **102**, third top coupling point **103**, and fourth top coupling point **104**. In that regard, the coupling of anchor **170** to front frame **110** may be a different location than each of first top coupling point **101**, second top coupling point **102**, third top coupling point **103**, and fourth top coupling point **104**.

(93) In various embodiments, each coupling (e.g., coupling point) between anchor **170** and front frame **110** may comprise any suitable or desired type of coupling. For example, anchor **170** may be fixably coupled or removably coupled to front frame **110**. As a further example, anchor **170** may be

coupled to front frame **110** via welding, an adhesive, and/or the like. As a further example, anchor **170** may be coupled to front frame **110** using a rope, a weave, a thread, and/or the like.

(94) In various embodiments, anchor **170** may be rotatably coupled to front frame **110**. A rotatable coupling may enable chair **100** to rotate (e.g., swivel, turn, etc.) while anchor **170** is coupled to an object to suspend chair **100**. Anchor **170** may comprise any suitable component to enable the rotatable coupling, such as, for example, a ball bearing mount, a swivel mount, and/or the like.

(95) In various embodiments, anchor **170** may comprise any suitable or desired shape. Anchor **170** may comprise a shape configured to form an opening in response to anchor **170** being coupled to front frame **110**. For example, anchor **170** may comprise a U-shape, a C-shape, a D-shape, and/or the like.

(96) In various embodiments, anchor **170** may comprise any suitable and/or desired material. For example, anchor **170** may comprise a rigid material. Anchor **170** may comprise a wood material. Anchor **170** may comprise a metal material, such as stainless steel, steel, aluminum, and/or the like. In some embodiments, anchor **170** may comprise a reinforced steel material (e.g., rebar). In some embodiments, anchor **170** may comprise an about $\frac{3}{8}$ -inch (0.9525 cm) steel rebar. In some embodiments, anchor **170** may comprise a same material as front frame **110**, support members **120**, cross members **150**, and/or armrests **160**. In some embodiments, anchor **170** may comprise a material having a diameter less than a diameter of a material of front frame **110** (e.g., front frame **110** may comprise a first material having a first diameter, anchor **170** may comprise a fifth material having a fifth diameter, and the first diameter may be greater than the fifth diameter). In some embodiments, anchor **170** may comprise a material having a diameter about equal to a diameter of a material of support members **120**, cross members **150**, and/or armrests **160** (e.g., support members **120** may comprise a second material having a second diameter, cross members **150** may comprise a third material having a third diameter, armrests **160** may comprise a fourth material having a fourth diameter, anchor **170** may comprise a fifth material having a fifth diameter, and the fifth diameter may be about equal to the second diameter, the third diameter, and the fourth diameter) (wherein “about” as used in this sentence refers only to ± 0.01 inches (0.0254 cm)).

(97) In various embodiments, and with reference to FIGS. 2A and 2B, chair **100** may be configured to transition between a rest position (e.g., a first position, an open position, etc.) to a load position (e.g., a second position, a seating position, etc.). As previously discussed, chair **100** may be configured to suspend from an external support structure **275**. External support structure **275** may comprise any object capable of coupling to and/or supporting chair **100**. For example, external support structure **275** may comprise a frame, a tree, a ceiling, a building beam, and/or the like. A connecting structure **277** may be coupled at a first end to external support structure **275** and at a second end to anchor **170** of chair **100**. Connecting structure **277** may comprise any suitable material, component, and/or the like configured to suspend chair **100** from external support structure **275**. For example, connecting structure **277** may comprise a rope, a chain, a linking structure, and/or the like. In some embodiments, chair **100**, external support structure **275**, and/or connecting structure **277** may be collectively referred to as a chair system (e.g., a hanging chair system, a chair support system, etc.). In that regard, a chair system may comprise chair **100**, external support structure **275**, and/or connecting structure **277**.

(98) With reference to FIG. 2A, chair **100** is depicted in the rest position. In the rest position, a bottom portion of front frame **110** may be tilted axially forward. For example, the bottom portion of front frame **110** may be axially forward a top portion of front frame **110** (e.g., the top portion of front frame **110** is axially rearward the bottom portion of front frame **110**). In the rest position, the top portion of front frame **110** and the bottom portion of front frame **110** may be misaligned (e.g., not aligned within a straight vertical plane relative to anchor **170** and connecting structure **277**). In the rest position, armrests **160** may not be parallel to a ground (e.g., a surface chair **100** is suspended over) and/or to external support structure **275**.

(99) With reference to FIG. 2B, chair **100** is depicted in a load position. Chair **100** may be configured to transition from the rest position to the load position in response to chair **100** receiving a load. As discussed herein, a “load” may refer to weight being transferred to an interior of chair **100**. For example, a user sitting within chair **100** may transfer a load to chair **100**. As a further example, a user placing an object with weight into an interior of chair **100** may transfer a load to chair **100**. Chair **100** may comprise a different orientation in the load position relative to the rest position (e.g., chair **100** comprises a first orientation in the rest position, chair **100** comprises a second orientation in the load position, and the first orientation is different from the second orientation).

(100) In the load position, a bottom portion of front frame **110** may be tilted axially rearward relative to chair **100** in the rest position. In the load position, the top portion of front frame **110** and the bottom portion of front frame **110** may be substantially aligned (e.g., substantially aligned within a straight vertical plane relative to anchor **170** and connecting structure **277**). In the load position, the bottom portion of front frame **110** may be closer in axially proximity to the top portion of front frame **110** compared to chair **100** in the rest position. In the load position, armrests **160** may be substantially parallel to a ground (e.g., a surface chair **100** is suspended over) and/or to external support structure **275**.

(101) In various embodiments, by transitioning from the rest position to the load position chair **100** may be configured optimize comfort, recline, and body position for a user sitting within chair **100** (e.g., in the load position). In that regard, chair **100** may be sized, shaped, and oriented in consideration of the difference in weight of chair **100** in the rest position compared to the load position. By offering a different orientation in the rest position, chair **100** may transition to a more optimal position for user comfort in response to the user sitting in chair **100** (and transitioning to the load state).

(102) In various embodiments, and with reference to FIG. 3, a chair **300** may comprise one or more surface coverings. Chair **300** may be similar to, or comprise similar components as, chair **100**, with brief reference to FIGS. 1A-1C. The one or more surface coverings may be coupled to one or more frames and/or members of chair **300**. In that respect, the one or more surface coverings may be configured to form one or more surfaces (e.g., platforms, seats, etc.) of chair **300**. The one or more surface coverings may also be configured to at least partially cover (e.g., obstruct) surfaces of the one or more frames and/or members of chair **300**. As shown in FIG. 3, support members **120**, cross members **150** (e.g., first cross member **150-1**, second cross member **150-2**, third cross member **150-3**), and armrests **160** (e.g., first armrest **160-1**, second armrest **160-2**) are depicted in dashed lines to show the relative positions of each component under a respective surface covering. Although not depicted in FIG. 3, in some embodiments, front frame **110** and/or anchor **170** may also be covered by and/or coupled to a surface covering.

(103) In various embodiments, chair **300** may comprise a support covering **325**. Support covering **325** may be coupled to an outer surface of support members **120**. Support covering **325** may be coupled between one or more support members **120**. Support covering **325** may be coupled to support members **120** from a top portion of front frame **110** to a bottom portion of front frame **110**. Support covering **325** may cover and/or obstruct surfaces of support members **120**. Support covering **325** may be configured to form a cover over support members **120**.

(104) Support covering **325** may be configured to form a seat, a backrest, and or a shade (e.g., roof, sun cover, overhead covering, etc.) in chair **300**. For example, support covering **325** may form the seat from the bottom portion of front frame **110** proximate to third cross member **150-3**. Support covering **325** may form the backrest from proximate third cross member **150-3** to proximate second cross member **150-2**. Support covering **325** may form the shade from proximate second cross member **150-2** to proximate first cross member **150-1**.

(105) In some embodiments, support covering **325** may provide chair **300** and a user sitting within chair **300** protection from elements (e.g., sunlight, rain, etc.). In some embodiments, support

covering **325** may be configured to provide a comfortable and/or smooth surface for a user while sitting within chair **300**.

(106) In various embodiments, support covering **325** may be coupled to support members **120** using any suitable process or technique. For example, support covering **325** may be wrapped and/or weaved on or between support members **120**. As a further example, support covering **325** may be coupled to support members **120** with an adhesive or via other chemical means. As a further example, support covering **325** may be coupled to support members **120** via a mechanical fastener, a hook and loop fastener, and/or the like. As a further example, support covering **325** may be stretched over support members **120** and coupled to a top portion and/or a bottom portion of front frame **110** to remain in position covering support members **120**.

(107) In various embodiments, support covering **325** may comprise any suitable and/or desired material. Support covering **325** may comprise a solution-dyed acrylic material, a vinyl mesh, a polyester fabric, a rope material, a netting material, and/or any other suitable material. Support covering **325** may comprise a synthetic rattan material that is wrapped and/or weaved over support members **120**. The synthetic rattan material may be wrapped and/or weaved in specific patterns and/or directions. For example, the synthetic rattan material may be wrapped and/or weaved in a circular pattern over support members **120**, in a side-to-side vertical pattern over cross members **150**, and/or the like. The synthetic rattan material may be wrapped and/or weaved in a generally horizontal direction over support members **120**.

(108) In various embodiments, chair **300** may comprise one or more armrest coverings **361**. For example, chair **300** may comprise a first armrest covering **361-1** coupled to an outer surface of first armrest **160-1** and a second armrest covering **361-2** coupled to an outer surface of second armrest **160-2**. Armrest coverings **361** may be coupled between one or more members or each armrest **160**. Armrest coverings **361** may be coupled over an entirety of each armrest **160**. Armrest coverings **361** may cover and/or obstruct surfaces of each armrest **160**. Armrest coverings **361** may be configured to form a cover over each armrest **160**.

(109) Armrest coverings **361** may be configured to form a surface (e.g., an armrest surface, a resting surface, etc.) over each armrest **160**. For example, first armrest covering **361-1** may form a surface over first armrest **160-1** and second armrest covering **361-2** may form a surface over second armrest **160-2**. In some embodiments, armrest coverings **361** may be configured to provide a comfortable and/or smooth surface for a user's arms while the user is sitting within chair **300**.

(110) In various embodiments, armrest coverings **361** may be coupled to each armrest **160** using any suitable process or technique. For example, armrest coverings **361** may be wrapped and/or weaved on or between members of each armrest **160**. As a further example, armrest coverings **361** may be coupled to each armrest **160** with an adhesive or via other chemical means. As a further example, armrest coverings **361** may be coupled to each armrest **160** via a mechanical fastener, a hook and loop fastener, and/or the like. As a further example, armrest coverings **361** may be stretched over each armrest **160** and coupled to a middle portion of front frame **110** and a middle portion of a respective outer support member **130** to remain in position covering each armrest **160**.

(111) In various embodiments, armrest coverings **361** may comprise any suitable and/or desired material. Armrest coverings **361** may comprise a solution-dyed acrylic material, a vinyl mesh, a polyester fabric, a rope material, a netting material, and/or any other suitable material. Armrest coverings **361** may comprise a synthetic rattan material that is wrapped and/or weaved over each armrest **160**. The synthetic rattan material may be wrapped and/or weaved in specific patterns and/or directions. For example, the synthetic rattan material may be wrapped and/or weaved in a circular pattern over each armrest **160** and/or the like. The synthetic rattan material may be wrapped and/or weaved in a generally horizontal direction over each armrest **160**.

(112) In various embodiments, coverings of chair **300** may form structures, surfaces, and/or platforms while not obstructing openings of chair **300**. In that regard, front opening **115**, first side opening **135** (including both first side top opening **137-1** and first side bottom opening **137-2**), and

second side opening **145** (including both second side top opening **147-1** and second side bottom opening **147-2**) may remain open, in fluid communication with each other, and unobstructed by coverings (e.g., support covering **325**, armrest coverings **361**).

(113) In various embodiments, and with reference to FIG. **4**, a chair **400** may include one or more accessories. Chair **400** may be similar to, or comprise similar components as, and other chair disclosed herein (e.g., chair **100**, with brief reference to FIGS. **1A-1C**: chair **300**, with brief reference to FIG. **3**: etc.).

(114) In various embodiments, chair **400** may comprise a cushion **480**. Chair **400** may comprise any suitable or desired number of cushions **440**. Chair **400** may comprise a cushion **480** defining a seat and a backrest. Chair **400** may comprise a plurality of cushions **480** including a seat cushion and a backrest cushion. Cushion **480** may be positioned or coupled to the interior of chair **480**. For example, cushion **480** may be positioned or coupled to support covering **325**. Cushion **480** may comprise any suitable type of cushion. Cushion **480** may comprise an object having an outer protective surface enclosing a mass of soft material (e.g., stuffing, feathers, foam, etc.). Cushion **480** may comprise a pillow, a pad, and/or the like. Cushion **480** may be configured to provide a comfortable sitting and up resting support for a user of chair **400**)

(115) In various embodiments, chair **400** may comprise a light accessory **482**. Light accessory **480** may be coupled to front frame **110**. Light accessory **482** may be translatable and/or rotatably coupled to front frame **110** such that light accessory **482** may translate up and/or down on front frame **110**. Light accessory **482** may comprise any suitable light source. For example, light accessory **482** may comprise a light emitting diode (LED), a flashlight, and/or the like. In some embodiments, light accessory **482** may comprise a reading light configured to provide a source of light to a user sitting within chair **400**.

(116) In various embodiments, light accessory **482** may comprise an external power source located external chair **400**. In that respect, an electrical connection (e.g., electrical cabling) from light accessory **482** to the external power source may be routed through chair **400**. In some embodiments, the electrical connection may be routed through an interior of front frame **110**. The electrical connection may exit front frame **110** proximate to anchor **170**. In some embodiments, the electrical connection may be routed between front frame **110** and a surface covering that covers front frame **110**. The electrical connection may exit the position between front frame **110** and the surface covering proximate to anchor **170**.

(117) In various embodiments, light accessory **482** may comprise an onboard power source. For example, a power source for light accessory **482** may be located within light accessory **482**. As a further example, a power source may be located within chair **100** (e.g., within a support member, coupled to a support member, coupled to an armrest, etc.). Light accessory **482** may be electrically coupled to the power source. As a further example, a solar panel may be coupled to chair **400**. Light accessory **482** may be electrically coupled to the solar panel and configured to receive electrical power from the solar panel.

(118) In various embodiments, chair **400** may comprise a holding accessory **484**. Holding accessory **484** may be coupled to front frame **110**. Holding accessory **484** may be translatable and/or rotatably coupled to front frame **110** such that holding accessory **484** may translate up and/or down on front frame **110**. Holding accessory **484** may comprise a holding object configured to hold and/or support a cup, a drink, a phone, a book, a notebook, a snack, and/or the like. Holding accessory **484** may comprise any suitable size, shape, and/or orientation.

(119) In some embodiments, holding accessory **484** may comprise a metal circular ring welded to front frame **110**. The metal circular ring may be welded to front frame **110** at a location radially upward from first armrest **160-1** (or second armrest **160-2**). The metal circular ring may comprise a small gap in the ring to enable holding accessory **484** expand and/or contract to receive different sized cups and beverages. The metal circular ring may be at least partially covered by a covering (e.g., as discussed with reference to FIG. **3**).

(120) In various embodiments, and with reference to FIG. 5, a chair **500** may comprise a footrest **586**. Chair **500** may be similar to, or comprise similar components as, and other chair disclosed herein (e.g., chair **100**, with brief reference to FIGS. **1A-1C**; chair **300**, with brief reference to FIG. **3**; chair **400**, with brief reference to FIG. **4**; etc.).

(121) In various embodiments, footrest **586** may comprise any suitable or desired type of footrest. Although depicted in FIG. 5 as comprising a thin, square shape, footrest **586** may comprise any suitable size, shape, and/or orientation. For example, footrest **586** may comprise a platform, an extension, a stool, a block, and/or the like.

(122) In various embodiments, footrest **586** may be coupled to a bottom surface of chair **500**. Footrest **586** may be coupled to a bottom surface of first inner support member **140-1** and/or second inner support member **140-2**. Footrest **586** may be coupled to a bottom surface of second end **141-2** of first inner support member **140-1** and/or a bottom surface of second end **142-2** of second inner support member **140-2**.

(123) In various embodiments, footrest **586** may be removably coupled to the bottom surface of chair **500**. In that regard, footrest **586** may be decoupled and used by a user with chair **500**, and then recoupled to remain with chair **500**. Footrest **586** may be removably coupled to chair **500** using any suitable or desired technique. For example, in some embodiments, chair **500** may comprise a storage box on a bottom surface of chair **500**. Footrest **586** may be stored, removed, and repositioned in the storage box. As a further example, in some embodiments, chair **500** may comprise rails, tracks, slides, or the like. Footrest **586** may engage the rails, tracks, slides, or the like to couple to chair **500**. Footrest **586** may be disengaged from the rails, tracks, slides, or the like to decouple from chair **500**.

(124) In various embodiments, footrest **586** may be translatably, slidably, and/or rotatably coupled to the bottom surface of chair **500**. In that regard, footrest **586** may be configured to translate, slide, and/or rotate between a stowed position (e.g., a first footrest position, a beneath position, etc.) and a deployed position (e.g., a second footrest position, a forward position, etc.). In the stowed position, footrest **586** may be positioned under (e.g., beneath, radially downward) chair **500** (e.g., as depicted in FIG. 5). In the deployed position, at least a portion of footrest **586** may be positioned forward (e.g., axially forward) of at least a portion of chair **500**. In the deployed position, footrest **586** may be oriented such that a user may rest her feet on footrest **586** while sitting within chair **500**.

(125) In some embodiments, footrest **586** may be configured to translate between the stowed position and the deployed position via a slide, a rail, a translatable member, and/or the like coupled to a bottom of chair **500**. In some embodiments, footrest **586** may be configured to slide between the stowed position and the deployed position via a slide, a rail, a slidable member, and/or the like coupled to a bottom of chair **500**. In some embodiments, footrest **586** may be configured to rotate between the stowed position and the deployed position via a hinge, a rotatable coupling, and/or the like coupled to a bottom of chair **500**.

(126) As previously discussed herein, in some embodiments components of a chair may be removably coupled to one or more other components of the chair. Removable couplings may enable the chair to be assembled and disassembled easily during transit and other events. In some embodiments, removable couplings may decrease shipping costs during sale and/or transmit of the chair (e.g., by enabling components of the chair to be separated to take less surface area in a package compared to a fully assembled chair). For example, in various embodiments and with reference to FIG. 6, a chair **600** with removable couplings is disclosed.

(127) In various embodiments, chair **600** may comprise any suitable number of removable couplings. Each removable coupling may comprise any suitable type of removable coupling. For example, one or more removable couplings may comprise a hook and latch coupling, a clamp coupling, a screw coupling, an insertion coupling, a push fitting coupling, a pin coupling, a connecting link coupling, a safety lock pin coupling, a clevis pin coupling, a quick release coupling, a spring release coupling, a pin and clip coupling, and/or any other suitable type of

removable coupling. As a further example, one or more removable couplings may comprise a welded fastener. The welded fastener may be configured to receive two or more members of chair **600**. The welded fastener may be configured to receive an end or portion of two or more members of chair **600**. For example, a first end or portion of a first member may be inserted into the welded fastener and a second end or portion of a second member may be inserted into the welded fastener to couple the first member to the second member. Respective members may be secured within the welded fastener using any suitable technique, such as, for example, using a pin and/or a clip. For example, a pin may be inserted through the welded fastener and a respective member to secure the respective member into the welded fastener. As a further example, the welded fastener may comprise a mounted clip that may engage a surface of a respective member to secure the respective member into the welded fastener. In some embodiments, a welded fastener may comprise a ½-inch (1.27 cm) metal tubing. The welded fastener may comprise a square tubing, a cylindrical tubing, and/or any other tubing sized and shaped to receive two or more members of chair **600**.

(128) In various embodiments, one or more coupling points of chair **600** may comprise a removable coupling. For example, top end **131-1** of first outer support member **130-1** may be removably coupled to front frame **110** at a first top removable coupling point **601** (e.g., a first removable coupling point). Top end **132-1** of second outer support member **130-2** may be removably coupled to front frame **110** at a second top removable coupling point **602** (e.g., a second removable coupling point). Top end **141-1** of first inner support member **140-1** may be removably coupled to front frame **110** at a third top removable coupling point **603** (e.g., a third removable coupling point). Top end **142-1** of second inner support member **140-2** may be removably coupled to front frame **110** at a fourth top removable coupling point **604** (e.g., a fourth removable coupling point). In some embodiments, one or more top removable coupling points may be similar to other coupling points disclosed herein.

(129) As a further example, bottom end **131-2** of first outer support member **130-1** may be removably coupled to front frame **110** at a first bottom removable coupling point **611** (e.g., a fifth removable coupling point). Bottom end **132-2** of second outer support member **130-2** may be removably coupled to front frame **110** at a second bottom removable coupling point **612** (e.g., a sixth removable coupling point). Bottom end **141-2** of first inner support member **140-1** may be removably coupled to front frame **110** at a third bottom removable coupling point **613** (e.g., a seventh removable coupling point). Bottom end **142-2** of second inner support member **140-2** may be removably coupled to front frame **110** at a fourth bottom removable coupling point **614** (e.g., an eighth removable coupling point). In some embodiments, one or more bottom removable coupling points may be similar to other coupling points disclosed herein.

(130) As a further example, one or more cross members **150** may be removably coupled to chair **600**. One or more cross members **150** may be removably coupled to one or more support members **120**. For example, first cross member **150-1** may be removably coupled to one or more support members **120**, second cross member **150-2** may be removably coupled to one or more support members **120**, and/or third cross member **150-3** may be removably coupled to one or more support members **120**. Although depicted in FIG. 6 as only second cross member **150-2** being removably coupled to one or more support members **120**, it should be understood that in some embodiments first cross member **150-1**, second cross member **150-2**, and/or third cross member **150-3** may be removably coupled to one or more support members **120**.

(131) Second cross member **150-2** may be removably coupled to first outer support member **130-1** at a first cross removable coupling point **691** (e.g., a ninth removable coupling point), to first inner support member **140-1** at a second cross removable coupling point **692** (e.g., a tenth removable coupling point), to second inner support member **140-2** at a third cross removable coupling point **693** (e.g., an eleventh removable coupling point), and/or to second outer support member **130-2** at a fourth cross removable coupling point **694** (e.g., a twelfth removable coupling point).

(132) As a further example, each armrest **160** may be removably coupled to chair **600**. Each

armrest **160** may be removably coupled to front frame **110** and a respective outer support member **130**. First armrest **160-1** may be removably coupled to first outer support member **130-1** at a first armrest removable coupling point **695** (e.g., a thirteenth removable coupling point). First armrest **160-1** may be removably coupled to front frame **110** at a second armrest removable coupling point **696** (e.g., a fourteenth removable coupling point). Second armrest **160-2** may be removably coupled to second outer support member **130-2** at a third armrest removable coupling point **698** (e.g., a fifteenth removable coupling point). Second armrest **160-2** may be removably coupled to front frame **110** at a second armrest removable coupling point **699** (e.g., a sixteenth removable coupling point).

(133) In various embodiments, removable couplings of chair **600** may enable chair **600** to separate into one or more distinct components. For example, front frame **110** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **601, 602, 603, 604, 611, 612, 613, 614, 696, and 699**. First outer support member **130-1** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **601, 611, 691, and 695**. First inner support member **140-1** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **603, 613, and 692**. Second inner support member **140-2** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **604, 614, and 693**. Second outer support member **130-2** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **602, 612, 694, and 698**. Second cross member **150-2** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **691, 692, 693, and 694**. Similarly, first cross member **150-1** and/or third cross member **150-3** may be separated (e.g., removably coupled) from chair **600** via removable coupling points on first outer support member **130-1**, first inner support member **140-1**, second inner support member **140-2**, and second outer support member **130-2**. First armrest **160-1** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **695 and 696**. Second armrest **160-2** may be separated (e.g., removably coupled) from chair **600** via removable coupling points **698 and 699**.

(134) In that regard, in some embodiments chair **600** may separate into ten separate and distinct components via the removable coupling points. The separation of relative components of chair **600** in this manner may enable chair **600** to compact in size (e.g., decrease in volumetric size compared to an assembled chair **600**) to take less surface area in a package compared to a fully assembled chair.

(135) Benefits, other advantages, and solutions to problems have been described herein with regard to specific embodiments. Furthermore, the connecting lines shown in the various figures contained herein are intended to represent exemplary functional relationships and/or physical couplings between the various elements. It should be noted that many alternative or additional functional relationships or physical connections may be present in a practical system. However, the benefits, advantages, solutions to problems, and any elements that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as critical, required, or essential features or elements of the disclosures. The scope of the disclosures is accordingly to be limited by nothing other than the appended claims and their legal equivalents, in which reference to an element in the singular is not intended to mean “one and only one” unless explicitly so stated, but rather “one or more.” Moreover, where a phrase similar to “at least one of A, B, or C” is used in the claims, it is intended that the phrase be interpreted to mean that A alone may be present in an embodiment, B alone may be present in an embodiment, C alone may be present in an embodiment, or that any combination of the elements A, B and C may be present in a single embodiment: for example, A and B, A and C, B and C, or A and B and C.

(136) In the detailed description herein, references to “various embodiments,” “one embodiment,” “an embodiment,” “an example embodiment,” “some embodiments,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic.

Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. After reading the description, it will be apparent to one skilled in the relevant art(s) how to implement the disclosure in alternative embodiments. Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element is intended to invoke 35 U.S.C. 112 (f) unless the element is expressly recited using the phrase “means for.” As used herein, the terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

Claims

1. A hanging chair comprising: a front frame defining a front opening; a plurality of support members coupled to the front frame, wherein the plurality of support members extend from a top portion of the front frame to a bottom portion of the front frame, and wherein the plurality of support members extend axially rearward the front frame; a first side opening defined between the front frame and a first outer support member of the plurality of support members; a second side opening defined between the front frame and a second outer support member of the plurality of support members, wherein the first side opening, the second side opening, and the front opening are in fluid communication; a first armrest coupled to the front frame and the first outer support member, wherein the first armrest intersects the first side opening, and wherein the intersection of the first armrest in the first side opening defines a first side top opening of the first side opening above the first armrest and a first side bottom opening of the first side opening below the first armrest; and a second armrest coupled to the front frame and the second outer support member, wherein the second armrest intersects the second side opening, and wherein the intersection of the second armrest in the second side opening defines a second side top opening of the second side opening above the second armrest and a second side bottom opening of the second side opening below the second armrest.
2. The hanging chair of claim 1, wherein the plurality of support members also comprise a first inner support member and a second inner support member, and wherein the first inner support member and the second inner support member are disposed between the first outer support member and the second outer support member.
3. The hanging chair of claim 2, wherein the first outer support member couples to the top portion of the front frame at a first coupling point, the second outer support member couples to the top portion of the front frame at a second coupling point, the first inner support member couples to the top portion of the front frame at a third coupling point, and the second inner support member couples to the top portion of the front frame at a fourth coupling point, and wherein the first coupling point, the second coupling point, the third coupling point, and the fourth coupling point comprise different locations on the front frame.
4. The hanging chair of claim 3, wherein the first coupling point and the second coupling point are radially inward from the third coupling point and the fourth coupling point.
5. The hanging chair of claim 3, further comprising an anchor coupled to the top portion of the front frame, wherein the anchor is disposed between the third coupling point and the fourth coupling point.
6. The hanging chair of claim 2, wherein the first outer support member couples to the bottom portion of the front frame at a fifth coupling point, the second outer support member couples to the

bottom portion of the front frame at a sixth coupling point, the first inner support member couples to the bottom portion of the front frame at a seventh coupling point, and the second inner support member couples to the bottom portion of the front frame at an eighth coupling point, and wherein the fifth coupling point, the sixth coupling point, the seventh coupling point, and the eighth coupling point comprise different locations on the front frame.

7. The hanging chair of claim 6, wherein the fifth coupling point and the sixth coupling point are radially inward from the seventh coupling point and the eighth coupling point.

8. The hanging chair of claim 2, wherein each end of the first outer support member and the second outer support member is displaced at a first angle, wherein each end of the first inner support member and the second inner support member is displaced at a second angle, and wherein the first angle is different from the second angle.

9. The hanging chair of claim 8, wherein the first angle is less than the second angle.

10. The hanging chair of claim 1, wherein the first side top opening comprises a first surface area, wherein the first side bottom opening comprises a second surface area, and wherein the first surface area is greater than the second surface area.

11. The hanging chair of claim 1, wherein the second side top opening comprises a third surface area, wherein the second side bottom opening comprises a fourth surface area, and wherein the third surface area is greater than the fourth surface area.

12. The hanging chair of claim 1, wherein the first side top opening comprises a first surface area, wherein the first side bottom opening comprises a second surface area, wherein the second side top opening comprises a third surface area, wherein the second side bottom opening comprises a fourth surface area, wherein the first surface area is similar to the third surface area, and wherein the second surface area is similar to the fourth surface area.

13. A hanging chair system comprising: an external support structure; a connecting structure comprising a first end opposite a second end, wherein the first end is coupled to the external support structure; and a hanging chair coupled to the second end of the connecting structure, wherein the hanging chair is configured to suspend in the air in response to being coupled to the second end of the connecting structure, and wherein the hanging chair comprises: a front frame defining a front opening; a plurality of support members coupled to the front frame, wherein the plurality of support members extend from a top portion of the front frame to a bottom portion of the front frame, and wherein the plurality of support members extend axially rearward the front frame; a first side opening defined between the front frame and a first outer support member of the plurality of support members; and a second side opening defined between the front frame and a second outer support member of the plurality of support members, wherein the first side opening, the second side opening, and the front opening are in fluid communication, wherein the hanging chair is configured to transition from a rest position to a load position in response to receiving a load within an interior of the hanging chair, wherein the hanging chair is in a different orientation in the rest position compared to in the load position, wherein in the rest position the bottom portion of the front frame is tilted axially forward the top portion of the front frame, and wherein in the load position the bottom portion of the front frame is axially closer to the top portion of the front compared to in the rest position.

14. The hanging chair system of claim 13, wherein the plurality of support members also comprise a first inner support member and a second inner support member, and wherein the first inner support member and the second inner support member are disposed between the first outer support member and the second outer support member.

15. The hanging chair system of claim 14, wherein the first outer support member couples to the top portion of the front frame at a first coupling point, the second outer support member couples to the top portion of the front frame at a second coupling point, the first inner support member couples to the top portion of the front frame at a third coupling point, and the second inner support member couples to the top portion of the front frame at a fourth coupling point, and wherein the first

coupling point, the second coupling point, the third coupling point, and the fourth coupling point comprise different locations on the front frame.

16. The hanging chair system of claim 15, further comprising an anchor coupled to the top portion of the front frame, wherein the anchor is disposed between the third coupling point and the fourth coupling point, and wherein the anchor is configured to couple the hanging chair to the second end of the connecting structure.

17. The hanging chair system of claim 13, wherein the hanging chair further comprises: a first armrest coupled to the front frame and the first outer support member, wherein the first armrest intersects the first side opening, and wherein the intersection of the first armrest in the first side opening defines a first side top opening of the first side opening above the first armrest and a first side bottom opening of the first side opening below the first armrest; and a second armrest coupled to the front frame and the second outer support member, wherein the second armrest intersects the second side opening, and wherein the intersection of the second armrest in the second side opening defines a second side top opening of the second side opening above the second armrest and a second side bottom opening of the second side opening below the second armrest.

18. A hanging chair comprising: a front frame defining a front opening; a first outer support member coupled to the front frame at a top portion of the front frame and at a bottom portion of the front frame, wherein the first outer support member extends from the top portion of the front frame to the bottom portion of the front frame, wherein the first outer support member extends axially rearward the front frame, and wherein the first outer support member and the front frame define a first side opening in fluid communication with the front opening; a second outer support member coupled to the front frame at the top portion of the front frame and at the bottom portion of the front frame, wherein the second outer support member extends from the top portion of the front frame to the bottom portion of the front frame, wherein the second outer support member extends axially rearward the front frame, and wherein the second outer support member and the front frame define a second side opening in fluid communication with the front opening; and a first inner support member coupled to the front frame at the top portion of the front frame and at the bottom portion of the front frame, wherein the first inner support member is disposed between the first outer support member and the second outer support member, wherein the first inner support member extends from the top portion of the front frame to the bottom portion of the front frame, and wherein the first inner support member extends axially rearward the front frame.

19. The hanging chair of claim 18, wherein the first outer support member is coupled to the top portion of the front frame at a first top coupling point, the second outer support member is coupled to the top portion of the front frame at a second top coupling point, and the first inner support member is coupled to the top portion of the front frame at a third top coupling point, and wherein the first top coupling point, the second top coupling point, and the third top coupling point comprise different locations on the front frame.

20. The hanging chair of claim 18, wherein the first outer support member is coupled to the bottom portion of the front frame at a first bottom coupling point, the second outer support member is coupled to the bottom portion of the front frame at a second bottom coupling point, and the first inner support member is coupled to the bottom portion of the front frame at a third bottom coupling point, and wherein the first bottom coupling point, the second bottom coupling point, and the third bottom coupling point comprise different locations on the front frame.
