

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415703
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Hoover; Donald Lynn

Canister-yarn tensioning assembly incorporating a pivoted yarn tensioner

Abstract

A canister-yarn tensioning assembly is adapted for controlling tension in a running yarn drawn from a yarn supply package located within an open-top canister. The canister-yarn tensioning assembly includes a cylindrical adapter configured to reside at a mouth of the open-top canister. The adapter defines an unobstructed package transfer space sufficient to allow the yarn supply package to be manually lowered through the adapter and into the canister. A pivoted support arm is carried by the adapter, and configured to pivot at a connection point located on a peripheral flange of the adapter. One or more yarn tensioners are carried by the pivoted support arm, and are movable between an operative position within the package transfer space and an inoperative package-replacement position outside of the package transfer space.

Inventors:	Hoover; Donald Lynn (Cramerton, NC)
Applicant:	American Linc, LLC (Gastonia, NC)
Family ID:	1000008820695
Assignee:	A.B. Carter, Inc. (Gastonia, NC)
Appl. No.:	18/021588
Filed (or PCT Filed):	August 26, 2021
PCT No.:	PCT/US2021/047725
PCT Pub. No.:	WO2022/047013
PCT Pub. Date:	March 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230294955 A1	Sep. 21, 2023

Related U.S. Application Data

us-provisional-application US 63129904 20201223

us-provisional-application US 63071121 20200827

Publication Classification

Int. Cl.: **B65H59/06** (20060101); **B65H49/08** (20060101); **B65H57/06** (20060101); **B65H67/06** (20060101)

U.S. Cl.:

CPC **B65H59/06** (20130101); **B65H49/08** (20130101); **B65H57/06** (20130101); **B65H67/06** (20130101); B65H2701/31 (20130101)

Field of Classification Search

CPC: B65H (59/06); B65H (49/08); B65H (67/06); B65H (67/0428); D01H (9/008)

USPC: 242/360

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
285727	12/1882	Boyden	242/153	B65H 49/08
356377	12/1886	Rose	242/154	B65H 49/08
681140	12/1900	Rand	242/156	B65H 49/08
745833	12/1902	Hanson	242/137.1	B65H 49/08
750574	12/1903	Bicket	242/150R	B65H 49/08
3009611	12/1960	Bates	242/138	D05B 91/14
3478982	12/1968	Paulson	242/129.8	B65H 59/12
4050648	12/1976	Tisma	132/321	B65H 75/14
4605182	12/1985	Zollinger	N/A	N/A
4991793	12/1990	Belsley	242/147R	B65H 59/22
5806780	12/1997	Schneider	242/128	B21C 47/20
2003/0209001	12/2002	Schacht	57/58.83	D01H 13/04
2005/0011984	12/2004	D'Agnolo	N/A	N/A
2014/0097287	12/2013	Weissbrod	242/551	B65H 49/12
2017/0130367	12/2016	Duralti	N/A	D01H 1/006
2019/0071275	12/2018	Ashton	N/A	A41G 5/002
2021/0221640	12/2020	Gelmetti	N/A	B65H 59/06

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111942961	12/2019	CN	B65H 49/08
2019246614	12/2018	WO	N/A

Primary Examiner: Momper; Anna M

Background/Summary

TECHNICAL FIELD AND BACKGROUND

(1) The present disclosure relates broadly and generally to the textile industry, and more particularly to a canister-yarn tensioning assembly incorporating a pivoted (e.g., swing-out) yarn tensioner. In one exemplary embodiment, the tensioning device of the present disclosure is utilized in a direct-cabling textile machine. In other applications, various components and features of the present disclosure may be used in combination with any other tensioning device and in any other textile machine.

SUMMARY OF EXEMPLARY EMBODIMENTS

(2) Various exemplary embodiments of the present disclosure are described below. Use of the term “exemplary” means illustrative or by way of example only, and any reference herein to “the invention” is not intended to restrict or limit the invention to exact features or steps of any one or more of the exemplary embodiments disclosed in the present specification. References to “exemplary embodiment,” “one embodiment,” “an embodiment,” “various embodiments,” and the like, may indicate that the embodiment(s) of the invention so described may include a particular feature, structure, or characteristic, but not every embodiment necessarily includes the particular feature, structure, or characteristic. Further, repeated use of the phrase “in one embodiment,” or “in an exemplary embodiment,” do not necessarily refer to the same embodiment, although they may.

(3) It is also noted that terms like “preferably”, “commonly”, and “typically” are not utilized herein to limit the scope of the invention or to imply that certain features are critical, essential, or even important to the structure or function of the invention. Rather, these terms are merely intended to highlight alternative or additional features that may or may not be utilized in a particular embodiment of the present invention.

(4) According to one exemplary embodiment, the present disclosure comprises a canister-yarn tensioning assembly adapted for controlling (or adjusting) tension in a running yarn drawn from a yarn supply package located within an open-top canister. The canister-yarn tensioning assembly includes a cylindrical adapter configured to reside at a mouth of the open-top canister. The adapter defines an unobstructed package transfer space sufficient to allow the yarn supply package to be manually lowered through the adapter and into the canister. A pivoted support arm is carried by the adapter, and configured to pivot at a connection point located on a peripheral flange of the adapter. One or more yarn tensioners are carried by the pivoted support arm, and are movable between an operative position within the package transfer space and an inoperative package-replacement position outside of the package transfer space.

(5) In the operative position, the yarn tensioner frictionally engages the running yarn drawn from the supply package during operation of the textile machine. The yarn tensioner receives running yarn pulled from the supply package at an unwinding tension, and adjusts the unwinding tension such that the yarn exits the tensioner at an adjusted downstream delivery tension.

(6) Upon depleting the yarn supply package, the support arm is pivoted at the connection point to move the yarn tensioner from the operative position to the package-replacement position such that a fresh yarn supply package can be freely lowered through the package transfer space and into the canister. After inserting the fresh yarn supply package into the canister, the support arm is pivoted at the connection point to move the yarn tensioner back into the operative position—receiving running yarn pulled from the fresh package.

- (7) According to another exemplary embodiment, the pivoted support arm is mounted on a generally semi-circular horizontal flex cover. The flex cover is attached to the adapter at the connection point.
- (8) According to another exemplary embodiment, a horizontal reinforcement plate is located between the pivoted support arm and the flex cover.
- (9) According to another exemplary embodiment, the flex cover is fabricated of a thin flexible stainless steel.
- (10) According to another exemplary embodiment, the flex cover has a downwardly angled lip formed along a diameter line of the flex cover and configured to extend across the package transfer space when the yarn tensioner resides in the operative position.
- (11) According to another exemplary embodiment, the flex cover has an arcuate outside edge configured to align with the peripheral flange of the adapter when the yarn tensioner resides in the operative position.
- (12) According to another exemplary embodiment, the support arm angles inwardly from the arcuate edge of the flex cover towards the diameter line of the flex cover.
- (13) According to another exemplary embodiment, the yarn tensioner comprises at least one of a pre-tensioner and an adjustable main tensioner.
- (14) According to another exemplary embodiment, a tensioner bracket is attached to the support arm and comprises spaced apart first and second yarn guides located at upstream and downstream sides of the yarn tensioner.
- (15) According to another exemplary embodiment, the adapter is configured to nest inside the canister and includes a plurality of spaced apart (e.g, equally spaced) outwardly projecting support pins for holding the adapter at the mouth of the canister.
- (16) In another exemplary embodiment, the present disclosure comprises a canister assembly for use in a direct-cabling textile machine. The canister assembly includes an open-top yarn canister configured for holding a yarn supply package, and for receiving the yarn supply package through a package transfer space. A pivoted support arm is configured to pivot at a connection point located adjacent an annular peripheral edge of the canister. One or more yarn tensioners are carried by the pivoted support arm, and are movable between an operative position within the package transfer space and an inoperative package-replacement position outside of the package transfer space. As previously described, in the operative position the yarn tensioner frictionally engages the running yarn drawn from the supply package during operation of the textile machine. Upon depleting the yarn supply package, the support arm is pivoted at the connection point to move the yarn tensioner from the operative position to the package-replacement position such that a fresh yarn supply package can be freely lowered through the package transfer space and into the canister. After inserting the fresh yarn supply package into the canister, the support arm is pivoted at the connection point to move the yarn tensioner back into the operative position.
- (17) In yet another exemplary embodiment, the present disclosure comprises a method of loading a fresh yarn supply package into a canister for use in a direct-cabling textile machine.
- (18) Use of the terms “upstream” and “downstream” refer herein to relative locations (or movement) of elements or structure to other elements or structure along or adjacent the path of yarn travel. In other words, a first element or structure which is encountered along or adjacent the path of yarn travel before a second element or structure is considered to be “upstream” of the second element or structure, and the second element structure is considered to be “downstream” of the first. The term “housing” refers broadly herein to any open, closed, or partially open or partially closed structure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Exemplary embodiments of the present disclosure will hereinafter be described in conjunction with the following drawing figures, wherein like numerals denote like elements, and wherein:
- (2) FIGS. **1** and **2** are views of a canister-yarn tensioning assembly according to one exemplary embodiment of the present disclosure;
- (3) FIG. **3** is a fragmentary perspective view of the exemplary canister-yarn tensioning assembly;
- (4) FIGS. **4** and **5** are side views of the exemplary canister-yarn tensioning assembly;
- (5) FIG. **6** is a perspective view of the exemplary canister-yarn tensioning assembly with various components exploded away;
- (6) FIG. **7** demonstrates an exemplary process of simultaneously lifting and pivoting the flex cover to open a package transfer space defined by the assembly adapter;
- (7) FIG. **8** shows the assembly in a package-replacement position whereby the empty package tube can be readily accessed, removed and discarded.

DESCRIPTION OF EXEMPLARY EMBODIMENTS AND BEST MODE

- (8) The present invention is described more fully hereinafter with reference to the accompanying drawings, in which one or more exemplary embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be operative, enabling, and complete. Accordingly, the particular arrangements disclosed are meant to be illustrative only and not limiting as to the scope of the invention, and any and all equivalents thereof. Moreover, many embodiments, such as adaptations, variations, modifications, and equivalent arrangements, will be implicitly disclosed by the embodiments described herein and fall within the scope of the present invention.
- (9) Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation. Unless otherwise expressly defined herein, such terms are intended to be given their broad ordinary and customary meaning not inconsistent with that applicable in the relevant industry and without restriction to any specific embodiment hereinafter described. As used herein, the article “a” is intended to include one or more items. Where only one item is intended, the term “one”, “single”, or similar language is used. When used herein to join a list of items, the term “or” denotes at least one of the items, but does not exclude a plurality of items of the list.
- (10) For exemplary methods or processes of the invention, the sequence and/or arrangement of steps described herein are illustrative and not restrictive. Accordingly, it should be understood that, although steps of various processes or methods may be shown and described as being in a sequence or temporal arrangement, the steps of any such processes or methods are not limited to being carried out in any particular sequence or arrangement, absent an indication otherwise. Indeed, the steps in such processes or methods generally may be carried out in various different sequences and arrangements while still falling within the scope of the present invention.
- (11) Additionally, any references to advantages, benefits, unexpected results, or operability of the present invention are not intended as an affirmation that the invention has been previously reduced to practice or that any testing has been performed. Likewise, unless stated otherwise, use of verbs in the past tense (present perfect or preterit) is not intended to indicate or imply that the invention has been previously reduced to practice or that any testing has been performed.
- (12) Referring now specifically to the drawings, a canister-yarn tensioning assembly according to one exemplary embodiment of the present disclosure is illustrated in FIGS. **1** and **2**, and shown generally at broad reference numeral **10**. The exemplary assembly resides between a yarn supply package **12** and a downstream textile machine—indicated at broad reference numeral **14**. The supply package **12** is held within an open-top aluminum or stainless steel canister **15** or other suitable metal container. As described further below, the present assembly **10** incorporates a

pivoted (or swing-out) yarn tensioner **20** configured and arranged to receive a running yarn **Y1** pulled from the supply package **12** at an unwinding tension, and to adjust the unwinding tension such that the yarn **Y1** exits the tensioner **20** at an adjusted downstream delivery tension. The exemplary yarn tensioner **20** may comprise a single yarn tensioning device or a combination pre-tensioner and adjustable main tensioner. Examples of Applicant's yarn pre-tensioner and adjustable main tensioner are disclosed in prior U.S. Pat. No. 10,407,272 and Publication No. US/2021/0163254. The complete disclosure of these publications is incorporated herein by reference.

(13) The exemplary textile machine **14** may be a conventional direct-cabling machine used to form high-quality pile in the manufacture of rugs and carpets. In a direct-cabling machine, the supply package **12** is loaded into the cannister **15** and the yarn **Y1** unwound and tensioned using a tensioning device, such as yarn tensioner **20**. A second yarn **Y2** drawn from a separate supply package (not shown) forms a revolving balloon around the cannister **15** and passes together with yarn **Y1** through a downstream guide **21**. At the balloon apex, both yarns **Y1**, **Y2** meet and wrap around each other. At the meeting point, both yarns **Y1**, **Y2** should have substantially the same tension in order to form a balanced composite yarn with no or limited residual torque and substantially equal lengths of component yarns. Each yarn **Y1**, **Y2** may comprise a single-ply filament yarn.

(14) The exemplary yarn tensioner **20** applies predetermined (e.g., calibrated) frictional resistance to the running yarn **Y1**, such that the downstream delivery tension is maintained at a generally uniform, constant and predictable level. When the yarn package **12** in the canister **15** is depleted, operation of the textile machine **14** position is temporarily suspended as a fresh package is added. Exemplary components and features of the present tensioning assembly **10** facilitate the process of removing the empty package tube and loading the fresh yarn package into the canister **15**, thereby improving labor efficiencies and reducing machine downtime.

(15) Referring to FIGS. 2-6, the present tensioning assembly **10** comprises a cylindrical metal (e.g., aluminum or stainless steel) adapter **25** configured to reside at an annular mouth **15A** of the open-top canister **15**. The adapter **25** partially nests inside the canister **15** and includes 3 or more equally spaced, outwardly projecting support pins **26** which function to place and hold the adapter **25** in position throughout operation of the textile machine **14**. As best shown in FIG. 2, each pin **26** is secured to an outside cylindrical wall of the adapter **25** and has an integrally formed spacer **26A** and outward projecting support **26B**. The spacer **26A** is designed to engage a cylindrical inside wall of the canister **15** while the pin support **26B** sits atop the mouth **15A** of canister **15**. As discussed further below, the adapter **25** defines a selectively accessible package transfer space **30** sufficient to allow the yarn package **12** to be manually lowered through the adapter **25** and into the canister **15**.

(16) The exemplary yarn tensioner **20** of assembly **10** is carried by an upwardly-angled support arm **31** and tensioner bracket **32** configured to centrally locate the tensioner **20** above the yarn supply package **12** held in canister **15**. The tensioner bracket **32** has a generally vertical leg **34** and integrally-formed horizontally-disposed upper and lower guide bars **35**, **36**—each bar defining a small annular yarn guide **37**, **38**. The support arm **31** is attached to the tensioner bracket **32** at one end and mounted at its opposite end to a small flat reinforcement plate **41**. The reinforcement plate **41** is affixed to a larger generally semi-circular resilient flex cover **42**. The exemplary flex cover **42** is fabricated of thin T302/304 stainless steel and is pivotably attached to a peripheral flange **25A** of the adapter **25** at a single pivot connection point **45**. See FIGS. 3, 4 and 6. The flex cover **42** is attached at the pivot connection point **45** using suitable hardware **46A**, **46B** shown in FIG. 6. In an exemplary embodiment, the yarn tensioner **20**, support arm **31**, tensioner bracket **32**, reinforcement plate **41** and flex cover **42** are joined together as a single “integrated unit” and pivot as a single unit between an operative position within (or inside of) the package transfer space **30** and a package-replacement position outside of the package transfer space **30**.

(17) As best shown in FIGS. 2, 3 and 6, the exemplary flex cover **42** has a downwardly turned lip

48 formed along a diameter line and an arcuate outside edge **49**. In the operative position of yarn tensioner **20**, the downwardly turned lip **48** of the flex cover **42** extends across the package transfer space **30** while the arcuate outside edge **49** aligns with the peripheral flange **25A** of the adapter **25**. Opposite ends **48A**, **48B** of the downwardly turned lip **48** may be slightly spaced from the arcuate edge **49** so that when manually pivoting the integrated unit including yarn tensioner **20** into the operative position, the flex cover **42** falls into place thereby precisely aligning the yarn tensioner **20** relative to the supply package **12**. An annular yarn guide (hole) **51** may be formed in the flex cover **42** adjacent the lip **48**. In the operative position, the yarn tensioner **20** frictionally engages the running yarn **Y1** drawn from the supply package **12** during operation of the textile machine **14**. The yarn tensioner **20** receives running yarn **Y1** pulled from the supply package **12** at an unwinding tension, and adjusts the unwinding tension such that the yarn **Y1** exits the tensioner **20** at an adjusted downstream delivery tension. The annular yarn guides **37**, **38** formed with the tensioner bracket **32** on upstream and downstream sides of the yarn tensioner **20** vertically align with the yarn guide **51** of flex cover **42** and cooperate to control and direct the path of running yarn **Y1** entering and exiting the tensioner **20**.

(18) Referring to FIGS. **7** and **8**, upon depleting the yarn supply package **12**, operation of the textile machine **14** position is temporarily suspended while the empty package tube **52** is removed from the canister **15** and a fresh yarn package **12'** manually loaded. The package transfer space **30** defined by adapter **25** is uncovered by simultaneously lifting and pivoting the flex cover **42**, as demonstrated by arrows **55** and **56** in FIG. **7**, so that the entire integrated unit including yarn tensioner **20** swings outwardly at the pivot connection point **45** into the package-replacement position shown in FIG. **8**. In the package-replacement position, the empty package tube **52** can be readily accessed, removed and discarded. The fresh yarn package **12'** is then quickly and conveniently placed into the canister **15** through the open transfer space **30** without any disassembly of parts. After loading the fresh yarn package **12'**, the entire integrated unit including yarn tensioner **20** is swung back into its original operative position over the yarn transfer space **30** of the adapter **25**. In the operative position, the flex cover **42** also functions to manage airflow which might otherwise disrupt unwinding of yarn **Y1** from the yarn package **12**, **12'**.

(19) In alternative embodiments of the present disclosure, the exemplary tensioning assembly may omit the stainless steel flex cover and the support arm carrying the yarn tensioner may be pivotably attached directly to the annular flange of the adapter; or in the absence of adapter, directly to the top annular edge of the canister. In still further exemplary embodiments, the support arm carrying the yarn tensioner may pivot at the connection point generally perpendicular to a plane of the package transfer space—as opposed to the side-to-side “swing-out” movement of the integrated unit described above.

(20) For the purposes of describing and defining the present invention it is noted that the use of relative terms, such as “substantially”, “generally”, “approximately”, and the like, are utilized herein to represent an inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, or other representation. These terms are also utilized herein to represent the degree by which a quantitative representation may vary from a stated reference without resulting in a change in the basic function of the subject matter at issue.

(21) Exemplary embodiments of the present invention are described above. No element, act, or instruction used in this description should be construed as important, necessary, critical, or essential to the invention unless explicitly described as such. Although only a few of the exemplary embodiments have been described in detail herein, those skilled in the art will readily appreciate that many modifications are possible in these exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the appended claims.

(22) In the claims, any means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents, but also equivalent

structures. Thus, although a nail and a screw may not be structural equivalents in that a nail employs a cylindrical surface to secure wooden parts together, whereas a screw employs a helical surface, in the environment of fastening wooden parts, a nail and a screw may be equivalent structures. Unless the exact language “means for” (performing a particular function or step) is recited in the claims, a construction under 35 U.S.C. § 112(f) [or 6th paragraph/pre-AIA] is not intended. Additionally, it is not intended that the scope of patent protection afforded the present invention be defined by reading into any claim a limitation found herein that does not explicitly appear in the claim itself.

Claims

1. A canister-yarn tensioning assembly adapted for controlling tension in a running yarn drawn from a yarn supply package located within an open-top canister, said canister-yarn tensioning assembly comprising: a cylindrical adapter configured to reside at a mouth of the open-top canister, and defining a package transfer space for inserting the yarn supply package through the adapter and into the canister; a pivoted support arm carried by said adapter, and configured to pivot at a connection point located on a peripheral flange of said adapter, and wherein said pivoted support arm is mounted on a generally semi-circular horizontal flex cover, and wherein said flex cover is attached to said adapter at said connection point; a yarn tensioner carried by said pivoted support arm and movable between an operative position within the package transfer space, wherein said yarn tensioner frictionally engages the running yarn drawn from the supply package, and a package-replacement position outside of the package transfer space, whereby: (i) upon depleting the yarn supply package, said support arm is pivoted at said connection point to move said yarn tensioner from the operative position to the package-replacement position such that a fresh yarn supply package can be freely inserted through the package transfer space and into the canister; and after inserting the fresh yarn supply package into the canister, said support arm is pivoted at said connection point to move the yarn tensioner back into the operative position.
2. The canister-yarn tensioning assembly according to claim 1, wherein said flex cover comprises a downwardly angled lip formed along a diameter line of said flex cover and configured to extend across the package transfer space when said yarn tensioner resides in the operative position.
3. The canister-yarn tensioning assembly according to claim 2, wherein said flex cover comprises an arcuate outside edge configured to align with the peripheral flange of said adapter when said yarn tensioner resides in the operative position.
4. The canister-yarn tensioning assembly according to claim 3, wherein said support arm angles inwardly from the arcuate edge of said flex cover towards the diameter line of said flex cover.
5. The canister-yarn tensioning assembly according to claim 1, and comprising a horizontal reinforcement plate located between said pivoted support arm and said flex cover.
6. The canister-yarn tensioning assembly according to claim 1, wherein said flex cover is fabricated of stainless steel.
7. The canister-yarn tensioning assembly according to claim 1, wherein said yarn tensioner comprises at least one of a pre-tensioner and an adjustable main tensioner.
8. The canister-yarn tensioning assembly according to claim 1, and comprising a tensioner bracket attached to said support arm and comprising spaced apart first and second yarn guides located at upstream and downstream sides of said yarn tensioner.
9. The canister-yarn tensioning assembly according to claim 1, wherein said adapter is configured to nest inside the canister and comprises a plurality of spaced apart outwardly projecting support pins for holding said adapter at the mouth of the canister.
10. A canister assembly for use in a direct-cabling textile machine, said canister assembly comprising: an open-top yarn canister configured for holding a yarn supply package, and for receiving the yarn supply package through a package transfer space; a pivoted support arm

mounted on a generally semi-circular horizontal flex cover and configured to pivot at a connection point located adjacent an annular peripheral edge of said canister; a yarn tensioner carried by said pivoted support arm and movable between an operative position within the package transfer space, wherein said yarn tensioner frictionally engages a running yarn drawn from the supply package, and a package-replacement position outside of the package transfer space, whereby: (i) upon depleting the yarn supply package, said support arm is pivoted at said connection point to move said yarn tensioner from the operative position to the package-replacement position such that a fresh yarn supply package can be inserted through the package transfer space and into the canister; and after inserting the fresh yarn supply package into the canister, said support arm is pivoted at said connection point to move the yarn tensioner back into the operative position.

11. The canister assembly according to claim 10, wherein said flex cover comprises a downwardly angled lip formed along a diameter line of said flex cover and configured to extend across the package transfer space when said yarn tensioner resides in the operative position.

12. The canister assembly according to claim 11, wherein said flex cover comprises an arcuate outside edge.

13. The canister assembly according to claim 12, wherein said support arm angles inwardly from the arcuate outside edge of said flex cover towards the diameter line of said flex cover.

14. The canister assembly according to claim 10, and comprising a horizontal reinforcement plate located between said pivoted support arm and said flex cover.

15. The canister assembly according to claim 10, wherein said flex cover is fabricated of stainless steel.

16. The canister assembly according to claim 10, and comprising a tensioner bracket attached to said support arm and comprising spaced apart first and second yarn guides located at upstream and downstream sides of said yarn tensioner.

17. The canister assembly according to claim 10, wherein said yarn tensioner comprises at least one of a pre-tensioner and an adjustable main tensioner.

18. The canister assembly according to claim 10, and comprising an adapter configured to nest inside the canister and comprises a plurality of spaced apart outwardly projecting support pins for holding said adapter at the mouth of the canister.

19. A canister-yarn tensioning assembly adapted for controlling tension in a running yarn drawn from a yarn supply package located within an open-top canister, said canister-yarn tensioning assembly comprising: a cylindrical adapter configured to reside at a mouth of the open-top canister, and defining a package transfer space for inserting the yarn supply package through the adapter and into the canister, and wherein said adapter is configured to nest inside the canister and comprises a plurality of spaced apart outwardly projecting support pins for holding said adapter at the mouth of the canister; a pivoted support arm carried by said adapter, and configured to pivot at a connection point located on a peripheral flange of said adapter; a yarn tensioner carried by said pivoted support arm and movable between an operative position within the package transfer space, wherein said yarn tensioner frictionally engages the running yarn drawn from the supply package, and a package-replacement position outside of the package transfer space, whereby: (i) upon depleting the yarn supply package, said support arm is pivoted at said connection point to move said yarn tensioner from the operative position to the package-replacement position such that a fresh yarn supply package can be freely inserted through the package transfer space and into the canister; and (ii) after inserting the fresh yarn supply package into the canister, said support arm is pivoted at said connection point to move the yarn tensioner back into the operative position.
