

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415717
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	D'Alfonso; Augusto et al.

Wrap, system, and method for the repair of gas station fuel pump islands and the like

Abstract

A method for repairing a damaged band of a fuel pump island, comprising: selecting among preformed band pieces to form a replacement band system for the fuel pump island, wherein the preformed band pieces include one or more of a straight band piece for covering a straight portion of a vertical wall of the fuel pump island, an outside corner band piece for covering an outside corner portion of the vertical wall of the fuel pump island, and an inside corner band piece for covering an inside corner portion of the vertical wall of the fuel pump island; preparing the fuel pump island by removing debris from the vertical wall and a top surface of the fuel pump island; installing the replacement band system over the damaged band of the fuel pump island by attaching respective wall portions of the preformed band pieces to the vertical wall of the fuel pump island; and, finishing a top surface of the fuel pump island to at least a height that is level with top surfaces of respective flange portions of the preformed band pieces.

Inventors:	D'Alfonso; Augusto (Harrow, CA), D'Alfonso; Marco (Lasalle, CA)
Applicant:	COUNTRYSIDE CONCRETE SERVICES LTD. (Lasalle, CA)
Family ID:	1000008820657
Assignee:	COUNTRYSIDE CONCRETE SERVICES LTD. (Lasalle, CA)
Appl. No.:	17/964960
Filed:	October 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230123411 A1	Apr. 20, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **E01F1/00** (20060101); **B60S5/02** (20060101); **B67D7/06** (20100101); **E01C11/22** (20060101)

U.S. Cl.:

CPC **B67D7/06** (20130101); **B60S5/02** (20130101); **E01C11/222** (20130101);

Field of Classification Search

CPC: E01C (11/222); B67D (7/06); B60S (5/02); E01F (1/00)

USPC: 404/7; 404/8

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2294855	12/1941	Thomason	404/8	E01F 1/00
2298378	12/1941	Hodges	362/152	E01F 1/00
2767626	12/1955	Rooke	52/612	E01F 1/00
3242834	12/1965	Sondheim	404/8	E01C 19/502
3379105	12/1967	Lynch	404/8	E01C 11/222
5700106	12/1996	Young	404/8	E01F 1/00
6010276	12/1999	Young	404/8	E01F 1/00
6099202	12/1999	Walton	404/8	E01F 1/00
6409422	12/2001	Mittermaier	249/188	E01C 11/222
7950872	12/2010	Radu, Jr.	249/4	E01F 1/00
8985892	12/2014	Hunter	404/8	E01F 1/00
8985894	12/2014	Hunter	404/8	E01F 1/00
2009/0113828	12/2008	Radu, Jr.	52/745.19	E01F 1/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1344718	12/1973	GB	E01C 11/222

Primary Examiner: Addie; Raymond W

Attorney, Agent or Firm: CONNEELY PC

Background/Summary

(1) This application claims priority from and the benefit of the filing date of U.S. Provisional Patent Application No. 63/256,255, filed Oct. 15, 2021, and the entire content of such application is incorporated herein by reference.

FIELD OF THE APPLICATION

(1) This application relates to the field of concrete structure repair, and more specifically, to a wrap, system, and method for repairing gas station fuel pump islands, and the like.

BACKGROUND

(2) A fuel pump island is generally that portion of an automobile or motor vehicle service station, gas station, public garage, or similar establishment for the sale of automotive fuels, that includes the fuel pumps, concrete base, overhead canopy and kiosk, but does not generally include any part of any building for the repair or service of automobiles or motor vehicles. Fire codes generally require that fuel dispensers be mounted on concrete islands or otherwise protected against collision from vehicles. As such, a fuel pump island generally includes an elevated concrete platform, usually from 4 to 8 inches high, on which fuel dispensing pumps are located. The side walls of the elevated concrete platform may be wrapped or fitted with a metal band or form to improve longevity of the platform.

(3) Over time the concrete and metal bands forming a fuel pump island may break down from weathering, rust, vehicular impacts, fuel spills, etc. When this happens, the fuel pump island will require replacement, refurbishment, or repair. This repair will typically require breaking out existing concrete, removing fuel pumps, cutting out the old metal band, inserting a new metal band, pouring new concrete, and reinstalling the fuel pumps. This is problematic for service station operators as the cost for making such repairs using exiting methods can be quite high especially if the entire fuel pump island requires replacement. Another problem, with high associated costs, is the two or three day downtime of the fuel pump that such repairs may require.

(4) A need therefore exists for an improved method and system for repairing fuel pump islands and the like. Accordingly, a solution that addresses, at least in part, the above and other shortcomings is desired.

SUMMARY OF THE APPLICATION

(5) According to one aspect of the application, there is provided a method for repairing a damaged band of a fuel pump island, comprising: selecting among preformed band pieces to form a replacement band system for the fuel pump island, wherein the preformed band pieces include one or more of a straight band piece for covering a straight portion of a vertical wall of the fuel pump island, an outside corner band piece for covering an outside corner portion of the vertical wall of the fuel pump island, and an inside corner band piece for covering an inside corner portion of the vertical wall of the fuel pump island; preparing the fuel pump island by removing debris from the vertical wall and a top surface of the fuel pump island; installing the replacement band system over the damaged band of the fuel pump island by attaching respective wall portions of the preformed band pieces to the vertical wall of the fuel pump island; and, finishing a top surface of the fuel pump island to at least a height that is level with top surfaces of respective flange portions of the preformed band pieces.

(6) According to another aspect of the application, there is provided a replacement band system for repairing a damaged band of a fuel pump island, comprising: one or more preformed band pieces, wherein the preformed band pieces include one or more of a straight band piece for covering a straight portion of a vertical wall of the fuel pump island, an outside corner band piece for covering an outside corner portion of the vertical wall of the fuel pump island, and an inside corner band piece for covering an inside corner portion of the vertical wall of the fuel pump island; wherein the replacement band system is installed over the damaged band of the fuel pump island by attaching respective wall portions of the preformed band pieces to the vertical wall of the fuel pump island.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features and advantages of the embodiments of the present application will become apparent from the following detailed description, taken in combination with the appended drawings, in which:
- (2) FIG. 1 is a front perspective view illustrating an example fuel pump island before repair in accordance with the prior art;
- (3) FIG. 2 is a front perspective view illustrating the example fuel pump island of FIG. 1 during repair in accordance with an embodiment of the application;
- (4) FIG. 3 is a front perspective view illustrating the example fuel pump island of FIG. 1 after repair in accordance with an embodiment of the application;
- (5) FIG. 4 is a front perspective view illustrating a straight band piece in accordance with an embodiment of the application;
- (6) FIG. 5 is a front view thereof;
- (7) FIG. 6 is right side view thereof, the left side view being substantially a mirror image thereof;
- (8) FIG. 7 is a front view thereof shown in an unfolded (or pre-folded) condition;
- (9) FIG. 8 is a front perspective view illustrating a non-punched straight band piece in accordance with an embodiment of the application;
- (10) FIG. 9 is a front view thereof;
- (11) FIG. 10 is right side view thereof, the left side view being substantially a mirror image thereof;
- (12) FIG. 11 is a front view thereof shown in an unfolded (or pre-folded) condition;
- (13) FIG. 12 is a left side view illustrating a curved outside corner band piece in accordance with an embodiment of the application;
- (14) FIG. 13 is a top view thereof;
- (15) FIG. 14 is a front perspective view illustrating a 90 degree inside corner band piece in accordance with an embodiment of the application;
- (16) FIG. 15 is a left side view thereof;
- (17) FIG. 16 is a right side view thereof;
- (18) FIG. 17 is a top view thereof;
- (19) FIG. 18 is a front perspective view thereof with a corner infill piece thereof removed in accordance with an embodiment of the application;
- (20) FIG. 19 is a left side view thereof;
- (21) FIG. 20 is a top view thereof;
- (22) FIG. 21 is a front view thereof shown in an unfolded (or pre-folded) condition;
- (23) FIG. 22 is a top view illustrating a corner infill piece of the 90 degree inside corner piece of FIG. 14 in isolation in accordance with an embodiment of the application;
- (24) FIG. 23 is a right side end view thereof, the lower side end view being substantially a mirror image thereof; and,
- (25) FIG. 24 is a front perspective view illustrating the example fuel pump island of FIG. 1 after repair in accordance with another embodiment of the application.
- (26) It will be noted that throughout the appended drawings, like features are identified by like reference numerals.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (27) In the following description, details are set forth to provide an understanding of the application. In some instances, certain structures, techniques and methods have not been described or shown in detail in order not to obscure the application.
- (28) FIG. 1 is a front perspective view illustrating an example fuel pump island **100** before repair in accordance with the prior art. The fuel pump island **100** includes a concrete platform **110** having a top surface **120** which is elevated at a height **130** above grade **140**. A vertical (or approximately vertical) wall **150** of the platform **110** is wrapped or formed with a metal band **160** (i.e., an existing

or damaged band). The top surface **120** has an edge portion **125** proximate the metal band **160**.

(29) FIG. 2 is a front perspective view illustrating the example fuel pump island **100** of FIG. 1 during repair in accordance with an embodiment of the application. The repair of the fuel pump island **100** is accomplished by the installation of a replacement band (or wrap or band system) **200** over the existing band **160** of the fuel pump island **100** as will be described further below. Prior to the installation of the replacement band system **200**, any debris and rust is removed from the fuel pump island **100** and the existing band **160**, the existing band **160** is straightened if required, and any damaged concrete is repaired.

(30) FIG. 3 is a front perspective view illustrating the example fuel pump island **100** of FIG. 1 after repair in accordance with an embodiment of the application. The repair of the fuel pump island **100** is completed by finishing the top surface **120** of the fuel pump island **100** with materials such as concrete, paint, clear coat epoxy, sealant, caulking, etc., to fill any gaps between the top surface **120** of the fuel pump island **100** and the replacement band system **200**. Similarly, any gaps between the replacement band system **200** and the vertical wall **150** of the fuel pump island **100** may also be filled. Also similarly, any gaps between the bottom edge **205** of the replacement band system **200** and grade **140** may also be filled.

(31) The replacement band system **200** includes a number of preformed band pieces **220** that are selected to provide a precise fit over the existing band **160** of the fuel pump island **100**. According to one embodiment, the preformed band pieces **220** may be made from a corrosion resistant metal such as stainless steel. According to one embodiment, the preformed band pieces **220** may be attached to the fuel pump island **100** using fasteners **700** such as stainless steel screw anchors (e.g., Tapcon™ 3/16 inch screw anchors), concrete screws, concrete nails, nuts and bolts, or the like.

(32) The preformed band pieces **220** may include one or more of the following: a straight band piece **300**; a non-punched straight band piece **400**; a curved outside corner band piece **500**; and, an inside 90 degree corner band piece **600**. Of course the preformed band pieces **220** may include other pieces such as, for example, 30, 45, and 60 degree inside corner band pieces and 120, 135, and 150 degree outside corner band pieces, to suit fuel pump islands **100** having different shapes or geometries.

(33) FIG. 4 is a front perspective view illustrating a straight band piece **300** in accordance with an embodiment of the application. FIG. 5 is a front view thereof. FIG. 6 is right side view thereof, the left side view being substantially a mirror image thereof. And, FIG. 7 is a front view thereof shown in an unfolded (or pre-folded) condition **307**.

(34) The straight (or approximately straight) band piece **300** is used for wrapping straight (or approximately straight) portions (e.g., **151**) of the vertical wall **150** of the platform **110** of the fuel pump island **100**.

(35) According to one embodiment, the straight band piece **300** is elongate having a first (or right) end **301**, a second (or left) end **302**, an outer surface **303** for facing away from the vertical wall **150** of the fuel pump island **100**, an inner surface **304** for facing toward the vertical wall **150** of the fuel pump island **100**, a wall portion **310**, a bullnose portion **320** attached to the wall portion **310**, and a flange portion **330** attached to the bullnose portion **320**. The wall portion **310** has one or more holes **311** formed therein for receiving fasteners **700** for attaching the wall portion **310** to the vertical wall **150** of the fuel pump island **100**. The one or more holes **311** may be positioned proximate the ends **301**, **302** of the straight band piece **300**. According to one embodiment, two holes **311** may be arranged vertically (or approximately vertically) at each end **301**, **302** of the straight band piece **300**. The flange portion **330** extends horizontally (or approximately horizontally) from the bullnose portion **320** and is for extending over the top edge **165** of the existing band **160** and the adjacent top edge portion **125** of the top surface **120** of the fuel pump island **100** when installed.

(36) According to one embodiment, the straight band piece **300** may be initially formed from a flat piece of metal in an unfolded (or pre-folded) condition **307** as shown in FIG. 7. The straight band piece **300** may then be folded (or bent, formed, molded, etc.) into its final folded form **309** as

shown in FIG. 4.

(37) FIG. 8 is a front perspective view illustrating a non-punched straight band piece **400** in accordance with an embodiment of the application. FIG. 9 is a front view thereof. FIG. 10 is right side view thereof, the left side view being substantially a mirror image thereof. And, FIG. 11 is a front view thereof shown in an unfolded (or pre-folded) condition **407**.

(38) Similar to the straight band piece **300**, the non-punched straight (or approximately straight) band piece **400** is used for wrapping straight (or approximately straight) portions (e.g., **151**) of the vertical wall **150** of the platform **110** of the fuel pump island **100**.

(39) According to one embodiment, the non-punched straight band piece **400** is elongate having a first (or right) end **401**, a second (or left) end **402**, an outer surface **403** for facing away from the vertical wall **150** of the fuel pump island **100**, an inner surface **404** for facing toward the vertical wall **150** of the fuel pump island **100**, a wall portion **410**, a bullnose portion **420**, and a flange portion **430**. The wall portion **410** does not initially have holes (e.g., **311**) formed therein. Rather, one or more holes **311** may be formed therein for receiving fasteners **700** for attaching the wall portion **310** to the vertical wall **150** of the fuel pump island **100** during installation. The flange portion **430** extends horizontally (or approximately horizontally) from the bullnose portion **420** and is for extending over the top edge **165** of the existing band **160** and the adjacent top edge portion **125** of the top surface **120** of the fuel pump island **100** when installed.

(40) According to one embodiment, the non-punched straight band piece **400** may be initially formed from a flat piece of metal in an unfolded (or pre-folded) condition **407** as shown in FIG. 8. The non-punched straight band piece **400** may then be folded (or bent, formed, molded, etc.) into its final folded form **409** as shown in FIG. 4.

(41) FIG. 12 is a left side view illustrating a curved outside corner band piece **500** in accordance with an embodiment of the application. And, FIG. 13 is a top view thereof.

(42) The curved outside corner band piece **500** is used for wrapping curved outside corner portions (e.g., **155**) of the vertical wall **150** of the platform **110** of the fuel pump island **100**.

(43) According to one embodiment, the curved outside corner band piece **500** has a first (or right) end **501**, a second (or left) end **502**, an outer surface **503** for facing away from the vertical wall **150** of the fuel pump island **100**, an inner surface **504** for facing toward the vertical wall **150** of the fuel pump island **100**, a wall portion **510**, a bullnose portion **520**, and a flange portion **530**. The wall portion **510** has one or more holes **511** formed therein for receiving fasteners **700** for attaching the wall portion **510** to the vertical wall **150** of the fuel pump island **100**. The one or more holes **511** may be positioned proximate the ends **501**, **502** of the curved outside corner band piece **500**.

According to one embodiment, two holes **511** may be arranged vertically at each end **501**, **502** of the curved outside corner band piece **500**. The flange portion **530** extends horizontally (or approximately horizontally) from the bullnose portion **520** and is for extending over the top edge **165** of the existing band **160** and the adjacent top edge portion **125** of the top surface **120** of the fuel pump island **100** when installed.

(44) FIG. 14 is a front perspective view illustrating a 90 degree inside corner band piece **600** in accordance with an embodiment of the application. FIG. 15 is a left side view thereof. FIG. 16 is a right side view thereof. FIG. 17 is a top view thereof. FIG. 18 is a front perspective view thereof with a corner infill piece **640** thereof removed in accordance with an embodiment of the application. FIG. 19 is a left side view thereof. FIG. 20 is a top view thereof. FIG. 21 is a front view thereof shown in an unfolded (or pre-folded) condition **607**. FIG. 22 is a top view illustrating a corner infill piece **640** of the 90 degree inside corner piece **600** of FIG. 14 in isolation in accordance with an embodiment of the application. And, FIG. 23 is a right side end view thereof, the lower side end view being substantially a mirror image thereof.

(45) The 90 degree (or approximately 90 degree) inside corner band piece **600** is used for wrapping 90 degree (or approximately 90 degree) inside corner portions (e.g., **158**) of the vertical wall **150** of the platform **110** of the fuel pump island **100**.

(46) According to one embodiment, the 90 degree inside corner piece **600** has a first (or right) end **601**, a second (or left) end **602**, an outer surface **603** for facing away from the vertical wall **150** of the fuel pump island **100**, an inner surface **604** for facing toward the vertical wall **150** of the fuel pump island **100**, a wall portion **610**, a bullnose portion **620**, and a flange portion **630**. The wall portion **610** has one or more holes **611** formed therein for receiving fasteners **700** for attaching the wall portion **610** to the vertical wall **150** of the fuel pump island **100**. The one or more holes **611** may be positioned proximate the ends **601**, **602** of the 90 degree inside corner band piece **600**. According to one embodiment, two holes **611** may be arranged vertically at each end **601**, **602** of the 90 degree inside corner band piece **600**. The flange portion **630** extends horizontally (or approximately horizontally) from the bullnose portion **620** and is for extending over the top edge **165** of the existing band **160** and the adjacent top edge portion **125** of the top surface **120** of the fuel pump island **100** when installed.

(47) According to one embodiment, the 90 degree inside corner band piece **600** may be initially formed from a flat piece of metal in an unfolded (or pre-folded) condition **607** as shown in FIG. **21**. The 90 degree inside corner band piece **600** may then be folded (or bent, formed, molded, etc.) into its final folded form **609** as shown in FIG. **18** and may be completed by the attachment (e.g., welding, etc.) of a corner fill piece **640** as shown in FIG. **14**. According to one embodiment, the corner fill piece **640** may be seamlessly formed with the 90 degree inside corner piece **600** (e.g., the 90 degree inside corner piece **600** may consist of one piece only).

(48) As shown in FIGS. **2** and **3**, according to one embodiment, the ends **301**, **302**, **601**, **602** of the curved outside corner band pieces **300** and the 90 degree inside corner band pieces **600** are installed so as to overlap the ends **401**, **402**, **501**, **502** of intervening straight and non-punched straight band pieces **400**, **500**. In other words, the straight and non-punched straight band pieces **400**, **500** are installed first. At least the straight and non-punched straight band pieces **400**, **500** may be cut to required length on site.

(49) According to one embodiment, the straight band piece **300** may have a length of 24 inches (or approximately 24 inches) and a height of 5.2 inches (or approximately 5.2 inches), the non-punched straight band piece **400** may have a length of 96 inches (or approximately 96 inches) and a height of 5.2 inches (or approximately 5.2 inches), the curved outside corner band piece **500** may have a length (i.e., side length) of 13.5 inches (or approximately 13.5 inches) and a height of 5.2 inches (or approximately 5.2 inches), and the 90 degree inside corner band piece **600** may have a length (i.e., side length) of 6.8 inches (or approximately 6.8 inches) and a height of 5.2 inches (or approximately 5.2 inches).

(50) FIG. **24** is a front perspective view illustrating the example fuel pump island **100** of FIG. **1** after repair in accordance with another embodiment of the application. According to one embodiment, a gasket **800** is installed over (or partially over or proximate to or on) the bottom edge **205** of the replacement band system **200** (i.e., over respective bottom edges **205** of the preformed band pieces **220**) to fill any gaps between the bottom edge **205** and grade **140** and to provide a more finished look for the repair. The gasket **800** may be made of rubber or similar material, may be U-shaped in cross section, and may be $\frac{1}{8}$ inches (or approximately $\frac{1}{8}$ inches) thick by $\frac{7}{16}$ inches (or approximately $\frac{7}{16}$ inches) high. The gasket **800** may extend from the outer surface (e.g., **303**) of the preformed band piece **220** (proximate the bottom edge **205**) over the bottom edge **205** to the inner surface (e.g., **304**) of the preformed band piece **220** (proximate the bottom edge **205**). Respective gaskets **800** (or a single lengthy gasket **800**) may slip onto or over (or partially over or proximate to) the bottom edges **205** of the preformed band pieces **220** as they are fastened to the fuel pump island **100**. Alternatively, one or more of the preformed band pieces **220** may have respective gaskets **800** preinstalled on (or over or partially over or proximate to) their bottom edges **205** prior to installation on the fuel pump island **100**.

(51) In operation, a damaged band **160** of a fuel pump island **100** may be repaired by the following method (or process) steps. First, a replacement band system (or band or wrap) **200** for the fuel

pump island **100** may be formed by selecting from among preformed band pieces **220**. The preformed band pieces **220** may include one or more of a straight (or approximately straight) band piece **300**, **400** for covering a straight (or approximately straight) portion (e.g., **151**) of a vertical (or approximately vertical) wall **150** of the fuel pump island **100**, an outside corner band piece **500** for covering an outside corner portion (e.g., **155**) of the vertical wall **150** of the fuel pump island **100**, and an inside corner band piece **600** for covering an inside corner portion (e.g., **158**) of the vertical wall **150** of the fuel pump island **100**. Second, the fuel pump island **100** is prepared by removing debris from the vertical wall **150** and a top surface **120** of the fuel pump island **100**. Third, the replacement band system **200** is installed over the damaged band **160** of the fuel pump island **100** by attaching respective wall portions **310**, **410**, **510**, **610** of the preformed band pieces **220** to the vertical wall **150** of the fuel pump island **100**. Fourth, the top surface **120** of the fuel pump island is finished to at least a height that is level with top (or outer) surfaces **304**, **404**, **504**, **604** of respective flange portions **330**, **430**, **530**, **630** of the preformed band pieces **220**.

(52) In the above method, the outside corner band piece **500** may be a curved outside corner band piece. The inside corner band piece **600** may be a 90 degree (or approximately 90 degree) inside corner band piece. The preformed band pieces **220** may be made from a corrosion resistant metal. The corrosion resistant metal may be stainless steel. The preformed band pieces **220** may each include a wall portion **310**, **410**, **510**, **610**, a bullnose portion **320**, **420**, **520**, **620**, and a flange portion **330**, **430**, **530**, **630**. The preformed band pieces **220** may be attached to the vertical wall of the fuel pump island using one or more fasteners **700**. The one or more fasteners **700** may be one or more stainless steel screw anchors. The one or more of the preformed band pieces **220** may have one or more holes **311**, **511**, **611** formed therein for receiving the one or more fasteners **700**. The one or more holes **311**, **511**, **611** may be positioned at first **301**, **501**, **601** and second ends **302**, **502**, **602** of the one or more of the preformed band pieces **220**. And, the method may further include installing or preinstalling a respective gasket **800** on or over (or partially over or proximate to) a respective bottom edge **205** of one or more of the preformed band pieces **220**.

(53) The above embodiments may contribute to an improved method and system repairing a damaged band **160** of a fuel pump island **100** and may provide one or more advantages. First, the replacement band system **200** provides the fuel pump island **100** with a clean fresh look. Second, existing fuel pumps need not be removed from the fuel pump island **100** prior to installation of the replacement band system **200**. Third, use of the replacement band system **200** reduces the cost and downtime required for fuel pump island **100** repair.

(54) The embodiments of the application described above are intended to be exemplary only. Those skilled in this art will understand that various modifications of detail may be made to these embodiments, all of which come within the scope of the application.

Claims

1. A method for repairing a damaged band of a fuel pump island, comprising: selecting among preformed band pieces to form a replacement band system for the fuel pump island, wherein the preformed band pieces include one or more of a straight band piece for covering a straight portion of a vertical wall of the fuel pump island, an outside corner band piece for covering an outside corner portion of the vertical wall of the fuel pump island, and an inside corner band piece for covering an inside corner portion of the vertical wall of the fuel pump island; preparing the fuel pump island by removing debris from the vertical wall and a top surface of the fuel pump island; installing the replacement band system over the damaged band of the fuel pump island by attaching respective wall portions of the preformed band pieces to the vertical wall of the fuel pump island; and, finishing a top surface of the fuel pump island to at least a height that is level with top surfaces of respective flange portions of the preformed band pieces.

2. The method of claim 1, wherein the outside corner band piece is a curved outside corner band

piece.

3. The method of claim 1, wherein the inside corner band piece is a 90 degree inside corner band piece.

4. The method of claim 1, further comprising installing or preinstalling a respective gasket on or over a respective bottom edge of one or more of the preformed band pieces.

5. The method of claim 1, wherein the preformed band pieces each include a wall portion, a bullnose portion, and a flange portion.

6. The method of claim 1, wherein the preformed band pieces are made from a corrosion resistant metal.

7. The method of claim 6, wherein the corrosion resistant metal is stainless steel.

8. The method of claim 1, wherein the preformed band pieces are attached to the vertical wall of the fuel pump island using one or more fasteners.

9. The method of claim 8, wherein the one or more fasteners are one or more stainless steel screw anchors.

10. The method of claim 8, wherein one or more of the preformed band pieces have one or more holes formed therein for receiving the one or more fasteners; and, wherein the one or more holes are positioned at first and second ends of the one or more of the preformed band pieces.

11. A replacement band system for repairing a damaged band of a fuel pump island, comprising: one or more preformed band pieces, wherein the preformed band pieces include one or more of a straight band piece for covering a straight portion of a vertical wall of the fuel pump island, an outside corner band piece for covering an outside corner portion of the vertical wall of the fuel pump island, and an inside corner band piece for covering an inside corner portion of the vertical wall of the fuel pump island; wherein the replacement band system is installed over the damaged band of the fuel pump island by attaching respective wall portions of the preformed band pieces to the vertical wall of the fuel pump island.

12. The replacement band system of claim 11, wherein the outside corner band piece is a curved outside corner band piece.

13. The replacement band system of claim 11, wherein the inside corner band piece is a 90 degree or approximately 90 degree inside corner band piece.

14. The replacement band system of claim 11, wherein the preformed band pieces each include a wall portion, a bullnose portion, and a flange portion.

15. The replacement band system of claim 11, wherein a respective gasket is installed or preinstalled on or over a respective bottom edge of one or more of the preformed band pieces.

16. The replacement band system of claim 11, wherein the preformed band pieces are made from a corrosion resistant metal.

17. The replacement band system of claim 16, wherein the corrosion resistant metal is stainless steel.

18. The replacement band system of claim 11, wherein the preformed band pieces are attached to the vertical wall of the fuel pump island using one or more fasteners.

19. The replacement band system of claim 18, wherein the one or more fasteners are one or more stainless steel screw anchors.

20. The replacement band system of claim 18, wherein one or more of the preformed band pieces have one or more holes formed therein for receiving the one or more fasteners; and, wherein the one or more holes are positioned at first and second ends of the one or more of the preformed band pieces.
