

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416541
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Takeuchi; Takayuki et al.

Electric connection box

Abstract

Provided is an electric connection box with which proactive measures can be taken by liquid inflow monitoring. The electric connection box includes a housing where an electronic component is mounted. The housing is provided with a detection part detecting liquid inflow.

Inventors: Takeuchi; Takayuki (Yokkaichi, JP), Yanagita; Yoshiki (Nagakute, JP), Tomihira; Shogo (Nisshin, JP)

Applicant: Sumitomo Wiring Systems, Ltd. (Yokkaichi, JP); TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Family ID: 1000008820696

Assignee: SUMITOMO WIRING SYSTEMS, LTD. (Mie, JP); TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Appl. No.: 18/054617

Filed: November 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230147180 A1	May. 11, 2023

Foreign Application Priority Data

JP	2021-184097	Nov. 11, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G01F23/24 (20060101); B60R16/023 (20060101); G01M3/18 (20060101)

U.S. Cl.:

CPC **G01M3/186** (20130101); **B60R16/0238** (20130101);

Field of Classification Search

CPC: G01F (23/0007); G01F (23/24-244); G01F (23/26-268)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4541446	12/1984	Hogan	73/304R	G01F 23/241
2011/0090625	12/2010	Oota	N/A	N/A
2013/0069675	12/2012	Woloszyk	324/693	G01M 3/16
2013/0214802	12/2012	Adachi	324/693	G01M 3/16
2018/0065576	12/2017	Kawaguchi	N/A	N/A
2018/0301722	12/2017	Kozuka	N/A	H01M 8/04835
2021/0226432	12/2020	Ohira et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H11135955	12/1998	JP	N/A
2011103444	12/2010	JP	N/A
2013170943	12/2012	JP	N/A
2021114852	12/2020	JP	N/A

OTHER PUBLICATIONS

English translation of JP 2013-170943 (Year: 2013). cited by examiner

Primary Examiner: Mercado; Alexander A

Attorney, Agent or Firm: Honigman LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This Non-provisional application claims priority of Japanese Patent Application No. 2021-184097 filed on Nov. 11, 2021, the entire contents of which are incorporated herein.

TECHNICAL FIELD

(2) The present disclosure relates to an electric connection box.

BACKGROUND

(3) In the related art, a vehicle is equipped with an electric connection box where an electronic component such as a relay is mounted. The vehicle equipped with the electric connection box may be involved in a flood or an accident, and a liquid such as water and seawater may flow into the electric connection box of such a vehicle. Such liquid inflow may result in a short circuit and a malfunction.

(4) Japanese Patent Application Laid-Open Publication No. 2018-042356 discloses an electric connection box in which a partition wall for partitioning between high- and low-voltage circuit

regions is configured to be higher than the peripheral wall of a housing having the high- and low-voltage circuit regions.

(5) According to Japanese Patent Laid-Open Publication No. 2018-042356, it is possible to avoid a short circuit occurring in both circuit regions via water even in a case where a liquid flows in and remains in the housing.

(6) Once the liquid flows into the electric connection box, it takes a considerable amount of time to completely drain the liquid. Besides, meanwhile, the risks of short circuit, malfunction, and the like still remain. Accordingly, it is desirable to monitor liquid inflow into the electric connection box and take countermeasures in advance.

(7) However, the electric connection box of Japanese Patent Laid-Open Publication No. 2018-042356 focuses only on post-liquid inflow risks, without devising anything as to liquid inflow monitoring and proactive measures against liquid inflow, and is incapable of solving the above problems.

SUMMARY

(8) The present disclosure has been made in view of such circumstances, and an object of the present disclosure is to provide an electric connection box with which proactive measures can be taken by liquid inflow monitoring.

(9) An electric connection box according to an embodiment of the present disclosure includes a housing where an electronic component is mounted. The housing is provided with a detection part detecting liquid inflow.

(10) According to the present disclosure, proactive measures can be taken by monitoring liquid flow into the electric connection box.

(11) The above and further objects and features will more fully be apparent from the following detailed description with accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of an electric connection box according to the present embodiment.

(2) FIG. 2 is a partial perspective view of a lower case of the electric connection box of the present embodiment.

(3) FIG. 3 is a partial plan view of the lower case of the electric connection box of the present embodiment.

(4) FIG. 4 is a partial cross-sectional view of the lower case taken along line IV-IV of FIG. 3.

(5) FIG. 5 is a partial cross-sectional view illustrating the internal configuration of a storage recess of a detection part.

(6) FIG. 6 is an explanatory diagram conceptually describing a circuit configuration for notifying a driver of an inflow liquid detection result of the detection part.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(7) First, an aspect of implementation of the present disclosure will be listed and described. In addition, at least a part of the embodiment described below may be combined in any manner.

First Aspect

(8) An electric connection box according to a first aspect of the present disclosure includes a housing where an electronic component is mounted, in which the housing includes a detection part detecting inflow of a liquid.

(9) In the first aspect, the detection part detecting the liquid inflow is provided, and thus the liquid inflow can be monitored and countermeasures can be taken in advance or early against the flow of the liquid into the housing.

Second Aspect

(10) In the electric connection box according to a second aspect of the present disclosure, the detection part has a storage recess having an inlet for the liquid and storing the liquid flowing in from the inlet and a detection needle disposed in the storage recess.

(11) In the second aspect, at the detection part, the liquid flowing into the storage recess through the inlet is stored in the storage recess and detected by the detection needle. Since the liquid flowing in is stored and detected, even a small amount of liquid can be detected.

Third Aspect

(12) In the electric connection box according to a third aspect of the present disclosure, the storage recess has a curved bottom surface guiding the liquid to an inner side wall facing the inlet, and the detection needle is disposed near the inner side wall.

(13) In the third aspect, the liquid flowing into the storage recess through the inlet is guided by the curved bottom surface to the inner side wall where the detection needle is disposed and stored.

Accordingly, even a small amount of liquid can be detected.

Fourth Aspect

(14) In the electric connection box according to a fourth aspect of the present disclosure, a liquid drain hole for the liquid is provided in the inner side wall.

(15) In the fourth aspect, the liquid that is greater than the amount necessary for the detection by the detection needle is discharged out of the housing by the liquid drain hole. Accordingly, it is possible to forestall the liquid being excessively stored in the storage recess and flowing into the housing over the storage recess.

Fifth Aspect

(16) In the electric connection box according to a fifth aspect of the present disclosure, a width on the inner side wall is smaller than a width on the inlet in the storage recess.

(17) In the fifth aspect, since the width on the inner side wall side is smaller than the width on the inlet side in the storage recess, the liquid surface rise in the vicinity of the inner side wall where the detection needle is disposed accelerates. Accordingly, the detection needle is capable of early liquid inflow detection.

Sixth Aspect

(18) In the electric connection box according to a sixth aspect of the present disclosure, the liquid drain hole is provided at a position separated from the curved bottom surface by a distance two to four times as long as a gap between the detection needle and the curved bottom surface.

(19) In the sixth aspect, since the liquid drain hole is provided at the position separated from the curved bottom surface by a distance two to four times as long as the gap between the detection needle and the curved bottom surface, it is possible to discharge out of the housing the liquid greater than the amount necessary for the detection while reliably executing the detection by the detection needle.

Seventh Aspect

(20) The electric connection box according to a seventh aspect of the present disclosure further includes a bus bar connected to the electronic component, in which the detection needle is formed integrally with the bus bar.

(21) In the seventh aspect, since the detection needle is formed integrally with the bus bar, a detection result of the detection needle can be acquired via the bus bar and a circuit configuration for the detection result of the detection needle is facilitated.

(22) An electric connection box according to an embodiment of the present disclosure will be described below with reference to the drawings. It should be noted that the present disclosure is not limited to the exemplifications. The present disclosure is defined by the scope of the claims and is intended to include every modification within the meaning and scope equivalent to the scope of the claims.

(23) Hereinafter, the present embodiment will be described by taking as an example an electronic component-mounted vehicular electric connection box.

(24) FIG. 1 is a perspective view of an electric connection box **100** according to the present embodiment.

(25) The electric connection box **100** is attached to the outside of, for example, an electric vehicle (EV) battery pack. The electric connection box **100** includes a housing **50** where an electronic component such as a fuse and a relay **400** is mounted.

(26) The housing **50** is made of, for example, resin or metal and includes a lower case **52** and an upper case **51** covering the lower case **52**. The housing **50** is, for example, attached to the battery pack such that a bottom plate **521** of the lower case **52** faces the battery pack. The bottom plate **521** has an uneven shape in the thickness direction.

(27) The lower case **52** has the shape of a flat housing with one surface open. A plurality of ribs are formed and a plurality of pedestals are formed inside the lower case **52**. A bus bar, an electronic component (not illustrated), and so on are attached to the pedestal.

(28) In addition, the lower case **52** is provided with a detection part **10** detecting the flow of a liquid such as rainwater and seawater into the battery pack or the electric connection box **100**.

(29) FIG. 2 is a partial perspective view of the lower case **52** of the electric connection box **100** of the present embodiment, and FIG. 3 is a partial plan view of the lower case **52** of the electric connection box **100** of the present embodiment. FIGS. 2 and 3 illustrate the detection part **10** and the surroundings of the detection part **10** in the lower case **52** with the upper case **51** removed.

(30) The detection part **10** has a storage recess **11** storing a liquid flowing into the electric connection box **100** from the outside (hereinafter, referred to as inflow liquid) and a pair of detection needles **121** and **131** disposed in the storage recess **11**.

(31) The storage recess **11** is provided in the vicinity of one side wall of the lower case **52**. The storage recess **11** communicates with the outside of the lower case **52** through an inlet **15** provided in the one side wall. In other words, the storage recess **11** has the inlet **15** communicating with the outside of the lower case **52**. Accordingly, before the inflow liquid starts to flow into the electric connection box **100**, the inflow liquid first flows into the storage recess **11** through the inlet **15**.

(32) The storage recess **11** is substantially trumpet-shaped in a plan view and has three side walls erected inside the bottom plate **521** of the lower case **52**. The storage recess **11** has an inner side wall **112** provided on the back side far from the inlet **15** and facing the inlet **15** and a first side wall **113** and a second side wall **114** continuously provided on both sides of the inner side wall **112** and disposed so as to substantially face each other. Each of the inside ends of the first side wall **113** and the second side wall **114** is provided so as to be continuous with the inner side wall **112** as described above. The outside ends of the first side wall **113** and the second side wall **114** configure the edge of the inlet **15**.

(33) The second side wall **114** extends straight from the inner side wall **112** toward the one side wall of the lower case **52**. On the other hand, the end portion of the first side wall **113** that is close to the one side wall of the lower case **52** is curved to the outside, that is, in the direction away from the second side wall **114**. Accordingly, the gap between the first side wall **113** and the second side wall **114** widens toward the inlet **15**. In other words, in the storage recess **11**, the width on the inner side wall **112** is smaller than the width on the inlet **15**. In other words, the dimension of the storage recess **11** in the direction intersecting the facing direction of the inlet **15** and the inner side wall **112** is shorter on the inner side wall **112** than at the inlet **15**.

(34) A bottom surface **111** (curved bottom surface) of the storage recess **11** is curved and guides the inflow liquid flowing into the storage recess **11** through the inlet **15** to the inner side wall **112**. FIG. 4 is a partial cross-sectional view of the lower case **52** taken along line IV-IV of FIG. 3.

(35) As can be seen from FIG. 4, in a cross-sectional view, the bottom surface **111** has a flat end portion near the inner side wall **112** and an upwardly curved end portion near the inlet **15**.

Accordingly, the flow of the inflow liquid flowing into the storage recess **11** through the inlet **15** can be strengthened and the inflow liquid easily flows to the inner side wall **112**.

(36) In addition, the detection part **10** has a liquid drain hole **14** for discharging, to the outside of

the electric connection box **100**, the inflow liquid that is greater than the amount necessary for the detection needles **121** and **131** to detect the inflow liquid. The liquid drain hole **14** is formed in the inner side wall **112**.

(37) FIG. 5 is a partial cross-sectional view illustrating the internal configuration of the storage recess **11** of the detection part **10**.

(38) The inner side wall **112** includes a lower inner side wall **112a** provided close to the bottom surface **111** and an upper inner side wall **112b** positioned farther from the bottom surface **111** than the lower inner side wall **112a**. The lower inner side wall **112a** is smaller than the upper inner side wall **112b** in up-down-direction dimension, and the lower inner side wall **112a** is provided so as to be continuous with the bottom surface **111**. The upper inner side wall **112b** is provided away from the lower inner side wall **112a** in the direction away from the inlet **15** and above the upper end of the lower inner side wall **112a**.

(39) In this manner, the inner side wall **112** includes the two parts of the lower inner side wall **112a** and the upper inner side wall **112b**, the upper inner side wall **112b** is separated from the lower inner side wall **112a** in the facing direction of the inlet **15** and the inner side wall **112**, and thus a substantially rectangular gap is formed between the lower inner side wall **112a** and the upper inner side wall **112b**. Such a gap corresponds to the liquid drain hole **14**. As described above, the liquid drain hole **14** communicates with the outside of the electric connection box **100**.

(40) In addition, in order to prevent the excessive inflow liquid that is equal to or greater than the amount necessary for the inflow liquid detection from storing in the storage recess **11**, in this configuration, the lower inner side wall **112a** is smaller than the upper inner side wall **112b** in up-down-direction dimension (hereinafter, referred to as up-down dimension) as described above. In FIG. 4, L denotes the up-down dimension of the lower inner side wall **112a**.

(41) In other words, the up-down dimension L of the lower inner side wall **112a** defines the liquid surface level of the inflow liquid storing in the storage recess **11**. In a case where the up-down dimension L of the lower inner side wall **112a** is too short, the liquid surface level of the inflow liquid is too low, and thus the inflow liquid detection by the detection needles **121** and **131** is inaccurate. On the other hand, in a case where the up-down dimension L of the lower inner side wall **112a** is too long, the liquid surface level of the inflow liquid is too high, and thus the inflow liquid in the storage recess **11** may flow into the lower case **52** by splashing over the first side wall **113** or the second side wall **114**.

(42) In view of such a problem, it is desirable that the up-down dimension L of the lower inner side wall **112a** is two to four times a gap G between the lower ends of the detection needles **121** and **131** and the bottom surface **111** (see FIG. 4). In other words, the liquid drain hole **14** is provided above the bottom surface **111** by a distance two to four times as long as the gap G between the detection needles **121** and **131** and the bottom surface **111**.

(43) The detection needles **121** and **131** are disposed in the vicinity of the inner side wall **112** in the storage recess **11**. The detection needles **121** and **131** are disposed with an insulation distance in the facing direction of the inlet **15** and the inner side wall **112**. The detection needles **121** and **131** are substantially strip-shaped, extend in the up-down direction, and are parallel to each other (see FIG. 4). The detection needles **121** and **131** have the same shape, and the lower end portions thereof are reduced in width. The lower ends of the detection needles **121** and **131** are provided apart by the gap G from the bottom surface **111** as described above.

(44) Bus bars **12** and **13** connected to the electronic component mounted on the electric connection box **100** are disposed in the vicinity of the storage recess **11** in the lower case **52**. The detection needles **121** and **131** are formed integrally with the bus bars **12** and **13**, respectively. The detection needle **121** is formed integrally with the bus bar **12**, and the detection needle **131** is formed integrally with the bus bar **13** (see FIGS. 2 and 3). The bus bars **12** and **13** are made of, for example, a conductive metal plate material.

(45) Specifically, although the detection needles **121** and **131** are disposed apart from the bus bars

12 and **13**, respectively, the upper end of the detection needle **121** is connected to the bus bar **12** by a strip-shaped plate member **122** and the upper end of the detection needle **131** is connected to the bus bar **13** by a strip-shaped plate member **132**.

(46) The detection part **10** configured as described above detects the flow of the inflow liquid into the electric connection box **100**. For example, when the inflow liquid flows into the electric connection box **100**, the inflow liquid flows into the storage recess **11** through the inlet **15** in the side wall of the lower case **52** and stores in the storage recess **11**. The detection needles **121** and **131** are immersed in the inflow liquid by the amount of the inflow liquid that is stored in the storage recess **11** increasing and the liquid surface level of the inflow liquid exceeding the gap **G** between the bottom surface **111** and the detection needles **121** and **131**. At this time, the resistance value between the detection needles **121** and **131**, that is, the resistance value between the bus bars **12** and **13** decreases, and thus the flow of the inflow liquid into the electric connection box **100** can be detected by monitoring the resistance value between the bus bars **12** and **13**.

(47) In other words, in the electric connection box **100**, the detection part **10** monitors (detects) the flow of the inflow liquid into the electric connection box **100**, and thus countermeasures against inflow of the inflow liquid can be quickly taken based on the monitoring result of the detection part **10**.

(48) The inflow liquid detection result of the detection part **10** may be output to the outside (e.g. ECU) and the driver of a vehicle equipped with the electric connection box **100** of the present embodiment may be notified of the result.

(49) FIG. **6** is an explanatory diagram conceptually illustrating a circuit configuration for notifying a driver of the inflow liquid detection result of the detection part **10**.

(50) An ECU **200** is connected to the electric connection box **100** (detection part **10**) and an instrument panel **300**. For example, the instrument panel **300** is provided with a warning light indicating the flow of the inflow liquid into the electric connection box **100** or the battery pack. The ECU **200** monitors a change in resistance value between the bus bars **12** and **13** (detection needles **121** and **131**) based on the detection result output from the detection part **10** and causes the warning light on the instrument panel **300** to flicker in accordance with the monitoring result.

(51) Specifically, the ECU **200** monitors the resistance value between the bus bars **12** and **13** and, in a case where such a resistance value decreases to or below a predetermined threshold, causes the warning light on the instrument panel **300** to flicker to notify the driver of the inflow of the inflow liquid.

(52) In the electric connection box **100** of the present embodiment, the detection part **10** communicates with the outside through the inlet **15** formed in the side wall of the lower case **52** as described above, and thus the inflow liquid easily flows into the storage recess **11** of the detection part **10**. Accordingly, the inflow liquid can be detected early immediately before the inflow liquid flows into the electric connection box **100**.

(53) In addition, as described above, in the storage recess **11** of the electric connection box **100**, the width on the inner side wall **112** is smaller than the width on the inlet **15**. Accordingly, in a case where the inflow liquid flows into the storage recess **11**, the liquid surface rise in the vicinity of the inner side wall **112**, that is, in the vicinity of the detection needles **121** and **131** accelerates and the detection needles **121** and **131** are capable of quickly detecting the inflow liquid even at a small inflow liquid amount.

(54) Further, as described above, the bottom surface **111** of the storage recess **11** is curved and the inflow liquid flowing into the storage recess **11** is guided to the inner side wall **112**. Accordingly, the liquid surface rise in the vicinity of the detection needles **121** and **131** further accelerates.

(55) In addition, in the electric connection box **100**, the detection part **10** has the liquid drain hole **14**, and thus the inflow liquid that is greater than the amount necessary for the inflow liquid detection is discharged out of the electric connection box **100** through the liquid drain hole **14**. Accordingly, no excessive inflow liquid storage occurs in the storage recess **11** and it is possible to

prevent the inflow liquid in the storage recess **11** from flowing into the lower case **52** over the first side wall **113** or the second side wall **114** when, for example, the electric connection box **100** vibrates.

(56) In addition, in the electric connection box **100**, the detection needles **121** and **131** are formed integrally with the bus bars **12** and **13**, respectively. Accordingly, a change in resistance value between the detection needles **121** and **131** can be confirmed via a change in resistance value between the bus bars **12** and **13**. Accordingly, the circuit configuration for outputting the inflow liquid detection result of the detection part **10** is easy and simple.

(57) The embodiment disclosed this time is an exemplification in every respect and should be considered not restrictive. The scope of the present disclosure is defined not by the meaning described above but by the scope of the claims and is intended to include every modification within the meaning and scope equivalent to the scope of the claims.

(58) It is to be noted that, as used herein and in the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise.

(59) It is to be noted that the disclosed embodiment is illustrative and not restrictive in all aspects. The scope of the present invention is defined by the appended claims rather than by the description preceding them, and all changes that fall within metes and bounds of the claims, or equivalence of such metes and bounds thereof are therefore intended to be embraced by the claims.

Claims

1. An electric connection box comprising: a housing where an electronic component is mounted, the housing having a first side wall spaced apart from a second side wall, an inner side wall extending between the first side wall and the second side wall and a bottom surface extending between the first side wall and the second side wall and from the inner side wall to a front opening of the housing so as to define a storage recess having an inlet for receiving liquid, wherein the inner side wall includes a lower inner side wall and an upper inner side wall that are parallel to and offset from each other so as to define a drain hole for draining the liquid, and a detection needle disposed in the storage recess to detect an inflow of liquid, wherein the detection needle is disposed closer to the inner side wall relative to the front opening of the storage recess.
 2. The electric connection box according to claim 1, wherein the bottom surface is curved so as to guide the liquid to the inner side wall.
 3. The electric connection box according to claim 2, wherein a width of the storage region at the inner side wall is smaller than a width of the storage region at the inlet.
 4. The electric connection box according to claim 1, wherein the a height of the lower inner side wall is distance two to four times as long as a gap between the detection needle and the bottom surface.
 5. The electric connection box according to claim 1, further comprising a bus bar connected to the electronic component, wherein the detection needle is formed integrally with the bus bar.
-